

# Basics of R Programming

## Contents

1 R as an Advanced Calculator .....	1
2 Data Types .....	7
2.1 Computing Basic Statistics .....	8
2.2 Creating Sequences .....	10
2.3 Comparing Vectors .....	11
2.4 Vector Slicing (Indexing) .....	12
2.5 Vector Masking .....	13
2.6 Vector Operations .....	13
2.7 Broadcasting .....	14
2.8 Matrices .....	15
3 User Defined Functions in R .....	15
4 Conditional Statements & Loops .....	16
5 Counting the Number of Combinations .....	17
6 Generating Random Numbers .....	17
6.1 Generating Reproducible Random Numbers .....	19
6.2 Generating a Random Sample .....	19
7 Data Cleaning Set the working directory. ....	20

## 1 R as an Advanced Calculator

- Arithmetic Operations in R

```
a = 3  
b = 5  
a+b
```

```
[1] 8
```

```
a*b
```

```
[1] 15
```

```
a/b
```

```
[1] 0.6
```

```
a^b
```

```
[1] 243
```

```
4^4
```

```
[1] 256
```

```
4^3 - 3^2
```

```
[1] 55
```

```
log(100, 10) #by default log gives natural log
```

```
[1] 2
```

- Logical Operations

- & and | operators perform element-wise operations and provide the length of the longer operand.
- && and || operators examine only the first element of the operands resulting in a single length logical vector.
- The logical & operator returns true only if both the options are true, or else returns false.

```
5==5 # True
```

```
[1] TRUE
```

```
4 == 5 # False
```

```
[1] FALSE
```

```
a = (5==5)  
a
```

```
[1] TRUE
```

```
F * 60 # False * 60 = 0
```

```
[1] 0
```

```
T * 50 # True * 50 = 50
```

```
[1] 50
```

```
5 > 2
```

```
[1] TRUE
```

```
4 != 5
```

```
[1] TRUE
```

```
5 >= 4
```

```
[1] TRUE
```

```
3 <= 4
```

```
[1] TRUE
```

```
TRUE & TRUE
```

```
[1] TRUE
```

```
T&T
```

```
[1] TRUE
```

```
T&FALSE
```

```
[1] FALSE
```

```
FALSE & FALSE
```

```
[1] FALSE
```

```
TRUE | FALSE
```

```
[1] TRUE
```

- Vectors

```
# vector creation  
#c() seq()  
  
v = c(1,2,3,4)  
v
```

```
[1] 1 2 3 4
```

```
head(v)
```

```
[1] 1 2 3 4
```

```
tail(v)
```

```
[1] 1 2 3 4
```

```
v1 = 5:13  
v1
```

```
[1] 5 6 7 8 9 10 11 12 13
```

```
v = 3.8:11.4  
v
```

```
[1] 3.8 4.8 5.8 6.8 7.8 8.8 9.8 10.8
```

```
seq(5,9, by = 0.4)
```

```
[1] 5.0 5.4 5.8 6.2 6.6 7.0 7.4 7.8 8.2 8.6 9.0
```

```
seq(0,1, length =11)
```

```
[1] 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
```

```
#vector manipulation  
#Two vectors of the same length can be added  
  
v1 = c(3,8,4,5,0,11)  
v2 = c(4,5,2,5,6,5)  
v1+v2
```

```
[1] 7 13 6 10 6 16
```

```
v1-v2
```

```
[1] -1 3 2 0 -6 6
```

```
v1*v2 #element wise multiplication
```

```
[1] 12 40 8 25 0 55
```

```
# vector element recycling  
v1 = c(3,4,5,2,2,4)  
v2 = c(4,11)  
  
v1 + v2 # v1 + c(4,11,4,11,4,11)
```

```
[1] 7 15 9 13 6 15
```

```
#vector element sorting
v = c(3,4,5,2,5,1)
sort(v)
```

```
[1] 1 2 3 4 5 5
```

```
sort(v, decreasing = T)
```

```
[1] 5 5 4 3 2 1
```

```
color = c("Red","Blue","White")
sort(color)
```

```
[1] "Blue" "Red"  "White"
```

```
#indexing
v[3] # counts from 1
```

```
[1] 5
```

```
v[3:6]
```

```
[1] 5 2 5 1
```

```
v[c(1,3,5)]
```

```
[1] 3 5 5
```

```
v[-c(5,7)]
```

```
[1] 3 4 5 2 1
```

```
fib <- c(0, 1, 1, 2, 3, 5, 8, 13, 21, 34)
cat("The first few Fibonacci numbers are:", fib, "...\\n")
```

```
The first few Fibonacci numbers are: 0 1 1 2 3 5 8 13 21 34 ...
```

## 2 Data Types

R's basic data types are Numeric, Character, Integer, Factor, and Logical.

```
# as.integer()
# as.character()
# as.factor() # categorical

y = 5
class(y) # numeric
```

```
[1] "numeric"
```

```
class(c("1", "4")) #character
```

```
[1] "character"
```

```
x = 4
y = 3
z = x>y
class(z) #logical
```

```
[1] "logical"
```

```
v2 = c("My", "Name", "is", "David")
class(v2) #character
```

```
[1] "character"
```

```
summary(v2)
```

```
Length      Class      Mode
4 character character
```

```
nchar(v2) # number of characters 2 4 2 5
```

```
[1] 2 4 2 5
```

```
#Factor Variables in R  
v5 = c("M", "F", "F", "M")  
class(v5) #character
```

```
[1] "character"
```

```
v5 = as.factor(v5)  
class(v5) #
```

```
[1] "factor"
```

```
summary(v5)
```

```
F M  
2 2
```

## 2.1 Computing Basic Statistics

```
x = c(0, 1, 1, 2, 3, 5, 8, 13, 21, 34)  
mean(x)
```

```
[1] 8.8
```

```
median(x)
```

```
[1] 4
```

```
sd(x)
```

```
[1] 11.03328
```

```
var(x)
```

```
[1] 121.7333
```



```
x = c(0, 1, 1, 2, 3, 5, 8, 13, 21, 34)
y = log(x + 1)
cor(x, y)
```

```
[1] 0.9068053
```

```
cov(x, y)
```

```
[1] 11.49988
```

```
# handling missing values...
x <- c(0, 1, 1, 2, 3, NA)
mean(x)
```

```
[1] NA
```

```
sd(x)
```

```
[1] NA
```

```
mean(x, na.rm = TRUE)
```

```
[1] 1.4
```

```
sd(x, na.rm = TRUE)
```

```
[1] 1.140175
```

```
data(cars)
head(cars)
```

```
  speed dist
1     4    2
2     4   10
3     7    4
4     7   22
```

```
5      8    16
6      9    10
```

```
var(cars)
```

```
      speed      dist
speed 27.95918 109.9469
dist  109.94694 664.0608
```

```
cor(cars)
```

```
      speed      dist
speed 1.0000000 0.8068949
dist  0.8068949 1.0000000
```

```
cov(cars)
```

```
      speed      dist
speed 27.95918 109.9469
dist  109.94694 664.0608
```

## 2.2 Creating Sequences

```
1:5
```

```
[1] 1 2 3 4 5
```

```
9:0
```

```
[1] 9 8 7 6 5 4 3 2 1 0
```

```
seq(from = 1, to = 5, by = 2)
```

```
[1] 1 3 5
```

```
rep(1, times = 5)
```

```
[1] 1 1 1 1 1
```

```
seq(from = 0, to = 20, length.out = 5)
```

```
[1] 0 5 10 15 20
```

```
seq(from = 1.0, to = 2.0, length.out = 5)
```

```
[1] 1.00 1.25 1.50 1.75 2.00
```

## 2.3 Comparing Vectors

```
v <- c(3, pi, 4)
w <- c(pi, pi, pi)
v == w
```

```
[1] FALSE TRUE FALSE
```

```
v < w
```

```
[1] TRUE FALSE FALSE
```

```
v > w
```

```
[1] FALSE FALSE TRUE
```

```
v != w
```

```
[1] TRUE FALSE TRUE
```

```
v <- c(3, pi, 4)
v == pi # Compare a 3-element vector against one number
```

```
[1] FALSE TRUE FALSE
```

```
v <- c(3, pi, 4)
any(v == pi) # Return TRUE if any element of v equals pi
```

```
[1] TRUE
```

```
all(v == 0) # Return TRUE if all elements of v are zero
```

```
[1] FALSE
```

## 2.4 Vector Slicing (Indexing)

```
a = c(0, 1, 1, 2, 3, 5, 8, 13, 21, 34)
a[1] # note that indexing starts at 1
```

```
[1] 0
```

```
a[5]
```

```
[1] 3
```

```
a[2:3] # also the last index is included, unlike Python
```

```
[1] 1 1
```

```
a[-1]
```

```
[1] 1 1 2 3 5 8 13 21 34
```

```
a[1:3]
```

```
[1] 0 1 1
```

```
a[-(1:3)] # Invert sign of index to exclude instead of select
```

```
[1] 2 3 5 8 13 21 34
```

## 2.5 Vector Masking

```
a = c(0, 1, 1, 2, 3, 5, 8, 13, 21, 34)
a < 10
```

```
[1] TRUE TRUE TRUE TRUE TRUE TRUE TRUE FALSE FALSE FALSE
```

```
a[a<10] #select all numbers < 10
```

```
[1] 0 1 1 2 3 5 8
```

```
a[a %% 2 == 0] #select all even numbers.
```

```
[1] 0 2 8 34
```

```
v <- c(3, 6, 1, 9, 11, 16, 0, 3, 1, 45, 2, 8, 9, 6, -4)
v[ v > median(v)]
```

```
[1] 9 11 16 45 8 9
```

## 2.6 Vector Operations

```
v <- c(11, 12, 13, 14, 15)
w <- c(1, 2, 3, 4, 5)
v + w
```

```
[1] 12 14 16 18 20
```

```
v - w
```

```
[1] 10 10 10 10 10
```

```
v * w
```

```
[1] 11 24 39 56 75
```

```
v / w
```

```
[1] 11.000000 6.000000 4.333333 3.500000 3.000000
```

```
vw
```

```
[1] 11 144 2197 38416 759375
```

```
sqrt(w)
```

```
[1] 1.000000 1.414214 1.732051 2.000000 2.236068
```

```
log(w)
```

```
[1] 0.0000000 0.6931472 1.0986123 1.3862944 1.6094379
```

## 2.7 Broadcasting

```
w
```

```
[1] 1 2 3 4 5
```

```
w+2
```

```
[1] 3 4 5 6 7
```

```
w*2
```

```
[1] 2 4 6 8 10
```

```
w/2
```

```
[1] 0.5 1.0 1.5 2.0 2.5
```

```
2w
```

```
[1] 2 4 8 16 32
```

```
w^2
```

```
[1] 1 4 9 16 25
```

**Example:**

```
(w - mean(w)) / sd(w)
```

```
[1] -1.2649111 -0.6324555 0.0000000 0.6324555 1.2649111
```

## 2.8 Matrices

```
M = matrix(c(1, 2, 3, 4), 2, 2)
print(M)
```

```
      [,1] [,2]
[1,]    1    3
[2,]    2    4
```

## 3 User Defined Functions in R

```
x = c(3,4,4,5,6,9,20,3)
mean(x)
```

```
[1] 6.75
```

```
sum(x)/length(x)
```

```
[1] 6.75
```

In the absence of standard mean function, we could define our own function.

```
myMean = function(y){
  sum(y) / length(y)
}
myMean(x)
```

```
[1] 6.75
```

```
mySD = function(z){  
  sqrt(sum(x-myMean(x))^2/ (length(x)-1))  
}
```

## 4 Conditional Statements & Loops

```
# ifelse(condition, expr1, expr2)  
  
gender = c("Male","Female","male","Female")  
  
ifelse(gender == "Male",print("M"), print("F"))
```

```
[1] "M"  
[1] "F"
```

```
[1] "M" "F" "F" "F"
```

```
length(gender)
```

```
[1] 4
```

```
x =3  
if (x > 1) {  
  1  
} else {  
  "Less Than 1"  
}
```

```
[1] 1
```

For Loop

```
for (i in 1:length(gender)){  
  ifelse(gender[i] == "Male",  
    print("M"),  
    print("F"))  
}
```



```
[1] "M"
[1] "F"
[1] "F"
[1] "F"
```

## 5 Counting the Number of Combinations

```
# choose(n, k)
choose(5, 3) # How many ways can we select 3 items from 5 items?
```

```
[1] 10
```

```
# generate all combinations of n items taken k at a time
items <- 2:5
k <- 2
combn(items, k)
```

```
      [,1] [,2] [,3] [,4] [,5] [,6]
[1,]    2    2    2    3    3    4
[2,]    3    4    5    4    5    5
```

```
combn(1:5, 3)
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,]    1    1    1    1    1    1    2    2    2    3
[2,]    2    2    2    3    3    4    3    3    4    4
[3,]    3    4    5    4    5    5    4    5    5    5
```

```
combn(c("T1", "T2", "T3", "T4", "T5"), 2)
```

```
      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10]
[1,] "T1" "T1" "T1" "T1" "T2" "T2" "T2" "T3" "T3" "T4"
[2,] "T2" "T3" "T4" "T5" "T3" "T4" "T5" "T4" "T5" "T5"
```

## 6 Generating Random Numbers

```
runif(1)
```

```
[1] 0.01695934
```

R can generate random variates from other distributions as well. For a given distribution, the name of the random number generator is “r” prefixed to the distribution’s abbreviated name (e.g., `rnorm` for the normal distribution’s random number generator). This example generates one random value from the standard normal distribution:

```
rnorm(1)
```

```
[1] 0.5300611
```

There are random number generators for all built-in distributions. Simply prefix the distribution name with “r” and you have the name of the corresponding random number generator. Here are some common ones:

```
runif(1, min = -3, max = 3)      # One uniform variate between -3 and +3
```

```
[1] -0.08476624
```

```
rnorm(1)                        # One standard normal variate
```

```
[1] 0.1828974
```

```
rnorm(1, mean = 100, sd = 15)   # One normal variate, mean 100 and SD 15
```

```
[1] 76.85778
```

```
rbinom(1, size = 10, prob = 0.5) # One binomial variate
```

```
[1] 5
```

```
rpois(1, lambda = 10)          # One Poisson variate
```

```
[1] 8
```

```
rexp(1, rate = 0.1)            # One exponential variate
```

```
[1] 3.57051
```

```
rgamma(1, shape = 2, rate = 0.1) # One gamma variate
```

```
[1] 10.48552
```

## 6.1 Generating Reproducible Random Numbers

Before running your R code, call the `set.seed` function to initialize the random number generator to a known state:

```
set.seed(42) # Or use any other positive integer...  
runif(10)
```

```
[1] 0.9148060 0.9370754 0.2861395 0.8304476 0.6417455 0.5190959 0.7365883  
[8] 0.1346666 0.6569923 0.7050648
```

## 6.2 Generating a Random Sample

The `sample` function will randomly select  $n$  items from a set:

```
# sample(set, n)  
s = seq(1:10)  
s
```

```
[1] 1 2 3 4 5 6 7 8 9 10
```

```
sample(s,3)
```

```
[1] 8 7 4
```

```
medians <- numeric(1000) # empty vector of 1000 numbers  
x = 10  
for (i in 1:1000) {  
  medians[i] <- median(sample(x, replace = TRUE))  
}  
head(medians)
```

```
[1] 5.0 5.5 4.5 5.5 5.5 6.0
```

```
sample(c("H", "T"), 10, replace = TRUE)
```

```
[1] "H" "T" "H" "T" "T" "H" "H" "H" "T" "H"
```

```
sample(c("H", "T"), 10, replace = TRUE, prob = c(0.2, 0.8))
```

```
[1] "T" "T" "T" "T" "T" "T" "T" "H" "T" "H"
```

## 7 Data Cleaning Set the working directory.

```
data = read.csv('../data/Salary_Data.csv')  
dim(data) #rows, cols
```

```
[1] 30  2
```

```
summary(data)
```

YearsExperience	Salary
Min. : 1.100	Min. : 37731
1st Qu.: 3.200	1st Qu.: 56721
Median : 4.700	Median : 65237
Mean : 5.313	Mean : 76003
3rd Qu.: 7.700	3rd Qu.: 100545
Max. : 10.500	Max. : 122391

```
head(data) #first 6
```

	YearsExperience	Salary
1	1.1	39343
2	1.3	46205
3	1.5	37731
4	2.0	43525
5	2.2	39891
6	2.9	56642

```
head(data, 8) #first 8
```

	YearsExperience	Salary
1	1.1	39343
2	1.3	46205
3	1.5	37731

```
4          2.0  43525
5          2.2  39891
6          2.9  56642
7          3.0  60150
8          3.2  54445
```

```
str(data)
```

```
'data.frame':  30 obs. of  2 variables:
 $ YearsExperience: num  1.1 1.3 1.5 2 2.2 2.9 3 3.2 3.2 3.7 ...
 $ Salary         : num  39343 46205 37731 43525 39891 ...
```

```
colnames(data)
```

```
[1] "YearsExperience" "Salary"
```

```
## change names of the column

# colnames(data)[1] = "Name"
# colnames(data)[2:4] = c("Title","ID","AgencyName")
```