

Vertical Balers

X-series



Baler X25 AD

Fits into tight spaces and low ceilings

Internal cross cylinders make this baler very low in height and makes it easy to install.


Achieve high bale weight

The superior press force combined with a long stroke helps you achieve a high bale weight.

Highlights

- For various types of material – even expandable
- Large and wide chamber
- Retainers prevent in-chamber material expansion
- Short cycle time for fast clean up
- Moving parts are protected inside the machine
- Low overall height
- Powder Coating provides durable finish in many colors

Optional Extras



Control who operates your baler with a digital auto lock.



You may choose other RAL colours for your balers.



With our monitoring system BRA-IN you can control and optimize your baler fleet.

Product details

Baler X25 AD



Whisper

30 dB



Refrigerator

50 dB




X25 AD

59-60 dB



Other balers

75 dB




Cars on highway

100 dB



Turbojet engine

160 dB



Technical specifications

BaleSizeWDH	1200 x 800 x 800
FeedOpenWH	1090 x 530
PowerSupply	3x400V 50Hz 16A
MotorKW	4.0
CycleTime	23
DimWDH	1755 x 1395 x 1995
Weight	1425
Stroke	950
NoTies	4
Tying	Twine / Steel wire
FullLight	Yes
BaleEject	Automatic



Bale weight

Cardboard (kg)	200-300
Plastic foil (kg)	250-350



Press force	25 t
-------------	------



Noise level	59-60 dB
-------------	----------



Waste types

Cardboard, plastic foil, paper, PET bottles, alu cans, tin cans, hard plastic, textile, EPS.

BRAMIDAN
bramidan.com

Bramidan A/S
Industrivej 69
6740 Bramming
Denmark
Tel. +45 7517 3266
bramidan@bramidan.dk