

# Introduction to Artificial Intelligence Coursework<sup>1</sup>

*(Submission by groups of two students allowed/welcome)*

*Due date: Wednesday 4 March 2015*

*Electronic submission (code + this worksheet) on CATE*

## 1. Introduction

We will be looking at a two player board game called “war of life” which will be played on an 8x8 board. Player 1 will start with a random configuration of 12 blue pieces and player 2 will start with a similar random configuration of 12 red pieces. An example initial configuration might be (where b stands for “blue piece” and r stands for “red piece”):

	1	2	3	4	5	6	7	8
1								r
2		r						
3				b	b		r	b
4	b	b				r		
5		b	r	b		b	b	
6		b				r		
7			b		b	r	r	r
8			r				r	r

We call the board places where pieces can be placed *cells* (there are 64 cells on an 8x8 board). In the game, player 1 goes first and moves one of his/her pieces. A piece can be moved to one of its neighbour cells (vertically, horizontally or diagonally) as long as no other piece is occupying the cell to be moved to. So, for example, the blue piece at (3, 8) can move to (2,7), (2,8) or (4,7) or (4,8), but not (3,7) because there is a red piece there already. We say that a piece is *surrounded* by the pieces in neighbouring cells.

There is a twist: after each player moves, “life” on the board “evolves” according to the following rules (referred to as Conway’s Crank):

For each of the (64) cells C on the board:

- If C contains a piece and the piece is surrounded by 0 or 1 other pieces, then the piece dies of loneliness and is taken away (i.e., the cell becomes empty).
- If C contains a piece and the piece is surrounded by 4, 5, 6, 7 or 8 pieces, then the piece dies of overcrowding and is taken away.
- (If C contains a piece and the piece is surrounded by 2 or 3 pieces, then it is happy and survives.)
- If C is empty and C is surrounded by
  - 2 blue pieces and 1 red piece, or
  - 3 blue pieces,then a blue life is born and C is filled with a blue piece.
- If C is empty and C is surrounded by
  - 2 red pieces and 1 blue piece, or
  - 3 red pieces,then a red life is born and C is filled with a red piece.

---

<sup>1</sup> Thanks to Simon Colton

The game terminates as follows:

- If at some stage no (red or blue) pieces at all are left on the board, then the game is *drawn*.
- If, when it is his/her turn, a player cannot move anywhere, then the game is declared a *stalemate* and is *drawn*.
- If one player has no pieces left on the board, then that player *loses* and the other player wins.
- If the game lasts for 250 moves without a winner, then it is declared an *exhausted draw*.

## Part 1 – Getting to know the Game

### Question 1

	1	2	3	4	5	6	7	8
1	b							r
2		r				b		r
3				b	b		r	b
4	b	b				r		
5			r				b	
6		b				r		
7	b		b		b	r	r	r
8			r				r	

Draw the board state after a turn of Conway's Crank, given the left board.

	1	2	3	4	5	6	7	8
1								
2								
3								
4								
5								
6								
7								
8								

Download the Prolog program `war_of_life.pl` from CATE.

This provides a set of predicates for playing the game:

#### Top Level Predicates in File

`start_config(+Configuration, -InitialBoardState)`

This returns an initial randomised board state with 12 pieces for each player on an 8x8 board.

`draw_board(+BoardState)`

Given a board state in the format described below, this predicate will present it on screen.

`next_generation(+BoardState, -NextGenerationBoardState)`

This performs a Conway Crank and produces the next generation board state.

`play(+Showboard, +FirstPlayerStrategy, +SecondPlayerStrategy, -NumberOfMoves, -WinningPlayer)`

This will play a game given the strategy of player 1 and the strategy of player 2. The `+Showboard` variable is either set to `verbose`, in which case it will print out the board states as the game progresses, or `quiet`, in which case it just returns an answer, namely the `NumberOfMoves` in the completed game and the colour of the `WinningPlayer`.

Board states are represented in the program as pairs of lists, where the first list contains the co-ordinates of all the alive blue pieces and the second list contains the co-ordinates of all the alive red pieces. For example, this is a simple board state with two alive blues and one alive red:

`[[[3,4],[5,7]],[[8,8]]]`

## Question 2

In the box below, write down the Prolog representation for the initial board state given in question 1.

Use this representation, and the predicate

```
next_generation(+BoardState, -NextGenerationBoardState)
```

to check whether your answer for question 1 was correct. If it is, then run a further two generations, and put the resulting board states in the tables below:

3<sup>rd</sup> Generation:

	1	2	3	4	5	6	7	8
1								
2								
3								
4								
5								
6								
7								
8								

4<sup>th</sup> Generation:

	1	2	3	4	5	6	7	8
1								
2								
3								
4								
5								
6								
7								
8								

## Question 3

In a Prolog shell, load the file `war_of_life.pl` and run this query:

```
play(verbose, random, random, NumMoves, WinningPlayer).
```

This will play a game of war of life. Each player will randomly move a piece until the game is won or drawn. The predicate records how many moves there were in the game and who won. Run this a few times to get a feel for what it does and how the games progress when players choose randomly.

Now open a new file called `my_wol.pl`. In the file, write a (Sicstus) Prolog program to act as a wrapper for the `play/5` predicate. In particular, you should write a predicate called `test_strategy/3` which takes three inputs: the number of games, `N`, to play, the strategy for player 1 and the strategy for player 2. When run, the predicate will play the war of life game `N` times and tell you (print to screen) how many draws and how many wins for each player there have been, the longest, shortest, and average moves in a game, and the average time taken to play a game. Use the `test_strategy/3` predicate to run the game 1000 times, with both players moving pieces randomly. Record the results in this box:

Number of draws	
Number of wins for player 1 (blue)	
Number of wins for player 2 (red)	
Longest (non-exhaustive) game	
Shortest game	
Average game length (including exhaustives)	
Average game time	

#### Question 4

Does it look like there is any advantage to playing first if both players choose moves randomly? Answer in the space below.

## **Part 2 – Implementing Strategies**

In this part, we will be implementing search strategies in order to improve a war of life playing agent's performance. They already have one strategy: `random`, which chooses any piece randomly and moves it randomly. The question is: can we implement any strategy which out-performs this one?

We will look at four strategies:

### **Bloodlust:**

This strategy chooses the next move for a player to be the one which (after Conway's crank) produces the board state with the fewest number of opponent's pieces on the board (ignoring the player's own pieces).

### **Self Preservation:**

This strategy chooses the next move for a player to be the one which (after Conway's crank) produces the board state with the largest number of that player's pieces on the board (ignoring the opponent's pieces).

### **Land Grab:**

This strategy chooses the next move for a player to be the one which (after Conway's crank) produces the board state which maximises this function: Number of Player's pieces – Number of Opponent's pieces.

### **Minimax:**

This strategy looks two-ply ahead using the heuristic measure described in the Land Grab strategy. It should follow the minimax principle and take into account the opponent's move after the one being chosen for the current player.

In your file `my_wol.pl`, write five predicates (use Sicstus Prolog):

```
bloodlust(+PlayerColour, +CurrentBoardState, -NewBoardState, -Move).
self_preservation(+PlayerColour, +CurrentBoardState, -NewBoardState, -Move).
land_grab(+PlayerColour, +CurrentBoardState, -NewBoardState, -Move).
minimax(+PlayerColour, +CurrentBoardState, -NewBoardState, -Move).
```

These predicates will implement the four strategies described above by choosing the next move for a player. They will all do the same thing: choose the next move for the player. `PlayerColour` will either be the constant `b` for blue or `r` for red. The `CurrentBoardState` will be the state of the board upon which the move choice is going to be made. The predicate will produce a `NewBoardState`, in the usual representation (pair of lists) which will represent the board state after the move, but before Conway's crank is turned. The predicate will also return the `Move` that changed the current to the new board state. This will be represented as a list `[r1,c1,r2,c2]` where the move chosen is to move the piece at co-ordinate `(r1, c1)` to the empty cell at co-ordinate `(r2, c2)`.

It should be possible to run these strategies in the same way as the random strategy, using the constants `bloodlust`, `self_preservation`, `land_grab`, `minimax`. For example, if you load `war_of_life.pl` and `my_wol.pl` into Prolog, then type the query:

```
play(verbose, bloodlust, land_grab, NumberOfMoves, WinningPlayer).
```

this will play a game in which player 1 uses the `bloodlust` strategy and player 2 uses the `land_grab` strategy. Check that this is working OK by running a few games with different strategy pairings.

## **Part 3 – A Tournament**

### Question 5

We want to know which, if any, strategy is the best for playing this game, and we'll do this by using a tournament. Play as many games as time will allow for each pairing of strategies, and fill in the table over the page.

### Question 6

If both players have the same strategy, for which strategies does it appear that playing first is an advantage/disadvantage? Answer in the space below:

### Question 7

Imagine playing football in a gale force wind and where the pitch is extremely muddy. Here, it is hardly worth the players kicking the ball, because the environment plays too big a factor in the game. What evidence do you have against the claim that the environment plays a bigger part than the movement of pieces in the war of life game? The environment here is Conway's Crank, which is beyond the control of the players. Answer in the space below:

## **Submitting Your Work**

### Electronic submission: submit

- 1) Your code `my_wol.pl` (written in Sicstus Prolog and executable on the lab machines). Please do not include or load (or ensure\_loaded) `war_of_life.pl` in `my_wol.pl`! (Yes, this means `my_wol.pl` will not work on its own, but this is crucial for the autotesting) Furthermore, use `play(quiet,...)` rather than `play(verbose,...)` and don't include any write-statements other than the necessary ones in `test_strategy` (like no. of draws, average time, ...).
- 2) A file `worksheet.pdf` (your completed version of this worksheet).

P1 strategy	P2 strategy	Games Played	P1 wins	P2 wins	Draws	Av. Game Length (moves)	Av. Game Time (seconds)
Random	Random						
Random	Bloodlust						
Random	Self Preservation						
Random	Land Grab						
Random	Minimax						
Bloodlust	Random						
Bloodlust	Bloodlust						
Bloodlust	Self Preservation						
Bloodlust	Land Grab						
Bloodlust	Minimax						
Self Preservation	Random						
Self Preservation	Bloodlust						
Self Preservation	Self Preservation						
Self Preservation	Land Grab						
Self Preservation	Minimax						
Land Grab	Random						
Land Grab	Bloodlust						
Land Grab	Self Preservation						
Land Grab	Land Grab						
Land Grab	Minimax						
Minimax	Random						
Minimax	Bloodlust						
Minimax	Self Preservation						
Minimax	Land Grab						
Minimax	Minimax						