

Safety Manual

Health & Safety Program

Test Company LLC

Effective ...

Important Notice. This safety manual is a customizable template provided as a starting point. It is **not legal or safety-compliance advice** and does not guarantee compliance with OSHA or any state safety agency. Job hazards, required written programs, and training vary by industry, task, and jurisdiction. **Have this manual reviewed by a qualified safety professional and adapted to your worksite before adoption.**

Contents

Introduction

About This Safety Manual

Section 1: Safety Program & Responsibilities

Safety Policy Statement

Roles & Responsibilities

Hazard Identification & Inspections

Safety Training

Return to Work & Modified Duty

Contractor & Subcontractor Safety

Safety Enforcement

Section 2: Core OSHA Programs

Written Safety & Health Program

Hazard Communication (HazCom / GHS)

Personal Protective Equipment (PPE)

Emergency Action & Fire Prevention

Injury Reporting & Recordkeeping

Safety Inspections & Audits

Incident Investigation

Near Miss & Hazard Reporting

Section 3: Job-Specific Hazard Programs

Lockout/Tagout (Control of Hazardous Energy)

Fall Protection

Scaffolding Safety (29 CFR 1926.451)

Excavation & Trenching (29 CFR 1926.650)

Ladders & Stairways (29 CFR 1926 Subpart X)

Steel Erection (29 CFR 1926 Subpart R)

Respiratory Protection

Respirable Crystalline Silica (29 CFR 1926.1153)

Asbestos & Lead Awareness

Confined Spaces

Electrical Safety

Hot Work, Welding & Cutting

Powered Industrial Trucks (Forklifts)

Cranes, Hoists & Rigging (29 CFR 1926 Subpart CC)

Aerial Lifts & Scissor Lifts

Bloodborne Pathogens

First Aid & Medical Services

Heat Illness Prevention

Workplace Violence Prevention

Ergonomics

Fleet & Driver Safety

Housekeeping & Slip, Trip and Fall Prevention

Acknowledgment

Safety Program Acknowledgment

Introduction

About This Safety Manual

*This Safety Manual is issued by **Test Company LLC** ("the Company"), effective [Effective Date]. It describes the Company's safety and health program and the responsibilities of every employee. Direct questions to your Human Resources Department.*

The Company is committed to providing a safe and healthful workplace and to complying with the federal Occupational Safety and Health Act (and, where applicable, an OSHA-approved state plan). This manual is a general program document; it does not replace the specific written programs, training, and site-specific procedures that certain hazards require.

Section 1: Safety Program & Responsibilities

Safety Policy Statement

The safety and health of our employees is a core priority. No task is so urgent that it cannot be done safely. Management is responsible for providing a safe workplace, the necessary training, and appropriate protective equipment. Every employee is responsible for following safe work practices, using required protection, and reporting hazards. Safety is a shared responsibility and a condition of employment.

Roles & Responsibilities

Management ensures resources, training, and enforcement of this program. Supervisors enforce safe practices, correct hazards, investigate incidents, and train their teams. Employees follow all safety rules, use required personal protective equipment (PPE), report hazards, injuries, and near-misses, and never remove or defeat a safety device. A designated safety coordinator maintains records and coordinates the program.

Hazard Identification & Inspections

The Company conducts periodic workplace inspections to identify and correct hazards. Employees are encouraged to report unsafe conditions immediately, without fear of retaliation. Identified hazards are prioritized and corrected, and interim protective measures are used until a permanent fix is in place.

Safety Training

Employees receive safety training at hire, when assigned new tasks or equipment, when hazards change, and periodically thereafter. Training covers this program, job-specific hazards, safe work procedures, and the proper use of PPE. Training is documented and retained.

Return to Work & Modified Duty OPTIONAL

An injured employee who returns to productive work recovers faster and costs less. Test Company LLC maintains a formal return-to-work program and will make every reasonable effort to provide temporary modified or transitional duty to an employee recovering from a work-related injury or illness.

How it works. After a work-related injury, the treating physician is given a written job description and asked to state the employee's specific physical capabilities and restrictions. The Company then identifies temporary work within those restrictions, a modification of the employee's regular job, a

reduced schedule, or a different assignment. The offer is made in writing and states the duties, hours, pay, and expected duration.

Terms. Modified duty is temporary, is reviewed at each medical appointment, and generally does not extend beyond ninety days without review by your Human Resources Department. It is not a permanent position and does not change the employee's regular job classification. Employees are paid for the work performed; where the modified wage is lower than the pre-injury wage, temporary partial disability benefits may apply under the state workers' compensation system.

Employee responsibilities. Attend all scheduled medical appointments, provide the Company with each work status report the same day it is issued, work within the stated restrictions both on and off the job, and report immediately any task that exceeds them. Refusing a bona fide offer of modified duty within the treating physician's restrictions may affect entitlement to wage replacement benefits under state law.

Participation in this program is not an admission of liability, is not discipline, and does not affect an employee's rights under workers' compensation, the ADA, or the FMLA. Where an injury results in a permanent limitation, the Company will engage in the interactive accommodation process separately.

Contractor & Subcontractor Safety OPTIONAL

Contractors, subcontractors, staffing agency workers, and their employees are expected to meet the same safety standards as Test Company LLC employees while on a Company or client worksite.

Before work begins. Every contractor must provide a current certificate of insurance naming Test Company LLC as additional insured, evidence of workers' compensation coverage for all of its workers, a copy of its written safety program, and, on request, its OSHA 300A summary and experience modification rate. A contractor that cannot produce proof of workers' compensation coverage may not begin work, uninsured subcontractor payroll is routinely charged back to the hiring contractor on a workers' compensation audit.

On site. Contractors receive a site-specific orientation covering hazards, emergency procedures, assembly points, PPE requirements, and reporting. Contractors are responsible for training and supervising their own workers, for providing their own PPE and equipment, and for complying with all applicable OSHA standards. Permit-required work (hot work, confined space entry, energized electrical work, excavation, roof work) requires a Company permit before it starts.

Reporting and enforcement. Contractors must report all injuries, near misses, spills, and property damage occurring on the worksite to the Company the same day. Any Company supervisor may stop contractor work that presents an imminent hazard. Repeated violations may result in removal from the site and termination of the contract.

Where Test Company LLC and a contractor both have employees exposed to the same hazard, the parties will coordinate to determine controlling responsibility and to ensure the hazard is corrected regardless of which employer created it.

Safety Enforcement

Compliance with safety rules is mandatory. Violations may result in corrective action, up to and including termination, consistent with Company policy and applicable law. Enforcement is applied fairly and consistently. Reporting a safety concern in good faith is protected and will never result in retaliation.

Section 2: Core OSHA Programs

Written Safety & Health Program

The Company maintains a written safety and health program that establishes responsibility, a system for identifying and correcting hazards, procedures for investigating incidents, safety training, and a means for employees to report hazards. Several states (for example, California's Injury and Illness Prevention Program) require a written program by law; the Company maintains one as a best practice regardless.

Hazard Communication (HazCom / GHS)

Employees who may be exposed to hazardous chemicals are informed and trained under the OSHA Hazard Communication Standard. The Company maintains a chemical inventory, keeps Safety Data Sheets (SDS) accessible to employees, ensures containers are properly labeled under the Globally Harmonized System (GHS), and trains employees on chemical hazards and protective measures.

Personal Protective Equipment (PPE)

Where hazards cannot be eliminated by other means, the Company provides and requires appropriate PPE, such as eye, head, hand, foot, hearing, and respiratory protection. The Company assesses PPE needs by task, trains employees on proper use and care, and requires that PPE be worn as directed. Employees must inspect PPE before use and report damaged equipment.

Emergency Action & Fire Prevention

The Company maintains an Emergency Action Plan covering evacuation routes and procedures, alarm systems, assembly points, and how to report emergencies. Fire prevention measures include control of ignition sources, proper storage of flammables, access to fire extinguishers, and clear exits. Employees are trained on emergency procedures and participate in drills as scheduled.

Injury Reporting & Recordkeeping

Employees must report every work-related injury or illness to their supervisor immediately, no matter how minor. The Company records and reports injuries and illnesses as required by OSHA (including, where covered, the OSHA 300 Log, 300A Summary, and 301 forms) and reports severe incidents to OSHA within required timeframes. Retaliation for reporting an injury is prohibited.

Safety Inspections & Audits OPTIONAL

Regular inspection is how hazards are found before they cause injury. Test Company LLC conducts documented safety inspections on a defined schedule: daily pre-shift walkarounds by the supervisor at each active work area, weekly documented inspections of tools, equipment, and housekeeping, and a comprehensive facility or site audit at least quarterly.

Inspections use a written checklist appropriate to the work being performed. Every finding is recorded with a description of the hazard, its location, an assigned corrective action, a responsible person, and a due date. Imminent hazards are corrected immediately or the area is barricaded and the work stopped. Open items are reviewed at the next safety meeting until closed.

Employees are encouraged to participate in inspections and to report hazards at any time without waiting for a scheduled walk. Inspection records are retained for at least three years and are reviewed for trends, a hazard that appears repeatedly indicates a systemic problem, not an individual failure.

Incident Investigation

The Company investigates injuries, illnesses, and significant near-misses to determine root causes and prevent recurrence. Investigations focus on identifying system and hazard causes rather than assigning blame. Corrective actions are tracked to completion.

Near Miss & Hazard Reporting OPTIONAL

A near miss is an event that could have caused injury or damage but did not. Near misses are free lessons, and reporting them is the single most effective way to prevent a future injury.

Employees must report every near miss, unsafe condition, unsafe act, and equipment defect to a supervisor as soon as it is safe to do so. Reports may be made verbally, on the Company's hazard report form, or anonymously through any method the Company provides. No employee will be disciplined, retaliated against, or have any incentive withheld for making a good faith report, and safety incentive programs will never be structured in a way that discourages reporting, which OSHA prohibits.

Every report is logged, investigated to the level warranted by its potential severity, and closed with a documented corrective action. The reporter is told what was done. Trends are reviewed in safety meetings and used to update training and inspection checklists.

Section 3: Job-Specific Hazard Programs

Lockout/Tagout (Control of Hazardous Energy) OPTIONAL

Before servicing or maintaining machines or equipment where unexpected energization could cause injury, authorized employees isolate and lock out all hazardous energy sources following written procedures. Only trained, authorized employees perform lockout/tagout. Employees must never operate equipment that is locked or tagged out.

Fall Protection OPTIONAL

Where employees are exposed to falls from height above the applicable trigger height, the Company provides fall protection (guardrails, safety nets, or personal fall-arrest systems) and trains employees in their use, inspection, and limitations. Fall-protection equipment is inspected before each use.

Scaffolding Safety (29 CFR 1926.451) OPTIONAL

Scaffolds are erected, moved, altered, and dismantled only under the supervision of a competent person qualified in scaffold erection, and only by trained and experienced employees.

Design and capacity. Every scaffold and component supports its own weight plus at least four times the maximum intended load. Scaffolds are erected on base plates and mud sills or another adequate firm foundation, plumb, level, and braced. Scaffolds are not supported by unstable objects such as barrels, boxes, loose brick, or concrete block.

Platforms and access. Platforms are fully planked with no gap greater than one inch between planks or between the platform and uprights. Fall protection is required above ten feet: a guardrail system with a top rail at 38 to 45 inches, a midrail, and toeboards where anyone may pass below, or a personal fall arrest system. Access is by stairway, ladder, ramp, or integral prefabricated frame access, never by climbing cross braces.

Daily inspection. A competent person inspects each scaffold and its components before every work shift and after any event that could affect structural integrity. Damaged parts are removed from service and tagged. Scaffolds are not used during high wind, storms, or when covered with ice or snow unless a competent person determines it is safe and fall protection is in place. Work is stopped and the scaffold cleared when the minimum safe clearance from energized power lines cannot be maintained.

Excavation & Trenching (29 CFR 1926.650) OPTIONAL

A cubic yard of soil weighs about as much as a small car. Trench collapse is the leading cause of death in excavation work and it happens without warning. No employee enters an unprotected trench.

Before digging. Underground utilities are located and marked through the 811 One Call service before any excavation begins, and are protected, supported, or removed once exposed. The competent person classifies the soil and determines the protective system.

Protective systems. Any excavation five feet deep or greater requires a protective system (sloping or benching to the angle required for the soil type, shoring, or a trench shield) unless the excavation is made entirely in stable rock. Excavations deeper than twenty feet require a system designed by a registered professional engineer. A protective system is required at any depth where the competent person finds evidence of a possible cave-in.

Access and hazards. A ladder, stairway, or ramp is provided in any trench four feet or deeper, located within twenty-five feet of every employee. Spoil piles, equipment, and materials are kept at least two feet from the edge. Employees do not work under suspended loads or under the reach of loading equipment. Air is tested where a hazardous atmosphere could exist, and water is not allowed to accumulate.

Inspection. The competent person inspects the excavation, adjacent areas, and protective systems daily before each shift, after every rainstorm, and after any other hazard-increasing event. Where any hazard is found, employees are removed until it is corrected.

Ladders & Stairways (29 CFR 1926 Subpart X) OPTIONAL

Ladders are inspected before each use and removed from service if damaged, missing parts, or contaminated with oil or grease. Damaged ladders are tagged and destroyed or repaired to original strength; they are never used in the meantime.

Use. Portable ladders used to access an upper level extend at least three feet above the landing surface and are secured at the top or held. Non-self-supporting ladders are set at a 4-to-1 pitch, one foot out for every four feet of working length. Employees face the ladder, maintain three points of contact, and do not carry loads that could cause a loss of balance. Only one person is on a ladder at a time unless it is designed for more.

Prohibited. Do not stand on the top step or top cap of a stepladder, place a ladder on boxes, barrels, or other unstable bases, use a ladder in a horizontal position as a platform or runway, tie ladders together to gain length, or move a ladder while occupied. Metal and wire-reinforced ladders are never used near energized electrical equipment.

Stairways. Stairways with four or more risers or rising more than thirty inches have a handrail and stair rail system. Treads are kept free of debris, and slippery conditions are corrected before the stairway is used. Temporary stairs are not filled with construction material.

Steel Erection (29 CFR 1926 Subpart R) OPTIONAL

Steel erection does not begin until the controlling contractor provides written notification that the concrete in footings, piers, and walls has attained either seventy-five percent of its intended minimum compressive design strength or sufficient strength to support the loads imposed, and that any repaired or replaced anchor bolts have been approved by the project structural engineer.

Site conditions. The controlling contractor provides and maintains adequate access roads and a firm, properly graded, drained area for the safe operation of equipment. Columns are anchored by a minimum of four anchor rods and designed to resist a 300-pound eccentric load.

Fall protection. Employees engaged in steel erection are protected from fall hazards of more than fifteen feet; connectors and employees working in a controlled decking zone are protected above fifteen feet under the specific conditions the standard allows. All other employees are protected above six feet. Perimeter safety cables are installed at the final interior and exterior perimeters of multi-story structures as soon as the metal decking is installed.

Hoisting and decking. A pre-shift visual inspection of cranes is performed by a competent person. No employee is permitted directly under a suspended load except those hooking or unhooking it. Multiple lifts are performed only with a rigging assembly specifically designed for that purpose. Metal decking is laid tightly and secured immediately to prevent accidental movement or displacement, and roof and floor holes are covered immediately after the deck is installed.

Respiratory Protection OPTIONAL

Where respiratory hazards are present and cannot be controlled by other means, the Company implements a respiratory protection program including hazard assessment, medical evaluation, fit testing, proper selection, training, and maintenance of respirators, in accordance with the OSHA Respiratory Protection Standard.

Respirable Crystalline Silica (29 CFR 1926.1153) OPTIONAL

Cutting, grinding, drilling, chipping, or crushing concrete, masonry, brick, stone, or engineered stone releases respirable crystalline silica. Long-term exposure causes silicosis, an incurable and disabling lung disease, and increases the risk of lung cancer and kidney disease.

Table 1 controls. For each covered task, Test Company LLC implements the engineering control, work practice, and respiratory protection specified in Table 1 of the standard, typically an integrated water delivery system that continuously wets the cutting surface or a dust collection system with a

HEPA-filtered vacuum sized to the tool. Where a task is not on Table 1, or the controls are not fully and properly implemented, exposure is assessed and kept below the permissible exposure limit of 50 micrograms per cubic meter as an eight-hour TWA.

Work practices. Dry sweeping and compressed air are prohibited for cleanup where they would cause silica to become airborne unless no safer alternative exists. Employees do not eat, drink, or smoke in dust-exposed areas, and wash hands and face before doing so.

Program requirements. A written exposure control plan identifies the tasks, controls, and housekeeping measures and designates a competent person to implement it and to conduct frequent inspections. Employees are trained on the health hazard, the tasks that create exposure, and the controls. Medical surveillance, including a chest X-ray and pulmonary function test, is offered at no cost to any employee required to wear a respirator for silica tasks thirty or more days a year.

Asbestos & Lead Awareness OPTIONAL

Buildings constructed before 1980 may contain asbestos in insulation, floor tile, mastic, roofing, siding, and pipe wrap, and lead in paint, solder, and plumbing. Disturbing these materials releases fibers or dust that cause serious, often delayed disease.

Presume and stop. Employees treat suspect material in a pre-1980 structure as containing asbestos or lead unless testing proves otherwise. No employee disturbs, cuts, sands, drills, scrapes, burns, or removes suspect material. Work stops and a supervisor is notified immediately if suspect material is discovered or damaged during other work.

Licensed work only. Abatement, removal, and disturbance of asbestos-containing material or lead-based paint is performed only by properly licensed and certified contractors under a separate written compliance program, with the required notifications, containment, air monitoring, and disposal. Test Company LLC employees do not perform this work unless specifically trained, certified, and enrolled in medical surveillance.

Renovation rule. Work that disturbs lead-based paint in housing or a child-occupied facility built before 1978 is subject to the EPA Renovation, Repair and Painting rule, which requires a certified firm, a certified renovator on site, lead-safe work practices, and documented client notification.

Confined Spaces OPTIONAL

Permit-required confined spaces are identified and controlled. Entry occurs only under a permit system with atmospheric testing, ventilation, attendants, communication, and rescue procedures. Only trained, authorized employees enter permit spaces.

Electrical Safety OPTIONAL

Only qualified employees perform electrical work. The Company follows safe electrical work practices, guards live parts, uses ground-fault protection where required, and de-energizes circuits before work whenever feasible. Employees report damaged cords, outlets, and equipment.

Hot Work, Welding & Cutting OPTIONAL

Hot work means welding, cutting, brazing, soldering, grinding, or any operation producing sparks, flame, or heat. Sparks travel, up to thirty-five feet horizontally and much farther when falling, and can smolder for hours before igniting.

Permit. A written hot work permit is required for any hot work performed outside a designated shop area. The permit is issued by an authorized person after the area is inspected, is valid for a defined period and location only, and is posted at the work site.

Before the work. Move combustibles at least thirty-five feet away, or shield them with fire-resistant covers. Protect or seal floor and wall openings, cracks, and ducts. Confirm the atmosphere is safe where flammable vapors may be present. Have the correct fire extinguisher immediately at hand and know the alarm procedure. Never perform hot work on a container that has held a flammable substance until it is cleaned and tested.

Fire watch. A trained fire watch with an extinguisher is posted during the work and continues for at least thirty minutes after it ends, sixty minutes where the risk warrants, and checks all adjacent areas, including the floor below and the far side of walls.

Personal protection. Welding helmets with the correct shade lens, flame-resistant clothing, leather gloves, and eye protection under the helmet are required. Ventilation or local exhaust removes welding fume; galvanized, stainless, cadmium, and coated metals require special attention. Cylinders are secured upright, stored with caps in place, and kept away from heat and electrical circuits.

Powered Industrial Trucks (Forklifts) OPTIONAL

Only trained, evaluated, and authorized operators may operate forklifts and other powered industrial trucks. Operators perform pre-use inspections, follow safe operating rules, and observe pedestrian and load-handling precautions. Operator certification is renewed as required.

Cranes, Hoists & Rigging (29 CFR 1926 Subpart CC) OPTIONAL

Only operators certified for the type and capacity of the equipment operate cranes and derricks in construction. Signal persons and riggers are qualified and their qualification documented.

Before the lift. The ground and supporting surface are assessed for adequate bearing capacity. Outriggers and stabilizers are fully deployed on firm footing with pads. The load is weighed or calculated and checked against the load chart for the configuration, radius, and boom length

actually in use. Rigging is inspected before each shift by a qualified rigger, and damaged slings, hooks, shackles, or synthetic web slings are removed from service immediately.

Power lines. No part of the crane, load line, or load may come within twenty feet of an energized power line up to 350 kV unless the line is de-energized and visibly grounded or an encroachment-prevention measure is in place. Distance is confirmed before work begins, not judged by eye during the lift.

During the lift. The swing radius is barricaded. No employee works or passes under a suspended load. Tag lines are used to control the load. Only one designated signal person directs the operator, using standard hand signals or a dedicated radio channel; the operator stops for any stop signal from anyone. Lifts stop in high wind, lightning, or any condition that impairs visibility or control.

Annual inspections by a qualified person and monthly documented inspections are maintained for every crane and hoist, along with all manufacturer service records.

Aerial Lifts & Scissor Lifts OPTIONAL

Only employees trained and authorized on the specific type of lift may operate one. Training covers the manufacturer's instructions, controls, load limits, hazards, and inspection, and is repeated after an accident, a near miss, a change of equipment, or observation of unsafe operation.

Before use. Complete a documented pre-use inspection of the controls, emergency lowering, guardrails, gates, tires, fluid levels, and warning devices, and a walkaround of the work area for holes, drop-offs, debris, slopes, overhead obstructions, and power lines. Defective lifts are tagged and removed from service.

Operation. In a boom-type aerial lift, employees wear a full body harness with a lanyard attached to the manufacturer's anchor point in the basket, never to an adjacent structure. In a scissor lift, the guardrail system is the fall protection; the gate or chain must be closed and employees must keep both feet on the platform floor. Never climb on or lean over the rails, never use a ladder or plank inside the platform to gain height, and never move an elevated lift unless the manufacturer permits it. Load and outreach limits are observed. Brakes are set and outriggers deployed where required.

Maintain minimum approach distance from energized lines; treat every line as energized unless the utility confirms otherwise.

Bloodborne Pathogens OPTIONAL

Where employees have occupational exposure to blood or other potentially infectious materials, the Company maintains an exposure control plan including universal precautions, engineering and work-practice controls, PPE, hepatitis B vaccination offers, and post-exposure follow-up.

First Aid & Medical Services OPTIONAL

Where medical services are not in near proximity to the worksite, Test Company LLC ensures that a person trained in first aid and CPR is available on each shift, and that adequate first aid supplies are readily accessible.

First aid kits are inspected before being sent to each job site and at least weekly on site, and are restocked immediately after use. Kit contents are appropriate to the hazards present. Where an employee may be exposed to injurious corrosive materials, an eyewash and quick-drench facility is provided within the work area for immediate emergency use.

Reporting. Every injury or illness, however minor, is reported to a supervisor before the end of the shift. Even minor cuts and strains are documented; a small injury reported late is the most common cause of a disputed claim. Employees are told where to obtain treatment and, where the state requires the employer to post or provide a designated provider list, that list is posted.

Emergency response. Each worksite has a posted emergency plan showing how to summon emergency services, the site address and nearest cross street, the location of the nearest emergency facility, and the assembly point. In a severe injury, call emergency services first, then notify a supervisor. Only trained responders provide care, using universal precautions and the personal protective equipment provided.

Heat Illness Prevention OPTIONAL

For employees working in high-heat conditions, the Company provides access to water, shade or cooling, rest breaks, acclimatization for new and returning workers, and training on recognizing and responding to heat illness. Several states have specific heat-illness standards; where they apply, the Company follows them.

Workplace Violence Prevention OPTIONAL

The Company maintains measures to prevent and respond to workplace violence, including reporting procedures, hazard assessment, and response planning. Some states (for example, California) require a written workplace violence prevention plan for many employers; where required, the Company maintains one.

Ergonomics OPTIONAL

The Company works to reduce ergonomic risk factors (such as repetitive motion, awkward postures, and manual lifting) through workplace design, safe lifting practices, and employee training. Employees are encouraged to report discomfort early.

Fleet & Driver Safety OPTIONAL

Motor vehicle crashes are the leading cause of work-related death in the United States. Every employee who drives on Company business is expected to hold a valid license appropriate to the vehicle, maintain a satisfactory driving record, and follow this program.

Before driving. Complete the pre-trip inspection required for the vehicle: tires, lights, brakes, mirrors, fluids, wipers, horn, load securement, and required equipment. Report defects and do not operate a vehicle with a safety defect. Adjust seat and mirrors before moving.

While driving. Seat belts are worn by the driver and every occupant. Obey posted limits and adjust speed for weather, traffic, and load. No handheld phone use, texting, eating, or other distraction. No driving while impaired by alcohol, cannabis, illegal drugs, prescription medication that carries a warning, or fatigue. Maintain a following distance of at least four seconds, and more for heavy vehicles or poor conditions.

Loads and backing. Loads are secured and within the vehicle's rated capacity. Backing is avoided by parking to pull forward; where backing is necessary, walk the path first and use a spotter whenever one is available.

Incidents. Report every crash, no matter how minor, to a supervisor the same day. Stop, render aid, call law enforcement, photograph the scene, exchange information, and do not admit fault or discuss liability. DOT-regulated drivers additionally follow hours-of-service, logging, medical certification, and testing requirements.

Housekeeping & Slip, Trip and Fall Prevention OPTIONAL

Slips, trips, and falls on the same level are among the most frequent workers' compensation claims in every industry, and nearly all of them are preventable by housekeeping.

Walkways, aisles, stairways, and exits are kept clear at all times. Spills are cleaned immediately and the area marked with a wet floor sign until dry. Cords and hoses are routed away from walkways or covered. Materials are stored in designated areas, stacked stably, and never in front of electrical panels, fire extinguishers, eyewash stations, or exits. Waste is removed to designated containers throughout the shift rather than at the end of it.

Lighting is maintained in all work and travel areas, and burned-out fixtures are reported. Floor damage, loose mats, torn carpet, and uneven surfaces are reported and repaired or marked. Ice and snow are cleared and treated at entrances and walkways. Employees wear footwear appropriate to the surface and the work, and use handrails on stairs.

Housekeeping is part of every job, not a separate task, and is inspected as part of the regular safety walkaround.

Acknowledgment

Safety Program Acknowledgment

I acknowledge that I have received and reviewed the Test Company LLC Safety Manual. I understand it is my responsibility to follow all safety rules, use required protective equipment, and report hazards, injuries, and near-misses to your Human Resources Department or my supervisor. I understand that failure to follow safety rules may result in corrective action.

Employee signature

Date

Employee name (print)

Supervisor