

Lab 8 - Decision Trees

An Introduction to Statistical Learning

```
pacman::p_load(tree, ISLR)
```

1. Fitting Classification Trees

The process has the following steps:

1. Fit the tree to the training data.
2. Find the optimal tree complexity using cross-validation.
3. Make predictions on the testing subset.

The `Carseats` dataset will be used.

Classification and Regression Trees are fitted using the `tree` library.

```
summary(Carseats)
```

```
##      Sales      CompPrice      Income      Advertising
##  Min.   : 0.000   Min.    : 77   Min.    : 21.00   Min.    : 0.000
## 1st Qu.: 5.390   1st Qu.:115   1st Qu.: 42.75   1st Qu.: 0.000
## Median : 7.490   Median :125   Median : 69.00   Median : 5.000
## Mean   : 7.496   Mean    :125   Mean    : 68.66   Mean    : 6.635
## 3rd Qu.: 9.320   3rd Qu.:135   3rd Qu.: 91.00   3rd Qu.:12.000
## Max.   :16.270   Max.    :175   Max.    :120.00   Max.    :29.000
##  Population      Price      ShelfLoc      Age      Education
##  Min.    : 10.0   Min.    : 24.0   Bad    : 96   Min.    :25.00   Min.    :10.0
## 1st Qu.:139.0   1st Qu.:100.0   Good   : 85   1st Qu.:39.75   1st Qu.:12.0
## Median :272.0   Median :117.0   Medium:219   Median :54.50   Median :14.0
## Mean    :264.8   Mean    :115.8               Mean    :53.32   Mean    :13.9
## 3rd Qu.:398.5   3rd Qu.:131.0               3rd Qu.:66.00   3rd Qu.:16.0
## Max.    :509.0   Max.    :191.0               Max.    :80.00   Max.    :18.0
## Urban      US
## No :118    No :142
## Yes:282    Yes:258
##
##
##
##
```

```
attach(Carseats)
```

First we split the data in train and testing subsets:

```
set.seed(1)
train = sample(1:nrow(Carseats), dim(Carseats)[1]/2)
```

We will classify the data according to `Sales`; as it's a continuous variable, we'll encode it as a binary variable, with `ifelse()`, using the mean as an approximate threshold. The resulting array must be converted to a categorical variable using `factor()`:

```
High = ifelse(Sales > 8, 'Yes', 'No')
High = factor(High)
```

We merge the new variable `High` in the dataset:

```
Carseats$High = High
```

Fitting the model

We fit the decision tree using all the variables but `Sales`:

```
tree.carseats = tree(High ~ . - Sales, data = Carseats, subset = train)
summary(tree.carseats)
```

```
##
## Classification tree:
## tree(formula = High ~ . - Sales, data = Carseats, subset = train)
## Variables actually used in tree construction:
## [1] "Price"          "Population"     "US"             "CompPrice"      "Advertising"
## [6] "Income"         "ShelveLoc"      "Age"
## Number of terminal nodes: 20
## Residual mean deviance: 0.4549 = 81.89 / 180
## Misclassification error rate: 0.105 = 21 / 200
```

The *residual mean deviance* is the deviance divided by $n - |T_0|$, being n the number of observations and T_0 the number of terminal nodes (reported by `summary()`). A small deviance indicates that the tree provides a good fit to the training data.

`summary()` also includes the *misclassification error rate*, which for *classification trees* is given by:


$$-2 \sum_m \sum_k n_{mk} \log \hat{p}_{mk}$$

where n_{mk} is the number of observations in the m th terminal node that belong to the k th class.

`tree()` selects the relevant variables and exclude the rest from the model (in this case, `Population`, `Education` and `Urban` have been excluded)

Plotting the tree

```
plot(tree.carseats)
text(tree.carseats, pretty = 0, cex = .5)
```



ShelveLoc appears to be an important indicator for Sales, because the first branch differentiates Good locations from Medium and Bad locations.

Making predictions

For classification trees, `type="class"` tells `predict()` to return the *actual class prediction*:

```
tree.pred = predict(tree.carseats, newdata = Carseats[-train,], type = 'class')
table(tree.pred, High[-train])
```

```
##
## tree.pred No Yes
##      No   84  37
##      Yes  35  44
```

The tree makes correct classifications for the 64% of the testing data:

```
mean(tree.pred == High[-train])
```

```
## [1] 0.64
```

Pruning the tree with Cross-Validation

Finding the optimal level of complexity

The optimal level of complexity for a fitted tree can be determined using cross-validation, with the `cv.tree()` function. The default metric used to guide cross-validation is the deviance, but we can specify that we want

the missclassification error rate with FUN=prune.misclass:

```
set.seed(42)
cv.carseats = cv.tree(tree.carseats, FUN = prune.misclass)
```

The result includes the following fields:

```
cv.carseats


## $size
## [1] 20 18 10  8  6  4  2  1
##
## $dev
## [1] 52 52 51 50 52 53 73 84
##
## $k
## [1] -Inf  0.0  0.5  1.5  2.0  4.0 12.0 19.0
##
## $method
## [1] "misclass"
##
## attr(,"class")
## [1] "prune"          "tree.sequence"
```

size is the number of terminal nodes of each tree considered. dev is actually the cross-validation error rate, as indicated with FUN. k is the cost-complexity parameter used, which corresponds to α in equation 8.4.

The 8-node tree has the lowest error rate, so we will use it as the final tree.

We can plot the error rate as a function of both k and size:

```
par(mfrow=c(1, 2))
plot(cv.carseats$size, cv.carseats$dev, type='b'); grid()
plot(cv.carseats$k, cv.carseats$dev, type='b'); grid()
```




Pruning the tree

We apply the `prune.misclass()` function to prune the tree to obtain the 8-node tree:

```
prune.carseats = prune.misclass(tree.carseats, best = 8)
```

```
plot(prune.carseats)
text(prune.carseats, pretty = 0, cex = .5)
```



Making predictions using the pruned tree

```
tree.pred = predict(prune.carseats, newdata = Carseats[-train,], type='class')
table(tree.pred, High[-train])
```

```
##
## tree.pred No Yes
##      No  83  24
##      Yes  36  57
```

```
mean(tree.pred == High[-train])
```

```
## [1] 0.7
```

Now the tree correctly labels the 70% of the testing data.

2. Fitting Regression Trees