# **Dot Language Specification**

David Vieten

May 9, 2024

#### Introduction

Fortunately, I have had the privilege of being around the sport of hockey for the majority of my lifetime. Over the years, it has become clear to me that the current method of drawing face-off plays is outdated and inefficient. A face-off takes place at the start of a game or following a whistle. The ref drops the puck and two center-men battle for the possesion. Face-offs play an important role in hockey, as it is an opportunity to gain possession and run a set play. As a result coaches draw up routes for each of the 5 guys on the ice, dictating the route of each player on a face-off win. Often, teams have multiple versions of these set routes called "face-off plays." These face-off plays may change on any given week depending on who the opponent is and what their weaknesses are. As a result, the players are responsible for memorizing their routes. Currently, coaches either draw up the faceoff plays on a white board and hope the players can remember it, or they draw them up on paper and distribute photocopies for the players to study.

The programming language "Dot" solves this problem. "Dot" allows coaches to create face-off plays in an svg that can be emailed to players. This language saves coaches a headache by providing a way to easily distribute face-off plays without wasting paper and ink to do so. Coaches will also be able to save face-off plays, allowing them to keep track of what plays they have used against who in the past. This ability to save face-off plays will allow coaches to save scouting reports, increasing prepardness for the team. In a typical game week, coaches will watch video on the opposing team to get an idea of what they will be faced with come game time. While watching video, coaches can create and save the opposing team's faceoff plays to determine the best counter plays. "Dot" will save coaches time and allow players to study their routes in an efficient manner.

#### **Design Principles**

Several design principles guide Dot's development to address the problem of creating and distributing faceoff plays. With accessibility and usability at the forefront of priorities, Dot produces an SVG allowing coaches to easily distribute visual representations of plays. Efficiency and scalability are two factors that Dot seeks to achieve. The ability to save and organize face-off plays supports scalability by allowing coaches to implement libraries of strategies/pre-scouts over time. Adaptability and extensibility are also fundamental design principles in the development of the language. Dot allows for the creation of custom plays designed for specific opponents, providing an advantage in the hockey world. Furthermore, Dot's support for saving and analyzing opponent's face-off plays contributes to its strategic use as a tool for planning and adapting. Moreover, Dot is built with accessibility, efficiency, and adaptability in mind.

Final Project May 9, 2024

# **Examples**

lefthash net right offense righthash corner right offense dot slot right offense leftpoint walkline right offense rightpoint halfwall right offense

stackinside corner right defense righthash backdoor right defense dot slot right defense rightpoint upwall right defense leftpoint hold right defense

lefthash hold left defense righthash slot left defense dot corner left defense stackinside net left defense stackoutside hold defense

### **Language Concepts**

To write programs in this language, users need to have a grasp on the concepts of primitives and combining forms as well as knowledge of the sport of hockey. The primitives help define areas on the hockey rink through the use of side and zone indicators to specify the context of the location. End routes represent endpoints that players will move to from their original position once the puck drops. Combining forms involve creating these routes by pairing start and end points. These routes can be organized into a board, which is a list of routes. A sequence of strategic moves can then be represented off a faceoff. By understanding these core concepts, users can effectively design player movements that will produce an advantage on game day.

Final Project May 9, 2024

# **Formal Syntax**

```
<expr> ::= <route>+
      <route>::= <routedef><dotplace>
  <routedef> ::= <startroute><endroute>
  <dotplace> ::= <side><zone>
  <endroute> ::= net
              | walkline
              | downwall
              | upwall
              | corner
              | hold
              | slot
              | backdoor
      <zone> ::= offense
             | defense
      <side> ::= right
             | left
<startroute> ::= lefthash
              | righthash
              | dot
              | rightpoint
              | leftpoint
              | stackinside
              | stackoutside
```

#### **Semantics**

Table 1: Semantics of Language

| Syntax                    | Abstract Syntax          | Prec./Assoc. | Meaning                                       |
|---------------------------|--------------------------|--------------|---|
| <side></side>             | Side of string           | N/A          | Side is primitive. Represents the sides of    |
|                           |                          |              | the ice: "right" or "left".                   |
| <zone></zone>             | Zone of string           | N/A          | Zone is primitive. Represents the zones of    |
|                           |                          |              | teh ice where players will line up.: "of-     |
|                           |                          |              | fense" or "defense".                          |
| <route></route>           | Route of RouteDef * Dot- | N/A          | Route is a combing form. Represents a         |
|                           | Place                    |              | path or route of a player on the ice, defined |
|                           |                          |              | by a route definition and a dot placement.    |
| <routedef></routedef>     | RouteDef of StartRoute * | N/A          | routedef is a combining form. Represents      |
|                           | EndRoute                 |              | the definition of a route, consisting of a    |
|                           |                          |              | start point and an end point.                 |
| <dotplace></dotplace>     | DotPlace of Side * Zone  | N/A          | dotplace is combining form. Represents        |
|                           |                          |              | the placement of a dot along a route, de-     |
|                           |                          |              | fined by side and zone.                       |
| <startroute></startroute> | StartRoute of string     | N/A          | startroute is a primitive. Represents the     |
|                           |                          |              | possible starting points or areas of a route. |
| <endroute></endroute>     | EndRoute of string       | N/A          | endroute is a primitive. Represents the pos-  |
|                           |                          |              | sible ending points of a route.               |