

# *Exercises week 1*

Klaas Isaac Bijlsma  
s2394480

David Vroom  
s2309939

November 28, 2017

## **Exercise 1**

*Attain some familiarity with the way functions are selected from namespaces*

We used the following code,

main.cc

```
1 #include <iostream>
2
3 namespace First
4 {
5     enum Enum
6     {};
7
8     void fun(First::Enum symbol)
9     {
10         std::cout << "First::fun called\n";
11     }
12 }
13
14 namespace Second
15 {
16     void fun(First::Enum symbol)
17     {
18         std::cout << "Second::fun called\n";
19     }
20 }
```

```

21 |
22 | int main()
23 | {
24 |     First::Enum symbol;
25 |
26 |     fun(symbol);           // First::fun called
27 | }

```

**Call fun and explain why `First::fun` is called. How would you call `Second::fun` instead?**

Als een functie uit een namespace wordt aangeroepen zonder de namespace te specificeren, dan wordt de namespace van het argument van de functie gebruikt om de namespace van de functie te bepalen; het zogenaamde 'Koenig Lookup'. Aangezien het argument is gedeclareerd als type `First::Enum` wordt `First::fun` aangeroepen. Om `Second::fun` aan te roepen moet de namespace expliciet worden genoemd: `Second::fun(symbol)`.

**In the namespaces slides (#6) it is stated that operator<<'s use is simplified because of the Koenig lookup. Explain.**

Zonder Koenig lookup zal de korte versie `std::cout << "Hello"` (net als de lange versie `operator<<(std::cout, "Hello")`) niet gebruikt kunnen worden. De insertion operator functie uit de standard namespace is dan niet bereikbaar zonder expliciete functie call `std::operator<<(std::cout, "Hello")` voor zowel de korte als de lange versie.

**Now, just above main, declare a function `void fun(First::Enum symbol)`. Compile this program. What happens? Why?**

Er ontstaat een foutmelding vanwege ambiguïteit. De compiler weet nu niet of hij de functie uit de namespace `First` of de globale functie net boven main moet aanroepen.

## Exercise 2

*Learn why streams can be used to determine the truth values of conditions, but not to assign values to bool variables.*

Note: The code given in the exercise is incomplete, and therefore won't compile even without the intended mistake. So first of all we state the following code as a starting point:

header.ih

```
1 | #include <iostream>
2 | #include <string>
3 |
4 | using namespace std;
5 |
6 | bool promptGet(istream &in, string &str);
7 | void process(string const &str);
```

main.cc

```
1 | #include "header.ih"
2 |
3 | int main()
4 | {
5 |     string str;
6 |     while (promptGet(cin, str))
7 |         process(str);
8 | }
```

process.cc

```
1 | #include "header.ih"
2 |
3 | void process(string const &str)
4 | {
5 |     cout << "processed: " << str << '\n';
6 | }
```

promptget.cc

```
1 | #include "header.ih"
2 |
3 | bool promptGet(istream &in, string &str)
4 | {
5 |     cout << "Enter a line or ^D\n";      // ^D signals end-of-input
6 |
7 |     return getline(in, str);
8 | }
```

**1. Why doesn't this work? (Explain why the error message is generated by the compiler)**

This code doesn't work, because `getline(in, str)` cannot be returned as a `bool` in `promptGet`. This is because the class `istream` defines `explicit operator bool() const`. This allows the compiler to only perform a conversion to a `bool` when this is explicitly required (as in a `while` statement), but not implicitly (as in the `return` statement above).

**2. Change `promptGet`'s body so that the code does compile.**

By changing `promptGet`'s body in the following way, the code does compile:

promptget.cc

```
1 | #include "header.ih"
2 |
3 | bool promptGet(istream &in, string &str)
4 | {
5 |     cout << "Enter a line or ^D\n";      // ^D signals end-of-input
6 |
7 |     return static_cast<bool>(getline(in, str));
8 | }
```

**3. Without changing `promptGet`'s body, change `promptGet` so that the code does compile.**

By changing `promptGet` (and the declaration in the internal header) in the following way, the code does compile:

promptget.cc

```
1 | #include "header.ih"
2 |
```

```
3 | istream &promptGet(istream &in, string &str)
4 | {
5 |     cout << "Enter a line or ^D\n";      // ^D signals end-of-input
6 |
7 |     return getline(in, str);
8 | }
```

## Exercise 3

*Learn to implement index operators*

The Matrix class that is used here, is derived from the solutions of exercise 64. Extensions to the class header made in upcoming exercises are also shown here.

We used the following code,

```
matrix/matrix.h
1 #ifndef INCLUDED_MATRIX_
2 #define INCLUDED_MATRIX_
3
4 #include <iosfwd>
5 #include <initializer_list>
6
7 class Matrix
8 {
9     size_t d_nRows = 0;
10    size_t d_nCols = 0;
11    double *d_data = 0;           // in fact R x C matrix
12
13    // exercise 4
14    // =====
15    friend Matrix operator+(Matrix const &lhs, Matrix const &rhs); // 1
16    friend Matrix operator+(Matrix &&lhs, Matrix const &rhs);      // 2
17
18    // exercise 5
19    // =====
20    friend std::ostream &operator<<(
21        std::ostream &out, Matrix const &matrix);
22    friend std::istream &operator>>(
23        std::istream &in, Matrix const &matrix);
24
25    size_t d_idxColStart = 0;
26    size_t d_idxRowStart = 0;
27    size_t d_nColEnd = d_nCols;
28    size_t d_nRowEnd = d_nRows;
29    std::istream &(Matrix::*d_extractMode)(
30        std::istream &in, Matrix const &matrix) const = &Matrix::extractRows;
```

```

31
32     // exercise 7
33     // =====
34 friend bool operator==(Matrix const &lhs, Matrix const &rhs);
35 friend bool operator!=(Matrix const &lhs, Matrix const &rhs);
36
37 public:
38     typedef std::initializer_list<std::initializer_list<double>> IniList;
39
40     Matrix() = default;
41     Matrix(size_t nRows, size_t nCols);           // 1
42     Matrix(Matrix const &other);                   // 2
43     Matrix(Matrix &&tmp);                           // 3
44     explicit Matrix(IniList inilist);              // 4
45
46     ~Matrix();
47
48     Matrix &operator=(Matrix const &rhs);
49     Matrix &operator=(Matrix &&tmp);
50
51     size_t nRows() const;
52     size_t nCols() const;
53     size_t size() const;                          // nRows * nCols
54
55     static Matrix identity(size_t dim);
56
57     Matrix &tr();                                  // transpose (must be square)
58     Matrix transpose() const;                      // any dim.
59
60     void swap(Matrix &other);
61
62     // exercise 3
63     // =====
64     double *operator[](size_t index);
65     double const *operator[](size_t index) const;
66
67     // exercise 4
68     // =====
69     Matrix &operator+=(Matrix const &other) &;      // 1
70     Matrix operator+=(Matrix const &other) &&;      // 2
71

```

```

72         // exercise 5
73         // =====
74     enum Mode
75     {
76         BY_ROWS,
77         BY_COLS
78     };
79
80     Matrix &operator()(
81         size_t nRows, size_t nCols, Mode byCols = BY_ROWS); // 1
82     Matrix &operator()(
83         Mode byCols, size_t idxStart = 0, size_t nSubLines = 0); // 2
84     Matrix &operator()(
85         Mode byCols, size_t idxRowStart, size_t nSubRows,
86         size_t idxColStart, size_t nSubCols); // 3
87
88     private:
89         double &el(size_t row, size_t col) const;
90         void transpose(double *dest) const;
91
92         // exercise 3
93         // ===== // private backdoor
94         double *operatorIndex(size_t index) const;
95
96         // exercise 4
97         // =====
98         void add(Matrix const &rhs);
99
100        // exercise 5
101        // =====
102        std::istream &extractRows(
103            std::istream &in, Matrix const &matrix) const;
104        std::istream &extractCols(
105            std::istream &in, Matrix const &matrix) const;
106
107    };
108
109    inline size_t Matrix::nCols() const
110    {
111        return d_nCols;
112    }

```



```

113
114 inline size_t Matrix::nRows() const
115 {
116     return d_nRows;
117 }
118
119 inline size_t Matrix::size() const
120 {
121     return d_nRows * d_nCols;
122 }
123
124 inline double &Matrix::el(size_t row, size_t col) const
125 {
126     return d_data[row * d_nCols + col];
127 }
128
129     // exercise 3
130     // =====
131 inline double *Matrix::operatorIndex(size_t index) const
132 {
133     return d_data + index * d_nCols;
134 }
135
136 inline double *Matrix::operator[](size_t index)
137 {
138     return operatorIndex(index);
139 }
140
141 inline double const *Matrix::operator[](size_t index) const
142 {
143     return operatorIndex(index);
144 }
145
146 #endif

```

## Exercise 4

*Learn to implement and spot opportunities for overloaded operators*

The header is shown in exercise 3, the implementations of the added functions are shown below:

matrix/add.cc

```
1 | #include "matrix.ih"
2 |
3 | void Matrix::add(Matrix const &rhs)
4 | {
5 |     if (rhs.d_nCols != d_nCols or rhs.d_nRows != d_nRows)
6 |     {
7 |         cerr << "Warning: Matrices have differnt size, "
8 |              "so cannot be added!\n";
9 |         exit(1);
10 |    }
11 |
12 |    for (size_t idx = size(); idx--> 0; )
13 |        d_data[idx] += rhs.d_data[idx];
14 | }
```

matrix/operatoradd1.cc

```
1 | #include "matrix.ih"
2 |
3 | Matrix operator+(Matrix const &lhs, Matrix const &rhs)
4 | {
5 |     Matrix tmp{ lhs };
6 |     tmp.add(rhs);
7 |     return tmp;
8 | }
```

matrix/operatoradd2.cc

```
1 | #include "matrix.ih"
2 |
```

```

3 | Matrix operator+(Matrix &&lhs, Matrix const &rhs)
4 | {
5 |     lhs.add(rhs);
6 |     return move(lhs);
7 | }

```

matrix/operatorcompadd1.cc

```

1 | #include "matrix.ih"
2 |
3 | Matrix &Matrix::operator+=(Matrix const &other) &
4 | {
5 |     Matrix tmp{ *this };
6 |     tmp.add(other);
7 |     swap(tmp);
8 |     return *this;
9 | }

```

matrix/operatorcompadd2.cc

```

1 | #include "matrix.ih"
2 |
3 | Matrix Matrix::operator+=(Matrix const &other) &&
4 | {
5 |     add(other);
6 |     return move(*this);
7 | }

```

## Exercise 5

*Learn to insert/extract objects of your own class*

**Explain why implementing the extraction operator when using compilers that do *not* implement the c++-17 standard is more complex than implementing the extraction operators when using compilers that *do* implement the c++-17 standard**

We don't know the answer to this question, and also could not find it in the lecture, annotations and the internet.

Also, we are aware that simply calling `mat(2,5)` does invalidate `mat`'s data with our code. We thought of making a proxy class and use a conversion operator to solve this, but we couldn't make it work. We would like some advice on this. However, the overloaded extraction and insertion operator of the `Matrix` object work properly.

The header is shown in exercise 3, the implementations of the added functions are shown below.

matrix/extractcols.cc

```
1 | #include "matrix.ih"
2 |
3 | std::istream &Matrix::extractCols(
4 |     std::istream &in, Matrix const &matrix) const
5 | {
6 |     for (size_t colIdx = matrix.d_idxColStart;
7 |         colIdx != matrix.d_nColEnd;
8 |         ++colIdx)
9 |         for (size_t rowIdx = matrix.d_idxRowStart;
10 |            rowIdx != matrix.d_nRowEnd;
11 |            ++rowIdx)
12 |             in >> matrix.el(rowIdx, colIdx);
13 |     return in;
14 | }
```

matrix/extractrows.cc

```
1 | #include "matrix.ih"
2 |
```

```

3 | std::istream &Matrix::extractRows(
4 |     std::istream &in, Matrix const &matrix) const
5 | {
6 |     for (size_t rowIdx = matrix.d_idxRowStart;
7 |         rowIdx != matrix.d_nRowEnd;
8 |         ++rowIdx)
9 |         for (size_t colIdx = matrix.d_idxColStart;
10 |            colIdx != matrix.d_nColEnd;
11 |            ++colIdx)
12 |             in >> matrix.el(rowIdx, colIdx);
13 |     return in;
14 | }

```

#### matrix/functor1.cc

```

1 | #include "matrix.ih"
2 |
3 | Matrix &Matrix::operator()(size_t nRows, size_t nCols, Mode byCols)
4 | {
5 |     Matrix tmp{ nRows, nCols };
6 |     swap(tmp);
7 |     if (byCols)
8 |         d_extractMode = &Matrix::extractCols;
9 |     return *this;
10 | }

```

#### matrix/functor2.cc

```

1 | #include "matrix.ih"
2 |
3 | Matrix &Matrix::operator()(Mode byCols, size_t idxStart, size_t nSubLines)
4 | {
5 |     if (byCols)
6 |     {
7 |         d_extractMode = &Matrix::extractCols;
8 |
9 |         if (idxStart >= d_nCols)
10 |         { // if requested submatrix lies outside matrix, do nothing
11 |             d_idxColStart = d_nColEnd;

```

```

12         return *this;
13     }
14     d_idxColStart = idxStart;
15         // if number of sublines is not default and
16         // submatrix lies within matrix, then set end of submatrix
17     if (nSubLines == true and d_idxColStart + nSubLines < d_nCols)
18         d_nColEnd = d_idxColStart + nSubLines;
19 }
20 else        // extract by rows
21 {
22     if (idxStart >= d_nRows)
23     {        // if requested submatrix lies outside matrix, do nothing
24         d_idxRowStart = d_nRowEnd;
25         return *this;
26     }
27     d_idxRowStart = idxStart;
28         // if number of sublines is not default and
29         // submatrix lies within matrix, then set end of submatrix
30     if (nSubLines == true and d_idxRowStart + nSubLines < d_nRows)
31         d_nRowEnd = d_idxRowStart + nSubLines;
32 }
33
34     return *this;
35 }

```

#### matrix/functor3.cc

```

1  #include "matrix.ih"
2
3  Matrix &Matrix::operator()(Mode byCols,
4      size_t idxRowStart, size_t nSubRows, size_t idxColStart, size_t nSubCols)
5  {
6      if (idxRowStart >= d_nRows or idxColStart >= d_nCols)
7      {        // if submatrix lies outside matrix then do nothing
8          d_idxRowStart = d_nRowEnd;
9          d_idxColStart = d_nColEnd;
10         return *this;
11     }
12
13     d_idxRowStart = idxRowStart; // set start values submatrix

```

```

14     d_idxColStart = idxColStart;
15
16     if (byCols)
17         d_extractMode = &Matrix::extractCols;
18
19     // if within matrix set end values of submatrix
20     if (d_idxRowStart + nSubRows < d_nRows)
21         d_nRowEnd = d_idxRowStart + nSubRows;
22
23     if (d_idxColStart + nSubCols < d_nCols)
24         d_nColEnd = d_idxColStart + nSubCols;
25
26     return *this;
27 }

```

#### matrix/operatorextract.cc

```

1 #include "matrix.ih"
2
3 istream &operator>>(istream &in, Matrix const &matrix)
4 {
5     return static_cast<istream &>(
6         (matrix.*matrix.d_extractMode)(in, matrix));
7 }

```

#### matrix/operatorinsert.cc

```

1 #include "matrix.ih"
2
3 ostream &operator<<(ostream &out, Matrix const &matrix)
4 {
5     for (size_t rowIdx = 0; rowIdx != matrix.d_nRows; ++rowIdx)
6     {
7         for (size_t colIdx = 0; colIdx != matrix.d_nCols; ++colIdx)
8             out << matrix.el(rowIdx, colIdx) << " ";
9         out << '\n'; // add newline after each row
10    }
11    return out;
12 }

```

## Exercise 7

*Learn to implement and spot opportunities for overloaded operators*

### 1.

The following two overloaded operators are added to compare two `Matrix` objects for (in)equality:

matrix/operatorequalto.cc

```
1 #include "matrix.ih"
2
3 bool operator==(Matrix const &lhs, Matrix const &rhs)
4 {
5     if (lhs.d_nCols != rhs.d_nCols or lhs.d_nRows != rhs.d_nRows)
6         return false;
7
8     for (size_t idx = lhs.size(); idx--;)
9     {
10         if (lhs.d_data[idx] != rhs.d_data[idx])
11             return false;
12     }
13     return true;
14 }
```

matrix/operatornotequalto.cc

```
1 #include "matrix.ih"
2
3 bool operator!=(Matrix const &lhs, Matrix const &rhs)
4 {
5     if (!(lhs == rhs))
6         return true;
7
8     return false;
9 }
```



## 2.

We modified the following code of the `Strings` class to facilitate comparing for (in)equality,

strings/strings.h

```
1  #ifndef EX62_STRINGS_
2  #define EX62_STRINGS_
3
4  #include <iosfwd>
5
6  class Strings
7  {
8      friend bool operator==(Strings const &lhs, Strings const &rhs);
9      friend bool operator!=(Strings const &lhs, Strings const &rhs);
10
11      size_t d_size = 0;
12      size_t d_capacity = 1;
13      std::string **d_str;
14
15      public:
16          Strings();
17          Strings(int argc, char **argv);
18          Strings(char **environLike);
19          Strings(Strings const &outerStrings);    // copy constructor
20          Strings(Strings &&tmp);                  // move constructor
21
22          ~Strings();
23
24          // copy assignment operator
25          Strings &operator=(Strings const &outerStrings);
26          // move assignment operator
27          Strings &operator=(Strings &&tmp);
28
29          void swap(Strings &other);
30
31          size_t size() const;
32          size_t capacity() const;
33          std::string const &at(size_t idx) const;
34          std::string &at(size_t idx);
35
36          void add(std::string const &next);
```

```

36
37     void resize(size_t newSize);
38     void reserve(size_t newCapacity);
39
40     private:
41         std::string &safeAt(size_t idx) const; // private backdoor
42         std::string **storageArea();
43         void destroy();
44         std::string **enlarged();
45         std::string **rawPointers(size_t nPointers);
46 };
47
48 inline size_t Strings::size() const
49 {
50     return d_size;
51 }
52
53 inline size_t Strings::capacity() const
54 {
55     return d_capacity;
56 }
57
58 inline std::string const &Strings::at(size_t idx) const
59 {
60     return safeAt(idx);
61 }
62
63 inline std::string &Strings::at(size_t idx)
64 {
65     return safeAt(idx);
66 }
67
68 #endif

```

#### strings/operatorequalto.cc

```

1 #include "strings.ih"
2
3 bool operator==(Strings const &lhs, Strings const &rhs)
4 {

```

```

5 |     if (lhs.d_size != rhs.d_size) // check size of array of Strings
6 |         return false;
7 |
8 |     for (size_t idx = 0; idx != lhs.d_size; ++idx)
9 |     {                                     // compare string objects
10 |         if (*lhs.d_str[idx] != *rhs.d_str[idx])
11 |             return false;
12 |     }
13 |     return true;
14 | }

```

strings/operatornotequalto.cc

```

1 | #include "strings.ih"
2 |
3 | bool operator!=(Strings const &lhs, Strings const &rhs)
4 | {
5 |     if (!(lhs == rhs))
6 |         return true;
7 |
8 |     return false;
9 | }

```