

Exercises week 3

Klaas Isaac Bijlsma
s2394480

David Vroom
s2309939

December 7, 2017

Exercise 20

Learn the implications of using friends

The exercise states that the classes `Addition` and `Subtraction`, which implement the binary addition and subtraction operators, are base classes of a class `Binops`. Furthermore, a class `Operations` implements the private functions `add` and `sub`, and inherits from `Binops`. Also, `Operations` declares `Binops` a friend class.

- An operator like `Addition::operator+=` has to call the private `add` member of `Operations`, but `Operations` does not declare `Addition` as a friend class.
We solved this problem by defining a wrapper function `binopsAdd` in `Binops`, which calls `add`. This is allowed, since `Binops` is a friend class of `Operations`. Then, `Addition` is declared a friend class of `Binops`, which is therefore allowed to call `binopsAdd`, and by that it calls `add`. Ommiting the wrapper function does not work, since `Addition`, a friend class of a friend class of `Operations`, can not call `add`. The problem is handled in a similar way for `Subtraction`.
- There is however a fundamental problem with this design. By defining the class hierarchy as stated in the exercise, multiple friendships among classes have to be defined. In this way, a strong coupling between the classes is obtained, which is undesirable.
- Below we provide the class interfaces of `Binops`, `Addition` and `Subtraction`.

`binops/binops.h`

```
1 | #ifndef EX20_BINOPS_H
```

```

2  #define EX20_BINOPS_H
3
4  #include "../addition/addition.h"
5  #include "../subtraction/subtraction.h"
6
7  class Binops: public Addition, public Subtraction
8  {
9      friend class Addition;
10     friend class Subtraction;
11
12     private:
13         void binopsAdd(Operations const &rhs);
14         void binopsSub(Operations const &rhs);
15 };
16
17 #endif

```

addition/addition.h

```

1  #ifndef EX20_ADDITION_H
2  #define EX20_ADDITION_H
3
4  class Operations;
5
6  class Addition
7  {
8      friend Operations operator+(
9          Operations const &lhs, Operations const &rhs);    // 1
10     friend Operations operator+(
11         Operations &&lhs, Operations const &rhs);           // 2
12
13     public:
14         Operations &operator+=(Operations const &rhs) &;    // 1
15         Operations operator+=(Operations const &rhs) &&;    // 2
16 };
17
18 #endif

```

subtraction/subtraction.h

```
1  #ifndef EX20_SUBTRACTION_H
2  #define EX20_SUBTRACTION_H
3
4  class Operations;
5
6  class Subtraction
7  {
8      friend Operations operator-(
9          Operations const &lhs, Operations const &rhs);    // 1
10     friend Operations operator-(
11         Operations &&lhs, Operations const &rhs);          // 2
12
13     public:
14         Operations &operator--(Operations const &rhs) &; // 1
15         Operations operator--(Operations const &rhs) &&; // 2
16 };
17
18 #endif
```

Exercise 21

Learn to implement a class hierarchy using friends in the final derived class

Below we provide the implementations of the classes `Binops`, `Addition` and `Subtraction`. (Not the free binary operators, see the next exercise for those.)

binops/binops.ih

```
1 | #include "binops.h"
2 | #include "../operations/operations.h"
```

binops/binopsadd.cc

```
1 | #include "binops.ih"
2 |
3 | void Binops::binopsAdd(Operations const &rhs)
4 | {
5 |     static_cast<Operations &>(*this).add(rhs);
6 | }
```

binops/binopssub.cc

```
1 | #include "binops.ih"
2 |
3 | void Binops::binopsSub(Operations const &rhs)
4 | {
5 |     static_cast<Operations &>(*this).sub(rhs);
6 | }
```

addition/addition.ih

```
1 | #include "addition.h"
2 | #include "../operations/operations.h"
3 |
4 | #include <utility>
5 |
6 | using namespace std;
```

addition/operatoraddis1.cc

```
1 #include "addition.ih"
2
3 Operations &Addition::operator+=(Operations const &rhs) &
4 {
5     cout << "operatoraddis1 calls: ";
6     static_cast<Binops &>(*this).binopsAdd(rhs);
7     return static_cast<Operations &>(*this);
8 }
```

addition/operatoraddis2.cc

```
1 #include "addition.ih"
2
3 Operations Addition::operator+=(Operations const &rhs) &&
4 {
5     cout << "operatoraddis2 calls: ";
6     static_cast<Binops &>(*this).binopsAdd(rhs);
7     return move(static_cast<Operations &>(*this));
8 }
```

subtraction/subtraction.ih

```
1 #include "subtraction.h"
2 #include "../operations/operations.h"
3
4 #include <utility>
5
6 using namespace std;
```

subtraction/operatorsubis1.cc

```
1 #include "subtraction.ih"
2
3 Operations &Subtraction::operator-=(Operations const &rhs) &
4 {
5     cout << "operatorsubis1 calls: ";
6     static_cast<Binops &>(*this).binopsSub(rhs);
7 }
```

```
7 |     return static_cast<Operations &>(*this);
8 | }
```

subtraction/operatorsubis2.cc

```
1 | #include "subtraction.ih"
2 |
3 | Operations Subtraction::operator-=(Operations const &rhs) &&
4 | {
5 |     cout << "operatorsubis2 calls: ";
6 |     static_cast<Binops &>(*this).binopsSub(rhs);
7 |     return move(static_cast<Operations &>(*this));
8 | }
```

Exercise 22

Learn to use a class hierarchy using friends in the final derived class

Below we provide the remaining members of the classes `Binops`, `Addition` and `Subtraction`. The members `add` and `sub` are implemented inline, and therefore we provide the interface of `Operations` as well. After those listings, we provide a main function calling the different binary operators, and the output it produces. From that we see that the code works as intended.

addition/operatoradd1.cc

```
1 | #include "addition.ih"
2 |
3 | Operations operator+(Operations const &lhs, Operations const &rhs)
4 | {
5 |     cout << "operatoradd1 calls: ";
6 |     return Operations{ lhs } += rhs;
7 | }
```

addition/operatoradd2.cc

```
1 | #include "addition.ih"
2 |
3 | Operations operator+(Operations &&lhs, Operations const &rhs)
4 | {
5 |     cout << "operatoradd2 calls: ";
6 |     Operations ret(move(lhs));
7 |     ret += rhs;
8 |     return ret;
9 | }
```

subtraction/operatorsub1.cc

```
1 | #include "subtraction.ih"
2 |
3 | Operations operator-(Operations const &lhs, Operations const &rhs)
4 | {
5 |     cout << "operatorsub1 calls: ";
```

```

6 |     return  Operations{ lhs } -= rhs;
7 | }

```

subtraction/operatorsub2.cc

```

1 | #include "subtraction.ih"
2 |
3 | Operations operator-(Operations &&lhs, Operations const &rhs)
4 | {
5 |     cout << "operatorsub2 calls: ";
6 |     Operations ret(move(lhs));
7 |     ret -= rhs;
8 |     return ret;
9 | }

```

operations/operations.h

```

1 | #ifndef EX20_OPERATIONS_H
2 | #define EX20_OPERATIONS_H
3 |
4 | #include <iostream>
5 | #include "../binops/binops.h"
6 |
7 | class Operations: public Binops
8 | {
9 |     friend Binops;
10 |
11 |     public:
12 |         Operations() = default;
13 |
14 |     private:
15 |         void add(Operations const &rhs);
16 |         void sub(Operations const &rhs);
17 | };
18 |
19 | inline void Operations::add(Operations const &rhs)
20 | {
21 |     std::cout << "addition\n";
22 | }

```



```

23 |
24 | inline void Operations::sub(Operations const &rhs)
25 | {
26 |     std::cout << "subtraction\n";
27 | }
28 |
29 | #endif

```

main.cc

```

1 | #include "operations/operations.h"
2 |
3 | int main()
4 | {
5 |     Operations obj;
6 |
7 |     obj += obj;
8 |     Operations{} += obj;
9 |     Operations obj2 = obj + obj;
10 |    obj2 = Operations{} + obj;
11 |
12 |    obj -= obj;
13 |    Operations{} -= obj;
14 |    Operations obj3 = obj - obj2;
15 |    obj3 = Operations{} - obj;
16 | }

```

Output of main.cc

```

operatoraddis1 calls: addition
operatoraddis2 calls: addition
operatoradd1 calls: operatoraddis1 calls: addition
operatoradd2 calls: operatoraddis1 calls: addition
operatorsubis1 calls: subtraction
operatorsubis2 calls: subtraction
operatorsub1 calls: operatorsubis1 calls: subtraction
operatorsub2 calls: operatorsubis1 calls: subtraction

```

Exercise 23

Learn to use a class hierarchy using friends in the final derived class

We made a basic calculator with the code of the previous exercises, with some modifications in the `cout` statements. Also, we added a data member, constructor and an accessor to the class `Operations`, to store and access values. To make sure that all different operators are called by the calculator, the implementation of `operatoradd1` and `operatorsub1` were slightly changed. The modified code is given below. Moreover, you find a simple main function which acts as an interactive basic calculator. Its output shows that all operators are called and work as intended.

Briefly describe the steps that must be performed to add another operator (like multiplication) to the calculator (i.e., to the class `Operations`).

In line with the exercise, one has to define a new base class `Multiplication`, and let `Binops` (publicly) inherit from this class. In `Operations`, a private member function `void mul(Operations const &rhs)` should be added that does the multiplication. Then in `Binops`, a wrapper function should be defined that calls `mul`. Also, it should define `Multiplication` a friend class. Then, the multiplication operators in `Multiplication` can call this wrapper function.

In our opinion, a much simpler solution is to define an overloaded multiplication operator and compound assignment operator in the class `Operations`.

addition/operatoradd1.cc

```
1 | #include "addition.ih"
2 |
3 | Operations operator+(Operations const &lhs, Operations const &rhs)
4 | {
5 |     cout << "operatoradd1 called\n";
6 |     return Operations{ lhs } += rhs;
7 | }
```

subtraction/operatorsub1.cc

```
1 | #include "subtraction.ih"
2 |
3 | Operations operator-(Operations const &lhs, Operations const &rhs)
4 | {
```

```

5 |     cout << "operatorsub1 called\n";
6 |     return Operations{ lhs } -= rhs;
7 | }

```

operations/operations.h

```

1 | #ifndef EX23_OPERATIONS_H
2 | #define EX23_OPERATIONS_H
3 |
4 | #include <iostream>
5 | #include "../binops/binops.h"
6 |
7 | class Operations: public Binops
8 | {
9 |     friend Binops;
10 |
11 |     double d_data = 0;
12 |
13 |     public:
14 |         Operations() = default;
15 |         explicit Operations(double initial);
16 |
17 |         double value() const;
18 |
19 |     private:
20 |         void add(Operations const &rhs);
21 |         void sub(Operations const &rhs);
22 | };
23 |
24 | inline void Operations::add(Operations const &rhs)
25 | {
26 |     d_data += rhs.d_data;
27 | }
28 |
29 | inline void Operations::sub(Operations const &rhs)
30 | {
31 |     d_data -= rhs.d_data;
32 | }
33 |
34 | inline double Operations::value() const

```

```

35 | {
36 |     return d_data;
37 | }
38 |
39 | #endif

```

operations/operations.ih

```

1 | #include "operations.h"

```

operations/operations.cc

```

1 | #include "operations.ih"
2 |
3 | Operations::Operations(double initial)
4 | :
5 |     d_data(initial)
6 | {}

```

main.cc

```

1 | #include "operations/operations.h"
2 |
3 | using namespace std;
4 |
5 | int main()
6 | {
7 |     double val1;
8 |     double val2;
9 |     double val3;
10 |
11 |     char op1;
12 |     char op2;
13 |
14 |     Operations result;
15 |
16 |     cout << "Please give something in the form: val1 +or- val2 +or- val3\n";
17 |

```

```

18     while (cin >> val1 >> op1 >> val2 >> op2 >> val3)
19     {
20         Operations obj1{val1};
21         Operations obj2{val2};
22         Operations obj3{val3};
23
24         if (op1 == '+' and op2 == '+')
25             result = obj1 + obj2 + obj3;
26
27         if (op1 == '-' and op2 == '-')
28             result = obj1 - obj2 - obj3;
29
30         if (op1 == '+' and op2 == '-')
31             result = obj1 + obj2 - obj3;
32
33         if (op1 == '-' and op2 == '+')
34             result = obj1 - obj2 + obj3;
35
36         cout << "\nResult: " << result.value() << '\n';
37         cout << "\nPlease give something in the form: "
38             << "val1 +or- val2 +or- val3\n";
39     }
40 }

```

Output of main.cc

```

Please give something in the form: val1 +or- val2 +or- val3
1+2+3
operatoradd1 called
operatoraddis2 called
operatoradd2 called
operatoraddis1 called

Result: 6

Please give something in the form: val1 +or- val2 +or- val3
1-2-3
operatorsub1 called
operatorsubis2 called
operatorsub2 called

```

operatorsubis1 called

Result: -4

Please give something in the form: val1 +or- val2 +or- val3

Exercise 24

Learn to initialize `string` objects with `new`

We used the following code,

main.ih

```
1 #include <string>
2 #include <iostream>
3
4 using namespace std;
5
6 string *factory(string const &str, size_t count);
```

main.cc

```
1 #include "main.ih"
2
3 int main()
4 {
5     string str = "test";
6     size_t count = 3;
7     string *sp = factory(str, count);
8     for (size_t idx = 0; idx != count; ++idx)
9         cout << sp[idx] << '\n';
10 }
```

factory.cc

```
1 #include "main.ih"
2
3 string *factory(string const &str, size_t count)
4 {
5     static string inputStr = str;          // made static s.t. Xstr has access
6
7     class Xstr: public string
8     {
9
```

```
10         public:
11             Xstr()
12             :
13                 string(inputStr)
14             {}
15     };
16
17     return new Xstr[count];
18 }
```