



KubeCon



CloudNativeCon

Europe 2020

Virtual

Managing Multi-Cluster/Multi-Tenant Kubernetes with GitOps

Chris Carty, CKA/CKAD



KubeCon



CloudNativeCon

Europe 2020

Virtual



GitOps Intro



KubeCon



CloudNativeCon

Europe 2020

Virtual

GitOps Intro





KubeCon



CloudNativeCon

Europe 2020

Virtual



GitOps Intro



GitOps Intro

AUTOMATE



GitOps Intro




Kelsey Hightower ✓

@kelseyhightower

GitOps is the best thing since configuration as code. Git changed how we collaborate, but declarative configuration is the key to dealing with infrastructure at scale, and sets the stage for the next generation of management tools.

11:07 AM · Aug 21, 2019 · [Twitter Web App](#)

GitOps Intro





flux




argo

CNCF GitOps Operator Projects

GitOps Intro

#GitOps



Project Structure



KubeCon




CloudNativeCon

Europe 2020

Virtual

Project Structure




App Developer



App Operator


Project Structure



The screenshot shows a VS Code editor with a dark theme. On the left, the Explorer sidebar shows a project structure with a folder named 'webapp' containing four files: 'deployment.yaml', 'ingress.yaml', 'namespace.yaml', and 'service.yaml'. The 'deployment.yaml' file is selected and open in the main editor. The editor shows the content of 'deployment.yaml' with line numbers 1 through 29. The code is a Kubernetes Deployment manifest for a 'hello-kubernetes' app in the 'webapp' namespace. It includes a selector, a template with metadata, and a spec with a container, ports, and resource requests/limits.

```
! deployment.yaml ×
webapp > ! deployment.yaml > apiVersion
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    name: hello-kubernetes
5    namespace: webapp
6    labels:
7      app: hello-kubernetes
8  spec:
9    selector:
10     matchLabels:
11       app: hello-kubernetes
12    template:
13     metadata:
14       labels:
15         app: hello-kubernetes
16     spec:
17       containers:
18       - name: hello-kubernetes
19         image: macintoshprime/hello-kubernetes:v8
20         ports:
21         - containerPort: 80
22       resources:
23         requests:
24           memory: "64Mi"
25           cpu: "100m"
26         limits:
27           memory: "250Mi"
28           cpu: "300m"
29
```

Project Structure




Project Structure



Open Policy Agent

Conftest

Kubeval



Project Structure



Validate

YAML

- Kubeval

Security Policy

- conftest

Test

Unit Tests

- Deploy to Kind
- Run Tests

Release

- Manual Approval

Project Structure



Single Repo



Multi-Repo

Single Repository



KubeCon





CloudNativeCon


Europe 2020

Virtual

Single Repository



Single Repository





KubeCon




CloudNativeCon

Europe 2020

Virtual


Multi-Repo Structure

Multi-Repo Structure



Branch/tag = Grouping/Environment/Region

Multi-Tenant Structure



Multi-Tenant Structure

```

└─ multi-tenant
  └─ .github
  └─ base
  └─ cluster
    └─ demo-team
      └─ ! flux-patch.yaml
      └─ ! kubeconfig.yaml
      └─ ! kustomization.yaml
      └─ ! namespace.yaml
      └─ ! psp.yaml
      └─ ! rbac.yaml
    └─ helmrelease
    └─ networking
    └─ security
      └─ ! flux-patch.yaml
      └─ ! kubeconfig.yaml
      └─ ! kustomization.yaml
      └─ ! namespace.yaml
      └─ ! psp.yaml
      └─ ! rbac.yaml
    └─ team1
      └─ ! kustomization.yaml
    └─ install
    └─ scripts
```

- Leverages kustomize
- Permissions access repo (Read or Write)
- Base contains main Flux deployment configs
- Each team has its own agent

Multi-Tenant Structure

```
! flux-patch.yaml ×
kubecon-eu-demo > multi-tenant > cluster > gatekeeper > ! flux-patch.yaml > kind
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    name: flux
5  spec:
6    template:
7      spec:
8        containers:
9          - name: flux
10            args:
11              - --manifest-generation=true
12              - --memcached-hostname=flux-memcached.flux-system
13              - --memcached-service=
14              - --git-poll-interval=2m
15              - --sync-interval=5m
16              - --ssh-keygen-dir=/var/fluxd/keygen
17              - --k8s-allow-namespace=gatekeeper-system
18              - --git-url=git@github.com:cartyc/kubecon-gatekeeper.git
19              - --git-branch=main
20  ---
21  apiVersion: rbac.authorization.k8s.io/v1beta1
22  kind: RoleBinding
23  metadata:
24    name: flux
25  subjects:
26    - kind: ServiceAccount
27      name: flux
28      namespace: gatekeeper-system
29
```

Demo



KubeCon



CloudNativeCon

Europe 2020

Virtual

Contact

- @macintoshprime (Twitter, Kubernetes Slack)

Resources

- Gitops.tech
- itnext.io/how-we-do-gitops-mettle-4cc771a6c029
- argoproj.github.io
- fluxcd.io



KubeCon



CloudNativeCon

Europe 2020



Virtual



KEEP CLOUD NATIVE

CONNECTED

