

PKI the Wrong Way

Simple TLS Mistakes and Surprising Consequences

Tabitha Sable, Datadog



PKI the Wrong Way

Simple TLS Mistakes and Surprising Consequences

Tabitha Sable, Datadog



@tabbysable


Hacker Agenda

- Kubernetes TLS Review
- Certifying Authority Capers
- Shared PKI Shenanigans
- Requestheader Auth Rowdiness
- PKI Chain Perpetrations

Kubernetes TLS Review

TMA

- TLS
- mTLS
- CA
- PKI



Kubernetes TLS Review

- etcd
 - Mutual TLS authentication of clients
 - Mutual TLS authentication of peers

Kubernetes TLS Review

- kube-apiserver
 - Mutual TLS authentication of clients
 - Mutual TLS authentication to etcd
 - Mutual TLS authentication to kubelet

Kubernetes TLS Review

- apiserver front-proxy / aggregation layer
 - requestheader-* arguments
 - Mutual TLS authentication of front-proxy
 - Mutual TLS authentication to extension apiservers

Kubernetes TLS Review


- kubelet and others
 - Mutual TLS authentication of clients
 - Mutual TLS authentication to apiserver

Kubernetes TLS Review

- Your Applications
 - TLS servers
 - mTLS servers
 - mTLS clients

Certifying Authority Capers

- CA signing controls Kubernetes RBAC




Mitigations

- Treat CA permissions with care
- Use least-privilege

Shared PKI Shenanigans

- etcd sharing Kubernetes PKI
 - mTLS for clients
 - Every cert has full access



Mitigations

- Separate PKI for etcd and k8s
- Network policy
- etcd authorization

Requestheader Auth Rowdiness

Requestheader Auth Rowdiness




Requestheader Auth Rowdiness



Requestheader Auth Rowdiness


- Aggregation layer sharing main PKI
 - Enabled by `--requestheader-*`
 - Forgotten `--requestheader-allowed-names`



Mitigations


- Use a separate PKI with strict access control
- Pass all requestheader-* arguments
- Pass no requestheader-* arguments
 - Extension apiservers won't autoconfigure

PKI Chain Perpetrations




PKI Chain Perpetrations

- mTLS trusted root CA
- Cross-cluster access




PKI Chain Perpetrations

- mTLS trusted root CA
- Application certificate Kubernetes access



PKI Chain Perpetrations

- mTLS trusted root CA
- Application certificate etcd access




Mitigations

- Use standalone CAs

Mitigations

- Use standalone CAs
- mTLS trust only the leaf cert



Mitigations

- Use standalone CAs
- mTLS trust only the leaf cert
- Tight CA permissions
- Set "client auth" and "server auth" cert flags
- etcd authentication

Wrapup

- PKI is complex
 - Details matter
- Be creative
 - These hacks are just examples

Take-Home

- Use 3 separate CAs per cluster
- Use standalone CAs
- Carefully understand all options

Thank You

- We're Hiring!
 - www.datadoghq.com/careers/
- I'm online
 - tsable@datadog.com
 - Kubernetes Slack
 - Twitter
- Play along
 - <https://github.com/tabbysable/pki-the-wrong-way>

