

Rhythm Master

Generated by Doxygen 1.8.17

1 Hierarchical Index	1
1.1 Class Hierarchy	1
2 Class Index	3
2.1 Class List	3
3 Class Documentation	5
3.1 ButtonController Class Reference	5
3.2 ChangeScene Class Reference	5
3.2.1 Member Function Documentation	5
3.2.1.1 BtnChangeScene()	5
3.3 CollisionDetector Class Reference	6
3.4 CompleteScreen Class Reference	6
3.4.1 Member Function Documentation	7
3.4.1.1 DisplayCompleteScreen()	7
3.5 DetectKey Class Reference	7
3.6 EffectManager Class Reference	8
3.7 Effects Class Reference	8
3.8 FileIO Class Reference	9
3.8.1 Member Function Documentation	9
3.8.1.1 AddEntryToLeaderboard()	9
3.8.1.2 GetLeaderboardList()	9
3.8.1.3 ReadFile()	10
3.9 GameManager Class Reference	10
3.9.1 Member Function Documentation	12
3.9.1.1 SetMultiplier()	12
3.9.1.2 SetScore()	12
3.10 LeaderboardEntry Class Reference	12
3.11 LoadSettings Class Reference	13
3.12 MainMenu Class Reference	13
3.13 MMSettings Class Reference	13
3.14 NoteObject Class Reference	14
3.15 NoteScroller Class Reference	14
3.16 NoteSpawner Class Reference	14
3.17 PauseMenu Class Reference	15
3.18 PopulateLeaderboard Class Reference	16
3.19 QuitGame Class Reference	16
3.20 ScoreCalculator Class Reference	17
3.20.1 Member Function Documentation	17
3.20.1.1 AccuracyCalculation()	17
3.20.1.2 GoodHit()	18
3.20.1.3 LongHit()	18
3.20.1.4 NormalHit()	19

3.20.1.5 NoteMissed()	19
3.20.1.6 PerfectHit()	19
3.21 SettingsMenu Class Reference	20
Index	21

Chapter 1

Hierarchical Index

1.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

LeaderboardEntry	12
MonoBehaviour	
ButtonController	5
ChangeScene	5
CollisionDetector	6
CompleteScreen	6
DetectKey	7
EffectManager	8
Effects	8
FileIO	9
GameManager	10
LoadSettings	13
MainMenu	13
MMSettings	13
NoteObject	14
NoteScroller	14
NoteSpawner	14
PauseMenu	15
PopulateLeaderboard	16
QuitGame	16
ScoreCalculator	17
SettingsMenu	20

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

ButtonController	5
ChangeScene	5
CollisionDetector	6
CompleteScreen	6
DetectKey	7
EffectManager	8
Effects	8
FileIO	9
GameManager	10
LeaderboardEntry	12
LoadSettings	13
MainMenu	13
MMSettings	13
NoteObject	14
NoteScroller	14
NoteSpawner	14
PauseMenu	15
PopulateLeaderboard	16
QuitGame	16
ScoreCalculator	17
SettingsMenu	20

Chapter 3

Class Documentation

3.1 ButtonController Class Reference

Inheritance diagram for ButtonController:

3.2 ChangeScene Class Reference

Inheritance diagram for ChangeScene:

Collaboration diagram for ChangeScene:

Public Member Functions

- void [BtnChangeScene](#) (string scene_name)
Changes the scene being displayed.

3.2.1 Member Function Documentation

3.2.1.1 BtnChangeScene()

```
void ChangeScene.BtnChangeScene (  
    string scene_name ) [inline]
```

Changes the scene being displayed.

Parameters

<i>scene_name</i>	The name of the scene to display.
-------------------	-----------------------------------

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/ChangeScene.cs

3.3 CollisionDetector Class Reference

Inheritance diagram for CollisionDetector:

Collaboration diagram for CollisionDetector:

Public Member Functions

- void [NoteHit](#) ()
Called when a note is hit. Calculates the accuracy of the hit. @detail Finds the distance from the note's centre and the key's centre at the time of hit.
- void [NoteMissed](#) ()
Called when a note is not hit.
- void [LongNoteHit](#) ()
Called when a long note is completed.
- void [LongNoteClicked](#) ()
Called when a long note is hit.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/CollisionDetector.cs

3.4 CompleteScreen Class Reference

Inheritance diagram for CompleteScreen:

Collaboration diagram for CompleteScreen:

Public Member Functions

- void [DisplayCompleteScreen](#) (float normalCount, float goodCount, float perfectCount, float missedCount, float accuracy, float finalScore)
Display the completion screen to the main display.
- void [SaveFinalScore](#) ()
Saves the player's submitted score to the high score database.

Public Attributes

- GameObject [completeScreen](#)
The screen to be displayed.
- TextMeshProUGUI [normalHitText](#)
- GameObject [submitButton](#)
The button to submit player score.

Static Public Attributes

- static [CompleteScreen](#) instance
The one instance of [CompleteScreen](#), to be referenced externally.

3.4.1 Member Function Documentation

3.4.1.1 DisplayCompleteScreen()

```
void CompleteScreen.DisplayCompleteScreen (
    float normalCount,
    float goodCount,
    float perfectCount,
    float missedCount,
    float accuracy,
    float finalScore ) [inline]
```

Display the completion screen to the main display.

Parameters

<i>normalCount</i>	The number of normal hits.
<i>goodCount</i>	The number of good hits.
<i>perfectCount</i>	The number of perfect hits.
<i>missedCount</i>	The number of missed hits.
<i>accuracy</i>	The player's hit accuracy, in percent.
<i>finalScore</i>	The final score.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/CompleteScreen.cs

3.5 DetectKey Class Reference

Inheritance diagram for DetectKey:

Collaboration diagram for DetectKey:

Public Attributes

- string `keyPressed`
The key the player selected.
- GameObject `key`
The object related to the key.
- string `keyColour`
The colour of the key the player selected.
- Text `settingsButtonText`
The text reflecting the key the player chose.
- GameObject `ui`
The prompt for a key displayed to the user.

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/DetectKey.cs`

3.6 EffectManager Class Reference

Inheritance diagram for EffectManager:

Collaboration diagram for EffectManager:

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/EffectManager.cs`

3.7 Effects Class Reference

Inheritance diagram for Effects:

Collaboration diagram for Effects:

Public Attributes

- float `lifetime` = 1f
Time before effect is despawned, in seconds.

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/Effects.cs`

3.8 FileIO Class Reference

Inheritance diagram for FileIO:

Collaboration diagram for FileIO:

Public Member Functions

- `string[] ReadFile` (string pathName, char separator)

Reads and returns the contents of the specified text file, splitting by the specified delimiter. @detail Note maps are specified by a set of individual entries each representing a set of notes to spawn simultaneously. Each entry's notes are separated by a slash (/) and are numbered from 0 to 4 from left to right. Long notes can additionally be identified by a decimal point, with the number after the decimal giving the long note's length.

Static Public Member Functions

- `static List< LeaderboardEntry > GetLeaderboardList` ()
Reads the high scores from storage.
- `static void AddEntryToLeaderboard` (LeaderboardEntry entry)
Write a new entry to the high score storage.

Static Public Attributes

- `static FileIO instance`
The one instance of FileIO to be referenced globally.

3.8.1 Member Function Documentation

3.8.1.1 AddEntryToLeaderboard()

```
static void FileIO.AddEntryToLeaderboard (  
    LeaderboardEntry entry ) [inline], [static]
```

Write a new entry to the high score storage.

Parameters

The	entry to be written.
-----	----------------------

3.8.1.2 GetLeaderboardList()

```
static List<LeaderboardEntry> FileIO.GetLeaderboardList ( ) [inline], [static]
```

Reads the high scores from storage.

Returns

A list of the entries in the high score list.

3.8.1.3 ReadFile()

```
string [ ] FileIO.ReadFile (
    string pathName,
    char separator ) [inline]
```

Reads and returns the contents of the specified text file, splitting by the specified delimiter. @detail Note maps are specified by a set of individual entries each representing a set of notes to spawn simultaneously. Each entry's notes are separated by a slash (/) and are numbered from 0 to 4 from left to right. Long notes can additionally be identified by a decimal point, with the number after the decimal giving the long note's length.

Parameters

<i>pathName</i>	The text file's full path, in UNIX format.
<i>separator</i>	The character to split the file by.

Returns

An array of strings containing the file's contents after being split.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/FileIO.cs

3.9 GameManager Class Reference

Inheritance diagram for GameManager:

Collaboration diagram for GameManager:

Public Member Functions

- void [StartMusic](#) ()
Start playing music.
- void [NormalHit](#) ()
Called during a normal hit.
- void [GoodHit](#) ()
Called during a good hit.
- void [PerfectHit](#) ()

- *Called during a perfect hit.*
void [LongHit](#) ()
- *Called after a long note is completed.*
void [NoteMissed](#) ()
- *Called when a note is missed.*
void [LongClicked](#) ()
- *Called when a long note has been hit.*
void [SetMultiplier](#) (int mult)
- *Setter method for multiplier.*
void [SetScore](#) (int score)
- *Setter method for score.*

Public Attributes

- AudioSource [song](#)
The music to play during gameplay.
- AudioSource [guitar](#)
The accompanying music, to play only when the player has hit the most recent note.
- int [currentScore](#)
The current score during the session.
- int [currentMultiplier](#)
The current score multiplier during the session.
- bool [songStarted](#) = false
False if the song has not begun playing.
- float [totalNotes](#) = 0
Total notes spawned.
- float [normalHits](#) = 0
Normal hits by the player.
- float [goodHits](#) = 0
Good hits by the player.
- float [perfectHits](#) = 0
Perfect hits by the player.
- float [missedHits](#) = 0
Missed hits by the player.
- float [accuracy](#) = 0
Net hit accuracy, in percent.
- int [scorePerNote](#) = 100
Baseline score to be awarded per note hit, before multipliers and accuracy bonuses.
- string[] [noteList](#)
The complete sequence of notes to spawn for the selected song. @detail Notes from left to right are number from 0 through 4. Long notes are additionally denoted by a decimal following this number. Simultaneous notes are separated by a slash (/). For example, 0.2 gives a long leftmost note of length 2.
- TextMeshProUGUI [scoreText](#)
Display text for score.
- TextMeshProUGUI [multiText](#)
Display text for multiplier.

Static Public Attributes

- static [GameManager](#) *instance*
The instance of [GameManager](#) to be referenced globally.

3.9.1 Member Function Documentation

3.9.1.1 SetMultiplier()

```
void GameManager.SetMultiplier (
    int mult ) [inline]
```

Setter method for multiplier.

Parameters

<i>mult</i>	The new multiplier.
-------------	---------------------

3.9.1.2 SetScore()

```
void GameManager.SetScore (
    int score ) [inline]
```

Setter method for score.

Parameters

<i>score</i>	The new score.
--------------	----------------

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/Game↵
Manager.cs

3.10 LeaderboardEntry Class Reference

Public Attributes

- string [name](#)
The chosen name for the entrant.
- int [score](#)
The entrant's score.
- string [date](#)
The date the entry was made.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/Leaderboard↵
Entry.cs

3.11 LoadSettings Class Reference

Inheritance diagram for LoadSettings:

Collaboration diagram for LoadSettings:

Public Attributes

- Text **greenButtonSettings**
- Text **redButtonSettings**
- Text **yellowButtonSettings**
- Text **blueButtonSettings**
- Text **pinkButtonSettings**

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/LoadSettings.cs

3.12 MainMenu Class Reference

Inheritance diagram for MainMenu:

Collaboration diagram for MainMenu:

Public Member Functions

- void **PlayGame** ()
Called when the user starts a new game.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/MainMenu.cs

3.13 MMSettings Class Reference

Inheritance diagram for MMSettings:

Collaboration diagram for MMSettings:

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/MMSettings.cs

3.14 NoteObject Class Reference

Inheritance diagram for NoteObject:

Collaboration diagram for NoteObject:

Public Attributes

- KeyCode [keyToPress](#)
The key that the user must press to hit this note.
- GameObject [key](#)
The in-game key associated with keyToPress.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/NoteObject.cs

3.15 NoteScroller Class Reference

Inheritance diagram for NoteScroller:

Collaboration diagram for NoteScroller:

Public Attributes

- float [beatTempo](#)
The speed at which the note moves down the screen.
- bool [hasStarted](#)
True if notes have started spawning.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/NoteScroller.cs

3.16 NoteSpawner Class Reference

Inheritance diagram for NoteSpawner:

Collaboration diagram for NoteSpawner:

Public Attributes

- `GameObject[] notes = new GameObject[5]`
The five possible short notes that can be spawned at once.
- `GameObject[] longNotes = new GameObject[5]`
The five possible long notes that can be spawned at once.
- `GameObject[] keys = new GameObject[5]`
The five possible keys to hit.
- `float BPM`
The tempo of the song, in beats per minute.
- `string[] noteList`
The list of notes to spawn. @detail Notes from left to right are number from 0 through 4. Long notes are additionally denoted by a decimal following this number. Simultaneous notes are separated by a slash (/). For example, 0.2 gives a long leftmost note of length 2. An entry in noteList is spawned once every beat.

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/NoteSpawner.cs`

3.17 PauseMenu Class Reference

Inheritance diagram for PauseMenu:

Collaboration diagram for PauseMenu:

Public Member Functions

- `void Resume ()`
Resume gameplay after it has been paused.
- `void Pause ()`
Pause gameplay in progress. Stops note spawning, movement, and music playing.
- `void Settings ()`
Displays settings menu UI.

Public Attributes

- `GameObject PauseMenuUI`
The pause menu display.
- `GameObject settingsMenuUI`
The settings menu display.

Static Public Attributes

- static bool `Paused` = false
True if the game is paused.
- static bool `SettingsShown` = false
True if settings are being shown.

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/PauseMenu.cs`

3.18 PopulateLeaderboard Class Reference

Inheritance diagram for `PopulateLeaderboard`:

Collaboration diagram for `PopulateLeaderboard`:

Public Attributes

- Text `textTemplate`
The text on the leaderboard screen.

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/PopulateLeaderboard.cs`

3.19 QuitGame Class Reference

Inheritance diagram for `QuitGame`:

Collaboration diagram for `QuitGame`:

Public Member Functions

- void `ExitGame` ()

The documentation for this class was generated from the following file:

- `/mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/QuitGame.cs`

3.20 ScoreCalculator Class Reference

Inheritance diagram for ScoreCalculator:

Collaboration diagram for ScoreCalculator:

Public Member Functions

- float [NormalHit](#) (int currentScore, int currentMultiplier)
Called when a normal hit has been made.
- float [GoodHit](#) (int currentScore, int currentMultiplier)
Called when a good hit has been made.
- float [PerfectHit](#) (int currentScore, int currentMultiplier)
Called when a perfect hit has been made.
- float [LongHit](#) (int currentScore, int currentMultiplier)
Called when a long hit has been made.
- float [NoteMissed](#) ()
Called when a note has been missed.
- float [AccuracyCalculation](#) (float normalHits, float goodHits, float perfectHits, float totalNotes)
Calculates the user's net accuracy.

Public Attributes

- int [multiplierTracker](#)
The number of notes going toward the next multiplier.
- int[] [multiplierThresholds](#)
The number of notes that must be hit for the next multiplier.
- int [scorePerNote](#) = 100
The score for a normal hit, before multipliers.
- int [scorePerGoodNote](#) = 125
The score for a good hit, before multipliers.
- int [scorePerPerfectNote](#) = 150
The score for a perfect hit, before multipliers.
- int [scorePerLongNote](#) = 200
The score for a long hit, before multipliers.

Static Public Attributes

- static [ScoreCalculator](#) *instance*
The instance of [ScoreCalculator](#) to be referenced globally.

3.20.1 Member Function Documentation

3.20.1.1 AccuracyCalculation()

```
float ScoreCalculator.AccuracyCalculation (
    float normalHits,
    float goodHits,
    float perfectHits,
    float totalNotes ) [inline]
```

Calculates the user's net accuracy.

Parameters

<i>normalHits</i>	The number of normal hits made.
<i>goodHits</i>	The number of good hits made.
<i>perfectHits</i>	The number of perfect hits made.
<i>totalNotes</i>	The number of notes spawned.

Returns

The user's hit accuracy, in percent.

3.20.1.2 GoodHit()

```
float ScoreCalculator.GoodHit (
    int currentScore,
    int currentMultiplier ) [inline]
```

Called when a good hit has been made.

Parameters

<i>currentScore</i>	The current gameplay score.
<i>currentMultiplier</i>	The current gameplay multiplier.

Returns

1. Used to increment the number of good hits logged.

3.20.1.3 LongHit()

```
float ScoreCalculator.LongHit (
    int currentScore,
    int currentMultiplier ) [inline]
```

Called when a long hit has been made.

Parameters

<i>currentScore</i>	The current gameplay score.
<i>currentMultiplier</i>	The current gameplay multiplier.

Returns

1. Used to increment the number of long hits logged.

3.20.1.4 NormalHit()

```
float ScoreCalculator.NormalHit (
    int currentScore,
    int currentMultiplier ) [inline]
```

Called when a normal hit has been made.

Parameters

<i>currentScore</i>	The current gameplay score.
<i>currentMultiplier</i>	The current gameplay multiplier.

Returns

1. Used to increment the number of normal hits logged.

3.20.1.5 NoteMissed()

```
float ScoreCalculator.NoteMissed ( ) [inline]
```

Called when a note has been missed.

Returns

1. Used to increment the number of misses logged.

3.20.1.6 PerfectHit()

```
float ScoreCalculator.PerfectHit (
    int currentScore,
    int currentMultiplier ) [inline]
```

Called when a perfect hit has been made.

Parameters

<i>currentScore</i>	The current gameplay score.
<i>currentMultiplier</i>	The current gameplay multiplier.

Returns

1. Used to increment the number of perfect hits logged.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/Score↔ Calculator.cs

3.21 SettingsMenu Class Reference

Inheritance diagram for SettingsMenu:

Collaboration diagram for SettingsMenu:

Public Member Functions

- void [SetVolume](#) ()
Sets game volume based on the current slider value.
- void [GreenPressed](#) ()
Green button to be rebound.
- void [RedPressed](#) ()
Red button to be rebound.
- void [YellowPressed](#) ()
Yellow button to be rebound.
- void [BluePressed](#) ()
Blue button to be rebound.
- void [PinkPressed](#) ()
Pink button to be rebound.

Public Attributes

- GameObject **uiGreen**
- GameObject **uiRed**
- GameObject **uiBlue**
- GameObject **uiYellow**
- GameObject **uiPink**
- Slider [slider](#)
Volume slider.

The documentation for this class was generated from the following file:

- /mnt/c/users/david/documents/everything/school/3xa3/3xa3__l01_gr16_project/src/Assets/Scripts/Settings↔ Menu.cs

Index

- AccuracyCalculation
 - ScoreCalculator, [17](#)
- AddEntryToLeaderboard
 - FileIO, [9](#)
- BtnChangeScene
 - ChangeScene, [5](#)
- ButtonController, [5](#)
- ChangeScene, [5](#)
 - BtnChangeScene, [5](#)
- CollisionDetector, [6](#)
- CompleteScreen, [6](#)
 - DisplayCompleteScreen, [7](#)
- DetectKey, [7](#)
- DisplayCompleteScreen
 - CompleteScreen, [7](#)
- EffectManager, [8](#)
- Effects, [8](#)
- FileIO, [9](#)
 - AddEntryToLeaderboard, [9](#)
 - GetLeaderboardList, [9](#)
 - ReadFile, [10](#)
- GameManager, [10](#)
 - SetMultiplier, [12](#)
 - SetScore, [12](#)
- GetLeaderboardList
 - FileIO, [9](#)
- GoodHit
 - ScoreCalculator, [18](#)
- LeaderboardEntry, [12](#)
- LoadSettings, [13](#)
- LongHit
 - ScoreCalculator, [18](#)
- MainMenu, [13](#)
- MMSettings, [13](#)
- NormalHit
 - ScoreCalculator, [19](#)
- NoteMissed
 - ScoreCalculator, [19](#)
- NoteObject, [14](#)
- NoteScroller, [14](#)
- NoteSpawner, [14](#)
- PauseMenu, [15](#)
- PerfectHit
 - ScoreCalculator, [19](#)
- PopulateLeaderboard, [16](#)
- QuitGame, [16](#)
- ReadFile
 - FileIO, [10](#)
- ScoreCalculator, [17](#)
 - AccuracyCalculation, [17](#)
 - GoodHit, [18](#)
 - LongHit, [18](#)
 - NormalHit, [19](#)
 - NoteMissed, [19](#)
 - PerfectHit, [19](#)
- SetMultiplier
 - GameManager, [12](#)
- SetScore
 - GameManager, [12](#)
- SettingsMenu, [20](#)