Ex. No. 06	INTEGRATE ANIMATIONS AND TRANSITION
Date of Exercise	
Git Hub Host Link	https://github.com/Urk23cs1226/exp6-flutter.git

Aim

To implement animations and page transitions in Flutter.

Description

This experiment demonstrates the use of Flutter's `AnimatedContainer` widget to create a smooth size animation. A Boolean state variable `isLarge` is used to control the size of the container. When the Animate button is pressed, `setState()` changes the value of `isLarge`, and the `AnimatedContainer` smoothly changes its width and height**.**

Procedure:

1. A new Flutter project named `animation_app` was created using the Flutter command.
2. The project was opened in Visual Studio Code.
3. A `StatefulWidget` was created to maintain the animation state.
4. A Boolean variable `isLarge` was initialized as `false` to control the size of the animated container.
5. An `AnimatedContainer` widget was added with a duration of one second.
6. The width and height of the container were set based on the value of `isLarge`. The container changes from 150 × 150 to 300 × 300.
7. An ElevatedButton named Animate was added to control the animation.
8. When the button is pressed, `setState()` changes the value of `isLarge`.
9. The application was executed and the Animate button was clicked to observe the smooth size transition.

Program

```
import 'package:flutter/material.dart';

void main() {

  runApp(const AnimationApp());

}

class AnimationApp extends StatelessWidget {

  const AnimationApp({super.key});
```


```
 @override
 Widget build(BuildContext context) {
  return MaterialApp(
   debugShowCheckedModeBanner: false,
   home: const AnimationPage(),
  );
 }
}
class AnimationPage extends StatefulWidget {
 const AnimationPage({super.key});
 @override
 State<AnimationPage> createState() => _AnimationPageState();
}
class _AnimationPageState extends State<AnimationPage> {
 bool isLarge = false;
 @override
 Widget build(BuildContext context) {
  return Scaffold(
   appBar: AppBar(
    title: const Text('Animation'),
   ),
   body: Center(
    child: Column(
     mainAxisAlignment: MainAxisAlignment.center,
```

```
children: [
  AnimatedContainer(
    duration: const Duration(seconds: 1),
    width: isLarge ? 300 : 150,
    height: isLarge ? 300 : 150,
    decoration: BoxDecoration(
      borderRadius: BorderRadius.circular(20),
      color: Colors.blue,
    ),
    child: const Center(
      child: Text(
        'Flutter',
        style: TextStyle(
          color: Colors.white,
          fontSize: 24,
        ),
      ),
    ),
  ),
),
 const SizedBox(height: 30),
 ElevatedButton(
   onPressed: () {
     setState(() {
```

```
            isLarge = !isLarge;
          });
        },
        child: const Text('Animate'),
      ),
    ],
  ),
 ),
);
}
}
```

24CS2016 Building Applications using Flutter **URK23CS1226**

Output



Result

Thus, the Flutter application was successfully developed to demonstrate animation using the `AnimatedContainer` widget. On clicking the Animate button, the container smoothly changes its size, demonstrating Flutter's animation behavior.