Contents

Kernel (app/core) **1**
- Files . . . 1
- How a module plugs in . . . 1
- Module health . . . 4
- How a refusal reaches the phone . . . 4
- Money . . . 4
- The clock . . . 5
- The database . . . 5
- Settings and constants . . . 5
- Records and errors . . . 5
- Design patterns . . . 6
- Tests . . . 6

Kernel (app/core)

The kernel holds what every module shares, and builds the app from the modules' plugins. `app/core/` never imports a module.

Folder	`src/backend/app/core/`, plus `app/main.py` and `app/registry.py`
Tables	None
Routes	`GET /v1/health`
Uses	No module
Used by	Every module: users, wallet, market, trading
Issue	#187, #191

Files

Every module may import any file in `app/core/`, so its names are `+`, or `-` if they start with `_`. `main.py` and `registry.py` sit above every module, so no module may import them, and their names are `~`.

How a module plugs in

The kernel doesn't know which modules exist. Each module fills in a `Plugin` in its `plugin.py`, with its routes, any work that runs while the app runs (a lifespan, such as market's poller thread) and a health check.

`registry.py` lists each module's `PLUGIN` in `PLUGINS`. A `plugin.py` imports its module's `models.py`, even with no routes, so importing the registry registers every module's tables. That is how Alembic finds them.

`create_app(plugins = PLUGINS)` in `main.py` builds the app: - It adds the health route and each module's routes under `/v1`. - When the app starts, it starts each lifespan in the order of `PLUGINS`. An exit stack stops them in reverse order when the app stops, even if one fails to start. A lifespan stops its work in a `finally` after its `yield`, so the work stops even when a later module fails to start. - It adds the two error handlers below.

`app = create_app()` is what `uv run uvicorn app.main:app` serves. Tests pass their own plugins to build a smaller app.

To add a module, write its `plugin.py` (importing its `models.py`), add one line to `PLUGINS`, and add the module to the layers in `pyproject.toml` so import-linter checks it. Nothing in `app/core/` or `create_app` changes.




Figure 1: UML class diagram of the kernel's files




Figure 2: UML class diagram of the plug-in kernel

Module health

`GET /v1/health` needs no user. It tells the team and CI whether the API can reach the database, and how each module with a health check is doing:

```
{"status": "ok", "database": "ok", "modules": {"market": {"status": "ok", "detail": null}}}
```

The database	The modules	Status	`status`
Reachable	All `ok`	200	`ok`
Reachable	One is `degraded`	200	`degraded`
Unreachable	Any	503	`degraded`

Nothing works without the database. A degraded module still gets 200, since the rest of the API still works. - A module without a health check is left out. In the PoC only market has one, for its poller. - A health check reads only what its module keeps in memory, with no database or network call, so it answers at once. - `detail` is a short fixed text, such as `poller stopped`, never a secret or an error's own text. - A check that raises, or returns something other than a `ModuleHealth`, is shown as `degraded` with the detail `health check failed`. Its error goes to the log only, since its text could say too much. - A module with a lifespan must have a health check, since background work can fail without any request seeing it. `Plugin` refuses one without it.

How a refusal reaches the phone

A module refuses a request by raising a subclass of `DomainError`, which sets its `code`, `message` and `status`:

```
class InsufficientFundsError(DomainError):
    code = "insufficient_funds"
    message = "You don't have enough currency for this."
    status = 409
```

`handle_domain_error` in `errors.py` sends any of them in one shape, with its status:

```
{"detail": {"code": "insufficient_funds", "message": "You don't have enough currency for this."}}
```

A message can be set when the error is raised, such as trading's `price_changed` giving the new price. The class's own message doesn't change. The PoC's refusals are users' `not_authenticated` (401), market's `unknown_asset` (404), wallet's `insufficient_funds` (409) and trading's four (409).

A request that doesn't fit its route, such as an amount with more than 4 decimals, gets 422 in FastAPI's shape, but `handle_validation_error` leaves out the values that were sent (`input`). FastAPI's own handler sends each one back, and some can't be written as JSON, such as `NaN` in a body, so the phone would get a 500.

```
{"detail": [{"type": "decimal_max_places", "loc": ["body", "expected_price"],
  "msg": "Decimal input should have no more than 4 decimal places",
  "ctx": {"decimal_places": 4}}]}
```

Money

`Money` is the type for amounts the API sends or takes. Python code gets a `Decimal`. JSON gets text with 4 decimals, such as `"84.0000"`, because JSON numbers can lose exactness on the way (NFR_Accuracy). A zero is always `"0.0000"`, never `"-0.0000"`. A reply's `Money` shows as text in the API docs. A request may send a number or text.

An amount with more than 4 decimals is refused, not rounded. A request with one gets a 422, as above. Code that builds a reply rounds an amount from a division or `avg()` first, with `.quantize(Decimal("0.0001"))`.

The clock

Code takes the time from a `Clock`, a function that returns the current time with its time zone, never from `datetime.now()` (rule 6). `system_clock` gives the real time in UTC. - A route asks for it with `Depends(get_clock)`. - A test sets the time with `app.dependency_overrides[get_clock]`, as the `at_time` fixture does. - Market's poller and `FakeProvider` are handed a clock, `system_clock` by default.

The database

`db.py` builds the engine from `DATABASE_URL` when it is first imported. Tests point it at a database ending in `_test` before that. - `get_db` gives each request its own session, through `Depends(get_db)`. The session closes when the request ends, which drops whatever the route didn't commit. A route commits once per request (rule 4). - `SessionLocal` makes a session outside a request, such as for each of market's polls and for `seed_demo`. That code commits once for each piece of work, such as one poll. - `Base` is every table's base class. Alembic reads its metadata. - `NAMING_CONVENTION` gives each index and constraint a name you can predict, such as `uq_prices_asset_id_quoted_at`, so a migration can refer to it. - Every `datetime` column is stored with its time zone (`timestamptz`), so times from users and the server compare correctly.

Settings and constants

`Settings` reads `DATABASE_URL` from the environment or a local `.env`, once per process (`get_settings`). Without one, it uses the local compose database (`fitfolio` on localhost:5432). Each module reads its own settings in its own `settings.py`, such as users' `DEMO_USER_ENABLED`. Migrations read the same `DATABASE_URL`. A password with characters like `@` is written with `%` in a URL, which Alembic would misread, so `migrations/env.py` doubles each `%`.

`constants.py` holds the SRS's symbolic constants (Appendix C). Change a value there and in the SRS together. Market uses `QUOTE_CURRENCY` and `QUOTE_STALENESS_LIMIT`. The rest wait for their features.

Records and errors




Figure 3: UML class diagram of the kernel's records and errors

`Plugin` and `ModuleHealth` are frozen, so nothing changes them once made. `Health` is the reply of `GET /v1/health`.

Design patterns

- **Plug-in kernel:** modules plug in through `Plugin` and `PLUGINS`, and the kernel doesn't change, as above.
- **Dependency injection:** routes get the session and the clock through `Depends(get_db)` and `Depends(get_clock)`, so tests hand in a test session or a fixed time.

Tests

File	What it checks
`test_create_app.py`	A lifespan without a health check refused, lifespans started in order and stopped in reverse, unique module names
`test_health.py`	`GET /v1/health`: 200 with a degraded module, 503 without the database, a module without a check left out, and a check that raises or returns the wrong thing, shown without its error
`test_errors.py`	A `DomainError`'s JSON and status, a message set when it is raised, and a 422 in FastAPI's shape without the values sent, even ones JSON can't write, such as `NaN`
`test_money.py`	`Money` as text with 4 decimals, a `Decimal` in Python, more than 4 decimals refused
`test_clock.py`	The real clock is in UTC, and `get_clock` gives routes that clock
`test_migrations.py`	One newest migration, a database password with special characters, and migrations that match the models
`test_public_files.py`	Modules import each other only through their public files, and only `registry.py` imports a `plugin.py`
`test_test_setup.py`	The shared test setup: each test's rows undone, a route keeps a row only if it commits, the real `get_db` through a healthy `GET /v1/health`, and `make_portfolio`'s funding