Contents

FitFolio backend architecture **1**
- Architecture . . . 1
- Technology . . . 3
- Modules . . . 4
- A module's files . . . 4
- How to read the class diagrams . . . 4
- Rules . . . 5
- Design patterns . . . 5
- How it runs . . . 5
- Migrations . . . 9

FitFolio backend architecture

Date	Version	Author	Notes
Nov 5, 2026	1.0	Davis Lenover	PoC version
Nov 7, 2026	1.1	Davis Lenover	Module health, users and wallet
Nov 8, 2026	1.2	Davis Lenover	Trading
Nov 8, 2026	1.3	Davis Lenover	One doc per module, access specifiers in the class diagrams
Nov 10, 2026	1.4	Davis Lenover	Technology, and why each was chosen

This is the high-level view. Each module is explained in its own doc, linked below. It covers only what the PoC needs, and grows as features are added.

Architecture

Client–server. The phone app is the client. It talks to one backend server over HTTPS, sending and receiving JSON (a REST API).

The server is a modular monolith on a small kernel. It is one FastAPI process with one PostgreSQL database, split into modules. - **Modules:** one per feature. Each is a folder in `src/backend/app/` and owns its own tables. - **Layers:** modules are stacked, and calls only go down. Trading calls market, but market never calls trading. - **Public interfaces:** other modules use a module only through its public files. - **Kernel:** `app/core/` holds what every module shares, and never imports a module. - **Plug-ins:** each module adds its routes to the app through its `plugin.py`, which is listed in `app/registry.py`. - **Adapter:** market gets prices through a provider class, so Finnhub can be swapped for another provider without changing other modules.

The server isn't split into separate services, because a buy must change the balance and the shares in one database transaction (FR_MktAtomicTrade). CI rejects any import that breaks these rules.

The rows inside "Modules" show the stacking. Trading uses market and wallet, activity uses wallet, and wallet uses users. Wallet and trading also use users to get the current user. Market's routes need no user.

The diagram's source is `figures/backend-poc.puml`. After changing a diagram, run this from the repository root to update its PNG:

```
plantuml -tpng docs/Design/SoftArchitecture/figures/backend-poc.puml
```




Figure 1: UML component diagram of the PoC backend

Technology

The Development Plan (Section 10, Expected Technology) gives the reasons for Python, FastAPI, PostgreSQL, pytest and Ruff, and their alternatives. The rest were chosen while building the PoC. In short:

- **Python 3.14** is the programming language the server is written in. Its libraries cover each of the server's jobs: calling Finnhub, serving the API, and later NumPy and pandas for market scenarios (FR_MktScenario). TypeScript would have matched the app, but Python's numerical libraries suit the simulation better.
- **FastAPI** is a Python web framework, a library for writing the routes of an API. **Uvicorn** is the web server that runs it.
  - It checks every request against the route's types before our code runs, so a malformed request is refused (SEC-25).
  - Its `Depends` hands each route its session, clock and user, so a test can swap them (dependency injection).
  - It writes the API's docs at `/docs` from the same types, so the app and the server agree on what is sent.
  - Django with Django REST Framework was the alternative, but Django brings much the project doesn't need, such as server-rendered pages.
- **Pydantic** is a library that checks data against declared types, such as a field that must be a decimal. `Money` uses it to refuse an amount with over 4 decimals (NFR_Accuracy). pydantic-settings, its add-on for settings, reads `.env` and keeps the Finnhub key a `SecretStr`, which prints as stars (SEC-33).
- **PostgreSQL 18** is a relational database: data lives in tables of rows and columns, and a row can point at a row in another table. It holds every module's tables.
  - The data is relational (users, portfolios, trades), and one transaction saves a buy's payment and shares together or not at all (FR_MktAtomicTrade).
  - It stores money as exact `NUMERIC` (NFR_Accuracy), and locks a portfolio's row so requests for it take turns (rule 5).
  - It checks each table's constraints, such as a balance never below 0, on every write, even for code that skips a module's own checks.
  - MongoDB was the alternative, but this data is relational.
- **Docker** runs a program in a container: a packaged copy of the program with everything it needs, kept apart from the rest of your computer. Here it runs PostgreSQL. `docker compose up -d` in `src/backend/` starts the same `postgres:18` image that CI tests against, so your database matches CI's, with nothing to install but Docker. Its credentials are for local use only.
- **SQLAlchemy 2** is a library for using a SQL database from Python. Each table is a Python class, and queries are Python code rather than strings of SQL. Each module defines its tables as typed classes on one `Base`, which names every constraint and index the same way. A session saves a request's changes in one commit (rule 4).
- **Alembic** is SQLAlchemy's migration tool. A migration is a small Python script that changes the database's tables, such as adding a column or a check, and can undo that change.
  - **We rarely write SQL.** A migration calls functions such as `op.create_table` or `op.add_column`, and Alembic turns them into the SQL PostgreSQL needs (`CREATE TABLE`, `ALTER TABLE`). Only small pieces are SQL text, such as a check's condition (`price > 0`).
  - **It drafts each migration for us.** `alembic revision --autogenerate` compares the classes in each module's `models.py` with the database, and writes a migration for the difference. We read it and fix what it can't see, such as a renamed column, which it takes for one dropped and one added.
  - **It knows what each database has had.** Each migration names the one before it, so they form one chain, and a database keeps the newest one it has had in a table called `alembic_version`. `alembic upgrade head` runs only the ones that database hasn't had, in order.
  - **Why:** a database that holds data, such as a deployed one, changes without being rebuilt or losing rows, and every developer's database ends up like CI's. Without it, each change would be SQL that everyone runs by hand, with nothing to say which databases have had it. CI checks there is one chain, that it upgrades and downgrades, and that it matches the models (`alembic check`).

Migrations and the backend README show how to make one.

- **httpx2** is a library for making HTTP requests from Python. It calls Finnhub with a 10 second timeout, and lets tests answer in Finnhub's place (`MockTransport`).
- **uv** is a tool that installs Python and a project's packages. It installs them from `uv.lock`, the list of exact versions, so everyone and CI get the same ones (`uv sync --locked`).
- **pytest** is a framework for writing and running tests, with little boilerplate. **Ruff** checks code for mistakes and style (a linter) and formats it, in one fast tool. **import-linter** checks which packages may import which, and fails CI when a module imports one above it (rule 2).

Modules

Module	What it does	Owns these tables	Routes	Issue
Kernel (`app/core/`)	What every module shares	none	`GET /v1/health`	#187
Users	Who is calling	`users`	none	#279
Wallet	Each portfolio's currency, and the one safe way to change it	`portfolios`, `balance_changes`	`GET /v1/me/balance`	#279, #189
Market	Stocks and their prices	`assets`, `prices`, `provider_requests`	`GET /v1/assets`, `GET /v1/market/usage`	#187
Trading	Buying shares, and what a portfolio is worth	`trades`, `holdings`	`POST /v1/me/trades`, `GET /v1/me/portfolio`	#188
Activity	Step rewards	`activity_daily_totals`	`PUT /v1/me/activity/daily-totals`	#190

Each module's pull request adds or updates its doc in `modules/`, and its UML class diagram in `figures/`.

A module's files

File	What it holds	Other modules may import it
`interface.py`	Functions other modules may call	Yes
`queries.py`	Reads other modules may call. They never write	Yes
`types.py`	Data classes and errors	Yes
`service.py`	The rules. Never commits	No
`models.py`	The tables	No
`routes.py`	HTTP routes. Commits once	No
`plugin.py`	Adds the module to the app: its routes, background work and health check	No, only `app/registry.py`

Leave out any file a module doesn't need.

How to read the class diagrams

Each kind of box has one color in every diagram, shown in its legend. For example, an entry point is orange, a public file green, logic purple, a table or record blue and an error red. An arrow means "uses", and a hollow arrowhead means "is a".

Each member has an access specifier. In a box for a file, it follows the import rules below: - `+` **public:** other modules may use it, because it is in the module's `interface.py`, `queries.py` or `types.py`. A route is `+` too, since the phone uses it. - `~` **module:** only the module's own files may use it, such as everything in `service.py` and `models.py`. - `-` **private:** only its own file uses it. In Python its name starts with `_`.

In a box for a class, such as a record, a table, an error or a provider, `+` is a member that anyone holding one may use, and `-` is one whose name starts with `_`. Which file the class is in says who may import it.

Rules

1. Import another module only through its `interface.py`, `queries.py` or `types.py`.
2. Never import a module above yours in the diagram.
3. Never use another module's tables. A foreign key into them is fine, such as `trades.asset_id` to `assets`.
4. A route commits once per request. Code that answers no request commits once for each piece of work, in its own session, such as each of market's polls or one run of `seed_demo`. Nothing below them commits.
5. Money only moves through wallet. Lock the portfolio with `wallet.interface.lock_live_portfolio()` before calling `change_balance`, as wallet shows.
6. Take the time from `app/core/clock.py`, never from `datetime.now()`, so tests can set it.

CI checks rules 1 and 2. import-linter (`uv run lint-imports`) refuses an import of a module above, or of any module from `app/core/`. `test_public_files.py` refuses an import of another module's other files.

Design patterns

Plug-in kernel. The kernel (`app/core/` and `create_app()`) doesn't know which modules exist. Each module fills in a `Plugin` in its `plugin.py`, with its routes, any work that runs in the background, and a health check, and `app/registry.py` lists them. Adding a module never changes the kernel. See the kernel.

Strategy, adapter and factory. Market asks for prices through one interface, `MarketDataProvider`. `FinnhubProvider` adapts Finnhub's API to it, `FakeProvider` makes up prices, and `build_provider` picks one from `MARKET_PROVIDER`. Each provider gives its own request limit, so a new one changes no code outside `market/providers/`. See market.

Dependency injection. Code is handed what it needs instead of fetching it. Routes get a database session and the clock from the kernel, through `Depends(get_db)` and `Depends(get_clock)`, and the current user from users, through `Depends(get_current_user)`. The poller is given its provider, clock and session factory. Tests hand in stand-ins, such as a fixed time or a stub provider.

Read-only records. A module hands other modules frozen copies, such as market's `CurrentPrice` or wallet's `BalanceChangeReceipt`, never database rows. That way no module can change another module's tables by accident.

Lock token. Wallet's `change_balance` only takes the `LockedPortfolio` that `lock_live_portfolio` returns, so changing a balance without locking it first is hard to do by accident. See wallet.

Idempotency key. Each buy carries a `request_id` from the phone, so a retried request gets its first answer back instead of buying twice. See trading.

How it runs

When the app starts, the kernel adds each module's routes and starts each module's background work. For market, that is the poller thread, which saves a price for every stock once a minute while the market is open.

A request goes from the kernel to the module's route, which reads through the module's queries.




Figure 2: UML class diagram of the plug-in kernel




Figure 3: UML sequence diagram of startup and a price poll




Figure 4: UML sequence diagram of a request for the asset list

Migrations

There is still one chain, and 0001 to 0003 don't change. Each new migration is named after its module and numbered within it, such as `market_0002`. If `main` gets a new migration while you work, set your migration's `down_revision` to it before you merge, and keep its name. The backend README shows the commands.