Contents

Trading module **1**
- Files . . . 1
- Buying shares . . . 1
- What a portfolio is worth . . . 2
- Records, errors and tables . . . 2
- Design patterns . . . 2
- Not built in the PoC . . . 2
- Tests . . . 2

Trading module

Trading buys whole shares with a portfolio's currency, and values the portfolio at the latest prices. The PoC only buys.

Folder	`src/backend/app/trading/`
Tables	`trades`, `holdings`
Routes	`POST /v1/me/trades`, `GET /v1/me/portfolio`
Uses	users, wallet, market
Used by	Nothing yet
Issue	#188

Files

`routes.py` reaches the other modules only through their public files. It locks the portfolio (1), and `buy` pays for the shares (2).

Buying shares

`POST /v1/me/trades` follows wallet's three steps: 1. The route locks the portfolio with `lock_live_portfolio`. 2. `buy` checks the request, pays with `change_balance`, adds the shares to `holdings` and saves the trade. It never commits. 3. The route commits once, so the payment, the shares and the trade are saved together or not at all (FR_MktAtomicTrade).

One trade per `request_id` (an idempotency key). The phone sends a new `request_id` for each buy the user confirms, and the same one again when it retries. A repeat gets the first trade back (200 instead of 201) and pays nothing, even after the market closes or the price moves (FR_MktNoDuplicate). The same `request_id` with a different symbol, quantity or price is refused. The database also refuses a second trade with one `request_id` in a portfolio.

Only at the price the user saw (SEC-29). The phone sends back `expected_price` exactly as `GET /v1/assets` gave it. `buy` reads the price once, and uses that one read for the check, the trade's price and the cost.

`buy` refuses, in this order:

Code	Status	When
`request_id_reused`	409	The `request_id` was used for a different trade
`market_closed`	409	The market is closed
`unknown_asset`	404	No stock has that symbol. Market refuses this one

Code	Status	When
`price_out_of_date`	409	The stock has no price yet, or it is delayed
`price_changed`	409	The price isn't `expected_price`. The message gives the new one
`insufficient_funds`	409	The balance is less than the cost. Wallet refuses this one

A refused buy saves nothing, so the same request can be sent again later.

What the phone must do: - Send `expected_price` back as the text `GET /v1/assets` gave. A rounded number gets `price_changed` every time. - Use a new `request_id` for each buy the user confirms, and the same one for each retry of it.

What a portfolio is worth

`GET /v1/me/portfolio` sends each holding at its quantity × its stock's latest price, sorted by symbol. A delayed price is still used, and its holding is marked `delayed`. Each holding gives both times of its price: `obtained_at`, when the server got it, which the phone shows with it (FR_MktPriceAge), and `quoted_at`, when the provider set it, which `delayed` goes by. - `holdings_value` is the sum of the holdings, the SRS's portfolio value (FR_MktPortfolioValue). It leaves the cash out. - `total_value` is `cash_balance` + `holdings_value`. - `simulated` is always true, so the phone labels the values as simulated (FR_MktLabelReturns).

It only reads, so it doesn't lock or commit. A buy that commits while it runs can make one reply off by that buy. The next one is right.

Records, errors and tables

The tables keep the money rules even for code that skips `buy`. For example, a trade's cost must equal its quantity × its price, and one payment can only pay for one trade.

Design patterns

- **Plug-in:** `plugin.py` adds trading's routes to the app. The kernel doesn't change.
- **Dependency injection:** the routes get the session, the clock and the user through `Depends`, so tests set the time and the user.
- **Read-only records:** `HoldingValue` and `PortfolioValue` are frozen copies. Wallet hands trading a `BalanceChangeReceipt`, and market a `CurrentPrice`, never their rows.
- **Lock token:** `buy` only takes the `LockedPortfolio` that `lock_live_portfolio` returns.
- **Idempotency key:** `request_id`, as above.

Not built in the PoC

- Selling, and queueing a buy for when the market opens (FR_MktQueueClosed). A buy while the market is closed is refused.
- Refusing a first trade before the user accepts the simulation notice (FR_MktSimNotice).

Tests

File	What it checks
`test_trading_request.py`	The request body, and the new price in `price_changed`'s message
`test_trading_tables.py`	The rules the tables keep by themselves

File	What it checks
`test_trading_buy.py`	`buy`: exact costs, every refusal and its order, each `request_id` once
`test_trading_routes.py`	`POST /v1/me/trades`: status codes, bodies, each refusal's code and message, all or nothing
`test_trading_portfolio.py`	`portfolio_value` and `GET /v1/me/portfolio`, with each holding's two times




Figure 1: UML class diagram of the trading module's files




Figure 2: UML sequence diagram of a buy




Figure 3: UML class diagram of trading's records, errors and tables