Contents

Wallet module **1**
- Files . . . 1
- Changing a balance . . . 1
- The balance route . . . 3
- Making and deleting a portfolio . . . 3
- Records, errors and tables . . . 3
- Design patterns . . . 3
- Not built in the PoC . . . 3
- Tests . . . 3

Wallet module

Wallet holds each portfolio's currency, and is the one safe way to change it. It records every change with its amount, time and reason (SEC-22).

Folder	`src/backend/app/wallet/`
Tables	`portfolios`, `balance_changes`
Routes	`GET /v1/me/balance`
Uses	users
Used by	trading, and `app/scripts/seed_demo.py`
Issue	#279, #189

Files

`interface.py` re-exports the four functions other modules may call from `service.py`, and `queries.py` holds the reads. Nothing in wallet commits.

Changing a balance

A route that changes money does three things:

```
from app.wallet.interface import change_balance, lock_live_portfolio
from app.wallet.types import BalanceChangeReason

locked = lock_live_portfolio(db, user.user_id)
receipt = change_balance(db, locked, -cost, BalanceChangeReason.TRADE_PURCHASE)
db.commit()
```

1. **Lock first.** `lock_live_portfolio` locks the user's live portfolio row (a `SELECT ... FOR UPDATE`) until the transaction ends. Two requests for one portfolio, such as a buy and a step sync, then run one after the other, and the second sees what the first saved.
2. **Change with one guarded `UPDATE`.** `change_balance` adds the amount only if the balance stays at 0 or more, then records the change in `balance_changes`. It never commits. If the lock is skipped, the guarded `UPDATE` still keeps the balance at 0 or more.
3. **Commit once.** The route commits after every step has succeeded, so the payment and what it pays for are saved together or not at all.

Read after the lock. The lock only holds for what the route reads after it. So read anything the amount depends on there, such as what a day's rewards have paid so far (`activity_paid`). `activity_paid` also refuses a `datetime` with `ValueError`.

`change_balance` refuses, before changing anything, a call that makes no sense. It raises `ValueError` for: - an amount that is 0, isn't a finite `Decimal`, or has more than 4 decimals, which the database would round




Figure 1: UML class diagram of the wallet module's files

quietly. So when a reward comes to 0, don't call it - a reward that takes currency away, or a purchase that adds it - a reward without its `activity_date` (the `date` it pays for), anything else with one, or a `datetime` instead of a `date`

These are mistakes in the calling code, not refusals. The one refusal the phone sees is:

Code	Status	When
`insufficient_funds`	409	The balance would go below 0 (FR_MktAtomicTrade). Nothing changes

The balance route

`GET /v1/me/balance` sends the current user's live balance as text with 4 decimals, such as `{"cash_balance": "412.0000"}`. It only reads, so it doesn't lock or commit. Without a user, users answers 401 `not_authenticated`.

Making and deleting a portfolio

Each user has one live portfolio, the one with no `scenario_id`. Neither of these commits: - `create_live_portfolio` gives a user their live portfolio, at 0, and returns its ID. - `delete_portfolio` is one `DELETE`. The database deletes what is under the portfolio in the same statement: its balance changes, and other modules' rows that point at it with `ON DELETE CASCADE`, such as trading's trades and holdings.

`seed_demo` makes the demo user's live portfolio, as users explains. It only uses users' and wallet's public files, never their tables. `reset` deletes the old portfolio with `delete_portfolio`, which takes its changes with it, and makes a new one with `create_live_portfolio`.

Records, errors and tables

Wallet hands other modules read-only copies, never rows. `BalanceChangeReceipt` holds the change's ID, its amount and the balance after it. Trading stores that ID with each trade, so every trade points at the change that paid for it.

The tables refuse bad rows, such as a balance below 0 or a reward that spends, even from code that skips `change_balance`. They don't check that a balance equals the sum of its changes (SEC-22). `change_balance` keeps that true by changing both in one transaction, which is why nothing else may change a balance.

Design patterns

- **Plug-in:** `plugin.py` adds wallet's route and tables to the app. The kernel doesn't change.
- **Dependency injection:** the route gets the session and the user through `Depends`, so tests set the user.
- **Read-only records:** `LockedPortfolio` and `BalanceChangeReceipt` are frozen copies.
- **Lock token:** `change_balance` only takes the `LockedPortfolio` that `lock_live_portfolio` returns.

Not built in the PoC

- Paying step rewards. `activity_reward` and `activity_paid`, which lets a step sync pay only the difference, are ready for activity (#190).
- Portfolios for market scenarios. Every portfolio is live, with no `scenario_id`.

Tests




Figure 2: UML class diagram of wallet's records, errors and tables

File	What it checks
`test_wallet_money.py`	The lock, `change_balance`, `delete_portfolio` and the queries: exact amounts, every refusal changes nothing, the balance is the sum of its changes, a second transaction waits for the lock, wallet never commits
`test_wallet_tables.py`	The rules the tables keep by themselves: a balance of 0 or more, one live portfolio per user, a real user, and each balance change's amount, reason and activity date
`test_wallet_balance.py`	`GET /v1/me/balance`: the balance as text, 0 for a new portfolio, 401 without a user
`test_seed_demo.py`	`seed` and `reset`: one demo user, a live portfolio at 0, a second run changes nothing, no old changes left
`test_test_setup.py`	Its `make_portfolio` test: a live portfolio funded by one old reward and committed