

Some Java Basics

Object Oriented Programming

2016375 - 5


Camilo López

Outline

- Why Java?
- Primitive Data Types
- Variables
- Arrays
- The String Type
- Java Expressions
- Flow Control Structures
- Anatomy of a Simple Java Program
- Intro to Eclipse
- User input
- Some Tips


Why Java?

Java Is Architecture Neutral



Why Java?

Java Is Architecture Neutral



Java Is Architecture Neutral



Platform dependent JVM




Platform dependent JVM

Platform independent bytecode

Why Java?

The Java Virtual Machine


- The JVM is a special piece of software that knows how to interpret and execute Java bytecode.



- **Performance:** a bit slower, in general, than compiled languages
- Java bytecode is, in theory, **forward compatible** with newer versions of the JVM.


Why Java?

Java Provides "One-Stop Shopping"



Why Java?

Java Provides "One-Stop Shopping"



Why Java?

Java Provides “One-Stop Shopping”



- the Java language provides an extensive set of **application programming interfaces (APIs)** → *platform-independent* means of accessing all underlying operating system functions
 - **java.io**: Used for file system access
 - **java.sql**: The JDBC API, used for communicating with relational databases in a vendor independent fashion
 - **java.awt**: The Abstract Windowing Toolkit, used for GUI development
 - **javax.swing**: Swing components, also used for GUI development

Why Java?

Java Provides “One-Stop Shopping”

- Java is OO from the Ground Up
 - C++ can be used as an improved version of C
 - All data, with the exception of a few primitive types, is rendered as objects.
 - All functions are associated with objects and are known as methods—there can be no “free-floating” functions as there are in C/C++.
- Java Is an Open Standard
- Java is Free!



Java lends itself particularly well to writing applications that uphold the OO paradigm.

Primitive Data Types

- The Java programming language is statically-typed

Data Type	Size (bits)	Default Value
byte	8	0
short	16	0
int	32	0
long	64	0L
float	32	0.0f
double	64	0.0d
char	16 (Unicode)	'\u0000'
boolean		false
String	...	null

- Local variables are slightly different; the compiler never assigns a default value to an uninitialized local variable.

Variables

- Before a variable can be used in a Java program, the type and name of the variable must be *declared* to the Java compiler.
- One declaration per line is recommended since it encourages commenting.
- Try to initialize local variables where they're declared.
- Naming
 - Meaningful and valid (must start with either an alphabetic character, an underscore, or a dollar sign (*whose use is discouraged, since it is used by the compiler when generating code*), and may contain any of these characters plus numeric digits)
 - camelCasing

Variables

- Some examples


```
int simple;  
int _under;  
int more$money_is_2much;
```

```
int 1bad;  
int number#sign;  
int foo-bar;  
int plus+sign;  
int x@y;  
int dotnotation;
```

Arrays

An **array** is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed.

```
datatype[ ] arrayName;  
datatype[ ][ ] arrayOfArrays;
```




```
int[ ] arrayName;  
arrayName = new int[10];  
arrayName[0] = 3;  
int[ ] anotherArray = {1, 2, 3, 4, 5, 6};
```

→ Declares an array of integers

Arrays

An **array** is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed.

```
datatype[ ] arrayName;  
datatype[ ][ ] arrayOfArrays;
```




```
int[ ] arrayName;  
arrayName = new int[10];  
arrayName[0] = 3;  
int[ ] anotherArray = {1, 2, 3, 4, 5, 6};
```

→ **allocates memory for 10 integers**

Arrays

An **array** is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed.

```
datatype[ ] arrayName;  
datatype[ ][ ] arrayOfArrays;
```




```
int[ ] arrayName;  
arrayName = new int[10];  
arrayName[0] = 3;  
int[ ] anotherArray = {1, 2, 3, 4, 5, 6};
```

→ initialize first element

Arrays

An **array** is a container object that holds a fixed number of values of a single type. The length of an array is established when the array is created. After creation, its length is fixed.

```
datatype[ ] arrayName;  
datatype[ ][ ] arrayOfArrays;
```



```
int[ ] arrayName;  
arrayName = new int[10];  
arrayName[0] = 3;  
int[ ] anotherArray = {1, 2, 3, 4, 5, 6};
```

→ **Declaration and initialization**

The String Type

- A String represents a sequence of zero or more Unicode characters.

```
String stringName = "stringValue";  
String shortString = "A";
```

```
String s = "";
```

```
String x = "foo";  
String y = "bar";  
String z = x + y + "!";
```

→ **Keep this in mind: it's a capital 'S'**

Java Expressions

- A constant: 7, false
- A char literal enclosed in single quotes: 'A', '3'
- A String literal enclosed in double quotes: "foo", "Java"
- The name of any properly declared variables: myString, x
- Any two of the preceding types of expression that are combined with one of the Java binary operators
- Any one of the preceding types of expression that is modified by one of the Java unary operators
- Any of the preceding types of expression enclosed in parentheses: (x + 2)

Java Expressions

Arithmetic Operators

Operator	Description
+	Addition
-	Subtraction
*	Multiplication
/	Division
%	Remainder (the remainder when the operand to the left of the % operator is divided by the operand to the right; e.g., $10 \% 3 = 1$, because 3 goes into 10 three times, leaving a remainder of 1)

unary increment (++) and decrement (--) operators are used to increase or decrease the value of a int variable by 1.

- $b = a++ \rightarrow b = a; a = a + 1;$
- $b = ++a \rightarrow a = a + 1; b = a;$
- $ch = 'c'; c++;$

Java Expressions

Java Compound Assignment Operators

Operator	Description
<code>+=</code>	<code>a += b</code> is equivalent to <code>a = a + b</code> .
<code>-=</code>	<code>a -= b</code> is equivalent to <code>a = a - b</code> .
<code>*=</code>	<code>a *= b</code> is equivalent to <code>a = a * b</code> .
<code>/=</code>	<code>a /= b</code> is equivalent to <code>a = a / b</code> .
<code>%=</code>	<code>a %= b</code> is equivalent to <code>a = a % b</code> .

Java Expressions

Relational Operators

Operator	Description
<i>exp1 == exp2</i>	true if <i>exp1</i> equals <i>exp2</i> (note use of a <i>double</i> equal sign for testing equality).
<i>exp1 > exp2</i>	true if <i>exp1</i> is greater than <i>exp2</i> .
<i>exp1 >= exp2</i>	true if <i>exp1</i> is greater or equal to <i>exp2</i> .
<i>exp1 < exp2</i>	true if <i>exp1</i> is less than <i>exp2</i> .
<i>exp1 <= exp2</i>	true if <i>exp1</i> is less than or equal to <i>exp2</i> .
<i>exp1 != exp2</i>	true if <i>exp1</i> is not equal to <i>exp2</i> (! is read as “not”).
<i>!exp</i>	true if <i>exp</i> is false, and false if <i>exp</i> is true.

Java Expressions

Logical Operators

Operator	Description
<i>exp1 && exp2</i>	Logical “and”; compound expression is true only if <i>both exp1 and exp2</i> are true
<i>exp1 exp2</i>	Logical “or”; compound expression is true if <i>either exp1 or exp2</i> is true
<i>!exp</i>	Logical “not”; toggles the value of a logical expression from true to false and vice versa

Java Expressions

Precedence and associativity of operations discussed.

Operators	Associativity	Type
* / %	left to right	multiplicative
+ -	left to right	additive
< <= > >=	left to right	relational
== !=	left to right	equality
=	right to left	assignment

Flow-Control Structures


if Statements

```
if (condition) {  
    statements;  
}
```


```
if (condition) {  
    statements;  
} else {  
    statements;  
}
```

```
if (condition) {  
    statements;  
} else if (condition) {  
    statements;  
} else if (condition) {  
    statements;  
}
```

if statement
(single selection)




if...else statement
(double selection)



Flow-Control Structures

switch Statements

```
switch (condition) {  
    case ABC:  
        statements;  
        /* falls through */  
  
    case DEF:  
        statements;  
        break;  
  
    case XYZ:  
        statements;  
        break;  
  
    default:  
        statements;  
        break;  
}
```



Every time a case doesn't include a break statement add a comment where the break statement would normally be


Flow-Control Structures

for Statements

```
for (initialization; condition; update) {  
    statements;  
}
```

```
for (int i = 0; i < 5; i++) {  
    statements;  
}
```

code to execute as long as the
value of i remains less than 5




Flow-Control Structures

for Statements

```
while (condition) {  
    statements;  
}
```

```
do {  
    statements;  
} while (condition);
```



Anatomy of a Simple Java Program

```
//This program illustrates basic Java anatomy
```

```
//Package and import statements
```

```
public class SimpleProgram {
```

```
    public static void main(String[] args) {  
        System.out.println("Hello World");  
    }
```

```
}
```

→ **Beginning comments**

Types of comments

// end-of-line comments

/* Traditional comments */

Anatomy of a Simple Java Program

```
//This program illustrates basic Java anatomy
```

```
//Package and import statements
```

```
public class SimpleProgram {
```

```
    public static void main(String[] args) {  
        System.out.println("Hello World");  
    }
```

```
}
```



→ **Class Declaration**

Anatomy of a Simple Java Program

```
//This program illustrates basic Java anatomy  
  
//Package and import statements  
  
public class SimpleProgram {  
  
    public static void main(String[] args) {  
        System.out.println("Hello World");  
    }  
  
}
```

Main Method



Anatomy of a Simple Java Program

```
//This program illustrates basic Java anatomy  
  
//Package and import statements  
  
public class SimpleProgram {  
  
    public static void main(String[] args) {  
        System.out.println("Hello World");  
    }  
}
```



→ **main method begins execution of Java application**

Print to the Screen


System.out.print("text to print");

System.out.println("text to print");

Eclipse

Open the Java Perspective

If you're not already in the Java perspective, in the main menu select **Window > Open Perspective > Java** or click on the icon shown below.




A perspective is a way to organize and view the files associated with your program.

Eclipse

Create a Java Project


Before creating a class, we need a project to put it in. In the main toolbar, click on the **New Java Project button**



or select **File > New > Java Project**

The project name is any name you choose.


Your project will be created in the workspace associated with Eclipse.



Eclipse

Create your HelloWorld Class


Now, let's create a new class. In the main toolbar again, click on the **New Java Class button** (or select **File > New > Class**).



Another option is to add the class to the src folder by right-clicking on it in the Package Explorer as shown in the image.

Eclipse

Add a print statement and run your application



User input

```
Scanner sc = new Scanner(System.in);  
int i = sc.nextInt();  
  
System.out.println("The integer was "+i);
```



→ read user input from console

User input

```
Scanner sc = new Scanner(System.in);  
int i = sc.nextInt();  
  
System.out.println("The integer was "+i);
```

→ read an integer

```
Scanner sc = new Scanner(System.in);  
String line = sc.nextLine();  
  
System.out.println("The string was "+line);
```

→ read a string of characters


For more info:

<http://java.sun.com/javase/6/docs/api/java/util/Scanner.html>

Returning char values from a String

```
String word = "abcde";  
char c = word.charAt(3);  
  
System.out.println(c + "is the char at position 4");
```

→ **This method (function)** returns the char value at the specified index.



0	1	2	3	4
'a'	'b'	'c'	'd'	'e'


→ **Considers the index as an array**

Some Tips

- Javadoc

If you want to know more about existing classes check the documentation at:

<http://java.sun.com/javase/6/docs/api/overview-summary.html>



- Try the Firefox Javadoc Search Engine

<http://mycroft.mozdev.org/search-engines.html?name=javadoc>

Some Tips

- Eclipse – Autocomplete

CTR + SPACE is an autocompletion shortcut

- Type **sysout** and press **CTR + SPACE** (the autocompletion) and it will be automagically changed to **System.out.println();**
- Try it Typing **for** and you'll get a skeleton of a for loop.

- Eclipse – Keyboard Shortcuts.

Of course you know Ctrl+C and Ctrl+V, but how about

- **Ctrl+F11** to run the application
- **Ctrl+A** to select all text
- **Ctrl+i** to correct the Indentation

and if you don't remember a shortcut

- **Ctrl+Shift+L** to show the Kew assist

References

- J. Barker, *Beginning Java Objects: From Concepts To Code, Second Edition*, Apress, 2005.
- H.M. Deitel and P.J. Deitel, *Java How to Program: Early Objects Version*, Prentice Hall, 2009.
- Java SE Tutorials (Last Updated [5/27/2009](#)), which can be found at: <http://java.sun.com/docs/books/tutorial>
- Code Conventions for the Java Programming Language, available at <http://java.sun.com/docs/codeconv/CodeConventions.pdf>
- Eclipse Tutorial
 - Eclipse Cheat Sheets
 - <http://www.cs.umd.edu/eclipse/EclipseTutorial/project.html>