Codewars(Problem solvings)

1.

8 kyu **Are You Playing Banjo?**

☆ 948 186 92% of 12,110 84,301 of 213,110 MRodalgaard

1 Issue Reported

Python 3.11 VIM EMACS

Instructions Output

Create a function which answers the question "Are you playing banjo?".
If your name starts with the letter "R" or lower case "r", you are playing banjo!

The function takes a name as its only argument, and returns one of the following strings:

```
name + " plays banjo"
name + " does not play banjo"
```

Names given are always valid strings.

Solution

```python
def are_you_playing_banjo(name):
    if name[0] == "R" or name[0] == "r":
        return name + " plays banjo"
    else:
        return name + " does not play banjo"
```

2.

8 kyu **Reverse List Order**

☆ 249 92 90% of 4,485 26,215 of 60,966 cmgerber

Python 3.11

Instructions Output

In this kata you will create a function that takes in a list and returns a list with the reverse order.

Examples (Input -> Output)

```
* [1, 2, 3, 4]  -> [4, 3, 2, 1]
* [9, 2, 0, 7]  -> [7, 0, 2, 9]
```

Solution

```python
def reverse_list(l):
    'return a list with the reverse order of l'
    return list(reversed(l))
```

3. Americans are odd people: in their buildings, the first floor is actually the ground floor and there is no 13th floor (due to superstition). Write a function that given a floor in the american system returns the floor in the european system. With the 1st floor being replaced by the ground floor and the 13th floor being removed, the numbers move down to take their place. In case of above 13, they move down by two because there are two omitted numbers below them. Basements (negatives) stay the same as the universal level.

8 kyu **What's the real floor?**

☆ 268 103 90% of 4,178 16,959 of 50,027 acadet

Python 3.11

Instructions Output

Americans are odd people: in their buildings, the first floor is actually the ground floor and there is no 13th floor (due to superstition).

Write a function that given a floor in the american system returns the floor in the european system.

With the 1st floor being replaced by the ground floor and the 13th floor being removed, the numbers move down to take their place. In case of above 13, they move down by two because there are two omitted numbers below them.

Basements (negatives) stay the same as the universal level.

Solution

```python
def get_real_floor(n):
    # code here
    if n <= 0:
        return n
    elif n < 13:
        return n - 1
    else:
        return n - 2
```

4.

8 kyu **Grasshopper - Terminal game combat function**

☆ 194 69 91% of 3,988 14,233 of 46,236 rom4eg

Python 3.11

Instructions Output

Create a combat function that takes the player's current health and the amount of damage received, and returns the player's new health. Health can't be less than **0.**

FUNDAMENTALS

Solution

```python
def combat(health, damage):
    #your code here
    return max(0, health - damage)
```

Good Job! You may take your time to refactor/comment your solution. Submit when ready.

5.

8 kyu **Name Shuffler**

☆ 307 122 93% of 3,853 18,384 of 46,995 debri

Python 3.11

Instructions Output

Write a function that returns a string in which firstname is swapped with last name.

Example(Input --> Output)

```
"john McClane" --> "McClane john"
```

STRINGS FUNDAMENTALS

Solution

```python
def name_shuffler(str_):
    #your code here
    return " ".join(str_.split()[::-1])
```

Excellent! You may take your time to refactor/comment your solution. Submit when ready.

6.

7 kyu **Ones and Zeros**

☆ 1752 471 90% of 11,916 61,411 of 163,303 user4386369

3 Issues Reported

Python 3.11

Instructions Output

Given an array of ones and zeroes, convert the equivalent binary value to an integer.

Eg: `[0, 0, 0, 1]` is treated as `0001` which is the binary representation of `1`.

Examples:

```
Testing: [0, 0, 0, 1] ==> 1
Testing: [0, 0, 1, 0] ==> 2
Testing: [0, 1, 0, 1] ==> 5
Testing: [1, 0, 0, 1] ==> 9
Testing: [0, 0, 1, 0] ==> 2
Testing: [0, 1, 1, 0] ==> 6
Testing: [1, 1, 1, 1] ==> 15
Testing: [1, 0, 1, 1] ==> 11
```

Solution

```python
def binary_array_to_number(arr):
    return int("".join(map(str, arr)), 2)
```

Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

Sample Tests

```python
import codewars_test as test
from solution import binary_array_to_number

@test.describe("Fixed Tests")
def fixed_tests():
```

7.

7 kyu **Two to One**

☆ 2297 513 89% of 15,117 73,124 of 190,822 g964

Instructions Output

Take 2 strings `s1` and `s2` including only letters from `a` to `z`. Return a new **sorted** string (alphabetical ascending), the longest possible, containing distinct letters - each taken only once - coming from s1 or s2.

Examples:

```
a = "xyaabbbccccdefww"
b = "xxxxyyyyabklmopq"
longest(a, b) -> "abcdefklmopqwxy"

a = "abcdefghijklmnopqrstuvwxyz"
longest(a, a) -> "abcdefghijklmnopqrstuvwxyz"
```

FUNDAMENTALS

Python 3.11 VIM EMACS

Solution

```python
def longest(a1, a2):
    combined = a1 + a2
    unique_letters = set(combined)
    sorted_letters = sorted(unique_letters)
    return ''.join(sorted_letters)
```

Sample Tests

```python
@test.describe("longest")
def tests():
    @test.it("basic tests")
    def basics():
        test.assert_equals(longest("aretheyhere", "yestheyarehere"), "aehrsty")
        test.assert_equals(longest("loopingisfunbutdangerous", "lessdangerousthancoding"), "abcdefgh
```

8.

7 kyu **Remove the minimum**

☆ 1474 367 86% of 8,068 35,605 of 92,651 bkaes 1 Issue Reported

Instructions Output

Task

Given an array of integers, remove the smallest value. Do not mutate the original array/list. If there are multiple elements with the same value, remove the one with the lowest index. If you get an empty array/list, return an empty array/list.

Don't change the order of the elements that are left.

Examples

```
* Input: [1,2,3,4,5], output = [2,3,4,5]
* Input: [5,3,2,1,4], output = [5,3,2,4]
* Input: [2,2,1,2,1], output = [2,2,2,1]
```

LISTS ARRAYS FUNDAMENTALS

The community has spoken.
See the top three priorities that have been chosen by the community. Read the announcement

codewars

Python 3.11 VIM EMACS

Solution

```python
def remove_smallest(numbers):
    numbers = numbers.copy()

    if numbers:
        numbers.remove(min(numbers))

    return numbers
```

Sample Tests

```python
import codewars_test as test
from solution import remove_smallest
from numpy.random import randint

def randlist():
    return list(randint(400, size=randint(1, 10)))

@test.describe("Fixed Tests")
def fixed_tests():
```

SKIP UNLOCK SOLUTIONS DISCUSS (240) RESET TEST ATTEMPT

9.

Instructions Output

friends name in it.

If a name has exactly 4 letters in it, you can be sure that it has to be a friend of yours! Otherwise, you can be sure he's not...

```
Input = ["Ryan", "Kieran", "Jason", "Yous"]
Output = ["Ryan", "Yous"]

Input = ["Peter", "Stephen", "Joe"]
Output = []
```

Input strings will only contain letters.
Note: keep the original order of the names in the output.

FUNDAMENTALS

The community has spoken.
See the top three priorities that have been chosen by the community. Read the announcement

codewars

Solution

```
def friend(x):
    names = []
    for a in x:
        if len(a)==4:
            names.append(a)
    return names
```

Sample Tests

```
from solution import friend

@test.describe("Fixed Tests")
def fixed_tests():
    @test.it('Sample Test Cases')
    def sample_test_cases():
        test.assert_equals(friend(["Ryan", "Kieran", "Mark",]), ["Ryan", "Mark"])
        test.assert_equals(friend(["Ryan", "Jimmy", "abc", "d", "Cool Man"]), ["Ryan"])
        test.assert_equals(friend(["Jimm", "Cari", "aret", "truehdnviegkwgvke", "sixtyiscooooool"]),
```

SKIP UNLOCK SOLUTIONS DISCUSS (168) RESET TEST ATTEMPT

10.

8 kyu **Filter out the geese**

524 176 92% of 4,460 18,178 of 47,780 stevehopkinson

1 Issue Reported

Python 3.11 VIM EMACS

Instructions Output

Write a function that takes a list of strings as an argument and returns a filtered list containing the same elements but with the 'geese' removed.

The geese are any strings in the following array, which is pre-populated in your solution:

```
["African", "Roman Tufted", "Toulouse", "Pilgrim", "Steinbacher"]
```

For example, if this array were passed as an argument:

```
ok Bill", "African", "Crested", "Pilgrim", "Toulouse", "Blue Swedish"]
```

Your function would return the following array:

Solution

```
geese = ["African", "Roman Tufted", "Toulouse", "Pilgrim", "Steinbacher"]
def goose_filter(birds):
    return [bird for bird in birds if bird not in geese]
```

Sample Tests

```
from solution import goose_filter

@test.describe("Fixed Tests")
def fixed_tests():
    @test.it('Basic Test Cases')
    def basic_test_cases():
        test.assert_equals(goose_filter(["Mallard", "Hook Bill", "African", "Crested", "Pilgrim", "T
        test.assert_equals(goose_filter(["Mallard", "Barbary", "Hook Bill", "Blue Swedish", "Crestec
```

11.

8 kyu altERnaTIng cAsE <=> ALTerNAtiNG CaSe

☆ 852 242 90% of 5,514 25,982 of 73,935 donaldsebleung

2 Issues Reported

Instructions Output

altERnaTIng cAsE <=> ALTerNAtiNG CaSe

Define `String.prototype.toAlternatingCase` (or a similar function/method *such as* `to_alternating_case` / `toAlternatingCase` / `ToAlternatingCase` in your selected language; **see the initial solution for details**) such that each lowercase letter becomes uppercase and each uppercase letter becomes lowercase. For example:

```
"hello world".toAlternatingCase() === "HELLO WORLD"
"HELLO WORLD".toAlternatingCase() === "hello world"
"hello WORLD".toAlternatingCase() === "HELLO world"
"HeLLo WoRLD".toAlternatingCase() === "hEllO wOrld"
"12345".toAlternatingCase()       === "12345"                    // Non
"1a2b3c4d5e".toAlternatingCase()  === "1A2B3C4D5E"
"String.prototype.toAlternatingCase".toAlternatingCase() === "sTRING.PI
```

8 Reasons Why Codewarriors Practice

Python 3.11 VIM EMACS

Solution

```
def to_alternating_case(string):
    return string.swapcase()
```

Sample Tests

```
        test.assert_equals(to_alternating_case("String.prototype.toAlternatingCase"), "sTRING.PROTOTY
        test.assert_equals(to_alternating_case(to_alternating_case("Hello World")), "Hello World")


    @test.it("should work for the title of this Kata")
    def test_title():
        title = "altERnaTIng cAsE"
        title = to_alternating_case(title)
        test.assert_equals(title, "ALTerNAtiNG CaSe")
```

12.

8 kyu Drink about

☆ 257 82 90% of 4,069 19,580 of 57,079 darlanmendonca

Instructions Output

- Kids drink toddy.
- Teens drink coke.
- Young adults drink beer.
- Adults drink whisky.

Make a function that receive age, and return what they drink.

Rules:

- Children under 14 old.
- Teens under 18 old.
- Young under 21 old.
- Adults have 21 or more.

Examples: (Input --> Output)

8 Reasons Why Codewarriors Practice Coding with Codewars

Python 3.11 VIM EMACS

Solution

```
def people_with_age_drink(age):
    if age < 14:
        return "drink toddy"
    elif age < 18:
        return "drink coke"
    elif age < 21:
        return "drink beer"
    else:
        return "drink whisky"
```

Sample Tests

```
import codewars_test as test
from solution import people_with_age_drink

@test.describe("Fixed Tests")
def fixed_tests():
    @test.it("should return 'drink toddy' when age is less than 14")
    def _():
        test.assert_equals(people_with_age_drink(13), 'drink toddy', "Wrong result for 13")
        test.assert_equals(people_with_age_drink(0), 'drink toddy', "Wrong result for 0")
```

13.

Heads Up! Unlock the full potential of your account – confirm your email to enable the full dojo experience!

8 kyu **L1: Set Alarm**

☆ 475 103 90% of 7,415 36,367 of 119,332 Swolebrain

Python 3.11 VIM EMACS

Instructions Output

Write a function named `setAlarm` / `set_alarm` / `set-alarm` / `setalarm` (depending on language) which receives two parameters. The first parameter, `employed`, is true whenever you are employed and the second parameter, `vacation` is true whenever you are on vacation.

The function should return true if you are employed and not on vacation (because these are the circumstances under which you need to set an alarm). It should return false otherwise. Examples:

```
employed | vacation
true     | true     => false
true     | false    => true
false    | true     => false
false    | false    => false
```

Quick Start Guide: Golang for Beginners
Ever asked yourself, "What's the point of learning Go?" Here's a guide to explain it all.

codewars

Solution

```python
def set_alarm(employed, vacation):
    return employed and not vacation
```

Sample Tests

```python
import codewars_test as test
from solution import set_alarm

@test.describe("Fixed Tests")
def fixed_tests():
    @test.it('Basic Test Cases')
    def basic_test_cases():
        test.assert_equals(set_alarm(True, True), False, "Fails when input is True, True")
        test.assert_equals(set_alarm(False, True), False, "Fails when input is False, True")
```

SKIP UNLOCK SOLUTIONS DISCUSS (43) RESET TEST ATTEMPT

14.

7 kyu **Anagram Detection**

☆ 594 197 93% of 4,080 16,785 of 54,768 user3793153

1 Issue Reported

Python 3.11 VIM EMACS

Instructions Output

An **anagram** is the result of rearranging the letters of a word to produce a new word (see wikipedia).

Note: anagrams are case insensitive

Complete the function to return `true` if the two arguments given are anagrams of each other; return `false` otherwise.

Examples

- `"foefet"` is an anagram of `"toffee"`
- `"Buckethead"` is an anagram of `"DeathCubeK"`

STRINGS FUNDAMENTALS

8 Reasons Why Codewarriors Practice Coding with Codewars
Not everyone trains the same. Discover new ways to leverage Codewars in your education and career.

codewars

Solution

```python
# write the function is_anagram
def is_anagram(test, original):
    return sorted(test.lower()) == sorted(original.lower())
```

Sample Tests

```python
import codewars_test as test
from solution import is_anagram

@test.describe("Fixed Tests")
def fixed_tests():
    @test.it('Basic Test Cases')
    def basic_test_cases():
        test.assert_equals(is_anagram("foefet", "toffee"), True, 'The word foefet is an anagram of to
        test.assert_equals(is_anagram("Buckethead", "DeathCubeK"), True, 'The word Buckethead is an a
```

SKIP UNLOCK SOLUTIONS DISCUSS (81) RESET TEST ATTEMPT

15.

8 kyu **Remove String Spaces**

1615 438 91% of 17,201 91,929 of 297,695 PG1

Instructions Output

Write a function that removes the spaces from the string, then return the resultant string.

Examples (**Input -> Output**):

```
"8 j 8   mBliB8g  imjB8B8  jl  B" -> "8j8mBliB8gimjB8B8jlB"
"8 8 Bi fk8h B 8 BB8B B B  B888 c hl8 BhB fd" -> "88Bifk8hB8BB8BBBB888cl
"8aaaaa dddd r     " -> "8aaaaaddddr"
```

Python 3.11

Solution

```python
def no_space(x):
    #your code here
    return x.replace(" ", "")
```

Correctamundo! You may take your time to refactor/comment your solution. Submit when ready.

16.

8 kyu **Simple multiplication**

686 104 92% of 10,923 63,011 of 212,123 grace555

2 Issues Reported

Instructions Output

This kata is about multiplying a given number by eight if it is an even number and by nine otherwise.

FUNDAMENTALS

Python 3.11

Solution

```python
def simple_multiplication(number) :
    # Your code goes here
    if number % 2 == 0:
        return number * 8
    else:
        return number * 9
```

Impressive! You may take your time to refactor/comment your solution. Submit when ready.

17.

8 kyu **Third Angle of a Triangle**

318 118 86% of 7,510 37,017 of 125,114 user5651159

2 Issues Reported

Instructions Output

You are given two interior angles (in degrees) of a triangle.

Write a function to return the 3rd.

Note: only positive integers will be tested.

https://en.wikipedia.org/wiki/Triangle

FUNDAMENTALS

Python 3.11

Solution

```
def other_angle(a, b):
    return 180 - a - b
```

Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

18.

8 kyu **Function 1 - hello world**

1195 170 83% of 16,046 93,332 of 308,151 ineiti 1 Issue Reported

Instructions Output

Make a simple function called `greet` that returns the most-famous "hello world!".

Style Points

Sure, this is about as easy as it gets. But how clever can you be to create the most creative "hello world" you can think of? What is a "hello world" solution you would want to show your friends?

FUNDAMENTALS

Python 3.11

Solution

```
# Write a function `greet` that returns "hello world!"
def greet():
    return 'hello world!'
```

Excellent! You may take your time to refactor/comment your solution. Submit when ready.

19.

7 kyu **Mumbling**

3744 890 91% of 21,335 86,191 of 254,826 g964

Instructions Output

This time no story, no theory. The examples below show you how to write function `accum`:

Examples:

```
accum("abcd") -> "A-Bb-Ccc-Dddd"
accum("RqaEzty") -> "R-Qq-Aaa-Eeee-Zzzzz-Tttttt-Yyyyyyy"
accum("cwAt") -> "C-Ww-Aaa-Tttt"
```

The parameter of accum is a string which includes only letters from `a..z` and `A..Z`.

Python 3.11

Solution

```python
def accum(st):
    result = []

    for i, char in enumerate(st):
        result.append(char.upper() + char.lower() * i)

    return "-".join(result)
```

Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

Sample Tests

20.

7 kyu **Odd or Even?**

707 250 92% of 10,218 55,714 of 160,312 ethaning 2 Issues Reported

Instructions Output

Task:

Given a list of integers, determine whether the sum of its elements is odd or even.

Give your answer as a string matching `"odd"` or `"even"`.

If the input array is empty consider it as: `[0]` (array with a zero).

Examples:

```
Input: [0]
Output: "even"

Input: [0, 1, 4]
Output: "odd"
```

Python 3.11

Solution

```python
def odd_or_even(arr):
    return "even" if sum(arr) % 2 == 0 else "odd"
```

Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

Sample Tests

```python
import codewars_test as test
from solution import odd_or_even

@test.describe("Fixed Tests")
def fixed_tests():
```