

Phil/LPS 31 Introduction to Inductive Logic

Lecture 5

David Mwakima

dmwakima@uci.edu

Department of Logic and Philosophy of Science
University of California, Irvine

April 12th 2023

Topics

- ▶ Inference in Quantified Relational Logic
- ▶ Models
- ▶ Witnesses and Counterexamples
- ▶ The Rules of Quantified Relational Logic are truth-preserving
- ▶ Tying things up

Inference in Quantified Relational Logic

- ▶ The goal is to say why this argument in quantified relational logic is valid.

1. All logicians are wise.
2. Ruth Barcan Marcus is a logician.

∴ 3. Ruth Barcan Marcus is wise.

Inference in Quantified Relational Logic

- ▶ The goal is to say why this argument in quantified relational logic is valid.

1. All logicians are wise.
2. Ruth Barcan Marcus is a logician.

∴ 3. Ruth Barcan Marcus is wise.

- ▶ So we need to discuss the mechanics of inference in quantified relational logic.

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.
- ▶ For each of these formulas: what is the scope of each quantifier? Provide an instance of each formula.

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.
- ▶ For each of these formulas: what is the scope of each quantifier? Provide an instance of each formula.

1 $\exists x Gx$

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.
- ▶ For each of these formulas: what is the scope of each quantifier? Provide an instance of each formula.
 - 1 $\exists x Gx$
 - 2 $\forall x \neg Gx$

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.
- ▶ For each of these formulas: what is the scope of each quantifier? Provide an instance of each formula.
 - 1 $\exists x Gx$
 - 2 $\forall x \neg Gx$
 - 3 $\forall x (\neg Qx \rightarrow \exists y Sxy)$

Inference in Quantified Relation Logic

- ▶ In order to do inference in quantified relational logic we need the notions of (1) the **scope of a quantifier** and (2) an **instance** of a formula in quantified relational logic.
- ▶ The **scope of quantifier** are all the free variables, which it binds, in a formula.
- ▶ An **instance** of a formula in quantified relational logic is a formula that is obtained by freeing a bound variable within the scope of a quantifier and **uniformly replacing** every occurrence of this free variable by a constant.
- ▶ For each of these formulas: what is the scope of each quantifier? Provide an instance of each formula.
 - 1 $\exists x Gx$
 - 2 $\forall x \neg Gx$
 - 3 $\forall x (\neg Qx \rightarrow \exists y Sxy)$
 - 4 $\forall x \forall y (Lxy \rightarrow \exists z (Lxz \wedge Lzy))$

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Rule 1. All the truth-preserving rules of inference covered in sentential logic are truth-preserving rules of inference in quantified relational logic.

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Rule 1. All the truth-preserving rules of inference covered in sentential logic are truth-preserving rules of inference in quantified relational logic.

Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Rule 1. All the truth-preserving rules of inference covered in sentential logic are truth-preserving rules of inference in quantified relational logic.

Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.

- ▶ Here is an example of an inference that uses Existential Generalization:

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Rule 1. All the truth-preserving rules of inference covered in sentential logic are truth-preserving rules of inference in quantified relational logic.

Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.

- ▶ Here is an example of an inference that uses Existential Generalization:
 1. Hypatia is wise. *Wh*

Inference in Quantified Relational Logic

- ▶ Finally we can state the inference rules of quantified relational logic which turn it into a deductive logic.

Rule 1. All the truth-preserving rules of inference covered in sentential logic are truth-preserving rules of inference in quantified relational logic.

Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.

- ▶ Here is an example of an inference that uses Existential Generalization:

1. Hypatia is wise. Wh
- \therefore 2. Someone is wise. $\exists xWx$ (From 1 and By Existential Generalization)

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Inference in Quantified Relational Logic

► Inference rules continued from previous slide:

Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:
Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**
- ▶ Here is an example of an inference that uses Universal Instantiation.

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:
Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**
- ▶ Here is an example of an inference that uses Universal Instantiation.
 1. All logicians are wise. $\forall x(Lx \rightarrow Wx)$

Inference in Quantified Relational Logic

- Inference rules continued from previous slide:

Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**

- Here is an example of an inference that uses Universal Instantiation.

1. All logicians are wise. $\forall x(Lx \rightarrow Wx)$
- ∴ 2. If Ruth Barcan Marcus is a logician, then she is wise.
($La \rightarrow Wa$) (From 1 and By Universal Instantiation)

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Inference in Quantified Relational Logic

- Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- ▶ Here is an example of **Existential Supposition**:

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- ▶ Here is an example of **Existential Supposition**:
 1. Someone is wise. $\exists xWx$

Inference in Quantified Relational Logic

- Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- Here is an example of **Existential Supposition**:

1. Someone is wise. $\exists xWx$
2. Suppose Cavendish is wise. Wc (From 1. and Existential Supposition)

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- ▶ Here is an example of **Existential Supposition**:

1. Someone is wise. $\exists xWx$
2. Suppose Cavendish is wise. Wc (From 1. and Existential Supposition)
3. Wise people use logic. (Additional Premise)

Inference in Quantified Relational Logic

- Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- Here is an example of **Existential Supposition**:

1. Someone is wise. $\exists xWx$
2. Suppose Cavendish is wise. Wc (From 1. and Existential Supposition)
3. Wise people use logic. (Additional Premise)
- ∴ 4. Cavendish uses logic. (G)

Inference in Quantified Relational Logic

- ▶ Inference rules continued from previous slide:

Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**. This rule is known as **Existential Supposition**.

- ▶ Here is an example of **Existential Supposition**:

1. Someone is wise. $\exists xWx$
2. Suppose Cavendish is wise. Wc (From 1. and Existential Supposition)
3. Wise people use logic. (Additional Premise)
- ∴ 4. Cavendish uses logic. (G)

- ▶ These are the only truth-preserving rules of inference that we will avail for ourselves in quantified relational logic but other rules of inference can be derived from these.

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$
 - \therefore 2. Not everyone is wise. $\neg \forall x Wx$

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$
 - ∴ 2. Not everyone is wise. $\neg \forall x Wx$
- ▶ And

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$
 - ∴ 2. Not everyone is wise. $\neg \forall x Wx$
- ▶ And
 1. Not everyone is wise. $\neg \forall x Wx$

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$
 - \therefore 2. Not everyone is wise. $\neg \forall x Wx$
- ▶ And
 1. Not everyone is wise. $\neg \forall x Wx$
 - \therefore 2. Someone is not wise. $\exists x \neg Wx$

Inference in Quantified Relational Logic

- ▶ For example, although many authors include a rule for **Universal Generalization** corresponding to the rule for **Existential Generalization**, we shall not do so here.
- ▶ Here's the brief answer why. It can be shown that for any formula \mathcal{F} in which x is free, $\exists x \neg \mathcal{F}$ is logically equivalent to $\neg \forall x \mathcal{F}$ in classical logic.
- ▶ To see why, think about this logical equivalence with actual English sentences.
 1. Someone is not wise. $\exists x \neg Wx$
 - \therefore 2. Not everyone is wise. $\neg \forall x Wx$
- ▶ And
 1. Not everyone is wise. $\neg \forall x Wx$
 - \therefore 2. Someone is not wise. $\exists x \neg Wx$
- ▶ So combining the first and second arguments we can conclude that something is not wise if and only if not everything is wise, i.e., $(\exists x \neg Wx \leftrightarrow \neg \forall x Wx)$

Inference in Quantified Relational Logic

- **Useful Equivalence:** For any formula \mathcal{F} in which x is free:

$$\boxed{(\neg \exists x \neg \mathcal{F} \leftrightarrow \forall x \mathcal{F})}$$

is a theorem of quantified relational logic.

Inference in Quantified Relational Logic

- **Useful Equivalence:** For any formula \mathcal{F} in which x is free:

$$\boxed{(\neg \exists x \neg \mathcal{F} \leftrightarrow \forall x \mathcal{F})}$$

is a theorem of quantified relational logic.

- So, to infer the Universal Generalization, $\forall x \mathcal{F}$, here are the steps.

Inference in Quantified Relational Logic

- **Useful Equivalence:** For any formula \mathcal{F} in which x is free:

$$\boxed{(\neg \exists x \neg \mathcal{F} \leftrightarrow \forall x \mathcal{F})}$$

is a theorem of quantified relational logic.

- So, to infer the Universal Generalization, $\forall x \mathcal{F}$, here are the steps.
 1. Use Existential Supposition with $\exists x \neg \mathcal{F}$.

Inference in Quantified Relational Logic

- **Useful Equivalence:** For any formula \mathcal{F} in which x is free:

$$\boxed{(\neg \exists x \neg \mathcal{F} \leftrightarrow \forall x \mathcal{F})}$$

is a theorem of quantified relational logic.

- So, to infer the Universal Generalization, $\forall x \mathcal{F}$, here are the steps.
 1. Use Existential Supposition with $\exists x \neg \mathcal{F}$.
 2. If you can show that $(\mathcal{F}(a) \wedge \neg \mathcal{F}(a))$, **which is contradictory**, then you can conclude $\neg \exists x \neg \mathcal{F}$, i.e., that your supposition is false.

Inference in Quantified Relational Logic

- **Useful Equivalence:** For any formula \mathcal{F} in which x is free:

$$\boxed{(\neg \exists x \neg \mathcal{F} \leftrightarrow \forall x \mathcal{F})}$$

is a theorem of quantified relational logic.

- So, to infer the Universal Generalization, $\forall x \mathcal{F}$, here are the steps.
 1. Use Existential Supposition with $\exists x \neg \mathcal{F}$.
 2. If you can show that $(\mathcal{F}(a) \wedge \neg \mathcal{F}(a))$, **which is contradictory**, then you can conclude $\neg \exists x \neg \mathcal{F}$, i.e., that your supposition is false.
 3. Infer $\forall x \mathcal{F}$ using the Useful Equivalence.

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.
 2. $\neg\forall x(Tx \rightarrow Sx)$ is equivalent to $\exists x(Tx \wedge \neg Sx)$ by **Useful Equivalence** and $((\mathcal{F} \rightarrow \mathcal{G}) \leftrightarrow \neg(\mathcal{F} \wedge \neg\mathcal{G}))$

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.
 2. $\neg\forall x(Tx \rightarrow Sx)$ is equivalent to $\exists x(Tx \wedge \neg Sx)$ by **Useful Equivalence** and $((\mathcal{F} \rightarrow \mathcal{G}) \leftrightarrow \neg(\mathcal{F} \wedge \neg\mathcal{G}))$
 3. From 2., suppose $(Ta \wedge \neg Sa)$ by Existential Supposition.

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.
 2. $\neg\forall x(Tx \rightarrow Sx)$ is equivalent to $\exists x(Tx \wedge \neg Sx)$ by **Useful Equivalence** and $((\mathcal{F} \rightarrow \mathcal{G}) \leftrightarrow \neg(\mathcal{F} \wedge \neg\mathcal{G}))$
 3. From 2., suppose $(Ta \wedge \neg Sa)$ by Existential Supposition.
 4. From 3. we can infer Ta . But Ta implies Sa . (By definition of tautology and satisfiable)

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.
 2. $\neg\forall x(Tx \rightarrow Sx)$ is equivalent to $\exists x(Tx \wedge \neg Sx)$ by **Useful Equivalence** and $((\mathcal{F} \rightarrow \mathcal{G}) \leftrightarrow \neg(\mathcal{F} \wedge \neg\mathcal{G}))$
 3. From 2., suppose $(Ta \wedge \neg Sa)$ by Existential Supposition.
 4. From 3. we can infer Ta . But Ta implies Sa . (By definition of tautology and satisfiable)
 5. But from line 3 and 4 this means we have $(Sa \wedge \neg Sa)$, which is a contradiction.

Inference in Quantified Relational Logic

- ▶ An example of Universal Generalization. We want to show that every tautology is satisfiable, i.e., $\forall x(Tx \rightarrow Sx)$. Here Tx paraphrases “ x is a tautology” and Sx paraphrases “ x is satisfiable.”
- ▶ Here's how we show it.
 1. Suppose $\neg\forall x(Tx \rightarrow Sx)$.
 2. $\neg\forall x(Tx \rightarrow Sx)$ is equivalent to $\exists x(Tx \wedge \neg Sx)$ by **Useful Equivalence** and $((\mathcal{F} \rightarrow \mathcal{G}) \leftrightarrow \neg(\mathcal{F} \wedge \neg\mathcal{G}))$
 3. From 2., suppose $(Ta \wedge \neg Sa)$ by Existential Supposition.
 4. From 3. we can infer Ta . But Ta implies Sa . (By definition of tautology and satisfiable)
 5. But from line 3 and 4 this means we have $(Sa \wedge \neg Sa)$, which is a contradiction.
 6. So $\neg\neg\forall x(Tx \rightarrow Sx)$, which is logically equivalent to $\forall x(Tx \rightarrow Sx)$.

Models: Sentential Logic

- ▶ We know why the truth-preserving rules of sentential logic are truth-preserving. But since \exists and \forall are **not truth-functional** we cannot use truth tables to check whether the rules of inference given above are truth-preserving.

Models: Sentential Logic

- ▶ We know why the truth-preserving rules of sentential logic are truth-preserving. But since \exists and \forall are **not truth-functional** we cannot use truth tables to check whether the rules of inference given above are truth-preserving.
- ▶ So, in order to say why the rule **Existential Generalization**, the rule **Universal Instantiation** and the rule **Existential Supposition** are truth-preserving rules of inference, we need to discuss the semantics, interpretation or meaning of **sentences** in quantified relational logic.

Models: Sentential Logic

- ▶ We know why the truth-preserving rules of sentential logic are truth-preserving. But since \exists and \forall are **not truth-functional** we cannot use truth tables to check whether the rules of inference given above are truth-preserving.
- ▶ So, in order to say why the rule **Existential Generalization**, the rule **Universal Instantiation** and the rule **Existential Supposition** are truth-preserving rules of inference, we need to discuss the semantics, interpretation or meaning of **sentences** in quantified relational logic.
- ▶ This will require a tool which we will call a **model** or **intended interpretation** of some **sentences** in quantified relational logic.

Models: Sentential Logic

- ▶ We know why the truth-preserving rules of sentential logic are truth-preserving. But since \exists and \forall are **not truth-functional** we cannot use truth tables to check whether the rules of inference given above are truth-preserving.
- ▶ So, in order to say why the rule **Existential Generalization**, the rule **Universal Instantiation** and the rule **Existential Supposition** are truth-preserving rules of inference, we need to discuss the semantics, interpretation or meaning of **sentences** in quantified relational logic.
- ▶ This will require a tool which we will call a **model** or **intended interpretation** of some **sentences** in quantified relational logic.
- ▶ I emphasize the word **sentence** because truth and falsity are properties of sentences, not formulas. A sentence in quantified relational logic is a formula with **no free variables** (Definition).

Models: Sentential Logic

- ▶ In sentential logic, the model for the formulas was a truth function which took as input the truth value of the simple sentences in the formulas and returned a truth value 1 or 0.

Models: Sentential Logic

- ▶ In sentential logic, the model for the formulas was a truth function which took as input the truth value of the simple sentences in the formulas and returned a truth value 1 or 0.
- ▶ In the model, the truth value of p is 1 if p is true and 0 if p is false. Similarly in the model, the truth value of $\neg p$ is 0 if p is true and 1 if p is false. And so on for the other formulas formed using the rest of the truth functional connectives.

Models: Sentential Logic

- ▶ In sentential logic, the model for the formulas was a truth function which took as input the truth value of the simple sentences in the formulas and returned a truth value 1 or 0.
- ▶ In the model, the truth value of p is 1 if p is true and 0 if p is false. Similarly in the model, the truth value of $\neg p$ is 0 if p is true and 1 if p is false. And so on for the other formulas formed using the rest of the truth functional connectives.
- ▶ Thus, the model for sentential logic can be visualized as a table, which specifies **the truth value conditions** of the sentences in sentential logic. This is the powerful idea behind **Tarski's definition of truth for formalized languages**, which influenced **truth conditional semantics** in philosophy, where we think of **the actual world** as a model for a natural language like English.

Models: Sentential Logic

Formula	Truth value conditions
(F)	1 if F is true; 0 otherwise.
$(\neg F)$	1 if F is false, 0 otherwise.
$(F \wedge G)$	1 if both F and G are true, 0 otherwise.
$(F \vee G)$	0 if both F and G are false, 1 otherwise.
$(F \rightarrow G)$	1 if either F is false or G is true; 0 otherwise.
$(F \leftrightarrow G)$	1 if truth value of $F =$ truth value of G ; 0 otherwise.

Models: Quantified Relational Logic

- ▶ Since quantified relational logic formalizes natural language to reveal more grammatical or internal structure, namely, proper names for individuals or terms and relations between these terms (in the right order); a model for quantified relational logic will necessarily be more complex.

Models: Quantified Relational Logic

- ▶ Since quantified relational logic formalizes natural language to reveal more grammatical or internal structure, namely, proper names for individuals or terms and relations between these terms (in the right order); a model for quantified relational logic will necessarily be more complex.
- ▶ But the idea is the same as the model for sentential logic. We will specify the truth value conditions for sentences in quantified relational logic. Importantly, the truth conditions **for truth functional connectives** in sentential logic **carry over**.

Models: Quantified Relational Logic

- ▶ Since quantified relational logic formalizes natural language to reveal more grammatical or internal structure, namely, proper names for individuals or terms and relations between these terms (in the right order); a model for quantified relational logic will necessarily be more complex.
- ▶ But the idea is the same as the model for sentential logic. We will specify the truth value conditions for sentences in quantified relational logic. Importantly, the truth conditions **for truth functional connectives** in sentential logic **carry over**.
- ▶ But! The **crucial difference** now is that we add more structure to the model in order to account for (1) terms, (2) predicates and relations, (3) the order in which the terms stand in various relations and (4) quantifiers.

Models and Counterexamples: Quantified Relational Logic

- ▶ To account for terms we introduce the notion of a **domain** or **universe of discourse**, \mathcal{U} .

Models and Counterexamples: Quantified Relational Logic

- ▶ To account for terms we introduce the notion of a **domain** or **universe of discourse**, \mathcal{U} .
- ▶ To account for relations we introduce the notion of an **extension**.

Models and Counterexamples: Quantified Relational Logic

- ▶ To account for terms we introduce the notion of a **domain** or **universe of discourse**, \mathcal{U} .
- ▶ To account for relations we introduce the notion of an **extension**.
- ▶ If P is a predicate symbol in quantified relational logic, the extension of P is a **set** of those terms to which the predicate applies. We write this set as $[P] = \{a \in \mathcal{U} \mid Pa\}$ “The set of those a 's in \mathcal{U} that are P ”

Models and Counterexamples: Quantified Relational Logic

- ▶ To account for terms we introduce the notion of a **domain** or **universe of discourse**, \mathcal{U} .
- ▶ To account for relations we introduce the notion of an **extension**.
- ▶ If P is a predicate symbol in quantified relational logic, the extension of P is a **set** of those terms to which the predicate applies. We write this set as $[P] = \{a \in \mathcal{U} \mid Pa\}$ “The set of those a ’s in \mathcal{U} that are P ”
- ▶ If R is a relation, the extension of R is a set of **ordered pairs** of terms that stand in that relation to each other or themselves. We write this set $[R] = \{ \langle a, b \rangle \text{ for } a, b \in \mathcal{U} \mid Rab \}$ “The set of those a ’s and b ’s in \mathcal{U} such that Rab ”

Models and Counterexamples: Quantified Relational Logic

- ▶ To account for terms we introduce the notion of a **domain** or **universe of discourse**, \mathcal{U} .
- ▶ To account for relations we introduce the notion of an **extension**.
- ▶ If P is a predicate symbol in quantified relational logic, the extension of P is a **set** of those terms to which the predicate applies. We write this set as $[P] = \{a \in \mathcal{U} \mid Pa\}$ “The set of those a ’s in \mathcal{U} that are P ”
- ▶ If R is a relation, the extension of R is a set of **ordered pairs** of terms that stand in that relation to each other or themselves. We write this set $[R] = \{ \langle a, b \rangle \text{ for } a, b \in \mathcal{U} \mid Rab \}$ “The set of those a ’s and b ’s in \mathcal{U} such that Rab ”
- ▶ To account for $\forall x\mathcal{F}$ we consider **every** x -variant \mathcal{F}' of \mathcal{F} and to account for $\exists x\mathcal{F}$ we consider **some** x -variant \mathcal{F}' of \mathcal{F} (Soon to be made precise).

Models: Quantified Relational Logic

Finally we can specify **the form of an interpretation or model** of quantified relational logic. The form of every model of some sentences in quantified relational logic will have two things: (1) the **interpretation of symbols** and (2) the **truth conditions** of sentences in the model.

Symbols	Interpretation
Constant	Term in the universe of discourse
Predicate, P	$[P] = \{a \in \mathcal{U} \mid Pa\}$
Relation, R	$[R] = \{ \langle a, b \rangle \text{ for } a, b \in \mathcal{U} \mid Rab \}$

Sentence	Truth value conditions in the model
Pa	1 if $a \in [P]$, 0 otherwise.
Rab	1 if $\langle a, b \rangle \in [R]$, 0 otherwise.
$\exists x \mathcal{F}$	1 if for some x -variant \mathcal{F}' of \mathcal{F} , the truth value of \mathcal{F}' is 1.
$\forall x \mathcal{F}$	1 if for every x -variant \mathcal{F}' of \mathcal{F} , the truth value of \mathcal{F}' is 1.

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:
 1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:
 1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$

Models: Quantified Relational Logic

- Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

1. *Lab* "a is larger than b."

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

1. Lab "a is larger than b."
2. Lbc "b is larger than c."

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

1. Lab "a is larger than b."
2. Lbc "b is larger than c."
3. Wca "c is west of a."

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

1. Lab " a is larger than b ."
2. Lbc " b is larger than c ."
3. Wca " c is west of a ."
4. $\exists x Lbx$ "There exists an x such that b is larger than x ."

Models: Quantified Relational Logic

- ▶ Here is an example of how we use models to check whether sentences in quantified relational logic are true **in a model**. The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$

- ▶ Determine whether the following sentences are true in the model:

1. Lab " a is larger than b ."
2. Lbc " b is larger than c ."
3. Wca " c is west of a ."
4. $\exists x Lbx$ "There exists an x such that b is larger than x ."
5. $\exists y Wyc$ "Some y is west of c ."

Models: Quantified Relational Logic

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Determine whether the following sentences are true in the model (Continued from previous slide):

Models: Quantified Relational Logic

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Determine whether the following sentences are true in the model (Continued from previous slide):
6. $\forall x Lax$ "a is larger than every x"

Models: Quantified Relational Logic

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Determine whether the following sentences are true in the model (Continued from previous slide):
6. $\forall x Lax$ "a is larger than every x"
 7. $\exists y Wyb$ "Some y is west of b"

Models: Quantified Relational Logic

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Determine whether the following sentences are true in the model (Continued from previous slide):
6. $\forall x Lax$ "a is larger than every x"
 7. $\exists y Wyb$ "Some y is west of b"
 8. $\forall x \exists y (Lxy \wedge Wyx)$ "For every x some y is larger than x and y is west of x."

Models: Quantified Relational Logic

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York, } b = \text{Los Angeles, } c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Determine whether the following sentences are true in the model (Continued from previous slide):
6. $\forall x Lax$ "a is larger than every x"
 7. $\exists y Wyb$ "Some y is west of b"
 8. $\forall x \exists y (Lxy \wedge Wyx)$ "For every x some y is larger than x and y is west of x."
 9. $\exists x \forall y (Lxy \wedge Wyx)$ "There is an x such that x is larger than every y and y is west of x."

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Consider (4) $\exists x Lbx$. We said that (4) is true because for some x -variant of Lbx , $\langle b, c \rangle \in [L]$, i.e., “Los Angeles is larger than Chicago”. The term $c = \text{Chicago}$ here is called a **witness** of the **existentially quantified** sentence $\exists x Lbx$.

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Find a witness for (5) $\exists y Wyc$.

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- ▶ Find a witness for (5) $\exists y W_{yc}$.
 - ▶ Is there a witness for (7) $\exists y W_{yb}$?

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- ▶ Find a witness for (5) $\exists y W_{yc}$.
 - ▶ Is there a witness for (7) $\exists y W_{yb}$?
 - ▶ Is there a witness for (9) $\exists x \forall y (L_{xy} \wedge W_{yx})$?

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Consider (5) $\forall x(Lax)$. We said this sentence is false because for some x -variant of Lax , $\langle a, a \rangle \notin [L]$, i.e., “New York is not larger than New York”. The term $a = \text{New York}$ here is called a **counterexample** of the **universally quantified** sentence $\forall xLax$.

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- Find a counterexample for $\forall x Wxa$

Models: Witnesses and Counterexamples

The model is:

1. $\mathcal{U} = \{ \text{New York, Los Angeles, Chicago} \}$
 2. $a = \text{New York}, b = \text{Los Angeles}, c = \text{Chicago}$
 3. $[L] = \{ \langle \text{New York, Los Angeles} \rangle, \langle \text{New York, Chicago} \rangle, \langle \text{Los Angeles, Chicago} \rangle \}$
 4. $[W] = \{ \langle \text{Los Angeles, Chicago} \rangle, \langle \text{Los Angeles, New York} \rangle, \langle \text{Chicago, New York} \rangle \}$
- ▶ Find a counterexample for $\forall x Wxa$
 - ▶ Is there a counterexample for (8) $\forall x \exists y (Lxy \wedge Wyx)$ "For every x there is some y that is larger than x and y is west of x ."?

Models: Witnesses and Counterexamples

- ▶ The case of (9) $\exists x \forall y (Lxy \wedge Wyx)$ and (10) $\exists x \exists y (Lxy \wedge Wyx)$ illustrate something important. (10) is true because we just need to find **at least one** witness; $(Lab \wedge Wba)$ is a witness. But (9) is false because we have to verify that there are **no counterexamples**. So we had to check **every** y -variant of $(Lay \wedge Wya)$ including $(Laa \wedge Waa)$, which is a counterexample.

Models: Witnesses and Counterexamples

- ▶ The case of (9) $\exists x \forall y (Lxy \wedge Wyx)$ and (10) $\exists x \exists y (Lxy \wedge Wyx)$ illustrate something important. (10) is true because we just need to find **at least one** witness; $(Lab \wedge Wba)$ is a witness. But (9) is false because we have to verify that there are **no counterexamples**. So we had to check **every** y -variant of $(Lay \wedge Wya)$ including $(Laa \wedge Waa)$, which is a counterexample.
- ▶ In general a **witness** to an **existentially** quantified sentence is a term in the domain that makes the sentence **true**.

Models: Witnesses and Counterexamples

- ▶ The case of (9) $\exists x\forall y(Lxy \wedge Wyx)$ and (10) $\exists x\exists y(Lxy \wedge Wyx)$ illustrate something important. (10) is true because we just need to find **at least one** witness; $(Lab \wedge Wba)$ is a witness. But (9) is false because we have to verify that there are **no counterexamples**. So we had to check **every** y -variant of $(Lay \wedge Wya)$ including $(Laa \wedge Waa)$, which is a counterexample.
- ▶ In general a **witness** to an **existentially** quantified sentence is a term in the domain that makes the sentence **true**.
- ▶ In general, for a **non-empty** domain \mathcal{U} , a counterexample to an **universally** quantified sentence is a term in \mathcal{U} that makes the sentence **false**.

Models: Witnesses and Counterexamples

- ▶ The case of (9) $\exists x\forall y(Lxy \wedge Wyx)$ and (10) $\exists x\exists y(Lxy \wedge Wyx)$ illustrate something important. (10) is true because we just need to find **at least one** witness; $(Lab \wedge Wba)$ is a witness. But (9) is false because we have to verify that there are **no counterexamples**. So we had to check **every** y -variant of $(Lay \wedge Wya)$ including $(Laa \wedge Waa)$, which is a counterexample.
- ▶ In general a **witness** to an **existentially** quantified sentence is a term in the domain that makes the sentence **true**.
- ▶ In general, for a **non-empty** domain \mathcal{U} , a counterexample to an **universally** quantified sentence is a term in \mathcal{U} that makes the sentence **false**.
- ▶ Note that in the case of counterexamples, the domain has to be non-empty. Think about it. If the domain is empty, then there is nothing to check. So there is trivially no counterexample!

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally, we can say why the rules of quantified relational logic are truth-preserving. We will not give a formal proof here. But we will reason in terms of **witnesses** and **counterexamples**.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally, we can say why the rules of quantified relational logic are truth-preserving. We will not give a formal proof here. But we will reason in terms of **witnesses** and **counterexamples**.
- ▶ Consider Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally, we can say why the rules of quantified relational logic are truth-preserving. We will not give a formal proof here. But we will reason in terms of **witnesses** and **counterexamples**.
- ▶ Consider Rule 2. From an instance \mathcal{F} , infer $(\exists x\mathcal{F})$. This rule is known as **Existential Generalization**.
- ▶ This rule is truth-preserving because the instance \mathcal{F} automatically acts as a witness to the existentially quantified sentence $(\exists x\mathcal{F})$. So the sentence $(\mathcal{F} \rightarrow \exists x\mathcal{F})$ is a tautology in the model.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Now consider Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Now consider Rule 3. From $\forall x\mathcal{F}$ you may infer **any** of its instances. This rule is known as **Universal Instantiation**.
- ▶ This rule is truth-preserving because if \mathcal{U} is not empty and if $\forall x\mathcal{F}$ is true, then there is no counterexample. So the sentence $\forall x\mathcal{F} \rightarrow \mathcal{F}$, where \mathcal{F} is any instance of $(\forall x\mathcal{F})$, is a tautology in the model.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally consider Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally consider Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**.
- ▶ This rule is truth-preserving for the following reason. Suppose \mathcal{U} is not empty. Either there is a witness for $\exists x\mathcal{F}$ or there is no witness for $\exists x\mathcal{F}$. If there is a witness, then $(\exists x\mathcal{F} \rightarrow G)$ is a tautology in the model because the inference to G is arrived at using other truth preserving rules of inference. If there is no witness, then $(\exists x\mathcal{F} \rightarrow G)$ is a tautology in the model because the antecedent is never satisfied.

Models: The Rules of Quantified Relational Logic are Truth-preserving.

- ▶ Finally consider Rule 4. From $\exists x\mathcal{F}$, you may suppose that $\mathcal{F}(a)$ and use $\mathcal{F}(a)$ together with other premises to infer a **sentence** G using other truth preserving rules of inference. Here $\mathcal{F}(a)$ is the result of uniformly replacing every free occurrence of x in \mathcal{F} with an arbitrary constant a , **which has not occurred before**.
- ▶ This rule is truth-preserving for the following reason. Suppose \mathcal{U} is not empty. Either there is a witness for $\exists x\mathcal{F}$ or there is no witness for $\exists x\mathcal{F}$. If there is a witness, then $(\exists x\mathcal{F} \rightarrow G)$ is a tautology in the model because the inference to G is arrived at using other truth preserving rules of inference. If there is no witness, then $(\exists x\mathcal{F} \rightarrow G)$ is a tautology in the model because the antecedent is never satisfied.
- ▶ In either case the inference from $\exists x\mathcal{F}$ to G is truth preserving. So, $(\exists x\mathcal{F} \rightarrow G)$ is a tautology in the model.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.
- ▶ This argument has the following form.

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.
- ▶ This argument has the following form.
 1. $\forall x(Lx \rightarrow Wx)$

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.
- ▶ This argument has the following form.
 1. $\forall x(Lx \rightarrow Wx)$
 2. La

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.
- ▶ This argument has the following form.
 1. $\forall x(Lx \rightarrow Wx)$
 2. La
 - ∴ 3. Wa

Models: Tying Everything Up.

- ▶ We can now say why the argument we started the discussion of quantified relational logic with is valid.
 1. All logicians are wise.
 2. Ruth Barcan Marcus is a logician.
 - ∴ 3. Ruth Barcan Marcus is wise.
- ▶ This argument has the following form.
 1. $\forall x(Lx \rightarrow Wx)$
 2. La
 - ∴ 3. Wa
- ▶ But it is not immediately obvious why it is valid.

Models: Tying Everything Up

- We can now say that his argument is valid because we can infer (Wa) using truth-preserving rules of inference as follows:

1.	$\forall x(Lx \rightarrow Wx)$	Premise
2.	La	Premise
3.	$(La \rightarrow Wa)$	From 1. and Universal Instantiation
4.	Wa	From 2. and 3. and Modus Ponens.

Models: Tying Everything Up

- ▶ We can now say that his argument is valid because we can infer (Wa) using truth-preserving rules of inference as follows:

1.	$\forall x(Lx \rightarrow Wx)$	Premise
2.	La	Premise
3.	$(La \rightarrow Wa)$	From 1. and Universal Instantiation
4.	Wa	From 2. and 3. and Modus Ponens.

- ▶ See **Homework 3** and **Homework 4** for more exercises.

Models: Tying Everything Up

- ▶ We can now say that his argument is valid because we can infer (Wa) using truth-preserving rules of inference as follows:

1.	$\forall x(Lx \rightarrow Wx)$	Premise
2.	La	Premise
3.	$(La \rightarrow Wa)$	From 1. and Universal Instantiation
4.	Wa	From 2. and 3. and Modus Ponens.

- ▶ See **Homework 3** and **Homework 4** for more exercises.
- ▶ We have now covered enough of deductive logic to understand its strengths. Next time we will begin discussing its limitations using Hume's Problem of Induction and Goodmans's Riddle of Induction in order to motivate inductive logic.