

Fsm exercise: solution

```
accept(_,Final,Q,[]) :- member(Q,Final).
```

```
member(X,[X|_]).
```

```
member(X,[_|L]):- member(X,L).
```

Fsm exercise: solution

```
accept(_,Final,Q,[]) :- member(Q,Final).  
accept(Trans,Final,Q,[H|T]) :-  
    member([Q,H,Qn],Trans),  
    accept(Trans,Final,Qn,T).  
member(X,[X|_]).  
member(X,[_|L]) :- member(X,L).
```


Fsm exercise: solution

```
accept(_,Final,Q,[ ]) :- member(Q,Final).
```

```
accept(Trans,Final,Q,[H|T]) :-  
    member([Q,H,Qn],Trans),  
    accept(Trans,Final,Qn,T).
```

```
member(X,[X|_]).
```

```
member(X,[_|L]) :- member(X,L).
```



Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Example: accept(Trans,Final,Q0,String)

```
Node as [Q,UnseenString]
```

Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Example: accept(Trans,Final,Q0,String)

Node as [Q,UnseenString]

```
goal(Q,[],Final) :- member(Q,Final).
```

Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Example: accept(Trans,Final,Q0,String)

Node as [Q,UnseenString]

```
goal(Q,[],Final) :- member(Q,Final).
```

```
arc([Q,[H|T]],[Qn,T],Trans) :-  
    member([Q,H,Qn],Trans).
```

Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Example: accept(Trans,Final,Q0,String)

Node as [Q,UnseenString]

```
goal(Q,[],Final) :- member(Q,Final).
```

```
arc([Q,[H|T]],[Qn,T],Trans) :-  
    member([Q,H,Qn],Trans).
```

```
search(Q,S,F,_) :- goal(Q,S,F).
```

```
search(Q,S,F,T) :- arc([Q,S],[Qn,Sn],T),  
    search(Qn,Sn,F,T).
```


Search (in Prolog)

Given goal, arc

```
search(Node) :- goal(Node).
```

```
search(Node) :- arc(Node,Next), search(Next).
```

Example: accept(Trans,Final,Q0,String)

Node as [Q,UnseenString]

```
goal(Q,[],Final) :- member(Q,Final).
```

```
arc([Q,[H|T]],[Qn,T],Trans) :-  
    member([Q,H,Qn],Trans).
```

```
search(Q,S,F,_) :- goal(Q,S,F).
```

```
search(Q,S,F,T) :- arc([Q,S],[Qn,Sn],T),  
    search(Qn,Sn,F,T).
```

```
accept(T,F,Q,S) :- search(Q,S,F,T).
```

Prolog as search

`i :- p,q.`

`i :- r.`

`p.`

`r.`

`| ?- i.`

Prolog as search

i :- p,q. [i]

i :- r.

p.

r.

| ?- i.

StartNode = [i]

Prolog as search


`i :- p,q.`

`i :- r.`

`p.`

`r.`

`| ?- i.`



`StartNode = [i]`

Prolog as search


i :- p,q.

i :- r.

p.

r.

| ?- i.



StartNode = [i]

Prolog as search


i :- p,q.

i :- r.

p.

r.

| ?- i.



StartNode = [i]

Prolog as search

`i :- p,q.`


`i :- r.`

`p.`

`r.`

`| ?- i.`

`yes`



`StartNode = [i]`

`goal([]).`

Prolog as search

`i :- p,q.`


`i :- r.`

`p.`

`r.`

`| ?- i.`

`yes`



`StartNode = [i]`

`goal([]).`

`prove(Node) :- goal(Node) .`

`prove(Node) :- arc(Node,Next), prove(Next).`

KB and arc

i :- p,q.

i :- r.

p.

r.

KB and arc

$i :- p, q.$

$[i, p, q]$

$i :- r.$

$[i, r]$

$p.$

$[p]$

$r.$

$[r]$

KB and arc

$i :- p, q.$

$[i, p, q]$

$i :- r.$

$[i, r]$

$p.$

$[p]$

$r.$

$[r]$

$KB = [[i, p, q], [i, r], [p], [r]]$

KB and arc

$i :- p, q.$

$[i, p, q]$

$i :- r.$

$[i, r]$

$p.$

$[p]$

$r.$

$[r]$

$KB = [[i, p, q], [i, r], [p], [r]]$

$\text{arc}(\text{Node1}, \text{Node2}, KB) :- ??$

KB and arc

<code>i :- p,q.</code>	<code>[i,p,q]</code>
------------------------	----------------------

<code>i :- r.</code>	<code>[i,r]</code>
----------------------	--------------------

<code>p.</code>	<code>[p]</code>
-----------------	------------------

<code>r.</code>	<code>[r]</code>
-----------------	------------------

`KB = [[i,p,q],[i,r],[p],[r]]`

`arc([H|T],N,KB) :- member([H|B],KB), append(B,T,N).`

KB and arc

$$i \text{ :- } p, q. \quad [i, p, q]$$
$$i \coloneqq r. \quad [i,r]$$

p. [p]

r.	[r]
----	-----

$$KB = [[i,p,q],[i,r],[p],[r]]$$

```
arc([H|T],N,KB) :- member([H|B],KB), append(B,T,N).
```

```
prove(Node,KB) :- goal(Node) ;
                  arc(Node,Next,KB), prove(Next,KB).
```

Non-termination

$i \text{ :- } p, q.$ [i]

$i \text{ :- } r.$

$p \text{ :- } i.$

$r.$

| ?- i.

$\text{prove}([], _).$

$\text{prove}([H|T], KB) \text{ :- } \text{member}([H|B], KB), \text{append}(B, T, \text{Next}),$
 $\text{prove}(\text{Next}, KB).$

Non-termination


`i :- p,q.`

`i :- r.`

`p :- i.`

`r.`

`| ?- i.`



`prove([],_).`

`prove([H|T],KB) :- member([H|B],KB), append(B,T,Next),
prove(Next,KB).`

Non-termination


`i :- p,q.`

`i :- r.`

`p :- i.`

`r.`

`| ?- i.`



`prove([],_).`

`prove([H|T],KB) :- member([H|B],KB), append(B,T,Next),
prove(Next,KB).`

Non-termination


$i :- p, q.$

$i :- r.$

$p :- i.$

$r.$

$| \text{ ?- } i.$



$\text{prove}([], _).$

$\text{prove}([H|T], KB) :- \text{member}([H|B], KB), \text{append}(B, T, \text{Next}),$
 $\text{prove}(\text{Next}, KB).$

Non-termination


$i \text{ :- } p, q.$

$i \text{ :- } r.$

$p \text{ :- } i.$

$r.$

$| \text{ ?- } i.$



$\text{prove}([], _).$

$\text{prove}([H|T], KB) \text{ :- } \text{member}([H|B], KB), \text{append}(B, T, \text{Next}),$
 $\text{prove}(\text{Next}, KB).$

Non-termination


$i \text{ :- } p, q.$

$i \text{ :- } r.$

$p \text{ :- } i.$

$r.$

$| \text{ ?- } i.$



$\text{prove}([], _).$

$\text{prove}([H|T], KB) \text{ :- } \text{member}([H|B], KB), \text{append}(B, T, \text{Next}),$
 $\text{prove}(\text{Next}, KB).$