

Files

Python Readline Method

To read only one line instead of multiple lines in a Python file, use the method .readline() on a file object that is returned from the open() function. Every subsequent .readline() will extract the next line in the file if it exists.

```
with open('story.txt') as story_obj
ect:
   print(story_object.readline())
```

will print only the first line in story.txt.

Python File Object

A Python file object is created when a file is opened with the open() function. You can associate this file object with a variable when you open a file using the with and as keywords. For example:

```
with open('somefile.txt') as file_o
bject:
```

You can then print the content of the file object,

```
file_object with print().
```

```
print(file_object)
```

You might see something like this on the output terminal:

```
<_io.TextIOWrapper name='somefile.t
xt' mode='r' encoding='UTF-8'>
```

Parsing JSON files to dictionary

JSON format is used to store key value pairs. Python's json module allows reading such data format and parsing it to a dictionary. The json.load function takes a file object as an argument and returns the data in a dictionary format.

code cademy

```
# Use json.load with an opened file object
to read the contents into a Python dictio
nary.

# Contents of file.json
# { 'userId': 10 }

import json
with open('file.json') as json_file:
    python_dict = json.load(json_file)

print(python_dict.get('userId'))
# Prints 10
```

Python Append To File

Writing to an opened file with the 'w' flag overwrites all previous content in the file. To avoid this, we can append to a file instead. Use the 'a' flag as the second argument to open(). If a file doesn't exist, it will be created for append mode.

```
with open('shopping.txt', 'a') as s
hop:
    shop.write('Tomatoes, cucumbers,
celery\n')
```

Python Write To File

By default, a file when opened with open() is only for reading. A second argument 'r' is passed to it by default. To write to a file, first open the file with write permission via the 'w' argument. Then use the .write() method to write to the file. If the file already exists, all prior content will be overwritten.

```
with open('diary.txt','w') as diary
:
   diary.write('Special events for t
oday')
```

Python Readlines Method



Instead of reading the entire content of a file, you can read a single line at a time. Instead of .read() which returns a string, call .readlines() to return a list of strings, each representing an individual line in the file. Calling this code:

```
with open('lines.txt') as file_obje
ct:
   file_data = file_object.readlines
()
print(file_data)
```

returns a list of strings in file_data:

```
['1. Learn Python.\n', '2. Work har
d.\n', '3. Graduate.']
```

Iterating over the list, file_data , and printing it:

```
for line in file_data:
   print(line)
```

outputs:

- 1. Learn Python.
- 2. Work hard.
- 3. Graduate.

Class csv.DictWriter



In Python, the CSV module implements classes to read and write tabular data in CSV format. It has a class

DictWriter which operates like a regular writer but maps a dictionary onto output rows. The keys of the dictionary are column names while values are actual data.

The csv.DictWriter constructor takes two arguments. The first is the open file handler that the CSV is being written to. The second named parameter,

fieldnames, is a list of field names that the CSV is going to handle.

Python Read Method

After a file is opened with open() returning a file object, call the .read() method of the file object to return the entire file content as a Python string. Executing the following Python code:

```
with open('mystery.txt') as text_fi
le:
   text_data = text_file.read()
print(text_data)
```

will produce a string containing the entire content of the read file:

```
Mystery solved. Congratulations!
```

```
# An example of csv.DictWriter
import csv
with open('companies.csv', 'w') as csvfile
  fieldnames = ['name', 'type']
  writer = csv.DictWriter(csvfile, fieldna
mes=fieldnames)
  writer.writeheader()
  writer.writerow({'name': 'Codecademy', '
type': 'Learning'})
  writer.writerow({'name': 'Google', 'type
': 'Search'})
....
After running the above code, companies.cs
v will contain the following information:
name, type
Codecademy, Learning
Google, Search
.....
```