CS4231 Parallel and Distributed Algorithms

Solution for Homework 5

Instructor: Haifeng YU

Homework Assignment

- Page 161
 - Problem 9.5 Remember to prove that the global snapshot you get is a consistent one
- Prove the following
 - If G and H are both consistent global snapshots, then G∩H and G∪H are also consistent global snapshots

Problem 9.5

For any event e, define:

```
cut(e) = { f | f has smaller logical clock value than e}
```

- Claim: For any event e, cut(e) is a consistent global snapshot
 - cut(e) is a global snapshot: if f2 is in the set and f1 is before f2 in process order, then f1 must be in the set
 - cut(e) is a consistent global snapshot: if f2 is in the set and f1 is before f2 in send-receive order, then f1 must be in the set

Aim to prove:

If G and H are both consistent global snapshots, then G∩H is also a consistent global snapshot

- G∩H is a global snapshot:
 - Need to prove that if e2 is in G∩H and e1 is before e2 in process order, then e1 must be in G∩H
 - e2 in G∩H ⇒ e2 in G and e2 in H ⇒ e1 in G and e1 in H ⇒ e1 in G∩H
- G∩H is a consistent global snapshot:
 - Need to prove that if e2 is in G∩H and e1 is before e2 in send-receive order, then e1 must be G∩H

Aim to prove:

If G and H are both consistent global snapshots, then GUH is also a consistent global snapshot.

- G∪H is a global snapshot:
 - Need to prove that if e2 is in G∪H and e1 is before e2 in process order, then e1 must be in G∪H
 - e2 in G∪H ⇒ W.I.o.g., e2 in G ⇒ e1 in G ⇒ e1 in G∪H
- G∪H is a consistent global snapshot:
 - Need to prove that if e2 is in G∪H and e1 is before e2 in send-receive order, then e1 must be G∪H