

Supplementary Materials

April 28, 2026

Supplement to the manuscript *Retrospective Benchmark of Optical Surface Roughness Workflows Against an Internal Tactile Baseline Across Multiple Materials and Processes*.

This document provides supplementary tables and representative figures for the multi-material retrospective benchmark reported in the main manuscript.

Its purpose is to provide compact numerical summaries across the archived conditions and a small set of additional figures illustrating the principal output types beyond those shown in the main text.

The supplement follows the same interpretive limits as the main manuscript. It reports archive-level discrepancy summaries between optical workflows and an internal tactile baseline; it does not establish a common measurand, formal traceability, or optical–tactile equivalence. Wavelength fits are low-degree-of-freedom screening summaries, and the tactile repeatability terms reported here are internal precision descriptors rather than a full uncertainty budget.

Contents

1	How to read this supplement	2
2	Supplementary tables	2
2.1	Table S1: Two-way ANOVA main effects and effect sizes	2
2.2	Table S2: System-wise slope versus wavelength	25
2.3	Table S3: Descriptive statistics by system	69
2.4	Table S4: Internal tactile repeatability summary	114
3	Representative supplementary figures	115
3.1	Case A: Ti6Al4V after finish milling (R_q)	115
3.2	Case B: C45 after wire EDM rough cutting (single-pass) (R_a)	119

1 How to read this supplement

Tables. Throughout this supplement, a *material–process group* denotes a specific material together with a specific surface-generation process. Combined with one roughness parameter, this corresponds to the *parameter–surface group* unit of analysis used in the main manuscript. In the manuscript subset, each of the eight parameters contributes 59 material–process groups, yielding 472 parameter–surface groups in total.

Table S1 reports exploratory two-way ANOVA screens for the factors *system* and *colour*. For each parameter and each material–process group, the table lists numerator and denominator degrees of freedom, the F statistic, the nominal p -value, and the effect size η^2 . Larger η^2 values indicate a larger fraction of variance associated with the given factor within that archive-defined group.

Table S2 reports system-wise linear screening fits of $|\text{diff}|(\%)$ versus illumination wavelength. The slope is given per nm together with a 95% confidence interval and a nominal p -value; positive slopes indicate increasing discrepancy with increasing wavelength, whereas negative slopes indicate decreasing discrepancy.

Because a large number of ANOVA models and regressions are reported across many groups, individual p -values should be interpreted as screening statistics only; emphasis should be placed on replicated patterns and aggregated rates rather than isolated significant results. In addition, most wavelength regressions are based on only three or four illumination levels within a given parameter–surface group, so Table S2 should be read as a low-degree-of-freedom descriptive summary rather than as a calibration or physics model.

Table S3 provides descriptive statistics of $|\text{diff}|(\%)$ by system (sample size n , mean, standard deviation, and standard error) for each parameter and material–process group. These summaries are descriptive only and, in many groups, are based on only a few available optical conditions per system. Where percentage-based summaries for R_{sk} appear in archive-derived tables, they are retained for completeness only and should not be interpreted on the same footing as the strictly positive parameters.

Table S4 summarises the internal repeatability of the tactile baseline used in the manuscript subset. For strictly positive parameters it reports the distribution of the relative standard error of the tactile mean, $100 u_S/|S|$, across parameter–surface groups; for R_{sk} it reports u_S in native units because the tactile reference can approach zero.

Figures. The supplementary figures are representative examples of (i) distributions of $|\text{diff}|(\%)$ across systems, (ii) optical–tactile discrepancy summaries, (iii) illumination-band trend plots with fitted screening lines, and (iv) technical-distance heatmaps between systems. They illustrate archive-level workflow behaviour and should not be read as validation figures for metrological equivalence.

2 Supplementary tables

The tables below are derived from the processed results produced by the analysis pipeline. They summarise the ANOVA results, wavelength-screening regression outputs, and descriptive summaries reported in the manuscript. Archive identifiers in the Material/process column are expanded to full material names and full process descriptions. The process codes used in the archive are MR (rough milling), MF (finish milling), TR/TF (rough/finish face turning), B (burnishing after MF), WEDM_R/WEDM_F (rough/finish wire EDM), GRI (grinding), GLA (glass bead blasting), and HON (honing).

2.1 Table S1: Two-way ANOVA main effects and effect sizes

Table S1: Two-way ANOVA for factors system and colour. Reported are numerator/denominator degrees of freedom, F statistic, p -value, and η^2 effect size.

Parameter	Material/process	Term	df ₁	df ₂	F	p	η^2
R_a	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	1.751	0.256	0.338
R_a	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	1.429	0.324	0.276
R_a	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.755	0.255	0.08
R_a	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	18.088	0.002	0.828
R_a	AISI 304 / EN 1.4301; grinding	color	3	6	0.755	0.559	0.052

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_a</i>	AISI 304 / EN 1.4301; grinding	system	3	6	11.67	0.006	0.809
<i>R_a</i>	AISI 304 / EN 1.4301; honing	color	3	6	2.81	0.13	0.16
<i>R_a</i>	AISI 304 / EN 1.4301; honing	system	3	6	12.765	0.005	0.726
<i>R_a</i>	AISI 304 / EN 1.4301; finish milling	color	3	6	0.95	0.474	0.246
<i>R_a</i>	AISI 304 / EN 1.4301; finish milling	system	3	6	0.911	0.49	0.236
<i>R_a</i>	AISI 304 / EN 1.4301; rough milling	color	3	6	1.824	0.243	0.47
<i>R_a</i>	AISI 304 / EN 1.4301; rough milling	system	3	6	0.054	0.982	0.014
<i>R_a</i>	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.422	0.744	0.079
<i>R_a</i>	AISI 304 / EN 1.4301; finish face turning	system	3	6	2.899	0.124	0.545
<i>R_a</i>	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.612	0.632	0.2
<i>R_a</i>	AISI 304 / EN 1.4301; rough face turning	system	3	6	0.447	0.729	0.146
<i>R_a</i>	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.604	0.285	0.04
<i>R_a</i>	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	36.792	2.939e-04	0.911
<i>R_a</i>	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.534	0.679	0.085
<i>R_a</i>	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	4.093	0.082	0.65
<i>R_a</i>	Al7075; burnishing after MF	color	3	6	1.491	0.309	0.38
<i>R_a</i>	Al7075; burnishing after MF	system	3	6	0.436	0.736	0.111
<i>R_a</i>	Al7075; glass bead blasting	color	3	6	0.917	0.487	0.097
<i>R_a</i>	Al7075; glass bead blasting	system	3	6	6.583	0.025	0.693
<i>R_a</i>	Al7075; grinding	color	3	6	0.348	0.792	0.041
<i>R_a</i>	Al7075; grinding	system	3	6	6.156	0.029	0.724
<i>R_a</i>	Al7075; honing	color	3	6	1.675	0.27	0.077
<i>R_a</i>	Al7075; honing	system	3	6	18.076	0.002	0.831
<i>R_a</i>	Al7075; finish milling	color	3	6	1.347	0.345	0.393
<i>R_a</i>	Al7075; finish milling	system	3	6	0.08	0.968	0.023
<i>R_a</i>	Al7075; rough milling	color	3	6	0.243	0.863	0.07
<i>R_a</i>	Al7075; rough milling	system	3	6	1.254	0.371	0.359
<i>R_a</i>	Al7075; finish face turning	color	3	6	1.024	0.446	0.242
<i>R_a</i>	Al7075; finish face turning	system	3	6	1.198	0.387	0.284
<i>R_a</i>	Al7075; rough face turning	color	3	6	1.181	0.393	0.224
<i>R_a</i>	Al7075; rough face turning	system	3	6	2.099	0.202	0.398
<i>R_a</i>	Al7075; finish wire EDM	color	3	6	1.748	0.256	0.023
<i>R_a</i>	Al7075; finish wire EDM	system	3	6	72.145	4.250e-05	0.951
<i>R_a</i>	Al7075; rough wire EDM	color	3	6	0.289	0.832	0.037
<i>R_a</i>	Al7075; rough wire EDM	system	3	6	5.556	0.036	0.708
<i>R_a</i>	C45 steel; burnishing after MF	color	3	6	3.039	0.114	0.585
<i>R_a</i>	C45 steel; burnishing after MF	system	3	6	0.157	0.922	0.03
<i>R_a</i>	C45 steel; glass bead blasting	color	3	6	1.781	0.251	0.21
<i>R_a</i>	C45 steel; glass bead blasting	system	3	6	4.69	0.051	0.554
<i>R_a</i>	C45 steel; grinding	color	3	6	1.051	0.436	0.037
<i>R_a</i>	C45 steel; grinding	system	3	6	25.009	8.632e-04	0.891
<i>R_a</i>	C45 steel; honing	color	3	6	2.444	0.162	0.243
<i>R_a</i>	C45 steel; honing	system	3	6	5.607	0.036	0.558
<i>R_a</i>	C45 steel; finish milling	color	3	5	0.337	0.8	0.035
<i>R_a</i>	C45 steel; finish milling	system	3	5	7.6	0.026	0.791
<i>R_a</i>	C45 steel; rough milling	color	3	5	0.606	0.639	0.091
<i>R_a</i>	C45 steel; rough milling	system	3	5	4.367	0.073	0.658
<i>R_a</i>	C45 steel; finish face turning	color	3	5	0.522	0.685	0.072
<i>R_a</i>	C45 steel; finish face turning	system	3	5	5.108	0.055	0.7
<i>R_a</i>	C45 steel; rough face turning	color	3	5	0.866	0.517	0.159
<i>R_a</i>	C45 steel; rough face turning	system	3	5	2.918	0.14	0.535
<i>R_a</i>	C45 steel; finish wire EDM	color	3	6	1.735	0.259	0.035

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_a</i>	C45 steel; finish wire EDM	system	3	6	45.358	1.621e-04	0.924
<i>R_a</i>	C45 steel; rough wire EDM	color	3	6	0.285	0.835	0.077
<i>R_a</i>	C45 steel; rough wire EDM	system	3	6	1.431	0.323	0.385
<i>R_a</i>	ELLOR graphite; glass bead blasting	color	3	6	1.381	0.336	0.074
<i>R_a</i>	ELLOR graphite; glass bead blasting	system	3	6	15.17	0.003	0.818
<i>R_a</i>	ELLOR graphite; grinding	color	3	6	1.741	0.258	0.288
<i>R_a</i>	ELLOR graphite; grinding	system	3	6	2.293	0.178	0.38
<i>R_a</i>	ELLOR graphite; honing	color	3	6	0.506	0.692	0.05
<i>R_a</i>	ELLOR graphite; honing	system	3	6	7.592	0.018	0.752
<i>R_a</i>	ELLOR graphite; finish milling	color	3	6	0.161	0.918	0.055
<i>R_a</i>	ELLOR graphite; finish milling	system	3	6	0.758	0.557	0.26
<i>R_a</i>	ELLOR graphite; rough milling	color	3	6	0.28	0.839	0.117
<i>R_a</i>	ELLOR graphite; rough milling	system	3	6	0.108	0.953	0.045
<i>R_a</i>	ELLOR graphite; finish face turning	color	3	6	0.345	0.794	0.098
<i>R_a</i>	ELLOR graphite; finish face turning	system	3	6	1.179	0.393	0.335
<i>R_a</i>	ELLOR graphite; rough face turning	color	3	6	1.077	0.427	0.284
<i>R_a</i>	ELLOR graphite; rough face turning	system	3	6	0.719	0.576	0.189
<i>R_a</i>	ELLOR graphite; finish wire EDM	color	3	5	1.416	0.342	0.073
<i>R_a</i>	ELLOR graphite; finish wire EDM	system	3	5	16.405	0.005	0.842
<i>R_a</i>	ELLOR graphite; rough wire EDM	color	3	6	0.337	0.8	0.074
<i>R_a</i>	ELLOR graphite; rough wire EDM	system	3	6	2.216	0.187	0.487
<i>R_a</i>	MO58A brass; burnishing after MF	color	2	7	0.913	0.444	0.191
<i>R_a</i>	MO58A brass; burnishing after MF	system	3	7	0.24	0.866	0.076
<i>R_a</i>	MO58A brass; glass bead blasting	color	3	6	4.818	0.049	0.162
<i>R_a</i>	MO58A brass; glass bead blasting	system	3	6	22.935	0.001	0.771
<i>R_a</i>	MO58A brass; grinding	color	3	6	0.531	0.677	0.036
<i>R_a</i>	MO58A brass; grinding	system	3	6	12.25	0.006	0.829
<i>R_a</i>	MO58A brass; honing	color	3	6	2.205	0.188	0.18
<i>R_a</i>	MO58A brass; honing	system	3	6	8.053	0.016	0.657
<i>R_a</i>	MO58A brass; finish milling	color	3	6	1.003	0.454	0.29
<i>R_a</i>	MO58A brass; finish milling	system	3	6	0.46	0.721	0.133
<i>R_a</i>	MO58A brass; rough milling	color	3	6	0.755	0.558	0.153
<i>R_a</i>	MO58A brass; rough milling	system	3	6	2.189	0.19	0.443
<i>R_a</i>	MO58A brass; finish face turning	color	3	6	0.985	0.46	0.102
<i>R_a</i>	MO58A brass; finish face turning	system	3	6	6.688	0.024	0.691
<i>R_a</i>	MO58A brass; rough face turning	color	3	6	0.59	0.644	0.104
<i>R_a</i>	MO58A brass; rough face turning	system	3	6	3.095	0.111	0.544
<i>R_a</i>	MO58A brass; finish wire EDM	color	3	6	0.874	0.505	0.024
<i>R_a</i>	MO58A brass; finish wire EDM	system	3	6	33.936	3.691e-04	0.922
<i>R_a</i>	MO58A brass; rough wire EDM	color	3	6	12.163	0.006	0.624
<i>R_a</i>	MO58A brass; rough wire EDM	system	3	6	5.318	0.04	0.273
<i>R_a</i>	Ti6Al4V; burnishing after MF	color	3	6	0.435	0.736	0.062
<i>R_a</i>	Ti6Al4V; burnishing after MF	system	3	6	4.554	0.055	0.652
<i>R_a</i>	Ti6Al4V; glass bead blasting	color	3	6	3.105	0.11	0.071
<i>R_a</i>	Ti6Al4V; glass bead blasting	system	3	6	38.797	2.529e-04	0.884
<i>R_a</i>	Ti6Al4V; grinding	color	3	6	0.251	0.858	0.04
<i>R_a</i>	Ti6Al4V; grinding	system	3	6	4.008	0.07	0.64
<i>R_a</i>	Ti6Al4V; honing	color	3	6	2.853	0.127	0.111
<i>R_a</i>	Ti6Al4V; honing	system	3	6	20.763	0.001	0.811
<i>R_a</i>	Ti6Al4V; finish milling	color	3	6	0.275	0.842	0.033
<i>R_a</i>	Ti6Al4V; finish milling	system	3	6	6.108	0.03	0.729
<i>R_a</i>	Ti6Al4V; rough milling	color	3	6	0.251	0.858	0.086
<i>R_a</i>	Ti6Al4V; rough milling	system	3	6	0.672	0.6	0.23
<i>R_a</i>	Ti6Al4V; finish face turning	color	3	6	4.024	0.069	0.547
<i>R_a</i>	Ti6Al4V; finish face turning	system	3	6	1.329	0.35	0.181
<i>R_a</i>	Ti6Al4V; rough face turning	color	3	6	0.633	0.62	0.143

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_a</i>	Ti6Al4V; rough face turning	system	3	6	1.794	0.248	0.405
<i>R_a</i>	Ti6Al4V; finish wire EDM	color	3	6	3.301	0.099	0.044
<i>R_a</i>	Ti6Al4V; finish wire EDM	system	3	6	70.188	4.603e-05	0.93
<i>R_a</i>	Ti6Al4V; rough wire EDM	color	3	6	0.213	0.884	0.054
<i>R_a</i>	Ti6Al4V; rough wire EDM	system	3	6	1.726	0.261	0.438
rku	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	0.229	0.873	0.022
rku	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	8.029	0.016	0.783
rku	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	0.993	0.457	0.168
rku	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	2.922	0.122	0.494
rku	AISI 304 / EN 1.4301; grinding	color	3	6	0.115	0.948	0.018
rku	AISI 304 / EN 1.4301; grinding	system	3	6	4.397	0.058	0.675
rku	AISI 304 / EN 1.4301; honing	color	3	6	2.714	0.138	0.088
rku	AISI 304 / EN 1.4301; honing	system	3	6	26.085	7.686e-04	0.847
rku	AISI 304 / EN 1.4301; finish milling	color	3	6	0.934	0.48	0.123
rku	AISI 304 / EN 1.4301; finish milling	system	3	6	4.649	0.052	0.613
rku	AISI 304 / EN 1.4301; rough milling	color	3	6	2.345	0.172	0.451
rku	AISI 304 / EN 1.4301; rough milling	system	3	6	0.857	0.512	0.165
rku	AISI 304 / EN 1.4301; finish face turning	color	3	6	3.195	0.105	0.329
rku	AISI 304 / EN 1.4301; finish face turning	system	3	6	4.508	0.056	0.465
rku	AISI 304 / EN 1.4301; rough face turning	color	3	6	1.823	0.243	0.174
rku	AISI 304 / EN 1.4301; rough face turning	system	3	6	6.674	0.024	0.636
rku	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	0.746	0.563	0.121
rku	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	3.406	0.094	0.554
rku	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.088	0.963	0.027
rku	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	1.56	0.309	0.471
rku	Al7075; burnishing after MF	color	3	6	1.526	0.301	0.3
rku	Al7075; burnishing after MF	system	3	6	1.564	0.293	0.307
rku	Al7075; glass bead blasting	color	3	6	0.581	0.649	0.107
rku	Al7075; glass bead blasting	system	3	6	2.843	0.128	0.524
rku	Al7075; grinding	color	3	6	1.859	0.237	0.188
rku	Al7075; grinding	system	3	6	6.045	0.03	0.61
rku	Al7075; honing	color	3	6	0.882	0.502	0.252
rku	Al7075; honing	system	3	6	0.613	0.631	0.175
rku	Al7075; finish milling	color	3	6	0.376	0.774	0.049
rku	Al7075; finish milling	system	3	6	5.33	0.04	0.692
rku	Al7075; rough milling	color	3	6	1.592	0.287	0.124
rku	Al7075; rough milling	system	3	6	9.278	0.011	0.721
rku	Al7075; finish face turning	color	3	6	3.039	0.114	0.443
rku	Al7075; finish face turning	system	3	6	1.817	0.244	0.265
rku	Al7075; rough face turning	color	3	6	0.797	0.539	0.234
rku	Al7075; rough face turning	system	3	6	0.613	0.631	0.18
rku	Al7075; finish wire EDM	color	3	6	1.847	0.239	0.409
rku	Al7075; finish wire EDM	system	3	6	0.668	0.602	0.148
rku	Al7075; rough wire EDM	color	3	6	0.58	0.65	0.016
rku	Al7075; rough wire EDM	system	3	6	32.648	4.115e-04	0.927
rku	C45 steel; burnishing after MF	color	3	6	1.096	0.421	0.035
rku	C45 steel; burnishing after MF	system	3	6	27.909	6.375e-04	0.9
rku	C45 steel; glass bead blasting	color	3	6	0.981	0.462	0.058

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
rku	C45 steel; glass bead blasting	system	3	6	14.071	0.004	0.825
rku	C45 steel; grinding	color	3	6	1.731	0.26	0.131
rku	C45 steel; grinding	system	3	6	9.474	0.011	0.717
rku	C45 steel; honing	color	3	6	0.425	0.742	0.037
rku	C45 steel; honing	system	3	6	9.176	0.012	0.791
rku	C45 steel; finish milling	color	3	5	1.091	0.433	0.22
rku	C45 steel; finish milling	system	3	5	2.205	0.206	0.444
rku	C45 steel; rough milling	color	3	5	0.463	0.72	0.038
rku	C45 steel; rough milling	system	3	5	10.085	0.015	0.826
rku	C45 steel; finish face turning	color	3	5	0.558	0.665	0.016
rku	C45 steel; finish face turning	system	3	5	31.841	0.001	0.935
rku	C45 steel; rough face turning	color	3	5	1.022	0.457	0.167
rku	C45 steel; rough face turning	system	3	5	3.443	0.108	0.562
rku	C45 steel; finish wire EDM	color	3	6	0.417	0.748	0.085
rku	C45 steel; finish wire EDM	system	3	6	2.481	0.158	0.507
rku	C45 steel; rough wire EDM	color	3	6	0.512	0.689	0.068
rku	C45 steel; rough wire EDM	system	3	6	4.989	0.045	0.665
rku	ELLOR graphite; glass bead blasting	color	3	6	0.826	0.526	0.186
rku	ELLOR graphite; glass bead blasting	system	3	6	1.609	0.283	0.363
rku	ELLOR graphite; grinding	color	3	6	1.789	0.249	0.155
rku	ELLOR graphite; grinding	system	3	6	7.732	0.017	0.671
rku	ELLOR graphite; honing	color	3	6	2.225	0.186	0.246
rku	ELLOR graphite; honing	system	3	6	4.807	0.049	0.532
rku	ELLOR graphite; finish milling	color	3	6	0.642	0.616	0.227
rku	ELLOR graphite; finish milling	system	3	6	0.191	0.899	0.068
rku	ELLOR graphite; rough milling	color	3	6	0.833	0.523	0.218
rku	ELLOR graphite; rough milling	system	3	6	0.994	0.457	0.26
rku	ELLOR graphite; finish face turning	color	3	6	0.872	0.506	0.199
rku	ELLOR graphite; finish face turning	system	3	6	1.512	0.304	0.345
rku	ELLOR graphite; rough face turning	color	3	6	0.302	0.824	0.037
rku	ELLOR graphite; rough face turning	system	3	6	5.895	0.032	0.719
rku	ELLOR graphite; finish wire EDM	color	3	5	1.611	0.299	0.042
rku	ELLOR graphite; finish wire EDM	system	3	5	35.107	8.763e-04	0.915
rku	ELLOR graphite; rough wire EDM	color	3	6	0.607	0.634	0.075
rku	ELLOR graphite; rough wire EDM	system	3	6	5.483	0.037	0.678
rku	MO58A brass; burnishing after MF	color	2	7	0.238	0.794	0.034
rku	MO58A brass; burnishing after MF	system	3	7	2.194	0.177	0.468
rku	MO58A brass; glass bead blasting	color	3	6	1.119	0.413	0.21
rku	MO58A brass; glass bead blasting	system	3	6	2.207	0.188	0.414
rku	MO58A brass; grinding	color	3	6	4.319	0.061	0.24
rku	MO58A brass; grinding	system	3	6	11.655	0.006	0.648
rku	MO58A brass; honing	color	3	6	11.138	0.007	0.17
rku	MO58A brass; honing	system	3	6	52.467	1.068e-04	0.8
rku	MO58A brass; finish milling	color	3	6	2.111	0.2	0.401
rku	MO58A brass; finish milling	system	3	6	1.156	0.401	0.219
rku	MO58A brass; rough milling	color	3	6	8.833	0.013	0.317
rku	MO58A brass; rough milling	system	3	6	17.039	0.002	0.611
rku	MO58A brass; finish face turning	color	3	6	0.626	0.624	0.032
rku	MO58A brass; finish face turning	system	3	6	16.728	0.003	0.864
rku	MO58A brass; rough face turning	color	3	6	0.529	0.678	0.052
rku	MO58A brass; rough face turning	system	3	6	7.696	0.018	0.753
rku	MO58A brass; finish wire EDM	color	3	6	0.106	0.954	0.021
rku	MO58A brass; finish wire EDM	system	3	6	3.034	0.115	0.59
rku	MO58A brass; rough wire EDM	color	3	6	1.661	0.273	0.347
rku	MO58A brass; rough wire EDM	system	3	6	1.131	0.409	0.236
rku	Ti6Al4V; burnishing after MF	color	3	6	1.174	0.395	0.122

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
rku	Ti6Al4V; burnishing after MF	system	3	6	6.416	0.027	0.669
rku	Ti6Al4V; glass bead blasting	color	3	6	1.058	0.434	0.149
rku	Ti6Al4V; glass bead blasting	system	3	6	4.055	0.068	0.57
rku	Ti6Al4V; grinding	color	3	6	0.124	0.942	0.017
rku	Ti6Al4V; grinding	system	3	6	5.145	0.043	0.708
rku	Ti6Al4V; honing	color	3	6	0.21	0.886	0.02
rku	Ti6Al4V; honing	system	3	6	8.36	0.015	0.791
rku	Ti6Al4V; finish milling	color	3	6	1.02	0.447	0.073
rku	Ti6Al4V; finish milling	system	3	6	10.963	0.008	0.784
rku	Ti6Al4V; rough milling	color	3	6	1.614	0.282	0.308
rku	Ti6Al4V; rough milling	system	3	6	1.618	0.282	0.309
rku	Ti6Al4V; finish face turning	color	3	6	3.484	0.09	0.538
rku	Ti6Al4V; finish face turning	system	3	6	0.987	0.46	0.153
rku	Ti6Al4V; rough face turning	color	3	6	0.766	0.553	0.053
rku	Ti6Al4V; rough face turning	system	3	6	11.613	0.007	0.808
rku	Ti6Al4V; finish wire EDM	color	3	6	1.337	0.348	0.232
rku	Ti6Al4V; finish wire EDM	system	3	6	2.417	0.165	0.42
rku	Ti6Al4V; rough wire EDM	color	3	6	1.36	0.342	0.098
rku	Ti6Al4V; rough wire EDM	system	3	6	10.445	0.009	0.757
rp	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	4.049	0.069	0.249
rp	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	10.222	0.009	0.628
rp	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	0.2	0.893	0.004
rp	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	51.007	1.158e-04	0.959
rp	AISI 304 / EN 1.4301; grinding	color	3	6	1.039	0.44	0.07
rp	AISI 304 / EN 1.4301; grinding	system	3	6	11.817	0.006	0.795
rp	AISI 304 / EN 1.4301; honing	color	3	6	0.571	0.654	0.048
rp	AISI 304 / EN 1.4301; honing	system	3	6	9.247	0.011	0.782
rp	AISI 304 / EN 1.4301; finish milling	color	3	6	1.028	0.444	0.279
rp	AISI 304 / EN 1.4301; finish milling	system	3	6	0.652	0.61	0.177
rp	AISI 304 / EN 1.4301; rough milling	color	3	6	1.991	0.217	0.484
rp	AISI 304 / EN 1.4301; rough milling	system	3	6	0.122	0.944	0.03
rp	AISI 304 / EN 1.4301; finish face turning	color	3	6	1.081	0.426	0.24
rp	AISI 304 / EN 1.4301; finish face turning	system	3	6	1.415	0.327	0.315
rp	AISI 304 / EN 1.4301; rough face turning	color	3	6	1.508	0.305	0.183
rp	AISI 304 / EN 1.4301; rough face turning	system	3	6	4.753	0.05	0.575
rp	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.382	0.336	0.052
rp	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	23.303	0.001	0.873
rp	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.557	0.666	0.029
rp	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	16.684	0.005	0.882
rp	Al7075; burnishing after MF	color	3	6	2.248	0.183	0.507
rp	Al7075; burnishing after MF	system	3	6	0.186	0.902	0.042
rp	Al7075; glass bead blasting	color	3	6	1.043	0.439	0.064
rp	Al7075; glass bead blasting	system	3	6	13.139	0.005	0.812
rp	Al7075; grinding	color	3	6	0.726	0.573	0.042
rp	Al7075; grinding	system	3	6	14.463	0.004	0.841
rp	Al7075; honing	color	3	6	0.382	0.77	0.034
rp	Al7075; honing	system	3	6	8.885	0.013	0.789
rp	Al7075; finish milling	color	3	6	2.772	0.133	0.469

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
rp	Al7075; finish milling	system	3	6	1.132	0.408	0.192
rp	Al7075; rough milling	color	3	6	0.325	0.808	0.087
rp	Al7075; rough milling	system	3	6	1.413	0.328	0.378
rp	Al7075; finish face turning	color	3	6	1.799	0.247	0.317
rp	Al7075; finish face turning	system	3	6	1.87	0.236	0.33
rp	Al7075; rough face turning	color	3	6	1.243	0.374	0.207
rp	Al7075; rough face turning	system	3	6	2.753	0.135	0.459
rp	Al7075; finish wire EDM	color	3	6	3.241	0.103	0.056
rp	Al7075; finish wire EDM	system	3	6	52.934	1.041e-04	0.91
rp	Al7075; rough wire EDM	color	3	6	0.065	0.976	0.001
rp	Al7075; rough wire EDM	system	3	6	59.453	7.448e-05	0.966
rp	C45 steel; burnishing after MF	color	3	6	2.689	0.14	0.536
rp	C45 steel; burnishing after MF	system	3	6	0.327	0.807	0.065
rp	C45 steel; glass bead blasting	color	3	6	0.724	0.573	0.006
rp	C45 steel; glass bead blasting	system	3	6	110.858	1.209e-05	0.976
rp	C45 steel; grinding	color	3	6	1.467	0.315	0.033
rp	C45 steel; grinding	system	3	6	41.051	2.155e-04	0.922
rp	C45 steel; honing	color	3	6	0.547	0.668	0.134
rp	C45 steel; honing	system	3	6	1.548	0.296	0.378
rp	C45 steel; finish milling	color	3	5	3.047	0.131	0.296
rp	C45 steel; finish milling	system	3	5	5.584	0.047	0.542
rp	C45 steel; rough milling	color	3	5	4.816	0.062	0.095
rp	C45 steel; rough milling	system	3	5	44.178	5.067e-04	0.872
rp	C45 steel; finish face turning	color	3	5	2.678	0.158	0.075
rp	C45 steel; finish face turning	system	3	5	31.519	0.001	0.879
rp	C45 steel; rough face turning	color	3	5	2.467	0.177	0.207
rp	C45 steel; rough face turning	system	3	5	7.786	0.025	0.653
rp	C45 steel; finish wire EDM	color	3	6	0.204	0.89	0.006
rp	C45 steel; finish wire EDM	system	3	6	30.504	4.977e-04	0.933
rp	C45 steel; rough wire EDM	color	3	6	1.641	0.277	0.042
rp	C45 steel; rough wire EDM	system	3	6	35.056	3.369e-04	0.906
rp	ELLOR graphite; glass bead blasting	color	3	6	0.903	0.493	0.051
rp	ELLOR graphite; glass bead blasting	system	3	6	14.75	0.004	0.836
rp	ELLOR graphite; grinding	color	3	6	0.693	0.589	0.186
rp	ELLOR graphite; grinding	system	3	6	1.033	0.443	0.277
rp	ELLOR graphite; honing	color	3	6	6.136	0.029	0.088
rp	ELLOR graphite; honing	system	3	6	61.337	6.806e-05	0.883
rp	ELLOR graphite; finish milling	color	3	6	2.034	0.211	0.023
rp	ELLOR graphite; finish milling	system	3	6	84.092	2.719e-05	0.954
rp	ELLOR graphite; rough milling	color	3	6	0.934	0.48	0.017
rp	ELLOR graphite; rough milling	system	3	6	51.065	1.154e-04	0.946
rp	ELLOR graphite; finish face turning	color	3	6	0.502	0.694	0.008
rp	ELLOR graphite; finish face turning	system	3	6	63.904	6.044e-05	0.962
rp	ELLOR graphite; rough face turning	color	3	6	1.143	0.405	0.125
rp	ELLOR graphite; rough face turning	system	3	6	5.985	0.031	0.656
rp	ELLOR graphite; finish wire EDM	color	3	5	2.407	0.183	0.026
rp	ELLOR graphite; finish wire EDM	system	3	5	88.692	9.351e-05	0.956
rp	ELLOR graphite; rough wire EDM	color	3	6	0.994	0.457	0.283
rp	ELLOR graphite; rough wire EDM	system	3	6	0.523	0.682	0.149
rp	MO58A brass; burnishing after MF	color	2	7	1.387	0.311	0.269
rp	MO58A brass; burnishing after MF	system	3	7	0.177	0.909	0.051
rp	MO58A brass; glass bead blasting	color	3	6	2.607	0.147	0.105
rp	MO58A brass; glass bead blasting	system	3	6	20.302	0.002	0.815
rp	MO58A brass; grinding	color	3	6	0.516	0.686	0.029
rp	MO58A brass; grinding	system	3	6	15.273	0.003	0.859
rp	MO58A brass; honing	color	3	6	0.428	0.741	0.075

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
rp	MO58A brass; honing	system	3	6	3.238	0.103	0.572
rp	MO58A brass; finish milling	color	3	6	4.232	0.063	0.363
rp	MO58A brass; finish milling	system	3	6	5.439	0.038	0.466
rp	MO58A brass; rough milling	color	3	6	5.891	0.032	0.279
rp	MO58A brass; rough milling	system	3	6	13.218	0.005	0.626
rp	MO58A brass; finish face turning	color	3	6	9.169	0.012	0.147
rp	MO58A brass; finish face turning	system	3	6	51.322	1.138e-04	0.821
rp	MO58A brass; rough face turning	color	3	6	2.959	0.12	0.11
rp	MO58A brass; rough face turning	system	3	6	22.056	0.001	0.816
rp	MO58A brass; finish wire EDM	color	3	6	3.107	0.11	0.034
rp	MO58A brass; finish wire EDM	system	3	6	85.366	2.602e-05	0.944
rp	MO58A brass; rough wire EDM	color	3	6	7.615	0.018	0.521
rp	MO58A brass; rough wire EDM	system	3	6	4.994	0.045	0.342
rp	Ti6Al4V; burnishing after MF	color	3	6	1.347	0.345	0.205
rp	Ti6Al4V; burnishing after MF	system	3	6	3.222	0.104	0.49
rp	Ti6Al4V; glass bead blasting	color	3	6	0.903	0.493	0.008
rp	Ti6Al4V; glass bead blasting	system	3	6	115.017	1.085e-05	0.975
rp	Ti6Al4V; grinding	color	3	6	2.841	0.128	0.105
rp	Ti6Al4V; grinding	system	3	6	22.197	0.001	0.821
rp	Ti6Al4V; honing	color	3	6	1.119	0.413	0.065
rp	Ti6Al4V; honing	system	3	6	13.968	0.004	0.817
rp	Ti6Al4V; finish milling	color	3	6	1.919	0.228	0.025
rp	Ti6Al4V; finish milling	system	3	6	73.322	4.054e-05	0.949
rp	Ti6Al4V; rough milling	color	3	6	1.853	0.238	0.268
rp	Ti6Al4V; rough milling	system	3	6	3.068	0.113	0.443
rp	Ti6Al4V; finish face turning	color	3	6	0.983	0.461	0.206
rp	Ti6Al4V; finish face turning	system	3	6	1.785	0.25	0.374
rp	Ti6Al4V; rough face turning	color	3	6	0.575	0.652	0.062
rp	Ti6Al4V; rough face turning	system	3	6	6.652	0.025	0.721
rp	Ti6Al4V; finish wire EDM	color	3	6	6.675	0.024	0.058
rp	Ti6Al4V; finish wire EDM	system	3	6	107.158	1.336e-05	0.925
rp	Ti6Al4V; rough wire EDM	color	3	6	0.254	0.856	0.01
rp	Ti6Al4V; rough wire EDM	system	3	6	22.153	0.001	0.908
R_q	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	1.515	0.304	0.301
R_q	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	1.524	0.302	0.302
R_q	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.449	0.319	0.048
R_q	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	26.896	7.062e-04	0.886
R_q	AISI 304 / EN 1.4301; grinding	color	3	6	0.89	0.498	0.055
R_q	AISI 304 / EN 1.4301; grinding	system	3	6	13.259	0.005	0.821
R_q	AISI 304 / EN 1.4301; honing	color	3	6	2.274	0.18	0.128
R_q	AISI 304 / EN 1.4301; honing	system	3	6	13.448	0.005	0.759
R_q	AISI 304 / EN 1.4301; finish milling	color	3	6	0.904	0.492	0.229
R_q	AISI 304 / EN 1.4301; finish milling	system	3	6	1.043	0.439	0.264
R_q	AISI 304 / EN 1.4301; rough milling	color	3	6	1.821	0.244	0.47
R_q	AISI 304 / EN 1.4301; rough milling	system	3	6	0.05	0.984	0.013
R_q	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.573	0.653	0.095
R_q	AISI 304 / EN 1.4301; finish face turning	system	3	6	3.437	0.093	0.572
R_q	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.56	0.661	0.191
R_q	AISI 304 / EN 1.4301; rough face turning	system	3	6	0.37	0.778	0.126
R_q	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.784	0.25	0.038

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_q	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	42.612	1.938e-04	0.918
R_q	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.192	0.898	0.03
R_q	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	4.593	0.067	0.712
R_q	Al7075; burnishing after MF	color	3	6	1.536	0.299	0.394
R_q	Al7075; burnishing after MF	system	3	6	0.367	0.78	0.094
R_q	Al7075; glass bead blasting	color	3	6	1.084	0.425	0.104
R_q	Al7075; glass bead blasting	system	3	6	7.379	0.019	0.705
R_q	Al7075; grinding	color	3	6	0.433	0.737	0.064
R_q	Al7075; grinding	system	3	6	4.362	0.059	0.642
R_q	Al7075; honing	color	3	6	1.996	0.216	0.086
R_q	Al7075; honing	system	3	6	19.294	0.002	0.828
R_q	Al7075; finish milling	color	3	6	0.874	0.505	0.283
R_q	Al7075; finish milling	system	3	6	0.217	0.882	0.07
R_q	Al7075; rough milling	color	3	6	0.265	0.848	0.078
R_q	Al7075; rough milling	system	3	6	1.155	0.401	0.338
R_q	Al7075; finish face turning	color	3	6	1.049	0.437	0.246
R_q	Al7075; finish face turning	system	3	6	1.22	0.381	0.286
R_q	Al7075; rough face turning	color	3	6	0.901	0.494	0.2
R_q	Al7075; rough face turning	system	3	6	1.614	0.282	0.357
R_q	Al7075; finish wire EDM	color	3	6	1.825	0.243	0.021
R_q	Al7075; finish wire EDM	system	3	6	81.3	3.000e-05	0.955
R_q	Al7075; rough wire EDM	color	3	6	0.691	0.59	0.048
R_q	Al7075; rough wire EDM	system	3	6	11.825	0.006	0.815
R_q	C45 steel; burnishing after MF	color	3	6	2.96	0.12	0.58
R_q	C45 steel; burnishing after MF	system	3	6	0.146	0.929	0.029
R_q	C45 steel; glass bead blasting	color	3	6	1.753	0.256	0.17
R_q	C45 steel; glass bead blasting	system	3	6	6.532	0.026	0.635
R_q	C45 steel; grinding	color	3	6	1.203	0.386	0.042
R_q	C45 steel; grinding	system	3	6	25.211	8.443e-04	0.887
R_q	C45 steel; honing	color	3	6	2.325	0.174	0.23
R_q	C45 steel; honing	system	3	6	5.781	0.033	0.572
R_q	C45 steel; finish milling	color	3	5	0.404	0.757	0.054
R_q	C45 steel; finish milling	system	3	5	5.365	0.051	0.721
R_q	C45 steel; rough milling	color	3	5	0.602	0.641	0.082
R_q	C45 steel; rough milling	system	3	5	5.057	0.057	0.69
R_q	C45 steel; finish face turning	color	3	5	0.499	0.699	0.063
R_q	C45 steel; finish face turning	system	3	5	5.749	0.045	0.726
R_q	C45 steel; rough face turning	color	3	5	0.885	0.509	0.159
R_q	C45 steel; rough face turning	system	3	5	3.004	0.134	0.541
R_q	C45 steel; finish wire EDM	color	3	6	1.572	0.291	0.026
R_q	C45 steel; finish wire EDM	system	3	6	58.021	7.992e-05	0.942
R_q	C45 steel; rough wire EDM	color	3	6	0.237	0.867	0.062
R_q	C45 steel; rough wire EDM	system	3	6	1.618	0.282	0.42
R_q	ELLOR graphite; glass bead blasting	color	3	6	0.068	0.975	0.005
R_q	ELLOR graphite; glass bead blasting	system	3	6	11.457	0.007	0.847
R_q	ELLOR graphite; grinding	color	3	6	1.749	0.256	0.305
R_q	ELLOR graphite; grinding	system	3	6	1.981	0.218	0.346
R_q	ELLOR graphite; honing	color	3	6	0.369	0.779	0.04
R_q	ELLOR graphite; honing	system	3	6	6.92	0.022	0.745
R_q	ELLOR graphite; finish milling	color	3	6	0.598	0.639	0.156
R_q	ELLOR graphite; finish milling	system	3	6	1.248	0.373	0.324
R_q	ELLOR graphite; rough milling	color	3	6	0.43	0.739	0.168
R_q	ELLOR graphite; rough milling	system	3	6	0.131	0.938	0.051
R_q	ELLOR graphite; finish face turning	color	3	6	0.42	0.746	0.139
R_q	ELLOR graphite; finish face turning	system	3	6	0.6	0.638	0.199
R_q	ELLOR graphite; rough face turning	color	3	6	1.065	0.431	0.286

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_q	ELLOR graphite; rough face turning	system	3	6	0.654	0.609	0.176
R_q	ELLOR graphite; finish wire EDM	color	3	5	1.132	0.42	0.062
R_q	ELLOR graphite; finish wire EDM	system	3	5	15.344	0.006	0.846
R_q	ELLOR graphite; rough wire EDM	color	3	6	0.441	0.732	0.132
R_q	ELLOR graphite; rough wire EDM	system	3	6	0.902	0.493	0.27
R_q	MO58A brass; burnishing after MF	color	2	7	0.93	0.438	0.197
R_q	MO58A brass; burnishing after MF	system	3	7	0.186	0.903	0.059
R_q	MO58A brass; glass bead blasting	color	3	6	4.438	0.057	0.172
R_q	MO58A brass; glass bead blasting	system	3	6	19.437	0.002	0.751
R_q	MO58A brass; grinding	color	3	6	0.631	0.621	0.041
R_q	MO58A brass; grinding	system	3	6	12.906	0.005	0.831
R_q	MO58A brass; honing	color	3	6	2.347	0.172	0.167
R_q	MO58A brass; honing	system	3	6	9.723	0.01	0.691
R_q	MO58A brass; finish milling	color	3	6	0.932	0.481	0.259
R_q	MO58A brass; finish milling	system	3	6	0.663	0.604	0.184
R_q	MO58A brass; rough milling	color	3	6	0.834	0.522	0.159
R_q	MO58A brass; rough milling	system	3	6	2.426	0.164	0.461
R_q	MO58A brass; finish face turning	color	3	6	0.941	0.477	0.091
R_q	MO58A brass; finish face turning	system	3	6	7.355	0.02	0.714
R_q	MO58A brass; rough face turning	color	3	6	0.77	0.551	0.105
R_q	MO58A brass; rough face turning	system	3	6	4.598	0.054	0.624
R_q	MO58A brass; finish wire EDM	color	3	6	1.285	0.362	0.027
R_q	MO58A brass; finish wire EDM	system	3	6	43.615	1.813e-04	0.93
R_q	MO58A brass; rough wire EDM	color	3	6	11.2	0.007	0.591
R_q	MO58A brass; rough wire EDM	system	3	6	5.735	0.034	0.303
R_q	Ti6Al4V; burnishing after MF	color	3	6	0.277	0.84	0.049
R_q	Ti6Al4V; burnishing after MF	system	3	6	3.373	0.096	0.597
R_q	Ti6Al4V; glass bead blasting	color	3	6	3.174	0.106	0.062
R_q	Ti6Al4V; glass bead blasting	system	3	6	46.318	1.527e-04	0.9
R_q	Ti6Al4V; grinding	color	3	6	0.323	0.809	0.049
R_q	Ti6Al4V; grinding	system	3	6	4.33	0.06	0.651
R_q	Ti6Al4V; honing	color	3	6	2.883	0.125	0.106
R_q	Ti6Al4V; honing	system	3	6	22.306	0.001	0.82
R_q	Ti6Al4V; finish milling	color	3	6	0.283	0.836	0.034
R_q	Ti6Al4V; finish milling	system	3	6	6.017	0.031	0.725
R_q	Ti6Al4V; rough milling	color	3	6	0.702	0.585	0.12
R_q	Ti6Al4V; rough milling	system	3	6	3.152	0.108	0.538
R_q	Ti6Al4V; finish face turning	color	3	6	2.94	0.121	0.473
R_q	Ti6Al4V; finish face turning	system	3	6	1.273	0.365	0.205
R_q	Ti6Al4V; rough face turning	color	3	6	0.762	0.555	0.15
R_q	Ti6Al4V; rough face turning	system	3	6	2.318	0.175	0.456
R_q	Ti6Al4V; finish wire EDM	color	3	6	3.477	0.091	0.043
R_q	Ti6Al4V; finish wire EDM	system	3	6	75.322	3.749e-05	0.932
R_q	Ti6Al4V; rough wire EDM	color	3	6	0.197	0.895	0.035
R_q	Ti6Al4V; rough wire EDM	system	3	6	3.383	0.095	0.606
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	1.609	0.283	0.392
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	0.495	0.699	0.121
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.122	0.412	0.164
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	3.733	0.08	0.545
R_{sk}	AISI 304 / EN 1.4301; grinding	color	3	6	1.498	0.308	0.076
R_{sk}	AISI 304 / EN 1.4301; grinding	system	3	6	16.252	0.003	0.823
R_{sk}	AISI 304 / EN 1.4301; honing	color	3	6	1.477	0.312	0.176
R_{sk}	AISI 304 / EN 1.4301; honing	system	3	6	4.917	0.047	0.586
R_{sk}	AISI 304 / EN 1.4301; finish milling	color	3	6	0.242	0.864	0.028
R_{sk}	AISI 304 / EN 1.4301; finish milling	system	3	6	6.49	0.026	0.743

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{sk}	AISI 304 / EN 1.4301; rough milling	color	3	6	1.597	0.286	0.359
R_{sk}	AISI 304 / EN 1.4301; rough milling	system	3	6	0.846	0.517	0.19
R_{sk}	AISI 304 / EN 1.4301; finish face turning	color	3	6	10.574	0.008	0.248
R_{sk}	AISI 304 / EN 1.4301; finish face turning	system	3	6	29.988	5.220e-04	0.705
R_{sk}	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.357	0.786	0.068
R_{sk}	AISI 304 / EN 1.4301; rough face turning	system	3	6	2.863	0.126	0.548
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.034	0.442	0.113
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	6.125	0.029	0.669
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.437	0.736	0.111
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	1.849	0.256	0.468
R_{sk}	Al7075; burnishing after MF	color	3	6	0.593	0.642	0.197
R_{sk}	Al7075; burnishing after MF	system	3	6	0.417	0.747	0.139
R_{sk}	Al7075; glass bead blasting	color	3	6	1.936	0.225	0.102
R_{sk}	Al7075; glass bead blasting	system	3	6	14.999	0.003	0.792
R_{sk}	Al7075; grinding	color	3	6	2.669	0.141	0.096
R_{sk}	Al7075; grinding	system	3	6	23.201	0.001	0.832
R_{sk}	Al7075; honing	color	3	6	3.912	0.073	0.385
R_{sk}	Al7075; honing	system	3	6	4.243	0.063	0.418
R_{sk}	Al7075; finish milling	color	3	6	2.026	0.212	0.468
R_{sk}	Al7075; finish milling	system	3	6	0.304	0.822	0.07
R_{sk}	Al7075; rough milling	color	3	6	1.417	0.327	0.273
R_{sk}	Al7075; rough milling	system	3	6	1.783	0.25	0.343
R_{sk}	Al7075; finish face turning	color	3	6	0.975	0.464	0.211
R_{sk}	Al7075; finish face turning	system	3	6	1.658	0.274	0.358
R_{sk}	Al7075; rough face turning	color	3	6	0.217	0.881	0.087
R_{sk}	Al7075; rough face turning	system	3	6	0.263	0.85	0.106
R_{sk}	Al7075; finish wire EDM	color	3	6	1.915	0.228	0.284
R_{sk}	Al7075; finish wire EDM	system	3	6	2.817	0.13	0.418
R_{sk}	Al7075; rough wire EDM	color	3	6	0.87	0.507	0.051
R_{sk}	Al7075; rough wire EDM	system	3	6	14.313	0.004	0.833
R_{sk}	C45 steel; burnishing after MF	color	3	6	0.18	0.907	0.043
R_{sk}	C45 steel; burnishing after MF	system	3	6	1.987	0.217	0.477
R_{sk}	C45 steel; glass bead blasting	color	3	6	1.542	0.298	0.213
R_{sk}	C45 steel; glass bead blasting	system	3	6	3.687	0.082	0.51
R_{sk}	C45 steel; grinding	color	3	6	1.96	0.221	0.07
R_{sk}	C45 steel; grinding	system	3	6	24.041	9.620e-04	0.859
R_{sk}	C45 steel; honing	color	3	6	1.17	0.396	0.171
R_{sk}	C45 steel; honing	system	3	6	3.667	0.082	0.536
R_{sk}	C45 steel; finish milling	color	3	5	0.096	0.959	0.015
R_{sk}	C45 steel; finish milling	system	3	5	4.686	0.065	0.727
R_{sk}	C45 steel; rough milling	color	3	5	0.773	0.557	0.108
R_{sk}	C45 steel; rough milling	system	3	5	4.71	0.064	0.659
R_{sk}	C45 steel; finish face turning	color	3	5	0.65	0.616	0.083
R_{sk}	C45 steel; finish face turning	system	3	5	5.543	0.048	0.705
R_{sk}	C45 steel; rough face turning	color	3	5	1.275	0.378	0.224
R_{sk}	C45 steel; rough face turning	system	3	5	2.741	0.153	0.482
R_{sk}	C45 steel; finish wire EDM	color	3	6	0.38	0.772	0.125
R_{sk}	C45 steel; finish wire EDM	system	3	6	0.65	0.611	0.215
R_{sk}	C45 steel; rough wire EDM	color	3	6	0.701	0.585	0.127
R_{sk}	C45 steel; rough wire EDM	system	3	6	2.834	0.128	0.512
R_{sk}	ELLOR graphite; glass bead blasting	color	3	6	1.632	0.279	0.436
R_{sk}	ELLOR graphite; glass bead blasting	system	3	6	0.113	0.95	0.03

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{sk}	ELLOR graphite; grinding	color	3	6	0.636	0.619	0.191
R_{sk}	ELLOR graphite; grinding	system	3	6	0.69	0.591	0.207
R_{sk}	ELLOR graphite; honing	color	3	6	2.283	0.179	0.328
R_{sk}	ELLOR graphite; honing	system	3	6	2.672	0.141	0.384
R_{sk}	ELLOR graphite; finish milling	color	3	6	1.004	0.453	0.316
R_{sk}	ELLOR graphite; finish milling	system	3	6	0.175	0.91	0.055
R_{sk}	ELLOR graphite; rough milling	color	3	6	0.832	0.523	0.257
R_{sk}	ELLOR graphite; rough milling	system	3	6	0.403	0.756	0.125
R_{sk}	ELLOR graphite; finish face turning	color	3	6	1.089	0.423	0.279
R_{sk}	ELLOR graphite; finish face turning	system	3	6	0.812	0.532	0.208
R_{sk}	ELLOR graphite; rough face turning	color	3	6	0.674	0.599	0.062
R_{sk}	ELLOR graphite; rough face turning	system	3	6	8.16	0.015	0.753
R_{sk}	ELLOR graphite; finish wire EDM	color	3	5	1.214	0.395	0.023
R_{sk}	ELLOR graphite; finish wire EDM	system	3	5	48.977	3.955e-04	0.944
R_{sk}	ELLOR graphite; rough wire EDM	color	3	6	1.088	0.423	0.334
R_{sk}	ELLOR graphite; rough wire EDM	system	3	6	0.171	0.912	0.052
R_{sk}	MO58A brass; burnishing after MF	color	2	7	0.158	0.857	0.023
R_{sk}	MO58A brass; burnishing after MF	system	3	7	2.144	0.183	0.468
R_{sk}	MO58A brass; glass bead blasting	color	3	6	2.216	0.187	0.225
R_{sk}	MO58A brass; glass bead blasting	system	3	6	5.615	0.035	0.571
R_{sk}	MO58A brass; grinding	color	3	6	1.471	0.314	0.11
R_{sk}	MO58A brass; grinding	system	3	6	9.963	0.01	0.742
R_{sk}	MO58A brass; honing	color	3	6	3.757	0.079	0.31
R_{sk}	MO58A brass; honing	system	3	6	6.37	0.027	0.525
R_{sk}	MO58A brass; finish milling	color	3	6	0.93	0.482	0.223
R_{sk}	MO58A brass; finish milling	system	3	6	1.239	0.375	0.297
R_{sk}	MO58A brass; rough milling	color	3	6	0.412	0.75	0.15
R_{sk}	MO58A brass; rough milling	system	3	6	0.337	0.8	0.122
R_{sk}	MO58A brass; finish face turning	color	3	6	1.043	0.439	0.225
R_{sk}	MO58A brass; finish face turning	system	3	6	1.584	0.289	0.342
R_{sk}	MO58A brass; rough face turning	color	3	6	0.66	0.606	0.229
R_{sk}	MO58A brass; rough face turning	system	3	6	0.228	0.873	0.079
R_{sk}	MO58A brass; finish wire EDM	color	3	6	0.923	0.485	0.06
R_{sk}	MO58A brass; finish wire EDM	system	3	6	12.424	0.006	0.81
R_{sk}	MO58A brass; rough wire EDM	color	3	6	1.775	0.252	0.361
R_{sk}	MO58A brass; rough wire EDM	system	3	6	1.148	0.403	0.233
R_{sk}	Ti6Al4V; burnishing after MF	color	3	6	1.734	0.259	0.318
R_{sk}	Ti6Al4V; burnishing after MF	system	3	6	1.713	0.263	0.314
R_{sk}	Ti6Al4V; glass bead blasting	color	3	6	2.25	0.183	0.325
R_{sk}	Ti6Al4V; glass bead blasting	system	3	6	2.668	0.141	0.386
R_{sk}	Ti6Al4V; grinding	color	3	6	3.308	0.099	0.127
R_{sk}	Ti6Al4V; grinding	system	3	6	20.828	0.001	0.797
R_{sk}	Ti6Al4V; honing	color	3	6	0.795	0.54	0.073
R_{sk}	Ti6Al4V; honing	system	3	6	8.113	0.016	0.744
R_{sk}	Ti6Al4V; finish milling	color	3	6	0.221	0.878	0.085
R_{sk}	Ti6Al4V; finish milling	system	3	6	0.368	0.779	0.142
R_{sk}	Ti6Al4V; rough milling	color	3	6	0.508	0.691	0.163
R_{sk}	Ti6Al4V; rough milling	system	3	6	0.606	0.635	0.195
R_{sk}	Ti6Al4V; finish face turning	color	3	6	0.865	0.509	0.208
R_{sk}	Ti6Al4V; finish face turning	system	3	6	1.286	0.361	0.31
R_{sk}	Ti6Al4V; rough face turning	color	3	6	0.537	0.674	0.146
R_{sk}	Ti6Al4V; rough face turning	system	3	6	1.146	0.404	0.311
R_{sk}	Ti6Al4V; finish wire EDM	color	3	6	1.882	0.234	0.115
R_{sk}	Ti6Al4V; finish wire EDM	system	3	6	12.481	0.005	0.763
R_{sk}	Ti6Al4V; rough wire EDM	color	3	6	1.299	0.358	0.141
R_{sk}	Ti6Al4V; rough wire EDM	system	3	6	5.918	0.032	0.642
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	1.969	0.22	0.06

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	28.812	5.835e-04	0.879
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	3.986	0.071	0.039
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	94.962	1.905e-05	0.941
R_{sm}	AISI 304 / EN 1.4301; grinding	color	3	6	1.584	0.289	0.037
R_{sm}	AISI 304 / EN 1.4301; grinding	system	3	6	39.535	2.398e-04	0.917
R_{sm}	AISI 304 / EN 1.4301; honing	color	3	6	2.456	0.161	0.046
R_{sm}	AISI 304 / EN 1.4301; honing	system	3	6	49.497	1.263e-04	0.917
R_{sm}	AISI 304 / EN 1.4301; finish milling	color	3	6	2.399	0.166	0.22
R_{sm}	AISI 304 / EN 1.4301; finish milling	system	3	6	6.499	0.026	0.596
R_{sm}	AISI 304 / EN 1.4301; rough milling	color	3	6	3.716	0.08	0.422
R_{sm}	AISI 304 / EN 1.4301; rough milling	system	3	6	3.094	0.111	0.351
R_{sm}	AISI 304 / EN 1.4301; finish face turning	color	3	6	2.705	0.138	0.358
R_{sm}	AISI 304 / EN 1.4301; finish face turning	system	3	6	2.847	0.127	0.377
R_{sm}	AISI 304 / EN 1.4301; rough face turning	color	3	6	2.507	0.156	0.388
R_{sm}	AISI 304 / EN 1.4301; rough face turning	system	3	6	1.955	0.222	0.303
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.295	0.359	0.025
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	48.669	1.325e-04	0.937
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.608	0.638	0.015
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	39.46	6.637e-04	0.945
R_{sm}	Al7075; burnishing after MF	color	3	6	7.681	0.018	0.194
R_{sm}	Al7075; burnishing after MF	system	3	6	29.965	5.231e-04	0.756
R_{sm}	Al7075; glass bead blasting	color	3	6	1.858	0.238	0.008
R_{sm}	Al7075; glass bead blasting	system	3	6	230.477	1.388e-06	0.984
R_{sm}	Al7075; grinding	color	3	6	0.644	0.614	0.007
R_{sm}	Al7075; grinding	system	3	6	89.389	2.274e-05	0.971
R_{sm}	Al7075; honing	color	3	6	0.235	0.869	0.004
R_{sm}	Al7075; honing	system	3	6	59.987	7.258e-05	0.964
R_{sm}	Al7075; finish milling	color	3	6	0.077	0.97	0.002
R_{sm}	Al7075; finish milling	system	3	6	48.802	1.315e-04	0.959
R_{sm}	Al7075; rough milling	color	3	6	2.765	0.134	0.125
R_{sm}	Al7075; rough milling	system	3	6	17.271	0.002	0.784
R_{sm}	Al7075; finish face turning	color	3	6	3.498	0.09	0.357
R_{sm}	Al7075; finish face turning	system	3	6	4.293	0.061	0.438
R_{sm}	Al7075; rough face turning	color	3	6	2.663	0.142	0.33
R_{sm}	Al7075; rough face turning	system	3	6	3.411	0.094	0.422
R_{sm}	Al7075; finish wire EDM	color	3	6	4.704	0.051	0.02
R_{sm}	Al7075; finish wire EDM	system	3	6	224.09	1.509e-06	0.971
R_{sm}	Al7075; rough wire EDM	color	3	6	1.153	0.401	0.074
R_{sm}	Al7075; rough wire EDM	system	3	6	12.428	0.006	0.798
R_{sm}	C45 steel; burnishing after MF	color	3	6	2.951	0.12	0.148
R_{sm}	C45 steel; burnishing after MF	system	3	6	14.999	0.003	0.752
R_{sm}	C45 steel; glass bead blasting	color	3	6	7.138	0.021	0.034
R_{sm}	C45 steel; glass bead blasting	system	3	6	199.761	2.123e-06	0.956
R_{sm}	C45 steel; grinding	color	3	6	0.326	0.807	0.004
R_{sm}	C45 steel; grinding	system	3	6	81.239	3.007e-05	0.972
R_{sm}	C45 steel; honing	color	3	6	2.612	0.146	0.057
R_{sm}	C45 steel; honing	system	3	6	41.418	2.101e-04	0.9
R_{sm}	C45 steel; finish milling	color	3	5	0.591	0.647	0.023
R_{sm}	C45 steel; finish milling	system	3	5	23.026	0.002	0.911

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_{sm}</i>	C45 steel; rough milling	color	3	5	2.965	0.136	0.193
<i>R_{sm}</i>	C45 steel; rough milling	system	3	5	10.736	0.013	0.699
<i>R_{sm}</i>	C45 steel; finish face turning	color	3	5	2.485	0.175	0.178
<i>R_{sm}</i>	C45 steel; finish face turning	system	3	5	9.846	0.015	0.703
<i>R_{sm}</i>	C45 steel; rough face turning	color	3	5	2.317	0.193	0.372
<i>R_{sm}</i>	C45 steel; rough face turning	system	3	5	2.24	0.202	0.36
<i>R_{sm}</i>	C45 steel; finish wire EDM	color	3	6	2.15	0.195	0.042
<i>R_{sm}</i>	C45 steel; finish wire EDM	system	3	6	47.549	1.417e-04	0.92
<i>R_{sm}</i>	C45 steel; rough wire EDM	color	3	6	1.312	0.354	0.289
<i>R_{sm}</i>	C45 steel; rough wire EDM	system	3	6	1.221	0.381	0.269
<i>R_{sm}</i>	ELLOR graphite; glass bead blasting	color	3	6	1.478	0.312	0.168
<i>R_{sm}</i>	ELLOR graphite; glass bead blasting	system	3	6	5.314	0.04	0.604
<i>R_{sm}</i>	ELLOR graphite; grinding	color	3	6	1.849	0.239	0.182
<i>R_{sm}</i>	ELLOR graphite; grinding	system	3	6	6.3	0.028	0.621
<i>R_{sm}</i>	ELLOR graphite; honing	color	3	6	1.341	0.347	0.028
<i>R_{sm}</i>	ELLOR graphite; honing	system	3	6	44.281	1.737e-04	0.93
<i>R_{sm}</i>	ELLOR graphite; finish milling	color	3	6	1.662	0.273	0.162
<i>R_{sm}</i>	ELLOR graphite; finish milling	system	3	6	6.619	0.025	0.644
<i>R_{sm}</i>	ELLOR graphite; rough milling	color	3	6	0.937	0.479	0.054
<i>R_{sm}</i>	ELLOR graphite; rough milling	system	3	6	14.486	0.004	0.831
<i>R_{sm}</i>	ELLOR graphite; finish face turning	color	3	6	1.18	0.393	0.007
<i>R_{sm}</i>	ELLOR graphite; finish face turning	system	3	6	158.281	4.230e-06	0.98
<i>R_{sm}</i>	ELLOR graphite; rough face turning	color	3	6	1.649	0.275	0.146
<i>R_{sm}</i>	ELLOR graphite; rough face turning	system	3	6	7.655	0.018	0.677
<i>R_{sm}</i>	ELLOR graphite; finish wire EDM	color	3	5	1.855	0.255	0.017
<i>R_{sm}</i>	ELLOR graphite; finish wire EDM	system	3	5	104.109	6.313e-05	0.967
<i>R_{sm}</i>	ELLOR graphite; rough wire EDM	color	3	6	1.454	0.318	0.193
<i>R_{sm}</i>	ELLOR graphite; rough wire EDM	system	3	6	4.065	0.068	0.541
<i>R_{sm}</i>	MO58A brass; burnishing after MF	color	2	7	0.701	0.528	0.101
<i>R_{sm}</i>	MO58A brass; burnishing after MF	system	3	7	1.815	0.232	0.393
<i>R_{sm}</i>	MO58A brass; glass bead blasting	color	3	6	0.453	0.725	0.003
<i>R_{sm}</i>	MO58A brass; glass bead blasting	system	3	6	142.108	5.817e-06	0.983
<i>R_{sm}</i>	MO58A brass; grinding	color	3	6	1.625	0.28	0.042
<i>R_{sm}</i>	MO58A brass; grinding	system	3	6	34.679	3.473e-04	0.905
<i>R_{sm}</i>	MO58A brass; honing	color	3	6	1.76	0.254	0.048
<i>R_{sm}</i>	MO58A brass; honing	system	3	6	32.994	3.995e-04	0.898
<i>R_{sm}</i>	MO58A brass; finish milling	color	3	6	1.097	0.42	0.031
<i>R_{sm}</i>	MO58A brass; finish milling	system	3	6	32.273	4.251e-04	0.912
<i>R_{sm}</i>	MO58A brass; rough milling	color	3	6	3.572	0.086	0.361
<i>R_{sm}</i>	MO58A brass; rough milling	system	3	6	4.317	0.061	0.437
<i>R_{sm}</i>	MO58A brass; finish face turning	color	3	6	4.057	0.068	0.216
<i>R_{sm}</i>	MO58A brass; finish face turning	system	3	6	12.709	0.005	0.677
<i>R_{sm}</i>	MO58A brass; rough face turning	color	3	6	2.441	0.162	0.173
<i>R_{sm}</i>	MO58A brass; rough face turning	system	3	6	9.658	0.01	0.685
<i>R_{sm}</i>	MO58A brass; finish wire EDM	color	3	6	4.273	0.062	0.05
<i>R_{sm}</i>	MO58A brass; finish wire EDM	system	3	6	78.92	3.272e-05	0.926
<i>R_{sm}</i>	MO58A brass; rough wire EDM	color	3	6	4.674	0.052	0.255
<i>R_{sm}</i>	MO58A brass; rough wire EDM	system	3	6	11.65	0.006	0.636
<i>R_{sm}</i>	Ti6Al4V; burnishing after MF	color	3	6	3.787	0.078	0.287
<i>R_{sm}</i>	Ti6Al4V; burnishing after MF	system	3	6	7.398	0.019	0.561
<i>R_{sm}</i>	Ti6Al4V; glass bead blasting	color	3	6	3.831	0.076	0.043
<i>R_{sm}</i>	Ti6Al4V; glass bead blasting	system	3	6	84.143	2.714e-05	0.935
<i>R_{sm}</i>	Ti6Al4V; grinding	color	3	6	3.507	0.089	0.024
<i>R_{sm}</i>	Ti6Al4V; grinding	system	3	6	139.589	6.132e-06	0.962
<i>R_{sm}</i>	Ti6Al4V; honing	color	3	6	1.835	0.241	0.025
<i>R_{sm}</i>	Ti6Al4V; honing	system	3	6	70.638	4.519e-05	0.949

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{sm}	Ti6Al4V; finish milling	color	3	6	2.044	0.209	0.048
R_{sm}	Ti6Al4V; finish milling	system	3	6	38.118	2.659e-04	0.904
R_{sm}	Ti6Al4V; rough milling	color	3	6	5.911	0.032	0.462
R_{sm}	Ti6Al4V; rough milling	system	3	6	4.889	0.047	0.382
R_{sm}	Ti6Al4V; finish face turning	color	3	6	2.974	0.119	0.3
R_{sm}	Ti6Al4V; finish face turning	system	3	6	4.955	0.046	0.499
R_{sm}	Ti6Al4V; rough face turning	color	3	6	4.977	0.046	0.426
R_{sm}	Ti6Al4V; rough face turning	system	3	6	4.707	0.051	0.403
R_{sm}	Ti6Al4V; finish wire EDM	color	3	6	1.698	0.266	0.002
R_{sm}	Ti6Al4V; finish wire EDM	system	3	6	688.575	5.308e-08	0.995
R_{sm}	Ti6Al4V; rough wire EDM	color	3	6	1.215	0.382	0.205
R_{sm}	Ti6Al4V; rough wire EDM	system	3	6	2.719	0.137	0.458
R_t	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	0.341	0.797	0.043
R_t	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	5.547	0.036	0.703
R_t	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.698	0.266	0.062
R_t	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	23.531	0.001	0.864
R_t	AISI 304 / EN 1.4301; grinding	color	3	6	2.221	0.186	0.178
R_t	AISI 304 / EN 1.4301; grinding	system	3	6	8.253	0.015	0.662
R_t	AISI 304 / EN 1.4301; honing	color	3	6	1.23	0.378	0.12
R_t	AISI 304 / EN 1.4301; honing	system	3	6	7.061	0.021	0.686
R_t	AISI 304 / EN 1.4301; finish milling	color	3	6	0.015	0.997	0.005
R_t	AISI 304 / EN 1.4301; finish milling	system	3	6	0.85	0.515	0.297
R_t	AISI 304 / EN 1.4301; rough milling	color	3	6	1.676	0.27	0.437
R_t	AISI 304 / EN 1.4301; rough milling	system	3	6	0.16	0.92	0.042
R_t	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.961	0.47	0.205
R_t	AISI 304 / EN 1.4301; finish face turning	system	3	6	1.733	0.259	0.369
R_t	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.123	0.943	0.028
R_t	AISI 304 / EN 1.4301; rough face turning	system	3	6	2.22	0.187	0.511
R_t	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.099	0.42	0.025
R_t	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	40.002	2.319e-04	0.928
R_t	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.746	0.57	0.143
R_t	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	2.791	0.149	0.536
R_t	Al7075; burnishing after MF	color	3	6	1.752	0.256	0.449
R_t	Al7075; burnishing after MF	system	3	6	0.152	0.924	0.039
R_t	Al7075; glass bead blasting	color	3	6	0.922	0.485	0.127
R_t	Al7075; glass bead blasting	system	3	6	4.324	0.06	0.597
R_t	Al7075; grinding	color	3	6	1.945	0.224	0.064
R_t	Al7075; grinding	system	3	6	26.281	7.529e-04	0.869
R_t	Al7075; honing	color	3	6	2.367	0.17	0.094
R_t	Al7075; honing	system	3	6	20.936	0.001	0.827
R_t	Al7075; finish milling	color	3	6	0.326	0.807	0.095
R_t	Al7075; finish milling	system	3	6	1.116	0.414	0.324
R_t	Al7075; rough milling	color	3	6	0.171	0.912	0.059
R_t	Al7075; rough milling	system	3	6	0.718	0.577	0.248
R_t	Al7075; finish face turning	color	3	6	1.199	0.387	0.245
R_t	Al7075; finish face turning	system	3	6	1.695	0.266	0.346
R_t	Al7075; rough face turning	color	3	6	0.42	0.745	0.082
R_t	Al7075; rough face turning	system	3	6	2.678	0.141	0.525

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_t</i>	Al7075; finish wire EDM	color	3	6	1.043	0.439	0.028
<i>R_t</i>	Al7075; finish wire EDM	system	3	6	34.388	3.556e-04	0.919
<i>R_t</i>	Al7075; rough wire EDM	color	3	6	0.619	0.628	0.017
<i>R_t</i>	Al7075; rough wire EDM	system	3	6	34.019	3.666e-04	0.929
<i>R_t</i>	C45 steel; burnishing after MF	color	3	6	2.241	0.184	0.466
<i>R_t</i>	C45 steel; burnishing after MF	system	3	6	0.568	0.656	0.118
<i>R_t</i>	C45 steel; glass bead blasting	color	3	6	1.399	0.332	0.092
<i>R_t</i>	C45 steel; glass bead blasting	system	3	6	11.837	0.006	0.777
<i>R_t</i>	C45 steel; grinding	color	3	6	2.064	0.206	0.101
<i>R_t</i>	C45 steel; grinding	system	3	6	16.316	0.003	0.801
<i>R_t</i>	C45 steel; honing	color	3	6	0.742	0.565	0.212
<i>R_t</i>	C45 steel; honing	system	3	6	0.766	0.553	0.218
<i>R_t</i>	C45 steel; finish milling	color	3	5	11.117	0.012	0.413
<i>R_t</i>	C45 steel; finish milling	system	3	5	14.113	0.007	0.525
<i>R_t</i>	C45 steel; rough milling	color	3	5	0.582	0.652	0.03
<i>R_t</i>	C45 steel; rough milling	system	3	5	17.292	0.005	0.885
<i>R_t</i>	C45 steel; finish face turning	color	3	5	0.584	0.651	0.031
<i>R_t</i>	C45 steel; finish face turning	system	3	5	16.63	0.005	0.881
<i>R_t</i>	C45 steel; rough face turning	color	3	5	1.477	0.327	0.16
<i>R_t</i>	C45 steel; rough face turning	system	3	5	6.11	0.04	0.66
<i>R_t</i>	C45 steel; finish wire EDM	color	3	6	0.31	0.818	0.011
<i>R_t</i>	C45 steel; finish wire EDM	system	3	6	25.142	8.507e-04	0.916
<i>R_t</i>	C45 steel; rough wire EDM	color	3	6	0.347	0.793	0.017
<i>R_t</i>	C45 steel; rough wire EDM	system	3	6	17.649	0.002	0.883
<i>R_t</i>	ELLOR graphite; glass bead blasting	color	3	6	0.999	0.455	0.046
<i>R_t</i>	ELLOR graphite; glass bead blasting	system	3	6	18.965	0.002	0.863
<i>R_t</i>	ELLOR graphite; grinding	color	3	6	0.552	0.665	0.145
<i>R_t</i>	ELLOR graphite; grinding	system	3	6	1.254	0.371	0.33
<i>R_t</i>	ELLOR graphite; honing	color	3	6	0.929	0.482	0.136
<i>R_t</i>	ELLOR graphite; honing	system	3	6	3.904	0.073	0.571
<i>R_t</i>	ELLOR graphite; finish milling	color	3	6	0.398	0.759	0.15
<i>R_t</i>	ELLOR graphite; finish milling	system	3	6	0.259	0.853	0.097
<i>R_t</i>	ELLOR graphite; rough milling	color	3	6	0.705	0.583	0.237
<i>R_t</i>	ELLOR graphite; rough milling	system	3	6	0.272	0.844	0.091
<i>R_t</i>	ELLOR graphite; finish face turning	color	3	6	0.931	0.482	0.214
<i>R_t</i>	ELLOR graphite; finish face turning	system	3	6	1.411	0.329	0.325
<i>R_t</i>	ELLOR graphite; rough face turning	color	3	6	1.165	0.398	0.274
<i>R_t</i>	ELLOR graphite; rough face turning	system	3	6	1.078	0.426	0.254
<i>R_t</i>	ELLOR graphite; finish wire EDM	color	3	5	1.842	0.257	0.044
<i>R_t</i>	ELLOR graphite; finish wire EDM	system	3	5	38.126	7.204e-04	0.916
<i>R_t</i>	ELLOR graphite; rough wire EDM	color	3	6	0.999	0.455	0.248
<i>R_t</i>	ELLOR graphite; rough wire EDM	system	3	6	1.03	0.444	0.256
<i>R_t</i>	MO58A brass; burnishing after MF	color	2	7	1.152	0.369	0.232
<i>R_t</i>	MO58A brass; burnishing after MF	system	3	7	0.21	0.886	0.064
<i>R_t</i>	MO58A brass; glass bead blasting	color	3	6	1.918	0.228	0.178
<i>R_t</i>	MO58A brass; glass bead blasting	system	3	6	6.854	0.023	0.636
<i>R_t</i>	MO58A brass; grinding	color	3	6	2.332	0.174	0.152
<i>R_t</i>	MO58A brass; grinding	system	3	6	11.017	0.007	0.718
<i>R_t</i>	MO58A brass; honing	color	3	6	0.406	0.754	0.106
<i>R_t</i>	MO58A brass; honing	system	3	6	1.426	0.325	0.372
<i>R_t</i>	MO58A brass; finish milling	color	3	6	1.205	0.385	0.133
<i>R_t</i>	MO58A brass; finish milling	system	3	6	5.873	0.032	0.647
<i>R_t</i>	MO58A brass; rough milling	color	3	6	0.987	0.46	0.125
<i>R_t</i>	MO58A brass; rough milling	system	3	6	4.925	0.047	0.622
<i>R_t</i>	MO58A brass; finish face turning	color	3	6	0.77	0.552	0.053
<i>R_t</i>	MO58A brass; finish face turning	system	3	6	11.665	0.006	0.808

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_t</i>	MO58A brass; rough face turning	color	3	6	1.467	0.315	0.066
<i>R_t</i>	MO58A brass; rough face turning	system	3	6	18.716	0.002	0.844
<i>R_t</i>	MO58A brass; finish wire EDM	color	3	6	2.77	0.133	0.041
<i>R_t</i>	MO58A brass; finish wire EDM	system	3	6	62.999	6.299e-05	0.93
<i>R_t</i>	MO58A brass; rough wire EDM	color	3	6	2.868	0.126	0.299
<i>R_t</i>	MO58A brass; rough wire EDM	system	3	6	4.735	0.05	0.493
<i>R_t</i>	Ti6Al4V; burnishing after MF	color	3	6	0.697	0.587	0.128
<i>R_t</i>	Ti6Al4V; burnishing after MF	system	3	6	2.749	0.135	0.505
<i>R_t</i>	Ti6Al4V; glass bead blasting	color	3	6	0.817	0.53	0.055
<i>R_t</i>	Ti6Al4V; glass bead blasting	system	3	6	12.147	0.006	0.812
<i>R_t</i>	Ti6Al4V; grinding	color	3	6	1.139	0.406	0.062
<i>R_t</i>	Ti6Al4V; grinding	system	3	6	15.122	0.003	0.828
<i>R_t</i>	Ti6Al4V; honing	color	3	6	3.619	0.084	0.141
<i>R_t</i>	Ti6Al4V; honing	system	3	6	20.074	0.002	0.781
<i>R_t</i>	Ti6Al4V; finish milling	color	3	6	0.3	0.825	0.039
<i>R_t</i>	Ti6Al4V; finish milling	system	3	6	5.364	0.039	0.7
<i>R_t</i>	Ti6Al4V; rough milling	color	3	6	1.777	0.251	0.352
<i>R_t</i>	Ti6Al4V; rough milling	system	3	6	1.277	0.364	0.253
<i>R_t</i>	Ti6Al4V; finish face turning	color	3	6	1.568	0.292	0.236
<i>R_t</i>	Ti6Al4V; finish face turning	system	3	6	3.078	0.112	0.463
<i>R_t</i>	Ti6Al4V; rough face turning	color	3	6	1.11	0.416	0.101
<i>R_t</i>	Ti6Al4V; rough face turning	system	3	6	7.923	0.016	0.718
<i>R_t</i>	Ti6Al4V; finish wire EDM	color	3	6	5.611	0.036	0.062
<i>R_t</i>	Ti6Al4V; finish wire EDM	system	3	6	82.601	2.864e-05	0.916
<i>R_t</i>	Ti6Al4V; rough wire EDM	color	3	6	0.954	0.472	0.053
<i>R_t</i>	Ti6Al4V; rough wire EDM	system	3	6	15.168	0.003	0.837
<i>R_v</i>	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	0.602	0.637	0.106
<i>R_v</i>	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	3.097	0.111	0.543
<i>R_v</i>	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.432	0.323	0.068
<i>R_v</i>	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	17.752	0.002	0.838
<i>R_v</i>	AISI 304 / EN 1.4301; grinding	color	3	6	0.778	0.548	0.061
<i>R_v</i>	AISI 304 / EN 1.4301; grinding	system	3	6	9.89	0.01	0.781
<i>R_v</i>	AISI 304 / EN 1.4301; honing	color	3	6	4.062	0.068	0.166
<i>R_v</i>	AISI 304 / EN 1.4301; honing	system	3	6	18.403	0.002	0.752
<i>R_v</i>	AISI 304 / EN 1.4301; finish milling	color	3	6	0.484	0.706	0.08
<i>R_v</i>	AISI 304 / EN 1.4301; finish milling	system	3	6	3.585	0.086	0.591
<i>R_v</i>	AISI 304 / EN 1.4301; rough milling	color	3	6	1.873	0.235	0.472
<i>R_v</i>	AISI 304 / EN 1.4301; rough milling	system	3	6	0.092	0.962	0.023
<i>R_v</i>	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.467	0.716	0.152
<i>R_v</i>	AISI 304 / EN 1.4301; finish face turning	system	3	6	0.609	0.633	0.198
<i>R_v</i>	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.676	0.598	0.178
<i>R_v</i>	AISI 304 / EN 1.4301; rough face turning	system	3	6	1.126	0.411	0.296
<i>R_v</i>	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.165	0.398	0.027
<i>R_v</i>	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	40.274	2.275e-04	0.927
<i>R_v</i>	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	1.324	0.365	0.191
<i>R_v</i>	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	3.946	0.087	0.569
<i>R_v</i>	Al7075; burnishing after MF	color	3	6	1.425	0.325	0.405
<i>R_v</i>	Al7075; burnishing after MF	system	3	6	0.096	0.96	0.027

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
<i>R_v</i>	Al7075; glass bead blasting	color	3	6	1.697	0.266	0.1
<i>R_v</i>	Al7075; glass bead blasting	system	3	6	13.32	0.005	0.783
<i>R_v</i>	Al7075; grinding	color	3	6	0.793	0.541	0.144
<i>R_v</i>	Al7075; grinding	system	3	6	2.698	0.139	0.491
<i>R_v</i>	Al7075; honing	color	3	6	0.499	0.697	0.057
<i>R_v</i>	Al7075; honing	system	3	6	6.275	0.028	0.715
<i>R_v</i>	Al7075; finish milling	color	3	6	1.085	0.424	0.254
<i>R_v</i>	Al7075; finish milling	system	3	6	1.185	0.391	0.278
<i>R_v</i>	Al7075; rough milling	color	3	6	0.229	0.873	0.072
<i>R_v</i>	Al7075; rough milling	system	3	6	0.959	0.47	0.301
<i>R_v</i>	Al7075; finish face turning	color	3	6	1.296	0.359	0.303
<i>R_v</i>	Al7075; finish face turning	system	3	6	0.985	0.46	0.23
<i>R_v</i>	Al7075; rough face turning	color	3	6	0.848	0.516	0.174
<i>R_v</i>	Al7075; rough face turning	system	3	6	2.018	0.213	0.415
<i>R_v</i>	Al7075; finish wire EDM	color	3	6	0.721	0.575	0.016
<i>R_v</i>	Al7075; finish wire EDM	system	3	6	41.49	2.090e-04	0.938
<i>R_v</i>	Al7075; rough wire EDM	color	3	6	1.187	0.391	0.031
<i>R_v</i>	Al7075; rough wire EDM	system	3	6	35.438	3.268e-04	0.917
<i>R_v</i>	C45 steel; burnishing after MF	color	3	6	1.917	0.228	0.428
<i>R_v</i>	C45 steel; burnishing after MF	system	3	6	0.559	0.662	0.125
<i>R_v</i>	C45 steel; glass bead blasting	color	3	6	1.504	0.306	0.095
<i>R_v</i>	C45 steel; glass bead blasting	system	3	6	12.353	0.006	0.779
<i>R_v</i>	C45 steel; grinding	color	3	6	0.727	0.572	0.064
<i>R_v</i>	C45 steel; grinding	system	3	6	8.548	0.014	0.758
<i>R_v</i>	C45 steel; honing	color	3	6	3.316	0.099	0.239
<i>R_v</i>	C45 steel; honing	system	3	6	8.559	0.014	0.617
<i>R_v</i>	C45 steel; finish milling	color	3	5	1.456	0.332	0.337
<i>R_v</i>	C45 steel; finish milling	system	3	5	1.196	0.4	0.277
<i>R_v</i>	C45 steel; rough milling	color	3	5	0.372	0.777	0.041
<i>R_v</i>	C45 steel; rough milling	system	3	5	6.957	0.031	0.773
<i>R_v</i>	C45 steel; finish face turning	color	3	5	0.386	0.769	0.037
<i>R_v</i>	C45 steel; finish face turning	system	3	5	8.51	0.021	0.806
<i>R_v</i>	C45 steel; rough face turning	color	3	5	1.138	0.418	0.221
<i>R_v</i>	C45 steel; rough face turning	system	3	5	2.351	0.189	0.456
<i>R_v</i>	C45 steel; finish wire EDM	color	3	6	2.098	0.202	0.023
<i>R_v</i>	C45 steel; finish wire EDM	system	3	6	87.505	2.420e-05	0.955
<i>R_v</i>	C45 steel; rough wire EDM	color	3	6	0.49	0.702	0.058
<i>R_v</i>	C45 steel; rough wire EDM	system	3	6	5.911	0.032	0.704
<i>R_v</i>	ELLOR graphite; glass bead blasting	color	3	6	0.143	0.93	0.024
<i>R_v</i>	ELLOR graphite; glass bead blasting	system	3	6	3.777	0.078	0.638
<i>R_v</i>	ELLOR graphite; grinding	color	3	6	1.687	0.268	0.34
<i>R_v</i>	ELLOR graphite; grinding	system	3	6	1.278	0.364	0.257
<i>R_v</i>	ELLOR graphite; honing	color	3	6	0.565	0.658	0.069
<i>R_v</i>	ELLOR graphite; honing	system	3	6	5.598	0.036	0.686
<i>R_v</i>	ELLOR graphite; finish milling	color	3	6	0.395	0.762	0.138
<i>R_v</i>	ELLOR graphite; finish milling	system	3	6	0.466	0.717	0.163
<i>R_v</i>	ELLOR graphite; rough milling	color	3	6	0.608	0.634	0.108
<i>R_v</i>	ELLOR graphite; rough milling	system	3	6	3.024	0.115	0.537
<i>R_v</i>	ELLOR graphite; finish face turning	color	3	6	0.506	0.692	0.149
<i>R_v</i>	ELLOR graphite; finish face turning	system	3	6	0.904	0.492	0.265
<i>R_v</i>	ELLOR graphite; rough face turning	color	3	6	0.763	0.555	0.14
<i>R_v</i>	ELLOR graphite; rough face turning	system	3	6	2.701	0.139	0.494
<i>R_v</i>	ELLOR graphite; finish wire EDM	color	3	5	0.45	0.728	0.02
<i>R_v</i>	ELLOR graphite; finish wire EDM	system	3	5	19.855	0.003	0.904
<i>R_v</i>	ELLOR graphite; rough wire EDM	color	3	6	0.467	0.716	0.063
<i>R_v</i>	ELLOR graphite; rough wire EDM	system	3	6	4.945	0.046	0.667
<i>R_v</i>	MO58A brass; burnishing after MF	color	2	7	0.778	0.495	0.159

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_v	MO58A brass; burnishing after MF	system	3	7	0.415	0.748	0.127
R_v	MO58A brass; glass bead blasting	color	3	6	2.588	0.148	0.18
R_v	MO58A brass; glass bead blasting	system	3	6	9.788	0.01	0.681
R_v	MO58A brass; grinding	color	3	6	5.406	0.038	0.175
R_v	MO58A brass; grinding	system	3	6	23.477	0.001	0.76
R_v	MO58A brass; honing	color	3	6	2.386	0.168	0.189
R_v	MO58A brass; honing	system	3	6	8.244	0.015	0.653
R_v	MO58A brass; finish milling	color	3	6	0.472	0.713	0.083
R_v	MO58A brass; finish milling	system	3	6	3.197	0.105	0.564
R_v	MO58A brass; rough milling	color	3	6	0.551	0.666	0.108
R_v	MO58A brass; rough milling	system	3	6	2.558	0.151	0.501
R_v	MO58A brass; finish face turning	color	3	6	0.359	0.785	0.043
R_v	MO58A brass; finish face turning	system	3	6	5.927	0.032	0.715
R_v	MO58A brass; rough face turning	color	3	6	0.468	0.715	0.064
R_v	MO58A brass; rough face turning	system	3	6	4.898	0.047	0.665
R_v	MO58A brass; finish wire EDM	color	3	6	1.378	0.337	0.033
R_v	MO58A brass; finish wire EDM	system	3	6	38.419	2.601e-04	0.919
R_v	MO58A brass; rough wire EDM	color	3	6	0.639	0.617	0.229
R_v	MO58A brass; rough wire EDM	system	3	6	0.147	0.928	0.053
R_v	Ti6Al4V; burnishing after MF	color	3	6	0.111	0.951	0.021
R_v	Ti6Al4V; burnishing after MF	system	3	6	3.047	0.114	0.591
R_v	Ti6Al4V; glass bead blasting	color	3	6	1.974	0.219	0.079
R_v	Ti6Al4V; glass bead blasting	system	3	6	21.126	0.001	0.842
R_v	Ti6Al4V; grinding	color	3	6	0.549	0.667	0.048
R_v	Ti6Al4V; grinding	system	3	6	8.847	0.013	0.776
R_v	Ti6Al4V; honing	color	3	6	1.874	0.235	0.079
R_v	Ti6Al4V; honing	system	3	6	19.717	0.002	0.836
R_v	Ti6Al4V; finish milling	color	3	6	0.258	0.853	0.033
R_v	Ti6Al4V; finish milling	system	3	6	5.458	0.038	0.707
R_v	Ti6Al4V; rough milling	color	3	6	0.637	0.618	0.127
R_v	Ti6Al4V; rough milling	system	3	6	2.364	0.17	0.473
R_v	Ti6Al4V; finish face turning	color	3	6	0.429	0.74	0.135
R_v	Ti6Al4V; finish face turning	system	3	6	0.75	0.561	0.236
R_v	Ti6Al4V; rough face turning	color	3	6	0.489	0.703	0.08
R_v	Ti6Al4V; rough face turning	system	3	6	3.641	0.083	0.594
R_v	Ti6Al4V; finish wire EDM	color	3	6	1.702	0.265	0.028
R_v	Ti6Al4V; finish wire EDM	system	3	6	57.858	8.057e-05	0.94
R_v	Ti6Al4V; rough wire EDM	color	3	6	1.06	0.433	0.071
R_v	Ti6Al4V; rough wire EDM	system	3	6	11.846	0.006	0.795
R_z	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	1.634	0.278	0.169
R_z	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	6.043	0.03	0.624
R_z	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	2.237	0.184	0.023
R_z	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	92.943	2.029e-05	0.956
R_z	AISI 304 / EN 1.4301; grinding	color	3	6	1.167	0.397	0.038
R_z	AISI 304 / EN 1.4301; grinding	system	3	6	27.254	6.808e-04	0.896
R_z	AISI 304 / EN 1.4301; honing	color	3	6	2.049	0.209	0.079
R_z	AISI 304 / EN 1.4301; honing	system	3	6	21.98	0.001	0.844
R_z	AISI 304 / EN 1.4301; finish milling	color	3	6	0.739	0.566	0.152
R_z	AISI 304 / EN 1.4301; finish milling	system	3	6	2.113	0.2	0.436
R_z	AISI 304 / EN 1.4301; rough milling	color	3	6	1.948	0.223	0.481
R_z	AISI 304 / EN 1.4301; rough milling	system	3	6	0.099	0.958	0.024
R_z	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.93	0.482	0.183
R_z	AISI 304 / EN 1.4301; finish face turning	system	3	6	2.155	0.194	0.424

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_z	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.855	0.513	0.218
R_z	AISI 304 / EN 1.4301; rough face turning	system	3	6	1.076	0.427	0.274
R_z	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	2.164	0.193	0.028
R_z	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	74.192	3.917e-05	0.947
R_z	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	1.686	0.284	0.149
R_z	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	7.968	0.024	0.704
R_z	Al7075; burnishing after MF	color	3	6	1.822	0.244	0.464
R_z	Al7075; burnishing after MF	system	3	6	0.106	0.954	0.027
R_z	Al7075; glass bead blasting	color	3	6	1.582	0.289	0.091
R_z	Al7075; glass bead blasting	system	3	6	13.828	0.004	0.794
R_z	Al7075; grinding	color	3	6	0.967	0.467	0.105
R_z	Al7075; grinding	system	3	6	6.247	0.028	0.678
R_z	Al7075; honing	color	3	6	2.425	0.164	0.081
R_z	Al7075; honing	system	3	6	25.46	8.217e-04	0.852
R_z	Al7075; finish milling	color	3	6	1.367	0.34	0.307
R_z	Al7075; finish milling	system	3	6	1.088	0.423	0.244
R_z	Al7075; rough milling	color	3	6	0.261	0.851	0.077
R_z	Al7075; rough milling	system	3	6	1.136	0.407	0.334
R_z	Al7075; finish face turning	color	3	6	1.162	0.399	0.259
R_z	Al7075; finish face turning	system	3	6	1.322	0.352	0.295
R_z	Al7075; rough face turning	color	3	6	0.99	0.459	0.188
R_z	Al7075; rough face turning	system	3	6	2.286	0.179	0.433
R_z	Al7075; finish wire EDM	color	3	6	4.502	0.056	0.018
R_z	Al7075; finish wire EDM	system	3	6	242.043	1.200e-06	0.974
R_z	Al7075; rough wire EDM	color	3	6	1.15	0.402	0.021
R_z	Al7075; rough wire EDM	system	3	6	51.901	1.102e-04	0.943
R_z	C45 steel; burnishing after MF	color	3	6	2.563	0.151	0.514
R_z	C45 steel; burnishing after MF	system	3	6	0.425	0.742	0.085
R_z	C45 steel; glass bead blasting	color	3	6	1.748	0.257	0.063
R_z	C45 steel; glass bead blasting	system	3	6	24.199	9.449e-04	0.866
R_z	C45 steel; grinding	color	3	6	1.371	0.339	0.042
R_z	C45 steel; grinding	system	3	6	29.48	5.474e-04	0.897
R_z	C45 steel; honing	color	3	6	1.924	0.227	0.203
R_z	C45 steel; honing	system	3	6	5.544	0.036	0.586
R_z	C45 steel; finish milling	color	3	5	2	0.233	0.089
R_z	C45 steel; finish milling	system	3	5	18.738	0.004	0.836
R_z	C45 steel; rough milling	color	3	5	0.755	0.565	0.05
R_z	C45 steel; rough milling	system	3	5	12.543	0.009	0.838
R_z	C45 steel; finish face turning	color	3	5	0.595	0.645	0.04
R_z	C45 steel; finish face turning	system	3	5	12.649	0.009	0.848
R_z	C45 steel; rough face turning	color	3	5	1.58	0.305	0.218
R_z	C45 steel; rough face turning	system	3	5	4.009	0.085	0.553
R_z	C45 steel; finish wire EDM	color	3	6	0.578	0.65	0.009
R_z	C45 steel; finish wire EDM	system	3	6	63.479	6.162e-05	0.961
R_z	C45 steel; rough wire EDM	color	3	6	0.408	0.753	0.035
R_z	C45 steel; rough wire EDM	system	3	6	9.344	0.011	0.795
R_z	ELLOR graphite; glass bead blasting	color	3	6	1.529	0.301	0.172
R_z	ELLOR graphite; glass bead blasting	system	3	6	5.372	0.039	0.604
R_z	ELLOR graphite; grinding	color	3	6	4.504	0.056	0.136
R_z	ELLOR graphite; grinding	system	3	6	26.636	7.255e-04	0.804
R_z	ELLOR graphite; honing	color	3	6	0.517	0.686	0.031
R_z	ELLOR graphite; honing	system	3	6	14.385	0.004	0.851
R_z	ELLOR graphite; finish milling	color	3	6	0.341	0.797	0.116
R_z	ELLOR graphite; finish milling	system	3	6	0.609	0.633	0.207
R_z	ELLOR graphite; rough milling	color	3	6	0.52	0.684	0.071
R_z	ELLOR graphite; rough milling	system	3	6	4.853	0.048	0.658

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_z	ELLOR graphite; finish face turning	color	3	6	0.362	0.783	0.124
R_z	ELLOR graphite; finish face turning	system	3	6	0.56	0.661	0.192
R_z	ELLOR graphite; rough face turning	color	3	6	0.738	0.567	0.233
R_z	ELLOR graphite; rough face turning	system	3	6	0.43	0.739	0.136
R_z	ELLOR graphite; finish wire EDM	color	3	5	1.095	0.432	0.027
R_z	ELLOR graphite; finish wire EDM	system	3	5	37.921	7.297e-04	0.932
R_z	ELLOR graphite; rough wire EDM	color	3	6	0.747	0.562	0.187
R_z	ELLOR graphite; rough wire EDM	system	3	6	1.249	0.372	0.313
R_z	MO58A brass; burnishing after MF	color	2	7	1.061	0.396	0.216
R_z	MO58A brass; burnishing after MF	system	3	7	0.227	0.875	0.069
R_z	MO58A brass; glass bead blasting	color	3	6	2.734	0.136	0.157
R_z	MO58A brass; glass bead blasting	system	3	6	12.659	0.005	0.728
R_z	MO58A brass; grinding	color	3	6	2.6	0.147	0.065
R_z	MO58A brass; grinding	system	3	6	35.479	3.257e-04	0.885
R_z	MO58A brass; honing	color	3	6	2.191	0.19	0.191
R_z	MO58A brass; honing	system	3	6	7.306	0.02	0.635
R_z	MO58A brass; finish milling	color	3	6	1.497	0.308	0.188
R_z	MO58A brass; finish milling	system	3	6	4.458	0.057	0.56
R_z	MO58A brass; rough milling	color	3	6	1.486	0.31	0.18
R_z	MO58A brass; rough milling	system	3	6	4.755	0.05	0.577
R_z	MO58A brass; finish face turning	color	3	6	0.916	0.487	0.054
R_z	MO58A brass; finish face turning	system	3	6	13.988	0.004	0.827
R_z	MO58A brass; rough face turning	color	3	6	1.407	0.329	0.068
R_z	MO58A brass; rough face turning	system	3	6	17.42	0.002	0.836
R_z	MO58A brass; finish wire EDM	color	3	6	2.373	0.169	0.034
R_z	MO58A brass; finish wire EDM	system	3	6	65.195	5.703e-05	0.937
R_z	MO58A brass; rough wire EDM	color	3	6	2.553	0.152	0.366
R_z	MO58A brass; rough wire EDM	system	3	6	2.421	0.164	0.347
R_z	Ti6Al4V; burnishing after MF	color	3	6	0.469	0.715	0.076
R_z	Ti6Al4V; burnishing after MF	system	3	6	3.677	0.082	0.598
R_z	Ti6Al4V; glass bead blasting	color	3	6	3.741	0.079	0.041
R_z	Ti6Al4V; glass bead blasting	system	3	6	84.806	2.652e-05	0.937
R_z	Ti6Al4V; grinding	color	3	6	0.838	0.521	0.051
R_z	Ti6Al4V; grinding	system	3	6	13.608	0.004	0.827
R_z	Ti6Al4V; honing	color	3	6	2.635	0.144	0.061
R_z	Ti6Al4V; honing	system	3	6	38.684	2.550e-04	0.893
R_z	Ti6Al4V; finish milling	color	3	6	0.352	0.79	0.023
R_z	Ti6Al4V; finish milling	system	3	6	13.199	0.005	0.849
R_z	Ti6Al4V; rough milling	color	3	6	1.179	0.394	0.202
R_z	Ti6Al4V; rough milling	system	3	6	2.656	0.142	0.455
R_z	Ti6Al4V; finish face turning	color	3	6	1.131	0.409	0.292
R_z	Ti6Al4V; finish face turning	system	3	6	0.747	0.562	0.193
R_z	Ti6Al4V; rough face turning	color	3	6	0.566	0.657	0.073
R_z	Ti6Al4V; rough face turning	system	3	6	5.21	0.042	0.67
R_z	Ti6Al4V; finish wire EDM	color	3	6	5.269	0.041	0.044
R_z	Ti6Al4V; finish wire EDM	system	3	6	113.343	1.133e-05	0.94
R_z	Ti6Al4V; rough wire EDM	color	3	6	0.824	0.527	0.048
R_z	Ti6Al4V; rough wire EDM	system	3	6	14.472	0.004	0.837
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	color	3	6	0.292	0.83	0.042
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	system	3	6	4.664	0.052	0.671
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	color	3	6	1.652	0.275	0.048
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	system	3	6	30.938	4.784e-04	0.894
R_{z1max}	AISI 304 / EN 1.4301; grinding	color	3	6	2.139	0.197	0.132
R_{z1max}	AISI 304 / EN 1.4301; grinding	system	3	6	12.03	0.006	0.744

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{z1max}	AISI 304 / EN 1.4301; honing	color	3	6	1.204	0.386	0.115
R_{z1max}	AISI 304 / EN 1.4301; honing	system	3	6	7.263	0.02	0.694
R_{z1max}	AISI 304 / EN 1.4301; finish milling	color	3	6	0.049	0.984	0.016
R_{z1max}	AISI 304 / EN 1.4301; finish milling	system	3	6	1.048	0.437	0.339
R_{z1max}	AISI 304 / EN 1.4301; rough milling	color	3	6	1.694	0.267	0.439
R_{z1max}	AISI 304 / EN 1.4301; rough milling	system	3	6	0.165	0.916	0.043
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	color	3	6	0.889	0.499	0.196
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	system	3	6	1.636	0.278	0.362
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	color	3	6	0.143	0.931	0.028
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	system	3	6	2.923	0.122	0.577
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	color	3	6	1.424	0.325	0.03
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	system	3	6	44.151	1.751e-04	0.928
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	color	3	5	0.748	0.568	0.149
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	system	3	5	2.603	0.164	0.519
R_{z1max}	Al7075; burnishing after MF	color	3	6	1.795	0.248	0.456
R_{z1max}	Al7075; burnishing after MF	system	3	6	0.142	0.931	0.036
R_{z1max}	Al7075; glass bead blasting	color	3	6	0.958	0.471	0.112
R_{z1max}	Al7075; glass bead blasting	system	3	6	5.612	0.036	0.655
R_{z1max}	Al7075; grinding	color	3	6	1.912	0.229	0.069
R_{z1max}	Al7075; grinding	system	3	6	23.81	9.878e-04	0.859
R_{z1max}	Al7075; honing	color	3	6	2.651	0.143	0.097
R_{z1max}	Al7075; honing	system	3	6	22.748	0.001	0.83
R_{z1max}	Al7075; finish milling	color	3	6	0.302	0.823	0.091
R_{z1max}	Al7075; finish milling	system	3	6	1.008	0.452	0.304
R_{z1max}	Al7075; rough milling	color	3	6	0.173	0.911	0.059
R_{z1max}	Al7075; rough milling	system	3	6	0.768	0.552	0.261
R_{z1max}	Al7075; finish face turning	color	3	6	1.122	0.412	0.233
R_{z1max}	Al7075; finish face turning	system	3	6	1.701	0.265	0.353
R_{z1max}	Al7075; rough face turning	color	3	6	0.479	0.709	0.08
R_{z1max}	Al7075; rough face turning	system	3	6	3.484	0.09	0.584
R_{z1max}	Al7075; finish wire EDM	color	3	6	1.085	0.424	0.025
R_{z1max}	Al7075; finish wire EDM	system	3	6	40.1	2.303e-04	0.929
R_{z1max}	Al7075; rough wire EDM	color	3	6	0.591	0.643	0.016
R_{z1max}	Al7075; rough wire EDM	system	3	6	35.39	3.280e-04	0.932
R_{z1max}	C45 steel; burnishing after MF	color	3	6	2.264	0.181	0.469
R_{z1max}	C45 steel; burnishing after MF	system	3	6	0.561	0.66	0.116
R_{z1max}	C45 steel; glass bead blasting	color	3	6	1.652	0.275	0.092
R_{z1max}	C45 steel; glass bead blasting	system	3	6	14.291	0.004	0.796
R_{z1max}	C45 steel; grinding	color	3	6	2.074	0.205	0.094
R_{z1max}	C45 steel; grinding	system	3	6	17.92	0.002	0.815
R_{z1max}	C45 steel; honing	color	3	6	1.042	0.439	0.256
R_{z1max}	C45 steel; honing	system	3	6	1.034	0.442	0.254
R_{z1max}	C45 steel; finish milling	color	3	5	7.471	0.027	0.404
R_{z1max}	C45 steel; finish milling	system	3	5	9.367	0.017	0.506
R_{z1max}	C45 steel; rough milling	color	3	5	0.648	0.617	0.036
R_{z1max}	C45 steel; rough milling	system	3	5	15.542	0.006	0.87
R_{z1max}	C45 steel; finish face turning	color	3	5	0.611	0.636	0.036
R_{z1max}	C45 steel; finish face turning	system	3	5	14.862	0.006	0.867
R_{z1max}	C45 steel; rough face turning	color	3	5	1.516	0.319	0.156
R_{z1max}	C45 steel; rough face turning	system	3	5	6.541	0.035	0.673
R_{z1max}	C45 steel; finish wire EDM	color	3	6	0.32	0.811	0.012
R_{z1max}	C45 steel; finish wire EDM	system	3	6	25.078	8.567e-04	0.915

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	<i>F</i>	<i>p</i>	η^2
R_{z1max}	C45 steel; rough wire EDM	color	3	6	0.401	0.758	0.02
R_{z1max}	C45 steel; rough wire EDM	system	3	6	17.511	0.002	0.879
R_{z1max}	ELLOR graphite; glass bead blasting	color	3	6	1.045	0.438	0.057
R_{z1max}	ELLOR graphite; glass bead blasting	system	3	6	15.369	0.003	0.835
R_{z1max}	ELLOR graphite; grinding	color	3	6	0.529	0.679	0.135
R_{z1max}	ELLOR graphite; grinding	system	3	6	1.402	0.331	0.357
R_{z1max}	ELLOR graphite; honing	color	3	6	3.241	0.103	0.233
R_{z1max}	ELLOR graphite; honing	system	3	6	8.647	0.013	0.623
R_{z1max}	ELLOR graphite; finish milling	color	3	6	0.414	0.75	0.158
R_{z1max}	ELLOR graphite; finish milling	system	3	6	0.212	0.885	0.081
R_{z1max}	ELLOR graphite; rough milling	color	3	6	0.713	0.579	0.235
R_{z1max}	ELLOR graphite; rough milling	system	3	6	0.316	0.814	0.104
R_{z1max}	ELLOR graphite; finish face turning	color	3	6	0.761	0.556	0.199
R_{z1max}	ELLOR graphite; finish face turning	system	3	6	1.059	0.433	0.277
R_{z1max}	ELLOR graphite; rough face turning	color	3	6	1.144	0.404	0.279
R_{z1max}	ELLOR graphite; rough face turning	system	3	6	0.961	0.47	0.234
R_{z1max}	ELLOR graphite; finish wire EDM	color	3	5	2	0.233	0.052
R_{z1max}	ELLOR graphite; finish wire EDM	system	3	5	34.547	9.103e-04	0.904
R_{z1max}	ELLOR graphite; rough wire EDM	color	3	6	1.044	0.439	0.254
R_{z1max}	ELLOR graphite; rough wire EDM	system	3	6	1.063	0.432	0.259
R_{z1max}	MO58A brass; burnishing after MF	color	2	7	1.154	0.369	0.234
R_{z1max}	MO58A brass; burnishing after MF	system	3	7	0.183	0.905	0.056
R_{z1max}	MO58A brass; glass bead blasting	color	3	6	2.376	0.169	0.185
R_{z1max}	MO58A brass; glass bead blasting	system	3	6	8.466	0.014	0.659
R_{z1max}	MO58A brass; grinding	color	3	6	2.254	0.183	0.134
R_{z1max}	MO58A brass; grinding	system	3	6	12.557	0.005	0.747
R_{z1max}	MO58A brass; honing	color	3	6	0.694	0.589	0.179
R_{z1max}	MO58A brass; honing	system	3	6	1.185	0.391	0.306
R_{z1max}	MO58A brass; finish milling	color	3	6	1.301	0.357	0.15
R_{z1max}	MO58A brass; finish milling	system	3	6	5.352	0.039	0.619
R_{z1max}	MO58A brass; rough milling	color	3	6	0.927	0.483	0.121
R_{z1max}	MO58A brass; rough milling	system	3	6	4.71	0.051	0.617
R_{z1max}	MO58A brass; finish face turning	color	3	6	0.769	0.552	0.053
R_{z1max}	MO58A brass; finish face turning	system	3	6	11.814	0.006	0.81
R_{z1max}	MO58A brass; rough face turning	color	3	6	1.471	0.314	0.071
R_{z1max}	MO58A brass; rough face turning	system	3	6	17.191	0.002	0.832
R_{z1max}	MO58A brass; finish wire EDM	color	3	6	2.821	0.129	0.041
R_{z1max}	MO58A brass; finish wire EDM	system	3	6	63.754	6.085e-05	0.93
R_{z1max}	MO58A brass; rough wire EDM	color	3	6	2.301	0.177	0.311
R_{z1max}	MO58A brass; rough wire EDM	system	3	6	3.086	0.112	0.418
R_{z1max}	Ti6Al4V; burnishing after MF	color	3	6	0.553	0.665	0.102
R_{z1max}	Ti6Al4V; burnishing after MF	system	3	6	2.877	0.125	0.53
R_{z1max}	Ti6Al4V; glass bead blasting	color	3	6	1.665	0.272	0.058
R_{z1max}	Ti6Al4V; glass bead blasting	system	3	6	25.006	8.635e-04	0.872
R_{z1max}	Ti6Al4V; grinding	color	3	6	0.973	0.465	0.059
R_{z1max}	Ti6Al4V; grinding	system	3	6	13.549	0.004	0.82
R_{z1max}	Ti6Al4V; honing	color	3	6	3.773	0.078	0.13
R_{z1max}	Ti6Al4V; honing	system	3	6	23.346	0.001	0.802
R_{z1max}	Ti6Al4V; finish milling	color	3	6	0.24	0.865	0.025
R_{z1max}	Ti6Al4V; finish milling	system	3	6	7.331	0.02	0.766
R_{z1max}	Ti6Al4V; rough milling	color	3	6	1.674	0.27	0.336
R_{z1max}	Ti6Al4V; rough milling	system	3	6	1.314	0.354	0.263
R_{z1max}	Ti6Al4V; finish face turning	color	3	6	1.732	0.259	0.234
R_{z1max}	Ti6Al4V; finish face turning	system	3	6	3.684	0.082	0.497
R_{z1max}	Ti6Al4V; rough face turning	color	3	6	1.367	0.34	0.12
R_{z1max}	Ti6Al4V; rough face turning	system	3	6	8.003	0.016	0.704

Continued on next page

Parameter	Material/process	Term	df ₁	df ₂	F	p	η^2
R_{z1max}	Ti6Al4V; finish wire EDM	color	3	6	5.899	0.032	0.058
R_{z1max}	Ti6Al4V; finish wire EDM	system	3	6	93.827	1.973e-05	0.922
R_{z1max}	Ti6Al4V; rough wire EDM	color	3	6	0.94	0.478	0.052
R_{z1max}	Ti6Al4V; rough wire EDM	system	3	6	15.178	0.003	0.838

2.2 Table S2: System-wise slope versus wavelength

Table S2: Linear slope (per nm) of $|\text{diff}|(\%)$ versus wavelength, estimated separately for each system. Reported are the number of wavelength levels n , 95% confidence interval bounds, and p -values; these fits should be interpreted as low-degree-of-freedom screening summaries.

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_a	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.9063	-2.6381	0.8256	0.492
R_a	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.2795	0.031	0.528	0.271
R_a	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.3245	-0.0089	0.6578	0.307
R_a	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.7164	-1.4061	2.839	0.628
R_a	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0377	-0.1963	0.121	0.723
R_a	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.1881	0.1388	0.2374	0.085
R_a	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.1605	0.1543	0.1668	0.013
R_a	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0125	-0.1163	0.1414	0.88
R_a	AISI 304 / EN 1.4301; grinding	FV	3	-0.0068	-0.3283	0.3147	0.974
R_a	AISI 304 / EN 1.4301; grinding	conf	3	0.0861	0.0835	0.0887	0.01
R_a	AISI 304 / EN 1.4301; grinding	fusion	3	0.0929	0.0726	0.1132	0.071
R_a	AISI 304 / EN 1.4301; grinding	int	3	-0.0186	-0.067	0.0299	0.59
R_a	AISI 304 / EN 1.4301; honing	FV	3	0.3854	0.2219	0.5489	0.136
R_a	AISI 304 / EN 1.4301; honing	conf	3	0.1854	0.1038	0.267	0.141
R_a	AISI 304 / EN 1.4301; honing	fusion	3	0.1552	0.1472	0.1632	0.017
R_a	AISI 304 / EN 1.4301; honing	int	3	-0.0153	-0.0686	0.038	0.674
R_a	AISI 304 / EN 1.4301; finish milling	FV	3	-0.2846	-0.8432	0.2741	0.501
R_a	AISI 304 / EN 1.4301; finish milling	conf	3	0.2336	0.2041	0.263	0.041
R_a	AISI 304 / EN 1.4301; finish milling	fusion	3	0.3468	0.2531	0.4404	0.087
R_a	AISI 304 / EN 1.4301; finish milling	int	3	-0.4066	-1.5263	0.7132	0.606
R_a	AISI 304 / EN 1.4301; rough milling	FV	3	0.0377	-0.0154	0.0907	0.397
R_a	AISI 304 / EN 1.4301; rough milling	conf	3	-0.042	-0.0523	-0.0316	0.08
R_a	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0444	-0.0573	-0.0315	0.094
R_a	AISI 304 / EN 1.4301; rough milling	int	3	-0.0173	-0.256	0.2214	0.91
R_a	AISI 304 / EN 1.4301; finish face turning	FV	3	0.1427	-0.0179	0.3034	0.332
R_a	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0321	-0.0465	-0.0177	0.143
R_a	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0458	-0.0705	-0.021	0.171
R_a	AISI 304 / EN 1.4301; finish face turning	int	3	0.0155	-0.0808	0.1118	0.805

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_a	AISI 304 / EN 1.4301; rough face turning	FV	3	0.0844	-0.0273	0.1961	0.378
R_a	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0209	-0.0331	-0.0088	0.184
R_a	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.0322	-0.049	-0.0154	0.166
R_a	AISI 304 / EN 1.4301; rough face turning	int	3	0.0216	-0.0699	0.1131	0.724
R_a	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-0.0373	-0.3703	0.2957	0.862
R_a	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.1679	0.1271	0.2086	0.078
R_a	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.1872	0.1056	0.2688	0.139
R_a	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.017	-0.1248	0.0907	0.809
R_a	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0355	-0.0714	4.8622e-04	0.304
R_a	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0154	0.0049	0.026	0.214
R_a	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	-1.0331e-04	-0.045	0.0448	0.997
R_a	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0371	—	—	—
R_a	Al7075; burnishing after MF	FV	3	-1.0199	-2.5981	0.5583	0.425
R_a	Al7075; burnishing after MF	conf	3	0.1401	-0.0536	0.3339	0.391
R_a	Al7075; burnishing after MF	fusion	3	0.1407	-0.1036	0.385	0.462
R_a	Al7075; burnishing after MF	int	3	3.5856	-2.5288	9.7	0.456
R_a	Al7075; glass bead blasting	FV	3	-0.0741	-0.1563	0.0081	0.328
R_a	Al7075; glass bead blasting	conf	3	0.2236	0.1346	0.3125	0.127
R_a	Al7075; glass bead blasting	fusion	3	0.1818	0.1511	0.2124	0.055
R_a	Al7075; glass bead blasting	int	3	-7.4857e-04	-0.0366	0.0351	0.974
R_a	Al7075; grinding	FV	3	-0.0941	-0.5287	0.3406	0.745
R_a	Al7075; grinding	conf	3	0.1648	0.1362	0.1934	0.056
R_a	Al7075; grinding	fusion	3	0.1814	0.1316	0.2313	0.089
R_a	Al7075; grinding	int	3	-0.0306	-0.1823	0.1211	0.76
R_a	Al7075; honing	FV	3	-0.024	-0.2491	0.201	0.869
R_a	Al7075; honing	conf	3	-0.1024	-0.1417	-0.0631	0.123
R_a	Al7075; honing	fusion	3	-0.1126	-0.166	-0.0593	0.151
R_a	Al7075; honing	int	3	-0.0046	-0.076	0.0668	0.921
R_a	Al7075; finish milling	FV	3	-0.6069	-1.6255	0.4118	0.451
R_a	Al7075; finish milling	conf	3	0.3209	0.2699	0.372	0.052
R_a	Al7075; finish milling	fusion	3	0.3085	0.2565	0.3605	0.055
R_a	Al7075; finish milling	int	3	1.2945	-0.8354	3.4243	0.445
R_a	Al7075; rough milling	FV	3	-0.9383	-1.699	-0.1776	0.25
R_a	Al7075; rough milling	conf	3	0.2087	0.1454	0.272	0.098
R_a	Al7075; rough milling	fusion	3	0.2561	0.0994	0.4128	0.193
R_a	Al7075; rough milling	int	3	0.7367	-0.0236	1.4969	0.309
R_a	Al7075; finish face turning	FV	3	0.1282	-0.0364	0.2929	0.369
R_a	Al7075; finish face turning	conf	3	-0.1048	-0.1407	-0.0689	0.11
R_a	Al7075; finish face turning	fusion	3	-0.1289	-0.1922	-0.0655	0.156
R_a	Al7075; finish face turning	int	3	-0.0949	-0.3861	0.1964	0.638
R_a	Al7075; rough face turning	FV	3	0.0259	-0.0104	0.0621	0.395
R_a	Al7075; rough face turning	conf	3	-0.0081	-0.013	-0.0031	0.192
R_a	Al7075; rough face turning	fusion	3	-0.011	-0.0137	-0.0083	0.079
R_a	Al7075; rough face turning	int	3	0.0172	-0.0227	0.0571	0.553
R_a	Al7075; finish wire EDM	FV	3	-0.0765	-0.4146	0.2617	0.734
R_a	Al7075; finish wire EDM	conf	3	0.1532	-0.0108	0.3172	0.318
R_a	Al7075; finish wire EDM	fusion	3	0.1657	-0.174	0.5055	0.514
R_a	Al7075; finish wire EDM	int	3	-0.1638	-0.3869	0.0593	0.387
R_a	Al7075; rough wire EDM	FV	3	-0.0566	-0.0836	-0.0295	0.152
R_a	Al7075; rough wire EDM	conf	3	0.0567	0.0419	0.0715	0.084
R_a	Al7075; rough wire EDM	fusion	3	0.1204	0.0971	0.1436	0.063
R_a	Al7075; rough wire EDM	int	3	-0.0257	-0.0714	0.02	0.469

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_a	C45 steel; burnishing after MF	FV	3	-0.6036	-2.1002	0.893	0.574
R_a	C45 steel; burnishing after MF	conf	2	0.5056	—	—	—
R_a	C45 steel; burnishing after MF	fusion	3	0.5176	0.3719	0.6633	0.091
R_a	C45 steel; burnishing after MF	int	4	-2.9736	-5.9551	0.0078	0.19
R_a	C45 steel; glass bead blasting	FV	3	-0.0069	-0.1643	0.1505	0.945
R_a	C45 steel; glass bead blasting	conf	3	0.2259	0.1392	0.3126	0.123
R_a	C45 steel; glass bead blasting	fusion	3	0.2292	0.1708	0.2877	0.082
R_a	C45 steel; glass bead blasting	int	3	-0.0148	-0.0235	-0.006	0.186
R_a	C45 steel; grinding	FV	3	-0.0426	-0.6062	0.521	0.906
R_a	C45 steel; grinding	conf	3	0.2032	0.1363	0.27	0.106
R_a	C45 steel; grinding	fusion	3	0.2217	0.1346	0.3088	0.126
R_a	C45 steel; grinding	int	3	0.027	-0.1056	0.1595	0.759
R_a	C45 steel; honing	FV	3	0.3484	0.1795	0.5173	0.154
R_a	C45 steel; honing	conf	3	0.1095	0.1042	0.1148	0.016
R_a	C45 steel; honing	fusion	3	0.1357	0.1081	0.1633	0.066
R_a	C45 steel; honing	int	3	-0.0106	-0.1005	0.0794	0.856
R_a	C45 steel; finish milling	FV	3	-0.0019	-0.1229	0.119	0.98
R_a	C45 steel; finish milling	conf	2	-0.1009	—	—	—
R_a	C45 steel; finish milling	fusion	3	-0.0167	-0.169	0.1356	0.865
R_a	C45 steel; finish milling	int	3	-0.0119	-0.0366	0.0129	0.519
R_a	C45 steel; rough milling	FV	3	0.0108	-0.0346	0.0563	0.722
R_a	C45 steel; rough milling	conf	2	-0.0366	—	—	—
R_a	C45 steel; rough milling	fusion	3	-0.0481	-0.055	-0.0412	0.046
R_a	C45 steel; rough milling	int	3	0.0355	-0.0228	0.0937	0.444
R_a	C45 steel; finish face turning	FV	3	-0.0042	-0.0334	0.0251	0.827
R_a	C45 steel; finish face turning	conf	2	-0.0256	—	—	—
R_a	C45 steel; finish face turning	fusion	3	-0.0389	-0.0505	-0.0272	0.097
R_a	C45 steel; finish face turning	int	3	0.0216	-0.0099	0.0532	0.407
R_a	C45 steel; rough face turning	FV	3	0.0324	-0.0153	0.08	0.41
R_a	C45 steel; rough face turning	conf	2	-0.0159	—	—	—
R_a	C45 steel; rough face turning	fusion	3	-0.0249	-0.0395	-0.0103	0.185
R_a	C45 steel; rough face turning	int	3	0.0044	-0.0538	0.0625	0.907
R_a	C45 steel; finish wire EDM	FV	3	0.121	-0.1058	0.3478	0.486
R_a	C45 steel; finish wire EDM	conf	3	0.2033	0.0619	0.3447	0.217
R_a	C45 steel; finish wire EDM	fusion	3	0.1762	0.0643	0.2882	0.2
R_a	C45 steel; finish wire EDM	int	3	-0.0455	-0.1094	0.0184	0.396
R_a	C45 steel; rough wire EDM	FV	3	0.0067	-0.0128	0.0262	0.621
R_a	C45 steel; rough wire EDM	conf	3	0.0428	0.0309	0.0547	0.09
R_a	C45 steel; rough wire EDM	fusion	3	0.0732	0.0573	0.089	0.07
R_a	C45 steel; rough wire EDM	int	3	-0.1506	-0.3383	0.0371	0.361
R_a	ELLOR graphite; glass bead blasting	FV	3	-0.0078	-0.0155	-7.3601e-05	0.298
R_a	ELLOR graphite; glass bead blasting	conf	3	0.0118	-2.9940e-04	0.0238	0.307
R_a	ELLOR graphite; glass bead blasting	fusion	3	0.0096	-0.003	0.0223	0.376
R_a	ELLOR graphite; glass bead blasting	int	3	0.0115	-0.014	0.0371	0.539
R_a	ELLOR graphite; grinding	FV	3	-0.0874	-0.2046	0.0299	0.382
R_a	ELLOR graphite; grinding	conf	3	0.1028	0.0651	0.1406	0.118
R_a	ELLOR graphite; grinding	fusion	3	0.1423	0.0169	0.2678	0.269
R_a	ELLOR graphite; grinding	int	3	0.9541	0.3437	1.5645	0.201
R_a	ELLOR graphite; honing	FV	3	-0.4457	-1.4422	0.5507	0.542
R_a	ELLOR graphite; honing	conf	3	0.5048	0.3991	0.6106	0.068
R_a	ELLOR graphite; honing	fusion	3	0.5614	0.344	0.7787	0.124
R_a	ELLOR graphite; honing	int	3	-0.2017	-0.53	0.1266	0.441
R_a	ELLOR graphite; finish milling	FV	3	0.057	-0.1419	0.256	0.674
R_a	ELLOR graphite; finish milling	conf	3	0.1059	0.074	0.1379	0.097
R_a	ELLOR graphite; finish milling	fusion	3	0.2007	0.17	0.2313	0.049
R_a	ELLOR graphite; finish milling	int	3	-0.2367	-0.5201	0.0466	0.349
R_a	ELLOR graphite; rough milling	FV	3	0.035	-0.0536	0.1237	0.58
R_a	ELLOR graphite; rough milling	conf	3	0.1008	0.0801	0.1214	0.066
R_a	ELLOR graphite; rough milling	fusion	3	0.1194	0.095	0.1438	0.066
R_a	ELLOR graphite; rough milling	int	3	-0.3099	-0.748	0.1283	0.398

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_a	ELLOR graphite; finish face turning	FV	3	0.0073	-0.066	0.0805	0.878
R_a	ELLOR graphite; finish face turning	conf	3	0.095	0.0933	0.0968	0.006
R_a	ELLOR graphite; finish face turning	fusion	3	0.1173	0.0763	0.1584	0.112
R_a	ELLOR graphite; finish face turning	int	3	-0.1384	-0.3597	0.083	0.436
R_a	ELLOR graphite; rough face turning	FV	3	0.013	-2.2603e-04	0.0263	0.305
R_a	ELLOR graphite; rough face turning	conf	3	-0.0091	-0.0098	-0.0085	0.024
R_a	ELLOR graphite; rough face turning	fusion	3	-0.0128	-0.0183	-0.0074	0.135
R_a	ELLOR graphite; rough face turning	int	3	-0.2265	-0.5651	0.1121	0.415
R_a	ELLOR graphite; finish wire EDM	FV	3	-0.0361	-0.1284	0.0561	0.583
R_a	ELLOR graphite; finish wire EDM	conf	3	0.082	0.0638	0.1001	0.072
R_a	ELLOR graphite; finish wire EDM	fusion	3	0.0845	0.0622	0.1069	0.085
R_a	ELLOR graphite; finish wire EDM	int	2	0.0943	—	—	—
R_a	ELLOR graphite; rough wire EDM	FV	3	-0.0319	-0.0577	-0.0061	0.249
R_a	ELLOR graphite; rough wire EDM	conf	3	0.0716	0.0439	0.0993	0.124
R_a	ELLOR graphite; rough wire EDM	fusion	3	0.0838	0.0661	0.1014	0.068
R_a	ELLOR graphite; rough wire EDM	int	3	-0.1206	-0.4345	0.1933	0.589
R_a	MO58A brass; burnishing after MF	FV	4	-1.8508	-5.7604	2.0588	0.451
R_a	MO58A brass; burnishing after MF	conf	3	-0.0589	-0.6886	0.5707	0.885
R_a	MO58A brass; burnishing after MF	fusion	3	-0.1112	-0.9223	0.6998	0.833
R_a	MO58A brass; burnishing after MF	int	3	7.7626	-1.8441	17.3692	0.359
R_a	MO58A brass; glass bead blasting	FV	3	0.1111	0.0176	0.2047	0.258
R_a	MO58A brass; glass bead blasting	conf	3	0.312	0.1282	0.4957	0.186
R_a	MO58A brass; glass bead blasting	fusion	3	0.2666	0.204	0.3292	0.076
R_a	MO58A brass; glass bead blasting	int	3	0.0459	-0.0387	0.1304	0.481
R_a	MO58A brass; grinding	FV	3	0.179	-0.0754	0.4334	0.399
R_a	MO58A brass; grinding	conf	3	0.1203	0.0534	0.1872	0.176
R_a	MO58A brass; grinding	fusion	3	-0.0991	-0.3674	0.1692	0.601
R_a	MO58A brass; grinding	int	3	-0.0077	-0.0744	0.0591	0.859
R_a	MO58A brass; honing	FV	3	0.3024	0.0889	0.5159	0.22
R_a	MO58A brass; honing	conf	3	0.1487	0.0873	0.2101	0.132
R_a	MO58A brass; honing	fusion	3	0.0897	0.0461	0.1334	0.155
R_a	MO58A brass; honing	int	3	-0.0111	-0.0839	0.0616	0.815
R_a	MO58A brass; finish milling	FV	3	-1.1612	-3.0601	0.7377	0.443
R_a	MO58A brass; finish milling	conf	3	0.3465	0.2673	0.4257	0.074
R_a	MO58A brass; finish milling	fusion	3	0.448	0.2511	0.6448	0.14
R_a	MO58A brass; finish milling	int	3	1.7547	-0.6565	4.166	0.389
R_a	MO58A brass; rough milling	FV	3	0.2059	-0.0619	0.4737	0.373
R_a	MO58A brass; rough milling	conf	3	-0.0336	-0.0396	-0.0276	0.058
R_a	MO58A brass; rough milling	fusion	3	-0.0316	-0.0494	-0.0139	0.178
R_a	MO58A brass; rough milling	int	3	0.0331	-0.0678	0.134	0.636
R_a	MO58A brass; finish face turning	FV	3	0.0201	-0.0361	0.0762	0.611
R_a	MO58A brass; finish face turning	conf	3	-0.0236	-0.027	-0.0202	0.047
R_a	MO58A brass; finish face turning	fusion	3	-0.0107	-0.0398	0.0184	0.603
R_a	MO58A brass; finish face turning	int	3	0.0149	-0.0068	0.0365	0.407
R_a	MO58A brass; rough face turning	FV	3	0.0216	-0.0412	0.0843	0.623
R_a	MO58A brass; rough face turning	conf	3	-0.03	-0.035	-0.0251	0.054
R_a	MO58A brass; rough face turning	fusion	3	-0.0203	-0.0384	-0.0022	0.272
R_a	MO58A brass; rough face turning	int	3	0.0055	-0.0099	0.021	0.611
R_a	MO58A brass; finish wire EDM	FV	3	-0.0035	-0.2735	0.2664	0.984
R_a	MO58A brass; finish wire EDM	conf	3	0.2341	0.1402	0.3279	0.128
R_a	MO58A brass; finish wire EDM	fusion	3	0.0252	-0.2365	0.2869	0.881
R_a	MO58A brass; finish wire EDM	int	3	-3.1727e-04	-0.0015	8.8863e-04	0.697

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_a	MO58A brass; rough wire EDM	FV	3	-0.0397	-0.0465	-0.0328	0.056
R_a	MO58A brass; rough wire EDM	conf	3	-0.1095	-0.2035	-0.0154	0.263
R_a	MO58A brass; rough wire EDM	fusion	3	-0.0797	-0.1143	-0.0451	0.139
R_a	MO58A brass; rough wire EDM	int	3	-0.069	-0.1873	0.0494	0.458
R_a	Ti6Al4V; burnishing after MF	FV	3	-0.4847	-1.0675	0.0981	0.35
R_a	Ti6Al4V; burnishing after MF	conf	3	0.4781	0.3842	0.5721	0.064
R_a	Ti6Al4V; burnishing after MF	fusion	3	0.4881	0.4038	0.5723	0.056
R_a	Ti6Al4V; burnishing after MF	int	3	0.099	-0.2908	0.4889	0.706
R_a	Ti6Al4V; glass bead blasting	FV	3	0.1186	-0.1222	0.3594	0.511
R_a	Ti6Al4V; glass bead blasting	conf	3	0.2803	0.2351	0.3255	0.052
R_a	Ti6Al4V; glass bead blasting	fusion	3	0.2843	0.2517	0.3169	0.037
R_a	Ti6Al4V; glass bead blasting	int	3	1.1631e-04	-0.1433	0.1436	0.999
R_a	Ti6Al4V; grinding	FV	3	-0.2146	-0.5947	0.1655	0.468
R_a	Ti6Al4V; grinding	conf	3	0.2107	0.1527	0.2686	0.089
R_a	Ti6Al4V; grinding	fusion	3	0.2529	0.1903	0.3155	0.08
R_a	Ti6Al4V; grinding	int	3	-0.0051	-0.0408	0.0306	0.825
R_a	Ti6Al4V; honing	FV	3	0.3709	-0.1422	0.8841	0.391
R_a	Ti6Al4V; honing	conf	3	0.299	0.1545	0.4435	0.154
R_a	Ti6Al4V; honing	fusion	3	0.3785	0.1696	0.5873	0.175
R_a	Ti6Al4V; honing	int	3	-0.0169	-0.0339	4.2803e-05	0.301
R_a	Ti6Al4V; finish milling	FV	3	-0.1611	-0.4143	0.0922	0.43
R_a	Ti6Al4V; finish milling	conf	3	0.1518	0.1043	0.1993	0.101
R_a	Ti6Al4V; finish milling	fusion	3	0.1568	0.1089	0.2047	0.098
R_a	Ti6Al4V; finish milling	int	3	0.033	-0.0117	0.0777	0.385
R_a	Ti6Al4V; rough milling	FV	3	-0.255	-0.6193	0.1092	0.401
R_a	Ti6Al4V; rough milling	conf	3	0.0777	-0.0111	0.1664	0.336
R_a	Ti6Al4V; rough milling	fusion	3	0.1646	0.0967	0.2324	0.132
R_a	Ti6Al4V; rough milling	int	3	0.3222	0.1445	0.4998	0.175
R_a	Ti6Al4V; finish face turning	FV	3	-0.0412	-0.0944	0.0119	0.37
R_a	Ti6Al4V; finish face turning	conf	3	-0.0702	-0.089	-0.0514	0.086
R_a	Ti6Al4V; finish face turning	fusion	3	-0.0771	-0.0858	-0.0684	0.037
R_a	Ti6Al4V; finish face turning	int	3	0.0071	-0.0862	0.1005	0.905
R_a	Ti6Al4V; rough face turning	FV	3	-0.0149	-0.0258	-0.004	0.228
R_a	Ti6Al4V; rough face turning	conf	3	-0.0381	-0.0432	-0.033	0.043
R_a	Ti6Al4V; rough face turning	fusion	3	-0.0398	-0.0445	-0.0351	0.038
R_a	Ti6Al4V; rough face turning	int	3	0.0352	-0.0137	0.084	0.392
R_a	Ti6Al4V; finish wire EDM	FV	3	0.1576	-0.2501	0.5653	0.587
R_a	Ti6Al4V; finish wire EDM	conf	3	0.2864	0.1843	0.3884	0.115
R_a	Ti6Al4V; finish wire EDM	fusion	3	0.347	0.2484	0.4457	0.092
R_a	Ti6Al4V; finish wire EDM	int	3	0.0427	-0.0765	0.1619	0.61
R_a	Ti6Al4V; rough wire EDM	FV	3	-0.0097	-0.0122	-0.0071	0.086
R_a	Ti6Al4V; rough wire EDM	conf	3	0.0407	0.0379	0.0436	0.023
R_a	Ti6Al4V; rough wire EDM	fusion	3	0.1135	0.0891	0.138	0.07
R_a	Ti6Al4V; rough wire EDM	int	3	-0.1422	-0.3308	0.0464	0.379
rku	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-3.1253e-04	-0.0066	0.006	0.938
rku	AISI 304 / EN 1.4301; burnishing after MF	conf	3	-0.0161	-0.0353	0.0032	0.349
rku	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	-0.0176	-0.0335	-0.0018	0.273
rku	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.0358	0.0276	0.0441	0.075
rku	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0601	-0.0849	-0.0352	0.132
rku	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.0332	-0.0186	0.0851	0.428
rku	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	-0.092	-0.2987	0.1148	0.543
rku	AISI 304 / EN 1.4301; glass bead blasting	int	3	-0.0652	-0.0684	-0.062	0.016
rku	AISI 304 / EN 1.4301; grinding	FV	3	-0.0231	-0.0343	-0.0118	0.156
rku	AISI 304 / EN 1.4301; grinding	conf	3	0.0124	0.0046	0.0202	0.198
rku	AISI 304 / EN 1.4301; grinding	fusion	3	0.0731	-0.0312	0.1773	0.401
rku	AISI 304 / EN 1.4301; grinding	int	3	-0.0371	-0.0836	0.0094	0.362

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rku	AISI 304 / EN 1.4301; honing	FV	3	0.0191	0.0061	0.0321	0.212
rku	AISI 304 / EN 1.4301; honing	conf	3	-0.0377	-0.0567	-0.0186	0.161
rku	AISI 304 / EN 1.4301; honing	fusion	3	-0.0264	-0.1162	0.0634	0.668
rku	AISI 304 / EN 1.4301; honing	int	3	-0.036	-0.1038	0.0317	0.486
rku	AISI 304 / EN 1.4301; finish milling	FV	3	0.0379	-0.0296	0.1054	0.469
rku	AISI 304 / EN 1.4301; finish milling	conf	3	-0.0525	-0.0816	-0.0234	0.175
rku	AISI 304 / EN 1.4301; finish milling	fusion	3	-0.0689	-0.1094	-0.0285	0.185
rku	AISI 304 / EN 1.4301; finish milling	int	3	0.0087	-0.1559	0.1733	0.934
rku	AISI 304 / EN 1.4301; rough milling	FV	3	-0.0573	-0.144	0.0295	0.419
rku	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0098	-0.0449	0.0253	0.681
rku	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0565	-0.1222	0.0092	0.341
rku	AISI 304 / EN 1.4301; rough milling	int	3	-0.2832	-0.9124	0.346	0.54
rku	AISI 304 / EN 1.4301; finish face turning	FV	3	0.0771	0.0107	0.1436	0.263
rku	AISI 304 / EN 1.4301; finish face turning	conf	3	0.0075	-0.0027	0.0177	0.387
rku	AISI 304 / EN 1.4301; finish face turning	fusion	3	0.0072	-0.0109	0.0253	0.578
rku	AISI 304 / EN 1.4301; finish face turning	int	3	0.0846	-0.0598	0.229	0.456
rku	AISI 304 / EN 1.4301; rough face turning	FV	3	0.0351	0.0236	0.0466	0.106
rku	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0163	-0.0516	0.019	0.531
rku	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.0288	-0.0476	-0.0101	0.204
rku	AISI 304 / EN 1.4301; rough face turning	int	3	0.0585	-0.2234	0.3405	0.754
rku	AISI 304 / EN 1.4301; finish wire EDM	FV	3	0.0026	-0.0205	0.0258	0.86
rku	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.059	0.0498	0.0681	0.05
rku	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	-0.2052	-0.5606	0.1503	0.461
rku	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.027	-0.1272	0.0732	0.691
rku	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0286	-0.0531	-0.0042	0.261
rku	AISI 304 / EN 1.4301; rough wire EDM	conf	3	-0.0216	-0.0347	-0.0085	0.191
rku	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.0962	0.0747	0.1177	0.072
rku	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0181	—	—	—
rku	Al7075; burnishing after MF	FV	3	-0.0223	-0.0323	-0.0123	0.143
rku	Al7075; burnishing after MF	conf	3	0.1338	0.0359	0.2317	0.228
rku	Al7075; burnishing after MF	fusion	3	0.2865	0.215	0.358	0.081
rku	Al7075; burnishing after MF	int	3	0.0209	-0.0453	0.087	0.648
rku	Al7075; glass bead blasting	FV	3	-0.0423	-0.0842	-4.4194e-04	0.298
rku	Al7075; glass bead blasting	conf	3	0.0775	0.0682	0.0869	0.039
rku	Al7075; glass bead blasting	fusion	3	0.2865	-0.5646	1.1377	0.629
rku	Al7075; glass bead blasting	int	3	-0.0182	-0.0552	0.0189	0.513
rku	Al7075; grinding	FV	3	-0.0268	-0.0349	-0.0188	0.096
rku	Al7075; grinding	conf	3	-0.0101	-0.0107	-0.0095	0.019
rku	Al7075; grinding	fusion	3	-0.0054	-0.0116	7.5545e-04	0.335
rku	Al7075; grinding	int	3	0.0051	-0.0881	0.0984	0.932

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rku	Al7075; honing	FV	3	0.0359	-0.197	0.2687	0.813
rku	Al7075; honing	conf	3	-0.0361	-0.0592	-0.0129	0.202
rku	Al7075; honing	fusion	3	-0.0272	-0.0275	-0.027	0.003
rku	Al7075; honing	int	3	0.0063	-0.2587	0.2713	0.97
rku	Al7075; finish milling	FV	3	0.0223	-0.0185	0.0631	0.477
rku	Al7075; finish milling	conf	3	-0.016	-0.0254	-0.0066	0.186
rku	Al7075; finish milling	fusion	3	-0.022	-0.0271	-0.0168	0.076
rku	Al7075; finish milling	int	3	0.0079	-0.0032	0.0191	0.397
rku	Al7075; rough milling	FV	3	0.0353	-0.026	0.0966	0.462
rku	Al7075; rough milling	conf	3	-0.025	-0.0473	-0.0027	0.272
rku	Al7075; rough milling	fusion	3	-0.0128	-0.04	0.0144	0.525
rku	Al7075; rough milling	int	3	-0.043	-0.1079	0.0219	0.418
rku	Al7075; finish face turning	FV	3	0.0214	-0.0142	0.057	0.448
rku	Al7075; finish face turning	conf	3	-0.0062	-0.0112	-0.0012	0.25
rku	Al7075; finish face turning	fusion	3	-0.0069	-0.0134	-4.6338e-04	0.283
rku	Al7075; finish face turning	int	3	0.0145	-0.0584	0.0873	0.764
rku	Al7075; rough face turning	FV	3	-0.1272	-0.2808	0.0264	0.352
rku	Al7075; rough face turning	conf	3	0.069	0.0611	0.0768	0.037
rku	Al7075; rough face turning	fusion	3	0.0494	0.0387	0.0601	0.07
rku	Al7075; rough face turning	int	3	-0.0844	-0.2984	0.1297	0.581
rku	Al7075; finish wire EDM	FV	3	-9.4759e-04	-0.0166	0.0147	0.925
rku	Al7075; finish wire EDM	conf	3	-0.0739	-0.1849	0.0371	0.416
rku	Al7075; finish wire EDM	fusion	3	-0.2341	-0.6004	0.1321	0.429
rku	Al7075; finish wire EDM	int	3	-0.0382	-0.0691	-0.0072	0.25
rku	Al7075; rough wire EDM	FV	3	0.0223	0.0092	0.0354	0.186
rku	Al7075; rough wire EDM	conf	3	0.5716	0.271	0.8722	0.167
rku	Al7075; rough wire EDM	fusion	3	0.4622	-0.0746	0.999	0.341
rku	Al7075; rough wire EDM	int	3	-0.2716	-0.6623	0.1191	0.403
rku	C45 steel; burnishing after MF	FV	3	0.0236	-0.0052	0.0525	0.355
rku	C45 steel; burnishing after MF	conf	2	-0.0246	—	—	—
rku	C45 steel; burnishing after MF	fusion	3	-0.0378	-0.0413	-0.0343	0.03
rku	C45 steel; burnishing after MF	int	4	-0.0288	-0.0423	-0.0153	0.053
rku	C45 steel; glass bead blasting	FV	3	0.0436	-0.0082	0.0954	0.347
rku	C45 steel; glass bead blasting	conf	3	0.0184	-0.0092	0.0461	0.416
rku	C45 steel; glass bead blasting	fusion	3	0.0954	0.0376	0.1532	0.191
rku	C45 steel; glass bead blasting	int	3	-0.0138	-0.1701	0.1426	0.891
rku	C45 steel; grinding	FV	3	-0.0753	-0.1065	-0.0442	0.132
rku	C45 steel; grinding	conf	3	-0.0127	-0.0164	-0.009	0.093
rku	C45 steel; grinding	fusion	3	-0.0022	-0.018	0.0137	0.834
rku	C45 steel; grinding	int	3	0.0093	-0.1671	0.1857	0.934
rku	C45 steel; honing	FV	3	0.032	0.0192	0.0449	0.128
rku	C45 steel; honing	conf	3	-0.0369	-0.0538	-0.02	0.146
rku	C45 steel; honing	fusion	3	0.0381	0.0283	0.0478	0.083
rku	C45 steel; honing	int	3	-0.055	-0.1502	0.0403	0.461
rku	C45 steel; finish milling	FV	3	0.1806	0.1611	0.2002	0.035
rku	C45 steel; finish milling	conf	2	-0.0068	—	—	—
rku	C45 steel; finish milling	fusion	3	-0.0622	-0.116	-0.0084	0.265
rku	C45 steel; finish milling	int	3	0.3197	-0.3134	0.9528	0.503
rku	C45 steel; rough milling	FV	3	0.0183	-0.0171	0.0537	0.496
rku	C45 steel; rough milling	conf	2	0.001	—	—	—
rku	C45 steel; rough milling	fusion	3	-0.0376	-0.0951	0.0199	0.422
rku	C45 steel; rough milling	int	3	-0.0229	-0.0889	0.0431	0.62
rku	C45 steel; finish face turning	FV	3	0.0164	0.0114	0.0215	0.099
rku	C45 steel; finish face turning	conf	2	-0.0072	—	—	—
rku	C45 steel; finish face turning	fusion	3	0.0061	-0.013	0.0252	0.643
rku	C45 steel; finish face turning	int	3	0.0028	-0.0364	0.042	0.911
rku	C45 steel; rough face turning	FV	3	-0.0031	-0.0194	0.0132	0.774
rku	C45 steel; rough face turning	conf	2	0.0042	—	—	—
rku	C45 steel; rough face turning	fusion	3	0.0076	-0.0185	0.0336	0.671
rku	C45 steel; rough face turning	int	3	0.0452	0.0337	0.0568	0.082
rku	C45 steel; finish wire EDM	FV	3	0.0117	-0.0126	0.0359	0.518
rku	C45 steel; finish wire EDM	conf	3	0.1443	0.0744	0.2143	0.154
rku	C45 steel; finish wire EDM	fusion	3	-0.6891	-1.7102	0.332	0.412
rku	C45 steel; finish wire EDM	int	3	-0.0128	-0.0452	0.0195	0.579

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rku	C45 steel; rough wire EDM	FV	3	-0.0023	-0.0103	0.0057	0.674
rku	C45 steel; rough wire EDM	conf	3	0.0044	-0.0038	0.0125	0.484
rku	C45 steel; rough wire EDM	fusion	3	0.7194	0.7094	0.7295	0.005
rku	C45 steel; rough wire EDM	int	3	-0.07	-0.1652	0.0251	0.386
rku	ELLOR graphite; glass bead blasting	FV	3	-0.0015	-0.0086	0.0056	0.751
rku	ELLOR graphite; glass bead blasting	conf	3	0.0044	-0.015	0.0237	0.735
rku	ELLOR graphite; glass bead blasting	fusion	3	0.0014	0.001	0.0017	0.082
rku	ELLOR graphite; glass bead blasting	int	3	0.0665	-0.0284	0.1614	0.401
rku	ELLOR graphite; grinding	FV	3	-0.0174	-0.0647	0.0299	0.603
rku	ELLOR graphite; grinding	conf	3	0.0279	0.0201	0.0357	0.09
rku	ELLOR graphite; grinding	fusion	3	0.0274	0.0017	0.0532	0.284
rku	ELLOR graphite; grinding	int	3	0.1354	0.1119	0.1589	0.056
rku	ELLOR graphite; honing	FV	3	-3.6608e-04	-0.0045	0.0037	0.89
rku	ELLOR graphite; honing	conf	3	-0.0061	-0.0123	1.4847e-04	0.307
rku	ELLOR graphite; honing	fusion	3	0.0092	-0.0138	0.0322	0.578
rku	ELLOR graphite; honing	int	3	0.0023	-0.2229	0.2275	0.987
rku	ELLOR graphite; finish milling	FV	3	0.0408	-0.2043	0.286	0.799
rku	ELLOR graphite; finish milling	conf	3	0.1033	0.0933	0.1132	0.031
rku	ELLOR graphite; finish milling	fusion	3	-0.2532	-0.4959	-0.0105	0.29
rku	ELLOR graphite; finish milling	int	3	-0.3772	-0.5392	-0.2152	0.137
rku	ELLOR graphite; rough milling	FV	3	0.0114	-0.1004	0.1231	0.875
rku	ELLOR graphite; rough milling	conf	3	0.0783	0.0726	0.0841	0.024
rku	ELLOR graphite; rough milling	fusion	3	0.0472	0.0187	0.0758	0.19
rku	ELLOR graphite; rough milling	int	3	-0.2563	-0.7103	0.1976	0.468
rku	ELLOR graphite; finish face turning	FV	3	0.0236	-0.0223	0.0695	0.498
rku	ELLOR graphite; finish face turning	conf	3	0.0608	0.0569	0.0646	0.02
rku	ELLOR graphite; finish face turning	fusion	3	0.0186	0.0046	0.0325	0.233
rku	ELLOR graphite; finish face turning	int	3	-0.2447	-0.6703	0.1808	0.462
rku	ELLOR graphite; rough face turning	FV	3	0.0031	0.0022	0.004	0.095
rku	ELLOR graphite; rough face turning	conf	3	0.0189	0.0164	0.0215	0.044
rku	ELLOR graphite; rough face turning	fusion	3	-0.0055	-0.0161	0.0051	0.495
rku	ELLOR graphite; rough face turning	int	3	-0.0181	-0.0503	0.014	0.468
rku	ELLOR graphite; finish wire EDM	FV	3	-0.0016	-0.0402	0.0369	0.947
rku	ELLOR graphite; finish wire EDM	conf	3	0.0497	0.049	0.0503	0.004
rku	ELLOR graphite; finish wire EDM	fusion	3	0.0233	0.0047	0.0419	0.246
rku	ELLOR graphite; finish wire EDM	int	2	0.0041	—	—	—
rku	ELLOR graphite; rough wire EDM	FV	3	-0.0196	-0.0687	0.0296	0.578
rku	ELLOR graphite; rough wire EDM	conf	3	0.0305	0.0227	0.0383	0.082
rku	ELLOR graphite; rough wire EDM	fusion	3	0.0223	0.0182	0.0264	0.059
rku	ELLOR graphite; rough wire EDM	int	3	-0.0579	-0.1709	0.0552	0.499
rku	MO58A brass; burnishing after MF	FV	4	0.023	-0.0023	0.0483	0.217
rku	MO58A brass; burnishing after MF	conf	3	-0.0262	-0.0443	-0.0081	0.216
rku	MO58A brass; burnishing after MF	fusion	3	-0.0392	-0.0549	-0.0236	0.128
rku	MO58A brass; burnishing after MF	int	3	0.0082	-0.0166	0.033	0.634
rku	MO58A brass; glass bead blasting	FV	3	-0.0062	-0.0594	0.047	0.857
rku	MO58A brass; glass bead blasting	conf	3	0.0989	0.0877	0.11	0.037
rku	MO58A brass; glass bead blasting	fusion	3	0.382	0.365	0.399	0.014
rku	MO58A brass; glass bead blasting	int	3	-0.0011	-0.0268	0.0246	0.947

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rku	MO58A brass; grinding	FV	3	-0.0148	-0.0303	7.8717e-04	0.314
rku	MO58A brass; grinding	conf	3	-0.0149	-0.0214	-0.0085	0.139
rku	MO58A brass; grinding	fusion	3	-0.0701	-0.1318	-0.0084	0.269
rku	MO58A brass; grinding	int	3	-0.0485	-0.1117	0.0148	0.374
rku	MO58A brass; honing	FV	3	-0.003	-0.0642	0.0582	0.939
rku	MO58A brass; honing	conf	3	-0.0482	-0.0937	-0.0027	0.286
rku	MO58A brass; honing	fusion	3	-0.0388	-0.0966	0.0189	0.413
rku	MO58A brass; honing	int	3	-0.0474	-0.0963	0.0015	0.309
rku	MO58A brass; finish milling	FV	3	-0.031	-0.0403	-0.0218	0.096
rku	MO58A brass; finish milling	conf	3	-0.0205	-0.0827	0.0417	0.635
rku	MO58A brass; finish milling	fusion	3	-0.0356	-0.0829	0.0116	0.379
rku	MO58A brass; finish milling	int	3	0.1091	-0.4953	0.7136	0.783
rku	MO58A brass; rough milling	FV	3	-0.0353	-0.0983	0.0277	0.47
rku	MO58A brass; rough milling	conf	3	-0.0096	-0.0587	0.0394	0.766
rku	MO58A brass; rough milling	fusion	3	-0.0798	-0.2075	0.048	0.436
rku	MO58A brass; rough milling	int	3	-0.0537	-0.2209	0.1135	0.642
rku	MO58A brass; finish face turning	FV	3	0.0104	-0.0271	0.0479	0.682
rku	MO58A brass; finish face turning	conf	3	-0.0139	-0.0235	-0.0042	0.216
rku	MO58A brass; finish face turning	fusion	3	-0.0162	-0.0311	-0.0012	0.28
rku	MO58A brass; finish face turning	int	3	0.0438	0.0077	0.08	0.254
rku	MO58A brass; rough face turning	FV	3	0.0183	-0.0325	0.069	0.609
rku	MO58A brass; rough face turning	conf	3	-0.0279	-0.034	-0.0217	0.072
rku	MO58A brass; rough face turning	fusion	3	-0.0319	-0.0736	0.0099	0.375
rku	MO58A brass; rough face turning	int	3	0.0033	-0.0398	0.0464	0.906
rku	MO58A brass; finish wire EDM	FV	3	0.0638	0.0367	0.0908	0.136
rku	MO58A brass; finish wire EDM	conf	3	-0.0973	-0.2625	0.0679	0.454
rku	MO58A brass; finish wire EDM	fusion	3	0.1284	0.0151	0.2418	0.269
rku	MO58A brass; finish wire EDM	int	3	-0.0063	-0.0124	-7.6940e-05	0.297
rku	MO58A brass; rough wire EDM	FV	3	0.0041	-0.0143	0.0225	0.738
rku	MO58A brass; rough wire EDM	conf	3	0.0906	0.0747	0.1066	0.057
rku	MO58A brass; rough wire EDM	fusion	3	0.2042	0.0862	0.3222	0.183
rku	MO58A brass; rough wire EDM	int	3	0.0092	-0.0037	0.022	0.394
rku	Ti6Al4V; burnishing after MF	FV	3	0.1296	0.1286	0.1306	0.003
rku	Ti6Al4V; burnishing after MF	conf	3	0.0365	0.0167	0.0563	0.172
rku	Ti6Al4V; burnishing after MF	fusion	3	-0.0456	-0.1566	0.0654	0.568
rku	Ti6Al4V; burnishing after MF	int	3	-0.248	-1.136	0.64	0.681
rku	Ti6Al4V; glass bead blasting	FV	3	-0.0215	-0.0479	0.0049	0.357
rku	Ti6Al4V; glass bead blasting	conf	3	0.0348	0.0073	0.0623	0.244
rku	Ti6Al4V; glass bead blasting	fusion	3	-0.0112	-0.0843	0.0618	0.814
rku	Ti6Al4V; glass bead blasting	int	3	-0.066	-0.306	0.174	0.685
rku	Ti6Al4V; grinding	FV	3	-0.0477	-0.08	-0.0155	0.211
rku	Ti6Al4V; grinding	conf	3	0.0048	0.002	0.0076	0.182
rku	Ti6Al4V; grinding	fusion	3	0.0086	-0.0038	0.0211	0.404
rku	Ti6Al4V; grinding	int	3	0.0109	0.0083	0.0135	0.076
rku	Ti6Al4V; honing	FV	3	-0.0127	-0.0309	0.0055	0.402
rku	Ti6Al4V; honing	conf	3	-0.0235	-0.0428	-0.0043	0.252
rku	Ti6Al4V; honing	fusion	3	0.0619	0.0019	0.1219	0.292
rku	Ti6Al4V; honing	int	3	-0.002	-0.0572	0.0532	0.955
rku	Ti6Al4V; finish milling	FV	3	0.0579	-0.0621	0.178	0.518
rku	Ti6Al4V; finish milling	conf	3	-0.0454	-0.0508	-0.0401	0.038
rku	Ti6Al4V; finish milling	fusion	3	-0.0415	-0.0572	-0.0257	0.122
rku	Ti6Al4V; finish milling	int	3	-0.0073	-0.1083	0.0936	0.91
rku	Ti6Al4V; rough milling	FV	3	-0.0057	-0.0179	0.0065	0.529
rku	Ti6Al4V; rough milling	conf	3	-0.0012	-0.0111	0.0086	0.848
rku	Ti6Al4V; rough milling	fusion	3	-0.0119	-0.0239	2.2510e-04	0.305
rku	Ti6Al4V; rough milling	int	3	0.0273	-0.0527	0.1074	0.625
rku	Ti6Al4V; finish face turning	FV	3	0.0441	-0.0172	0.1055	0.393
rku	Ti6Al4V; finish face turning	conf	3	0.0196	0.0095	0.0296	0.163
rku	Ti6Al4V; finish face turning	fusion	3	0.0492	0.023	0.0754	0.169
rku	Ti6Al4V; finish face turning	int	3	0.0078	-0.1925	0.2081	0.952
rku	Ti6Al4V; rough face turning	FV	3	0.122	0.0744	0.1696	0.125
rku	Ti6Al4V; rough face turning	conf	3	0.0437	-0.0539	0.1413	0.541
rku	Ti6Al4V; rough face turning	fusion	3	-0.0348	-0.038	-0.0316	0.03
rku	Ti6Al4V; rough face turning	int	3	-5.8231e-04	-0.005	0.0038	0.838

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rku	Ti6Al4V; finish wire EDM	FV	3	-0.0264	-0.0542	0.0013	0.313
rku	Ti6Al4V; finish wire EDM	conf	3	-0.0084	-0.0111	-0.0057	0.105
rku	Ti6Al4V; finish wire EDM	fusion	3	0.0049	-0.051	0.0608	0.892
rku	Ti6Al4V; finish wire EDM	int	3	-0.0575	-0.1001	-0.0149	0.23
rku	Ti6Al4V; rough wire EDM	FV	3	0.0073	0.0027	0.0119	0.197
rku	Ti6Al4V; rough wire EDM	conf	3	0.3748	0.3398	0.4097	0.03
rku	Ti6Al4V; rough wire EDM	fusion	3	0.7331	-0.1006	1.5667	0.335
rku	Ti6Al4V; rough wire EDM	int	3	-0.0169	-0.0377	0.004	0.359
rp	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.2752	-1.7469	1.1964	0.776
rp	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.8072	0.5223	1.0921	0.113
rp	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.6365	0.1145	1.1584	0.252
rp	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.4945	-3.042	4.0309	0.83
rp	AISI 304 / EN 1.4301; glass bead blasting	FV	3	0.0262	-0.0725	0.1249	0.695
rp	AISI 304 / EN 1.4301; glass bead blasting	conf	3	-0.0431	-0.0936	0.0075	0.343
rp	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	-0.1166	-0.3374	0.1041	0.489
rp	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0696	-0.0822	0.2215	0.534
rp	AISI 304 / EN 1.4301; grinding	FV	3	0.1003	-0.3285	0.5291	0.726
rp	AISI 304 / EN 1.4301; grinding	conf	3	0.014	-0.0653	0.0934	0.787
rp	AISI 304 / EN 1.4301; grinding	fusion	3	-0.314	-0.8667	0.2387	0.466
rp	AISI 304 / EN 1.4301; grinding	int	3	-0.0313	-0.0676	0.0051	0.341
rp	AISI 304 / EN 1.4301; honing	FV	3	0.2287	0.1537	0.3036	0.106
rp	AISI 304 / EN 1.4301; honing	conf	3	-0.0226	-0.0389	-0.0064	0.224
rp	AISI 304 / EN 1.4301; honing	fusion	3	-0.1627	-0.4436	0.1182	0.46
rp	AISI 304 / EN 1.4301; honing	int	3	-0.0675	-0.3018	0.1668	0.673
rp	AISI 304 / EN 1.4301; finish milling	FV	3	-0.1973	-0.6354	0.2408	0.54
rp	AISI 304 / EN 1.4301; finish milling	conf	3	0.2425	0.2276	0.2575	0.02
rp	AISI 304 / EN 1.4301; finish milling	fusion	3	0.3203	0.2653	0.3753	0.056
rp	AISI 304 / EN 1.4301; finish milling	int	3	-0.5774	-2.0873	0.9326	0.591
rp	AISI 304 / EN 1.4301; rough milling	FV	3	0.0388	-0.0217	0.0993	0.428
rp	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0552	-0.0597	-0.0506	0.027
rp	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0507	-0.0522	-0.0493	0.009
rp	AISI 304 / EN 1.4301; rough milling	int	3	0.0243	-0.4191	0.4677	0.932
rp	AISI 304 / EN 1.4301; finish face turning	FV	3	0.2101	-0.0715	0.4917	0.382
rp	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0194	-0.0255	-0.0134	0.1
rp	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0272	-0.0363	-0.0181	0.108
rp	AISI 304 / EN 1.4301; finish face turning	int	3	0.0368	-0.1581	0.2318	0.774
rp	AISI 304 / EN 1.4301; rough face turning	FV	3	0.0612	-0.0337	0.156	0.426
rp	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0073	-0.0078	-0.0067	0.025
rp	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.016	-0.0194	-0.0126	0.069
rp	AISI 304 / EN 1.4301; rough face turning	int	3	0.0116	-0.0968	0.1201	0.868

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rp	AISI 304 / EN 1.4301; finish wire EDM	FV	3	0.023	-0.2455	0.2915	0.894
rp	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.3224	0.2078	0.4371	0.114
rp	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	-0.1805	-0.9594	0.5984	0.729
rp	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0476	-0.2904	0.1951	0.766
rp	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0239	-0.0363	-0.0115	0.165
rp	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0251	0.014	0.0363	0.141
rp	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.0417	-0.0173	0.1006	0.398
rp	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0357	—	—	—
rp	Al7075; burnishing after MF	FV	3	-0.4727	-1.7852	0.8397	0.609
rp	Al7075; burnishing after MF	conf	3	0.6039	0.1794	1.0285	0.219
rp	Al7075; burnishing after MF	fusion	3	0.5816	-0.064	1.2272	0.328
rp	Al7075; burnishing after MF	int	3	3.8905	-3.3466	11.1276	0.483
rp	Al7075; glass bead blasting	FV	3	-0.0101	-0.1266	0.1064	0.893
rp	Al7075; glass bead blasting	conf	3	0.0813	0.0565	0.106	0.098
rp	Al7075; glass bead blasting	fusion	3	0.2965	-0.1455	0.7385	0.414
rp	Al7075; glass bead blasting	int	3	0.0071	-0.0304	0.0446	0.775
rp	Al7075; grinding	FV	3	0.0775	-0.523	0.678	0.842
rp	Al7075; grinding	conf	3	0.0993	0.061	0.1377	0.124
rp	Al7075; grinding	fusion	3	-0.0097	-0.1946	0.1752	0.935
rp	Al7075; grinding	int	3	0.0283	-0.2405	0.2971	0.87
rp	Al7075; honing	FV	3	0.2395	0.0534	0.4255	0.24
rp	Al7075; honing	conf	3	-0.0512	-0.0591	-0.0433	0.05
rp	Al7075; honing	fusion	3	-0.0071	-0.0878	0.0735	0.891
rp	Al7075; honing	int	3	0.0158	-0.1293	0.1609	0.866
rp	Al7075; finish milling	FV	3	-0.1557	-0.7331	0.4216	0.69
rp	Al7075; finish milling	conf	3	0.4902	0.449	0.5314	0.027
rp	Al7075; finish milling	fusion	3	0.4367	0.4362	0.4371	3.503e-04
rp	Al7075; finish milling	int	3	0.8243	-0.2037	1.8522	0.361
rp	Al7075; rough milling	FV	3	-0.6854	-1.2857	-0.085	0.268
rp	Al7075; rough milling	conf	3	0.1561	0.1491	0.1632	0.015
rp	Al7075; rough milling	fusion	3	0.16	0.0987	0.2213	0.123
rp	Al7075; rough milling	int	3	0.5573	-0.0535	1.1681	0.325
rp	Al7075; finish face turning	FV	3	0.1038	-0.062	0.2697	0.435
rp	Al7075; finish face turning	conf	3	-0.1092	-0.1392	-0.0791	0.089
rp	Al7075; finish face turning	fusion	3	-0.1188	-0.1718	-0.0657	0.143
rp	Al7075; finish face turning	int	3	-0.0954	-0.6064	0.4156	0.777
rp	Al7075; rough face turning	FV	3	0.0493	-0.0141	0.1128	0.37
rp	Al7075; rough face turning	conf	3	-0.0219	-0.0224	-0.0214	0.007
rp	Al7075; rough face turning	fusion	3	-0.017	-0.0237	-0.0103	0.126
rp	Al7075; rough face turning	int	3	0.0406	-0.0588	0.1401	0.57
rp	Al7075; finish wire EDM	FV	3	-0.048	-0.3502	0.2542	0.808
rp	Al7075; finish wire EDM	conf	3	-0.0691	-0.5821	0.4439	0.836
rp	Al7075; finish wire EDM	fusion	3	-0.4835	-1.5104	0.5433	0.526
rp	Al7075; finish wire EDM	int	3	-0.0676	-0.2637	0.1284	0.621
rp	Al7075; rough wire EDM	FV	3	-0.0375	-0.0604	-0.0146	0.192
rp	Al7075; rough wire EDM	conf	3	-0.0083	-0.09	0.0733	0.874
rp	Al7075; rough wire EDM	fusion	3	0.1271	-0.1667	0.4208	0.552
rp	Al7075; rough wire EDM	int	3	-0.042	-0.1075	0.0235	0.428
rp	C45 steel; burnishing after MF	FV	3	-0.0167	-1.0236	0.9901	0.979
rp	C45 steel; burnishing after MF	conf	2	0.6686	—	—	—
rp	C45 steel; burnishing after MF	fusion	3	0.3661	-0.041	0.7733	0.329
rp	C45 steel; burnishing after MF	int	4	-3.4096	-6.9159	0.0967	0.197
rp	C45 steel; glass bead blasting	FV	3	0.0172	-0.1163	0.1506	0.843
rp	C45 steel; glass bead blasting	conf	3	0.0389	0.0079	0.0698	0.246
rp	C45 steel; glass bead blasting	fusion	3	0.0421	-0.0482	0.1323	0.529
rp	C45 steel; glass bead blasting	int	3	0.0089	-0.0233	0.0412	0.684

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rp	C45 steel; grinding	FV	3	0.3336	-0.5899	1.2572	0.608
rp	C45 steel; grinding	conf	3	0.1148	0.0596	0.1699	0.153
rp	C45 steel; grinding	fusion	3	-0.0364	-0.3257	0.2529	0.846
rp	C45 steel; grinding	int	3	-0.0295	-0.1276	0.0687	0.661
rp	C45 steel; honing	FV	3	0.2435	0.135	0.3521	0.142
rp	C45 steel; honing	conf	3	-0.045	-0.0471	-0.0428	0.016
rp	C45 steel; honing	fusion	3	-0.0333	-0.1656	0.0989	0.708
rp	C45 steel; honing	int	3	-0.0881	-0.3138	0.1376	0.584
rp	C45 steel; finish milling	FV	3	0.1996	-0.1092	0.5084	0.425
rp	C45 steel; finish milling	conf	2	0.1219	—	—	—
rp	C45 steel; finish milling	fusion	3	0.0171	-0.14	0.1742	0.866
rp	C45 steel; finish milling	int	3	0.2157	0.1027	0.3287	0.166
rp	C45 steel; rough milling	FV	3	0.0054	-0.0429	0.0536	0.864
rp	C45 steel; rough milling	conf	2	-0.0318	—	—	—
rp	C45 steel; rough milling	fusion	3	0.0014	-0.0481	0.0509	0.965
rp	C45 steel; rough milling	int	3	0.0478	-0.0195	0.1151	0.396
rp	C45 steel; finish face turning	FV	3	-0.0024	-0.0471	0.0422	0.932
rp	C45 steel; finish face turning	conf	2	-0.0221	—	—	—
rp	C45 steel; finish face turning	fusion	3	-0.0095	-0.0321	0.0131	0.561
rp	C45 steel; finish face turning	int	3	0.0305	-0.0139	0.075	0.406
rp	C45 steel; rough face turning	FV	3	0.0258	-0.0234	0.075	0.492
rp	C45 steel; rough face turning	conf	2	-0.0139	—	—	—
rp	C45 steel; rough face turning	fusion	3	-0.0157	-0.0171	-0.0142	0.03
rp	C45 steel; rough face turning	int	3	0.0184	-0.0689	0.1056	0.751
rp	C45 steel; finish wire EDM	FV	3	0.0594	-0.1167	0.2354	0.628
rp	C45 steel; finish wire EDM	conf	3	0.5365	0.209	0.8639	0.192
rp	C45 steel; finish wire EDM	fusion	3	-0.2993	-0.9972	0.3986	0.555
rp	C45 steel; finish wire EDM	int	3	-0.0432	-0.1997	0.1133	0.684
rp	C45 steel; rough wire EDM	FV	3	-0.021	-0.0498	0.0078	0.388
rp	C45 steel; rough wire EDM	conf	3	0.0174	0.0085	0.0262	0.162
rp	C45 steel; rough wire EDM	fusion	3	0.0034	-0.1386	0.1454	0.97
rp	C45 steel; rough wire EDM	int	3	-0.0866	-0.1802	0.007	0.321
rp	ELLOR graphite; glass bead blasting	FV	3	-0.0234	-0.0552	0.0084	0.386
rp	ELLOR graphite; glass bead blasting	conf	3	0.0326	0.0241	0.041	0.084
rp	ELLOR graphite; glass bead blasting	fusion	3	0.0228	-0.0248	0.0704	0.52
rp	ELLOR graphite; glass bead blasting	int	3	0.0703	-0.0384	0.1791	0.425
rp	ELLOR graphite; grinding	FV	3	0.0109	-0.1563	0.178	0.919
rp	ELLOR graphite; grinding	conf	3	0.1555	0.0977	0.2133	0.119
rp	ELLOR graphite; grinding	fusion	3	0.1733	0.1221	0.2246	0.095
rp	ELLOR graphite; grinding	int	3	-0.8788	-2.5228	0.7653	0.485
rp	ELLOR graphite; honing	FV	3	-0.1388	-1.006	0.7284	0.806
rp	ELLOR graphite; honing	conf	3	0.1279	-0.3072	0.5629	0.667
rp	ELLOR graphite; honing	fusion	3	-0.1628	-1.2088	0.8831	0.811
rp	ELLOR graphite; honing	int	3	-0.3982	-0.9037	0.1073	0.366
rp	ELLOR graphite; finish milling	FV	3	0.1115	-0.1537	0.3768	0.561
rp	ELLOR graphite; finish milling	conf	3	-0.0771	-0.349	0.1948	0.677
rp	ELLOR graphite; finish milling	fusion	3	-0.0933	-0.5015	0.3149	0.732
rp	ELLOR graphite; finish milling	int	3	-0.0866	-0.132	-0.0413	0.166
rp	ELLOR graphite; rough milling	FV	3	0.0247	-0.0971	0.1465	0.759
rp	ELLOR graphite; rough milling	conf	3	0.1533	0.129	0.1776	0.051
rp	ELLOR graphite; rough milling	fusion	3	0.0981	0.0247	0.1714	0.232
rp	ELLOR graphite; rough milling	int	3	-0.1019	-0.2607	0.0568	0.427
rp	ELLOR graphite; finish face turning	FV	3	-0.0108	-0.0948	0.0732	0.842
rp	ELLOR graphite; finish face turning	conf	3	0.0591	-0.0023	0.1206	0.31
rp	ELLOR graphite; finish face turning	fusion	3	0.0516	-0.0654	0.1685	0.546
rp	ELLOR graphite; finish face turning	int	3	-0.0662	-0.1941	0.0616	0.495

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rp	ELLOR graphite; rough face turning	FV	3	0.0139	-0.0168	0.0446	0.538
rp	ELLOR graphite; rough face turning	conf	3	-0.0288	-0.0376	-0.0201	0.098
rp	ELLOR graphite; rough face turning	fusion	3	-0.0257	-0.0597	0.0083	0.378
rp	ELLOR graphite; rough face turning	int	3	-0.1501	-0.3809	0.0807	0.423
rp	ELLOR graphite; finish wire EDM	FV	3	-0.0225	-0.1419	0.097	0.775
rp	ELLOR graphite; finish wire EDM	conf	3	0.103	0.0947	0.1113	0.026
rp	ELLOR graphite; finish wire EDM	fusion	3	0.095	-0.0135	0.2034	0.336
rp	ELLOR graphite; finish wire EDM	int	2	0.0817	—	—	—
rp	ELLOR graphite; rough wire EDM	FV	3	-0.039	-0.1276	0.0496	0.547
rp	ELLOR graphite; rough wire EDM	conf	3	0.0752	0.0619	0.0886	0.058
rp	ELLOR graphite; rough wire EDM	fusion	3	0.0687	-0.0202	0.1575	0.371
rp	ELLOR graphite; rough wire EDM	int	3	-1.3343	-3.418	0.7494	0.428
rp	MO58A brass; burnishing after MF	FV	4	-0.481	-3.17	2.2079	0.759
rp	MO58A brass; burnishing after MF	conf	3	0.1997	-0.6644	1.0638	0.729
rp	MO58A brass; burnishing after MF	fusion	3	-0.0662	-1.3531	1.2206	0.936
rp	MO58A brass; burnishing after MF	int	3	5.852	-1.9554	13.6595	0.38
rp	MO58A brass; glass bead blasting	FV	3	0.1087	-0.055	0.2724	0.417
rp	MO58A brass; glass bead blasting	conf	3	0.1213	0.0853	0.1573	0.096
rp	MO58A brass; glass bead blasting	fusion	3	0.3812	0.3301	0.4322	0.043
rp	MO58A brass; glass bead blasting	int	3	0.0317	-0.066	0.1295	0.639
rp	MO58A brass; grinding	FV	3	0.3141	-0.1087	0.737	0.383
rp	MO58A brass; grinding	conf	3	0.0532	0.0292	0.0771	0.144
rp	MO58A brass; grinding	fusion	3	-0.2134	-0.5661	0.1394	0.446
rp	MO58A brass; grinding	int	3	-0.0138	-0.015	-0.0126	0.028
rp	MO58A brass; honing	FV	3	0.3165	0.2142	0.4187	0.104
rp	MO58A brass; honing	conf	3	-0.0353	-0.0617	-0.0089	0.232
rp	MO58A brass; honing	fusion	3	-0.0836	-0.2342	0.0671	0.473
rp	MO58A brass; honing	int	3	-0.0645	-0.2671	0.1381	0.645
rp	MO58A brass; finish milling	FV	3	-0.0244	-1.3988	1.3499	0.978
rp	MO58A brass; finish milling	conf	3	0.8103	0.5082	1.1124	0.12
rp	MO58A brass; finish milling	fusion	3	0.7795	0.13	1.429	0.256
rp	MO58A brass; finish milling	int	3	1.7639	-1.794	5.3219	0.509
rp	MO58A brass; rough milling	FV	3	0.2073	-0.0669	0.4816	0.378
rp	MO58A brass; rough milling	conf	3	0.0279	-0.024	0.0799	0.484
rp	MO58A brass; rough milling	fusion	3	0.0929	-0.0377	0.2235	0.396
rp	MO58A brass; rough milling	int	3	0.0691	-0.1326	0.2709	0.623
rp	MO58A brass; finish face turning	FV	3	0.0183	-0.0561	0.0928	0.714
rp	MO58A brass; finish face turning	conf	3	-8.0083e-04	-0.022	0.0204	0.953
rp	MO58A brass; finish face turning	fusion	3	0.0254	-0.0376	0.0885	0.574
rp	MO58A brass; finish face turning	int	3	0.0345	-0.0255	0.0945	0.462
rp	MO58A brass; rough face turning	FV	3	0.027	-0.0854	0.1395	0.72
rp	MO58A brass; rough face turning	conf	3	-0.0139	-0.0287	8.7542e-04	0.316
rp	MO58A brass; rough face turning	fusion	3	-0.0044	-0.0203	0.0114	0.682
rp	MO58A brass; rough face turning	int	3	0.016	-0.0718	0.1038	0.781
rp	MO58A brass; finish wire EDM	FV	3	0.0767	-0.2051	0.3584	0.688
rp	MO58A brass; finish wire EDM	conf	3	0.1004	-0.0581	0.2589	0.432
rp	MO58A brass; finish wire EDM	fusion	3	0.2858	0.0986	0.4731	0.205
rp	MO58A brass; finish wire EDM	int	3	0.0217	-0.0121	0.0555	0.427
rp	MO58A brass; rough wire EDM	FV	3	-0.0192	-0.02	-0.0184	0.013
rp	MO58A brass; rough wire EDM	conf	3	-0.0926	-0.1715	-0.0136	0.261
rp	MO58A brass; rough wire EDM	fusion	3	-0.0952	-0.1497	-0.0406	0.181
rp	MO58A brass; rough wire EDM	int	3	-0.0952	-0.2711	0.0806	0.481
rp	Ti6Al4V; burnishing after MF	FV	3	-0.307	-0.9211	0.3071	0.506
rp	Ti6Al4V; burnishing after MF	conf	3	0.7814	0.7291	0.8337	0.022
rp	Ti6Al4V; burnishing after MF	fusion	3	0.7175	0.6577	0.7772	0.027
rp	Ti6Al4V; burnishing after MF	int	3	-0.2511	-2.2427	1.7406	0.846

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
rp	Ti6Al4V; glass bead blasting	FV	3	0.1256	0.1151	0.1361	0.027
rp	Ti6Al4V; glass bead blasting	conf	3	-0.0258	-0.1035	0.052	0.633
rp	Ti6Al4V; glass bead blasting	fusion	3	0.0146	-0.1275	0.1567	0.873
rp	Ti6Al4V; glass bead blasting	int	3	0.0563	-0.0539	0.1666	0.5
rp	Ti6Al4V; grinding	FV	3	-0.1152	-0.63	0.3996	0.737
rp	Ti6Al4V; grinding	conf	3	0.1945	0.1662	0.2229	0.047
rp	Ti6Al4V; grinding	fusion	3	0.0204	-0.2623	0.303	0.911
rp	Ti6Al4V; grinding	int	3	-0.0117	-0.3818	0.3584	0.961
rp	Ti6Al4V; honing	FV	3	0.3797	0.0561	0.7032	0.261
rp	Ti6Al4V; honing	conf	3	0.0785	0.0445	0.1124	0.138
rp	Ti6Al4V; honing	fusion	3	-0.078	-0.3734	0.2174	0.696
rp	Ti6Al4V; honing	int	3	0.0196	-0.0542	0.0934	0.694
rp	Ti6Al4V; finish milling	FV	3	-0.1205	-0.3998	0.1587	0.553
rp	Ti6Al4V; finish milling	conf	3	0.0545	0.0178	0.0912	0.211
rp	Ti6Al4V; finish milling	fusion	3	0.003	-0.0633	0.0694	0.944
rp	Ti6Al4V; finish milling	int	3	8.3168e-04	-0.1829	0.1845	0.994
rp	Ti6Al4V; rough milling	FV	3	0.0733	-0.1078	0.2544	0.573
rp	Ti6Al4V; rough milling	conf	3	-0.0888	-0.1103	-0.0673	0.078
rp	Ti6Al4V; rough milling	fusion	3	0.0303	-0.0351	0.0958	0.531
rp	Ti6Al4V; rough milling	int	3	0.0937	-0.5123	0.6996	0.813
rp	Ti6Al4V; finish face turning	FV	3	0.0161	-0.1165	0.1486	0.851
rp	Ti6Al4V; finish face turning	conf	3	-0.1005	-0.1152	-0.0858	0.048
rp	Ti6Al4V; finish face turning	fusion	3	0.0238	-0.0597	0.1072	0.676
rp	Ti6Al4V; finish face turning	int	3	0.0604	-0.2378	0.3586	0.759
rp	Ti6Al4V; rough face turning	FV	3	-0.0423	-0.0535	-0.031	0.086
rp	Ti6Al4V; rough face turning	conf	3	-0.0391	-0.0464	-0.0318	0.06
rp	Ti6Al4V; rough face turning	fusion	3	-0.0169	-0.0316	-0.0022	0.265
rp	Ti6Al4V; rough face turning	int	3	0.0522	-0.0324	0.1369	0.44
rp	Ti6Al4V; finish wire EDM	FV	3	0.215	-0.0722	0.5022	0.381
rp	Ti6Al4V; finish wire EDM	conf	3	0.2608	0.2203	0.3013	0.05
rp	Ti6Al4V; finish wire EDM	fusion	3	0.2683	-0.0072	0.5438	0.307
rp	Ti6Al4V; finish wire EDM	int	3	0.1308	-0.0936	0.3551	0.458
rp	Ti6Al4V; rough wire EDM	FV	3	-0.0011	-0.003	8.1815e-04	0.463
rp	Ti6Al4V; rough wire EDM	conf	3	0.0073	-0.0186	0.0333	0.678
rp	Ti6Al4V; rough wire EDM	fusion	3	0.1973	-0.0904	0.485	0.407
rp	Ti6Al4V; rough wire EDM	int	3	-0.0668	-0.1399	0.0062	0.324
R_q	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.7655	-2.2412	0.7102	0.495
R_q	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.2841	0.0902	0.4779	0.213
R_q	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.3372	0.0617	0.6126	0.251
R_q	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.5153	-0.9436	1.9742	0.615
R_q	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0417	-0.1828	0.0993	0.666
R_q	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.1803	0.1367	0.2238	0.078
R_q	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.1373	0.0901	0.1844	0.11
R_q	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0138	-0.1025	0.1301	0.855
R_q	AISI 304 / EN 1.4301; grinding	FV	3	0.0027	-0.3004	0.3057	0.989
R_q	AISI 304 / EN 1.4301; grinding	conf	3	0.0764	0.0705	0.0823	0.025
R_q	AISI 304 / EN 1.4301; grinding	fusion	3	0.0678	0.0202	0.1155	0.219
R_q	AISI 304 / EN 1.4301; grinding	int	3	-0.012	-0.065	0.041	0.734
R_q	AISI 304 / EN 1.4301; honing	FV	3	0.3632	0.2136	0.5129	0.132
R_q	AISI 304 / EN 1.4301; honing	conf	3	0.1859	0.1056	0.2662	0.138
R_q	AISI 304 / EN 1.4301; honing	fusion	3	0.0942	0.0287	0.1598	0.217
R_q	AISI 304 / EN 1.4301; honing	int	3	-0.0198	-0.0392	-3.5534e-04	0.296
R_q	AISI 304 / EN 1.4301; finish milling	FV	3	-0.2834	-0.8367	0.2699	0.499
R_q	AISI 304 / EN 1.4301; finish milling	conf	3	0.2485	0.2304	0.2666	0.024

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_q	AISI 304 / EN 1.4301; finish milling	fusion	3	0.3678	0.2666	0.469	0.089
R_q	AISI 304 / EN 1.4301; finish milling	int	3	-0.4093	-1.5378	0.7191	0.607
R_q	AISI 304 / EN 1.4301; rough milling	FV	3	0.0424	-0.0174	0.1022	0.397
R_q	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0454	-0.0563	-0.0345	0.078
R_q	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0474	-0.0606	-0.0342	0.09
R_q	AISI 304 / EN 1.4301; rough milling	int	3	-0.0113	-0.2887	0.2661	0.949
R_q	AISI 304 / EN 1.4301; finish face turning	FV	3	0.1193	-0.0021	0.2407	0.305
R_q	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.028	-0.039	-0.017	0.126
R_q	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0418	-0.0622	-0.0214	0.155
R_q	AISI 304 / EN 1.4301; finish face turning	int	3	0.0254	-0.092	0.1428	0.745
R_q	AISI 304 / EN 1.4301; rough face turning	FV	3	0.0884	-0.0306	0.2073	0.383
R_q	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0221	-0.0347	-0.0096	0.179
R_q	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.0341	-0.0507	-0.0176	0.154
R_q	AISI 304 / EN 1.4301; rough face turning	int	3	0.0192	-0.0689	0.1073	0.743
R_q	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-0.0301	-0.3611	0.3009	0.888
R_q	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.181	0.1429	0.2191	0.068
R_q	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.1778	0.0688	0.2868	0.193
R_q	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0198	-0.1353	0.0957	0.794
R_q	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0236	-0.0585	0.0113	0.412
R_q	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0196	0.0116	0.0275	0.131
R_q	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.0145	-0.0211	0.05	0.572
R_q	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0325	—	—	—
R_q	Al7075; burnishing after MF	FV	3	-0.9988	-2.5549	0.5573	0.428
R_q	Al7075; burnishing after MF	conf	3	0.176	-0.0112	0.3632	0.316
R_q	Al7075; burnishing after MF	fusion	3	0.1949	-0.0499	0.4396	0.363
R_q	Al7075; burnishing after MF	int	3	3.1628	-2.3437	8.6693	0.462
R_q	Al7075; glass bead blasting	FV	3	-0.0657	-0.1522	0.0209	0.377
R_q	Al7075; glass bead blasting	conf	3	0.2332	0.1434	0.3231	0.124
R_q	Al7075; glass bead blasting	fusion	3	0.2143	0.14	0.2885	0.111
R_q	Al7075; glass bead blasting	int	3	-0.0039	-0.0399	0.0322	0.867
R_q	Al7075; grinding	FV	3	-0.0688	-0.4796	0.342	0.798
R_q	Al7075; grinding	conf	3	0.1562	0.1327	0.1798	0.049
R_q	Al7075; grinding	fusion	3	0.1695	0.1285	0.2104	0.078
R_q	Al7075; grinding	int	3	-0.0249	-0.1473	0.0975	0.759
R_q	Al7075; honing	FV	3	-0.049	-0.2749	0.1769	0.744
R_q	Al7075; honing	conf	3	-0.1011	-0.1392	-0.0631	0.121
R_q	Al7075; honing	fusion	3	-0.1109	-0.1607	-0.0611	0.143
R_q	Al7075; honing	int	3	-0.0022	-0.0589	0.0545	0.952
R_q	Al7075; finish milling	FV	3	-0.4666	-1.2465	0.3134	0.45
R_q	Al7075; finish milling	conf	3	0.2522	0.2265	0.278	0.033
R_q	Al7075; finish milling	fusion	3	0.2508	0.2219	0.2797	0.037
R_q	Al7075; finish milling	int	3	0.8491	0.0909	1.6073	0.272

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_q	Al7075; rough milling	FV	3	-0.9547	-1.7468	-0.1626	0.255
R_q	Al7075; rough milling	conf	3	0.2151	0.1561	0.2742	0.089
R_q	Al7075; rough milling	fusion	3	0.2623	0.1097	0.415	0.184
R_q	Al7075; rough milling	int	3	0.7272	-0.0831	1.5374	0.329
R_q	Al7075; finish face turning	FV	3	0.1359	-0.043	0.3149	0.377
R_q	Al7075; finish face turning	conf	3	-0.1084	-0.1432	-0.0736	0.103
R_q	Al7075; finish face turning	fusion	3	-0.1361	-0.1983	-0.0738	0.146
R_q	Al7075; finish face turning	int	3	-0.0902	-0.4128	0.2323	0.681
R_q	Al7075; rough face turning	FV	3	0.033	-0.0129	0.0789	0.393
R_q	Al7075; rough face turning	conf	3	-0.0126	-0.0162	-0.009	0.091
R_q	Al7075; rough face turning	fusion	3	-0.0157	-0.0171	-0.0142	0.031
R_q	Al7075; rough face turning	int	3	0.0207	-0.0261	0.0675	0.545
R_q	Al7075; finish wire EDM	FV	3	-0.0781	-0.4129	0.2566	0.727
R_q	Al7075; finish wire EDM	conf	3	0.145	-0.0383	0.3283	0.365
R_q	Al7075; finish wire EDM	fusion	3	0.1643	-0.1483	0.4769	0.491
R_q	Al7075; finish wire EDM	int	3	-0.1565	-0.3716	0.0585	0.389
R_q	Al7075; rough wire EDM	FV	3	-0.0526	-0.0775	-0.0277	0.151
R_q	Al7075; rough wire EDM	conf	3	0.0911	0.0588	0.1233	0.114
R_q	Al7075; rough wire EDM	fusion	3	0.2056	0.1337	0.2776	0.113
R_q	Al7075; rough wire EDM	int	3	-0.007	-0.0259	0.0119	0.601
R_q	C45 steel; burnishing after MF	FV	3	-0.5849	-2.0235	0.8537	0.572
R_q	C45 steel; burnishing after MF	conf	2	0.5202	—	—	—
R_q	C45 steel; burnishing after MF	fusion	3	0.5483	0.3972	0.6994	0.089
R_q	C45 steel; burnishing after MF	int	4	-2.7689	-5.5355	-0.0023	0.189
R_q	C45 steel; glass bead blasting	FV	3	-0.0082	-0.1749	0.1586	0.939
R_q	C45 steel; glass bead blasting	conf	3	0.2293	0.1453	0.3132	0.118
R_q	C45 steel; glass bead blasting	fusion	3	0.239	0.1888	0.2892	0.068
R_q	C45 steel; glass bead blasting	int	3	-0.0133	-0.0155	-0.0111	0.054
R_q	C45 steel; grinding	FV	3	-0.0126	-0.5608	0.5357	0.971
R_q	C45 steel; grinding	conf	3	0.1926	0.1329	0.2524	0.1
R_q	C45 steel; grinding	fusion	3	0.2071	0.1358	0.2785	0.111
R_q	C45 steel; grinding	int	3	0.0242	-0.0877	0.136	0.745
R_q	C45 steel; honing	FV	3	0.3304	0.1732	0.4875	0.152
R_q	C45 steel; honing	conf	3	0.1088	0.1084	0.1092	0.001
R_q	C45 steel; honing	fusion	3	0.1157	0.1099	0.1214	0.016
R_q	C45 steel; honing	int	3	-0.017	-0.1225	0.0885	0.805
R_q	C45 steel; finish milling	FV	3	-0.0103	-0.1367	0.1162	0.899
R_q	C45 steel; finish milling	conf	2	-0.0988	—	—	—
R_q	C45 steel; finish milling	fusion	3	0.0051	-0.1455	0.1558	0.957
R_q	C45 steel; finish milling	int	3	-0.0475	-0.0725	-0.0226	0.166
R_q	C45 steel; rough milling	FV	3	0.011	-0.0324	0.0544	0.707
R_q	C45 steel; rough milling	conf	2	-0.0374	—	—	—
R_q	C45 steel; rough milling	fusion	3	-0.0475	-0.0514	-0.0436	0.027
R_q	C45 steel; rough milling	int	3	0.0364	-0.0196	0.0924	0.423
R_q	C45 steel; finish face turning	FV	3	-0.002	-0.0304	0.0264	0.912
R_q	C45 steel; finish face turning	conf	2	-0.0254	—	—	—
R_q	C45 steel; finish face turning	fusion	3	-0.038	-0.0487	-0.0273	0.091
R_q	C45 steel; finish face turning	int	3	0.0206	-0.0082	0.0493	0.395
R_q	C45 steel; rough face turning	FV	3	0.0236	-0.0121	0.0592	0.418
R_q	C45 steel; rough face turning	conf	2	-0.0111	—	—	—
R_q	C45 steel; rough face turning	fusion	3	-0.0179	-0.0277	-0.008	0.175
R_q	C45 steel; rough face turning	int	3	0.0048	-0.0362	0.0458	0.856
R_q	C45 steel; finish wire EDM	FV	3	0.1177	-0.1101	0.3456	0.496
R_q	C45 steel; finish wire EDM	conf	3	0.225	0.0664	0.3837	0.22
R_q	C45 steel; finish wire EDM	fusion	3	0.1273	0.092	0.1626	0.09
R_q	C45 steel; finish wire EDM	int	3	-0.0456	-0.113	0.0217	0.411
R_q	C45 steel; rough wire EDM	FV	3	0.0054	-0.0147	0.0254	0.693
R_q	C45 steel; rough wire EDM	conf	3	0.0416	0.031	0.0522	0.082
R_q	C45 steel; rough wire EDM	fusion	3	0.1137	0.0898	0.1375	0.068
R_q	C45 steel; rough wire EDM	int	3	-0.145	-0.3261	0.0361	0.361
R_q	ELLOR graphite; glass bead blasting	FV	3	-0.0073	-0.0139	-6.9641e-04	0.275
R_q	ELLOR graphite; glass bead blasting	conf	3	0.011	-0.0052	0.0273	0.411

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_q	ELLOR graphite; glass bead blasting	fusion	3	0.01	-0.0011	0.0211	0.327
R_q	ELLOR graphite; glass bead blasting	int	3	-0.0172	-0.0336	-8.9709e-04	0.287
R_q	ELLOR graphite; grinding	FV	3	-0.0592	-0.1334	0.0151	0.363
R_q	ELLOR graphite; grinding	conf	3	0.0721	0.0416	0.1027	0.135
R_q	ELLOR graphite; grinding	fusion	3	0.1049	0.018	0.1918	0.255
R_q	ELLOR graphite; grinding	int	3	0.8123	0.3114	1.3132	0.194
R_q	ELLOR graphite; honing	FV	3	-0.3669	-1.1872	0.4534	0.542
R_q	ELLOR graphite; honing	conf	3	0.4309	0.3399	0.5219	0.068
R_q	ELLOR graphite; honing	fusion	3	0.4659	0.2392	0.6926	0.155
R_q	ELLOR graphite; honing	int	3	-0.1908	-0.2263	-0.1553	0.06
R_q	ELLOR graphite; finish milling	FV	3	0.0624	-0.0627	0.1875	0.507
R_q	ELLOR graphite; finish milling	conf	3	-0.0116	-0.1087	0.0855	0.853
R_q	ELLOR graphite; finish milling	fusion	3	0.1045	-0.0604	0.2693	0.432
R_q	ELLOR graphite; finish milling	int	3	-0.3009	-0.7477	0.1458	0.413
R_q	ELLOR graphite; rough milling	FV	3	0.0363	-0.0205	0.0931	0.429
R_q	ELLOR graphite; rough milling	conf	3	0.0581	0.0415	0.0748	0.093
R_q	ELLOR graphite; rough milling	fusion	3	0.0784	0.0671	0.0898	0.047
R_q	ELLOR graphite; rough milling	int	3	-0.3237	-0.7697	0.1223	0.39
R_q	ELLOR graphite; finish face turning	FV	3	0.013	-0.0457	0.0717	0.74
R_q	ELLOR graphite; finish face turning	conf	3	0.0657	0.0604	0.071	0.026
R_q	ELLOR graphite; finish face turning	fusion	3	0.0988	0.0678	0.1297	0.101
R_q	ELLOR graphite; finish face turning	int	3	-0.175	-0.4604	0.1104	0.442
R_q	ELLOR graphite; rough face turning	FV	3	0.01	3.3634e-04	0.0197	0.292
R_q	ELLOR graphite; rough face turning	conf	3	-0.0067	-0.007	-0.0063	0.017
R_q	ELLOR graphite; rough face turning	fusion	3	-0.0111	-0.0182	-0.0039	0.203
R_q	ELLOR graphite; rough face turning	int	3	-0.2364	-0.5872	0.1144	0.413
R_q	ELLOR graphite; finish wire EDM	FV	3	-0.0351	-0.109	0.0388	0.523
R_q	ELLOR graphite; finish wire EDM	conf	3	0.0519	0.0353	0.0686	0.103
R_q	ELLOR graphite; finish wire EDM	fusion	3	0.0605	0.0428	0.0783	0.094
R_q	ELLOR graphite; finish wire EDM	int	2	0.0938	—	—	—
R_q	ELLOR graphite; rough wire EDM	FV	3	0.0132	-0.0187	0.0451	0.565
R_q	ELLOR graphite; rough wire EDM	conf	3	0.0521	0.0198	0.0844	0.195
R_q	ELLOR graphite; rough wire EDM	fusion	3	0.0628	0.0478	0.0778	0.077
R_q	ELLOR graphite; rough wire EDM	int	3	-0.2091	-0.613	0.1949	0.495
R_q	MO58A brass; burnishing after MF	FV	4	-1.0805	-3.3215	1.1604	0.444
R_q	MO58A brass; burnishing after MF	conf	3	0.0261	-0.2906	0.3429	0.898
R_q	MO58A brass; burnishing after MF	fusion	3	0.0324	-0.3835	0.4483	0.904
R_q	MO58A brass; burnishing after MF	int	3	4.1057	-1.1011	9.3126	0.366
R_q	MO58A brass; glass bead blasting	FV	3	0.1102	0.0094	0.211	0.278
R_q	MO58A brass; glass bead blasting	conf	3	0.3286	0.1407	0.5165	0.181
R_q	MO58A brass; glass bead blasting	fusion	3	0.3324	0.2486	0.4162	0.081
R_q	MO58A brass; glass bead blasting	int	3	0.0452	-0.0429	0.1334	0.498
R_q	MO58A brass; grinding	FV	3	0.1754	-0.0664	0.4172	0.39
R_q	MO58A brass; grinding	conf	3	0.1152	0.0572	0.1732	0.16
R_q	MO58A brass; grinding	fusion	3	-0.08	-0.3229	0.1629	0.635
R_q	MO58A brass; grinding	int	3	-9.4296e-04	-0.0695	0.0676	0.983
R_q	MO58A brass; honing	FV	3	0.2818	0.0891	0.4745	0.214
R_q	MO58A brass; honing	conf	3	0.1499	0.0853	0.2144	0.138
R_q	MO58A brass; honing	fusion	3	0.0778	0.024	0.1316	0.216
R_q	MO58A brass; honing	int	3	-0.0054	-0.055	0.0442	0.866

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_q	MO58A brass; finish milling	FV	3	-1.0115	-2.701	0.678	0.449
R_q	MO58A brass; finish milling	conf	3	0.3479	0.3063	0.3895	0.039
R_q	MO58A brass; finish milling	fusion	3	0.4568	0.3047	0.6088	0.107
R_q	MO58A brass; finish milling	int	3	1.4543	-0.3746	3.2833	0.363
R_q	MO58A brass; rough milling	FV	3	0.2107	-0.0628	0.4841	0.372
R_q	MO58A brass; rough milling	conf	3	-0.0329	-0.0414	-0.0244	0.083
R_q	MO58A brass; rough milling	fusion	3	-0.0288	-0.0527	-0.005	0.254
R_q	MO58A brass; rough milling	int	3	0.0388	-0.0674	0.145	0.604
R_q	MO58A brass; finish face turning	FV	3	0.0215	-0.0362	0.0793	0.599
R_q	MO58A brass; finish face turning	conf	3	-0.0242	-0.0281	-0.0203	0.052
R_q	MO58A brass; finish face turning	fusion	3	-0.0125	-0.0415	0.0164	0.552
R_q	MO58A brass; finish face turning	int	3	0.0166	-0.0067	0.0399	0.395
R_q	MO58A brass; rough face turning	FV	3	0.0225	-0.0451	0.0901	0.632
R_q	MO58A brass; rough face turning	conf	3	-0.0321	-0.0361	-0.028	0.041
R_q	MO58A brass; rough face turning	fusion	3	-0.0174	-0.0464	0.0116	0.448
R_q	MO58A brass; rough face turning	int	3	0.0048	-0.0138	0.0234	0.703
R_q	MO58A brass; finish wire EDM	FV	3	0.004	-0.2719	0.2799	0.982
R_q	MO58A brass; finish wire EDM	conf	3	0.2252	0.1543	0.2961	0.101
R_q	MO58A brass; finish wire EDM	fusion	3	0.0856	-0.1144	0.2856	0.556
R_q	MO58A brass; finish wire EDM	int	3	-0.0021	-0.004	-1.4214e-04	0.282
R_q	MO58A brass; rough wire EDM	FV	3	-0.0394	-0.0442	-0.0346	0.039
R_q	MO58A brass; rough wire EDM	conf	3	-0.1158	-0.208	-0.0236	0.246
R_q	MO58A brass; rough wire EDM	fusion	3	-0.0922	-0.1216	-0.0627	0.103
R_q	MO58A brass; rough wire EDM	int	3	-0.067	-0.1822	0.0481	0.458
R_q	Ti6Al4V; burnishing after MF	FV	3	-0.5153	-1.0798	0.0492	0.324
R_q	Ti6Al4V; burnishing after MF	conf	3	0.4424	0.3644	0.5203	0.057
R_q	Ti6Al4V; burnishing after MF	fusion	3	0.4457	0.3809	0.5105	0.047
R_q	Ti6Al4V; burnishing after MF	int	3	0.0499	-0.2383	0.3381	0.792
R_q	Ti6Al4V; glass bead blasting	FV	3	0.1168	-0.1233	0.3568	0.515
R_q	Ti6Al4V; glass bead blasting	conf	3	0.2604	0.2207	0.3002	0.049
R_q	Ti6Al4V; glass bead blasting	fusion	3	0.2698	0.2183	0.3213	0.062
R_q	Ti6Al4V; glass bead blasting	int	3	-1.9244e-04	-0.1146	0.1142	0.998
R_q	Ti6Al4V; grinding	FV	3	-0.1788	-0.5231	0.1655	0.494
R_q	Ti6Al4V; grinding	conf	3	0.1979	0.1474	0.2485	0.082
R_q	Ti6Al4V; grinding	fusion	3	0.2349	0.1861	0.2837	0.067
R_q	Ti6Al4V; grinding	int	3	-0.0059	-0.0522	0.0404	0.844
R_q	Ti6Al4V; honing	FV	3	0.3522	-0.1348	0.8391	0.391
R_q	Ti6Al4V; honing	conf	3	0.2938	0.1529	0.4347	0.153
R_q	Ti6Al4V; honing	fusion	3	0.3483	0.1656	0.5309	0.166
R_q	Ti6Al4V; honing	int	3	-0.0171	-0.0236	-0.0106	0.122
R_q	Ti6Al4V; finish milling	FV	3	-0.1725	-0.4487	0.1038	0.436
R_q	Ti6Al4V; finish milling	conf	3	0.1586	0.1126	0.2046	0.094
R_q	Ti6Al4V; finish milling	fusion	3	0.1639	0.1198	0.2081	0.087
R_q	Ti6Al4V; finish milling	int	3	0.0309	-0.0321	0.094	0.512
R_q	Ti6Al4V; rough milling	FV	3	-2.5829e-04	-0.0061	0.0055	0.945
R_q	Ti6Al4V; rough milling	conf	3	-0.1345	-0.1711	-0.0978	0.088
R_q	Ti6Al4V; rough milling	fusion	3	0.0211	-0.0826	0.1247	0.759
R_q	Ti6Al4V; rough milling	int	3	0.0992	-0.3331	0.5315	0.731
R_q	Ti6Al4V; finish face turning	FV	3	-0.0295	-0.1017	0.0426	0.569
R_q	Ti6Al4V; finish face turning	conf	3	-0.0886	-0.0972	-0.0799	0.032
R_q	Ti6Al4V; finish face turning	fusion	3	-0.0949	-0.0963	-0.0936	0.004
R_q	Ti6Al4V; finish face turning	int	3	0.01	-0.1151	0.135	0.902
R_q	Ti6Al4V; rough face turning	FV	3	-0.0226	-0.0313	-0.014	0.123
R_q	Ti6Al4V; rough face turning	conf	3	-0.0463	-0.0561	-0.0365	0.069
R_q	Ti6Al4V; rough face turning	fusion	3	-0.0469	-0.0542	-0.0395	0.051
R_q	Ti6Al4V; rough face turning	int	3	0.0367	-0.0149	0.0883	0.396
R_q	Ti6Al4V; finish wire EDM	FV	3	0.1603	-0.2413	0.5619	0.577
R_q	Ti6Al4V; finish wire EDM	conf	3	0.288	0.1849	0.3911	0.115
R_q	Ti6Al4V; finish wire EDM	fusion	3	0.3411	0.2647	0.4176	0.073
R_q	Ti6Al4V; finish wire EDM	int	3	0.0465	-0.0791	0.1722	0.6
R_q	Ti6Al4V; rough wire EDM	FV	3	-0.009	-0.0113	-0.0066	0.084
R_q	Ti6Al4V; rough wire EDM	conf	3	0.0617	0.0597	0.0638	0.011
R_q	Ti6Al4V; rough wire EDM	fusion	3	0.1981	0.1203	0.2758	0.126
R_q	Ti6Al4V; rough wire EDM	int	3	-0.1365	-0.3188	0.0457	0.381

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	0.2049	0.0513	0.3585	0.233
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.0536	0.0451	0.062	0.051
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	-0.0122	-0.0226	-0.0018	0.262
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.0538	-5.3777e-04	0.1082	0.303
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.3265	-0.4476	-0.2054	0.119
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.9366	0.2756	1.5977	0.22
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.552	0.3649	0.739	0.109
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.1619	-0.6167	0.9405	0.754
R_{sk}	AISI 304 / EN 1.4301; grinding	FV	3	0.0758	-0.0359	0.1875	0.41
R_{sk}	AISI 304 / EN 1.4301; grinding	conf	3	-0.0323	-0.09	0.0255	0.471
R_{sk}	AISI 304 / EN 1.4301; grinding	fusion	3	-0.2917	-0.6762	0.0927	0.377
R_{sk}	AISI 304 / EN 1.4301; grinding	int	3	-0.0744	-0.2477	0.0989	0.555
R_{sk}	AISI 304 / EN 1.4301; honing	FV	3	0.1226	0.0224	0.2228	0.252
R_{sk}	AISI 304 / EN 1.4301; honing	conf	3	0.4332	0.0507	0.8156	0.269
R_{sk}	AISI 304 / EN 1.4301; honing	fusion	3	0.6493	-0.0479	1.3465	0.319
R_{sk}	AISI 304 / EN 1.4301; honing	int	3	-0.0627	-0.499	0.3736	0.825
R_{sk}	AISI 304 / EN 1.4301; finish milling	FV	3	-0.3717	-0.9191	0.1756	0.41
R_{sk}	AISI 304 / EN 1.4301; finish milling	conf	3	0.138	0.0962	0.1798	0.098
R_{sk}	AISI 304 / EN 1.4301; finish milling	fusion	3	0.2208	0.0554	0.3862	0.232
R_{sk}	AISI 304 / EN 1.4301; finish milling	int	3	0.1387	-0.2276	0.505	0.594
R_{sk}	AISI 304 / EN 1.4301; rough milling	FV	3	0.5838	0.142	1.0256	0.235
R_{sk}	AISI 304 / EN 1.4301; rough milling	conf	3	0.305	0.2581	0.3519	0.05
R_{sk}	AISI 304 / EN 1.4301; rough milling	fusion	3	0.1719	-0.0628	0.4066	0.387
R_{sk}	AISI 304 / EN 1.4301; rough milling	int	3	-0.3112	-1.0793	0.4569	0.573
R_{sk}	AISI 304 / EN 1.4301; finish face turning	FV	3	-0.1907	-0.3401	-0.0413	0.242
R_{sk}	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0738	-0.1523	0.0046	0.316
R_{sk}	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0697	-0.1549	0.0155	0.355
R_{sk}	AISI 304 / EN 1.4301; finish face turning	int	3	-0.1953	-0.3636	-0.027	0.264
R_{sk}	AISI 304 / EN 1.4301; rough face turning	FV	3	2.1761	0.347	4.0053	0.258
R_{sk}	AISI 304 / EN 1.4301; rough face turning	conf	3	-1.3857	-2.2029	-0.5685	0.186
R_{sk}	AISI 304 / EN 1.4301; rough face turning	fusion	3	-1.7932	-3.3429	-0.2435	0.264
R_{sk}	AISI 304 / EN 1.4301; rough face turning	int	3	1.9795	-2.4621	6.4211	0.543
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	0.3172	0.0106	0.6238	0.292
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.081	-0.6857	0.8478	0.87
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.4896	-0.4031	1.3824	0.477
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.1508	-1.1749	0.8733	0.821

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.4296	-0.5846	-0.2747	0.116
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.3341	-0.0605	0.7286	0.345
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	1.026	0.6048	1.4471	0.131
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	int	2	0.1186	—	—	—
R_{sk}	Al7075; burnishing after MF	FV	3	-0.79	-1.6389	0.059	0.319
R_{sk}	Al7075; burnishing after MF	conf	3	-0.0488	-0.0598	-0.0379	0.073
R_{sk}	Al7075; burnishing after MF	fusion	3	0.0812	0.0661	0.0964	0.061
R_{sk}	Al7075; burnishing after MF	int	3	0.0134	0.0073	0.0195	0.146
R_{sk}	Al7075; glass bead blasting	FV	3	-0.0986	-0.2552	0.058	0.434
R_{sk}	Al7075; glass bead blasting	conf	3	1.3598	0.3259	2.3936	0.236
R_{sk}	Al7075; glass bead blasting	fusion	3	1.1735	0.8004	1.5465	0.102
R_{sk}	Al7075; glass bead blasting	int	3	0.2192	0.0716	0.3668	0.211
R_{sk}	Al7075; grinding	FV	3	0.067	-0.0091	0.143	0.334
R_{sk}	Al7075; grinding	conf	3	-0.0836	-0.1449	-0.0223	0.228
R_{sk}	Al7075; grinding	fusion	3	-0.1577	-0.3176	0.0022	0.304
R_{sk}	Al7075; grinding	int	3	-0.01	-0.3942	0.3742	0.967
R_{sk}	Al7075; honing	FV	3	2.4541	1.8499	3.0582	0.08
R_{sk}	Al7075; honing	conf	3	0.747	-0.0732	1.5672	0.325
R_{sk}	Al7075; honing	fusion	3	1.3204	-0.197	2.8377	0.338
R_{sk}	Al7075; honing	int	3	-0.1452	-4.4644	4.174	0.958
R_{sk}	Al7075; finish milling	FV	3	-0.206	-0.388	-0.024	0.27
R_{sk}	Al7075; finish milling	conf	3	-0.0837	-0.1276	-0.0398	0.166
R_{sk}	Al7075; finish milling	fusion	3	-0.0499	-0.0849	-0.0149	0.219
R_{sk}	Al7075; finish milling	int	3	0.0147	0.0042	0.0253	0.223
R_{sk}	Al7075; rough milling	FV	3	-5.5913	-19.2634	8.0808	0.57
R_{sk}	Al7075; rough milling	conf	3	-1.0894	-2.7052	0.5264	0.412
R_{sk}	Al7075; rough milling	fusion	3	1.3446	0.5876	2.1016	0.178
R_{sk}	Al7075; rough milling	int	3	1.1689	-4.9328	7.2707	0.771
R_{sk}	Al7075; finish face turning	FV	3	-0.2232	-0.4232	-0.0232	0.273
R_{sk}	Al7075; finish face turning	conf	3	-0.0028	-0.0117	0.0062	0.651
R_{sk}	Al7075; finish face turning	fusion	3	0.0309	0.0282	0.0337	0.029
R_{sk}	Al7075; finish face turning	int	3	-0.0905	-0.1302	-0.0507	0.14
R_{sk}	Al7075; rough face turning	FV	3	-0.1624	-0.2646	-0.0601	0.198
R_{sk}	Al7075; rough face turning	conf	3	0.1555	0.152	0.159	0.007
R_{sk}	Al7075; rough face turning	fusion	3	0.2998	0.1633	0.4363	0.145
R_{sk}	Al7075; rough face turning	int	3	-0.1061	-0.5206	0.3084	0.704
R_{sk}	Al7075; finish wire EDM	FV	3	0.3814	0.0603	0.7024	0.258
R_{sk}	Al7075; finish wire EDM	conf	3	-1.0837	-2.4638	0.2963	0.367
R_{sk}	Al7075; finish wire EDM	fusion	3	-1.5087	-3.4536	0.4361	0.37
R_{sk}	Al7075; finish wire EDM	int	3	-0.1967	-1.2068	0.8134	0.768
R_{sk}	Al7075; rough wire EDM	FV	3	-0.1046	-0.3218	0.1125	0.518
R_{sk}	Al7075; rough wire EDM	conf	3	3.3277	2.4323	4.2232	0.087
R_{sk}	Al7075; rough wire EDM	fusion	3	4.0295	2.6677	5.3914	0.109
R_{sk}	Al7075; rough wire EDM	int	3	-1.2346	-2.7861	0.3169	0.363
R_{sk}	C45 steel; burnishing after MF	FV	3	0.5627	0.146	0.9794	0.23
R_{sk}	C45 steel; burnishing after MF	conf	2	0.0044	—	—	—
R_{sk}	C45 steel; burnishing after MF	fusion	3	-0.2047	-0.3268	-0.0826	0.188
R_{sk}	C45 steel; burnishing after MF	int	4	-0.029	-0.0471	-0.0109	0.088
R_{sk}	C45 steel; glass bead blasting	FV	3	-0.1759	-0.772	0.4202	0.666
R_{sk}	C45 steel; glass bead blasting	conf	3	1.5516	0.3702	2.7329	0.236
R_{sk}	C45 steel; glass bead blasting	fusion	3	2.2138	0.5915	3.8361	0.228
R_{sk}	C45 steel; glass bead blasting	int	3	0.1263	-0.1163	0.3689	0.494
R_{sk}	C45 steel; grinding	FV	3	0.1522	0.0804	0.224	0.15
R_{sk}	C45 steel; grinding	conf	3	-0.074	-0.1546	0.0066	0.323
R_{sk}	C45 steel; grinding	fusion	3	-0.1378	-0.2904	0.0148	0.327
R_{sk}	C45 steel; grinding	int	3	0.0275	-0.38	0.4351	0.916
R_{sk}	C45 steel; honing	FV	3	0.1938	0.0722	0.3155	0.197
R_{sk}	C45 steel; honing	conf	3	0.6579	0.1267	1.1891	0.249
R_{sk}	C45 steel; honing	fusion	3	1.1606	-0.4883	2.8094	0.399
R_{sk}	C45 steel; honing	int	3	-0.1264	-1.0058	0.753	0.825

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sk}	C45 steel; finish milling	FV	3	0.3036	0.2898	0.3174	0.015
R_{sk}	C45 steel; finish milling	conf	2	-0.0209	—	—	—
R_{sk}	C45 steel; finish milling	fusion	3	-0.2606	-0.5335	0.0124	0.312
R_{sk}	C45 steel; finish milling	int	3	0.1201	0.0332	0.207	0.225
R_{sk}	C45 steel; rough milling	FV	3	0.291	-0.2964	0.8785	0.509
R_{sk}	C45 steel; rough milling	conf	2	0.3118	—	—	—
R_{sk}	C45 steel; rough milling	fusion	3	0.0586	-0.8081	0.9253	0.916
R_{sk}	C45 steel; rough milling	int	3	0.2206	-0.5129	0.9542	0.661
R_{sk}	C45 steel; finish face turning	FV	3	-0.0328	-0.1206	0.055	0.598
R_{sk}	C45 steel; finish face turning	conf	2	-0.2875	—	—	—
R_{sk}	C45 steel; finish face turning	fusion	3	-0.5629	-0.9569	-0.169	0.218
R_{sk}	C45 steel; finish face turning	int	3	0.0894	-0.2215	0.4003	0.673
R_{sk}	C45 steel; rough face turning	FV	3	1.3453	-1.2312	3.9217	0.493
R_{sk}	C45 steel; rough face turning	conf	2	-0.6399	—	—	—
R_{sk}	C45 steel; rough face turning	fusion	3	-2.1959	-4.6387	0.2469	0.329
R_{sk}	C45 steel; rough face turning	int	3	-1.888	-3.1594	-0.6166	0.211
R_{sk}	C45 steel; finish wire EDM	FV	3	0.3003	-0.0275	0.628	0.323
R_{sk}	C45 steel; finish wire EDM	conf	3	0.6184	0.2391	0.9977	0.193
R_{sk}	C45 steel; finish wire EDM	fusion	3	-1.812	-4.5815	0.9575	0.422
R_{sk}	C45 steel; finish wire EDM	int	3	-0.0148	-0.5876	0.558	0.968
R_{sk}	C45 steel; rough wire EDM	FV	3	-0.5441	-1.1431	0.0548	0.326
R_{sk}	C45 steel; rough wire EDM	conf	3	0.811	0.1856	1.4364	0.239
R_{sk}	C45 steel; rough wire EDM	fusion	3	5.0782	3.671	6.4853	0.089
R_{sk}	C45 steel; rough wire EDM	int	3	-0.0452	-0.2027	0.1124	0.674
R_{sk}	ELLOR graphite; glass bead blast- ing	FV	3	-0.0097	-0.0264	0.0069	0.457
R_{sk}	ELLOR graphite; glass bead blast- ing	conf	3	0.0106	-0.0258	0.0471	0.669
R_{sk}	ELLOR graphite; glass bead blast- ing	fusion	3	0.0031	-0.0083	0.0145	0.687
R_{sk}	ELLOR graphite; glass bead blast- ing	int	3	-0.0813	-0.2009	0.0383	0.41
R_{sk}	ELLOR graphite; grinding	FV	3	-0.0126	-0.0346	0.0094	0.463
R_{sk}	ELLOR graphite; grinding	conf	3	0.0474	0.0396	0.0552	0.053
R_{sk}	ELLOR graphite; grinding	fusion	3	0.0517	0.0406	0.0628	0.069
R_{sk}	ELLOR graphite; grinding	int	3	-0.3753	-0.8183	0.0677	0.345
R_{sk}	ELLOR graphite; honing	FV	3	0.1422	0.1088	0.1757	0.076
R_{sk}	ELLOR graphite; honing	conf	3	-0.1529	-0.3098	0.004	0.307
R_{sk}	ELLOR graphite; honing	fusion	3	-0.2761	-0.5723	0.0201	0.319
R_{sk}	ELLOR graphite; honing	int	3	-0.0258	-0.788	0.7364	0.958
R_{sk}	ELLOR graphite; finish milling	FV	3	0.1365	-0.0697	0.3427	0.418
R_{sk}	ELLOR graphite; finish milling	conf	3	0.0391	-0.0575	0.1357	0.573
R_{sk}	ELLOR graphite; finish milling	fusion	3	-0.2565	-0.2809	-0.232	0.031
R_{sk}	ELLOR graphite; finish milling	int	3	-0.4776	-0.9039	-0.0514	0.272
R_{sk}	ELLOR graphite; rough milling	FV	3	0.046	-0.0675	0.1595	0.573
R_{sk}	ELLOR graphite; rough milling	conf	3	0.0791	0.0655	0.0926	0.056
R_{sk}	ELLOR graphite; rough milling	fusion	3	0.0289	-0.0152	0.073	0.421
R_{sk}	ELLOR graphite; rough milling	int	3	-0.4635	-1.1711	0.2442	0.421
R_{sk}	ELLOR graphite; finish face turn- ing	FV	3	0.0519	0.0152	0.0885	0.22
R_{sk}	ELLOR graphite; finish face turn- ing	conf	3	0.0409	-3.8882e-04	0.0821	0.303
R_{sk}	ELLOR graphite; finish face turn- ing	fusion	3	-0.0363	-0.1284	0.0557	0.581
R_{sk}	ELLOR graphite; finish face turn- ing	int	3	-0.4292	-1.1015	0.2431	0.429
R_{sk}	ELLOR graphite; rough face turn- ing	FV	3	0.0246	-0.0223	0.0716	0.491
R_{sk}	ELLOR graphite; rough face turn- ing	conf	3	-0.0388	-0.0403	-0.0373	0.013
R_{sk}	ELLOR graphite; rough face turn- ing	fusion	3	-0.0215	-0.0361	-0.0069	0.213
R_{sk}	ELLOR graphite; rough face turn- ing	int	3	0.0662	-0.0253	0.1576	0.391

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sk}	ELLOR graphite; finish wire EDM	FV	3	0.0069	-0.0367	0.0506	0.809
R_{sk}	ELLOR graphite; finish wire EDM	conf	3	0.0522	0.0386	0.0659	0.084
R_{sk}	ELLOR graphite; finish wire EDM	fusion	3	0.0132	-0.0561	0.0826	0.772
R_{sk}	ELLOR graphite; finish wire EDM	int	2	-0.0145	—	—	—
R_{sk}	ELLOR graphite; rough wire EDM	FV	3	-0.02	-0.0793	0.0393	0.628
R_{sk}	ELLOR graphite; rough wire EDM	conf	3	0.0345	0.0125	0.0564	0.2
R_{sk}	ELLOR graphite; rough wire EDM	fusion	3	0.0158	-0.0334	0.0649	0.643
R_{sk}	ELLOR graphite; rough wire EDM	int	3	-0.3498	-0.7921	0.0925	0.365
R_{sk}	MO58A brass; burnishing after MF	FV	4	0.4423	0.1835	0.7011	0.079
R_{sk}	MO58A brass; burnishing after MF	conf	3	-0.1035	-0.2736	0.0667	0.444
R_{sk}	MO58A brass; burnishing after MF	fusion	3	-0.2174	-0.3955	-0.0392	0.252
R_{sk}	MO58A brass; burnishing after MF	int	3	-0.0203	-0.0655	0.0249	0.541
R_{sk}	MO58A brass; glass bead blasting	FV	3	0.0402	-0.1056	0.186	0.684
R_{sk}	MO58A brass; glass bead blasting	conf	3	2.6754	0.5859	4.765	0.241
R_{sk}	MO58A brass; glass bead blasting	fusion	3	2.7388	1.5605	3.9171	0.138
R_{sk}	MO58A brass; glass bead blasting	int	3	0.199	-0.0761	0.4742	0.391
R_{sk}	MO58A brass; grinding	FV	3	0.0869	-0.0867	0.2605	0.506
R_{sk}	MO58A brass; grinding	conf	3	-0.0673	-0.1179	-0.0166	0.233
R_{sk}	MO58A brass; grinding	fusion	3	-0.378	-0.8039	0.048	0.332
R_{sk}	MO58A brass; grinding	int	3	-0.0719	-0.2756	0.1318	0.615
R_{sk}	MO58A brass; honing	FV	3	1.5791	-0.0032	3.1614	0.301
R_{sk}	MO58A brass; honing	conf	3	2.0715	0.2749	3.8681	0.265
R_{sk}	MO58A brass; honing	fusion	3	2.8841	0.1023	5.6658	0.291
R_{sk}	MO58A brass; honing	int	3	-0.0399	-1.0383	0.9585	0.95
R_{sk}	MO58A brass; finish milling	FV	3	-0.0163	-1.8006	1.768	0.989
R_{sk}	MO58A brass; finish milling	conf	3	-0.3831	-0.6763	-0.0899	0.237
R_{sk}	MO58A brass; finish milling	fusion	3	-0.1018	-0.5274	0.3238	0.721
R_{sk}	MO58A brass; finish milling	int	3	-0.2511	-0.9082	0.406	0.591
R_{sk}	MO58A brass; rough milling	FV	3	0.2854	0.0679	0.5029	0.236
R_{sk}	MO58A brass; rough milling	conf	3	-0.4017	-0.6036	-0.1999	0.16
R_{sk}	MO58A brass; rough milling	fusion	3	-0.7241	-1.3675	-0.0806	0.271
R_{sk}	MO58A brass; rough milling	int	3	0.1207	0.1133	0.128	0.02
R_{sk}	MO58A brass; finish face turning	FV	3	0.3771	0.2137	0.5405	0.139
R_{sk}	MO58A brass; finish face turning	conf	3	-0.5979	-1.163	-0.0328	0.286
R_{sk}	MO58A brass; finish face turning	fusion	3	-0.8992	-2.8398	1.0413	0.531
R_{sk}	MO58A brass; finish face turning	int	3	-0.193	-0.4012	0.0152	0.32
R_{sk}	MO58A brass; rough face turning	FV	3	0.0885	0.0479	0.1292	0.146
R_{sk}	MO58A brass; rough face turning	conf	3	-0.1615	-0.1707	-0.1524	0.018
R_{sk}	MO58A brass; rough face turning	fusion	3	-0.8329	-1.6839	0.0182	0.306
R_{sk}	MO58A brass; rough face turning	int	3	0.0372	-0.0708	0.1452	0.622
R_{sk}	MO58A brass; finish wire EDM	FV	3	0.4873	0.2513	0.7233	0.154
R_{sk}	MO58A brass; finish wire EDM	conf	3	-1.1679	-2.7293	0.3935	0.381
R_{sk}	MO58A brass; finish wire EDM	fusion	3	-0.3479	-0.6556	-0.0402	0.27
R_{sk}	MO58A brass; finish wire EDM	int	3	-0.5473	-0.7552	-0.3393	0.122
R_{sk}	MO58A brass; rough wire EDM	FV	3	-1.1835	-1.8602	-0.5067	0.181
R_{sk}	MO58A brass; rough wire EDM	conf	3	3.7813	3.7431	3.8195	0.003
R_{sk}	MO58A brass; rough wire EDM	fusion	3	6.3653	4.4321	8.2985	0.098
R_{sk}	MO58A brass; rough wire EDM	int	3	1.9469	-2.6553	6.549	0.559
R_{sk}	Ti6Al4V; burnishing after MF	FV	3	0.1781	-0.0662	0.4224	0.389
R_{sk}	Ti6Al4V; burnishing after MF	conf	3	0.158	0.1447	0.1713	0.027
R_{sk}	Ti6Al4V; burnishing after MF	fusion	3	0.1332	0.104	0.1623	0.071
R_{sk}	Ti6Al4V; burnishing after MF	int	3	0.0292	-1.4465	1.5049	0.975
R_{sk}	Ti6Al4V; glass bead blasting	FV	3	-0.1124	-0.1501	-0.0747	0.108
R_{sk}	Ti6Al4V; glass bead blasting	conf	3	0.5558	0.0993	1.0122	0.253
R_{sk}	Ti6Al4V; glass bead blasting	fusion	3	0.7697	0.2515	1.2879	0.211
R_{sk}	Ti6Al4V; glass bead blasting	int	3	0.0758	-0.4862	0.6377	0.836
R_{sk}	Ti6Al4V; grinding	FV	3	0.1223	-0.7106	0.9552	0.822
R_{sk}	Ti6Al4V; grinding	conf	3	-0.122	-0.2167	-0.0272	0.24
R_{sk}	Ti6Al4V; grinding	fusion	3	0.348	-0.2522	0.9481	0.459
R_{sk}	Ti6Al4V; grinding	int	3	-0.2762	-1.2493	0.6969	0.677

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sk}	Ti6Al4V; honing	FV	3	-0.2378	-0.3408	-0.1348	0.138
R_{sk}	Ti6Al4V; honing	conf	3	0.3167	-0.0379	0.6713	0.33
R_{sk}	Ti6Al4V; honing	fusion	3	0.5239	-0.2565	1.3042	0.414
R_{sk}	Ti6Al4V; honing	int	3	0.0273	-0.0377	0.0924	0.561
R_{sk}	Ti6Al4V; finish milling	FV	3	-0.2553	-0.5648	0.0542	0.353
R_{sk}	Ti6Al4V; finish milling	conf	3	0.2509	0.0559	0.4458	0.24
R_{sk}	Ti6Al4V; finish milling	fusion	3	0.3729	0.1325	0.6133	0.202
R_{sk}	Ti6Al4V; finish milling	int	3	-0.0293	-0.1038	0.0453	0.582
R_{sk}	Ti6Al4V; rough milling	FV	3	-0.3978	-0.6727	-0.1229	0.216
R_{sk}	Ti6Al4V; rough milling	conf	3	0.0224	-0.0621	0.1069	0.695
R_{sk}	Ti6Al4V; rough milling	fusion	3	0.1369	0.1308	0.1431	0.015
R_{sk}	Ti6Al4V; rough milling	int	3	-0.1343	-0.1691	-0.0996	0.084
R_{sk}	Ti6Al4V; finish face turning	FV	3	0.0084	-0.0505	0.0673	0.827
R_{sk}	Ti6Al4V; finish face turning	conf	3	0.0012	-0.1445	0.1469	0.99
R_{sk}	Ti6Al4V; finish face turning	fusion	3	0.0978	0.0321	0.1634	0.21
R_{sk}	Ti6Al4V; finish face turning	int	3	-0.1019	-0.3061	0.1024	0.507
R_{sk}	Ti6Al4V; rough face turning	FV	3	-0.1164	-0.413	0.1803	0.583
R_{sk}	Ti6Al4V; rough face turning	conf	3	0.3256	0.1961	0.4551	0.127
R_{sk}	Ti6Al4V; rough face turning	fusion	3	0.508	0.1488	0.8672	0.22
R_{sk}	Ti6Al4V; rough face turning	int	3	-0.1158	-0.3491	0.1176	0.509
R_{sk}	Ti6Al4V; finish wire EDM	FV	3	-0.1737	-0.5136	0.1661	0.499
R_{sk}	Ti6Al4V; finish wire EDM	conf	3	0.2112	0.0302	0.3922	0.262
R_{sk}	Ti6Al4V; finish wire EDM	fusion	3	0.3358	-0.4036	1.0752	0.537
R_{sk}	Ti6Al4V; finish wire EDM	int	3	0.3065	-0.4946	1.1076	0.59
R_{sk}	Ti6Al4V; rough wire EDM	FV	3	-0.1402	-0.1504	-0.13	0.024
R_{sk}	Ti6Al4V; rough wire EDM	conf	3	1.3235	1.0861	1.5609	0.058
R_{sk}	Ti6Al4V; rough wire EDM	fusion	3	2.6309	1.269	3.9928	0.164
R_{sk}	Ti6Al4V; rough wire EDM	int	3	-0.085	-0.1779	0.0079	0.324
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-2.3551e-05	-3.7339e-05	-9.7629e-06	0.185
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	-1.0308e-05	-2.4596e-05	3.9801e-06	0.392
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	-9.0417e-06	-2.1932e-05	3.8489e-06	0.4
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	int	3	1.7702e-05	-1.2162e-04	1.5702e-04	0.845
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-1.4245e-05	-2.0653e-05	-7.8370e-06	0.144
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	-2.3889e-05	-3.5289e-05	-1.2488e-05	0.152
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	-2.1051e-05	-2.7021e-05	-1.5081e-05	0.091
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	int	3	-1.3926e-05	-1.2605e-04	9.8200e-05	0.848
R_{sm}	AISI 304 / EN 1.4301; grinding	FV	3	-1.1264e-05	-4.3297e-05	2.0768e-05	0.616
R_{sm}	AISI 304 / EN 1.4301; grinding	conf	3	2.0665e-05	6.2282e-06	3.5103e-05	0.218
R_{sm}	AISI 304 / EN 1.4301; grinding	fusion	3	2.0227e-05	6.0328e-06	3.4421e-05	0.219
R_{sm}	AISI 304 / EN 1.4301; grinding	int	3	1.0826e-04	-8.8266e-05	3.0479e-04	0.476
R_{sm}	AISI 304 / EN 1.4301; honing	FV	3	1.8549e-05	1.8131e-06	3.5286e-05	0.275
R_{sm}	AISI 304 / EN 1.4301; honing	conf	3	3.9169e-05	-7.2937e-06	8.5632e-05	0.346
R_{sm}	AISI 304 / EN 1.4301; honing	fusion	3	4.6877e-05	-6.0216e-06	9.9776e-05	0.333
R_{sm}	AISI 304 / EN 1.4301; honing	int	3	1.8578e-04	-1.0174e-04	4.7330e-04	0.426
R_{sm}	AISI 304 / EN 1.4301; finish milling	FV	3	1.0765e-05	7.7066e-06	1.3824e-05	0.092
R_{sm}	AISI 304 / EN 1.4301; finish milling	conf	3	-7.4991e-06	-3.2537e-05	1.7538e-05	0.662
R_{sm}	AISI 304 / EN 1.4301; finish milling	fusion	3	-4.4070e-06	-2.4050e-05	1.5236e-05	0.736
R_{sm}	AISI 304 / EN 1.4301; finish milling	int	3	-9.3934e-07	-3.8263e-04	3.8076e-04	0.997
R_{sm}	AISI 304 / EN 1.4301; rough milling	FV	3	-2.4070e-05	-2.4725e-05	-2.3415e-05	0.009
R_{sm}	AISI 304 / EN 1.4301; rough milling	conf	3	-2.3412e-05	-4.9901e-05	3.0773e-06	0.333

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sm}	AISI 304 / EN 1.4301; rough milling	fusion	3	-2.3929e-05	-5.1023e-05	3.1640e-06	0.333
R_{sm}	AISI 304 / EN 1.4301; rough milling	int	3	4.4541e-05	-1.0641e-04	1.9549e-04	0.666
R_{sm}	AISI 304 / EN 1.4301; finish face turning	FV	3	-8.2828e-05	-1.6141e-04	-4.2429e-06	0.287
R_{sm}	AISI 304 / EN 1.4301; finish face turning	conf	3	-2.2117e-04	-2.8247e-04	-1.5986e-04	0.089
R_{sm}	AISI 304 / EN 1.4301; finish face turning	fusion	3	-2.2015e-04	-2.9468e-04	-1.4562e-04	0.109
R_{sm}	AISI 304 / EN 1.4301; finish face turning	int	3	2.9553e-04	-0.003	0.0035	0.888
R_{sm}	AISI 304 / EN 1.4301; rough face turning	FV	3	-1.0266e-04	-1.9632e-04	-9.0000e-06	0.277
R_{sm}	AISI 304 / EN 1.4301; rough face turning	conf	3	-8.6690e-05	-9.5044e-05	-7.8336e-05	0.031
R_{sm}	AISI 304 / EN 1.4301; rough face turning	fusion	3	-8.8235e-05	-1.3621e-04	-4.0264e-05	0.172
R_{sm}	AISI 304 / EN 1.4301; rough face turning	int	3	1.3410e-04	-0.0021	0.0023	0.924
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-2.3286e-06	-1.4957e-05	1.0300e-05	0.779
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	-2.8711e-06	-4.4427e-06	-1.2995e-06	0.173
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	1.0892e-05	-1.2606e-05	3.4389e-05	0.53
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	int	3	1.1661e-04	-7.9313e-05	3.1254e-04	0.451
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-2.4693e-05	-5.5421e-05	6.0347e-06	0.36
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	2.1508e-05	-5.4221e-06	4.8437e-05	0.362
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	-6.7411e-06	-6.5488e-05	5.2005e-05	0.859
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	int	2	-4.4870e-05	—	—	—
R_{sm}	Al7075; burnishing after MF	FV	3	-3.1862e-05	-6.1415e-05	-2.3079e-06	0.281
R_{sm}	Al7075; burnishing after MF	conf	3	-1.3305e-05	-2.6661e-05	5.2116e-08	0.301
R_{sm}	Al7075; burnishing after MF	fusion	3	-1.6680e-05	-1.9546e-05	-1.3815e-05	0.056
R_{sm}	Al7075; burnishing after MF	int	3	3.4403e-05	-1.7825e-04	2.4706e-04	0.805
R_{sm}	Al7075; glass bead blasting	FV	3	-4.1516e-05	-1.0335e-04	2.0314e-05	0.414
R_{sm}	Al7075; glass bead blasting	conf	3	1.5408e-06	-1.1239e-05	1.4321e-05	0.852
R_{sm}	Al7075; glass bead blasting	fusion	3	-1.4271e-05	-3.6891e-05	8.3484e-06	0.433
R_{sm}	Al7075; glass bead blasting	int	3	-1.6643e-05	-2.0151e-05	-1.3136e-05	0.068
R_{sm}	Al7075; grinding	FV	3	-3.2093e-06	-1.9692e-05	1.3274e-05	0.768
R_{sm}	Al7075; grinding	conf	3	-4.1201e-06	-1.9840e-05	1.1600e-05	0.698
R_{sm}	Al7075; grinding	fusion	3	-2.8113e-06	-1.4626e-05	9.0039e-06	0.722
R_{sm}	Al7075; grinding	int	3	7.4099e-05	3.1154e-05	1.1704e-04	0.183
R_{sm}	Al7075; honing	FV	3	-3.4809e-05	-3.8091e-05	-3.1527e-05	0.031
R_{sm}	Al7075; honing	conf	3	-1.8695e-05	-3.6178e-05	-1.2117e-06	0.283
R_{sm}	Al7075; honing	fusion	3	-1.2988e-05	-2.7512e-05	1.5353e-06	0.33
R_{sm}	Al7075; honing	int	3	1.1399e-04	4.0975e-05	1.8701e-04	0.201
R_{sm}	Al7075; finish milling	FV	3	1.1142e-05	-1.7152e-05	3.9436e-05	0.582
R_{sm}	Al7075; finish milling	conf	3	-8.6932e-06	-1.0020e-05	-7.3663e-06	0.049
R_{sm}	Al7075; finish milling	fusion	3	-1.1772e-05	-1.3692e-05	-9.8520e-06	0.053
R_{sm}	Al7075; finish milling	int	3	1.9811e-05	-2.6141e-06	4.2236e-05	0.333
R_{sm}	Al7075; rough milling	FV	3	-2.7056e-05	-1.1579e-04	6.1673e-05	0.657
R_{sm}	Al7075; rough milling	conf	3	-1.5207e-04	-2.8003e-04	-2.4099e-05	0.258
R_{sm}	Al7075; rough milling	fusion	3	-1.4498e-04	-2.6414e-04	-2.5816e-05	0.253
R_{sm}	Al7075; rough milling	int	3	1.8964e-04	-1.3072e-04	5.0999e-04	0.453
R_{sm}	Al7075; finish face turning	FV	3	-9.7365e-05	-1.0896e-04	-8.5767e-05	0.039
R_{sm}	Al7075; finish face turning	conf	3	-9.3369e-05	-1.4872e-04	-3.8015e-05	0.187
R_{sm}	Al7075; finish face turning	fusion	3	-8.5127e-05	-1.3773e-04	-3.2528e-05	0.194
R_{sm}	Al7075; finish face turning	int	3	2.5931e-04	-0.0012	0.0017	0.786

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sm}	Al7075; rough face turning	FV	3	-1.6392e-04	-3.4711e-04	1.9266e-05	0.33
R_{sm}	Al7075; rough face turning	conf	3	-5.8865e-05	-1.0051e-04	-1.7220e-05	0.221
R_{sm}	Al7075; rough face turning	fusion	3	-3.0843e-05	-5.2812e-05	-8.8750e-06	0.222
R_{sm}	Al7075; rough face turning	int	3	4.0247e-05	-0.0027	0.0028	0.982
R_{sm}	Al7075; finish wire EDM	FV	3	6.7840e-06	-1.1728e-05	2.5296e-05	0.603
R_{sm}	Al7075; finish wire EDM	conf	3	4.2888e-05	2.4211e-06	8.3355e-05	0.286
R_{sm}	Al7075; finish wire EDM	fusion	3	7.6553e-05	-1.4045e-05	1.6715e-04	0.346
R_{sm}	Al7075; finish wire EDM	int	3	4.8296e-05	-8.1160e-05	1.7775e-04	0.598
R_{sm}	Al7075; rough wire EDM	FV	3	6.6797e-06	-1.4551e-05	2.7911e-05	0.648
R_{sm}	Al7075; rough wire EDM	conf	3	3.8178e-06	-6.5930e-06	1.4229e-05	0.603
R_{sm}	Al7075; rough wire EDM	fusion	3	8.9596e-06	-2.2316e-05	4.0236e-05	0.674
R_{sm}	Al7075; rough wire EDM	int	3	1.0696e-04	-8.5338e-05	2.9925e-04	0.473
R_{sm}	C45 steel; burnishing after MF	FV	3	8.3680e-06	-2.0622e-05	3.7358e-05	0.672
R_{sm}	C45 steel; burnishing after MF	conf	2	1.2199e-05	—	—	—
R_{sm}	C45 steel; burnishing after MF	fusion	3	5.2740e-06	3.2055e-06	7.3426e-06	0.126
R_{sm}	C45 steel; burnishing after MF	int	4	-4.2972e-05	-1.6279e-04	7.6846e-05	0.555
R_{sm}	C45 steel; glass bead blasting	FV	3	-2.5951e-05	-6.5635e-05	1.3732e-05	0.422
R_{sm}	C45 steel; glass bead blasting	conf	3	-1.8364e-05	-2.5118e-05	-1.1609e-05	0.118
R_{sm}	C45 steel; glass bead blasting	fusion	3	-2.1187e-05	-2.9478e-05	-1.2895e-05	0.125
R_{sm}	C45 steel; glass bead blasting	int	3	-2.5011e-05	-1.2101e-04	7.0989e-05	0.699
R_{sm}	C45 steel; grinding	FV	3	-1.6548e-05	-3.5327e-05	2.2319e-06	0.334
R_{sm}	C45 steel; grinding	conf	3	-5.9639e-06	-1.8395e-05	6.4676e-06	0.52
R_{sm}	C45 steel; grinding	fusion	3	-3.6589e-06	-1.4444e-05	7.1266e-06	0.626
R_{sm}	C45 steel; grinding	int	3	9.1087e-05	8.5095e-05	9.7079e-05	0.021
R_{sm}	C45 steel; honing	FV	3	3.2721e-05	3.0859e-05	3.4583e-05	0.018
R_{sm}	C45 steel; honing	conf	3	4.0949e-05	-4.7893e-06	8.6687e-05	0.33
R_{sm}	C45 steel; honing	fusion	3	4.3496e-05	-1.3939e-06	8.8385e-05	0.309
R_{sm}	C45 steel; honing	int	3	2.0127e-04	-1.0818e-04	5.1072e-04	0.423
R_{sm}	C45 steel; finish milling	FV	3	5.3703e-06	1.7667e-06	8.9740e-06	0.21
R_{sm}	C45 steel; finish milling	conf	2	6.1334e-06	—	—	—
R_{sm}	C45 steel; finish milling	fusion	3	1.1596e-05	-6.5202e-07	2.3844e-05	0.315
R_{sm}	C45 steel; finish milling	int	3	-5.1526e-05	-2.6850e-04	1.6545e-04	0.723
R_{sm}	C45 steel; rough milling	FV	3	-3.5257e-05	-1.4469e-04	7.4176e-05	0.641
R_{sm}	C45 steel; rough milling	conf	2	2.2346e-05	—	—	—
R_{sm}	C45 steel; rough milling	fusion	3	9.0551e-06	2.0264e-06	1.6084e-05	0.24
R_{sm}	C45 steel; rough milling	int	3	-1.1872e-04	-4.7683e-04	2.3939e-04	0.633
R_{sm}	C45 steel; finish face turning	FV	3	-3.3231e-05	-1.6797e-04	1.0151e-04	0.713
R_{sm}	C45 steel; finish face turning	conf	2	2.3216e-05	—	—	—
R_{sm}	C45 steel; finish face turning	fusion	3	8.9745e-06	1.7900e-07	1.7770e-05	0.295
R_{sm}	C45 steel; finish face turning	int	3	-2.0597e-04	-7.3825e-04	3.2630e-04	0.587
R_{sm}	C45 steel; rough face turning	FV	3	-1.4886e-04	-1.5123e-04	-1.4648e-04	0.005
R_{sm}	C45 steel; rough face turning	conf	2	-4.7235e-05	—	—	—
R_{sm}	C45 steel; rough face turning	fusion	3	-8.0030e-05	-1.2498e-04	-3.5082e-05	0.178
R_{sm}	C45 steel; rough face turning	int	3	1.0173e-04	-0.001	0.0012	0.889
R_{sm}	C45 steel; finish wire EDM	FV	3	1.3191e-05	-6.8268e-06	3.3210e-05	0.419
R_{sm}	C45 steel; finish wire EDM	conf	3	1.0931e-05	-2.7874e-05	4.9737e-05	0.679
R_{sm}	C45 steel; finish wire EDM	fusion	3	3.0950e-05	-3.0640e-05	9.2539e-05	0.505
R_{sm}	C45 steel; finish wire EDM	int	3	1.4229e-04	-6.3014e-05	3.4759e-04	0.404
R_{sm}	C45 steel; rough wire EDM	FV	3	4.3526e-06	-9.9966e-06	1.8702e-05	0.659
R_{sm}	C45 steel; rough wire EDM	conf	3	4.3850e-05	1.4395e-05	7.3306e-05	0.21
R_{sm}	C45 steel; rough wire EDM	fusion	3	1.7792e-05	1.0564e-05	2.5021e-05	0.13
R_{sm}	C45 steel; rough wire EDM	int	3	4.1649e-04	-2.4475e-04	0.0011	0.433
R_{sm}	ELLOR graphite; glass bead blasting	FV	3	-7.7459e-06	-3.7458e-05	2.1966e-05	0.699
R_{sm}	ELLOR graphite; glass bead blasting	conf	3	4.5716e-05	4.4959e-05	4.6474e-05	0.005
R_{sm}	ELLOR graphite; glass bead blasting	fusion	3	4.8693e-05	3.5744e-05	6.1643e-05	0.086
R_{sm}	ELLOR graphite; glass bead blasting	int	3	2.6857e-04	-1.8212e-04	7.1926e-04	0.451
R_{sm}	ELLOR graphite; grinding	FV	3	-3.1025e-05	-2.7363e-04	2.1157e-04	0.844
R_{sm}	ELLOR graphite; grinding	conf	3	1.6775e-04	1.6315e-04	1.7236e-04	0.009
R_{sm}	ELLOR graphite; grinding	fusion	3	1.3663e-04	8.7608e-05	1.8565e-04	0.115
R_{sm}	ELLOR graphite; grinding	int	3	7.5531e-04	6.7692e-06	0.0015	0.298

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sm}	ELLOR graphite; honing	FV	3	2.1629e-05	7.5237e-06	3.5733e-05	0.204
R_{sm}	ELLOR graphite; honing	conf	3	-2.0088e-05	-3.4092e-05	-6.0845e-06	0.218
R_{sm}	ELLOR graphite; honing	fusion	3	-1.3661e-05	-1.6044e-05	-1.1279e-05	0.057
R_{sm}	ELLOR graphite; honing	int	3	-1.0944e-05	-1.9457e-04	1.7268e-04	0.926
R_{sm}	ELLOR graphite; finish milling	FV	3	3.5425e-05	-2.4879e-05	9.5728e-05	0.455
R_{sm}	ELLOR graphite; finish milling	conf	3	7.3519e-06	-9.0657e-06	2.3769e-05	0.541
R_{sm}	ELLOR graphite; finish milling	fusion	3	-2.0541e-05	-4.1893e-05	8.1022e-07	0.31
R_{sm}	ELLOR graphite; finish milling	int	3	-1.3431e-04	-6.0077e-04	3.3214e-04	0.673
R_{sm}	ELLOR graphite; rough milling	FV	3	3.9326e-05	-4.8763e-05	1.2741e-04	0.542
R_{sm}	ELLOR graphite; rough milling	conf	3	4.0133e-05	3.4685e-05	4.5582e-05	0.044
R_{sm}	ELLOR graphite; rough milling	fusion	3	2.1767e-05	2.1024e-05	2.2509e-05	0.011
R_{sm}	ELLOR graphite; rough milling	int	3	-1.3303e-04	-3.9086e-04	1.2480e-04	0.496
R_{sm}	ELLOR graphite; finish face turning	FV	3	5.4895e-06	-7.8904e-05	8.9883e-05	0.919
R_{sm}	ELLOR graphite; finish face turning	conf	3	2.5309e-05	2.3595e-05	2.7024e-05	0.022
R_{sm}	ELLOR graphite; finish face turning	fusion	3	1.5851e-05	1.2640e-05	1.9063e-05	0.066
R_{sm}	ELLOR graphite; finish face turning	int	3	-2.7499e-05	-7.3385e-05	1.8388e-05	0.449
R_{sm}	ELLOR graphite; rough face turning	FV	3	-9.4631e-06	-5.9811e-05	4.0884e-05	0.775
R_{sm}	ELLOR graphite; rough face turning	conf	3	4.7701e-05	4.6395e-05	4.9006e-05	0.009
R_{sm}	ELLOR graphite; rough face turning	fusion	3	5.1115e-05	4.0749e-05	6.1481e-05	0.066
R_{sm}	ELLOR graphite; rough face turning	int	3	1.6152e-04	-1.3815e-04	4.6119e-04	0.483
R_{sm}	ELLOR graphite; finish wire EDM	FV	3	-6.7174e-06	-7.7603e-05	6.4168e-05	0.883
R_{sm}	ELLOR graphite; finish wire EDM	conf	3	5.6563e-05	3.7256e-05	7.5870e-05	0.11
R_{sm}	ELLOR graphite; finish wire EDM	fusion	3	3.0062e-05	2.9239e-05	3.0885e-05	0.009
R_{sm}	ELLOR graphite; finish wire EDM	int	2	5.4465e-05	—	—	—
R_{sm}	ELLOR graphite; rough wire EDM	FV	3	-3.1681e-06	-7.8321e-05	7.1984e-05	0.948
R_{sm}	ELLOR graphite; rough wire EDM	conf	3	4.7157e-05	4.1145e-05	5.3169e-05	0.041
R_{sm}	ELLOR graphite; rough wire EDM	fusion	3	3.1173e-05	2.9393e-05	3.2953e-05	0.019
R_{sm}	ELLOR graphite; rough wire EDM	int	3	4.0443e-04	1.5912e-05	7.9295e-04	0.29
R_{sm}	MO58A brass; burnishing after MF	FV	4	1.6270e-04	-2.4203e-04	5.6743e-04	0.513
R_{sm}	MO58A brass; burnishing after MF	conf	3	-3.1134e-06	-1.1168e-05	4.9416e-06	0.587
R_{sm}	MO58A brass; burnishing after MF	fusion	3	-4.2096e-06	-8.8506e-06	4.3138e-07	0.326
R_{sm}	MO58A brass; burnishing after MF	int	3	4.1506e-05	-8.7400e-05	1.7041e-04	0.642
R_{sm}	MO58A brass; glass bead blasting	FV	3	-1.5439e-05	-8.6110e-05	5.5233e-05	0.742
R_{sm}	MO58A brass; glass bead blasting	conf	3	2.7814e-05	-1.5462e-05	7.1090e-05	0.427
R_{sm}	MO58A brass; glass bead blasting	fusion	3	2.7247e-05	-3.4998e-05	8.9491e-05	0.549
R_{sm}	MO58A brass; glass bead blasting	int	3	1.2647e-05	-8.5357e-06	3.3830e-05	0.45
R_{sm}	MO58A brass; grinding	FV	3	3.4699e-06	-2.4550e-05	3.1490e-05	0.848
R_{sm}	MO58A brass; grinding	conf	3	1.7519e-05	3.4308e-06	3.1607e-05	0.248
R_{sm}	MO58A brass; grinding	fusion	3	2.6260e-05	1.2789e-06	5.1240e-05	0.288
R_{sm}	MO58A brass; grinding	int	3	1.4456e-04	-9.4574e-05	3.8370e-04	0.446
R_{sm}	MO58A brass; honing	FV	3	7.9138e-06	-1.5674e-05	3.1502e-05	0.63
R_{sm}	MO58A brass; honing	conf	3	2.5783e-05	-9.6978e-06	6.1263e-05	0.39
R_{sm}	MO58A brass; honing	fusion	3	2.0175e-05	-5.0866e-06	4.5437e-05	0.362
R_{sm}	MO58A brass; honing	int	3	1.6007e-04	-9.8972e-05	4.1912e-04	0.439
R_{sm}	MO58A brass; finish milling	FV	3	1.1512e-05	-2.8291e-05	5.1315e-05	0.672
R_{sm}	MO58A brass; finish milling	conf	3	-4.5155e-06	-1.2287e-05	3.2561e-06	0.459
R_{sm}	MO58A brass; finish milling	fusion	3	-1.4956e-05	-2.0693e-05	-9.2200e-06	0.123
R_{sm}	MO58A brass; finish milling	int	3	2.7569e-05	-5.1309e-05	1.0645e-04	0.618
R_{sm}	MO58A brass; rough milling	FV	3	-6.9944e-05	-1.0436e-04	-3.5531e-05	0.157
R_{sm}	MO58A brass; rough milling	conf	3	-9.9332e-05	-1.5905e-04	-3.9613e-05	0.189
R_{sm}	MO58A brass; rough milling	fusion	3	-1.0222e-04	-1.8916e-04	-1.5275e-05	0.261
R_{sm}	MO58A brass; rough milling	int	3	8.4138e-05	-0.0013	0.0014	0.923

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{sm}	MO58A brass; finish face turning	FV	3	-1.4192e-04	-2.9666e-04	1.2814e-05	0.323
R_{sm}	MO58A brass; finish face turning	conf	3	-4.2077e-05	-1.0154e-04	1.7383e-05	0.398
R_{sm}	MO58A brass; finish face turning	fusion	3	-3.3564e-05	-7.7029e-05	9.9003e-06	0.372
R_{sm}	MO58A brass; finish face turning	int	3	-1.1354e-04	-8.4749e-04	6.2041e-04	0.813
R_{sm}	MO58A brass; rough face turning	FV	3	-1.7479e-04	-4.5163e-04	1.0206e-04	0.433
R_{sm}	MO58A brass; rough face turning	conf	3	4.4524e-05	3.9409e-05	4.9639e-05	0.037
R_{sm}	MO58A brass; rough face turning	fusion	3	3.0397e-06	-1.9953e-05	2.6032e-05	0.839
R_{sm}	MO58A brass; rough face turning	int	3	-1.3111e-04	-8.6341e-04	6.0119e-04	0.785
R_{sm}	MO58A brass; finish wire EDM	FV	3	3.1675e-06	-2.6946e-05	3.3281e-05	0.871
R_{sm}	MO58A brass; finish wire EDM	conf	3	9.2796e-05	-3.4891e-05	2.2048e-04	0.39
R_{sm}	MO58A brass; finish wire EDM	fusion	3	4.4950e-05	-2.2702e-05	1.1260e-04	0.417
R_{sm}	MO58A brass; finish wire EDM	int	3	8.8569e-05	-9.3014e-05	2.7015e-04	0.514
R_{sm}	MO58A brass; rough wire EDM	FV	3	5.7309e-06	-3.7659e-05	4.9121e-05	0.839
R_{sm}	MO58A brass; rough wire EDM	conf	3	1.0026e-04	-6.7363e-06	2.0726e-04	0.317
R_{sm}	MO58A brass; rough wire EDM	fusion	3	1.1201e-04	-2.3644e-05	2.4766e-04	0.352
R_{sm}	MO58A brass; rough wire EDM	int	3	1.4004e-04	-1.3897e-04	4.1904e-04	0.505
R_{sm}	Ti6Al4V; burnishing after MF	FV	3	8.3011e-06	-1.0794e-05	2.7396e-05	0.551
R_{sm}	Ti6Al4V; burnishing after MF	conf	3	2.4206e-06	1.1248e-06	3.7165e-06	0.17
R_{sm}	Ti6Al4V; burnishing after MF	fusion	3	-9.6917e-06	-1.2761e-05	-6.6229e-06	0.102
R_{sm}	Ti6Al4V; burnishing after MF	int	3	2.9534e-05	-1.7666e-04	2.3573e-04	0.826
R_{sm}	Ti6Al4V; glass bead blasting	FV	3	-2.8982e-05	-5.3725e-05	-4.2384e-06	0.262
R_{sm}	Ti6Al4V; glass bead blasting	conf	3	-1.4612e-05	-2.1896e-05	-7.3280e-06	0.159
R_{sm}	Ti6Al4V; glass bead blasting	fusion	3	-1.4392e-05	-1.7571e-05	-1.1213e-05	0.071
R_{sm}	Ti6Al4V; glass bead blasting	int	3	-3.5188e-05	-1.9739e-04	1.2701e-04	0.744
R_{sm}	Ti6Al4V; grinding	FV	3	6.7044e-06	-2.6075e-05	3.9484e-05	0.757
R_{sm}	Ti6Al4V; grinding	conf	3	5.4823e-06	2.9861e-06	7.9786e-06	0.145
R_{sm}	Ti6Al4V; grinding	fusion	3	4.9708e-06	1.2128e-06	8.7288e-06	0.234
R_{sm}	Ti6Al4V; grinding	int	3	1.4076e-05	-3.5739e-05	6.3890e-05	0.678
R_{sm}	Ti6Al4V; honing	FV	3	2.0371e-06	-8.7755e-06	1.2850e-05	0.775
R_{sm}	Ti6Al4V; honing	conf	3	2.4355e-05	-1.4284e-05	6.2993e-05	0.433
R_{sm}	Ti6Al4V; honing	fusion	3	2.6122e-05	-9.9454e-06	6.2190e-05	0.391
R_{sm}	Ti6Al4V; honing	int	3	1.5782e-04	-5.2688e-05	3.6832e-04	0.38
R_{sm}	Ti6Al4V; finish milling	FV	3	-4.3090e-05	-9.3479e-05	7.2997e-06	0.342
R_{sm}	Ti6Al4V; finish milling	conf	3	-1.0715e-05	-1.3067e-05	-8.3626e-06	0.071
R_{sm}	Ti6Al4V; finish milling	fusion	3	-1.3265e-05	-1.4037e-05	-1.2492e-05	0.019
R_{sm}	Ti6Al4V; finish milling	int	3	2.5008e-05	-1.0326e-04	1.5328e-04	0.768
R_{sm}	Ti6Al4V; rough milling	FV	3	-1.0955e-04	-1.6009e-04	-5.9016e-05	0.147
R_{sm}	Ti6Al4V; rough milling	conf	3	-7.4649e-05	-1.7479e-04	2.5489e-05	0.382
R_{sm}	Ti6Al4V; rough milling	fusion	3	-6.7637e-05	-1.5738e-04	2.2109e-05	0.379
R_{sm}	Ti6Al4V; rough milling	int	3	1.4104e-04	-4.5490e-04	7.3698e-04	0.723
R_{sm}	Ti6Al4V; finish face turning	FV	3	-5.5539e-04	-9.8037e-04	-1.3040e-04	0.237
R_{sm}	Ti6Al4V; finish face turning	conf	3	-1.9783e-05	-7.9006e-05	3.9440e-05	0.631
R_{sm}	Ti6Al4V; finish face turning	fusion	3	-6.4675e-05	-1.1899e-04	-1.0358e-05	0.258
R_{sm}	Ti6Al4V; finish face turning	int	3	-2.1302e-04	-0.003	0.0026	0.906
R_{sm}	Ti6Al4V; rough face turning	FV	3	-1.6782e-04	-3.5325e-04	1.7602e-05	0.327
R_{sm}	Ti6Al4V; rough face turning	conf	3	-5.8361e-05	-7.2875e-05	-4.3847e-05	0.08
R_{sm}	Ti6Al4V; rough face turning	fusion	3	-5.4760e-05	-6.9135e-05	-4.0385e-05	0.085
R_{sm}	Ti6Al4V; rough face turning	int	3	-1.5737e-04	-9.5989e-04	6.4515e-04	0.766
R_{sm}	Ti6Al4V; finish wire EDM	FV	3	-4.1865e-07	-1.7033e-05	1.6196e-05	0.969
R_{sm}	Ti6Al4V; finish wire EDM	conf	3	3.5158e-06	-1.0457e-05	1.7488e-05	0.708
R_{sm}	Ti6Al4V; finish wire EDM	fusion	3	1.0592e-06	-1.1256e-05	1.3374e-05	0.894
R_{sm}	Ti6Al4V; finish wire EDM	int	3	3.5304e-05	-3.8598e-05	1.0921e-04	0.521
R_{sm}	Ti6Al4V; rough wire EDM	FV	3	2.1227e-05	1.1311e-05	3.1143e-05	0.149
R_{sm}	Ti6Al4V; rough wire EDM	conf	3	6.9699e-06	6.1152e-07	1.3328e-05	0.277
R_{sm}	Ti6Al4V; rough wire EDM	fusion	3	1.8118e-05	-4.7342e-06	4.0970e-05	0.364
R_{sm}	Ti6Al4V; rough wire EDM	int	3	2.9609e-04	-1.8257e-04	7.7475e-04	0.439
R_t	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.3608	-1.1114	0.3898	0.519
R_t	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.2787	0.2091	0.3482	0.081
R_t	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.2721	0.1113	0.4329	0.186
R_t	AISI 304 / EN 1.4301; burnishing after MF	int	3	-0.0702	-0.0965	-0.0439	0.12

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_t	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0067	-0.2503	0.2369	0.966
R_t	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.1211	0.0829	0.1593	0.102
R_t	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.2311	0.1608	0.3014	0.098
R_t	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0384	0.0366	0.0403	0.016
R_t	AISI 304 / EN 1.4301; grinding	FV	3	0.0757	-0.1706	0.322	0.655
R_t	AISI 304 / EN 1.4301; grinding	conf	3	0.0135	-0.0163	0.0434	0.537
R_t	AISI 304 / EN 1.4301; grinding	fusion	3	-0.0444	-0.1929	0.104	0.662
R_t	AISI 304 / EN 1.4301; grinding	int	3	0.0041	-0.0534	0.0617	0.911
R_t	AISI 304 / EN 1.4301; honing	FV	3	0.2373	0.1407	0.3339	0.13
R_t	AISI 304 / EN 1.4301; honing	conf	3	0.0375	-0.0398	0.1148	0.516
R_t	AISI 304 / EN 1.4301; honing	fusion	3	0.0873	0.0629	0.1118	0.09
R_t	AISI 304 / EN 1.4301; honing	int	3	-0.0588	-0.193	0.0754	0.548
R_t	AISI 304 / EN 1.4301; finish milling	FV	3	-0.2473	-0.5341	0.0394	0.34
R_t	AISI 304 / EN 1.4301; finish milling	conf	3	0.2308	0.187	0.2747	0.062
R_t	AISI 304 / EN 1.4301; finish milling	fusion	3	0.3271	0.2053	0.4489	0.12
R_t	AISI 304 / EN 1.4301; finish milling	int	3	-0.3132	-0.3195	-0.3068	0.007
R_t	AISI 304 / EN 1.4301; rough milling	FV	3	0.0795	-0.0377	0.1967	0.41
R_t	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0651	-0.0796	-0.0507	0.072
R_t	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0579	-0.0661	-0.0497	0.046
R_t	AISI 304 / EN 1.4301; rough milling	int	3	0.099	-0.4515	0.6495	0.784
R_t	AISI 304 / EN 1.4301; finish face turning	FV	3	0.2404	-0.0555	0.5363	0.357
R_t	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0141	-0.0158	-0.0125	0.038
R_t	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0222	-0.0238	-0.0207	0.023
R_t	AISI 304 / EN 1.4301; finish face turning	int	3	0.0415	-0.0927	0.1756	0.653
R_t	AISI 304 / EN 1.4301; rough face turning	FV	3	0.0849	-0.0397	0.2095	0.409
R_t	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0281	-0.04	-0.0163	0.135
R_t	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.052	-0.063	-0.0409	0.069
R_t	AISI 304 / EN 1.4301; rough face turning	int	3	-0.0301	-0.0347	-0.0255	0.049
R_t	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-0.0038	-0.0289	0.0214	0.818
R_t	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.241	0.2205	0.2615	0.028
R_t	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.0099	-0.5193	0.539	0.977
R_t	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0302	-0.1967	0.1363	0.783
R_t	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.003	-0.0123	0.0062	0.636
R_t	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0015	-0.0471	0.0501	0.962
R_t	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.2555	0.0529	0.458	0.245
R_t	AISI 304 / EN 1.4301; rough wire EDM	int	2	0.0184	—	—	—

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_t	Al7075; burnishing after MF	FV	3	-1.1391	-2.8574	0.5791	0.418
R_t	Al7075; burnishing after MF	conf	3	0.5344	0.265	0.8038	0.16
R_t	Al7075; burnishing after MF	fusion	3	0.6453	0.0849	1.2057	0.266
R_t	Al7075; burnishing after MF	int	3	2.5623	-2.1001	7.2247	0.476
R_t	Al7075; glass bead blasting	FV	3	-0.074	-0.2421	0.094	0.546
R_t	Al7075; glass bead blasting	conf	3	0.2268	0.1839	0.2698	0.061
R_t	Al7075; glass bead blasting	fusion	3	0.6439	-0.1625	1.4503	0.362
R_t	Al7075; glass bead blasting	int	3	-0.0276	-0.1096	0.0543	0.628
R_t	Al7075; grinding	FV	3	-0.0385	-0.2732	0.1962	0.802
R_t	Al7075; grinding	conf	3	-0.0769	-0.0799	-0.074	0.013
R_t	Al7075; grinding	fusion	3	-0.0584	-0.0761	-0.0408	0.097
R_t	Al7075; grinding	int	3	0.0123	-0.0403	0.0649	0.726
R_t	Al7075; honing	FV	3	-0.1338	-0.3102	0.0427	0.377
R_t	Al7075; honing	conf	3	-0.0776	-0.0953	-0.06	0.074
R_t	Al7075; honing	fusion	3	-0.0671	-0.0838	-0.0505	0.08
R_t	Al7075; honing	int	3	0.0158	-0.0188	0.0503	0.535
R_t	Al7075; finish milling	FV	3	-0.2693	-0.5456	0.007	0.307
R_t	Al7075; finish milling	conf	3	0.1258	0.0048	0.2468	0.29
R_t	Al7075; finish milling	fusion	3	0.2181	0.1819	0.2543	0.054
R_t	Al7075; finish milling	int	3	0.1274	-0.3165	0.5712	0.674
R_t	Al7075; rough milling	FV	3	-0.758	-1.5086	-0.0075	0.298
R_t	Al7075; rough milling	conf	3	0.1999	0.1941	0.2057	0.009
R_t	Al7075; rough milling	fusion	3	0.2395	0.1794	0.2995	0.081
R_t	Al7075; rough milling	int	3	0.3053	0.0012	0.6094	0.299
R_t	Al7075; finish face turning	FV	3	0.1114	-0.0533	0.2762	0.411
R_t	Al7075; finish face turning	conf	3	-0.0709	-0.0833	-0.0585	0.057
R_t	Al7075; finish face turning	fusion	3	-0.0796	-0.105	-0.0543	0.102
R_t	Al7075; finish face turning	int	3	-0.0147	-0.3052	0.2757	0.937
R_t	Al7075; rough face turning	FV	3	0.0694	-0.0402	0.179	0.432
R_t	Al7075; rough face turning	conf	3	-0.0626	-0.0715	-0.0537	0.046
R_t	Al7075; rough face turning	fusion	3	-0.0609	-0.0633	-0.0586	0.012
R_t	Al7075; rough face turning	int	3	0.0285	-0.0627	0.1196	0.65
R_t	Al7075; finish wire EDM	FV	3	-0.0726	-0.328	0.1828	0.676
R_t	Al7075; finish wire EDM	conf	3	0.0478	-0.2102	0.3059	0.778
R_t	Al7075; finish wire EDM	fusion	3	-0.2954	-0.9716	0.3808	0.549
R_t	Al7075; finish wire EDM	int	3	0.096	-0.0121	0.204	0.332
R_t	Al7075; rough wire EDM	FV	3	-0.0347	-0.0411	-0.0283	0.059
R_t	Al7075; rough wire EDM	conf	3	0.2629	0.1436	0.3823	0.145
R_t	Al7075; rough wire EDM	fusion	3	0.4197	0.04	0.7995	0.275
R_t	Al7075; rough wire EDM	int	3	-0.1216	-0.3021	0.0589	0.413
R_t	C45 steel; burnishing after MF	FV	3	-0.3872	-1.2727	0.4982	0.549
R_t	C45 steel; burnishing after MF	conf	2	0.4256	—	—	—
R_t	C45 steel; burnishing after MF	fusion	3	0.4559	0.3128	0.5989	0.101
R_t	C45 steel; burnishing after MF	int	4	-1.4389	-2.448	-0.4298	0.108
R_t	C45 steel; glass bead blasting	FV	3	-0.004	-0.1864	0.1785	0.973
R_t	C45 steel; glass bead blasting	conf	3	0.1943	0.1385	0.2501	0.093
R_t	C45 steel; glass bead blasting	fusion	3	0.3662	0.353	0.3794	0.012
R_t	C45 steel; glass bead blasting	int	3	-0.0061	-0.1557	0.1436	0.95
R_t	C45 steel; grinding	FV	3	0.162	-0.319	0.6429	0.629
R_t	C45 steel; grinding	conf	3	0.1616	0.1443	0.179	0.035
R_t	C45 steel; grinding	fusion	3	0.0967	0.0215	0.1719	0.241
R_t	C45 steel; grinding	int	3	0.0235	-0.0488	0.0959	0.639
R_t	C45 steel; honing	FV	3	0.118	-0.0998	0.3357	0.481
R_t	C45 steel; honing	conf	3	-0.0608	-0.1534	0.0317	0.42
R_t	C45 steel; honing	fusion	3	0.0958	0.0332	0.1584	0.205
R_t	C45 steel; honing	int	3	-0.0731	-0.2306	0.0845	0.53
R_t	C45 steel; finish milling	FV	3	0.0097	-0.0555	0.0749	0.82
R_t	C45 steel; finish milling	conf	2	0.0685	—	—	—
R_t	C45 steel; finish milling	fusion	3	0.1024	0.0735	0.1313	0.091
R_t	C45 steel; finish milling	int	3	0.1173	0.0755	0.1592	0.115
R_t	C45 steel; rough milling	FV	3	0.006	-0.0368	0.0487	0.83
R_t	C45 steel; rough milling	conf	2	-0.0568	—	—	—
R_t	C45 steel; rough milling	fusion	3	-0.0633	-0.0656	-0.061	0.012
R_t	C45 steel; rough milling	int	3	0.0429	-0.016	0.1018	0.389

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_t	C45 steel; finish face turning	FV	3	0.0031	-0.0236	0.0297	0.859
R_t	C45 steel; finish face turning	conf	2	-0.0242	—	—	—
R_t	C45 steel; finish face turning	fusion	3	-0.0314	-0.0362	-0.0266	0.049
R_t	C45 steel; finish face turning	int	3	0.0173	-0.01	0.0446	0.432
R_t	C45 steel; rough face turning	FV	3	0.0139	-0.0118	0.0396	0.482
R_t	C45 steel; rough face turning	conf	2	-0.0092	—	—	—
R_t	C45 steel; rough face turning	fusion	3	-0.0125	-0.0137	-0.0112	0.032
R_t	C45 steel; rough face turning	int	3	0.0116	-0.019	0.0422	0.594
R_t	C45 steel; finish wire EDM	FV	3	0.0801	-0.128	0.2882	0.588
R_t	C45 steel; finish wire EDM	conf	3	0.2843	0.1132	0.4553	0.19
R_t	C45 steel; finish wire EDM	fusion	3	-0.4149	-1.1745	0.3447	0.478
R_t	C45 steel; finish wire EDM	int	3	-0.0301	-0.1534	0.0933	0.716
R_t	C45 steel; rough wire EDM	FV	3	-0.0127	-0.028	0.0027	0.352
R_t	C45 steel; rough wire EDM	conf	3	0.0151	-0.0297	0.06	0.629
R_t	C45 steel; rough wire EDM	fusion	3	0.3759	0.3511	0.4007	0.021
R_t	C45 steel; rough wire EDM	int	3	-0.0959	-0.2448	0.0529	0.426
R_t	ELLOR graphite; glass bead blasting	FV	3	0.0089	0.0014	0.0164	0.258
R_t	ELLOR graphite; glass bead blasting	conf	3	-0.0076	-0.0421	0.0268	0.739
R_t	ELLOR graphite; glass bead blasting	fusion	3	0.0021	-0.0022	0.0064	0.521
R_t	ELLOR graphite; glass bead blasting	int	3	-0.0094	-0.0274	0.0086	0.493
R_t	ELLOR graphite; grinding	FV	3	-0.008	-0.0274	0.0114	0.566
R_t	ELLOR graphite; grinding	conf	3	0.0295	0.0087	0.0502	0.22
R_t	ELLOR graphite; grinding	fusion	3	0.0666	0.0456	0.0876	0.101
R_t	ELLOR graphite; grinding	int	3	-0.2395	-0.7406	0.2615	0.521
R_t	ELLOR graphite; honing	FV	3	0.1194	-0.1567	0.3955	0.552
R_t	ELLOR graphite; honing	conf	3	-0.0786	-0.0863	-0.0709	0.032
R_t	ELLOR graphite; honing	fusion	3	0.1703	0.0183	0.3223	0.272
R_t	ELLOR graphite; honing	int	3	0.0614	-0.1293	0.252	0.642
R_t	ELLOR graphite; finish milling	FV	3	0.0363	-0.0023	0.0749	0.316
R_t	ELLOR graphite; finish milling	conf	3	0.0064	-0.0047	0.0176	0.461
R_t	ELLOR graphite; finish milling	fusion	3	0.4737	0.0821	0.8654	0.254
R_t	ELLOR graphite; finish milling	int	3	-0.3435	-0.8579	0.1709	0.415
R_t	ELLOR graphite; rough milling	FV	3	0.0176	-0.0164	0.0516	0.495
R_t	ELLOR graphite; rough milling	conf	3	0.0236	0.0184	0.0288	0.071
R_t	ELLOR graphite; rough milling	fusion	3	0.0576	0.0194	0.0957	0.207
R_t	ELLOR graphite; rough milling	int	3	-0.353	-0.855	0.1491	0.4
R_t	ELLOR graphite; finish face turning	FV	3	0.0137	-0.0057	0.0332	0.399
R_t	ELLOR graphite; finish face turning	conf	3	-0.0096	-0.0162	-0.003	0.215
R_t	ELLOR graphite; finish face turning	fusion	3	0.0397	-0.0104	0.0897	0.364
R_t	ELLOR graphite; finish face turning	int	3	-0.2522	-0.6499	0.1454	0.431
R_t	ELLOR graphite; rough face turning	FV	3	0.0043	-0.0059	0.0144	0.561
R_t	ELLOR graphite; rough face turning	conf	3	-0.0066	-0.0071	-0.006	0.026
R_t	ELLOR graphite; rough face turning	fusion	3	-0.0214	-0.0379	-0.0049	0.239
R_t	ELLOR graphite; rough face turning	int	3	-0.173	-0.4258	0.0797	0.408
R_t	ELLOR graphite; finish wire EDM	FV	3	-0.0199	-0.0757	0.0359	0.612
R_t	ELLOR graphite; finish wire EDM	conf	3	-0.0266	-0.0685	0.0153	0.431
R_t	ELLOR graphite; finish wire EDM	fusion	3	0.0348	-0.0049	0.0744	0.335
R_t	ELLOR graphite; finish wire EDM	int	2	0.0507	—	—	—
R_t	ELLOR graphite; rough wire EDM	FV	3	0.011	-0.0063	0.0282	0.432
R_t	ELLOR graphite; rough wire EDM	conf	3	-0.0167	-0.0374	0.004	0.36
R_t	ELLOR graphite; rough wire EDM	fusion	3	0.0155	-0.012	0.0431	0.468
R_t	ELLOR graphite; rough wire EDM	int	3	-0.4477	-0.9351	0.0398	0.323

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_t	MO58A brass; burnishing after MF	FV	4	-1.0479	-3.327	1.2312	0.463
R_t	MO58A brass; burnishing after MF	conf	3	0.3589	0.1159	0.602	0.212
R_t	MO58A brass; burnishing after MF	fusion	3	0.4664	0.0159	0.9169	0.291
R_t	MO58A brass; burnishing after MF	int	3	3.6702	-1.4095	8.75	0.391
R_t	MO58A brass; glass bead blasting	FV	3	0.1056	-0.0601	0.2713	0.43
R_t	MO58A brass; glass bead blasting	conf	3	0.3662	0.2329	0.4996	0.117
R_t	MO58A brass; glass bead blasting	fusion	3	0.912	0.8802	0.9438	0.011
R_t	MO58A brass; glass bead blasting	int	3	0.008	-0.0395	0.0555	0.796
R_t	MO58A brass; grinding	FV	3	0.2003	0.0339	0.3666	0.255
R_t	MO58A brass; grinding	conf	3	0.0958	0.0729	0.1187	0.077
R_t	MO58A brass; grinding	fusion	3	0.0381	-0.0183	0.0944	0.412
R_t	MO58A brass; grinding	int	3	-5.5005e-04	-0.0547	0.0536	0.987
R_t	MO58A brass; honing	FV	3	0.0949	-0.0939	0.2836	0.505
R_t	MO58A brass; honing	conf	3	-0.0985	-0.1809	-0.016	0.257
R_t	MO58A brass; honing	fusion	3	0.1141	0.0467	0.1815	0.186
R_t	MO58A brass; honing	int	3	-0.0518	-0.1629	0.0593	0.529
R_t	MO58A brass; finish milling	FV	3	-0.5163	-1.6044	0.5717	0.523
R_t	MO58A brass; finish milling	conf	3	0.2979	0.2493	0.3465	0.053
R_t	MO58A brass; finish milling	fusion	3	0.5014	0.2093	0.7936	0.184
R_t	MO58A brass; finish milling	int	3	0.5798	-0.1487	1.3084	0.363
R_t	MO58A brass; rough milling	FV	3	0.2297	-0.0644	0.5238	0.368
R_t	MO58A brass; rough milling	conf	3	-0.0278	-0.0613	0.0057	0.351
R_t	MO58A brass; rough milling	fusion	3	-0.0467	-0.0563	-0.0371	0.067
R_t	MO58A brass; rough milling	int	3	0.0753	-0.0644	0.2151	0.482
R_t	MO58A brass; finish face turning	FV	3	0.0137	-0.0424	0.0698	0.716
R_t	MO58A brass; finish face turning	conf	3	-0.0309	-0.0369	-0.0249	0.063
R_t	MO58A brass; finish face turning	fusion	3	-0.0396	-0.0403	-0.0388	0.006
R_t	MO58A brass; finish face turning	int	3	0.0144	-0.0173	0.046	0.537
R_t	MO58A brass; rough face turning	FV	3	0.0278	-0.0815	0.137	0.706
R_t	MO58A brass; rough face turning	conf	3	-0.0439	-0.0515	-0.0362	0.056
R_t	MO58A brass; rough face turning	fusion	3	-0.0418	-0.0802	-0.0035	0.279
R_t	MO58A brass; rough face turning	int	3	0.017	-0.0543	0.0883	0.721
R_t	MO58A brass; finish wire EDM	FV	3	0.0327	-0.2122	0.2775	0.837
R_t	MO58A brass; finish wire EDM	conf	3	0.1429	0.0775	0.2083	0.146
R_t	MO58A brass; finish wire EDM	fusion	3	0.2448	0.143	0.3465	0.133
R_t	MO58A brass; finish wire EDM	int	3	-3.8266e-04	-0.064	0.0632	0.992
R_t	MO58A brass; rough wire EDM	FV	3	-0.0289	-0.0371	-0.0208	0.091
R_t	MO58A brass; rough wire EDM	conf	3	-0.1331	-0.2597	-0.0066	0.287
R_t	MO58A brass; rough wire EDM	fusion	3	0.0036	-0.2267	0.2339	0.98
R_t	MO58A brass; rough wire EDM	int	3	-0.0545	-0.1527	0.0438	0.474
R_t	Ti6Al4V; burnishing after MF	FV	3	-0.4833	-1.0558	0.0892	0.346
R_t	Ti6Al4V; burnishing after MF	conf	3	0.4406	0.3848	0.4963	0.041
R_t	Ti6Al4V; burnishing after MF	fusion	3	0.4097	0.3817	0.4377	0.022
R_t	Ti6Al4V; burnishing after MF	int	3	-0.2759	-1.2924	0.7405	0.689
R_t	Ti6Al4V; glass bead blasting	FV	3	-0.0718	-0.2419	0.0983	0.56
R_t	Ti6Al4V; glass bead blasting	conf	3	0.1375	0.1176	0.1573	0.047
R_t	Ti6Al4V; glass bead blasting	fusion	3	0.3878	0.2859	0.4896	0.085
R_t	Ti6Al4V; glass bead blasting	int	3	0.0094	-0.064	0.0828	0.844
R_t	Ti6Al4V; grinding	FV	3	-0.0495	-0.289	0.19	0.755
R_t	Ti6Al4V; grinding	conf	3	0.1561	0.1338	0.1783	0.046
R_t	Ti6Al4V; grinding	fusion	3	0.0979	0.0127	0.183	0.266
R_t	Ti6Al4V; grinding	int	3	-0.0376	-0.1757	0.1004	0.688
R_t	Ti6Al4V; honing	FV	3	0.2278	-0.047	0.5026	0.351
R_t	Ti6Al4V; honing	conf	3	0.1684	0.1093	0.2275	0.113
R_t	Ti6Al4V; honing	fusion	3	0.0968	0.0828	0.1109	0.047
R_t	Ti6Al4V; honing	int	3	0.0205	-0.0562	0.0972	0.693
R_t	Ti6Al4V; finish milling	FV	3	-0.1943	-0.513	0.1245	0.444
R_t	Ti6Al4V; finish milling	conf	3	0.2042	0.1415	0.2668	0.099
R_t	Ti6Al4V; finish milling	fusion	3	0.2324	0.1915	0.2733	0.057
R_t	Ti6Al4V; finish milling	int	3	0.0279	-0.1656	0.2213	0.825

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_t	Ti6Al4V; rough milling	FV	3	0.115	-0.0843	0.3144	0.461
R_t	Ti6Al4V; rough milling	conf	3	-0.0717	-0.0778	-0.0656	0.028
R_t	Ti6Al4V; rough milling	fusion	3	-0.0836	-0.1012	-0.0661	0.068
R_t	Ti6Al4V; rough milling	int	3	-0.0644	-0.5418	0.4129	0.835
R_t	Ti6Al4V; finish face turning	FV	3	-0.0092	-0.1384	0.12	0.912
R_t	Ti6Al4V; finish face turning	conf	3	-0.118	-0.1224	-0.1136	0.012
R_t	Ti6Al4V; finish face turning	fusion	3	-0.0851	-0.1131	-0.0571	0.106
R_t	Ti6Al4V; finish face turning	int	3	0.0531	-0.2497	0.3559	0.789
R_t	Ti6Al4V; rough face turning	FV	3	-0.0658	-0.0961	-0.0355	0.147
R_t	Ti6Al4V; rough face turning	conf	3	-0.1249	-0.1729	-0.0769	0.123
R_t	Ti6Al4V; rough face turning	fusion	3	-0.112	-0.1435	-0.0806	0.091
R_t	Ti6Al4V; rough face turning	int	3	0.0684	-0.0592	0.196	0.484
R_t	Ti6Al4V; finish wire EDM	FV	3	0.1426	-0.1398	0.425	0.503
R_t	Ti6Al4V; finish wire EDM	conf	3	0.2659	0.2061	0.3257	0.073
R_t	Ti6Al4V; finish wire EDM	fusion	3	0.2817	0.1709	0.3925	0.126
R_t	Ti6Al4V; finish wire EDM	int	3	0.0818	-0.0493	0.2128	0.436
R_t	Ti6Al4V; rough wire EDM	FV	3	-0.0215	-0.0249	-0.0181	0.051
R_t	Ti6Al4V; rough wire EDM	conf	3	0.3111	0.1429	0.4794	0.171
R_t	Ti6Al4V; rough wire EDM	fusion	3	0.4457	-0.0353	0.9267	0.32
R_t	Ti6Al4V; rough wire EDM	int	3	-0.0907	-0.2331	0.0517	0.43
R_v	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.9571	-2.3744	0.4603	0.412
R_v	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.3358	0.2449	0.4266	0.087
R_v	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.5421	0.361	0.7232	0.107
R_v	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.0509	-0.7554	0.8571	0.922
R_v	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.096	-0.1397	-0.0522	0.145
R_v	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.4034	0.25	0.5568	0.122
R_v	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.6488	0.4724	0.8252	0.088
R_v	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0367	0.0047	0.0688	0.266
R_v	AISI 304 / EN 1.4301; grinding	FV	3	-0.0218	-0.0868	0.0431	0.629
R_v	AISI 304 / EN 1.4301; grinding	conf	3	0.0801	0.0795	0.0807	0.002
R_v	AISI 304 / EN 1.4301; grinding	fusion	3	0.1447	0.0877	0.2017	0.126
R_v	AISI 304 / EN 1.4301; grinding	int	3	-0.0223	-0.0515	0.0069	0.375
R_v	AISI 304 / EN 1.4301; honing	FV	3	0.3577	0.2002	0.5153	0.141
R_v	AISI 304 / EN 1.4301; honing	conf	3	0.367	0.1645	0.5695	0.175
R_v	AISI 304 / EN 1.4301; honing	fusion	3	0.435	0.1052	0.7648	0.235
R_v	AISI 304 / EN 1.4301; honing	int	3	-0.0187	-0.0411	0.0036	0.348
R_v	AISI 304 / EN 1.4301; finish milling	FV	3	-0.5557	-1.5439	0.4325	0.469
R_v	AISI 304 / EN 1.4301; finish milling	conf	3	0.5153	0.4126	0.618	0.065
R_v	AISI 304 / EN 1.4301; finish milling	fusion	3	0.8009	0.4388	1.1631	0.144
R_v	AISI 304 / EN 1.4301; finish milling	int	3	-0.5233	-1.9921	0.9456	0.612
R_v	AISI 304 / EN 1.4301; rough milling	FV	3	0.1047	-0.0315	0.2409	0.373
R_v	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0604	-0.075	-0.0458	0.078
R_v	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.064	-0.0829	-0.0452	0.095
R_v	AISI 304 / EN 1.4301; rough milling	int	3	0.0165	-0.5438	0.5768	0.963
R_v	AISI 304 / EN 1.4301; finish face turning	FV	3	-0.6386	-1.6036	0.3265	0.418
R_v	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0315	-0.0402	-0.0228	0.089

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_v	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0484	-0.0591	-0.0376	0.072
R_v	AISI 304 / EN 1.4301; finish face turning	int	3	0.1052	-0.271	0.4815	0.681
R_v	AISI 304 / EN 1.4301; rough face turning	FV	3	0.1746	-0.0417	0.3909	0.359
R_v	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0464	-0.0691	-0.0236	0.156
R_v	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.0666	-0.1041	-0.029	0.179
R_v	AISI 304 / EN 1.4301; rough face turning	int	3	0.0631	-0.1457	0.272	0.66
R_v	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-0.051	-0.2218	0.1199	0.663
R_v	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.2426	0.1966	0.2885	0.061
R_v	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.4547	0.3554	0.554	0.071
R_v	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0063	-0.072	0.0594	0.882
R_v	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0137	-0.0423	0.0149	0.521
R_v	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0886	0.0823	0.0949	0.023
R_v	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.3144	0.2581	0.3708	0.058
R_v	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0064	—	—	—
R_v	Al7075; burnishing after MF	FV	3	-2.2936	-5.4238	0.8366	0.387
R_v	Al7075; burnishing after MF	conf	3	0.5254	0.1772	0.8737	0.208
R_v	Al7075; burnishing after MF	fusion	3	0.853	0.2873	1.4187	0.208
R_v	Al7075; burnishing after MF	int	3	3.2614	-2.7549	9.2777	0.481
R_v	Al7075; glass bead blasting	FV	3	-0.0014	-0.0795	0.0767	0.977
R_v	Al7075; glass bead blasting	conf	3	0.5182	0.3303	0.7061	0.116
R_v	Al7075; glass bead blasting	fusion	3	0.6301	0.393	0.8673	0.121
R_v	Al7075; glass bead blasting	int	3	-0.0387	-0.1257	0.0484	0.544
R_v	Al7075; grinding	FV	3	-0.0599	-0.3449	0.2251	0.751
R_v	Al7075; grinding	conf	3	0.1949	0.1538	0.236	0.068
R_v	Al7075; grinding	fusion	3	0.2591	0.1424	0.3758	0.144
R_v	Al7075; grinding	int	3	-0.0095	-0.0113	-0.0076	0.062
R_v	Al7075; honing	FV	3	0.0358	-0.1485	0.2201	0.768
R_v	Al7075; honing	conf	3	-0.1364	-0.2037	-0.0691	0.157
R_v	Al7075; honing	fusion	3	-0.083	-0.2747	0.1086	0.552
R_v	Al7075; honing	int	3	0.0015	-0.0355	0.0385	0.95
R_v	Al7075; finish milling	FV	3	-1.6646	-3.9272	0.598	0.386
R_v	Al7075; finish milling	conf	3	0.4457	0.2924	0.599	0.111
R_v	Al7075; finish milling	fusion	3	0.6277	0.4273	0.8281	0.103
R_v	Al7075; finish milling	int	3	1.4825	-1.6831	4.6481	0.527
R_v	Al7075; rough milling	FV	3	-1.1907	-2.247	-0.1344	0.271
R_v	Al7075; rough milling	conf	3	0.2298	0.1935	0.2661	0.051
R_v	Al7075; rough milling	fusion	3	0.3204	0.1962	0.4446	0.124
R_v	Al7075; rough milling	int	3	0.5865	-0.1871	1.36	0.377
R_v	Al7075; finish face turning	FV	3	0.0349	0.0347	0.0351	0.002
R_v	Al7075; finish face turning	conf	3	-0.137	-0.1833	-0.0906	0.109
R_v	Al7075; finish face turning	fusion	3	0.0406	-0.081	0.1621	0.631
R_v	Al7075; finish face turning	int	3	-0.0586	-0.603	0.4858	0.868
R_v	Al7075; rough face turning	FV	3	0.0746	-0.0394	0.1886	0.422
R_v	Al7075; rough face turning	conf	3	-0.0401	-0.0413	-0.0389	0.01
R_v	Al7075; rough face turning	fusion	3	-0.0496	-0.0562	-0.0429	0.044
R_v	Al7075; rough face turning	int	3	0.055	-0.0957	0.2057	0.605
R_v	Al7075; finish wire EDM	FV	3	-0.1044	-0.3949	0.186	0.609
R_v	Al7075; finish wire EDM	conf	3	0.242	0.2032	0.2808	0.052
R_v	Al7075; finish wire EDM	fusion	3	0.3443	0.327	0.3616	0.016
R_v	Al7075; finish wire EDM	int	3	-0.0353	-0.04	-0.0306	0.043

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_v	Al7075; rough wire EDM	FV	3	-0.0489	-0.0574	-0.0405	0.056
R_v	Al7075; rough wire EDM	conf	3	0.6551	0.4942	0.816	0.079
R_v	Al7075; rough wire EDM	fusion	3	0.7428	0.379	1.1066	0.156
R_v	Al7075; rough wire EDM	int	3	-0.1058	-0.2569	0.0452	0.401
R_v	C45 steel; burnishing after MF	FV	3	-0.7171	-1.9022	0.4681	0.446
R_v	C45 steel; burnishing after MF	conf	2	0.506	—	—	—
R_v	C45 steel; burnishing after MF	fusion	3	0.7175	0.6351	0.7999	0.037
R_v	C45 steel; burnishing after MF	int	4	-1.5739	-2.6296	-0.5182	0.1
R_v	C45 steel; glass bead blasting	FV	3	-0.0592	-0.1575	0.039	0.447
R_v	C45 steel; glass bead blasting	conf	3	0.4689	0.2801	0.6578	0.129
R_v	C45 steel; glass bead blasting	fusion	3	0.7179	0.5053	0.9306	0.095
R_v	C45 steel; glass bead blasting	int	3	-0.0085	-0.0416	0.0247	0.705
R_v	C45 steel; grinding	FV	3	-0.0724	-0.4267	0.2818	0.757
R_v	C45 steel; grinding	conf	3	0.2111	0.1195	0.3028	0.139
R_v	C45 steel; grinding	fusion	3	0.2597	0.1272	0.3922	0.162
R_v	C45 steel; grinding	int	3	0.0037	-0.0102	0.0176	0.694
R_v	C45 steel; honing	FV	3	0.2767	0.127	0.4264	0.171
R_v	C45 steel; honing	conf	3	0.2857	0.1411	0.4304	0.161
R_v	C45 steel; honing	fusion	3	0.3115	0.0178	0.6051	0.285
R_v	C45 steel; honing	int	3	-0.0307	-0.0883	0.0269	0.486
R_v	C45 steel; finish milling	FV	3	0.0273	-0.1001	0.1546	0.747
R_v	C45 steel; finish milling	conf	2	0.1425	—	—	—
R_v	C45 steel; finish milling	fusion	3	0.264	0.1482	0.3798	0.14
R_v	C45 steel; finish milling	int	3	0.0034	-0.0281	0.0348	0.869
R_v	C45 steel; rough milling	FV	3	0.0324	-0.0561	0.1208	0.604
R_v	C45 steel; rough milling	conf	2	-0.0888	—	—	—
R_v	C45 steel; rough milling	fusion	3	-0.1447	-0.1926	-0.0969	0.106
R_v	C45 steel; rough milling	int	3	0.0746	-0.0536	0.2028	0.458
R_v	C45 steel; finish face turning	FV	3	0.0035	-0.0381	0.0451	0.895
R_v	C45 steel; finish face turning	conf	2	-0.0492	—	—	—
R_v	C45 steel; finish face turning	fusion	3	-0.0833	-0.1229	-0.0437	0.151
R_v	C45 steel; finish face turning	int	3	0.0382	-0.0271	0.1034	0.457
R_v	C45 steel; rough face turning	FV	3	0.0578	-0.0133	0.129	0.357
R_v	C45 steel; rough face turning	conf	2	-0.0161	—	—	—
R_v	C45 steel; rough face turning	fusion	3	-0.0324	-0.0472	-0.0177	0.145
R_v	C45 steel; rough face turning	int	3	0.0225	-0.0759	0.1209	0.731
R_v	C45 steel; finish wire EDM	FV	3	0.144	-0.1192	0.4072	0.478
R_v	C45 steel; finish wire EDM	conf	3	0.1919	0.0468	0.3369	0.234
R_v	C45 steel; finish wire EDM	fusion	3	0.2222	0.0723	0.3721	0.211
R_v	C45 steel; finish wire EDM	int	3	-0.0278	-0.066	0.0105	0.39
R_v	C45 steel; rough wire EDM	FV	3	-0.0396	-0.0567	-0.0225	0.138
R_v	C45 steel; rough wire EDM	conf	3	0.1138	0.06	0.1676	0.151
R_v	C45 steel; rough wire EDM	fusion	3	0.8423	0.6497	1.0349	0.074
R_v	C45 steel; rough wire EDM	int	3	-0.1475	-0.3394	0.0443	0.373
R_v	ELLOR graphite; glass bead blasting	FV	3	0.005	0.002	0.0081	0.192
R_v	ELLOR graphite; glass bead blasting	conf	3	0.0097	-0.0216	0.0411	0.652
R_v	ELLOR graphite; glass bead blasting	fusion	3	0.0249	0.0165	0.0333	0.108
R_v	ELLOR graphite; glass bead blasting	int	3	-0.0676	-0.1447	0.0094	0.335
R_v	ELLOR graphite; grinding	FV	3	-0.0282	-0.0434	-0.013	0.171
R_v	ELLOR graphite; grinding	conf	3	0.0228	0.0225	0.0232	0.005
R_v	ELLOR graphite; grinding	fusion	3	0.0819	0.069	0.0949	0.051
R_v	ELLOR graphite; grinding	int	3	0.64	0.0969	1.1832	0.26
R_v	ELLOR graphite; honing	FV	3	-0.2753	-0.6462	0.0957	0.383
R_v	ELLOR graphite; honing	conf	3	0.4588	0.4371	0.4805	0.015
R_v	ELLOR graphite; honing	fusion	3	0.6764	0.6372	0.7156	0.019
R_v	ELLOR graphite; honing	int	3	-0.0442	-0.0865	-0.0019	0.289
R_v	ELLOR graphite; finish milling	FV	3	0.0953	0.0558	0.1347	0.132
R_v	ELLOR graphite; finish milling	conf	3	-0.004	-0.028	0.0201	0.801
R_v	ELLOR graphite; finish milling	fusion	3	0.3578	-0.022	0.7377	0.316
R_v	ELLOR graphite; finish milling	int	3	-0.3759	-0.8444	0.0927	0.361

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_v	ELLOR graphite; rough milling	FV	3	-0.024	-0.0585	0.0105	0.402
R_v	ELLOR graphite; rough milling	conf	3	0.0164	-8.3670e-04	0.0336	0.313
R_v	ELLOR graphite; rough milling	fusion	3	0.0745	0.0646	0.0845	0.043
R_v	ELLOR graphite; rough milling	int	3	-0.2598	-0.5778	0.0581	0.355
R_v	ELLOR graphite; finish face turning	FV	3	0.0291	-0.0016	0.0598	0.314
R_v	ELLOR graphite; finish face turning	conf	3	0.0045	-0.0206	0.0295	0.786
R_v	ELLOR graphite; finish face turning	fusion	3	0.0881	0.0733	0.103	0.054
R_v	ELLOR graphite; finish face turning	int	3	-0.3265	-0.7191	0.0662	0.35
R_v	ELLOR graphite; rough face turning	FV	3	-0.0044	-0.0105	0.0017	0.394
R_v	ELLOR graphite; rough face turning	conf	3	0.0044	9.3514e-04	0.0078	0.243
R_v	ELLOR graphite; rough face turning	fusion	3	0.0253	0.0063	0.0443	0.233
R_v	ELLOR graphite; rough face turning	int	3	-0.1677	-0.3881	0.0527	0.376
R_v	ELLOR graphite; finish wire EDM	FV	3	-0.0363	-0.0849	0.0124	0.382
R_v	ELLOR graphite; finish wire EDM	conf	3	0.0035	-0.0054	0.0125	0.581
R_v	ELLOR graphite; finish wire EDM	fusion	3	0.0533	0.0413	0.0653	0.073
R_v	ELLOR graphite; finish wire EDM	int	2	0.0978	—	—	—
R_v	ELLOR graphite; rough wire EDM	FV	3	-0.0129	-0.0338	0.0079	0.438
R_v	ELLOR graphite; rough wire EDM	conf	3	0.0263	-0.0154	0.0681	0.433
R_v	ELLOR graphite; rough wire EDM	fusion	3	0.0499	0.0245	0.0753	0.162
R_v	ELLOR graphite; rough wire EDM	int	3	-0.0083	-0.3598	0.3433	0.971
R_v	MO58A brass; burnishing after MF	FV	4	-2.4182	-6.0487	1.2122	0.322
R_v	MO58A brass; burnishing after MF	conf	3	0.5103	0.2816	0.739	0.143
R_v	MO58A brass; burnishing after MF	fusion	3	0.9483	0.6013	1.2953	0.117
R_v	MO58A brass; burnishing after MF	int	3	3.7458	-1.1772	8.6688	0.376
R_v	MO58A brass; glass bead blasting	FV	3	0.1009	-0.0503	0.2521	0.415
R_v	MO58A brass; glass bead blasting	conf	3	0.7582	0.3713	1.1451	0.162
R_v	MO58A brass; glass bead blasting	fusion	3	1.1518	0.8816	1.422	0.076
R_v	MO58A brass; glass bead blasting	int	3	0.0801	-0.0578	0.2179	0.459
R_v	MO58A brass; grinding	FV	3	0.0893	-0.0187	0.1972	0.352
R_v	MO58A brass; grinding	conf	3	0.1599	0.0877	0.2322	0.144
R_v	MO58A brass; grinding	fusion	3	0.2061	0.1296	0.2826	0.119
R_v	MO58A brass; grinding	int	3	0.0414	-0.0734	0.1562	0.609
R_v	MO58A brass; honing	FV	3	0.1302	0.0452	0.2151	0.205
R_v	MO58A brass; honing	conf	3	0.2591	0.105	0.4133	0.188
R_v	MO58A brass; honing	fusion	3	0.366	0.075	0.657	0.245
R_v	MO58A brass; honing	int	3	-0.0348	-0.0886	0.0191	0.426
R_v	MO58A brass; finish milling	FV	3	-1.5277	-3.6335	0.5781	0.39
R_v	MO58A brass; finish milling	conf	3	0.4021	0.3102	0.494	0.074
R_v	MO58A brass; finish milling	fusion	3	0.6977	0.6443	0.7512	0.025
R_v	MO58A brass; finish milling	int	3	1.1738	-0.0447	2.3923	0.31
R_v	MO58A brass; rough milling	FV	3	0.2739	-0.0722	0.62	0.365
R_v	MO58A brass; rough milling	conf	3	-0.0632	-0.0676	-0.0588	0.023
R_v	MO58A brass; rough milling	fusion	3	-0.0901	-0.1074	-0.0729	0.062
R_v	MO58A brass; rough milling	int	3	0.0684	-0.1033	0.2402	0.578
R_v	MO58A brass; finish face turning	FV	3	0.0543	-0.0388	0.1474	0.458
R_v	MO58A brass; finish face turning	conf	3	-0.0615	-0.0682	-0.0547	0.036
R_v	MO58A brass; finish face turning	fusion	3	-0.0887	-0.1083	-0.0691	0.072
R_v	MO58A brass; finish face turning	int	3	0.0239	-0.0405	0.0883	0.6
R_v	MO58A brass; rough face turning	FV	3	0.0551	-0.0511	0.1614	0.495
R_v	MO58A brass; rough face turning	conf	3	-0.0797	-0.0941	-0.0653	0.058
R_v	MO58A brass; rough face turning	fusion	3	-0.1105	-0.1566	-0.0644	0.133
R_v	MO58A brass; rough face turning	int	3	0.0192	-0.0696	0.1079	0.745

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_v	MO58A brass; finish wire EDM	FV	3	-0.0285	-0.174	0.117	0.767
R_v	MO58A brass; finish wire EDM	conf	3	0.2878	0.1753	0.4003	0.125
R_v	MO58A brass; finish wire EDM	fusion	3	0.3089	0.252	0.3657	0.06
R_v	MO58A brass; finish wire EDM	int	3	-0.0121	-0.0793	0.055	0.783
R_v	MO58A brass; rough wire EDM	FV	3	-0.0575	-0.0738	-0.0411	0.092
R_v	MO58A brass; rough wire EDM	conf	3	0.074	-0.0861	0.2341	0.531
R_v	MO58A brass; rough wire EDM	fusion	3	0.2598	0.0898	0.4298	0.205
R_v	MO58A brass; rough wire EDM	int	3	-0.0523	-0.1284	0.0239	0.407
R_v	Ti6Al4V; burnishing after MF	FV	3	-0.7462	-1.424	-0.0684	0.276
R_v	Ti6Al4V; burnishing after MF	conf	3	0.3679	0.3279	0.4079	0.035
R_v	Ti6Al4V; burnishing after MF	fusion	3	0.3396	0.3338	0.3454	0.006
R_v	Ti6Al4V; burnishing after MF	int	3	-0.1588	-0.2494	-0.0682	0.18
R_v	Ti6Al4V; glass bead blasting	FV	3	0.0646	-0.1834	0.3126	0.7
R_v	Ti6Al4V; glass bead blasting	conf	3	0.4986	0.3153	0.682	0.118
R_v	Ti6Al4V; glass bead blasting	fusion	3	0.8463	0.7678	0.9248	0.03
R_v	Ti6Al4V; glass bead blasting	int	3	-0.0035	-0.1372	0.1301	0.967
R_v	Ti6Al4V; grinding	FV	3	-0.1517	-0.5025	0.199	0.552
R_v	Ti6Al4V; grinding	conf	3	0.3438	0.2236	0.4639	0.112
R_v	Ti6Al4V; grinding	fusion	3	0.4845	0.287	0.682	0.131
R_v	Ti6Al4V; grinding	int	3	-0.0789	-0.1791	0.0213	0.366
R_v	Ti6Al4V; honing	FV	3	0.14	-0.3228	0.6028	0.659
R_v	Ti6Al4V; honing	conf	3	0.505	0.1803	0.8297	0.202
R_v	Ti6Al4V; honing	fusion	3	0.5926	0.0608	1.1244	0.273
R_v	Ti6Al4V; honing	int	3	-0.0263	-0.0659	0.0133	0.417
R_v	Ti6Al4V; finish milling	FV	3	-0.4047	-1.0527	0.2433	0.436
R_v	Ti6Al4V; finish milling	conf	3	0.4211	0.2566	0.5857	0.125
R_v	Ti6Al4V; finish milling	fusion	3	0.5027	0.3422	0.6633	0.103
R_v	Ti6Al4V; finish milling	int	3	-0.0177	-0.201	0.1656	0.881
R_v	Ti6Al4V; rough milling	FV	3	-0.1281	-0.3405	0.0843	0.447
R_v	Ti6Al4V; rough milling	conf	3	0.0547	-0.0829	0.1922	0.579
R_v	Ti6Al4V; rough milling	fusion	3	0.2237	0.1901	0.2572	0.049
R_v	Ti6Al4V; rough milling	int	3	0.1726	-0.1009	0.4461	0.433
R_v	Ti6Al4V; finish face turning	FV	3	0.0129	-0.1109	0.1366	0.872
R_v	Ti6Al4V; finish face turning	conf	3	0.0638	-0.109	0.2366	0.601
R_v	Ti6Al4V; finish face turning	fusion	3	0.2244	0.214	0.2348	0.015
R_v	Ti6Al4V; finish face turning	int	3	-0.1089	-0.2972	0.0793	0.46
R_v	Ti6Al4V; rough face turning	FV	3	5.0872e-04	-0.0506	0.0516	0.988
R_v	Ti6Al4V; rough face turning	conf	3	-0.1299	-0.1822	-0.0776	0.129
R_v	Ti6Al4V; rough face turning	fusion	3	-0.1573	-0.2385	-0.076	0.164
R_v	Ti6Al4V; rough face turning	int	3	0.1043	-0.0836	0.2922	0.473
R_v	Ti6Al4V; finish wire EDM	FV	3	0.0792	-0.3244	0.4828	0.766
R_v	Ti6Al4V; finish wire EDM	conf	3	0.3766	0.2129	0.5402	0.139
R_v	Ti6Al4V; finish wire EDM	fusion	3	0.4648	0.2212	0.7083	0.166
R_v	Ti6Al4V; finish wire EDM	int	3	-0.0312	-0.0755	0.0131	0.399
R_v	Ti6Al4V; rough wire EDM	FV	3	-0.0409	-0.0496	-0.0322	0.069
R_v	Ti6Al4V; rough wire EDM	conf	3	0.5411	0.4048	0.6774	0.081
R_v	Ti6Al4V; rough wire EDM	fusion	3	0.9132	0.2176	1.6089	0.236
R_v	Ti6Al4V; rough wire EDM	int	3	-0.1249	-0.3115	0.0617	0.415
R_z	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.7442	-2.1786	0.6901	0.495
R_z	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.4829	0.3315	0.6343	0.101
R_z	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.5715	0.2841	0.859	0.16
R_z	AISI 304 / EN 1.4301; burnishing after MF	int	3	0.1956	-1.5752	1.9664	0.864
R_z	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0267	-0.1016	0.0482	0.612
R_z	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.1503	0.1125	0.1881	0.081
R_z	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.2149	0.1661	0.2636	0.073
R_z	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0554	-0.0168	0.1276	0.374

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_z	AISI 304 / EN 1.4301; grinding	FV	3	0.0273	-0.2411	0.2957	0.875
R_z	AISI 304 / EN 1.4301; grinding	conf	3	0.0556	0.0258	0.0854	0.17
R_z	AISI 304 / EN 1.4301; grinding	fusion	3	-0.0254	-0.1944	0.1437	0.818
R_z	AISI 304 / EN 1.4301; grinding	int	3	-0.0015	-0.068	0.065	0.972
R_z	AISI 304 / EN 1.4301; honing	FV	3	0.2842	0.1737	0.3947	0.125
R_z	AISI 304 / EN 1.4301; honing	conf	3	0.1742	0.0992	0.2491	0.138
R_z	AISI 304 / EN 1.4301; honing	fusion	3	0.0945	0.0763	0.1126	0.062
R_z	AISI 304 / EN 1.4301; honing	int	3	-0.0487	-0.1969	0.0994	0.635
R_z	AISI 304 / EN 1.4301; finish milling	FV	3	-0.3649	-1.0602	0.3304	0.491
R_z	AISI 304 / EN 1.4301; finish milling	conf	3	0.3701	0.3141	0.426	0.049
R_z	AISI 304 / EN 1.4301; finish milling	fusion	3	0.545	0.3464	0.7437	0.117
R_z	AISI 304 / EN 1.4301; finish milling	int	3	-0.5521	-2.0428	0.9387	0.6
R_z	AISI 304 / EN 1.4301; rough milling	FV	3	0.0683	-0.0261	0.1627	0.391
R_z	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0575	-0.0666	-0.0485	0.051
R_z	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0567	-0.0659	-0.0475	0.053
R_z	AISI 304 / EN 1.4301; rough milling	int	3	0.0208	-0.4749	0.5166	0.948
R_z	AISI 304 / EN 1.4301; finish face turning	FV	3	0.0027	-0.0673	0.0728	0.951
R_z	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.024	-0.031	-0.0169	0.095
R_z	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0351	-0.0449	-0.0254	0.089
R_z	AISI 304 / EN 1.4301; finish face turning	int	3	0.0787	-0.2075	0.3648	0.685
R_z	AISI 304 / EN 1.4301; rough face turning	FV	3	0.1194	-0.0378	0.2765	0.377
R_z	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0273	-0.0393	-0.0154	0.14
R_z	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.042	-0.0596	-0.0243	0.134
R_z	AISI 304 / EN 1.4301; rough face turning	int	3	0.0381	-0.1219	0.198	0.722
R_z	AISI 304 / EN 1.4301; finish wire EDM	FV	3	-0.0073	-0.3068	0.2923	0.97
R_z	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.2851	0.2455	0.3248	0.045
R_z	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	0.1161	-0.2527	0.4849	0.648
R_z	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0283	-0.1884	0.1318	0.788
R_z	AISI 304 / EN 1.4301; rough wire EDM	FV	3	0.004	-0.0134	0.0214	0.729
R_z	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0555	0.0467	0.0643	0.052
R_z	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.1721	0.1144	0.2298	0.108
R_z	AISI 304 / EN 1.4301; rough wire EDM	int	2	-0.0217	—	—	—
R_z	Al7075; burnishing after MF	FV	3	-1.4718	-3.7816	0.838	0.43
R_z	Al7075; burnishing after MF	conf	3	0.5609	0.1782	0.9435	0.213
R_z	Al7075; burnishing after MF	fusion	3	0.7305	0.1288	1.3322	0.253
R_z	Al7075; burnishing after MF	int	3	3.5453	-3.0219	10.1126	0.482
R_z	Al7075; glass bead blasting	FV	3	-0.0061	-0.1049	0.0927	0.923
R_z	Al7075; glass bead blasting	conf	3	0.2821	0.2091	0.3551	0.084
R_z	Al7075; glass bead blasting	fusion	3	0.4499	0.102	0.7977	0.239
R_z	Al7075; glass bead blasting	int	3	-0.0139	-0.0742	0.0463	0.729

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_z	Al7075; grinding	FV	3	-0.0046	-0.4167	0.4076	0.986
R_z	Al7075; grinding	conf	3	0.1564	0.1473	0.1655	0.019
R_z	Al7075; grinding	fusion	3	0.1508	0.1459	0.1556	0.01
R_z	Al7075; grinding	int	3	0.0058	-0.1036	0.1152	0.935
R_z	Al7075; honing	FV	3	-0.0861	-0.2983	0.126	0.572
R_z	Al7075; honing	conf	3	-0.0969	-0.1294	-0.0645	0.108
R_z	Al7075; honing	fusion	3	-0.0981	-0.1203	-0.076	0.073
R_z	Al7075; honing	int	3	0.0081	-0.0392	0.0555	0.793
R_z	Al7075; finish milling	FV	3	-0.7356	-1.9605	0.4894	0.448
R_z	Al7075; finish milling	conf	3	0.4731	0.4396	0.5067	0.023
R_z	Al7075; finish milling	fusion	3	0.5101	0.4328	0.5874	0.049
R_z	Al7075; finish milling	int	3	1.0799	-0.8181	2.9779	0.465
R_z	Al7075; rough milling	FV	3	-0.9359	-1.7623	-0.1095	0.269
R_z	Al7075; rough milling	conf	3	0.1927	0.1782	0.2071	0.024
R_z	Al7075; rough milling	fusion	3	0.2395	0.147	0.332	0.124
R_z	Al7075; rough milling	int	3	0.5718	-0.1197	1.2633	0.352
R_z	Al7075; finish face turning	FV	3	0.1356	-0.0436	0.3148	0.378
R_z	Al7075; finish face turning	conf	3	-0.1226	-0.1606	-0.0847	0.1
R_z	Al7075; finish face turning	fusion	3	-0.0369	-0.2063	0.1326	0.743
R_z	Al7075; finish face turning	int	3	-0.0776	-0.6048	0.4497	0.821
R_z	Al7075; rough face turning	FV	3	0.0612	-0.0261	0.1485	0.4
R_z	Al7075; rough face turning	conf	3	-0.0305	-0.0308	-0.0302	0.003
R_z	Al7075; rough face turning	fusion	3	-0.0323	-0.0327	-0.0319	0.004
R_z	Al7075; rough face turning	int	3	0.0474	-0.0762	0.171	0.59
R_z	Al7075; finish wire EDM	FV	3	-0.0778	-0.3738	0.2182	0.697
R_z	Al7075; finish wire EDM	conf	3	0.0953	-0.1671	0.3577	0.606
R_z	Al7075; finish wire EDM	fusion	3	-0.0461	-0.5211	0.429	0.88
R_z	Al7075; finish wire EDM	int	3	-0.0505	-0.1405	0.0394	0.469
R_z	Al7075; rough wire EDM	FV	3	-0.0428	-0.0512	-0.0345	0.063
R_z	Al7075; rough wire EDM	conf	3	0.2995	0.181	0.4179	0.127
R_z	Al7075; rough wire EDM	fusion	3	0.4127	0.0865	0.7389	0.244
R_z	Al7075; rough wire EDM	int	3	-0.0204	-0.0607	0.0199	0.502
R_z	C45 steel; burnishing after MF	FV	3	-0.4705	-1.5929	0.6519	0.562
R_z	C45 steel; burnishing after MF	conf	2	0.5632	—	—	—
R_z	C45 steel; burnishing after MF	fusion	3	0.5938	0.3971	0.7905	0.107
R_z	C45 steel; burnishing after MF	int	4	-2.2247	-4.2263	-0.2231	0.161
R_z	C45 steel; glass bead blasting	FV	3	-0.01	-0.1386	0.1186	0.904
R_z	C45 steel; glass bead blasting	conf	3	0.236	0.1662	0.3058	0.095
R_z	C45 steel; glass bead blasting	fusion	3	0.3519	0.3033	0.4005	0.045
R_z	C45 steel; glass bead blasting	int	3	9.5479e-04	-0.0317	0.0336	0.964
R_z	C45 steel; grinding	FV	3	0.0692	-0.4836	0.6219	0.847
R_z	C45 steel; grinding	conf	3	0.1775	0.1371	0.218	0.074
R_z	C45 steel; grinding	fusion	3	0.1565	0.1419	0.171	0.03
R_z	C45 steel; grinding	int	3	-0.0131	-0.0311	0.0049	0.389
R_z	C45 steel; honing	FV	3	0.2588	0.1313	0.3863	0.157
R_z	C45 steel; honing	conf	3	0.156	0.0881	0.2239	0.139
R_z	C45 steel; honing	fusion	3	0.1257	0.0615	0.1899	0.162
R_z	C45 steel; honing	int	3	-0.0605	-0.2277	0.1067	0.607
R_z	C45 steel; finish milling	FV	3	0.0386	-0.0616	0.1388	0.588
R_z	C45 steel; finish milling	conf	2	0.135	—	—	—
R_z	C45 steel; finish milling	fusion	3	0.1746	0.1577	0.1915	0.031
R_z	C45 steel; finish milling	int	3	0.0166	-0.0478	0.0811	0.701
R_z	C45 steel; rough milling	FV	3	0.0181	-0.0491	0.0854	0.69
R_z	C45 steel; rough milling	conf	2	-0.0588	—	—	—
R_z	C45 steel; rough milling	fusion	3	-0.0678	-0.0712	-0.0644	0.016
R_z	C45 steel; rough milling	int	3	0.0605	-0.0356	0.1566	0.434
R_z	C45 steel; finish face turning	FV	3	7.9557e-04	-0.0422	0.0438	0.977
R_z	C45 steel; finish face turning	conf	2	-0.0368	—	—	—
R_z	C45 steel; finish face turning	fusion	3	-0.0496	-0.0608	-0.0384	0.073
R_z	C45 steel; finish face turning	int	3	0.0347	-0.021	0.0904	0.437
R_z	C45 steel; rough face turning	FV	3	0.0422	-0.0183	0.1027	0.402
R_z	C45 steel; rough face turning	conf	2	-0.015	—	—	—
R_z	C45 steel; rough face turning	fusion	3	-0.0243	-0.0326	-0.016	0.11
R_z	C45 steel; rough face turning	int	3	0.0205	-0.0725	0.1135	0.74

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_z	C45 steel; finish wire EDM	FV	3	0.0989	-0.1179	0.3156	0.536
R_z	C45 steel; finish wire EDM	conf	3	0.3755	0.1333	0.6178	0.202
R_z	C45 steel; finish wire EDM	fusion	3	-0.0558	-0.3578	0.2462	0.779
R_z	C45 steel; finish wire EDM	int	3	-0.036	-0.1373	0.0653	0.613
R_z	C45 steel; rough wire EDM	FV	3	-0.0082	-0.0314	0.0149	0.613
R_z	C45 steel; rough wire EDM	conf	3	0.0639	0.0425	0.0853	0.108
R_z	C45 steel; rough wire EDM	fusion	3	0.4084	0.3889	0.4279	0.016
R_z	C45 steel; rough wire EDM	int	3	-0.116	-0.257	0.025	0.353
R_z	ELLOR graphite; glass bead blasting	FV	3	-0.011	-0.0234	0.0014	0.333
R_z	ELLOR graphite; glass bead blasting	conf	3	0.0172	-0.0067	0.041	0.393
R_z	ELLOR graphite; glass bead blasting	fusion	3	0.0242	0.0031	0.0454	0.267
R_z	ELLOR graphite; glass bead blasting	int	3	0.0839	-0.0527	0.2205	0.441
R_z	ELLOR graphite; grinding	FV	3	-0.0162	-0.0781	0.0458	0.699
R_z	ELLOR graphite; grinding	conf	3	0.0636	0.0456	0.0816	0.091
R_z	ELLOR graphite; grinding	fusion	3	0.11	0.1033	0.1168	0.02
R_z	ELLOR graphite; grinding	int	3	0.1729	0.0435	0.3024	0.232
R_z	ELLOR graphite; honing	FV	3	-0.2742	-0.9086	0.3602	0.553
R_z	ELLOR graphite; honing	conf	3	0.3476	0.2159	0.4794	0.122
R_z	ELLOR graphite; honing	fusion	3	0.3945	0.0691	0.7198	0.254
R_z	ELLOR graphite; honing	int	3	-0.208	-0.311	-0.1051	0.157
R_z	ELLOR graphite; finish milling	FV	3	0.0587	-0.0287	0.1461	0.414
R_z	ELLOR graphite; finish milling	conf	3	0.0189	-0.0047	0.0425	0.361
R_z	ELLOR graphite; finish milling	fusion	3	0.3567	0.0834	0.63	0.237
R_z	ELLOR graphite; finish milling	int	3	-0.3223	-0.7565	0.1119	0.383
R_z	ELLOR graphite; rough milling	FV	3	-0.026	-0.0729	0.0209	0.473
R_z	ELLOR graphite; rough milling	conf	3	0.0501	0.0311	0.0691	0.121
R_z	ELLOR graphite; rough milling	fusion	3	0.0803	0.0547	0.1059	0.103
R_z	ELLOR graphite; rough milling	int	3	-0.221	-0.4997	0.0578	0.364
R_z	ELLOR graphite; finish face turning	FV	3	0.0168	-0.0303	0.0639	0.612
R_z	ELLOR graphite; finish face turning	conf	3	0.0378	0.0252	0.0504	0.107
R_z	ELLOR graphite; finish face turning	fusion	3	0.0875	0.0565	0.1185	0.114
R_z	ELLOR graphite; finish face turning	int	3	-0.2554	-0.5586	0.0479	0.347
R_z	ELLOR graphite; rough face turning	FV	3	0.0078	-0.0072	0.0227	0.493
R_z	ELLOR graphite; rough face turning	conf	3	0.0132	0.0078	0.0185	0.13
R_z	ELLOR graphite; rough face turning	fusion	3	0.0254	0.001	0.0498	0.29
R_z	ELLOR graphite; rough face turning	int	3	-0.2448	-0.5779	0.0883	0.386
R_z	ELLOR graphite; finish wire EDM	FV	3	-0.0327	-0.0998	0.0345	0.515
R_z	ELLOR graphite; finish wire EDM	conf	3	0.0295	0.0251	0.0339	0.049
R_z	ELLOR graphite; finish wire EDM	fusion	3	0.0642	0.0447	0.0836	0.098
R_z	ELLOR graphite; finish wire EDM	int	2	0.0936	—	—	—
R_z	ELLOR graphite; rough wire EDM	FV	3	-0.0193	-0.0671	0.0284	0.573
R_z	ELLOR graphite; rough wire EDM	conf	3	0.0393	0.0121	0.0664	0.216
R_z	ELLOR graphite; rough wire EDM	fusion	3	0.0549	0.0501	0.0597	0.028
R_z	ELLOR graphite; rough wire EDM	int	3	-0.3581	-1.1852	0.4691	0.552
R_z	MO58A brass; burnishing after MF	FV	4	-1.6634	-4.9151	1.5883	0.422
R_z	MO58A brass; burnishing after MF	conf	3	0.3893	-0.087	0.8656	0.355
R_z	MO58A brass; burnishing after MF	fusion	3	0.553	-0.1602	1.2662	0.37
R_z	MO58A brass; burnishing after MF	int	3	4.5665	-1.4804	10.6133	0.378

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_z	MO58A brass; glass bead blasting	FV	3	0.105	-0.0528	0.2629	0.416
R_z	MO58A brass; glass bead blasting	conf	3	0.4203	0.2196	0.621	0.152
R_z	MO58A brass; glass bead blasting	fusion	3	0.743	0.589	0.8969	0.067
R_z	MO58A brass; glass bead blasting	int	3	0.0544	-0.0621	0.171	0.528
R_z	MO58A brass; grinding	FV	3	0.1746	-0.0528	0.402	0.373
R_z	MO58A brass; grinding	conf	3	0.1194	0.0837	0.1552	0.096
R_z	MO58A brass; grinding	fusion	3	0.047	-0.0393	0.1333	0.48
R_z	MO58A brass; grinding	int	3	0.0286	-0.0548	0.112	0.623
R_z	MO58A brass; honing	FV	3	0.2267	0.0955	0.3579	0.183
R_z	MO58A brass; honing	conf	3	0.154	0.0718	0.2362	0.169
R_z	MO58A brass; honing	fusion	3	0.1381	0.071	0.2053	0.155
R_z	MO58A brass; honing	int	3	-0.0498	-0.1791	0.0794	0.588
R_z	MO58A brass; finish milling	FV	3	-0.9528	-2.7788	0.8733	0.493
R_z	MO58A brass; finish milling	conf	3	0.5582	0.4995	0.617	0.034
R_z	MO58A brass; finish milling	fusion	3	0.729	0.4476	1.0104	0.124
R_z	MO58A brass; finish milling	int	3	1.3995	-0.7137	3.5127	0.418
R_z	MO58A brass; rough milling	FV	3	0.2453	-0.0699	0.5604	0.369
R_z	MO58A brass; rough milling	conf	3	-0.024	-0.0488	8.9358e-04	0.31
R_z	MO58A brass; rough milling	fusion	3	-0.0114	-0.0577	0.035	0.715
R_z	MO58A brass; rough milling	int	3	0.0687	-0.1159	0.2534	0.599
R_z	MO58A brass; finish face turning	FV	3	0.0367	-0.0473	0.1206	0.549
R_z	MO58A brass; finish face turning	conf	3	-0.0318	-0.0387	-0.0248	0.071
R_z	MO58A brass; finish face turning	fusion	3	-0.0328	-0.0536	-0.012	0.2
R_z	MO58A brass; finish face turning	int	3	0.0291	-0.0332	0.0914	0.528
R_z	MO58A brass; rough face turning	FV	3	0.0423	-0.0668	0.1514	0.587
R_z	MO58A brass; rough face turning	conf	3	-0.0496	-0.0506	-0.0485	0.007
R_z	MO58A brass; rough face turning	fusion	3	-0.0254	-0.0772	0.0264	0.512
R_z	MO58A brass; rough face turning	int	3	0.0177	-0.0706	0.1061	0.761
R_z	MO58A brass; finish wire EDM	FV	3	0.0246	-0.2428	0.292	0.886
R_z	MO58A brass; finish wire EDM	conf	3	0.1988	0.1827	0.215	0.026
R_z	MO58A brass; finish wire EDM	fusion	3	0.2979	0.2389	0.3569	0.064
R_z	MO58A brass; finish wire EDM	int	3	0.0099	-0.0471	0.067	0.791
R_z	MO58A brass; rough wire EDM	FV	3	-0.038	-0.0464	-0.0296	0.072
R_z	MO58A brass; rough wire EDM	conf	3	-0.0565	-0.2897	0.1767	0.718
R_z	MO58A brass; rough wire EDM	fusion	3	0.0596	-0.1635	0.2827	0.693
R_z	MO58A brass; rough wire EDM	int	3	-0.0741	-0.201	0.0527	0.457
R_z	Ti6Al4V; burnishing after MF	FV	3	-0.5875	-1.2422	0.0673	0.329
R_z	Ti6Al4V; burnishing after MF	conf	3	0.5174	0.4729	0.5618	0.028
R_z	Ti6Al4V; burnishing after MF	fusion	3	0.4762	0.4583	0.4941	0.012
R_z	Ti6Al4V; burnishing after MF	int	3	-0.1922	-0.9699	0.5856	0.713
R_z	Ti6Al4V; glass bead blasting	FV	3	0.1001	-0.0118	0.212	0.33
R_z	Ti6Al4V; glass bead blasting	conf	3	0.194	0.1623	0.2257	0.053
R_z	Ti6Al4V; glass bead blasting	fusion	3	0.3633	0.3136	0.4129	0.044
R_z	Ti6Al4V; glass bead blasting	int	3	0.0342	0.0262	0.0422	0.076
R_z	Ti6Al4V; grinding	FV	3	-0.1336	-0.5658	0.2986	0.653
R_z	Ti6Al4V; grinding	conf	3	0.2697	0.2233	0.3161	0.056
R_z	Ti6Al4V; grinding	fusion	3	0.2541	0.2132	0.2949	0.052
R_z	Ti6Al4V; grinding	int	3	-0.0455	-0.2797	0.1886	0.768
R_z	Ti6Al4V; honing	FV	3	0.2802	-0.1011	0.6615	0.386
R_z	Ti6Al4V; honing	conf	3	0.2555	0.1406	0.3704	0.144
R_z	Ti6Al4V; honing	fusion	3	0.2003	0.1524	0.2483	0.077
R_z	Ti6Al4V; honing	int	3	-0.0224	-0.082	0.0372	0.596
R_z	Ti6Al4V; finish milling	FV	3	-0.2506	-0.6986	0.1974	0.471
R_z	Ti6Al4V; finish milling	conf	3	0.2223	0.1669	0.2776	0.081
R_z	Ti6Al4V; finish milling	fusion	3	0.2317	0.1942	0.2692	0.052
R_z	Ti6Al4V; finish milling	int	3	-0.0067	-0.2068	0.1933	0.958
R_z	Ti6Al4V; rough milling	FV	3	-0.018	-0.0207	-0.0152	0.05
R_z	Ti6Al4V; rough milling	conf	3	-0.0741	-0.1159	-0.0323	0.178
R_z	Ti6Al4V; rough milling	fusion	3	0.1373	0.1301	0.1446	0.017
R_z	Ti6Al4V; rough milling	int	3	0.1549	-0.3369	0.6466	0.648
R_z	Ti6Al4V; finish face turning	FV	3	0.0241	-0.1182	0.1664	0.796
R_z	Ti6Al4V; finish face turning	conf	3	-0.0359	-0.1247	0.053	0.574
R_z	Ti6Al4V; finish face turning	fusion	3	0.1197	0.0924	0.1471	0.074
R_z	Ti6Al4V; finish face turning	int	3	0.0079	-0.271	0.2869	0.965

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_z	Ti6Al4V; rough face turning	FV	3	-0.0257	-0.0524	9.8472e-04	0.31
R_z	Ti6Al4V; rough face turning	conf	3	-0.0743	-0.099	-0.0496	0.107
R_z	Ti6Al4V; rough face turning	fusion	3	-0.0713	-0.0938	-0.0488	0.102
R_z	Ti6Al4V; rough face turning	int	3	0.0724	-0.0522	0.1971	0.459
R_z	Ti6Al4V; finish wire EDM	FV	3	0.1548	-0.184	0.4936	0.535
R_z	Ti6Al4V; finish wire EDM	conf	3	0.3121	0.217	0.4072	0.098
R_z	Ti6Al4V; finish wire EDM	fusion	3	0.3554	0.31	0.4008	0.041
R_z	Ti6Al4V; finish wire EDM	int	3	0.1047	-0.0663	0.2757	0.442
R_z	Ti6Al4V; rough wire EDM	FV	3	-0.0186	-0.0216	-0.0155	0.054
R_z	Ti6Al4V; rough wire EDM	conf	3	0.2571	0.2072	0.3071	0.063
R_z	Ti6Al4V; rough wire EDM	fusion	3	0.5324	0.0537	1.011	0.274
R_z	Ti6Al4V; rough wire EDM	int	3	-0.101	-0.2305	0.0285	0.369
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	-0.3745	-1.1413	0.3923	0.514
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	0.261	0.1957	0.3264	0.081
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	0.2636	0.1188	0.4085	0.174
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	int	3	-0.0467	-0.1413	0.048	0.511
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	-0.0145	-0.264	0.2349	0.928
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	0.1182	0.0851	0.1514	0.09
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	0.2039	0.1462	0.2615	0.091
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	int	3	0.0382	0.0187	0.0576	0.162
R_{z1max}	AISI 304 / EN 1.4301; grinding	FV	3	0.0845	-0.1731	0.342	0.636
R_{z1max}	AISI 304 / EN 1.4301; grinding	conf	3	0.0525	0.021	0.084	0.189
R_{z1max}	AISI 304 / EN 1.4301; grinding	fusion	3	-0.0495	-0.2302	0.1312	0.686
R_{z1max}	AISI 304 / EN 1.4301; grinding	int	3	-3.9763e-04	-0.058	0.0572	0.991
R_{z1max}	AISI 304 / EN 1.4301; honing	FV	3	0.2374	0.1308	0.3439	0.143
R_{z1max}	AISI 304 / EN 1.4301; honing	conf	3	0.0411	-0.0328	0.1151	0.473
R_{z1max}	AISI 304 / EN 1.4301; honing	fusion	3	0.0821	0.0746	0.0896	0.03
R_{z1max}	AISI 304 / EN 1.4301; honing	int	3	-0.0649	-0.201	0.0712	0.521
R_{z1max}	AISI 304 / EN 1.4301; finish milling	FV	3	-0.2554	-0.7143	0.2036	0.472
R_{z1max}	AISI 304 / EN 1.4301; finish milling	conf	3	0.2518	0.1966	0.3071	0.071
R_{z1max}	AISI 304 / EN 1.4301; finish milling	fusion	3	0.3611	0.2239	0.4983	0.122
R_{z1max}	AISI 304 / EN 1.4301; finish milling	int	3	-0.3563	-0.4938	-0.2188	0.124
R_{z1max}	AISI 304 / EN 1.4301; rough milling	FV	3	0.0752	-0.0369	0.1874	0.414
R_{z1max}	AISI 304 / EN 1.4301; rough milling	conf	3	-0.0633	-0.076	-0.0505	0.065
R_{z1max}	AISI 304 / EN 1.4301; rough milling	fusion	3	-0.0554	-0.0601	-0.0507	0.028
R_{z1max}	AISI 304 / EN 1.4301; rough milling	int	3	0.0906	-0.4241	0.6052	0.788
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	FV	3	0.2478	-0.0542	0.5497	0.354
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	conf	3	-0.0157	-0.0176	-0.0139	0.037
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	fusion	3	-0.0245	-0.0254	-0.0235	0.013
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	int	3	0.0378	-0.0907	0.1664	0.667
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	FV	3	0.072	-0.0386	0.1825	0.423
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	conf	3	-0.0252	-0.0396	-0.0108	0.181

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	fusion	3	-0.0522	-0.0665	-0.038	0.088
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	int	3	-0.0347	-0.0362	-0.0333	0.014
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	0.0037	-0.1218	0.1293	0.963
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	0.2584	0.2218	0.2949	0.046
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	-0.0041	-0.5645	0.5563	0.991
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	int	3	-0.0289	-0.201	0.1431	0.797
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	-0.0018	-0.0097	0.0062	0.737
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	0.0018	-0.0472	0.0507	0.955
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	0.2234	0.0748	0.372	0.208
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	int	2	0.0175	—	—	—
R_{z1max}	Al7075; burnishing after MF	FV	3	-1.2197	-3.0972	0.6579	0.424
R_{z1max}	Al7075; burnishing after MF	conf	3	0.5448	0.2146	0.8749	0.191
R_{z1max}	Al7075; burnishing after MF	fusion	3	0.6446	0.0636	1.2255	0.274
R_{z1max}	Al7075; burnishing after MF	int	3	2.5971	-2.2275	7.4217	0.483
R_{z1max}	Al7075; glass bead blasting	FV	3	-0.0774	-0.2586	0.1038	0.556
R_{z1max}	Al7075; glass bead blasting	conf	3	0.2553	0.2054	0.3052	0.063
R_{z1max}	Al7075; glass bead blasting	fusion	3	0.6507	-0.2319	1.5334	0.385
R_{z1max}	Al7075; glass bead blasting	int	3	-0.0287	-0.1123	0.0549	0.623
R_{z1max}	Al7075; grinding	FV	3	-0.0326	-0.2682	0.2029	0.831
R_{z1max}	Al7075; grinding	conf	3	-0.0745	-0.075	-0.074	0.002
R_{z1max}	Al7075; grinding	fusion	3	-0.061	-0.0808	-0.0412	0.104
R_{z1max}	Al7075; grinding	int	3	0.0105	-0.0404	0.0614	0.755
R_{z1max}	Al7075; honing	FV	3	-0.1352	-0.3061	0.0356	0.364
R_{z1max}	Al7075; honing	conf	3	-0.0858	-0.1093	-0.0622	0.089
R_{z1max}	Al7075; honing	fusion	3	-0.072	-0.0824	-0.0615	0.047
R_{z1max}	Al7075; honing	int	3	0.011	-0.0183	0.0402	0.597
R_{z1max}	Al7075; finish milling	FV	3	-0.2929	-0.6209	0.0351	0.33
R_{z1max}	Al7075; finish milling	conf	3	0.1438	0.0501	0.2376	0.204
R_{z1max}	Al7075; finish milling	fusion	3	0.2194	0.1841	0.2548	0.052
R_{z1max}	Al7075; finish milling	int	3	0.1749	-0.2529	0.6027	0.57
R_{z1max}	Al7075; rough milling	FV	3	-0.7677	-1.5253	-0.0101	0.297
R_{z1max}	Al7075; rough milling	conf	3	0.1805	0.177	0.184	0.006
R_{z1max}	Al7075; rough milling	fusion	3	0.2286	0.1941	0.2632	0.049
R_{z1max}	Al7075; rough milling	int	3	0.2547	-0.0086	0.518	0.309
R_{z1max}	Al7075; finish face turning	FV	3	0.1085	-0.051	0.2679	0.41
R_{z1max}	Al7075; finish face turning	conf	3	-0.0711	-0.0857	-0.0564	0.067
R_{z1max}	Al7075; finish face turning	fusion	3	-0.0819	-0.1105	-0.0532	0.113
R_{z1max}	Al7075; finish face turning	int	3	-0.0136	-0.2931	0.2659	0.939
R_{z1max}	Al7075; rough face turning	FV	3	0.0519	-0.0378	0.1416	0.46
R_{z1max}	Al7075; rough face turning	conf	3	-0.0639	-0.0766	-0.0511	0.065
R_{z1max}	Al7075; rough face turning	fusion	3	-0.0612	-0.0667	-0.0557	0.029
R_{z1max}	Al7075; rough face turning	int	3	0.0271	-0.0643	0.1185	0.665
R_{z1max}	Al7075; finish wire EDM	FV	3	-0.0761	-0.341	0.1888	0.673
R_{z1max}	Al7075; finish wire EDM	conf	3	0.0547	-0.2077	0.317	0.753
R_{z1max}	Al7075; finish wire EDM	fusion	3	-0.2776	-0.9725	0.4174	0.577
R_{z1max}	Al7075; finish wire EDM	int	3	0.0952	-0.016	0.2064	0.342
R_{z1max}	Al7075; rough wire EDM	FV	3	-0.0342	-0.0418	-0.0265	0.072
R_{z1max}	Al7075; rough wire EDM	conf	3	0.2806	0.1822	0.3791	0.113
R_{z1max}	Al7075; rough wire EDM	fusion	3	0.3694	0.0436	0.6952	0.269
R_{z1max}	Al7075; rough wire EDM	int	3	-0.1332	-0.33	0.0636	0.411
R_{z1max}	C45 steel; burnishing after MF	FV	3	-0.39	-1.3062	0.5262	0.557
R_{z1max}	C45 steel; burnishing after MF	conf	2	0.4438	—	—	—
R_{z1max}	C45 steel; burnishing after MF	fusion	3	0.4697	0.3138	0.6257	0.107
R_{z1max}	C45 steel; burnishing after MF	int	4	-1.4739	-2.5302	-0.4176	0.112

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{z1max}	C45 steel; glass bead blasting	FV	3	0.01	-0.1566	0.1767	0.925
R_{z1max}	C45 steel; glass bead blasting	conf	3	0.2095	0.1626	0.2564	0.072
R_{z1max}	C45 steel; glass bead blasting	fusion	3	0.3608	0.3414	0.3802	0.017
R_{z1max}	C45 steel; glass bead blasting	int	3	-0.0017	-0.1418	0.1384	0.985
R_{z1max}	C45 steel; grinding	FV	3	0.1571	-0.3654	0.6796	0.661
R_{z1max}	C45 steel; grinding	conf	3	0.1795	0.1514	0.2077	0.051
R_{z1max}	C45 steel; grinding	fusion	3	0.1276	0.0659	0.1894	0.154
R_{z1max}	C45 steel; grinding	int	3	0.0234	-0.0489	0.0957	0.641
R_{z1max}	C45 steel; honing	FV	3	0.146	-0.0576	0.3496	0.394
R_{z1max}	C45 steel; honing	conf	3	-0.0237	-0.1641	0.1168	0.797
R_{z1max}	C45 steel; honing	fusion	3	0.0954	0.0374	0.1534	0.192
R_{z1max}	C45 steel; honing	int	3	-0.0716	-0.2279	0.0847	0.534
R_{z1max}	C45 steel; finish milling	FV	3	0.0142	-0.0674	0.0958	0.791
R_{z1max}	C45 steel; finish milling	conf	2	0.1114	—	—	—
R_{z1max}	C45 steel; finish milling	fusion	3	0.1028	0.0643	0.1413	0.12
R_{z1max}	C45 steel; finish milling	int	3	0.1642	0.0693	0.2592	0.183
R_{z1max}	C45 steel; rough milling	FV	3	0.0081	-0.0365	0.0526	0.783
R_{z1max}	C45 steel; rough milling	conf	2	-0.0586	—	—	—
R_{z1max}	C45 steel; rough milling	fusion	3	-0.0637	-0.0729	-0.0545	0.047
R_{z1max}	C45 steel; rough milling	int	3	0.0444	-0.0188	0.1075	0.4
R_{z1max}	C45 steel; finish face turning	FV	3	0.0039	-0.0228	0.0305	0.824
R_{z1max}	C45 steel; finish face turning	conf	2	-0.0253	—	—	—
R_{z1max}	C45 steel; finish face turning	fusion	3	-0.0319	-0.0358	-0.0279	0.04
R_{z1max}	C45 steel; finish face turning	int	3	0.0162	-0.0102	0.0426	0.442
R_{z1max}	C45 steel; rough face turning	FV	3	0.0132	-0.0119	0.0384	0.49
R_{z1max}	C45 steel; rough face turning	conf	2	-0.0093	—	—	—
R_{z1max}	C45 steel; rough face turning	fusion	3	-0.0122	-0.0131	-0.0113	0.024
R_{z1max}	C45 steel; rough face turning	int	3	0.0109	-0.0194	0.0412	0.609
R_{z1max}	C45 steel; finish wire EDM	FV	3	0.0761	-0.1445	0.2968	0.622
R_{z1max}	C45 steel; finish wire EDM	conf	3	0.3033	0.1385	0.4682	0.172
R_{z1max}	C45 steel; finish wire EDM	fusion	3	-0.437	-1.244	0.37	0.481
R_{z1max}	C45 steel; finish wire EDM	int	3	-0.0309	-0.1534	0.0916	0.708
R_{z1max}	C45 steel; rough wire EDM	FV	3	-0.0068	-0.0246	0.011	0.592
R_{z1max}	C45 steel; rough wire EDM	conf	3	0.052	0.0408	0.0632	0.07
R_{z1max}	C45 steel; rough wire EDM	fusion	3	0.3963	0.3335	0.459	0.051
R_{z1max}	C45 steel; rough wire EDM	int	3	-0.111	-0.2858	0.0638	0.431
R_{z1max}	ELLOR graphite; glass bead blasting	FV	3	0.007	0.0014	0.0127	0.247
R_{z1max}	ELLOR graphite; glass bead blasting	conf	3	-0.0096	-0.047	0.0279	0.705
R_{z1max}	ELLOR graphite; glass bead blasting	fusion	3	-0.0018	-0.0156	0.012	0.842
R_{z1max}	ELLOR graphite; glass bead blasting	int	3	-0.015	-0.0419	0.0118	0.471
R_{z1max}	ELLOR graphite; grinding	FV	3	-0.0105	-0.0262	0.0053	0.417
R_{z1max}	ELLOR graphite; grinding	conf	3	0.0273	0.003	0.0516	0.271
R_{z1max}	ELLOR graphite; grinding	fusion	3	0.0636	0.0521	0.0751	0.058
R_{z1max}	ELLOR graphite; grinding	int	3	-0.2272	-0.6993	0.245	0.519
R_{z1max}	ELLOR graphite; honing	FV	3	0.104	-0.1744	0.3823	0.598
R_{z1max}	ELLOR graphite; honing	conf	3	0.1623	0.0732	0.2513	0.174
R_{z1max}	ELLOR graphite; honing	fusion	3	0.1977	0.0068	0.3885	0.291
R_{z1max}	ELLOR graphite; honing	int	3	0.0732	-0.1492	0.2956	0.635
R_{z1max}	ELLOR graphite; finish milling	FV	3	0.0451	0.0084	0.0818	0.25
R_{z1max}	ELLOR graphite; finish milling	conf	3	0.0023	-0.0125	0.0171	0.811
R_{z1max}	ELLOR graphite; finish milling	fusion	3	0.4675	0.0546	0.8804	0.27
R_{z1max}	ELLOR graphite; finish milling	int	3	-0.3488	-0.8695	0.1719	0.414
R_{z1max}	ELLOR graphite; rough milling	FV	3	0.0202	-0.0145	0.055	0.458
R_{z1max}	ELLOR graphite; rough milling	conf	3	0.0209	0.0175	0.0243	0.052
R_{z1max}	ELLOR graphite; rough milling	fusion	3	0.0625	0.021	0.1039	0.208
R_{z1max}	ELLOR graphite; rough milling	int	3	-0.3569	-0.8601	0.1464	0.397
R_{z1max}	ELLOR graphite; finish face turning	FV	3	0.0182	-7.1383e-04	0.0372	0.31
R_{z1max}	ELLOR graphite; finish face turning	conf	3	-0.0098	-0.0216	0.0019	0.349

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{z1max}	ELLOR graphite; finish face turning	fusion	3	0.0585	0.0259	0.0911	0.176
R_{z1max}	ELLOR graphite; finish face turning	int	3	-0.2647	-0.6763	0.1468	0.427
R_{z1max}	ELLOR graphite; rough face turning	FV	3	0.0037	-0.0064	0.0138	0.605
R_{z1max}	ELLOR graphite; rough face turning	conf	3	-0.0053	-0.0055	-0.0051	0.011
R_{z1max}	ELLOR graphite; rough face turning	fusion	3	-0.0192	-0.0349	-0.0034	0.253
R_{z1max}	ELLOR graphite; rough face turning	int	3	-0.1771	-0.4332	0.079	0.405
R_{z1max}	ELLOR graphite; finish wire EDM	FV	3	-0.0212	-0.0772	0.0348	0.594
R_{z1max}	ELLOR graphite; finish wire EDM	conf	3	-0.0281	-0.0702	0.014	0.415
R_{z1max}	ELLOR graphite; finish wire EDM	fusion	3	0.0309	-0.0061	0.068	0.349
R_{z1max}	ELLOR graphite; finish wire EDM	int	2	0.0534	—	—	—
R_{z1max}	ELLOR graphite; rough wire EDM	FV	3	0.0104	-0.0051	0.0259	0.414
R_{z1max}	ELLOR graphite; rough wire EDM	conf	3	-0.0175	-0.0411	0.0062	0.385
R_{z1max}	ELLOR graphite; rough wire EDM	fusion	3	0.0044	-0.0151	0.0238	0.736
R_{z1max}	ELLOR graphite; rough wire EDM	int	3	-0.4274	-0.8837	0.0288	0.317
R_{z1max}	MO58A brass; burnishing after MF	FV	4	-1.2114	-3.672	1.2493	0.436
R_{z1max}	MO58A brass; burnishing after MF	conf	3	0.3595	0.0213	0.6976	0.285
R_{z1max}	MO58A brass; burnishing after MF	fusion	3	0.478	-0.0631	1.019	0.333
R_{z1max}	MO58A brass; burnishing after MF	int	3	3.8211	-1.4346	9.0769	0.39
R_{z1max}	MO58A brass; glass bead blasting	FV	3	0.1173	-0.0514	0.2859	0.403
R_{z1max}	MO58A brass; glass bead blasting	conf	3	0.4026	0.2393	0.5659	0.13
R_{z1max}	MO58A brass; glass bead blasting	fusion	3	0.8894	0.8672	0.9115	0.008
R_{z1max}	MO58A brass; glass bead blasting	int	3	0.053	-0.0655	0.1714	0.542
R_{z1max}	MO58A brass; grinding	FV	3	0.2059	0.0176	0.3941	0.278
R_{z1max}	MO58A brass; grinding	conf	3	0.1046	0.0809	0.1282	0.073
R_{z1max}	MO58A brass; grinding	fusion	3	0.0413	-0.0316	0.1143	0.467
R_{z1max}	MO58A brass; grinding	int	3	-0.0071	-0.0595	0.0453	0.834
R_{z1max}	MO58A brass; honing	FV	3	0.1553	0.005	0.3057	0.292
R_{z1max}	MO58A brass; honing	conf	3	-0.0549	-0.1773	0.0675	0.541
R_{z1max}	MO58A brass; honing	fusion	3	0.1196	0.0606	0.1786	0.157
R_{z1max}	MO58A brass; honing	int	3	-0.0514	-0.1621	0.0594	0.53
R_{z1max}	MO58A brass; finish milling	FV	3	-0.608	-1.8095	0.5936	0.503
R_{z1max}	MO58A brass; finish milling	conf	3	0.3331	0.2632	0.403	0.068
R_{z1max}	MO58A brass; finish milling	fusion	3	0.5463	0.2468	0.8457	0.174
R_{z1max}	MO58A brass; finish milling	int	3	0.7032	-0.3517	1.7582	0.416
R_{z1max}	MO58A brass; rough milling	FV	3	0.2287	-0.0653	0.5226	0.37
R_{z1max}	MO58A brass; rough milling	conf	3	-0.0321	-0.0642	-4.5533e-05	0.3
R_{z1max}	MO58A brass; rough milling	fusion	3	-0.055	-0.0694	-0.0407	0.084
R_{z1max}	MO58A brass; rough milling	int	3	0.0759	-0.0683	0.22	0.49
R_{z1max}	MO58A brass; finish face turning	FV	3	0.0141	-0.0385	0.0668	0.691
R_{z1max}	MO58A brass; finish face turning	conf	3	-0.0291	-0.0329	-0.0253	0.042
R_{z1max}	MO58A brass; finish face turning	fusion	3	-0.0386	-0.0431	-0.0341	0.038
R_{z1max}	MO58A brass; finish face turning	int	3	0.0126	-0.0158	0.041	0.544
R_{z1max}	MO58A brass; rough face turning	FV	3	0.0275	-0.0772	0.1323	0.697
R_{z1max}	MO58A brass; rough face turning	conf	3	-0.0469	-0.0564	-0.0375	0.065
R_{z1max}	MO58A brass; rough face turning	fusion	3	-0.0433	-0.079	-0.0076	0.254
R_{z1max}	MO58A brass; rough face turning	int	3	0.0144	-0.0567	0.0855	0.76
R_{z1max}	MO58A brass; finish wire EDM	FV	3	0.0348	-0.2104	0.2799	0.827
R_{z1max}	MO58A brass; finish wire EDM	conf	3	0.1585	0.0975	0.2195	0.123
R_{z1max}	MO58A brass; finish wire EDM	fusion	3	0.2624	0.1715	0.3533	0.111
R_{z1max}	MO58A brass; finish wire EDM	int	3	0.0047	-0.0626	0.0719	0.914
R_{z1max}	MO58A brass; rough wire EDM	FV	3	-0.0321	-0.0391	-0.0252	0.07
R_{z1max}	MO58A brass; rough wire EDM	conf	3	-0.0972	-0.2596	0.0653	0.45
R_{z1max}	MO58A brass; rough wire EDM	fusion	3	0.0442	-0.2278	0.3163	0.804
R_{z1max}	MO58A brass; rough wire EDM	int	3	-0.0559	-0.158	0.0463	0.478

Continued on next page

Parameter	Material/process	System	n	Slope/nm	CI low	CI high	p
R_{z1max}	Ti6Al4V; burnishing after MF	FV	3	-0.5125	-1.0884	0.0634	0.331
R_{z1max}	Ti6Al4V; burnishing after MF	conf	3	0.4579	0.3933	0.5226	0.046
R_{z1max}	Ti6Al4V; burnishing after MF	fusion	3	0.4238	0.4071	0.4405	0.013
R_{z1max}	Ti6Al4V; burnishing after MF	int	3	-0.2841	-1.1772	0.609	0.645
R_{z1max}	Ti6Al4V; glass bead blasting	FV	3	0.0109	-0.0905	0.1123	0.868
R_{z1max}	Ti6Al4V; glass bead blasting	conf	3	0.1579	0.1368	0.1789	0.043
R_{z1max}	Ti6Al4V; glass bead blasting	fusion	3	0.3745	0.281	0.4679	0.081
R_{z1max}	Ti6Al4V; glass bead blasting	int	3	0.0139	-0.0409	0.0687	0.707
R_{z1max}	Ti6Al4V; grinding	FV	3	-0.0646	-0.3166	0.1874	0.704
R_{z1max}	Ti6Al4V; grinding	conf	3	0.1716	0.1378	0.2054	0.064
R_{z1max}	Ti6Al4V; grinding	fusion	3	0.1324	0.0652	0.1996	0.161
R_{z1max}	Ti6Al4V; grinding	int	3	-0.0299	-0.1596	0.0998	0.73
R_{z1max}	Ti6Al4V; honing	FV	3	0.248	-0.0357	0.5317	0.336
R_{z1max}	Ti6Al4V; honing	conf	3	0.188	0.1283	0.2477	0.102
R_{z1max}	Ti6Al4V; honing	fusion	3	0.1107	0.1005	0.121	0.03
R_{z1max}	Ti6Al4V; honing	int	3	0.0211	-0.0449	0.0872	0.643
R_{z1max}	Ti6Al4V; finish milling	FV	3	-0.1984	-0.581	0.1843	0.495
R_{z1max}	Ti6Al4V; finish milling	conf	3	0.2279	0.1649	0.2909	0.089
R_{z1max}	Ti6Al4V; finish milling	fusion	3	0.2519	0.2096	0.2942	0.054
R_{z1max}	Ti6Al4V; finish milling	int	3	-0.0147	-0.1391	0.1097	0.855
R_{z1max}	Ti6Al4V; rough milling	FV	3	0.125	-0.0862	0.3361	0.453
R_{z1max}	Ti6Al4V; rough milling	conf	3	-0.075	-0.0871	-0.0629	0.052
R_{z1max}	Ti6Al4V; rough milling	fusion	3	-0.0826	-0.1065	-0.0587	0.093
R_{z1max}	Ti6Al4V; rough milling	int	3	-0.0602	-0.5433	0.4229	0.847
R_{z1max}	Ti6Al4V; finish face turning	FV	3	-0.0285	-0.1461	0.0891	0.718
R_{z1max}	Ti6Al4V; finish face turning	conf	3	-0.1222	-0.1269	-0.1176	0.012
R_{z1max}	Ti6Al4V; finish face turning	fusion	3	-0.0767	-0.1152	-0.0382	0.159
R_{z1max}	Ti6Al4V; finish face turning	int	3	0.0409	-0.2353	0.3171	0.82
R_{z1max}	Ti6Al4V; rough face turning	FV	3	-0.0692	-0.0924	-0.046	0.108
R_{z1max}	Ti6Al4V; rough face turning	conf	3	-0.1245	-0.1726	-0.0763	0.124
R_{z1max}	Ti6Al4V; rough face turning	fusion	3	-0.1189	-0.1544	-0.0834	0.096
R_{z1max}	Ti6Al4V; rough face turning	int	3	0.0574	-0.0556	0.1704	0.501
R_{z1max}	Ti6Al4V; finish wire EDM	FV	3	0.1546	-0.1359	0.4451	0.487
R_{z1max}	Ti6Al4V; finish wire EDM	conf	3	0.2812	0.2138	0.3486	0.077
R_{z1max}	Ti6Al4V; finish wire EDM	fusion	3	0.2873	0.173	0.4015	0.127
R_{z1max}	Ti6Al4V; finish wire EDM	int	3	0.0908	-0.055	0.2366	0.437
R_{z1max}	Ti6Al4V; rough wire EDM	FV	3	-0.0174	-0.0177	-0.017	0.007
R_{z1max}	Ti6Al4V; rough wire EDM	conf	3	0.3223	0.1694	0.4753	0.151
R_{z1max}	Ti6Al4V; rough wire EDM	fusion	3	0.4293	-1.7840e-04	0.8588	0.3
R_{z1max}	Ti6Al4V; rough wire EDM	int	3	-0.0973	-0.2499	0.0553	0.43

2.3 Table S3: Descriptive statistics by system

Table S3: Per-system descriptive statistics for $|\text{diff}|(\%)$ within each parameter and material/process group.

Parameter	Material/process	System	n	Mean	SD	SE
R_a	AISI 304 / EN 1.4301; burnishing after MF	FV	3	209.6369	117.7736	67.9966
R_a	AISI 304 / EN 1.4301; burnishing after MF	conf	3	165.3083	28.5605	16.4894
R_a	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	214.3675	34.0872	19.6803
R_a	AISI 304 / EN 1.4301; burnishing after MF	int	4	105.8284	114.7874	57.3937
R_a	AISI 304 / EN 1.4301; glass bead blasting	FV	3	8.002	8.3082	4.7968
R_a	AISI 304 / EN 1.4301; glass bead blasting	conf	3	36.0463	17.6579	10.1948
R_a	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	72.9871	14.9404	8.6259

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_a	AISI 304 / EN 1.4301; glass bead blasting	int	4	35.0665	6.4301	3.215
R_a	AISI 304 / EN 1.4301; grinding	FV	3	52.8077	15.2763	8.8197
R_a	AISI 304 / EN 1.4301; grinding	conf	3	36.1143	8.0108	4.625
R_a	AISI 304 / EN 1.4301; grinding	fusion	3	55.2735	8.6975	5.0215
R_a	AISI 304 / EN 1.4301; grinding	int	4	17.2601	3.0491	1.5245
R_a	AISI 304 / EN 1.4301; honing	FV	3	65.2381	36.6933	21.1849
R_a	AISI 304 / EN 1.4301; honing	conf	3	30.4348	17.681	10.2081
R_a	AISI 304 / EN 1.4301; honing	fusion	3	69.5921	14.4434	8.3389
R_a	AISI 304 / EN 1.4301; honing	int	4	4.0109	3.053	1.5265
R_a	AISI 304 / EN 1.4301; finish milling	FV	3	82.1297	37.4762	21.6369
R_a	AISI 304 / EN 1.4301; finish milling	conf	3	99.4392	21.7782	12.5736
R_a	AISI 304 / EN 1.4301; finish milling	fusion	3	131.4834	32.5714	18.8051
R_a	AISI 304 / EN 1.4301; finish milling	int	4	81.6181	60.3966	30.1983
R_a	AISI 304 / EN 1.4301; rough milling	FV	3	78.4385	4.3152	2.4914
R_a	AISI 304 / EN 1.4301; rough milling	conf	3	79.766	3.9356	2.2722
R_a	AISI 304 / EN 1.4301; rough milling	fusion	3	77.7412	4.1785	2.4124
R_a	AISI 304 / EN 1.4301; rough milling	int	4	79.1857	11.602	5.801
R_a	AISI 304 / EN 1.4301; finish face turning	FV	3	33.4384	15.3168	8.8431
R_a	AISI 304 / EN 1.4301; finish face turning	conf	3	43.7916	3.0658	1.77
R_a	AISI 304 / EN 1.4301; finish face turning	fusion	3	37.5874	4.4195	2.5516
R_a	AISI 304 / EN 1.4301; finish face turning	int	4	52.3616	4.7735	2.3867
R_a	AISI 304 / EN 1.4301; rough face turning	FV	3	52.9417	9.4777	5.472
R_a	AISI 304 / EN 1.4301; rough face turning	conf	3	56.1346	2.0326	1.1735
R_a	AISI 304 / EN 1.4301; rough face turning	fusion	3	52.4036	3.0985	1.7889
R_a	AISI 304 / EN 1.4301; rough face turning	int	4	56.6291	4.5713	2.2856
R_a	AISI 304 / EN 1.4301; finish wire EDM	FV	3	18.9552	16.1857	9.3448
R_a	AISI 304 / EN 1.4301; finish wire EDM	conf	3	60.0793	15.7417	9.0885
R_a	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	106.9151	17.8458	10.3033
R_a	AISI 304 / EN 1.4301; finish wire EDM	int	4	14.928	5.2404	2.6202
R_a	AISI 304 / EN 1.4301; rough wire EDM	FV	3	2.9037	3.7169	2.1459
R_a	AISI 304 / EN 1.4301; rough wire EDM	conf	3	3.9948	1.5196	0.8773
R_a	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	8.4945	2.1314	1.2306
R_a	AISI 304 / EN 1.4301; rough wire EDM	int	3	9.4445	2.1804	1.2589
R_a	Al7075; burnishing after MF	FV	3	202.615	120.9142	69.8099
R_a	Al7075; burnishing after MF	conf	3	145.6237	15.9584	9.2136
R_a	Al7075; burnishing after MF	fusion	3	177.7927	17.4895	10.0976
R_a	Al7075; burnishing after MF	int	4	326.2165	413.9565	206.9782
R_a	Al7075; glass bead blasting	FV	3	12.0675	7.9221	4.5738
R_a	Al7075; glass bead blasting	conf	3	29.5222	21.2256	12.2546

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_a	Al7075; glass bead blasting	fusion	3	51.6028	16.9772	9.8018
R_a	Al7075; glass bead blasting	int	4	9.5481	1.7058	0.8529
R_a	Al7075; grinding	FV	3	65.1509	22.4154	12.9415
R_a	Al7075; grinding	conf	3	31.8234	15.3937	8.8876
R_a	Al7075; grinding	fusion	3	53.9564	17.0487	9.8431
R_a	Al7075; grinding	int	4	11.4348	8.0569	4.0285
R_a	Al7075; honing	FV	3	13.3357	10.9141	6.3013
R_a	Al7075; honing	conf	3	34.3005	9.7115	5.6069
R_a	Al7075; honing	fusion	3	21.313	10.7825	6.2253
R_a	Al7075; honing	int	4	54.5109	3.5004	1.7502
R_a	Al7075; finish milling	FV	3	130.037	74.3453	42.9233
R_a	Al7075; finish milling	conf	3	111.974	29.9601	17.2975
R_a	Al7075; finish milling	fusion	3	145.2929	28.8111	16.6341
R_a	Al7075; finish milling	int	4	122.5746	141.4751	70.7375
R_a	Al7075; rough milling	FV	3	172.8211	94.4854	54.5512
R_a	Al7075; rough milling	conf	3	78.0195	19.6475	11.3435
R_a	Al7075; rough milling	fusion	3	124.163	24.9634	14.4126
R_a	Al7075; rough milling	int	4	81.9933	66.8517	33.4259
R_a	Al7075; finish face turning	FV	3	18.9043	14.265	8.2359
R_a	Al7075; finish face turning	conf	3	27.5597	9.8993	5.7154
R_a	Al7075; finish face turning	fusion	3	15.685	12.3623	7.1374
R_a	Al7075; finish face turning	int	4	33.4733	16.3244	8.1622
R_a	Al7075; rough face turning	FV	3	69.2147	2.9582	1.7079
R_a	Al7075; rough face turning	conf	3	69.5452	0.7857	0.4536
R_a	Al7075; rough face turning	fusion	3	67.9275	1.0353	0.5977
R_a	Al7075; rough face turning	int	4	71.5526	2.2644	1.1322
R_a	Al7075; finish wire EDM	FV	3	60.6567	17.5584	10.1374
R_a	Al7075; finish wire EDM	conf	3	107.3516	16.2425	9.3776
R_a	Al7075; finish wire EDM	fusion	3	186.4962	22.3164	12.8844
R_a	Al7075; finish wire EDM	int	4	12.8552	15.4566	7.7283
R_a	Al7075; rough wire EDM	FV	3	8.0671	5.4167	3.1273
R_a	Al7075; rough wire EDM	conf	3	6.0493	5.3218	3.0725
R_a	Al7075; rough wire EDM	fusion	3	27.0397	11.255	6.4981
R_a	Al7075; rough wire EDM	int	4	6.2022	3.0205	1.5102
R_a	C45 steel; burnishing after MF	FV	3	175.4545	90.5669	52.2888
R_a	C45 steel; burnishing after MF	conf	2	188.2852	39.3251	27.8071
R_a	C45 steel; burnishing after MF	fusion	3	213.2224	48.657	28.0922
R_a	C45 steel; burnishing after MF	int	5	251.4206	311.211	139.1778
R_a	C45 steel; glass bead blasting	FV	3	13.4899	7.4982	4.3291
R_a	C45 steel; glass bead blasting	conf	3	28.0197	21.4167	12.3649
R_a	C45 steel; glass bead blasting	fusion	3	51.441	21.5106	12.4192
R_a	C45 steel; glass bead blasting	int	4	21.8375	1.3023	0.6512
R_a	C45 steel; grinding	FV	3	125.9688	27.0475	15.6159
R_a	C45 steel; grinding	conf	3	66.2942	19.168	11.0667
R_a	C45 steel; grinding	fusion	3	91.0827	21.0391	12.1469
R_a	C45 steel; grinding	int	4	7.1568	7.0537	3.5268
R_a	C45 steel; honing	FV	3	43.5759	33.3963	19.2814
R_a	C45 steel; honing	conf	3	13.7745	10.191	5.8838
R_a	C45 steel; honing	fusion	3	39.6338	12.6935	7.3286
R_a	C45 steel; honing	int	4	5.5336	4.5345	2.2672
R_a	C45 steel; finish milling	FV	3	25.9252	5.7444	3.3165
R_a	C45 steel; finish milling	conf	2	6.8144	7.8482	5.5495
R_a	C45 steel; finish milling	fusion	3	9.3384	7.3958	4.27
R_a	C45 steel; finish milling	int	4	26.9689	2.5816	1.2908
R_a	C45 steel; rough milling	FV	3	50.8756	2.3813	1.3748
R_a	C45 steel; rough milling	conf	2	44.6113	2.8492	2.0147
R_a	C45 steel; rough milling	fusion	3	41.5882	4.4874	2.5908
R_a	C45 steel; rough milling	int	4	50.7356	3.7906	1.8953
R_a	C45 steel; finish face turning	FV	3	64.9867	1.4414	0.8322
R_a	C45 steel; finish face turning	conf	2	60.7107	1.9947	1.4104
R_a	C45 steel; finish face turning	fusion	3	57.8476	3.659	2.1125
R_a	C45 steel; finish face turning	int	4	64.9964	2.1829	1.0915
R_a	C45 steel; rough face turning	FV	3	84.4021	3.7684	2.1757
R_a	C45 steel; rough face turning	conf	2	84.1032	1.2342	0.8727

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_a	C45 steel; rough face turning	fusion	3	82.341	2.421	1.3978
R_a	C45 steel; rough face turning	int	4	88.5687	2.7554	1.3777
R_a	C45 steel; finish wire EDM	FV	3	26.7562	15.5778	8.9939
R_a	C45 steel; finish wire EDM	conf	3	82.362	20.0729	11.5891
R_a	C45 steel; finish wire EDM	fusion	3	126.041	17.2403	9.9537
R_a	C45 steel; finish wire EDM	int	4	22.1086	4.4757	2.2378
R_a	C45 steel; rough wire EDM	FV	3	1.3764	1.1172	0.645
R_a	C45 steel; rough wire EDM	conf	3	7.0079	4.0232	2.3228
R_a	C45 steel; rough wire EDM	fusion	3	15.317	6.8492	3.9544
R_a	C45 steel; rough wire EDM	int	4	15.6272	14.2181	7.109
R_a	ELLOR graphite; glass bead blasting	FV	3	13.3265	0.8095	0.4674
R_a	ELLOR graphite; glass bead blasting	conf	3	17.8399	1.2349	0.713
R_a	ELLOR graphite; glass bead blasting	fusion	3	19.8354	1.0773	0.622
R_a	ELLOR graphite; glass bead blasting	int	4	17.4039	1.6623	0.8312
R_a	ELLOR graphite; grinding	FV	3	198.625	9.8521	5.6881
R_a	ELLOR graphite; grinding	conf	3	240.5749	9.7347	5.6204
R_a	ELLOR graphite; grinding	fusion	3	240.3186	14.5216	8.3841
R_a	ELLOR graphite; grinding	int	4	164.2581	86.418	43.209
R_a	ELLOR graphite; honing	FV	3	109.7734	62.9127	36.3227
R_a	ELLOR graphite; honing	conf	3	147.2986	47.2437	27.2762
R_a	ELLOR graphite; honing	fusion	3	213.1052	53.2439	30.7404
R_a	ELLOR graphite; honing	int	4	33.399	20.5722	10.2861
R_a	ELLOR graphite; finish milling	FV	3	31.3222	10.8354	6.2558
R_a	ELLOR graphite; finish milling	conf	3	15.9538	9.9736	5.7582
R_a	ELLOR graphite; finish milling	fusion	3	16.8146	18.7277	10.8124
R_a	ELLOR graphite; finish milling	int	4	34.1407	21.8341	10.917
R_a	ELLOR graphite; rough milling	FV	3	11.9404	5.3238	3.0737
R_a	ELLOR graphite; rough milling	conf	3	18.3179	9.4272	5.4428
R_a	ELLOR graphite; rough milling	fusion	3	21.9033	11.1733	6.4509
R_a	ELLOR graphite; rough milling	int	4	16.3496	30.6341	15.3171
R_a	ELLOR graphite; finish face turning	FV	3	14.0348	3.5426	2.0453
R_a	ELLOR graphite; finish face turning	conf	3	12.7893	8.8429	5.1055
R_a	ELLOR graphite; finish face turning	fusion	3	29.0914	11.0912	6.4035
R_a	ELLOR graphite; finish face turning	int	4	14.7201	14.605	7.3025
R_a	ELLOR graphite; rough face turning	FV	3	18.6326	1.365	0.7881
R_a	ELLOR graphite; rough face turning	conf	3	13.3429	0.8512	0.4914
R_a	ELLOR graphite; rough face turning	fusion	3	11.4508	1.2231	0.7061
R_a	ELLOR graphite; rough face turning	int	4	24.8345	23.2273	11.6137
R_a	ELLOR graphite; finish wire EDM	FV	3	13.8954	5.5204	3.1872
R_a	ELLOR graphite; finish wire EDM	conf	3	35.1281	7.6749	4.4311
R_a	ELLOR graphite; finish wire EDM	fusion	3	45.2404	7.9382	4.5831
R_a	ELLOR graphite; finish wire EDM	int	3	18.1287	5.408	3.1223
R_a	ELLOR graphite; rough wire EDM	FV	3	3.4204	3.2082	1.8522
R_a	ELLOR graphite; rough wire EDM	conf	3	22.6406	6.7896	3.92
R_a	ELLOR graphite; rough wire EDM	fusion	3	26.1096	7.84	4.5264
R_a	ELLOR graphite; rough wire EDM	int	4	20.5464	15.6926	7.8463
R_a	MO58A brass; burnishing after MF	FV	4	544.7931	295.0955	147.5478
R_a	MO58A brass; burnishing after MF	conf	3	408.6199	30.3914	17.5465
R_a	MO58A brass; burnishing after MF	fusion	3	503.7804	39.8707	23.0193

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
R_a	MO58A brass; burnishing after MF	int	3	708.5742	854.2423	493.197
R_a	MO58A brass; glass bead blasting	FV	3	18.7977	11.2526	6.4967
R_a	MO58A brass; glass bead blasting	conf	3	58.2215	30.3103	17.4997
R_a	MO58A brass; glass bead blasting	fusion	3	83.9375	24.9842	14.4246
R_a	MO58A brass; glass bead blasting	int	4	11.0185	5.0776	2.5388
R_a	MO58A brass; grinding	FV	3	64.9242	20.5753	11.8791
R_a	MO58A brass; grinding	conf	3	43.2491	11.6389	6.7197
R_a	MO58A brass; grinding	fusion	3	81.0075	15.7268	9.0799
R_a	MO58A brass; grinding	int	4	17.2063	3.46	1.73
R_a	MO58A brass; honing	FV	3	48.4848	29.9074	17.267
R_a	MO58A brass; honing	conf	3	17.4357	14.1376	8.1623
R_a	MO58A brass; honing	fusion	3	47.7841	8.6028	4.9668
R_a	MO58A brass; honing	int	4	6.8573	3.7079	1.8539
R_a	MO58A brass; finish milling	FV	3	203.056	140.7174	81.2433
R_a	MO58A brass; finish milling	conf	3	177.6197	32.4592	18.7403
R_a	MO58A brass; finish milling	fusion	3	225.4485	42.7185	24.6636
R_a	MO58A brass; finish milling	int	4	121.6407	177.0463	88.5231
R_a	MO58A brass; rough milling	FV	3	44.8902	22.9969	13.2773
R_a	MO58A brass; rough milling	conf	3	53.2683	3.1419	1.814
R_a	MO58A brass; rough milling	fusion	3	43.3534	3.0605	1.767
R_a	MO58A brass; rough milling	int	4	63.8125	5.2917	2.6459
R_a	MO58A brass; finish face turning	FV	3	57.7456	3.2532	1.8782
R_a	MO58A brass; finish face turning	conf	3	56.3063	2.2025	1.2716
R_a	MO58A brass; finish face turning	fusion	3	50.498	1.7035	0.9835
R_a	MO58A brass; finish face turning	int	4	56.5799	1.467	0.7335
R_a	MO58A brass; rough face turning	FV	3	19.4509	3.5927	2.0742
R_a	MO58A brass; rough face turning	conf	3	21.3538	2.8053	1.6196
R_a	MO58A brass; rough face turning	fusion	3	15.812	2.0769	1.1991
R_a	MO58A brass; rough face turning	int	4	21.15	0.7454	0.3727
R_a	MO58A brass; finish wire EDM	FV	3	26.7702	12.8205	7.4019
R_a	MO58A brass; finish wire EDM	conf	3	46.4511	22.2296	12.8342
R_a	MO58A brass; finish wire EDM	fusion	3	106.6595	12.6451	7.3007
R_a	MO58A brass; finish wire EDM	int	4	3.1348	0.4689	0.2344
R_a	MO58A brass; rough wire EDM	FV	3	28.5793	3.7039	2.1384
R_a	MO58A brass; rough wire EDM	conf	3	22.2209	11.122	6.4213
R_a	MO58A brass; rough wire EDM	fusion	3	16.8897	7.5962	4.3857
R_a	MO58A brass; rough wire EDM	int	4	23.9221	7.5418	3.7709
R_a	Ti6Al4V; burnishing after MF	FV	3	114.4095	52.9112	30.5483
R_a	Ti6Al4V; burnishing after MF	conf	3	138.7379	44.7137	25.8154
R_a	Ti6Al4V; burnishing after MF	fusion	3	152.5616	45.5917	26.3224
R_a	Ti6Al4V; burnishing after MF	int	4	38.1807	21.5336	10.7668
R_a	Ti6Al4V; glass bead blasting	FV	3	22.6873	15.8893	9.1737
R_a	Ti6Al4V; glass bead blasting	conf	3	78.3502	26.1689	15.1086
R_a	Ti6Al4V; glass bead blasting	fusion	3	124.9816	26.4996	15.2996
R_a	Ti6Al4V; glass bead blasting	int	4	14.3482	7.0044	3.5022
R_a	Ti6Al4V; grinding	FV	3	96.3803	26.9127	15.5381
R_a	Ti6Al4V; grinding	conf	3	107.451	19.7947	11.4285
R_a	Ti6Al4V; grinding	fusion	3	128.0218	23.7185	13.6939
R_a	Ti6Al4V; grinding	int	4	70.3919	3.0841	1.542
R_a	Ti6Al4V; honing	FV	3	147.3282	42.2461	24.3908
R_a	Ti6Al4V; honing	conf	3	91.3442	28.6524	16.5425
R_a	Ti6Al4V; honing	fusion	3	139.9422	36.585	21.1223
R_a	Ti6Al4V; honing	int	4	25.2436	1.5663	0.7832
R_a	Ti6Al4V; finish milling	FV	3	44.3352	19.2143	11.0934
R_a	Ti6Al4V; finish milling	conf	3	50.8746	14.3032	8.2579
R_a	Ti6Al4V; finish milling	fusion	3	63.676	14.7687	8.5267
R_a	Ti6Al4V; finish milling	int	4	16.0707	3.4891	1.7445
R_a	Ti6Al4V; rough milling	FV	3	27.3731	29.3632	16.9529
R_a	Ti6Al4V; rough milling	conf	3	13.3795	8.3652	4.8297
R_a	Ti6Al4V; rough milling	fusion	3	26.4486	15.6479	9.0343
R_a	Ti6Al4V; rough milling	int	4	40.6295	25.5418	12.7709
R_a	Ti6Al4V; finish face turning	FV	3	22.249	4.594	2.6524
R_a	Ti6Al4V; finish face turning	conf	3	23.9099	6.594	3.807

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_a	Ti6Al4V; finish face turning	fusion	3	17.8231	7.1872	4.1496
R_a	Ti6Al4V; finish face turning	int	4	20.0689	4.3469	2.1734
R_a	Ti6Al4V; rough face turning	FV	3	71.8945	1.4787	0.8538
R_a	Ti6Al4V; rough face turning	conf	3	69.8475	3.5551	2.0525
R_a	Ti6Al4V; rough face turning	fusion	3	66.5305	3.7075	2.1405
R_a	Ti6Al4V; rough face turning	int	4	72.1597	3.5496	1.7748
R_a	Ti6Al4V; finish wire EDM	FV	3	83.3996	24.2823	14.0194
R_a	Ti6Al4V; finish wire EDM	conf	3	130.4078	27.0822	15.6359
R_a	Ti6Al4V; finish wire EDM	fusion	3	207.1685	32.6286	18.8381
R_a	Ti6Al4V; finish wire EDM	int	4	17.7206	6.7675	3.3837
R_a	Ti6Al4V; rough wire EDM	FV	3	6.813	0.9065	0.5234
R_a	Ti6Al4V; rough wire EDM	conf	3	7.5455	3.79	2.1881
R_a	Ti6Al4V; rough wire EDM	fusion	3	24.7333	10.6283	6.1363
R_a	Ti6Al4V; rough wire EDM	int	4	10.3291	13.6737	6.8368
rku	AISI 304 / EN 1.4301; burnishing after MF	FV	3	86.6243	0.3001	0.1733
rku	AISI 304 / EN 1.4301; burnishing after MF	conf	3	81.5133	1.7516	1.0113
rku	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	78.5735	1.8057	1.0425
rku	AISI 304 / EN 1.4301; burnishing after MF	int	4	85.8521	2.8787	1.4394
rku	AISI 304 / EN 1.4301; glass bead blasting	FV	3	10.0489	5.7144	3.2992
rku	AISI 304 / EN 1.4301; glass bead blasting	conf	3	4.6199	3.9525	2.282
rku	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	21.5012	13.0219	7.5182
rku	AISI 304 / EN 1.4301; glass bead blasting	int	4	7.4832	5.162	2.581
rku	AISI 304 / EN 1.4301; grinding	FV	3	37.4255	2.2109	1.2765
rku	AISI 304 / EN 1.4301; grinding	conf	3	34.7367	1.2114	0.6994
rku	AISI 304 / EN 1.4301; grinding	fusion	3	27.6229	8.4098	4.8554
rku	AISI 304 / EN 1.4301; grinding	int	4	23.8458	3.5603	1.7802
rku	AISI 304 / EN 1.4301; honing	FV	3	35.776	1.8818	1.0865
rku	AISI 304 / EN 1.4301; honing	conf	3	20.8157	3.6183	2.089
rku	AISI 304 / EN 1.4301; honing	fusion	3	14.8016	4.9195	2.8403
rku	AISI 304 / EN 1.4301; honing	int	4	27.1029	4.0946	2.0473
rku	AISI 304 / EN 1.4301; finish milling	FV	3	46.1191	4.766	2.7516
rku	AISI 304 / EN 1.4301; finish milling	conf	3	41.9641	5.0761	2.9307
rku	AISI 304 / EN 1.4301; finish milling	fusion	3	36.0721	6.6964	3.8661
rku	AISI 304 / EN 1.4301; finish milling	int	4	54.0251	7.9377	3.9688
rku	AISI 304 / EN 1.4301; rough milling	FV	3	34.4964	6.7338	3.8878
rku	AISI 304 / EN 1.4301; rough milling	conf	3	35.1321	1.8997	1.0968
rku	AISI 304 / EN 1.4301; rough milling	fusion	3	42.6397	6.1124	3.529
rku	AISI 304 / EN 1.4301; rough milling	int	4	53.1163	36.0913	18.0456
rku	AISI 304 / EN 1.4301; finish face turning	FV	3	41.1029	7.8407	4.5268
rku	AISI 304 / EN 1.4301; finish face turning	conf	3	53.979	0.8497	0.4906
rku	AISI 304 / EN 1.4301; finish face turning	fusion	3	53.6912	1.0903	0.6295
rku	AISI 304 / EN 1.4301; finish face turning	int	4	48.4427	9.1502	4.5751
rku	AISI 304 / EN 1.4301; rough face turning	FV	3	42.0478	3.3117	1.912

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rku	AISI 304 / EN 1.4301; rough face turning	conf	3	56.3616	2.2607	1.3052
rku	AISI 304 / EN 1.4301; rough face turning	fusion	3	61.0511	2.8283	1.6329
rku	AISI 304 / EN 1.4301; rough face turning	int	4	69.6813	15.5116	7.7558
rku	AISI 304 / EN 1.4301; finish wire EDM	FV	3	3.9025	1.1246	0.6493
rku	AISI 304 / EN 1.4301; finish wire EDM	conf	3	8.273	5.5029	3.1771
rku	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	32.807	25.479	14.7103
rku	AISI 304 / EN 1.4301; finish wire EDM	int	4	4.1939	4.9463	2.4732
rku	AISI 304 / EN 1.4301; rough wire EDM	FV	3	5.8049	2.9063	1.6779
rku	AISI 304 / EN 1.4301; rough wire EDM	conf	3	4.0241	2.1061	1.216
rku	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	13.9405	9.0096	5.2017
rku	AISI 304 / EN 1.4301; rough wire EDM	int	3	8.7373	1.0607	0.6124
rku	Al7075; burnishing after MF	FV	3	13.2056	2.1267	1.2278
rku	Al7075; burnishing after MF	conf	3	14.2681	13.29	7.673
rku	Al7075; burnishing after MF	fusion	3	25.8514	26.8729	15.5151
rku	Al7075; burnishing after MF	int	4	31.7026	4.8368	2.4184
rku	Al7075; glass bead blasting	FV	3	3.2596	4.4137	2.5483
rku	Al7075; glass bead blasting	conf	3	15.4771	7.2284	4.1733
rku	Al7075; glass bead blasting	fusion	3	54.6457	48.411	27.9501
rku	Al7075; glass bead blasting	int	4	5.3226	2.2662	1.1331
rku	Al7075; grinding	FV	3	74.5042	2.5273	1.4591
rku	Al7075; grinding	conf	3	74.8161	0.9425	0.5441
rku	Al7075; grinding	fusion	3	74.0467	0.5829	0.3366
rku	Al7075; grinding	int	4	67.7131	4.6799	2.34
rku	Al7075; honing	FV	3	15.2647	11.548	6.6672
rku	Al7075; honing	conf	3	14.8213	3.5313	2.0388
rku	Al7075; honing	fusion	3	8.5945	2.5351	1.4636
rku	Al7075; honing	int	4	19.0983	14.006	7.003
rku	Al7075; finish milling	FV	3	82.2285	2.8417	1.6407
rku	Al7075; finish milling	conf	3	81.5826	1.5534	0.8969
rku	Al7075; finish milling	fusion	3	80.177	2.0608	1.1898
rku	Al7075; finish milling	int	4	86.5319	1.5142	0.7571
rku	Al7075; rough milling	FV	3	16.0102	4.3893	2.5341
rku	Al7075; rough milling	conf	3	7.3146	2.5536	1.4743
rku	Al7075; rough milling	fusion	3	2.8612	1.7572	1.0145
rku	Al7075; rough milling	int	4	5.2701	4.4332	2.2166
rku	Al7075; finish face turning	FV	3	75.4023	2.613	1.5086
rku	Al7075; finish face turning	conf	3	74.6341	0.6238	0.3602
rku	Al7075; finish face turning	fusion	3	72.8878	0.7134	0.4119
rku	Al7075; finish face turning	int	4	76.4183	3.931	1.9655
rku	Al7075; rough face turning	FV	3	65.5177	13.9031	8.027
rku	Al7075; rough face turning	conf	3	59.82	6.4276	3.7109
rku	Al7075; rough face turning	fusion	3	65.077	4.622	2.6685
rku	Al7075; rough face turning	int	4	56.3942	11.4931	5.7465
rku	Al7075; finish wire EDM	FV	3	7.4743	0.749	0.4324
rku	Al7075; finish wire EDM	conf	3	6.6741	8.6603	5
rku	Al7075; finish wire EDM	fusion	3	19.055	27.8754	16.0939
rku	Al7075; finish wire EDM	int	4	13.3181	3.3369	1.6684
rku	Al7075; rough wire EDM	FV	3	5.913	2.1652	1.2501
rku	Al7075; rough wire EDM	conf	3	82.4235	55.069	31.7941
rku	Al7075; rough wire EDM	fusion	3	296.693	49.9904	28.862
rku	Al7075; rough wire EDM	int	4	19.7424	27.5606	13.7803
rku	C45 steel; burnishing after MF	FV	3	57.0999	2.5888	1.4947
rku	C45 steel; burnishing after MF	conf	2	50.61	1.9135	1.3531

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rku	C45 steel; burnishing after MF	fusion	3	44.8776	3.5216	2.0332
rku	C45 steel; burnishing after MF	int	5	61.6642	2.3768	1.063
rku	C45 steel; glass bead blasting	FV	3	16.6133	4.7476	2.741
rku	C45 steel; glass bead blasting	conf	3	23.4366	2.159	1.2465
rku	C45 steel; glass bead blasting	fusion	3	38.0011	9.2912	5.3643
rku	C45 steel; glass bead blasting	int	4	6.5651	6.9915	3.4957
rku	C45 steel; grinding	FV	3	42.5576	7.1641	4.1362
rku	C45 steel; grinding	conf	3	43.7118	1.1956	0.6903
rku	C45 steel; grinding	fusion	3	42.8766	0.7787	0.4496
rku	C45 steel; grinding	int	4	24.5632	9.4303	4.7152
rku	C45 steel; honing	FV	3	23.7152	3.0411	1.7558
rku	C45 steel; honing	conf	3	7.4341	3.5278	2.0368
rku	C45 steel; honing	fusion	3	4.1865	3.5717	2.0621
rku	C45 steel; honing	int	4	10.0169	5.9718	2.9859
rku	C45 steel; finish milling	FV	3	20.5175	16.8344	9.7193
rku	C45 steel; finish milling	conf	2	12.5462	0.5273	0.3729
rku	C45 steel; finish milling	fusion	3	34.1963	6.3262	3.6524
rku	C45 steel; finish milling	int	4	56.5839	35.2727	17.6363
rku	C45 steel; rough milling	FV	3	18.5525	2.3914	1.3807
rku	C45 steel; rough milling	conf	2	27.9015	0.0782	0.0553
rku	C45 steel; rough milling	fusion	3	34.1917	4.4373	2.5619
rku	C45 steel; rough milling	int	4	31.0287	3.5446	1.7723
rku	C45 steel; finish face turning	FV	3	23.1404	1.5459	0.8925
rku	C45 steel; finish face turning	conf	2	14.995	0.5564	0.3934
rku	C45 steel; finish face turning	fusion	3	11.7286	1.0698	0.6176
rku	C45 steel; finish face turning	int	4	14.0707	1.6638	0.8319
rku	C45 steel; rough face turning	FV	3	69.2799	0.8255	0.4766
rku	C45 steel; rough face turning	conf	2	66.3481	0.3228	0.2283
rku	C45 steel; rough face turning	fusion	3	64.0869	1.4226	0.8214
rku	C45 steel; rough face turning	int	4	64.4035	3.4761	1.738
rku	C45 steel; finish wire EDM	FV	3	1.5486	1.5837	0.9143
rku	C45 steel; finish wire EDM	conf	3	46.7824	13.8357	7.988
rku	C45 steel; finish wire EDM	fusion	3	79.7313	80.3857	46.4107
rku	C45 steel; finish wire EDM	int	4	2.6624	2.0838	1.0419
rku	C45 steel; rough wire EDM	FV	3	4.4332	0.4363	0.2519
rku	C45 steel; rough wire EDM	conf	3	5.2025	0.5595	0.3231
rku	C45 steel; rough wire EDM	fusion	3	96.2645	66.9465	38.6516
rku	C45 steel; rough wire EDM	int	4	13.1916	6.7741	3.3871
rku	ELLOR graphite; glass bead blasting	FV	3	39.4061	0.3642	0.2103
rku	ELLOR graphite; glass bead blasting	conf	3	39.9967	1.0025	0.5788
rku	ELLOR graphite; glass bead blasting	fusion	3	39.2894	0.129	0.0745
rku	ELLOR graphite; glass bead blasting	int	4	34.4081	6.5446	3.2723
rku	ELLOR graphite; grinding	FV	3	39.4144	2.7662	1.597
rku	ELLOR graphite; grinding	conf	3	48.1512	2.6242	1.5151
rku	ELLOR graphite; grinding	fusion	3	47.2666	2.8311	1.6345
rku	ELLOR graphite; grinding	int	4	28.2815	11.5419	5.7709
rku	ELLOR graphite; honing	FV	3	86.0256	0.1976	0.1141
rku	ELLOR graphite; honing	conf	3	82.8108	0.6369	0.3677
rku	ELLOR graphite; honing	fusion	3	79.6229	1.3868	0.8006
rku	ELLOR graphite; honing	int	4	71.1521	11.264	5.632
rku	ELLOR graphite; finish milling	FV	3	38.0907	12.2416	7.0677
rku	ELLOR graphite; finish milling	conf	3	50.4909	9.6199	5.554
rku	ELLOR graphite; finish milling	fusion	3	38.4258	26.2245	15.1407
rku	ELLOR graphite; finish milling	int	4	39.3682	29.4977	14.7489
rku	ELLOR graphite; rough milling	FV	3	28.7571	5.4108	3.1239
rku	ELLOR graphite; rough milling	conf	3	44.5406	7.2931	4.2107
rku	ELLOR graphite; rough milling	fusion	3	46.5184	4.6001	2.6559
rku	ELLOR graphite; rough milling	int	4	28.3409	28.7262	14.3631
rku	ELLOR graphite; finish face turning	FV	3	42.1534	3.092	1.7852

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rku	ELLOR graphite; finish face turning	conf	3	47.2341	5.6575	3.2664
rku	ELLOR graphite; finish face turning	fusion	3	53.3977	1.8491	1.0676
rku	ELLOR graphite; finish face turning	int	4	28.5016	27.0077	13.5039
rku	ELLOR graphite; rough face turning	FV	3	2.2349	0.2903	0.1676
rku	ELLOR graphite; rough face turning	conf	3	6.7656	1.7636	1.0182
rku	ELLOR graphite; rough face turning	fusion	3	5.2607	0.7192	0.4152
rku	ELLOR graphite; rough face turning	int	4	2.1095	2.0501	1.0251
rku	ELLOR graphite; finish wire EDM	FV	3	47.6495	1.8347	1.0593
rku	ELLOR graphite; finish wire EDM	conf	3	53.0743	4.6207	2.6678
rku	ELLOR graphite; finish wire EDM	fusion	3	55.6131	2.3416	1.3519
rku	ELLOR graphite; finish wire EDM	int	3	36.3833	0.6469	0.3735
rku	ELLOR graphite; rough wire EDM	FV	3	53.9503	2.9605	1.7093
rku	ELLOR graphite; rough wire EDM	conf	3	59.8385	2.8612	1.6519
rku	ELLOR graphite; rough wire EDM	fusion	3	61.3354	2.0849	1.2037
rku	ELLOR graphite; rough wire EDM	int	4	49.0376	6.2101	3.105
rku	MO58A brass; burnishing after MF	FV	4	87.6215	2.5704	1.2852
rku	MO58A brass; burnishing after MF	conf	3	85.4468	2.585	1.4924
rku	MO58A brass; burnishing after MF	fusion	3	83.8124	3.7271	2.1518
rku	MO58A brass; burnishing after MF	int	3	89.5293	1.4037	0.8104
rku	MO58A brass; glass bead blasting	FV	3	6.3975	2.5898	1.4952
rku	MO58A brass; glass bead blasting	conf	3	22.8965	9.2136	5.3195
rku	MO58A brass; glass bead blasting	fusion	3	33.0719	35.5513	20.5255
rku	MO58A brass; glass bead blasting	int	4	3.4253	1.3284	0.6642
rku	MO58A brass; grinding	FV	3	33.1691	1.5582	0.8996
rku	MO58A brass; grinding	conf	3	29.8239	1.4245	0.8224
rku	MO58A brass; grinding	fusion	3	31.6338	7.1469	4.1263
rku	MO58A brass; grinding	int	4	21.1273	4.5058	2.2529
rku	MO58A brass; honing	FV	3	23.9761	2.9191	1.6854
rku	MO58A brass; honing	conf	3	14.8617	4.9768	2.8734
rku	MO58A brass; honing	fusion	3	10.0792	4.5377	2.6198
rku	MO58A brass; honing	int	4	27.3811	4.1708	2.0854
rku	MO58A brass; finish milling	FV	3	36.5484	2.9213	1.6866
rku	MO58A brass; finish milling	conf	3	23.3771	3.514	2.0288
rku	MO58A brass; finish milling	fusion	3	15.6586	4.0038	2.3116
rku	MO58A brass; finish milling	int	4	31.7585	30.1787	15.0894
rku	MO58A brass; rough milling	FV	3	3.2461	4.4421	2.5646
rku	MO58A brass; rough milling	conf	3	11.5137	2.4945	1.4402
rku	MO58A brass; rough milling	fusion	3	23.9364	9.5864	5.5347
rku	MO58A brass; rough milling	int	4	7.1277	8.8824	4.4412
rku	MO58A brass; finish face turning	FV	3	24.6266	2.0252	1.1692
rku	MO58A brass; finish face turning	conf	3	17.9458	1.3685	0.7901
rku	MO58A brass; finish face turning	fusion	3	12.451	1.662	0.9596
rku	MO58A brass; finish face turning	int	4	25.42	3.6207	1.8104
rku	MO58A brass; rough face turning	FV	3	10.2383	2.9475	1.7017
rku	MO58A brass; rough face turning	conf	3	8.5464	2.6095	1.5066
rku	MO58A brass; rough face turning	fusion	3	5.0814	3.5668	2.0593
rku	MO58A brass; rough face turning	int	4	15.7829	2.0779	1.0389
rku	MO58A brass; finish wire EDM	FV	3	20.7225	6.0728	3.5061
rku	MO58A brass; finish wire EDM	conf	3	23.4639	11.9762	6.9145
rku	MO58A brass; finish wire EDM	fusion	3	19.9827	13.108	7.5679
rku	MO58A brass; finish wire EDM	int	4	2.4128	0.7912	0.3956
rku	MO58A brass; rough wire EDM	FV	3	4.9788	0.954	0.5508
rku	MO58A brass; rough wire EDM	conf	3	9.0603	8.4682	4.8891

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rku	MO58A brass; rough wire EDM	fusion	3	15.6741	19.8084	11.4364
rku	MO58A brass; rough wire EDM	int	4	3.5077	0.887	0.4435
rku	Ti6Al4V; burnishing after MF	FV	3	12.3323	12.0557	6.9604
rku	Ti6Al4V; burnishing after MF	conf	3	6.4098	3.5265	2.036
rku	Ti6Al4V; burnishing after MF	fusion	3	5.5689	6.7675	3.9072
rku	Ti6Al4V; burnishing after MF	int	4	77.996	45.921	22.9605
rku	Ti6Al4V; glass bead blasting	FV	3	31.8976	2.3588	1.3619
rku	Ti6Al4V; glass bead blasting	conf	3	24.8871	3.4948	2.0177
rku	Ti6Al4V; glass bead blasting	fusion	3	12.7764	3.6232	2.0919
rku	Ti6Al4V; glass bead blasting	int	4	15.1617	12.858	6.429
rku	Ti6Al4V; grinding	FV	3	37.8026	4.6975	2.7121
rku	Ti6Al4V; grinding	conf	3	35.2345	0.4666	0.2694
rku	Ti6Al4V; grinding	fusion	3	32.679	0.9994	0.577
rku	Ti6Al4V; grinding	int	4	29.8938	0.8861	0.4431
rku	Ti6Al4V; honing	FV	3	39.135	1.4622	0.8442
rku	Ti6Al4V; honing	conf	3	29.9396	2.372	1.3695
rku	Ti6Al4V; honing	fusion	3	22.5703	6.4248	3.7094
rku	Ti6Al4V; honing	int	4	34.3139	2.6781	1.3391
rku	Ti6Al4V; finish milling	FV	3	26.0814	7.8444	4.529
rku	Ti6Al4V; finish milling	conf	3	17.4448	4.2366	2.446
rku	Ti6Al4V; finish milling	fusion	3	7.9312	3.9295	2.2687
rku	Ti6Al4V; finish milling	int	4	29.7736	4.7582	2.3791
rku	Ti6Al4V; rough milling	FV	3	78.4689	0.787	0.4544
rku	Ti6Al4V; rough milling	conf	3	76.7876	0.4806	0.2775
rku	Ti6Al4V; rough milling	fusion	3	74.4046	1.2434	0.7179
rku	Ti6Al4V; rough milling	int	4	76.1107	4.1759	2.0879
rku	Ti6Al4V; finish face turning	FV	3	8.0716	5.0344	2.9066
rku	Ti6Al4V; finish face turning	conf	3	5.957	1.8807	1.0858
rku	Ti6Al4V; finish face turning	fusion	3	6.5664	4.7434	2.7386
rku	Ti6Al4V; finish face turning	int	4	11.4943	9.4258	4.7129
rku	Ti6Al4V; rough face turning	FV	3	76.2043	11.5742	6.6824
rku	Ti6Al4V; rough face turning	conf	3	90.8494	6.1653	3.5595
rku	Ti6Al4V; rough face turning	fusion	3	100.5305	3.2389	1.87
rku	Ti6Al4V; rough face turning	int	4	73.7957	1.3929	0.6965
rku	Ti6Al4V; finish wire EDM	FV	3	10.441	2.7915	1.6117
rku	Ti6Al4V; finish wire EDM	conf	3	8.8239	0.7924	0.4575
rku	Ti6Al4V; finish wire EDM	fusion	3	3.9885	2.6919	1.5542
rku	Ti6Al4V; finish wire EDM	int	4	5.9417	4.9854	2.4927
rku	Ti6Al4V; rough wire EDM	FV	3	1.9263	0.7173	0.4141
rku	Ti6Al4V; rough wire EDM	conf	3	36.6204	34.9108	20.1557
rku	Ti6Al4V; rough wire EDM	fusion	3	153.0016	78.8604	45.5301
rku	Ti6Al4V; rough wire EDM	int	4	7.7985	1.5148	0.7574
rp	AISI 304 / EN 1.4301; burnishing after MF	FV	3	303.3203	74.4108	42.9611
rp	AISI 304 / EN 1.4301; burnishing after MF	conf	3	359.1149	76.3171	44.0617
rp	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	506.6633	64.1987	37.0651
rp	AISI 304 / EN 1.4301; burnishing after MF	int	4	160.2016	177.525	88.7625
rp	AISI 304 / EN 1.4301; glass bead blasting	FV	3	9.5454	5.2829	3.0501
rp	AISI 304 / EN 1.4301; glass bead blasting	conf	3	36.256	4.672	2.6974
rp	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	115.2105	15.0882	8.7112
rp	AISI 304 / EN 1.4301; glass bead blasting	int	4	42.1546	8.9842	4.4921
rp	AISI 304 / EN 1.4301; grinding	FV	3	78.9221	22.3964	12.9306
rp	AISI 304 / EN 1.4301; grinding	conf	3	37.1895	3.9877	2.3023
rp	AISI 304 / EN 1.4301; grinding	fusion	3	91.7159	39.2714	22.6734
rp	AISI 304 / EN 1.4301; grinding	int	4	5.5552	3.0037	1.5019
rp	AISI 304 / EN 1.4301; honing	FV	3	22.8206	21.5728	12.4551
rp	AISI 304 / EN 1.4301; honing	conf	3	3.1028	2.2407	1.2937

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
rp	AISI 304 / EN 1.4301; honing	fusion	3	67.7203	20.1732	11.647
rp	AISI 304 / EN 1.4301; honing	int	4	9.4315	12.113	6.0565
rp	AISI 304 / EN 1.4301; finish milling	FV	3	56.8921	27.7446	16.0184
rp	AISI 304 / EN 1.4301; finish milling	conf	3	76.4029	22.5779	13.0353
rp	AISI 304 / EN 1.4301; finish milling	fusion	3	107.9214	29.917	17.2726
rp	AISI 304 / EN 1.4301; finish milling	int	4	58.6287	82.0987	41.0493
rp	AISI 304 / EN 1.4301; rough milling	FV	3	71.3591	4.6166	2.6654
rp	AISI 304 / EN 1.4301; rough milling	conf	3	70.7995	5.1391	2.9671
rp	AISI 304 / EN 1.4301; rough milling	fusion	3	66.708	4.722	2.7262
rp	AISI 304 / EN 1.4301; rough milling	int	4	68.0289	21.253	10.6265
rp	AISI 304 / EN 1.4301; finish face turning	FV	3	44.6782	23.6867	13.6755
rp	AISI 304 / EN 1.4301; finish face turning	conf	3	56.9485	1.8314	1.0574
rp	AISI 304 / EN 1.4301; finish face turning	fusion	3	49.5995	2.5683	1.4828
rp	AISI 304 / EN 1.4301; finish face turning	int	4	62.7888	9.6645	4.8323
rp	AISI 304 / EN 1.4301; rough face turning	FV	3	36.9145	7.2563	4.1894
rp	AISI 304 / EN 1.4301; rough face turning	conf	3	32.3006	0.6756	0.3901
rp	AISI 304 / EN 1.4301; rough face turning	fusion	3	24.0867	1.5014	0.8668
rp	AISI 304 / EN 1.4301; rough face turning	int	4	30.1744	5.0973	2.5486
rp	AISI 304 / EN 1.4301; finish wire EDM	FV	3	21.4294	12.9265	7.4631
rp	AISI 304 / EN 1.4301; finish wire EDM	conf	3	86.1075	30.4924	17.6048
rp	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	154.8551	40.6155	23.4494
rp	AISI 304 / EN 1.4301; finish wire EDM	int	4	15.771	12.2317	6.1158
rp	AISI 304 / EN 1.4301; rough wire EDM	FV	3	2.7311	2.2991	1.3274
rp	AISI 304 / EN 1.4301; rough wire EDM	conf	3	5.9991	2.3984	1.3847
rp	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	21.2018	4.7814	2.7605
rp	AISI 304 / EN 1.4301; rough wire EDM	int	3	9.6538	2.2303	1.2877
rp	Al7075; burnishing after MF	FV	3	278.4983	76.2691	44.034
rp	Al7075; burnishing after MF	conf	3	292.6464	59.699	34.4672
rp	Al7075; burnishing after MF	fusion	3	367.8772	62.191	35.906
rp	Al7075; burnishing after MF	int	4	390.6332	473.1527	236.5764
rp	Al7075; glass bead blasting	FV	3	9.711	5.609	3.2384
rp	Al7075; glass bead blasting	conf	3	20.5311	7.6522	4.418
rp	Al7075; glass bead blasting	fusion	3	82.9543	34.6655	20.0141
rp	Al7075; glass bead blasting	int	4	12.077	1.9074	0.9537
rp	Al7075; grinding	FV	3	101.5505	29.4054	16.9772
rp	Al7075; grinding	conf	3	26.829	9.4212	5.4393
rp	Al7075; grinding	fusion	3	63.9823	8.8236	5.0943
rp	Al7075; grinding	int	4	20.4089	13.0798	6.5399
rp	Al7075; honing	FV	3	15.9198	23.9688	13.8384
rp	Al7075; honing	conf	3	43.2004	4.7794	2.7594

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rp	Al7075; honing	fusion	3	24.4066	3.885	2.243
rp	Al7075; honing	int	4	65.635	7.0531	3.5265
rp	Al7075; finish milling	FV	3	85.3258	31.0037	17.9
rp	Al7075; finish milling	conf	3	103.5879	45.658	26.3606
rp	Al7075; finish milling	fusion	3	144.6254	40.6309	23.4582
rp	Al7075; finish milling	int	4	89.1661	80.795	40.3975
rp	Al7075; rough milling	FV	3	141.278	69.8521	40.3291
rp	Al7075; rough milling	conf	3	84.9768	14.5329	8.3906
rp	Al7075; rough milling	fusion	3	138.1039	15.1708	8.7589
rp	Al7075; rough milling	int	4	77.5831	51.6555	25.8278
rp	Al7075; finish face turning	FV	3	27.0115	12.4632	7.1956
rp	Al7075; finish face turning	conf	3	26.8989	10.257	5.9219
rp	Al7075; finish face turning	fusion	3	10.8813	11.3333	6.5433
rp	Al7075; finish face turning	int	4	39.5458	26.3569	13.1784
rp	Al7075; rough face turning	FV	3	58.5484	5.4894	3.1693
rp	Al7075; rough face turning	conf	3	58.9987	2.0372	1.1762
rp	Al7075; rough face turning	fusion	3	54.2634	1.6125	0.931
rp	Al7075; rough face turning	int	4	63.306	5.5776	2.7888
rp	Al7075; finish wire EDM	FV	3	61.3198	15.0245	8.6744
rp	Al7075; finish wire EDM	conf	3	148.9128	25.1892	14.543
rp	Al7075; finish wire EDM	fusion	3	252.131	66.3404	38.3016
rp	Al7075; finish wire EDM	int	4	12.6952	11.2645	5.6323
rp	Al7075; rough wire EDM	FV	3	5.5766	3.6576	2.1117
rp	Al7075; rough wire EDM	conf	3	20.5437	3.9532	2.2824
rp	Al7075; rough wire EDM	fusion	3	106.6782	18.2827	10.5555
rp	Al7075; rough wire EDM	int	4	3.9248	4.1057	2.0528
rp	C45 steel; burnishing after MF	FV	3	182.537	47.8265	27.6126
rp	C45 steel; burnishing after MF	conf	2	249.8398	52.0034	36.772
rp	C45 steel; burnishing after MF	fusion	3	318.6049	39.1705	22.6151
rp	C45 steel; burnishing after MF	int	5	305.8059	361.8532	161.8257
rp	C45 steel; glass bead blasting	FV	3	7.2589	6.5326	3.7716
rp	C45 steel; glass bead blasting	conf	3	31.1037	3.906	2.2551
rp	C45 steel; glass bead blasting	fusion	3	74.3401	5.8028	3.3503
rp	C45 steel; glass bead blasting	int	4	20.7946	1.4654	0.7327
rp	C45 steel; grinding	FV	3	223.7202	53.7235	31.0173
rp	C45 steel; grinding	conf	3	79.183	10.9962	6.3487
rp	C45 steel; grinding	fusion	3	128.2668	14.1449	8.1665
rp	C45 steel; grinding	int	4	17.2857	4.5562	2.2781
rp	C45 steel; honing	FV	3	21.0741	23.2372	13.416
rp	C45 steel; honing	conf	3	6.4647	4.1839	2.4156
rp	C45 steel; honing	fusion	3	29.1699	7.0042	4.0439
rp	C45 steel; honing	int	4	10.1054	12.2057	6.1028
rp	C45 steel; finish milling	FV	3	43.551	23.6644	13.6626
rp	C45 steel; finish milling	conf	2	34.0232	9.4819	6.7047
rp	C45 steel; finish milling	fusion	3	70.073	7.627	4.4034
rp	C45 steel; finish milling	int	4	30.6061	19.7399	9.87
rp	C45 steel; rough milling	FV	3	40.2307	2.3454	1.3541
rp	C45 steel; rough milling	conf	2	30.5246	2.4748	1.7499
rp	C45 steel; rough milling	fusion	3	21.5757	2.3536	1.3588
rp	C45 steel; rough milling	int	4	37.7873	4.7428	2.3714
rp	C45 steel; finish face turning	FV	3	57.4139	2.1319	1.2309
rp	C45 steel; finish face turning	conf	2	51.0963	1.7219	1.2176
rp	C45 steel; finish face turning	fusion	3	44.0253	1.3892	0.802
rp	C45 steel; finish face turning	int	4	55.4796	3.119	1.5595
rp	C45 steel; rough face turning	FV	3	81.149	3.3476	1.9328
rp	C45 steel; rough face turning	conf	2	79.6612	1.0843	0.7667
rp	C45 steel; rough face turning	fusion	3	75.8054	1.4607	0.8433
rp	C45 steel; rough face turning	int	4	85.4507	4.4392	2.2196
rp	C45 steel; finish wire EDM	FV	3	20.9582	10.019	5.7845
rp	C45 steel; finish wire EDM	conf	3	178.3332	52.2822	30.1851
rp	C45 steel; finish wire EDM	fusion	3	257.365	43.281	24.9883
rp	C45 steel; finish wire EDM	int	4	23.1574	8.1525	4.0763
rp	C45 steel; rough wire EDM	FV	3	1.5097	2.3878	1.3786
rp	C45 steel; rough wire EDM	conf	3	10.9245	1.6711	0.9648

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rp	C45 steel; rough wire EDM	fusion	3	42.488	6.7493	3.8967
rp	C45 steel; rough wire EDM	int	4	13.9618	7.8397	3.9198
rp	ELLOR graphite; glass bead blasting	FV	3	41.9683	2.6479	1.5288
rp	ELLOR graphite; glass bead blasting	conf	3	54.74	3.056	1.7644
rp	ELLOR graphite; glass bead blasting	fusion	3	64.5723	3.1006	1.7901
rp	ELLOR graphite; glass bead blasting	int	4	43.5139	7.2338	3.6169
rp	ELLOR graphite; grinding	FV	3	113.5846	8.0004	4.6191
rp	ELLOR graphite; grinding	conf	3	162.5627	14.7261	8.5021
rp	ELLOR graphite; grinding	fusion	3	198.9987	16.3125	9.418
rp	ELLOR graphite; grinding	int	4	149.9536	96.882	48.441
rp	ELLOR graphite; honing	FV	3	100.244	43.1498	24.9126
rp	ELLOR graphite; honing	conf	3	152.8532	23.8357	13.7615
rp	ELLOR graphite; honing	fusion	3	293.2011	51.9168	29.9742
rp	ELLOR graphite; honing	int	4	48.6551	37.4524	18.7262
rp	ELLOR graphite; finish milling	FV	3	17.7806	16.3182	9.4213
rp	ELLOR graphite; finish milling	conf	3	80.1798	14.7684	8.5265
rp	ELLOR graphite; finish milling	fusion	3	153.2062	21.235	12.26
rp	ELLOR graphite; finish milling	int	4	10.8603	7.239	3.6195
rp	ELLOR graphite; rough milling	FV	3	7.4563	6.2216	3.592
rp	ELLOR graphite; rough milling	conf	3	63.6391	14.3134	8.2638
rp	ELLOR graphite; rough milling	fusion	3	99.8706	9.7671	5.639
rp	ELLOR graphite; rough milling	int	4	13.1687	11.182	5.591
rp	ELLOR graphite; finish face turning	FV	3	2.974	4.1141	2.3753
rp	ELLOR graphite; finish face turning	conf	3	35.302	6.2271	3.5952
rp	ELLOR graphite; finish face turning	fusion	3	71.6838	7.3383	4.2368
rp	ELLOR graphite; finish face turning	int	4	5.085	7.4516	3.7258
rp	ELLOR graphite; rough face turning	FV	3	26.5954	1.9468	1.124
rp	ELLOR graphite; rough face turning	conf	3	13.058	2.7161	1.5681
rp	ELLOR graphite; rough face turning	fusion	3	3.8175	2.8833	1.6647
rp	ELLOR graphite; rough face turning	int	4	29.9328	15.508	7.754
rp	ELLOR graphite; finish wire EDM	FV	3	19.0913	6.0431	3.489
rp	ELLOR graphite; finish wire EDM	conf	3	49.2408	9.5961	5.5403
rp	ELLOR graphite; finish wire EDM	fusion	3	92.1757	10.2276	5.9049
rp	ELLOR graphite; finish wire EDM	int	3	16.7423	4.7422	2.7379
rp	ELLOR graphite; rough wire EDM	FV	3	5.779	5.557	3.2083
rp	ELLOR graphite; rough wire EDM	conf	3	31.4256	7.0295	4.0585
rp	ELLOR graphite; rough wire EDM	fusion	3	60.7486	7.6567	4.4206
rp	ELLOR graphite; rough wire EDM	int	4	77.1263	137.9247	68.9623
rp	MO58A brass; burnishing after MF	FV	4	467.319	174.8322	87.4161
rp	MO58A brass; burnishing after MF	conf	3	458.3593	45.0337	26.0002
rp	MO58A brass; burnishing after MF	fusion	3	605.1459	61.402	35.4504
rp	MO58A brass; burnishing after MF	int	3	573.1996	658.7097	380.3063
rp	MO58A brass; glass bead blasting	FV	3	25.5231	12.7562	7.3648
rp	MO58A brass; glass bead blasting	conf	3	56.9258	11.4132	6.5894
rp	MO58A brass; glass bead blasting	fusion	3	96.4489	35.5522	20.5261
rp	MO58A brass; glass bead blasting	int	4	11.2748	5.0151	2.5075
rp	MO58A brass; grinding	FV	3	101.6269	35.4602	20.473
rp	MO58A brass; grinding	conf	3	46.2482	5.0773	2.9314

Continued on next page

Parameter	Material/process	System	<i>n</i>	Mean	SD	SE
rp	MO58A brass; grinding	fusion	3	106.6298	25.9724	14.9952
rp	MO58A brass; grinding	int	4	6.3584	1.0902	0.5451
rp	MO58A brass; honing	FV	3	41.8205	29.8438	17.2303
rp	MO58A brass; honing	conf	3	4.3365	3.5143	2.029
rp	MO58A brass; honing	fusion	3	33.8281	10.5643	6.0993
rp	MO58A brass; honing	int	4	9.5098	10.5667	5.2834
rp	MO58A brass; finish milling	FV	3	285.084	65.2853	37.6925
rp	MO58A brass; finish milling	conf	3	326.2016	76.7524	44.313
rp	MO58A brass; finish milling	fusion	3	466.5207	78.8148	45.5037
rp	MO58A brass; finish milling	int	4	169.4144	218.9855	109.4927
rp	MO58A brass; rough milling	FV	3	39.1567	23.276	13.4384
rp	MO58A brass; rough milling	conf	3	39.1483	3.5826	2.0684
rp	MO58A brass; rough milling	fusion	3	19.1658	10.6359	6.1407
rp	MO58A brass; rough milling	int	4	59.6369	10.9515	5.4757
rp	MO58A brass; finish face turning	FV	3	59.5967	3.924	2.2655
rp	MO58A brass; finish face turning	conf	3	54.3859	1.009	0.5826
rp	MO58A brass; finish face turning	fusion	3	44.4174	3.8151	2.2026
rp	MO58A brass; finish face turning	int	4	59.6103	3.8161	1.908
rp	MO58A brass; rough face turning	FV	3	21.5548	5.9013	3.4071
rp	MO58A brass; rough face turning	conf	3	20.6514	1.4708	0.8491
rp	MO58A brass; rough face turning	fusion	3	9.7096	0.8577	0.4952
rp	MO58A brass; rough face turning	int	4	27.9166	4.2159	2.1079
rp	MO58A brass; finish wire EDM	FV	3	57.5996	15.1587	8.7519
rp	MO58A brass; finish wire EDM	conf	3	86.0294	11.9983	6.9272
rp	MO58A brass; finish wire EDM	fusion	3	153.7323	28.0427	16.1904
rp	MO58A brass; finish wire EDM	int	4	4.8363	3.0508	1.5254
rp	MO58A brass; rough wire EDM	FV	3	27.7628	1.7864	1.0314
rp	MO58A brass; rough wire EDM	conf	3	16.8454	9.3934	5.4233
rp	MO58A brass; rough wire EDM	fusion	3	12.8659	9.2284	5.328
rp	MO58A brass; rough wire EDM	int	4	17.25	10.855	5.4275
rp	Ti6Al4V; burnishing after MF	FV	3	136.0182	40.8191	23.5669
rp	Ti6Al4V; burnishing after MF	conf	3	201.9405	72.7525	42.0037
rp	Ti6Al4V; burnishing after MF	fusion	3	250.2768	66.8216	38.5795
rp	Ti6Al4V; burnishing after MF	int	4	91.6973	98.3133	49.1567
rp	Ti6Al4V; glass bead blasting	FV	3	11.0624	11.6953	6.7523
rp	Ti6Al4V; glass bead blasting	conf	3	50.8011	4.4024	2.5417
rp	Ti6Al4V; glass bead blasting	fusion	3	122.8952	6.8829	3.9738
rp	Ti6Al4V; glass bead blasting	int	4	33.1188	6.7379	3.369
rp	Ti6Al4V; grinding	FV	3	102.2328	26.6869	15.4077
rp	Ti6Al4V; grinding	conf	3	98.6463	18.1502	10.479
rp	Ti6Al4V; grinding	fusion	3	142.0604	13.5528	7.8247
rp	Ti6Al4V; grinding	int	4	47.5776	18.2501	9.125
rp	Ti6Al4V; honing	FV	3	91.206	38.5219	22.2406
rp	Ti6Al4V; honing	conf	3	28.9259	7.4765	4.3166
rp	Ti6Al4V; honing	fusion	3	81.6795	15.7894	9.116
rp	Ti6Al4V; honing	int	4	8.7976	3.8238	1.9119
rp	Ti6Al4V; finish milling	FV	3	35.4254	17.3666	10.0266
rp	Ti6Al4V; finish milling	conf	3	67.1244	5.3588	3.0939
rp	Ti6Al4V; finish milling	fusion	3	103.1076	3.1623	1.8257
rp	Ti6Al4V; finish milling	int	4	9.0696	8.3834	4.1917
rp	Ti6Al4V; rough milling	FV	3	24.4254	10.9737	6.3357
rp	Ti6Al4V; rough milling	conf	3	17.6332	8.3245	4.8061
rp	Ti6Al4V; rough milling	fusion	3	4.0527	4.1974	2.4234
rp	Ti6Al4V; rough milling	int	4	40.3637	29.2606	14.6303
rp	Ti6Al4V; finish face turning	FV	3	18.8483	6.4673	3.7339
rp	Ti6Al4V; finish face turning	conf	3	10.3461	9.3753	5.4128
rp	Ti6Al4V; finish face turning	fusion	3	5.6993	4.5376	2.6198
rp	Ti6Al4V; finish face turning	int	4	22.1196	14.7639	7.3819
rp	Ti6Al4V; rough face turning	FV	3	61.7511	3.9702	2.2922
rp	Ti6Al4V; rough face turning	conf	3	57.1737	3.6564	2.111
rp	Ti6Al4V; rough face turning	fusion	3	49.4437	1.7218	0.9941
rp	Ti6Al4V; rough face turning	int	4	64.0799	5.5854	2.7927
rp	Ti6Al4V; finish wire EDM	FV	3	62.6162	24.2134	13.9796
rp	Ti6Al4V; finish wire EDM	conf	3	113.9086	24.3432	14.0546

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
rp	Ti6Al4V; finish wire EDM	fusion	3	203.6366	28.181	16.2703
rp	Ti6Al4V; finish wire EDM	int	4	29.8373	14.5222	7.2611
rp	Ti6Al4V; rough wire EDM	FV	3	0.89	0.1372	0.0792
rp	Ti6Al4V; rough wire EDM	conf	3	21.7882	1.4096	0.8138
rp	Ti6Al4V; rough wire EDM	fusion	3	80.6352	22.88	13.2097
rp	Ti6Al4V; rough wire EDM	int	4	14.0105	6.0661	3.033
R_q	AISI 304 / EN 1.4301; burnishing after MF	FV	3	165.5581	99.9112	57.6838
R_q	AISI 304 / EN 1.4301; burnishing after MF	conf	3	136.9082	27.9897	16.1598
R_q	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	186.3547	33.9888	19.6235
R_q	AISI 304 / EN 1.4301; burnishing after MF	int	4	89.6295	79.6019	39.801
R_q	AISI 304 / EN 1.4301; glass bead blasting	FV	3	8.2414	7.7394	4.4683
R_q	AISI 304 / EN 1.4301; glass bead blasting	conf	3	39.5422	16.8994	9.7569
R_q	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	83.3757	12.9663	7.4861
R_q	AISI 304 / EN 1.4301; glass bead blasting	int	4	33.7682	5.8822	2.9411
R_q	AISI 304 / EN 1.4301; grinding	FV	3	46.8074	14.3893	8.3077
R_q	AISI 304 / EN 1.4301; grinding	conf	3	30.4397	7.1173	4.1092
R_q	AISI 304 / EN 1.4301; grinding	fusion	3	50.6195	6.7057	3.8715
R_q	AISI 304 / EN 1.4301; grinding	int	4	14.3529	3.0194	1.5097
R_q	AISI 304 / EN 1.4301; honing	FV	3	59.6307	34.5388	19.941
R_q	AISI 304 / EN 1.4301; honing	conf	3	29.0804	17.7152	10.2279
R_q	AISI 304 / EN 1.4301; honing	fusion	3	74.1472	9.305	5.3722
R_q	AISI 304 / EN 1.4301; honing	int	4	4.4153	1.953	0.9765
R_q	AISI 304 / EN 1.4301; finish milling	FV	3	72.4477	37.2195	21.4887
R_q	AISI 304 / EN 1.4301; finish milling	conf	3	90.7318	23.1382	13.3588
R_q	AISI 304 / EN 1.4301; finish milling	fusion	3	123.9623	34.5602	19.9533
R_q	AISI 304 / EN 1.4301; finish milling	int	4	67.855	60.9507	30.4754
R_q	AISI 304 / EN 1.4301; rough milling	FV	3	76.5349	4.8596	2.8057
R_q	AISI 304 / EN 1.4301; rough milling	conf	3	77.9948	4.2555	2.4569
R_q	AISI 304 / EN 1.4301; rough milling	fusion	3	75.6249	4.4569	2.5732
R_q	AISI 304 / EN 1.4301; rough milling	int	4	76.7351	13.3727	6.6863
R_q	AISI 304 / EN 1.4301; finish face turning	FV	3	34.8435	12.5097	7.2225
R_q	AISI 304 / EN 1.4301; finish face turning	conf	3	44.2979	2.6584	1.5348
R_q	AISI 304 / EN 1.4301; finish face turning	fusion	3	38.2167	4.0126	2.3167
R_q	AISI 304 / EN 1.4301; finish face turning	int	4	52.2945	5.88	2.94
R_q	AISI 304 / EN 1.4301; rough face turning	FV	3	48.7263	9.9744	5.7587
R_q	AISI 304 / EN 1.4301; rough face turning	conf	3	51.7732	2.1433	1.2374
R_q	AISI 304 / EN 1.4301; rough face turning	fusion	3	47.6261	3.2703	1.8881
R_q	AISI 304 / EN 1.4301; rough face turning	int	4	51.5963	4.3549	2.1774
R_q	AISI 304 / EN 1.4301; finish wire EDM	FV	3	19.423	15.9601	9.2146

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_q	AISI 304 / EN 1.4301; finish wire EDM	conf	3	62.5514	16.9374	9.7788
R_q	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	112.9163	17.333	10.0072
R_q	AISI 304 / EN 1.4301; finish wire EDM	int	4	15.0197	5.6603	2.8302
R_q	AISI 304 / EN 1.4301; rough wire EDM	FV	3	2.2064	2.7495	1.5874
R_q	AISI 304 / EN 1.4301; rough wire EDM	conf	3	3.5247	1.8593	1.0735
R_q	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	8.8617	2.1599	1.247
R_q	AISI 304 / EN 1.4301; rough wire EDM	int	3	7.9453	1.9274	1.1128
R_q	Al7075; burnishing after MF	FV	3	184.5512	118.7249	68.5458
R_q	Al7075; burnishing after MF	conf	3	130.7718	18.6336	10.7581
R_q	Al7075; burnishing after MF	fusion	3	163.9641	21.5351	12.4333
R_q	Al7075; burnishing after MF	int	4	281.6467	369.574	184.787
R_q	Al7075; glass bead blasting	FV	3	11.6492	7.3618	4.2504
R_q	Al7075; glass bead blasting	conf	3	32.4049	22.1176	12.7696
R_q	Al7075; glass bead blasting	fusion	3	56.4185	20.2452	11.6886
R_q	Al7075; glass bead blasting	int	4	9.6651	1.7333	0.8666
R_q	Al7075; grinding	FV	3	55.2752	20.5257	11.8505
R_q	Al7075; grinding	conf	3	22.8839	14.5816	8.4187
R_q	Al7075; grinding	fusion	3	43.9089	15.8901	9.1741
R_q	Al7075; grinding	int	4	15.2975	6.4953	3.2476
R_q	Al7075; honing	FV	3	12.6817	11.654	6.7284
R_q	Al7075; honing	conf	3	35.5432	9.5823	5.5323
R_q	Al7075; honing	fusion	3	22.183	10.589	6.1136
R_q	Al7075; honing	int	4	54.0974	2.7337	1.3668
R_q	Al7075; finish milling	FV	3	66.6779	57.0616	32.9445
R_q	Al7075; finish milling	conf	3	54.9448	23.5035	13.5697
R_q	Al7075; finish milling	fusion	3	80.6414	23.3773	13.4969
R_q	Al7075; finish milling	int	4	85.5019	74.1154	37.0577
R_q	Al7075; rough milling	FV	3	171.0053	96.4687	55.6962
R_q	Al7075; rough milling	conf	3	79.1788	20.213	11.67
R_q	Al7075; rough milling	fusion	3	127.268	25.4639	14.7016
R_q	Al7075; rough milling	int	4	83.8029	67.5657	33.7828
R_q	Al7075; finish face turning	FV	3	20.5829	15.238	8.7977
R_q	Al7075; finish face turning	conf	3	28.9603	10.2197	5.9003
R_q	Al7075; finish face turning	fusion	3	16.3738	12.9999	7.5055
R_q	Al7075; finish face turning	int	4	35.7516	17.4961	8.748
R_q	Al7075; rough face turning	FV	3	66.5102	3.7682	2.1756
R_q	Al7075; rough face turning	conf	3	67.1769	1.1836	0.6834
R_q	Al7075; rough face turning	fusion	3	65.2968	1.4581	0.8418
R_q	Al7075; rough face turning	int	4	69.4005	2.6664	1.3332
R_q	Al7075; finish wire EDM	FV	3	59.9253	17.4772	10.0905
R_q	Al7075; finish wire EDM	conf	3	110.4805	16.0542	9.2689
R_q	Al7075; finish wire EDM	fusion	3	187.8722	21.3058	12.3009
R_q	Al7075; finish wire EDM	int	4	11.2082	14.8712	7.4356
R_q	Al7075; rough wire EDM	FV	3	8.6654	5.0329	2.9058
R_q	Al7075; rough wire EDM	conf	3	10.3103	8.6123	4.9723
R_q	Al7075; rough wire EDM	fusion	3	50.5935	19.437	11.222
R_q	Al7075; rough wire EDM	int	4	5.8189	1.346	0.673
R_q	C45 steel; burnishing after MF	FV	3	163.8913	87.332	50.4212
R_q	C45 steel; burnishing after MF	conf	2	182.8914	40.4622	28.6111
R_q	C45 steel; burnishing after MF	fusion	3	211.5571	51.5213	29.7459
R_q	C45 steel; burnishing after MF	int	5	234.2422	288.6759	129.0998
R_q	C45 steel; glass bead blasting	FV	3	11.9176	7.9524	4.5913
R_q	C45 steel; glass bead blasting	conf	3	31.574	21.7026	12.53
R_q	C45 steel; glass bead blasting	fusion	3	57.8097	22.3649	12.9124
R_q	C45 steel; glass bead blasting	int	4	21.3648	1.1081	0.554
R_q	C45 steel; grinding	FV	3	115.7359	26.0538	15.0422
R_q	C45 steel; grinding	conf	3	57.6246	18.1484	10.478

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_q	C45 steel; grinding	fusion	3	81.4987	19.5697	11.2986
R_q	C45 steel; grinding	int	4	5.2736	5.8132	2.9066
R_q	C45 steel; honing	FV	3	39.9914	31.6352	18.2646
R_q	C45 steel; honing	conf	3	13.8914	10.1226	5.8443
R_q	C45 steel; honing	fusion	3	41.3814	10.7687	6.2173
R_q	C45 steel; honing	int	4	5.3249	5.3241	2.662
R_q	C45 steel; finish milling	FV	3	25.2156	6.0797	3.5101
R_q	C45 steel; finish milling	conf	2	7.3051	7.6836	5.4332
R_q	C45 steel; finish milling	fusion	3	8.4619	7.168	4.1385
R_q	C45 steel; finish milling	int	4	23.2959	4.4678	2.2339
R_q	C45 steel; rough milling	FV	3	49.3648	2.2987	1.3271
R_q	C45 steel; rough milling	conf	2	42.4011	2.908	2.0563
R_q	C45 steel; rough milling	fusion	3	39.0968	4.4217	2.5529
R_q	C45 steel; rough milling	int	4	48.5888	3.7776	1.8888
R_q	C45 steel; finish face turning	FV	3	66.1063	1.3618	0.7862
R_q	C45 steel; finish face turning	conf	2	61.4079	1.976	1.3973
R_q	C45 steel; finish face turning	fusion	3	58.5414	3.5748	2.0639
R_q	C45 steel; finish face turning	int	4	65.6764	2.0431	1.0215
R_q	C45 steel; rough face turning	FV	3	88.6565	2.7708	1.5997
R_q	C45 steel; rough face turning	conf	2	88.3005	0.8658	0.6122
R_q	C45 steel; rough face turning	fusion	3	86.8777	1.7266	0.9969
R_q	C45 steel; rough face turning	int	4	91.4931	1.9634	0.9817
R_q	C45 steel; finish wire EDM	FV	3	27.0866	15.3954	8.8885
R_q	C45 steel; finish wire EDM	conf	3	90.1655	22.2512	12.8468
R_q	C45 steel; finish wire EDM	fusion	3	137.5601	11.9652	6.9081
R_q	C45 steel; finish wire EDM	int	4	21.8238	4.5932	2.2966
R_q	C45 steel; rough wire EDM	FV	3	2.0694	1.0758	0.6211
R_q	C45 steel; rough wire EDM	conf	3	6.237	3.903	2.2534
R_q	C45 steel; rough wire EDM	fusion	3	20.2574	10.637	6.1412
R_q	C45 steel; rough wire EDM	int	4	13.794	13.7091	6.8546
R_q	ELLOR graphite; glass bead blasting	FV	3	8.908	0.7466	0.431
R_q	ELLOR graphite; glass bead blasting	conf	3	13.1291	1.282	0.7401
R_q	ELLOR graphite; glass bead blasting	fusion	3	15.0944	1.0682	0.6167
R_q	ELLOR graphite; glass bead blasting	int	4	14.4922	1.4575	0.7288
R_q	ELLOR graphite; grinding	FV	3	216.5751	6.5364	3.7738
R_q	ELLOR graphite; grinding	conf	3	246.8339	6.8676	3.965
R_q	ELLOR graphite; grinding	fusion	3	247.8622	10.5946	6.1168
R_q	ELLOR graphite; grinding	int	4	187.1609	73.5889	36.7945
R_q	ELLOR graphite; honing	FV	3	74.9477	51.7883	29.9
R_q	ELLOR graphite; honing	conf	3	111.4193	40.3269	23.2828
R_q	ELLOR graphite; honing	fusion	3	172.7777	44.6664	25.7882
R_q	ELLOR graphite; honing	int	4	26.5017	14.7411	7.3706
R_q	ELLOR graphite; finish milling	FV	3	34.3635	8.3075	4.7963
R_q	ELLOR graphite; finish milling	conf	3	7.5921	4.7336	2.7329
R_q	ELLOR graphite; finish milling	fusion	3	11.2493	12.4788	7.2046
R_q	ELLOR graphite; finish milling	int	4	27.9154	30.1981	15.0991
R_q	ELLOR graphite; rough milling	FV	3	10.1382	4.3222	2.4954
R_q	ELLOR graphite; rough milling	conf	3	13.3397	5.4678	3.1568
R_q	ELLOR graphite; rough milling	fusion	3	15.8996	7.3188	4.2255
R_q	ELLOR graphite; rough milling	int	4	19.8337	31.834	15.917
R_q	ELLOR graphite; finish face turning	FV	3	18.4268	3.0367	1.7533
R_q	ELLOR graphite; finish face turning	conf	3	6.0622	6.12	3.5334
R_q	ELLOR graphite; finish face turning	fusion	3	18.7409	9.3056	5.3726
R_q	ELLOR graphite; finish face turning	int	4	16.506	18.6876	9.3438
R_q	ELLOR graphite; rough face turning	FV	3	14.7909	1.0391	0.5999

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_q	ELLOR graphite; rough face turning	conf	3	10.6828	0.6223	0.3593
R_q	ELLOR graphite; rough face turning	fusion	3	8.5282	1.0847	0.6262
R_q	ELLOR graphite; rough face turning	int	4	21.9771	24.1438	12.0719
R_q	ELLOR graphite; finish wire EDM	FV	3	13.7384	4.7921	2.7667
R_q	ELLOR graphite; finish wire EDM	conf	3	31.2014	4.898	2.8279
R_q	ELLOR graphite; finish wire EDM	fusion	3	39.7156	5.6966	3.2889
R_q	ELLOR graphite; finish wire EDM	int	3	20.8843	5.2535	3.0331
R_q	ELLOR graphite; rough wire EDM	FV	3	3.7317	1.9497	1.1257
R_q	ELLOR graphite; rough wire EDM	conf	3	14.8497	5.0819	2.934
R_q	ELLOR graphite; rough wire EDM	fusion	3	17.21	5.8845	3.3974
R_q	ELLOR graphite; rough wire EDM	int	4	23.2273	23.596	11.798
R_q	MO58A brass; burnishing after MF	FV	4	266.7328	170.0969	85.0484
R_q	MO58A brass; burnishing after MF	conf	3	193.4323	15.2342	8.7955
R_q	MO58A brass; burnishing after MF	fusion	3	251.6748	19.9749	11.5325
R_q	MO58A brass; burnishing after MF	int	3	337.496	455.0373	262.7159
R_q	MO58A brass; glass bead blasting	FV	3	19.6734	11.3172	6.534
R_q	MO58A brass; glass bead blasting	conf	3	62.1681	31.8502	18.3887
R_q	MO58A brass; glass bead blasting	fusion	3	88.8313	31.1862	18.0054
R_q	MO58A brass; glass bead blasting	int	4	11.4663	5.176	2.588
R_q	MO58A brass; grinding	FV	3	60.1613	19.954	11.5205
R_q	MO58A brass; grinding	conf	3	38.7086	11.0669	6.3895
R_q	MO58A brass; grinding	fusion	3	74.6936	13.724	7.9235
R_q	MO58A brass; grinding	int	4	14.6894	3.4071	1.7035
R_q	MO58A brass; honing	FV	3	43.1859	27.7727	16.0346
R_q	MO58A brass; honing	conf	3	15.1664	14.2768	8.2427
R_q	MO58A brass; honing	fusion	3	47.0778	7.6797	4.4339
R_q	MO58A brass; honing	int	4	3.0732	2.4775	1.2387
R_q	MO58A brass; finish milling	FV	3	174.7394	123.6627	71.3967
R_q	MO58A brass; finish milling	conf	3	160.1774	32.4323	18.7248
R_q	MO58A brass; finish milling	fusion	3	209.4093	43.1133	24.8915
R_q	MO58A brass; finish milling	int	4	100.817	141.5805	70.7902
R_q	MO58A brass; rough milling	FV	3	44.3876	23.5103	13.5737
R_q	MO58A brass; rough milling	conf	3	52.089	3.0867	1.7821
R_q	MO58A brass; rough milling	fusion	3	41.2656	2.9124	1.6814
R_q	MO58A brass; rough milling	int	4	63.6877	5.7121	2.856
R_q	MO58A brass; finish face turning	FV	3	59.569	3.3947	1.9599
R_q	MO58A brass; finish face turning	conf	3	57.7277	2.261	1.3054
R_q	MO58A brass; finish face turning	fusion	3	51.7021	1.8029	1.0409
R_q	MO58A brass; finish face turning	int	4	58.84	1.6139	0.8069
R_q	MO58A brass; rough face turning	FV	3	21.1462	3.8314	2.212
R_q	MO58A brass; rough face turning	conf	3	23.0773	2.9895	1.726
R_q	MO58A brass; rough face turning	fusion	3	16.5525	2.1252	1.227
R_q	MO58A brass; rough face turning	int	4	23.5231	0.8418	0.4209
R_q	MO58A brass; finish wire EDM	FV	3	30.0876	13.1036	7.5654
R_q	MO58A brass; finish wire EDM	conf	3	50.965	21.2216	12.2523
R_q	MO58A brass; finish wire EDM	fusion	3	110.2599	12.3917	7.1544
R_q	MO58A brass; finish wire EDM	int	4	3.0041	0.4532	0.2266
R_q	MO58A brass; rough wire EDM	FV	3	29.0192	3.6755	2.1221
R_q	MO58A brass; rough wire EDM	conf	3	21.6141	11.6316	6.7155
R_q	MO58A brass; rough wire EDM	fusion	3	16.0909	8.6875	5.0158
R_q	MO58A brass; rough wire EDM	int	4	24.3657	7.3324	3.6662
R_q	Ti6Al4V; burnishing after MF	FV	3	109.2095	54.9302	31.714
R_q	Ti6Al4V; burnishing after MF	conf	3	133.0785	41.3298	23.8618
R_q	Ti6Al4V; burnishing after MF	fusion	3	147.6979	41.5851	24.0092
R_q	Ti6Al4V; burnishing after MF	int	4	49.4882	15.6444	7.8222
R_q	Ti6Al4V; glass bead blasting	FV	3	19.2861	15.7444	9.09
R_q	Ti6Al4V; glass bead blasting	conf	3	76.3166	24.3075	14.034

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_q	Ti6Al4V; glass bead blasting	fusion	3	127.3531	25.2215	14.5616
R_q	Ti6Al4V; glass bead blasting	int	4	15.1022	5.5944	2.7972
R_q	Ti6Al4V; grinding	FV	3	87.798	23.3258	13.4672
R_q	Ti6Al4V; grinding	conf	3	98.3864	18.5733	10.7233
R_q	Ti6Al4V; grinding	fusion	3	118.8151	21.9805	12.6905
R_q	Ti6Al4V; grinding	int	4	65.1719	3.3932	1.6966
R_q	Ti6Al4V; honing	FV	3	138.4136	40.1042	23.1542
R_q	Ti6Al4V; honing	conf	3	87.6258	28.1438	16.2488
R_q	Ti6Al4V; honing	fusion	3	137.8728	33.5478	19.3688
R_q	Ti6Al4V; honing	int	4	22.3177	1.357	0.6785
R_q	Ti6Al4V; finish milling	FV	3	35.8532	20.7251	11.9656
R_q	Ti6Al4V; finish milling	conf	3	43.6584	14.9185	8.6132
R_q	Ti6Al4V; finish milling	fusion	3	58.2783	15.396	8.8889
R_q	Ti6Al4V; finish milling	int	4	7.7379	4.0489	2.0244
R_q	Ti6Al4V; rough milling	FV	3	28.7846	0.2763	0.1595
R_q	Ti6Al4V; rough milling	conf	3	14.3986	12.6343	7.2944
R_q	Ti6Al4V; rough milling	fusion	3	9.2119	5.2956	3.0574
R_q	Ti6Al4V; rough milling	int	4	40.0453	21.3182	10.6591
R_q	Ti6Al4V; finish face turning	FV	3	19.394	4.3916	2.5355
R_q	Ti6Al4V; finish face turning	conf	3	19.5161	8.2505	4.7634
R_q	Ti6Al4V; finish face turning	fusion	3	12.3419	8.8349	5.1009
R_q	Ti6Al4V; finish face turning	int	4	19.0702	5.8946	2.9473
R_q	Ti6Al4V; rough face turning	FV	3	68.096	2.1467	1.2394
R_q	Ti6Al4V; rough face turning	conf	3	65.3855	4.3333	2.5018
R_q	Ti6Al4V; rough face turning	fusion	3	61.3162	4.3761	2.5265
R_q	Ti6Al4V; rough face turning	int	4	68.5316	3.6944	1.8472
R_q	Ti6Al4V; finish wire EDM	FV	3	82.0481	24.2085	13.9768
R_q	Ti6Al4V; finish wire EDM	conf	3	130.1027	27.2406	15.7274
R_q	Ti6Al4V; finish wire EDM	fusion	3	209.2674	31.951	18.4469
R_q	Ti6Al4V; finish wire EDM	int	4	17.4224	7.1049	3.5524
R_q	Ti6Al4V; rough wire EDM	FV	3	6.5906	0.8415	0.4858
R_q	Ti6Al4V; rough wire EDM	conf	3	9.6886	5.7452	3.317
R_q	Ti6Al4V; rough wire EDM	fusion	3	37.891	18.7964	10.8521
R_q	Ti6Al4V; rough wire EDM	int	4	9.3634	13.1784	6.5892
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	94.9293	20.4131	11.7855
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	88.97	5.0016	2.8877
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	86.4804	1.2355	0.7133
R_{sk}	AISI 304 / EN 1.4301; burnishing after MF	int	4	93.06	6.0775	3.0388
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	31.3414	30.9182	17.8506
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	138.7888	92.633	53.4817
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	137.87	52.1234	30.0935
R_{sk}	AISI 304 / EN 1.4301; glass bead blasting	int	4	168.3326	39.2538	19.6269
R_{sk}	AISI 304 / EN 1.4301; grinding	FV	3	96.6101	8.8248	5.095
R_{sk}	AISI 304 / EN 1.4301; grinding	conf	3	47.7256	4.0667	2.3479
R_{sk}	AISI 304 / EN 1.4301; grinding	fusion	3	63.8783	32.7102	18.8852
R_{sk}	AISI 304 / EN 1.4301; grinding	int	4	13.7528	10.3039	5.1519
R_{sk}	AISI 304 / EN 1.4301; honing	FV	3	85.949	12.3613	7.1368
R_{sk}	AISI 304 / EN 1.4301; honing	conf	3	182.3157	44.2065	25.5226
R_{sk}	AISI 304 / EN 1.4301; honing	fusion	3	137.2234	68.8882	39.7726
R_{sk}	AISI 304 / EN 1.4301; honing	int	4	83.7549	21.084	10.542
R_{sk}	AISI 304 / EN 1.4301; finish milling	FV	3	159.2593	43.2632	24.978
R_{sk}	AISI 304 / EN 1.4301; finish milling	conf	3	186.8537	12.9968	7.5037
R_{sk}	AISI 304 / EN 1.4301; finish milling	fusion	3	216.0701	21.9965	12.6997

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sk}	AISI 304 / EN 1.4301; finish milling	int	4	115.3819	22.9853	11.4927
R_{sk}	AISI 304 / EN 1.4301; rough milling	FV	3	146.1326	58.2325	33.6206
R_{sk}	AISI 304 / EN 1.4301; rough milling	conf	3	186.6587	28.4666	16.4352
R_{sk}	AISI 304 / EN 1.4301; rough milling	fusion	3	174.0013	19.4948	11.2554
R_{sk}	AISI 304 / EN 1.4301; rough milling	int	4	144.2254	54.7575	27.3787
R_{sk}	AISI 304 / EN 1.4301; finish face turning	FV	3	172.8029	19.1103	11.0333
R_{sk}	AISI 304 / EN 1.4301; finish face turning	conf	3	131.562	7.8149	4.512
R_{sk}	AISI 304 / EN 1.4301; finish face turning	fusion	3	125.1011	7.6466	4.4148
R_{sk}	AISI 304 / EN 1.4301; finish face turning	int	4	134.3218	16.3904	8.1952
R_{sk}	AISI 304 / EN 1.4301; rough face turning	FV	3	360.6028	220.3247	127.2045
R_{sk}	AISI 304 / EN 1.4301; rough face turning	conf	3	688.2924	134.6486	77.7394
R_{sk}	AISI 304 / EN 1.4301; rough face turning	fusion	3	603.5508	182.3578	105.2843
R_{sk}	AISI 304 / EN 1.4301; rough face turning	int	4	883.4517	255.2194	127.6097
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	86.3544	32.9069	18.9988
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	80.1513	37.1741	21.4625
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	223.6587	62.2259	35.9261
R_{sk}	AISI 304 / EN 1.4301; finish wire EDM	int	4	88.6462	55.4963	27.7482
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	60.1779	40.6495	23.469
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	97.3843	36.2942	20.9545
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	129.6347	97.5387	56.314
R_{sk}	AISI 304 / EN 1.4301; rough wire EDM	int	3	14.6946	6.7744	3.9112
R_{sk}	Al7075; burnishing after MF	FV	3	130.0839	83.8297	48.3991
R_{sk}	Al7075; burnishing after MF	conf	3	124.169	4.5743	2.641
R_{sk}	Al7075; burnishing after MF	fusion	3	139.3237	7.5945	4.3847
R_{sk}	Al7075; burnishing after MF	int	4	104.7425	1.6515	0.8257
R_{sk}	Al7075; glass bead blasting	FV	3	20.2444	11.8083	6.8175
R_{sk}	Al7075; glass bead blasting	conf	3	354.3837	135.7152	78.3552
R_{sk}	Al7075; glass bead blasting	fusion	3	194.8762	110.6199	63.8664
R_{sk}	Al7075; glass bead blasting	int	4	29.1113	19.628	9.814
R_{sk}	Al7075; grinding	FV	3	113.0606	7.2011	4.1576
R_{sk}	Al7075; grinding	conf	3	63.6882	8.3019	4.7931
R_{sk}	Al7075; grinding	fusion	3	68.8187	16.5181	9.5367
R_{sk}	Al7075; grinding	int	4	40.7731	18.6452	9.3226
R_{sk}	Al7075; honing	FV	3	493.7797	230.1447	132.8741
R_{sk}	Al7075; honing	conf	3	246.3232	79.6714	45.9983
R_{sk}	Al7075; honing	fusion	3	233.9822	142.4195	82.2259
R_{sk}	Al7075; honing	int	4	500.9985	216.2963	108.1482
R_{sk}	Al7075; finish milling	FV	3	105.8195	21.0262	12.1395
R_{sk}	Al7075; finish milling	conf	3	104.1977	8.0611	4.6541
R_{sk}	Al7075; finish milling	fusion	3	106.7215	4.9337	2.8485
R_{sk}	Al7075; finish milling	int	4	100.4695	2.7919	1.3959
R_{sk}	Al7075; rough milling	FV	3	790.5903	831.8559	480.2722
R_{sk}	Al7075; rough milling	conf	3	93.2626	127.1246	73.3954

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sk}	Al7075; rough milling	fusion	3	178.8954	130.1782	75.1584
R_{sk}	Al7075; rough milling	int	4	468.2437	306.5446	153.2723
R_{sk}	Al7075; finish face turning	FV	3	125.633	22.8352	13.1839
R_{sk}	Al7075; finish face turning	conf	3	106.2382	0.4979	0.2874
R_{sk}	Al7075; finish face turning	fusion	3	115.529	2.8793	1.6624
R_{sk}	Al7075; finish face turning	int	4	109.2479	7.4586	3.7293
R_{sk}	Al7075; rough face turning	FV	3	30.4336	15.8692	9.1621
R_{sk}	Al7075; rough face turning	conf	3	33.5721	14.468	8.3531
R_{sk}	Al7075; rough face turning	fusion	3	41.4641	28.6386	16.5345
R_{sk}	Al7075; rough face turning	int	4	25.7212	19.5579	9.7789
R_{sk}	Al7075; finish wire EDM	FV	3	248.9498	38.6216	22.2982
R_{sk}	Al7075; finish wire EDM	conf	3	218.3058	120.2557	69.4296
R_{sk}	Al7075; finish wire EDM	fusion	3	224.2557	168.0284	97.0113
R_{sk}	Al7075; finish wire EDM	int	4	72.2019	58.4774	29.2387
R_{sk}	Al7075; rough wire EDM	FV	3	17.5398	14.1808	8.1873
R_{sk}	Al7075; rough wire EDM	conf	3	427.8525	312.5508	180.4513
R_{sk}	Al7075; rough wire EDM	fusion	3	1183.6765	380.4813	219.671
R_{sk}	Al7075; rough wire EDM	int	4	113.0277	112.9425	56.4712
R_{sk}	C45 steel; burnishing after MF	FV	3	81.2532	55.9736	32.3164
R_{sk}	C45 steel; burnishing after MF	conf	2	65.8281	0.3448	0.2438
R_{sk}	C45 steel; burnishing after MF	fusion	3	56.1492	19.9078	11.4937
R_{sk}	C45 steel; burnishing after MF	int	5	110.2536	2.4123	1.0788
R_{sk}	C45 steel; glass bead blasting	FV	3	31.0746	32.6917	18.8746
R_{sk}	C45 steel; glass bead blasting	conf	3	278.0553	154.8822	89.4213
R_{sk}	C45 steel; glass bead blasting	fusion	3	252.7663	219.9194	126.9705
R_{sk}	C45 steel; glass bead blasting	int	4	63.0849	14.1424	7.0712
R_{sk}	C45 steel; grinding	FV	3	113.9951	14.5662	8.4098
R_{sk}	C45 steel; grinding	conf	3	58.6155	7.8761	4.5472
R_{sk}	C45 steel; grinding	fusion	3	63.7891	14.7279	8.5031
R_{sk}	C45 steel; grinding	int	4	23.6623	21.0508	10.5254
R_{sk}	C45 steel; honing	FV	3	52.8661	18.9389	10.9344
R_{sk}	C45 steel; honing	conf	3	233.08	66.2116	38.2273
R_{sk}	C45 steel; honing	fusion	3	171.2495	133.3781	77.0059
R_{sk}	C45 steel; honing	int	4	98.3154	42.5982	21.2991
R_{sk}	C45 steel; finish milling	FV	3	107.2956	28.2569	16.3141
R_{sk}	C45 steel; finish milling	conf	2	33.2093	1.6271	1.1505
R_{sk}	C45 steel; finish milling	fusion	3	41.5644	27.49	15.8713
R_{sk}	C45 steel; finish milling	int	4	70.1217	10.3692	5.1846
R_{sk}	C45 steel; rough milling	FV	3	74.365	38.8742	22.444
R_{sk}	C45 steel; rough milling	conf	2	32.8332	24.2517	17.1486
R_{sk}	C45 steel; rough milling	fusion	3	97.2734	41.5062	23.9636
R_{sk}	C45 steel; rough milling	int	4	152.406	38.0291	19.0146
R_{sk}	C45 steel; finish face turning	FV	3	137.5419	5.1645	2.9817
R_{sk}	C45 steel; finish face turning	conf	2	93.0825	22.3642	15.8139
R_{sk}	C45 steel; finish face turning	fusion	3	94.6938	55.6203	32.1124
R_{sk}	C45 steel; finish face turning	int	4	183.8556	15.9464	7.9732
R_{sk}	C45 steel; rough face turning	FV	3	485.3536	175.0164	101.0458
R_{sk}	C45 steel; rough face turning	conf	2	237.2865	49.77	35.1927
R_{sk}	C45 steel; rough face turning	fusion	3	164.6625	234.9469	135.6467
R_{sk}	C45 steel; rough face turning	int	4	139.2778	163.915	81.9575
R_{sk}	C45 steel; finish wire EDM	FV	3	27.8164	31.9794	18.4633
R_{sk}	C45 steel; finish wire EDM	conf	3	123.5685	60.2946	34.8111
R_{sk}	C45 steel; finish wire EDM	fusion	3	148.52	213.8101	123.4433
R_{sk}	C45 steel; finish wire EDM	int	4	63.1872	26.5901	13.295
R_{sk}	C45 steel; rough wire EDM	FV	3	62.442	58.0706	33.5271
R_{sk}	C45 steel; rough wire EDM	conf	3	95.5821	81.0957	46.8206
R_{sk}	C45 steel; rough wire EDM	fusion	3	509.9976	477.2231	275.5249
R_{sk}	C45 steel; rough wire EDM	int	4	9.5715	7.2167	3.6083
R_{sk}	ELLOR graphite; glass bead blasting	FV	3	64.6281	1.201	0.6934
R_{sk}	ELLOR graphite; glass bead blasting	conf	3	65.3451	1.9924	1.1503
R_{sk}	ELLOR graphite; glass bead blasting	fusion	3	65.8705	0.6131	0.354

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sk}	ELLOR graphite; glass bead blasting	int	4	63.9661	8.5266	4.2633
R_{sk}	ELLOR graphite; grinding	FV	3	2.6817	1.5685	0.9056
R_{sk}	ELLOR graphite; grinding	conf	3	9.9974	4.4267	2.5558
R_{sk}	ELLOR graphite; grinding	fusion	3	13.1906	4.8406	2.7947
R_{sk}	ELLOR graphite; grinding	int	4	25.7941	35.0861	17.543
R_{sk}	ELLOR graphite; honing	FV	3	92.7167	13.331	7.6966
R_{sk}	ELLOR graphite; honing	conf	3	75.308	16.0579	9.271
R_{sk}	ELLOR graphite; honing	fusion	3	84.4143	29.2887	16.9099
R_{sk}	ELLOR graphite; honing	int	4	48.0812	36.1353	18.0676
R_{sk}	ELLOR graphite; finish milling	FV	3	45.3637	16.0338	9.2571
R_{sk}	ELLOR graphite; finish milling	conf	3	41.1589	5.8536	3.3796
R_{sk}	ELLOR graphite; finish milling	fusion	3	53.1785	23.8922	13.7941
R_{sk}	ELLOR graphite; finish milling	int	4	38.7198	40.9877	20.4938
R_{sk}	ELLOR graphite; rough milling	FV	3	22.7971	6.8834	3.9741
R_{sk}	ELLOR graphite; rough milling	conf	3	32.9695	7.3866	4.2646
R_{sk}	ELLOR graphite; rough milling	fusion	3	46.5626	3.4073	1.9672
R_{sk}	ELLOR graphite; rough milling	int	4	27.0337	47.3934	23.6967
R_{sk}	ELLOR graphite; finish face turning	FV	3	55.4514	5.1311	2.9625
R_{sk}	ELLOR graphite; finish face turning	conf	3	53.7351	4.2783	2.4701
R_{sk}	ELLOR graphite; finish face turning	fusion	3	73.807	5.5258	3.1903
R_{sk}	ELLOR graphite; finish face turning	int	4	43.2632	44.692	22.346
R_{sk}	ELLOR graphite; rough face turning	FV	3	34.4663	3.1979	1.8463
R_{sk}	ELLOR graphite; rough face turning	conf	3	22.3609	3.6135	2.0862
R_{sk}	ELLOR graphite; rough face turning	fusion	3	19.0208	2.1188	1.2233
R_{sk}	ELLOR graphite; rough face turning	int	4	33.0508	6.5598	3.2799
R_{sk}	ELLOR graphite; finish wire EDM	FV	3	34.7157	2.1696	1.2526
R_{sk}	ELLOR graphite; finish wire EDM	conf	3	36.7133	4.9038	2.8312
R_{sk}	ELLOR graphite; finish wire EDM	fusion	3	48.7868	3.5136	2.0286
R_{sk}	ELLOR graphite; finish wire EDM	int	3	18.0792	1.0671	0.6161
R_{sk}	ELLOR graphite; rough wire EDM	FV	3	41.7346	3.3761	1.9492
R_{sk}	ELLOR graphite; rough wire EDM	conf	3	44.1619	3.3714	1.9465
R_{sk}	ELLOR graphite; rough wire EDM	fusion	3	52.5272	2.7551	1.5907
R_{sk}	ELLOR graphite; rough wire EDM	int	4	46.3182	33.7261	16.863
R_{sk}	MO58A brass; burnishing after MF	FV	4	64.0138	41.9882	20.9941
R_{sk}	MO58A brass; burnishing after MF	conf	3	49.2165	12.5675	7.2558
R_{sk}	MO58A brass; burnishing after MF	fusion	3	42.6846	21.9218	12.6566
R_{sk}	MO58A brass; burnishing after MF	int	3	99.4429	2.8602	1.6514
R_{sk}	MO58A brass; glass bead blasting	FV	3	51.0286	7.8683	4.5428
R_{sk}	MO58A brass; glass bead blasting	conf	3	376.6713	267.9869	154.7223
R_{sk}	MO58A brass; glass bead blasting	fusion	3	363.9765	260.9103	150.6366
R_{sk}	MO58A brass; glass bead blasting	int	4	15.7948	21.2739	10.637
R_{sk}	MO58A brass; grinding	FV	3	95.1142	11.5435	6.6647
R_{sk}	MO58A brass; grinding	conf	3	42.8855	6.7048	3.871
R_{sk}	MO58A brass; grinding	fusion	3	67.7822	40.5686	23.4223
R_{sk}	MO58A brass; grinding	int	4	17.0062	10.7485	5.3743
R_{sk}	MO58A brass; honing	FV	3	379.936	165.0246	95.277
R_{sk}	MO58A brass; honing	conf	3	677.977	210.784	121.6962
R_{sk}	MO58A brass; honing	fusion	3	693.7961	299.0967	172.6836
R_{sk}	MO58A brass; honing	int	4	331.8981	45.7157	22.8578
R_{sk}	MO58A brass; finish milling	FV	3	109.3984	84.7236	48.9152
R_{sk}	MO58A brass; finish milling	conf	3	83.5736	38.2678	22.0939

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sk}	MO58A brass; finish milling	fusion	3	86.1824	22.3163	12.8843
R_{sk}	MO58A brass; finish milling	int	4	154.2087	55.0447	27.5223
R_{sk}	MO58A brass; rough milling	FV	3	35.8532	28.4923	16.45
R_{sk}	MO58A brass; rough milling	conf	3	61.0436	38.5896	22.2797
R_{sk}	MO58A brass; rough milling	fusion	3	70.1649	73.9751	42.7095
R_{sk}	MO58A brass; rough milling	int	4	66.3279	9.6857	4.8429
R_{sk}	MO58A brass; finish face turning	FV	3	54.1875	35.9375	20.7485
R_{sk}	MO58A brass; finish face turning	conf	3	61.248	61.7649	35.66
R_{sk}	MO58A brass; finish face turning	fusion	3	106.5728	124.4549	71.8541
R_{sk}	MO58A brass; finish face turning	int	4	152.6323	18.481	9.2405
R_{sk}	MO58A brass; rough face turning	FV	3	45.4628	8.4596	4.8842
R_{sk}	MO58A brass; rough face turning	conf	3	40.6647	15.035	8.6805
R_{sk}	MO58A brass; rough face turning	fusion	3	67.6374	87.3985	50.4596
R_{sk}	MO58A brass; rough face turning	int	4	58.0901	5.7004	2.8502
R_{sk}	MO58A brass; finish wire EDM	FV	3	353.2992	46.7057	26.9655
R_{sk}	MO58A brass; finish wire EDM	conf	3	88.7402	131.5453	75.9477
R_{sk}	MO58A brass; finish wire EDM	fusion	3	37.3351	35.5135	20.5037
R_{sk}	MO58A brass; finish wire EDM	int	4	58.8385	43.6584	21.8292
R_{sk}	MO58A brass; rough wire EDM	FV	3	208.6691	114.711	66.2285
R_{sk}	MO58A brass; rough wire EDM	conf	3	579.1569	351.8565	203.1444
R_{sk}	MO58A brass; rough wire EDM	fusion	3	671.5845	599.3617	346.0417
R_{sk}	MO58A brass; rough wire EDM	int	4	449.5294	260.7711	130.3855
R_{sk}	Ti6Al4V; burnishing after MF	FV	3	19.7302	20.2263	11.6776
R_{sk}	Ti6Al4V; burnishing after MF	conf	3	18.9032	14.7149	8.4957
R_{sk}	Ti6Al4V; burnishing after MF	fusion	3	18.6286	12.4687	7.1988
R_{sk}	Ti6Al4V; burnishing after MF	int	4	71.0218	70.0679	35.034
R_{sk}	Ti6Al4V; glass bead blasting	FV	3	58.7139	10.6101	6.1257
R_{sk}	Ti6Al4V; glass bead blasting	conf	3	128.6565	56.0692	32.3716
R_{sk}	Ti6Al4V; glass bead blasting	fusion	3	101.8949	75.7285	43.7219
R_{sk}	Ti6Al4V; glass bead blasting	int	4	139.8833	27.4017	13.7009
R_{sk}	Ti6Al4V; grinding	FV	3	68.0074	41.1469	23.7562
R_{sk}	Ti6Al4V; grinding	conf	3	193.7314	12.2063	7.0473
R_{sk}	Ti6Al4V; grinding	fusion	3	182.5652	43.1301	24.9012
R_{sk}	Ti6Al4V; grinding	int	4	256.6456	52.6433	26.3217
R_{sk}	Ti6Al4V; honing	FV	3	49.3191	22.6624	13.0841
R_{sk}	Ti6Al4V; honing	conf	3	178.1022	33.9387	19.5945
R_{sk}	Ti6Al4V; honing	fusion	3	171.3215	61.2239	35.3476
R_{sk}	Ti6Al4V; honing	int	4	137.6371	4.2201	2.1101
R_{sk}	Ti6Al4V; finish milling	FV	3	125.9224	27.9339	16.1277
R_{sk}	Ti6Al4V; finish milling	conf	3	120.7291	25.1135	14.4993
R_{sk}	Ti6Al4V; finish milling	fusion	3	121.9234	36.5251	21.0878
R_{sk}	Ti6Al4V; finish milling	int	4	105.1008	3.9972	1.9986
R_{sk}	Ti6Al4V; rough milling	FV	3	92.9481	39.2472	22.6594
R_{sk}	Ti6Al4V; rough milling	conf	3	104.8243	4.5211	2.6102
R_{sk}	Ti6Al4V; rough milling	fusion	3	118.0007	12.7449	7.3583
R_{sk}	Ti6Al4V; rough milling	int	4	105.2758	12.2671	6.1335
R_{sk}	Ti6Al4V; finish face turning	FV	3	38.4607	2.9043	1.6768
R_{sk}	Ti6Al4V; finish face turning	conf	3	35.6847	6.9167	3.9934
R_{sk}	Ti6Al4V; finish face turning	fusion	3	45.8104	9.616	5.5518
R_{sk}	Ti6Al4V; finish face turning	int	4	32.1181	12.2478	6.1239
R_{sk}	Ti6Al4V; rough face turning	FV	3	18.2738	17.7645	10.2564
R_{sk}	Ti6Al4V; rough face turning	conf	3	47.9292	30.9115	17.8468
R_{sk}	Ti6Al4V; rough face turning	fusion	3	59.5073	50.2509	29.0124
R_{sk}	Ti6Al4V; rough face turning	int	4	22.7926	14.7694	7.3847
R_{sk}	Ti6Al4V; finish wire EDM	FV	3	17.9457	22.8385	13.1858
R_{sk}	Ti6Al4V; finish wire EDM	conf	3	89.1603	21.4492	12.3837
R_{sk}	Ti6Al4V; finish wire EDM	fusion	3	80.1416	46.9941	27.132
R_{sk}	Ti6Al4V; finish wire EDM	int	4	171.7288	47.3199	23.66
R_{sk}	Ti6Al4V; rough wire EDM	FV	3	17.6386	13.0559	7.5378
R_{sk}	Ti6Al4V; rough wire EDM	conf	3	128.7699	123.6663	71.3987
R_{sk}	Ti6Al4V; rough wire EDM	fusion	3	386.8725	253.2	146.1851
R_{sk}	Ti6Al4V; rough wire EDM	int	4	18.2246	7.7444	3.8722
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	99.9612	0.0023	0.0013

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	99.9791	0.0012	6.7825e-04
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	99.9824	0.001	6.0065e-04
R_{sm}	AISI 304 / EN 1.4301; burnishing after MF	int	4	99.9628	0.0069	0.0034
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	99.947	0.0014	7.8517e-04
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	99.9718	0.0023	0.0013
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	99.9753	0.002	0.0011
R_{sm}	AISI 304 / EN 1.4301; glass bead blasting	int	4	99.9531	0.0055	0.0028
R_{sm}	AISI 304 / EN 1.4301; grinding	FV	3	99.9078	0.0018	0.0011
R_{sm}	AISI 304 / EN 1.4301; grinding	conf	3	99.9524	0.002	0.0012
R_{sm}	AISI 304 / EN 1.4301; grinding	fusion	3	99.9621	0.002	0.0012
R_{sm}	AISI 304 / EN 1.4301; grinding	int	4	99.9284	0.0125	0.0063
R_{sm}	AISI 304 / EN 1.4301; honing	FV	3	99.8741	0.0019	0.0011
R_{sm}	AISI 304 / EN 1.4301; honing	conf	3	99.9476	0.0043	0.0025
R_{sm}	AISI 304 / EN 1.4301; honing	fusion	3	99.9582	0.005	0.0029
R_{sm}	AISI 304 / EN 1.4301; honing	int	4	99.9088	0.0193	0.0097
R_{sm}	AISI 304 / EN 1.4301; finish milling	FV	3	99.9555	0.001	5.8439e-04
R_{sm}	AISI 304 / EN 1.4301; finish milling	conf	3	99.9731	0.0014	7.9578e-04
R_{sm}	AISI 304 / EN 1.4301; finish milling	fusion	3	99.9798	0.001	5.8816e-04
R_{sm}	AISI 304 / EN 1.4301; finish milling	int	4	99.9524	0.0198	0.0099
R_{sm}	AISI 304 / EN 1.4301; rough milling	FV	3	99.9821	0.0022	0.0013
R_{sm}	AISI 304 / EN 1.4301; rough milling	conf	3	99.985	0.0025	0.0015
R_{sm}	AISI 304 / EN 1.4301; rough milling	fusion	3	99.9864	0.0026	0.0015
R_{sm}	AISI 304 / EN 1.4301; rough milling	int	4	99.9769	0.0102	0.0051
R_{sm}	AISI 304 / EN 1.4301; finish face turning	FV	3	99.851	0.0086	0.0049
R_{sm}	AISI 304 / EN 1.4301; finish face turning	conf	3	99.8652	0.0208	0.012
R_{sm}	AISI 304 / EN 1.4301; finish face turning	fusion	3	99.8861	0.0208	0.012
R_{sm}	AISI 304 / EN 1.4301; finish face turning	int	4	99.7314	0.1693	0.0846
R_{sm}	AISI 304 / EN 1.4301; rough face turning	FV	3	99.8947	0.0105	0.0061
R_{sm}	AISI 304 / EN 1.4301; rough face turning	conf	3	99.8873	0.0081	0.0047
R_{sm}	AISI 304 / EN 1.4301; rough face turning	fusion	3	99.9111	0.0085	0.0049
R_{sm}	AISI 304 / EN 1.4301; rough face turning	int	4	99.8238	0.1102	0.0551
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	99.8935	6.3750e-04	3.6806e-04
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	99.9486	2.7738e-04	1.6015e-04
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	99.9554	0.0015	8.7015e-04
R_{sm}	AISI 304 / EN 1.4301; finish wire EDM	int	4	99.9201	0.0128	0.0064
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	99.919	0.0027	0.0016

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	99.9363	0.0024	0.0014
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	99.9428	0.0029	0.0017
R_{sm}	AISI 304 / EN 1.4301; rough wire EDM	int	3	99.9397	0.0028	0.0016
R_{sm}	Al7075; burnishing after MF	FV	3	99.9565	0.0033	0.0019
R_{sm}	Al7075; burnishing after MF	conf	3	99.9785	0.0014	8.0306e-04
R_{sm}	Al7075; burnishing after MF	fusion	3	99.9826	0.0016	8.9954e-04
R_{sm}	Al7075; burnishing after MF	int	4	99.9463	0.018	0.009
R_{sm}	Al7075; glass bead blasting	FV	3	99.9247	0.0049	0.0028
R_{sm}	Al7075; glass bead blasting	conf	3	99.9601	6.2344e-04	3.5994e-04
R_{sm}	Al7075; glass bead blasting	fusion	3	99.9635	0.0017	9.8600e-04
R_{sm}	Al7075; glass bead blasting	int	4	99.9332	0.0013	6.4433e-04
R_{sm}	Al7075; grinding	FV	3	99.9354	8.3757e-04	4.8357e-04
R_{sm}	Al7075; grinding	conf	3	99.9687	8.3900e-04	4.8440e-04
R_{sm}	Al7075; grinding	fusion	3	99.9754	6.1892e-04	3.5733e-04
R_{sm}	Al7075; grinding	int	4	99.9392	0.0061	0.0031
R_{sm}	Al7075; honing	FV	3	99.903	0.0032	0.0019
R_{sm}	Al7075; honing	conf	3	99.9575	0.0019	0.0011
R_{sm}	Al7075; honing	fusion	3	99.9659	0.0014	8.0333e-04
R_{sm}	Al7075; honing	int	4	99.9252	0.0093	0.0046
R_{sm}	Al7075; finish milling	FV	3	99.9739	0.0017	9.7965e-04
R_{sm}	Al7075; finish milling	conf	3	99.9871	8.1135e-04	4.6843e-04
R_{sm}	Al7075; finish milling	fusion	3	99.9894	0.0011	6.3461e-04
R_{sm}	Al7075; finish milling	int	4	99.9811	0.0018	8.7502e-04
R_{sm}	Al7075; rough milling	FV	3	99.9276	0.0049	0.0028
R_{sm}	Al7075; rough milling	conf	3	99.9389	0.0154	0.0089
R_{sm}	Al7075; rough milling	fusion	3	99.9418	0.0146	0.0084
R_{sm}	Al7075; rough milling	int	4	99.8642	0.0321	0.0161
R_{sm}	Al7075; finish face turning	FV	3	99.9142	0.0091	0.0052
R_{sm}	Al7075; finish face turning	conf	3	99.9293	0.0091	0.0052
R_{sm}	Al7075; finish face turning	fusion	3	99.9424	0.0083	0.0048
R_{sm}	Al7075; finish face turning	int	4	99.8507	0.0868	0.0434
R_{sm}	Al7075; rough face turning	FV	3	99.8867	0.0176	0.0101
R_{sm}	Al7075; rough face turning	conf	3	99.8942	0.0058	0.0034
R_{sm}	Al7075; rough face turning	fusion	3	99.9253	0.0031	0.0018
R_{sm}	Al7075; rough face turning	int	4	99.783	0.1372	0.0686
R_{sm}	Al7075; finish wire EDM	FV	3	99.872	0.0011	6.2473e-04
R_{sm}	Al7075; finish wire EDM	conf	3	99.9411	0.0044	0.0026
R_{sm}	Al7075; finish wire EDM	fusion	3	99.95	0.0083	0.0048
R_{sm}	Al7075; finish wire EDM	int	4	99.9159	0.007	0.0035
R_{sm}	Al7075; rough wire EDM	FV	3	99.9228	0.0012	6.8368e-04
R_{sm}	Al7075; rough wire EDM	conf	3	99.9469	6.0867e-04	3.5142e-04
R_{sm}	Al7075; rough wire EDM	fusion	3	99.9521	0.0017	9.8314e-04
R_{sm}	Al7075; rough wire EDM	int	4	99.9308	0.012	0.006
R_{sm}	C45 steel; burnishing after MF	FV	3	99.9555	0.0016	9.1296e-04
R_{sm}	C45 steel; burnishing after MF	conf	2	99.9754	9.4888e-04	6.7096e-04
R_{sm}	C45 steel; burnishing after MF	fusion	3	99.9792	5.0048e-04	2.8895e-04
R_{sm}	C45 steel; burnishing after MF	int	5	99.9605	0.0098	0.0044
R_{sm}	C45 steel; glass bead blasting	FV	3	99.9416	0.0031	0.0018
R_{sm}	C45 steel; glass bead blasting	conf	3	99.9679	0.0017	0.001
R_{sm}	C45 steel; glass bead blasting	fusion	3	99.9722	0.002	0.0012
R_{sm}	C45 steel; glass bead blasting	int	4	99.9439	0.0051	0.0025
R_{sm}	C45 steel; grinding	FV	3	99.9218	0.0018	0.001
R_{sm}	C45 steel; grinding	conf	3	99.9613	8.1010e-04	4.6771e-04
R_{sm}	C45 steel; grinding	fusion	3	99.9695	6.1490e-04	3.5501e-04
R_{sm}	C45 steel; grinding	int	4	99.9273	0.007	0.0035
R_{sm}	C45 steel; honing	FV	3	99.8756	0.003	0.0018
R_{sm}	C45 steel; honing	conf	3	99.945	0.0044	0.0025
R_{sm}	C45 steel; honing	fusion	3	99.9577	0.0046	0.0026
R_{sm}	C45 steel; honing	int	4	99.9077	0.0209	0.0104
R_{sm}	C45 steel; finish milling	FV	3	99.9379	5.2819e-04	3.0495e-04
R_{sm}	C45 steel; finish milling	conf	2	99.9615	4.7706e-04	3.3733e-04

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sm}	C45 steel; finish milling	fusion	3	99.9674	0.0012	7.0766e-04
R_{sm}	C45 steel; finish milling	int	4	99.9332	0.0093	0.0046
R_{sm}	C45 steel; rough milling	FV	3	99.9519	0.0061	0.0035
R_{sm}	C45 steel; rough milling	conf	2	99.9648	0.0017	0.0012
R_{sm}	C45 steel; rough milling	fusion	3	99.9739	9.0624e-04	5.2322e-04
R_{sm}	C45 steel; rough milling	int	4	99.935	0.0197	0.0098
R_{sm}	C45 steel; finish face turning	FV	3	99.933	0.0071	0.0041
R_{sm}	C45 steel; finish face turning	conf	2	99.9504	0.0018	0.0013
R_{sm}	C45 steel; finish face turning	fusion	3	99.9629	9.3366e-04	5.3905e-04
R_{sm}	C45 steel; finish face turning	int	4	99.9037	0.0301	0.0151
R_{sm}	C45 steel; rough face turning	FV	3	99.9585	0.0139	0.008
R_{sm}	C45 steel; rough face turning	conf	2	99.9484	0.0037	0.0026
R_{sm}	C45 steel; rough face turning	fusion	3	99.9599	0.0077	0.0045
R_{sm}	C45 steel; rough face turning	int	4	99.909	0.0591	0.0296
R_{sm}	C45 steel; finish wire EDM	FV	3	99.8903	0.0016	8.9626e-04
R_{sm}	C45 steel; finish wire EDM	conf	3	99.9448	0.0021	0.0012
R_{sm}	C45 steel; finish wire EDM	fusion	3	99.9509	0.0041	0.0024
R_{sm}	C45 steel; finish wire EDM	int	4	99.9087	0.0145	0.0073
R_{sm}	C45 steel; rough wire EDM	FV	3	99.9186	7.9252e-04	4.5756e-04
R_{sm}	C45 steel; rough wire EDM	conf	3	99.9449	0.0043	0.0025
R_{sm}	C45 steel; rough wire EDM	fusion	3	99.9446	0.0017	9.7615e-04
R_{sm}	C45 steel; rough wire EDM	int	4	99.9195	0.0437	0.0218
R_{sm}	ELLOR graphite; glass bead blasting	FV	3	99.9047	0.0016	9.1455e-04
R_{sm}	ELLOR graphite; glass bead blasting	conf	3	99.9327	0.0043	0.0025
R_{sm}	ELLOR graphite; glass bead blasting	fusion	3	99.9492	0.0046	0.0026
R_{sm}	ELLOR graphite; glass bead blasting	int	4	99.9101	0.0292	0.0146
R_{sm}	ELLOR graphite; grinding	FV	3	99.8013	0.0119	0.0069
R_{sm}	ELLOR graphite; grinding	conf	3	99.8672	0.0156	0.009
R_{sm}	ELLOR graphite; grinding	fusion	3	99.907	0.0129	0.0075
R_{sm}	ELLOR graphite; grinding	int	4	99.7977	0.0721	0.0361
R_{sm}	ELLOR graphite; honing	FV	3	99.9353	0.0021	0.0012
R_{sm}	ELLOR graphite; honing	conf	3	99.9661	0.002	0.0011
R_{sm}	ELLOR graphite; honing	fusion	3	99.9722	0.0013	7.3682e-04
R_{sm}	ELLOR graphite; honing	int	4	99.9432	0.0082	0.0041
R_{sm}	ELLOR graphite; finish milling	FV	3	99.952	0.0044	0.0025
R_{sm}	ELLOR graphite; finish milling	conf	3	99.9737	0.001	5.9874e-04
R_{sm}	ELLOR graphite; finish milling	fusion	3	99.9811	0.0022	0.0012
R_{sm}	ELLOR graphite; finish milling	int	4	99.943	0.0241	0.0121
R_{sm}	ELLOR graphite; rough milling	FV	3	99.9347	0.0056	0.0032
R_{sm}	ELLOR graphite; rough milling	conf	3	99.9644	0.0037	0.0022
R_{sm}	ELLOR graphite; rough milling	fusion	3	99.9771	0.002	0.0012
R_{sm}	ELLOR graphite; rough milling	int	4	99.9372	0.0157	0.0078
R_{sm}	ELLOR graphite; finish face turning	FV	3	99.9339	0.004	0.0023
R_{sm}	ELLOR graphite; finish face turning	conf	3	99.9658	0.0024	0.0014
R_{sm}	ELLOR graphite; finish face turning	fusion	3	99.9754	0.0015	8.5611e-04
R_{sm}	ELLOR graphite; finish face turning	int	4	99.938	0.0033	0.0016
R_{sm}	ELLOR graphite; rough face turning	FV	3	99.919	0.0025	0.0015
R_{sm}	ELLOR graphite; rough face turning	conf	3	99.9424	0.0044	0.0026
R_{sm}	ELLOR graphite; rough face turning	fusion	3	99.9565	0.0048	0.0028
R_{sm}	ELLOR graphite; rough face turning	int	4	99.9305	0.0185	0.0093
R_{sm}	ELLOR graphite; finish wire EDM	FV	3	99.9285	0.0034	0.002
R_{sm}	ELLOR graphite; finish wire EDM	conf	3	99.9616	0.0053	0.0031

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sm}	ELLOR graphite; finish wire EDM	fusion	3	99.9736	0.0028	0.0016
R_{sm}	ELLOR graphite; finish wire EDM	int	3	99.9437	0.0034	0.002
R_{sm}	ELLOR graphite; rough wire EDM	FV	3	99.9353	0.0036	0.0021
R_{sm}	ELLOR graphite; rough wire EDM	conf	3	99.9632	0.0044	0.0025
R_{sm}	ELLOR graphite; rough wire EDM	fusion	3	99.9754	0.0029	0.0017
R_{sm}	ELLOR graphite; rough wire EDM	int	4	99.9278	0.0375	0.0187
R_{sm}	MO58A brass; burnishing after MF	FV	4	99.9648	0.0292	0.0146
R_{sm}	MO58A brass; burnishing after MF	conf	3	99.9906	4.7975e-04	2.7698e-04
R_{sm}	MO58A brass; burnishing after MF	fusion	3	99.9921	4.4942e-04	2.5947e-04
R_{sm}	MO58A brass; burnishing after MF	int	3	99.9768	0.0072	0.0042
R_{sm}	MO58A brass; glass bead blasting	FV	3	99.9192	0.0036	0.0021
R_{sm}	MO58A brass; glass bead blasting	conf	3	99.9579	0.0033	0.0019
R_{sm}	MO58A brass; glass bead blasting	fusion	3	99.9626	0.0039	0.0022
R_{sm}	MO58A brass; glass bead blasting	int	4	99.9238	0.0013	6.3700e-04
R_{sm}	MO58A brass; grinding	FV	3	99.8969	0.0014	7.9032e-04
R_{sm}	MO58A brass; grinding	conf	3	99.9481	0.0018	0.001
R_{sm}	MO58A brass; grinding	fusion	3	99.9584	0.0027	0.0016
R_{sm}	MO58A brass; grinding	int	4	99.9188	0.0156	0.0078
R_{sm}	MO58A brass; honing	FV	3	99.8985	0.0013	7.7379e-04
R_{sm}	MO58A brass; honing	conf	3	99.9531	0.0029	0.0017
R_{sm}	MO58A brass; honing	fusion	3	99.964	0.0022	0.0013
R_{sm}	MO58A brass; honing	int	4	99.9248	0.017	0.0085
R_{sm}	MO58A brass; finish milling	FV	3	99.9626	0.0022	0.0013
R_{sm}	MO58A brass; finish milling	conf	3	99.9805	5.5916e-04	3.2283e-04
R_{sm}	MO58A brass; finish milling	fusion	3	99.9837	0.0014	8.1874e-04
R_{sm}	MO58A brass; finish milling	int	4	99.9718	0.0046	0.0023
R_{sm}	MO58A brass; rough milling	FV	3	99.9376	0.0067	0.0039
R_{sm}	MO58A brass; rough milling	conf	3	99.9397	0.0097	0.0056
R_{sm}	MO58A brass; rough milling	fusion	3	99.9484	0.0104	0.006
R_{sm}	MO58A brass; rough milling	int	4	99.8736	0.074	0.037
R_{sm}	MO58A brass; finish face turning	FV	3	99.9211	0.0151	0.0087
R_{sm}	MO58A brass; finish face turning	conf	3	99.9354	0.0048	0.0028
R_{sm}	MO58A brass; finish face turning	fusion	3	99.9512	0.0037	0.0022
R_{sm}	MO58A brass; finish face turning	int	4	99.8795	0.0379	0.019
R_{sm}	MO58A brass; rough face turning	FV	3	99.8828	0.0209	0.0121
R_{sm}	MO58A brass; rough face turning	conf	3	99.9094	0.0042	0.0024
R_{sm}	MO58A brass; rough face turning	fusion	3	99.9355	0.0011	6.5103e-04
R_{sm}	MO58A brass; rough face turning	int	4	99.8619	0.0359	0.0179
R_{sm}	MO58A brass; finish wire EDM	FV	3	99.8862	0.0015	8.4275e-04
R_{sm}	MO58A brass; finish wire EDM	conf	3	99.9424	0.0106	0.0061
R_{sm}	MO58A brass; finish wire EDM	fusion	3	99.9539	0.0053	0.003
R_{sm}	MO58A brass; finish wire EDM	int	4	99.92	0.0109	0.0054
R_{sm}	MO58A brass; rough wire EDM	FV	3	99.9204	0.0021	0.0012
R_{sm}	MO58A brass; rough wire EDM	conf	3	99.9512	0.0106	0.0061
R_{sm}	MO58A brass; rough wire EDM	fusion	3	99.956	0.0123	0.0071
R_{sm}	MO58A brass; rough wire EDM	int	4	99.9346	0.0168	0.0084
R_{sm}	Ti6Al4V; burnishing after MF	FV	3	99.9697	0.0012	6.8761e-04
R_{sm}	Ti6Al4V; burnishing after MF	conf	3	99.9786	2.3349e-04	1.3480e-04
R_{sm}	Ti6Al4V; burnishing after MF	fusion	3	99.9829	9.1351e-04	5.2742e-04
R_{sm}	Ti6Al4V; burnishing after MF	int	4	99.967	0.0119	0.006
R_{sm}	Ti6Al4V; glass bead blasting	FV	3	99.9301	0.0029	0.0017
R_{sm}	Ti6Al4V; glass bead blasting	conf	3	99.9638	0.0014	8.0998e-04
R_{sm}	Ti6Al4V; glass bead blasting	fusion	3	99.9689	0.0013	7.7808e-04
R_{sm}	Ti6Al4V; glass bead blasting	int	4	99.9368	0.0085	0.0043
R_{sm}	Ti6Al4V; grinding	FV	3	99.9718	0.0017	9.6797e-04
R_{sm}	Ti6Al4V; grinding	conf	3	99.9839	5.2372e-04	3.0237e-04
R_{sm}	Ti6Al4V; grinding	fusion	3	99.988	4.9575e-04	2.8622e-04
R_{sm}	Ti6Al4V; grinding	int	4	99.9707	0.0027	0.0014
R_{sm}	Ti6Al4V; honing	FV	3	99.8765	5.4720e-04	3.1593e-04
R_{sm}	Ti6Al4V; honing	conf	3	99.9505	0.0029	0.0017

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{sm}	Ti6Al4V; honing	fusion	3	99.9602	0.003	0.0017
R_{sm}	Ti6Al4V; honing	int	4	99.9083	0.0154	0.0077
R_{sm}	Ti6Al4V; finish milling	FV	3	99.9516	0.0047	0.0027
R_{sm}	Ti6Al4V; finish milling	conf	3	99.9715	0.001	5.7923e-04
R_{sm}	Ti6Al4V; finish milling	fusion	3	99.9777	0.0012	7.1292e-04
R_{sm}	Ti6Al4V; finish milling	int	4	99.952	0.0067	0.0034
R_{sm}	Ti6Al4V; rough milling	FV	3	99.9498	0.0105	0.006
R_{sm}	Ti6Al4V; rough milling	conf	3	99.9557	0.0084	0.0049
R_{sm}	Ti6Al4V; rough milling	fusion	3	99.9595	0.0076	0.0044
R_{sm}	Ti6Al4V; rough milling	int	4	99.9183	0.0439	0.0219
R_{sm}	Ti6Al4V; finish face turning	FV	3	99.7948	0.0555	0.032
R_{sm}	Ti6Al4V; finish face turning	conf	3	99.8586	0.0034	0.0019
R_{sm}	Ti6Al4V; finish face turning	fusion	3	99.8962	0.0065	0.0038
R_{sm}	Ti6Al4V; finish face turning	int	4	99.7096	0.1464	0.0732
R_{sm}	Ti6Al4V; rough face turning	FV	3	99.8889	0.0179	0.0103
R_{sm}	Ti6Al4V; rough face turning	conf	3	99.9199	0.0055	0.0032
R_{sm}	Ti6Al4V; rough face turning	fusion	3	99.9364	0.0051	0.003
R_{sm}	Ti6Al4V; rough face turning	int	4	99.8924	0.0467	0.0233
R_{sm}	Ti6Al4V; finish wire EDM	FV	3	99.8695	7.8973e-04	4.5595e-04
R_{sm}	Ti6Al4V; finish wire EDM	conf	3	99.9413	7.3963e-04	4.2702e-04
R_{sm}	Ti6Al4V; finish wire EDM	fusion	3	99.9495	5.9291e-04	3.4232e-04
R_{sm}	Ti6Al4V; finish wire EDM	int	4	99.9099	0.0045	0.0023
R_{sm}	Ti6Al4V; rough wire EDM	FV	3	99.9244	0.002	0.0012
R_{sm}	Ti6Al4V; rough wire EDM	conf	3	99.95	7.1536e-04	4.1301e-04
R_{sm}	Ti6Al4V; rough wire EDM	fusion	3	99.956	0.002	0.0012
R_{sm}	Ti6Al4V; rough wire EDM	int	4	99.9263	0.0313	0.0157
R_t	AISI 304 / EN 1.4301; burnishing after MF	FV	3	50.6796	48.9577	28.2658
R_t	AISI 304 / EN 1.4301; burnishing after MF	conf	3	82.9509	26.1405	15.0922
R_t	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	141.0738	26.4468	15.2691
R_t	AISI 304 / EN 1.4301; burnishing after MF	int	4	46.6007	6.2386	3.1193
R_t	AISI 304 / EN 1.4301; glass bead blasting	FV	3	15.5387	11.5818	6.6867
R_t	AISI 304 / EN 1.4301; glass bead blasting	conf	3	25.1457	11.412	6.5887
R_t	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	88.8416	21.7626	12.5646
R_t	AISI 304 / EN 1.4301; glass bead blasting	int	4	39.7673	2.9207	1.4604
R_t	AISI 304 / EN 1.4301; grinding	FV	3	18.4665	13.6494	7.8805
R_t	AISI 304 / EN 1.4301; grinding	conf	3	3.4578	1.8947	1.0939
R_t	AISI 304 / EN 1.4301; grinding	fusion	3	29.2597	8.1698	4.7168
R_t	AISI 304 / EN 1.4301; grinding	int	4	12.8214	3.021	1.5105
R_t	AISI 304 / EN 1.4301; honing	FV	3	20.6118	22.5545	13.0219
R_t	AISI 304 / EN 1.4301; honing	conf	3	9.8398	5.0656	2.9246
R_t	AISI 304 / EN 1.4301; honing	fusion	3	52.0791	8.2093	4.7396
R_t	AISI 304 / EN 1.4301; honing	int	4	20.6685	7.7072	3.8536
R_t	AISI 304 / EN 1.4301; finish milling	FV	3	19.6533	26.7375	15.4369
R_t	AISI 304 / EN 1.4301; finish milling	conf	3	29.8389	21.5802	12.4593
R_t	AISI 304 / EN 1.4301; finish milling	fusion	3	59.1248	30.9795	17.886
R_t	AISI 304 / EN 1.4301; finish milling	int	4	33.877	24.0091	12.0045
R_t	AISI 304 / EN 1.4301; rough milling	FV	3	64.6505	9.2551	5.3434
R_t	AISI 304 / EN 1.4301; rough milling	conf	3	65.7651	6.0999	3.5218
R_t	AISI 304 / EN 1.4301; rough milling	fusion	3	58.27	5.3988	3.117

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_t	AISI 304 / EN 1.4301; rough milling	int	4	60.958	27.0263	13.5131
R_t	AISI 304 / EN 1.4301; finish face turning	FV	3	47.0532	26.4137	15.25
R_t	AISI 304 / EN 1.4301; finish face turning	conf	3	66.8655	1.3163	0.76
R_t	AISI 304 / EN 1.4301; finish face turning	fusion	3	62.5599	2.0705	1.1954
R_t	AISI 304 / EN 1.4301; finish face turning	int	4	68.4672	6.9628	3.4814
R_t	AISI 304 / EN 1.4301; rough face turning	FV	3	28.5604	9.8682	5.6974
R_t	AISI 304 / EN 1.4301; rough face turning	conf	3	23.9103	2.6789	1.5467
R_t	AISI 304 / EN 1.4301; rough face turning	fusion	3	15.0037	4.8651	2.8089
R_t	AISI 304 / EN 1.4301; rough face turning	int	4	22.21	2.3124	1.1562
R_t	AISI 304 / EN 1.4301; finish wire EDM	FV	3	10.6879	1.2449	0.7187
R_t	AISI 304 / EN 1.4301; finish wire EDM	conf	3	60.3318	22.4436	12.9578
R_t	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	141.9522	25.1394	14.5142
R_t	AISI 304 / EN 1.4301; finish wire EDM	int	4	26.4593	8.0095	4.0048
R_t	AISI 304 / EN 1.4301; rough wire EDM	FV	3	7.7845	0.5216	0.3011
R_t	AISI 304 / EN 1.4301; rough wire EDM	conf	3	2.8709	2.3115	1.3346
R_t	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	31.0523	25.6429	14.8049
R_t	AISI 304 / EN 1.4301; rough wire EDM	int	3	5.0286	1.0212	0.5896
R_t	Al7075; burnishing after MF	FV	3	216.4585	133.7518	77.2216
R_t	Al7075; burnishing after MF	conf	3	220.549	51.3461	29.6447
R_t	Al7075; burnishing after MF	fusion	3	297.2649	65.6774	37.9189
R_t	Al7075; burnishing after MF	int	4	227.8697	303.1446	151.5723
R_t	Al7075; glass bead blasting	FV	3	17.7914	10.5408	6.0857
R_t	Al7075; glass bead blasting	conf	3	26.6581	21.2054	12.243
R_t	Al7075; glass bead blasting	fusion	3	107.3382	71.1002	41.0497
R_t	Al7075; glass bead blasting	int	4	23.0351	4.4786	2.2393
R_t	Al7075; grinding	FV	3	15.6176	11.7058	6.7583
R_t	Al7075; grinding	conf	3	35.4345	7.1602	4.1339
R_t	Al7075; grinding	fusion	3	20.4336	5.4995	3.1751
R_t	Al7075; grinding	int	4	53.3392	2.6565	1.3283
R_t	Al7075; honing	FV	3	22.3186	15.0054	8.6634
R_t	Al7075; honing	conf	3	47.52	7.2728	4.199
R_t	Al7075; honing	fusion	3	32.0524	6.2959	3.6349
R_t	Al7075; honing	int	4	61.7244	1.9902	0.9951
R_t	Al7075; finish milling	FV	3	28.671	28.2872	16.3316
R_t	Al7075; finish milling	conf	3	14.5935	13.0408	7.5291
R_t	Al7075; finish milling	fusion	3	35.9882	20.365	11.7578
R_t	Al7075; finish milling	int	4	48.8158	23.1371	11.5685
R_t	Al7075; rough milling	FV	3	101.6449	79.0258	45.6256
R_t	Al7075; rough milling	conf	3	51.0379	18.6032	10.7406
R_t	Al7075; rough milling	fusion	3	98.1753	22.4649	12.9701
R_t	Al7075; rough milling	int	4	68.5319	27.2082	13.6041
R_t	Al7075; finish face turning	FV	3	50.0097	12.9897	7.4996
R_t	Al7075; finish face turning	conf	3	52.8109	6.6251	3.825
R_t	Al7075; finish face turning	fusion	3	41.3735	7.5074	4.3344
R_t	Al7075; finish face turning	int	4	59.9496	14.1723	7.0862
R_t	Al7075; rough face turning	FV	3	31.2625	8.2938	4.7884
R_t	Al7075; rough face turning	conf	3	26.4253	5.8394	3.3714

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_t	Al7075; rough face turning	fusion	3	21.753	5.6721	3.2748
R_t	Al7075; rough face turning	int	4	35.731	4.7122	2.3561
R_t	Al7075; finish wire EDM	FV	3	25.0695	13.8817	8.0146
R_t	Al7075; finish wire EDM	conf	3	88.1905	13.034	7.5252
R_t	Al7075; finish wire EDM	fusion	3	174.1692	42.2634	24.4008
R_t	Al7075; finish wire EDM	int	4	16.2611	8.7012	4.3506
R_t	Al7075; rough wire EDM	FV	3	15.4737	3.2447	1.8733
R_t	Al7075; rough wire EDM	conf	3	78.8201	25.1142	14.4997
R_t	Al7075; rough wire EDM	fusion	3	201.9688	43.0149	24.8347
R_t	Al7075; rough wire EDM	int	4	20.0707	12.7824	6.3912
R_t	C45 steel; burnishing after MF	FV	3	69.878	55.3657	31.9654
R_t	C45 steel; burnishing after MF	conf	2	111.1405	33.1001	23.4053
R_t	C45 steel; burnishing after MF	fusion	3	150.8254	42.9601	24.803
R_t	C45 steel; burnishing after MF	int	5	127.3256	131.2373	58.6911
R_t	C45 steel; glass bead blasting	FV	3	6.787	8.6694	5.0053
R_t	C45 steel; glass bead blasting	conf	3	38.5976	18.2728	10.5498
R_t	C45 steel; glass bead blasting	fusion	3	87.4691	34.0798	19.676
R_t	C45 steel; glass bead blasting	int	4	21.1677	6.5604	3.2802
R_t	C45 steel; grinding	FV	3	82.0131	27.3581	15.7952
R_t	C45 steel; grinding	conf	3	25.9459	15.0602	8.695
R_t	C45 steel; grinding	fusion	3	51.5801	9.677	5.587
R_t	C45 steel; grinding	int	4	15.0365	3.7949	1.8975
R_t	C45 steel; honing	FV	3	14.41	15.0779	8.7052
R_t	C45 steel; honing	conf	3	8.3904	7.1642	4.1362
R_t	C45 steel; honing	fusion	3	18.8143	9.3992	5.4266
R_t	C45 steel; honing	int	4	20.2734	9.3259	4.6629
R_t	C45 steel; finish milling	FV	3	11.5393	3.2228	1.8607
R_t	C45 steel; finish milling	conf	2	5.3149	5.3253	3.7655
R_t	C45 steel; finish milling	fusion	3	32.0816	9.6271	5.5582
R_t	C45 steel; finish milling	int	4	25.025	16.7193	8.3597
R_t	C45 steel; rough milling	FV	3	36.7787	2.1028	1.2141
R_t	C45 steel; rough milling	conf	2	20.7818	4.4161	3.1226
R_t	C45 steel; rough milling	fusion	3	13.5852	5.8901	3.4006
R_t	C45 steel; rough milling	int	4	35.1155	4.21	2.105
R_t	C45 steel; finish face turning	FV	3	68.1043	1.2979	0.7493
R_t	C45 steel; finish face turning	conf	2	60.6537	1.8852	1.3331
R_t	C45 steel; finish face turning	fusion	3	56.6392	2.9325	1.6931
R_t	C45 steel; finish face turning	int	4	66.2358	1.8092	0.9046
R_t	C45 steel; rough face turning	FV	3	91.3978	1.7769	1.0259
R_t	C45 steel; rough face turning	conf	2	90.0088	0.7175	0.5074
R_t	C45 steel; rough face turning	fusion	3	88.2161	1.1609	0.6702
R_t	C45 steel; rough face turning	int	4	92.5918	1.691	0.8455
R_t	C45 steel; finish wire EDM	FV	3	14.746	12.3774	7.1461
R_t	C45 steel; finish wire EDM	conf	3	124.6485	27.6688	15.9746
R_t	C45 steel; finish wire EDM	fusion	3	213.4248	52.8301	30.5015
R_t	C45 steel; finish wire EDM	int	4	27.3612	6.1559	3.078
R_t	C45 steel; rough wire EDM	FV	3	11.4868	1.3868	0.8007
R_t	C45 steel; rough wire EDM	conf	3	3.3761	2.5519	1.4734
R_t	C45 steel; rough wire EDM	fusion	3	104.0734	34.9966	20.2053
R_t	C45 steel; rough wire EDM	int	4	12.8128	9.9264	4.9632
R_t	ELLOR graphite; glass bead blasting	FV	3	8.2398	0.9001	0.5197
R_t	ELLOR graphite; glass bead blasting	conf	3	3.4849	1.7836	1.0298
R_t	ELLOR graphite; glass bead blasting	fusion	3	1.1816	0.2795	0.1614
R_t	ELLOR graphite; glass bead blasting	int	4	4.6726	1.1853	0.5926
R_t	ELLOR graphite; grinding	FV	3	132.9048	1.1851	0.6842
R_t	ELLOR graphite; grinding	conf	3	147.6487	2.9129	1.6818
R_t	ELLOR graphite; grinding	fusion	3	160.443	6.2769	3.6239
R_t	ELLOR graphite; grinding	int	4	147.6295	27.2169	13.6085
R_t	ELLOR graphite; honing	FV	3	34.4912	17.1838	9.9211
R_t	ELLOR graphite; honing	conf	3	13.3028	7.3233	4.2281

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_t	ELLOR graphite; honing	fusion	3	32.0407	17.4112	10.0523
R_t	ELLOR graphite; honing	int	4	48.7045	10.2469	5.1234
R_t	ELLOR graphite; finish milling	FV	3	23.7382	3.8426	2.2185
R_t	ELLOR graphite; finish milling	conf	3	8.4342	0.7998	0.4618
R_t	ELLOR graphite; finish milling	fusion	3	30.7297	47.8412	27.6211
R_t	ELLOR graphite; finish milling	int	4	27.1204	34.6391	17.3195
R_t	ELLOR graphite; rough milling	FV	3	7.152	2.2985	1.3271
R_t	ELLOR graphite; rough milling	conf	3	6.8552	2.2119	1.277
R_t	ELLOR graphite; rough milling	fusion	3	17.278	5.6528	3.2637
R_t	ELLOR graphite; rough milling	int	4	18.2991	35.2266	17.6133
R_t	ELLOR graphite; finish face turning	FV	3	25.0834	1.5777	0.9109
R_t	ELLOR graphite; finish face turning	conf	3	9.7099	0.9458	0.546
R_t	ELLOR graphite; finish face turning	fusion	3	3.5061	4.39	2.5346
R_t	ELLOR graphite; finish face turning	int	4	23.1288	26.5252	13.2626
R_t	ELLOR graphite; rough face turning	FV	3	15.4904	0.625	0.3608
R_t	ELLOR graphite; rough face turning	conf	3	10.9105	0.6111	0.3528
R_t	ELLOR graphite; rough face turning	fusion	3	6.1249	2.1371	1.2339
R_t	ELLOR graphite; rough face turning	int	4	19.0763	17.5735	8.7868
R_t	ELLOR graphite; finish wire EDM	FV	3	13.9494	3.2316	1.8658
R_t	ELLOR graphite; finish wire EDM	conf	3	15.5235	3.178	1.8348
R_t	ELLOR graphite; finish wire EDM	fusion	3	33.8945	3.7435	2.1613
R_t	ELLOR graphite; finish wire EDM	int	3	11.0157	3.1575	1.823
R_t	ELLOR graphite; rough wire EDM	FV	3	13.5338	1.3088	0.7556
R_t	ELLOR graphite; rough wire EDM	conf	3	7.0037	1.8354	1.0596
R_t	ELLOR graphite; rough wire EDM	fusion	3	1.7821	1.9494	1.1255
R_t	ELLOR graphite; rough wire EDM	int	4	31.1464	41.3151	20.6575
R_t	MO58A brass; burnishing after MF	FV	4	296.9109	170.5528	85.2764
R_t	MO58A brass; burnishing after MF	conf	3	302.486	35.3374	20.402
R_t	MO58A brass; burnishing after MF	fusion	3	418.8259	48.3837	27.9343
R_t	MO58A brass; burnishing after MF	int	3	330.2181	418.0789	241.378
R_t	MO58A brass; glass bead blasting	FV	3	16.4295	12.5875	7.2674
R_t	MO58A brass; glass bead blasting	conf	3	71.1577	34.6613	20.0117
R_t	MO58A brass; glass bead blasting	fusion	3	127.6004	84.8733	49.0016
R_t	MO58A brass; glass bead blasting	int	4	7.4239	2.2685	1.1342
R_t	MO58A brass; grinding	FV	3	35.7014	20.2374	11.6841
R_t	MO58A brass; grinding	conf	3	10.4947	8.9782	5.1835
R_t	MO58A brass; grinding	fusion	3	42.0885	4.4407	2.5638
R_t	MO58A brass; grinding	int	4	10.788	2.3708	1.1854
R_t	MO58A brass; honing	FV	3	12.4481	12.5804	7.2633
R_t	MO58A brass; honing	conf	3	9.5192	9.9635	5.7524
R_t	MO58A brass; honing	fusion	3	16.8142	11.0882	6.4018
R_t	MO58A brass; honing	int	4	25.5918	6.455	3.2275
R_t	MO58A brass; finish milling	FV	3	128.9245	70.545	40.7292
R_t	MO58A brass; finish milling	conf	3	144.6317	27.8176	16.0605
R_t	MO58A brass; finish milling	fusion	3	217.6342	48.6767	28.1035
R_t	MO58A brass; finish milling	int	4	53.7411	55.9125	27.9563
R_t	MO58A brass; rough milling	FV	3	37.1963	25.5301	14.7398
R_t	MO58A brass; rough milling	conf	3	33.8319	3.0343	1.7519
R_t	MO58A brass; rough milling	fusion	3	18.0476	4.3704	2.5233
R_t	MO58A brass; rough milling	int	4	56.455	8.6246	4.3123
R_t	MO58A brass; finish face turning	FV	3	64.5754	2.9519	1.7043
R_t	MO58A brass; finish face turning	conf	3	59.6354	2.8851	1.6657

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_t	MO58A brass; finish face turning	fusion	3	53.3089	3.6807	2.1251
R_t	MO58A brass; finish face turning	int	4	65.4379	1.8326	0.9163
R_t	MO58A brass; rough face turning	FV	3	26.5046	5.7954	3.3459
R_t	MO58A brass; rough face turning	conf	3	23.5409	4.0971	2.3655
R_t	MO58A brass; rough face turning	fusion	3	10.9195	4.2986	2.4818
R_t	MO58A brass; rough face turning	int	4	34.1548	3.4929	1.7465
R_t	MO58A brass; finish wire EDM	FV	3	26.5761	12.0147	6.9367
R_t	MO58A brass; finish wire EDM	conf	3	60.9361	13.6533	7.8827
R_t	MO58A brass; finish wire EDM	fusion	3	123.2586	23.2812	13.4414
R_t	MO58A brass; finish wire EDM	int	4	13.0275	3.2864	1.6432
R_t	MO58A brass; rough wire EDM	FV	3	33.6484	2.7198	1.5703
R_t	MO58A brass; rough wire EDM	conf	3	14.7253	13.7684	7.9492
R_t	MO58A brass; rough wire EDM	fusion	3	18.6256	10.9395	6.3159
R_t	MO58A brass; rough wire EDM	int	4	29.1105	6.1472	3.0736
R_t	Ti6Al4V; burnishing after MF	FV	3	92.6806	52.5497	30.3396
R_t	Ti6Al4V; burnishing after MF	conf	3	135.1084	41.0817	23.7185
R_t	Ti6Al4V; burnishing after MF	fusion	3	172.7228	38.1436	22.0222
R_t	Ti6Al4V; burnishing after MF	int	4	69.7186	53.8064	26.9032
R_t	Ti6Al4V; glass bead blasting	FV	3	13.3069	10.4812	6.0513
R_t	Ti6Al4V; glass bead blasting	conf	3	38.0646	12.825	7.4045
R_t	Ti6Al4V; glass bead blasting	fusion	3	102.3147	36.4031	21.0174
R_t	Ti6Al4V; glass bead blasting	int	4	29.6424	3.4815	1.7407
R_t	Ti6Al4V; grinding	FV	3	36.2643	12.2697	7.0839
R_t	Ti6Al4V; grinding	conf	3	46.5802	14.5597	8.4061
R_t	Ti6Al4V; grinding	fusion	3	71.7598	9.9644	5.753
R_t	Ti6Al4V; grinding	int	4	17.2545	7.46	3.73
R_t	Ti6Al4V; honing	FV	3	55.137	24.8906	14.3706
R_t	Ti6Al4V; honing	conf	3	30.6148	15.9173	9.1898
R_t	Ti6Al4V; honing	fusion	3	75.4062	9.0351	5.2164
R_t	Ti6Al4V; honing	int	4	15.8982	3.8581	1.9291
R_t	Ti6Al4V; finish milling	FV	3	16.9404	23.5739	13.6104
R_t	Ti6Al4V; finish milling	conf	3	42.9535	19.2285	11.1016
R_t	Ti6Al4V; finish milling	fusion	3	71.9865	21.7077	12.533
R_t	Ti6Al4V; finish milling	int	4	13.4225	9.3874	4.6937
R_t	Ti6Al4V; rough milling	FV	3	57.3703	14.2866	8.2484
R_t	Ti6Al4V; rough milling	conf	3	53.2569	6.6762	3.8545
R_t	Ti6Al4V; rough milling	fusion	3	39.6833	7.8253	4.5179
R_t	Ti6Al4V; rough milling	int	4	59.5338	23.3044	11.6522
R_t	Ti6Al4V; finish face turning	FV	3	29.4746	6.1951	3.5768
R_t	Ti6Al4V; finish face turning	conf	3	20.256	10.9832	6.3411
R_t	Ti6Al4V; finish face turning	fusion	3	11.2845	8.0338	4.6383
R_t	Ti6Al4V; finish face turning	int	4	33.0118	14.6508	7.3254
R_t	Ti6Al4V; rough face turning	FV	3	38.4388	6.2893	3.6312
R_t	Ti6Al4V; rough face turning	conf	3	25.5997	11.8441	6.8382
R_t	Ti6Al4V; rough face turning	fusion	3	11.1018	10.5323	6.0808
R_t	Ti6Al4V; rough face turning	int	4	42.2919	7.796	3.898
R_t	Ti6Al4V; finish wire EDM	FV	3	42.2526	18.8615	10.8897
R_t	Ti6Al4V; finish wire EDM	conf	3	91.6813	24.9028	14.3776
R_t	Ti6Al4V; finish wire EDM	fusion	3	169.6757	26.7335	15.4346
R_t	Ti6Al4V; finish wire EDM	int	4	29.0383	8.7449	4.3724
R_t	Ti6Al4V; rough wire EDM	FV	3	12.8177	2.0067	1.1586
R_t	Ti6Al4V; rough wire EDM	conf	3	52.4897	30.0338	17.34
R_t	Ti6Al4V; rough wire EDM	fusion	3	139.7551	47.3411	27.3324
R_t	Ti6Al4V; rough wire EDM	int	4	13.4656	9.2749	4.6375
R_v	AISI 304 / EN 1.4301; burnishing after MF	FV	3	112.6532	111.618	64.4427
R_v	AISI 304 / EN 1.4301; burnishing after MF	conf	3	145.7359	31.5391	18.2091
R_v	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	224.4223	51.1682	29.5419
R_v	AISI 304 / EN 1.4301; burnishing after MF	int	4	68.3787	38.3645	19.1823
R_v	AISI 304 / EN 1.4301; glass bead blasting	FV	3	11.5735	9.167	5.2926

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_v	AISI 304 / EN 1.4301; glass bead blasting	conf	3	96.7517	38.239	22.0773
R_v	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	165.8445	60.9477	35.1882
R_v	AISI 304 / EN 1.4301; glass bead blasting	int	4	9.096	3.207	1.6035
R_v	AISI 304 / EN 1.4301; grinding	FV	3	7.7921	3.6916	2.1314
R_v	AISI 304 / EN 1.4301; grinding	conf	3	15.7628	7.4518	4.3023
R_v	AISI 304 / EN 1.4301; grinding	fusion	3	35.9848	13.7347	7.9297
R_v	AISI 304 / EN 1.4301; grinding	int	4	4.6133	2.6317	1.3158
R_v	AISI 304 / EN 1.4301; honing	FV	3	54.2848	34.1152	19.6964
R_v	AISI 304 / EN 1.4301; honing	conf	3	78.1155	35.4801	20.4844
R_v	AISI 304 / EN 1.4301; honing	fusion	3	121.8999	43.397	25.0553
R_v	AISI 304 / EN 1.4301; honing	int	4	1.689	1.711	0.8555
R_v	AISI 304 / EN 1.4301; finish milling	FV	3	121.9146	69.8178	40.3093
R_v	AISI 304 / EN 1.4301; finish milling	conf	3	184.2185	48.1939	27.8248
R_v	AISI 304 / EN 1.4301; finish milling	fusion	3	264.9535	76.4841	44.1581
R_v	AISI 304 / EN 1.4301; finish milling	int	4	80.562	78.3668	39.1834
R_v	AISI 304 / EN 1.4301; rough milling	FV	3	63.3586	11.6909	6.7498
R_v	AISI 304 / EN 1.4301; rough milling	conf	3	66.2552	5.6627	3.2694
R_v	AISI 304 / EN 1.4301; rough milling	fusion	3	60.4536	6.0265	3.4794
R_v	AISI 304 / EN 1.4301; rough milling	int	4	61.3508	26.9193	13.4597
R_v	AISI 304 / EN 1.4301; finish face turning	FV	3	49.5699	75.0307	43.319
R_v	AISI 304 / EN 1.4301; finish face turning	conf	3	18.6565	2.9607	1.7094
R_v	AISI 304 / EN 1.4301; finish face turning	fusion	3	6.294	4.5281	2.6143
R_v	AISI 304 / EN 1.4301; finish face turning	int	4	30.7265	19.5161	9.758
R_v	AISI 304 / EN 1.4301; rough face turning	FV	3	47.0317	19.2198	11.0966
R_v	AISI 304 / EN 1.4301; rough face turning	conf	3	53.0764	4.4464	2.5671
R_v	AISI 304 / EN 1.4301; rough face turning	fusion	3	43.8734	6.4452	3.7212
R_v	AISI 304 / EN 1.4301; rough face turning	int	4	59.7205	10.8863	5.4432
R_v	AISI 304 / EN 1.4301; finish wire EDM	FV	3	15.5017	9.3971	5.4254
R_v	AISI 304 / EN 1.4301; finish wire EDM	conf	3	94.7172	22.675	13.0914
R_v	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	184.1072	42.5705	24.5781
R_v	AISI 304 / EN 1.4301; finish wire EDM	int	4	15.1319	2.7959	1.398
R_v	AISI 304 / EN 1.4301; rough wire EDM	FV	3	5.0228	1.8611	1.0745
R_v	AISI 304 / EN 1.4301; rough wire EDM	conf	3	14.1949	8.2503	4.7633
R_v	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	38.5778	29.3796	16.9623
R_v	AISI 304 / EN 1.4301; rough wire EDM	int	3	2.1166	0.3646	0.2105
R_v	Al7075; burnishing after MF	FV	3	301.4711	260.0607	150.1461
R_v	Al7075; burnishing after MF	conf	3	276.2654	51.6127	29.7986

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_v	Al7075; burnishing after MF	fusion	3	378.9383	83.7927	48.3777
R_v	Al7075; burnishing after MF	int	4	310.1644	395.3171	197.6585
R_v	Al7075; glass bead blasting	FV	3	9.9124	3.7097	2.1418
R_v	Al7075; glass bead blasting	conf	3	104.0395	49.0387	28.3125
R_v	Al7075; glass bead blasting	fusion	3	135.8094	59.7031	34.4696
R_v	Al7075; glass bead blasting	int	4	3.3916	4.9967	2.4984
R_v	Al7075; grinding	FV	3	15.92	14.6338	8.4488
R_v	Al7075; grinding	conf	3	23.1274	18.2422	10.5322
R_v	Al7075; grinding	fusion	3	47.0071	24.7349	14.2807
R_v	Al7075; grinding	int	4	13.3387	0.8103	0.4051
R_v	Al7075; honing	FV	3	36.9488	9.3633	5.4059
R_v	Al7075; honing	conf	3	26.2028	13.0899	7.5575
R_v	Al7075; honing	fusion	3	12.173	11.9377	6.8922
R_v	Al7075; honing	int	4	45.2013	1.9136	0.9568
R_v	Al7075; finish milling	FV	3	251.9078	188.4926	108.8262
R_v	Al7075; finish milling	conf	3	257.0002	42.1079	24.311
R_v	Al7075; finish milling	fusion	3	353.751	59.1772	34.1659
R_v	Al7075; finish milling	int	4	148.4793	190.8235	95.4118
R_v	Al7075; rough milling	FV	3	169.1113	121.6161	70.2151
R_v	Al7075; rough milling	conf	3	90.0833	21.454	12.3865
R_v	Al7075; rough milling	fusion	3	154.5232	30.3878	17.5444
R_v	Al7075; rough milling	int	4	85.7081	57.2477	28.6239
R_v	Al7075; finish face turning	FV	3	25.4638	3.2466	1.8744
R_v	Al7075; finish face turning	conf	3	18.9257	12.9322	7.4664
R_v	Al7075; finish face turning	fusion	3	14.1944	6.8965	3.9817
R_v	Al7075; finish face turning	int	4	34.3404	27.2359	13.6179
R_v	Al7075; rough face turning	FV	3	59.3744	8.8026	5.0822
R_v	Al7075; rough face turning	conf	3	57.3956	3.7329	2.1552
R_v	Al7075; rough face turning	fusion	3	51.916	4.622	2.6685
R_v	Al7075; rough face turning	int	4	64.9813	8.17	4.085
R_v	Al7075; finish wire EDM	FV	3	22.7741	16.87	9.7399
R_v	Al7075; finish wire EDM	conf	3	97.7724	22.595	13.0452
R_v	Al7075; finish wire EDM	fusion	3	171.0812	32.0501	18.5041
R_v	Al7075; finish wire EDM	int	4	6.19	2.8282	1.4141
R_v	Al7075; rough wire EDM	FV	3	7.4054	4.5713	2.6392
R_v	Al7075; rough wire EDM	conf	3	124.1854	61.4353	35.4697
R_v	Al7075; rough wire EDM	fusion	3	317.6396	71.2407	41.1308
R_v	Al7075; rough wire EDM	int	4	10.5134	10.5609	5.2804
R_v	C45 steel; burnishing after MF	FV	3	82.6306	87.2791	50.3906
R_v	C45 steel; burnishing after MF	conf	2	138.5457	39.3543	27.8277
R_v	C45 steel; burnishing after MF	fusion	3	182.9871	66.8804	38.6134
R_v	C45 steel; burnishing after MF	int	5	133.6377	141.9119	63.4649
R_v	C45 steel; glass bead blasting	FV	3	8.6114	7.2212	4.1692
R_v	C45 steel; glass bead blasting	conf	3	96.9116	44.545	25.718
R_v	C45 steel; glass bead blasting	fusion	3	149.841	67.5626	39.0073
R_v	C45 steel; glass bead blasting	int	4	9.0343	1.5721	0.786
R_v	C45 steel; grinding	FV	3	46.1811	18.1197	10.4614
R_v	C45 steel; grinding	conf	3	44.011	20.1223	11.6176
R_v	C45 steel; grinding	fusion	3	68.2804	24.9717	14.4174
R_v	C45 steel; grinding	int	4	1.0294	0.7588	0.3794
R_v	C45 steel; honing	FV	3	24.5721	26.7079	15.4198
R_v	C45 steel; honing	conf	3	45.0764	27.4581	15.8529
R_v	C45 steel; honing	fusion	3	73.1891	32.1613	18.5684
R_v	C45 steel; honing	int	4	7.1118	3.5663	1.7832
R_v	C45 steel; finish milling	FV	3	26.2676	6.557	3.7857
R_v	C45 steel; finish milling	conf	2	20.5288	11.084	7.8376
R_v	C45 steel; finish milling	fusion	3	36.4508	25.1762	14.5355
R_v	C45 steel; finish milling	int	4	19.1571	2.3306	1.1653
R_v	C45 steel; rough milling	FV	3	44.993	5.168	2.9837
R_v	C45 steel; rough milling	conf	2	24.4	6.9068	4.8839
R_v	C45 steel; rough milling	fusion	3	15.4772	13.6584	7.8857
R_v	C45 steel; rough milling	int	4	47.6227	8.1885	4.0943
R_v	C45 steel; finish face turning	FV	3	67.4489	2.0016	1.1556
R_v	C45 steel; finish face turning	conf	2	55.0801	3.8241	2.7041

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_v	C45 steel; finish face turning	fusion	3	49.4876	7.9781	4.6062
R_v	C45 steel; finish face turning	int	4	68.9073	4.1964	2.0982
R_v	C45 steel; rough face turning	FV	3	83.4811	6.3523	3.6675
R_v	C45 steel; rough face turning	conf	2	81.9958	1.2494	0.8835
R_v	C45 steel; rough face turning	fusion	3	77.9589	3.0967	1.7879
R_v	C45 steel; rough face turning	int	4	87.0786	4.9019	2.4509
R_v	C45 steel; finish wire EDM	FV	3	22.4802	18.3188	10.5764
R_v	C45 steel; finish wire EDM	conf	3	109.3598	19.1335	11.0467
R_v	C45 steel; finish wire EDM	fusion	3	171.0102	21.8657	12.6241
R_v	C45 steel; finish wire EDM	int	4	21.5744	2.7305	1.3652
R_v	C45 steel; rough wire EDM	FV	3	5.1242	3.7695	2.1763
R_v	C45 steel; rough wire EDM	conf	3	20.6512	10.8897	6.2872
R_v	C45 steel; rough wire EDM	fusion	3	128.1409	78.9065	45.5567
R_v	C45 steel; rough wire EDM	int	4	10.1891	14.1262	7.0631
R_v	ELLOR graphite; glass bead blast- ing	FV	3	1.5226	0.4903	0.2831
R_v	ELLOR graphite; glass bead blast- ing	conf	3	6.1678	1.7413	1.0053
R_v	ELLOR graphite; glass bead blast- ing	fusion	3	10.6646	2.3499	1.3567
R_v	ELLOR graphite; glass bead blast- ing	int	4	12.0047	6.0001	3.0001
R_v	ELLOR graphite; grinding	FV	3	192.0434	2.7203	1.5706
R_v	ELLOR graphite; grinding	conf	3	215.0603	2.1221	1.2252
R_v	ELLOR graphite; grinding	fusion	3	228.2641	7.6478	4.4155
R_v	ELLOR graphite; grinding	int	4	186.1134	60.3918	30.1959
R_v	ELLOR graphite; honing	FV	3	25.8629	31.0847	17.9468
R_v	ELLOR graphite; honing	conf	3	76.9408	42.7067	24.6567
R_v	ELLOR graphite; honing	fusion	3	133.9303	62.9651	36.3529
R_v	ELLOR graphite; honing	int	4	12.7889	4.8589	2.4294
R_v	ELLOR graphite; finish milling	FV	3	30.1085	9.0587	5.23
R_v	ELLOR graphite; finish milling	conf	3	4.7481	1.2013	0.6936
R_v	ELLOR graphite; finish milling	fusion	3	28.0991	37.8658	21.8618
R_v	ELLOR graphite; finish milling	int	4	28.2968	35.8466	17.9233
R_v	ELLOR graphite; rough milling	FV	3	3.2566	2.7706	1.5996
R_v	ELLOR graphite; rough milling	conf	3	22.5344	1.7322	1.0001
R_v	ELLOR graphite; rough milling	fusion	3	28.1138	6.9523	4.0139
R_v	ELLOR graphite; rough milling	int	4	38.5055	24.2849	12.1425
R_v	ELLOR graphite; finish face turn- ing	FV	3	25.2943	3.0761	1.776
R_v	ELLOR graphite; finish face turn- ing	conf	3	1.957	1.2604	0.7277
R_v	ELLOR graphite; finish face turn- ing	fusion	3	8.6948	8.2322	4.7529
R_v	ELLOR graphite; finish face turn- ing	int	4	20.2589	30.3792	15.1896
R_v	ELLOR graphite; rough face turn- ing	FV	3	3.463	0.4988	0.288
R_v	ELLOR graphite; rough face turn- ing	conf	3	9.5296	0.4378	0.2527
R_v	ELLOR graphite; rough face turn- ing	fusion	3	15.1088	2.5172	1.4533
R_v	ELLOR graphite; rough face turn- ing	int	4	23.5239	15.9433	7.9716
R_v	ELLOR graphite; finish wire EDM	FV	3	21.5695	4.0885	2.3605
R_v	ELLOR graphite; finish wire EDM	conf	3	41.2985	0.5358	0.3093
R_v	ELLOR graphite; finish wire EDM	fusion	3	49.8641	4.9916	2.8819
R_v	ELLOR graphite; finish wire EDM	int	3	43.5056	5.4435	3.1428
R_v	ELLOR graphite; rough wire EDM	FV	3	2.3099	1.5587	0.8999
R_v	ELLOR graphite; rough wire EDM	conf	3	21.6906	3.1513	1.8194
R_v	ELLOR graphite; rough wire EDM	fusion	3	24.6248	4.7988	2.7706
R_v	ELLOR graphite; rough wire EDM	int	4	27.9415	13.6557	6.8279
R_v	MO58A brass; burnishing after MF	FV	4	432.1703	311.8137	155.9069

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_v	MO58A brass; burnishing after MF	conf	3	428.3734	48.711	28.1233
R_v	MO58A brass; burnishing after MF	fusion	3	579.2819	89.7649	51.8258
R_v	MO58A brass; burnishing after MF	int	3	327.6418	419.6547	242.2877
R_v	MO58A brass; glass bead blasting	FV	3	23.0115	11.8193	6.8239
R_v	MO58A brass; glass bead blasting	conf	3	143.2812	72.9055	42.092
R_v	MO58A brass; glass bead blasting	fusion	3	192.4093	107.938	62.318
R_v	MO58A brass; glass bead blasting	int	4	19.1923	8.652	4.326
R_v	MO58A brass; grinding	FV	3	20.8869	9.7601	5.635
R_v	MO58A brass; grinding	conf	3	35.9134	15.2706	8.8165
R_v	MO58A brass; grinding	fusion	3	60.9844	19.5186	11.2691
R_v	MO58A brass; grinding	int	4	9.9259	6.0458	3.0229
R_v	MO58A brass; honing	FV	3	9.2904	12.7653	7.37
R_v	MO58A brass; honing	conf	3	38.6061	25.1992	14.5488
R_v	MO58A brass; honing	fusion	3	69.3398	36.7499	21.2175
R_v	MO58A brass; honing	int	4	7.6051	3.6661	1.833
R_v	MO58A brass; finish milling	FV	3	226.0466	173.7856	100.3352
R_v	MO58A brass; finish milling	conf	3	276.9592	37.671	21.7494
R_v	MO58A brass; finish milling	fusion	3	377.2073	64.9732	37.5123
R_v	MO58A brass; finish milling	int	4	99.0193	110.5595	55.2797
R_v	MO58A brass; rough milling	FV	3	39.1398	30.3226	17.5067
R_v	MO58A brass; rough milling	conf	3	47.1192	5.8822	3.3961
R_v	MO58A brass; rough milling	fusion	3	32.0804	8.4261	4.8648
R_v	MO58A brass; rough milling	int	4	66.256	9.5544	4.7772
R_v	MO58A brass; finish face turning	FV	3	58.0584	6.7105	3.8743
R_v	MO58A brass; finish face turning	conf	3	51.9368	5.7288	3.3075
R_v	MO58A brass; finish face turning	fusion	3	41.9599	8.3059	4.7954
R_v	MO58A brass; finish face turning	int	4	63.1846	3.5215	1.7608
R_v	MO58A brass; rough face turning	FV	3	27.0469	7.1949	4.154
R_v	MO58A brass; rough face turning	conf	3	22.791	7.4475	4.2998
R_v	MO58A brass; rough face turning	fusion	3	11.0504	10.5117	6.0689
R_v	MO58A brass; rough face turning	int	4	34.5754	4.3478	2.1739
R_v	MO58A brass; finish wire EDM	FV	3	12.1035	7.3992	4.2719
R_v	MO58A brass; finish wire EDM	conf	3	69.7674	27.3041	15.764
R_v	MO58A brass; finish wire EDM	fusion	3	140.3554	28.8654	16.6654
R_v	MO58A brass; finish wire EDM	int	4	6.3764	2.9529	1.4764
R_v	MO58A brass; rough wire EDM	FV	3	28.5364	5.4037	3.1198
R_v	MO58A brass; rough wire EDM	conf	3	23.193	10.2564	5.9215
R_v	MO58A brass; rough wire EDM	fusion	3	30.6814	25.4875	14.7152
R_v	MO58A brass; rough wire EDM	int	4	26.4733	5.3204	2.6602
R_v	Ti6Al4V; burnishing after MF	FV	3	128.3773	76.528	44.1834
R_v	Ti6Al4V; burnishing after MF	conf	3	177.6453	34.286	19.795
R_v	Ti6Al4V; burnishing after MF	fusion	3	215.2853	31.6008	18.2447
R_v	Ti6Al4V; burnishing after MF	int	4	106.281	13.7725	6.8863
R_v	Ti6Al4V; glass bead blasting	FV	3	14.4502	13.2177	7.6313
R_v	Ti6Al4V; glass bead blasting	conf	3	133.127	47.2063	27.2546
R_v	Ti6Al4V; glass bead blasting	fusion	3	213.0431	78.8388	45.5176
R_v	Ti6Al4V; glass bead blasting	int	4	12.1002	6.3811	3.1906
R_v	Ti6Al4V; grinding	FV	3	142.2925	21.8315	12.6044
R_v	Ti6Al4V; grinding	conf	3	196.7571	32.4914	18.7589
R_v	Ti6Al4V; grinding	fusion	3	242.7274	46.0438	26.5834
R_v	Ti6Al4V; grinding	int	4	131.1991	8.2478	4.1239
R_v	Ti6Al4V; honing	FV	3	110.9919	25.5413	14.7463
R_v	Ti6Al4V; honing	conf	3	157.2101	49.4576	28.5543
R_v	Ti6Al4V; honing	fusion	3	232.6806	60.6504	35.0165
R_v	Ti6Al4V; honing	int	4	37.4445	2.7949	1.3975
R_v	Ti6Al4V; finish milling	FV	3	73.5054	48.6244	28.0733
R_v	Ti6Al4V; finish milling	conf	3	111.4759	39.959	23.0703
R_v	Ti6Al4V; finish milling	fusion	3	154.084	47.3964	27.3643
R_v	Ti6Al4V; finish milling	int	4	26.3594	8.6142	4.3071
R_v	Ti6Al4V; rough milling	FV	3	34.4262	15.6121	9.0136
R_v	Ti6Al4V; rough milling	conf	3	11.4536	8.2763	4.7783

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_v	Ti6Al4V; rough milling	fusion	3	35.262	20.8719	12.0504
R_v	Ti6Al4V; rough milling	int	4	47.3791	18.29	9.145
R_v	Ti6Al4V; finish face turning	FV	3	7.3459	5.9959	3.4617
R_v	Ti6Al4V; finish face turning	conf	3	11.3459	10.1274	5.8471
R_v	Ti6Al4V; finish face turning	fusion	3	22.521	20.8833	12.057
R_v	Ti6Al4V; finish face turning	int	4	20.5154	12.4536	6.2268
R_v	Ti6Al4V; rough face turning	FV	3	60.2871	2.4249	1.4
R_v	Ti6Al4V; rough face turning	conf	3	43.9279	12.3405	7.1248
R_v	Ti6Al4V; rough face turning	fusion	3	31.0285	15.1341	8.7377
R_v	Ti6Al4V; rough face turning	int	4	58.0763	11.9299	5.965
R_v	Ti6Al4V; finish wire EDM	FV	3	63.89	20.5311	11.8536
R_v	Ti6Al4V; finish wire EDM	conf	3	156.9535	35.8893	20.7207
R_v	Ti6Al4V; finish wire EDM	fusion	3	254.9569	44.7677	25.8467
R_v	Ti6Al4V; finish wire EDM	int	4	9.3017	3.016	1.508
R_v	Ti6Al4V; rough wire EDM	FV	3	8.0807	3.8277	2.2099
R_v	Ti6Al4V; rough wire EDM	conf	3	77.1656	50.7626	29.3078
R_v	Ti6Al4V; rough wire EDM	fusion	3	210.24	91.1692	52.6366
R_v	Ti6Al4V; rough wire EDM	int	4	7.5345	12.6139	6.3069
R_z	AISI 304 / EN 1.4301; burnishing after MF	FV	3	172.1646	97.1213	56.073
R_z	AISI 304 / EN 1.4301; burnishing after MF	conf	3	212.3361	45.5057	26.2728
R_z	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	312.5159	54.9053	31.6996
R_z	AISI 304 / EN 1.4301; burnishing after MF	int	4	94.6107	84.4671	42.2336
R_z	AISI 304 / EN 1.4301; glass bead blasting	FV	3	10.4239	4.3392	2.5052
R_z	AISI 304 / EN 1.4301; glass bead blasting	conf	3	62.4585	14.1015	8.1415
R_z	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	137.1416	20.1286	11.6213
R_z	AISI 304 / EN 1.4301; glass bead blasting	int	4	27.8359	5.4314	2.7157
R_z	AISI 304 / EN 1.4301; grinding	FV	3	32.2759	12.9947	7.5025
R_z	AISI 304 / EN 1.4301; grinding	conf	3	23.7076	5.3632	3.0964
R_z	AISI 304 / EN 1.4301; grinding	fusion	3	56.6493	8.3657	4.8299
R_z	AISI 304 / EN 1.4301; grinding	int	4	3.7579	3.4489	1.7244
R_z	AISI 304 / EN 1.4301; honing	FV	3	36.3578	26.9589	15.5647
R_z	AISI 304 / EN 1.4301; honing	conf	3	32.0384	16.5922	9.5795
R_z	AISI 304 / EN 1.4301; honing	fusion	3	91.0306	8.8315	5.0989
R_z	AISI 304 / EN 1.4301; honing	int	4	5.8331	7.6774	3.8387
R_z	AISI 304 / EN 1.4301; finish milling	FV	3	87.2971	47.3561	27.3411
R_z	AISI 304 / EN 1.4301; finish milling	conf	3	126.8184	34.537	19.9399
R_z	AISI 304 / EN 1.4301; finish milling	fusion	3	181.3509	51.5852	29.7828
R_z	AISI 304 / EN 1.4301; finish milling	int	4	68.166	81.0129	40.5064
R_z	AISI 304 / EN 1.4301; rough milling	FV	3	67.7772	7.7776	4.4904
R_z	AISI 304 / EN 1.4301; rough milling	conf	3	68.7649	5.3692	3.0999
R_z	AISI 304 / EN 1.4301; rough milling	fusion	3	63.9078	5.2941	3.0565
R_z	AISI 304 / EN 1.4301; rough milling	int	4	65.0391	23.7849	11.8924
R_z	AISI 304 / EN 1.4301; finish face turning	FV	3	38.1777	3.3338	1.9248
R_z	AISI 304 / EN 1.4301; finish face turning	conf	3	42.5943	2.2546	1.3017
R_z	AISI 304 / EN 1.4301; finish face turning	fusion	3	33.3659	3.3017	1.9062

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_z	AISI 304 / EN 1.4301; finish face turning	int	4	49.962	14.766	7.383
R_z	AISI 304 / EN 1.4301; rough face turning	FV	3	42.1065	13.3813	7.7257
R_z	AISI 304 / EN 1.4301; rough face turning	conf	3	42.9624	2.6046	1.5038
R_z	AISI 304 / EN 1.4301; rough face turning	fusion	3	34.241	3.9937	2.3058
R_z	AISI 304 / EN 1.4301; rough face turning	int	4	45.3371	7.9999	4
R_z	AISI 304 / EN 1.4301; finish wire EDM	FV	3	16.5487	14.2364	8.2194
R_z	AISI 304 / EN 1.4301; finish wire EDM	conf	3	90.1282	26.598	15.3564
R_z	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	168.5157	20.5743	11.8786
R_z	AISI 304 / EN 1.4301; finish wire EDM	int	4	15.4725	7.7861	3.893
R_z	AISI 304 / EN 1.4301; rough wire EDM	FV	3	1.1032	0.9068	0.5236
R_z	AISI 304 / EN 1.4301; rough wire EDM	conf	3	9.9173	5.1798	2.9906
R_z	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	29.5089	16.2437	9.3783
R_z	AISI 304 / EN 1.4301; rough wire EDM	int	3	6.0504	1.2958	0.7482
R_z	Al7075; burnishing after MF	FV	3	291.1032	175.4446	101.293
R_z	Al7075; burnishing after MF	conf	3	283.6583	55.2598	31.9043
R_z	Al7075; burnishing after MF	fusion	3	373.9463	73.7323	42.5694
R_z	Al7075; burnishing after MF	int	4	346.4809	430.4444	215.2222
R_z	Al7075; glass bead blasting	FV	3	9.8036	4.7266	2.7289
R_z	Al7075; glass bead blasting	conf	3	58.9134	26.4767	15.2863
R_z	Al7075; glass bead blasting	fusion	3	107.2477	44.9988	25.9801
R_z	Al7075; glass bead blasting	int	4	8.085	3.0363	1.5181
R_z	Al7075; grinding	FV	3	50.4236	19.5695	11.2985
R_z	Al7075; grinding	conf	3	24.6189	14.5603	8.4064
R_z	Al7075; grinding	fusion	3	53.847	14.0307	8.1006
R_z	Al7075; grinding	int	4	16.1875	5.3815	2.6907
R_z	Al7075; honing	FV	3	13.8137	12.8724	7.4319
R_z	Al7075; honing	conf	3	34.0779	9.1509	5.2833
R_z	Al7075; honing	fusion	3	14.8924	9.189	5.3053
R_z	Al7075; honing	int	4	54.6683	2.2864	1.1432
R_z	Al7075; finish milling	FV	3	149.3394	89.8133	51.8538
R_z	Al7075; finish milling	conf	3	162.5407	44.0533	25.4342
R_z	Al7075; finish milling	fusion	3	224.9876	47.6036	27.4839
R_z	Al7075; finish milling	int	4	110.9533	123.0581	61.529
R_z	Al7075; rough milling	FV	3	155.0784	95.5176	55.1471
R_z	Al7075; rough milling	conf	3	87.5087	17.9414	10.3585
R_z	Al7075; rough milling	fusion	3	146.2449	22.7157	13.1149
R_z	Al7075; rough milling	int	4	81.6117	54.3876	27.1938
R_z	Al7075; finish face turning	FV	3	21.9196	15.2171	8.7856
R_z	Al7075; finish face turning	conf	3	23.034	11.5523	6.6698
R_z	Al7075; finish face turning	fusion	3	10.194	8.7457	5.0493
R_z	Al7075; finish face turning	int	4	37.0226	26.7391	13.3695
R_z	Al7075; rough face turning	FV	3	58.9371	7.0428	4.0662
R_z	Al7075; rough face turning	conf	3	58.2443	2.8349	1.6367
R_z	Al7075; rough face turning	fusion	3	53.1588	3.0071	1.7361
R_z	Al7075; rough face turning	int	4	64.0944	6.7954	3.3977
R_z	Al7075; finish wire EDM	FV	3	40.9502	15.8077	9.1266
R_z	Al7075; finish wire EDM	conf	3	121.8875	15.2925	8.8291
R_z	Al7075; finish wire EDM	fusion	3	209.3	22.9579	13.2548
R_z	Al7075; finish wire EDM	int	4	9.2575	5.8084	2.9042
R_z	Al7075; rough wire EDM	FV	3	6.4251	4.0044	2.3119
R_z	Al7075; rough wire EDM	conf	3	68.626	28.4267	16.4122

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_z	Al7075; rough wire EDM	fusion	3	204.5491	41.4081	23.907
R_z	Al7075; rough wire EDM	int	4	3.0782	2.9778	1.4889
R_z	C45 steel; burnishing after MF	FV	3	117.8012	68.9653	39.8171
R_z	C45 steel; burnishing after MF	conf	2	177.7252	43.8072	30.9764
R_z	C45 steel; burnishing after MF	fusion	3	230.7294	56.0392	32.3542
R_z	C45 steel; burnishing after MF	int	5	190.862	221.43	99.0265
R_z	C45 steel; glass bead blasting	FV	3	7.3558	6.1756	3.5655
R_z	C45 steel; glass bead blasting	conf	3	61.2674	22.2086	12.8221
R_z	C45 steel; glass bead blasting	fusion	3	108.9467	32.8216	18.9496
R_z	C45 steel; glass bead blasting	int	4	15.4041	1.3574	0.6787
R_z	C45 steel; grinding	FV	3	108.087	27.0204	15.6003
R_z	C45 steel; grinding	conf	3	56.2751	16.631	9.6019
R_z	C45 steel; grinding	fusion	3	89.197	14.576	8.4155
R_z	C45 steel; grinding	int	4	5.6186	1.2145	0.6072
R_z	C45 steel; honing	FV	3	22.6878	24.8318	14.3367
R_z	C45 steel; honing	conf	3	17.312	14.8711	8.5858
R_z	C45 steel; honing	fusion	3	49.4766	12.0898	6.9801
R_z	C45 steel; honing	int	4	7.7337	9.115	4.5575
R_z	C45 steel; finish milling	FV	3	7.1216	5.9606	3.4414
R_z	C45 steel; finish milling	conf	2	25.4192	10.5034	7.427
R_z	C45 steel; finish milling	fusion	3	48.6355	16.2621	9.3889
R_z	C45 steel; finish milling	int	4	6.0901	3.2246	1.6123
R_z	C45 steel; rough milling	FV	3	42.4851	3.6135	2.0863
R_z	C45 steel; rough milling	conf	2	27.6252	4.5729	3.2335
R_z	C45 steel; rough milling	fusion	3	18.6887	6.3098	3.643
R_z	C45 steel; rough milling	int	4	42.4434	6.3647	3.1824
R_z	C45 steel; finish face turning	FV	3	62.8672	2.0422	1.1791
R_z	C45 steel; finish face turning	conf	2	53.2612	2.8643	2.0254
R_z	C45 steel; finish face turning	fusion	3	46.9937	4.6478	2.6834
R_z	C45 steel; finish face turning	int	4	62.7766	3.7019	1.8509
R_z	C45 steel; rough face turning	FV	3	82.3461	4.8656	2.8091
R_z	C45 steel; rough face turning	conf	2	80.8595	1.169	0.8266
R_z	C45 steel; rough face turning	fusion	3	76.9108	2.2924	1.3235
R_z	C45 steel; rough face turning	int	4	86.2862	4.6747	2.3373
R_z	C45 steel; finish wire EDM	FV	3	21.6689	13.8032	7.9693
R_z	C45 steel; finish wire EDM	conf	3	146.1248	36.788	21.2396
R_z	C45 steel; finish wire EDM	fusion	3	217.0401	15.2474	8.8031
R_z	C45 steel; finish wire EDM	int	4	22.4182	5.511	2.7555
R_z	C45 steel; rough wire EDM	FV	3	1.6932	1.3389	0.773
R_z	C45 steel; rough wire EDM	conf	3	15.6206	6.0337	3.4836
R_z	C45 steel; rough wire EDM	fusion	3	83.8417	38.0141	21.9475
R_z	C45 steel; rough wire EDM	int	4	12.1403	10.8664	5.4332
R_z	ELLOR graphite; glass bead blasting	FV	3	12.6512	1.1824	0.6826
R_z	ELLOR graphite; glass bead blasting	conf	3	21.9977	1.9586	1.1308
R_z	ELLOR graphite; glass bead blasting	fusion	3	28.2333	2.467	1.4243
R_z	ELLOR graphite; glass bead blasting	int	4	16.9501	9.1113	4.5557
R_z	ELLOR graphite; grinding	FV	3	167.9148	3.3033	1.9072
R_z	ELLOR graphite; grinding	conf	3	198.9156	5.9803	3.4527
R_z	ELLOR graphite; grinding	fusion	3	219.2641	10.2442	5.9145
R_z	ELLOR graphite; grinding	int	4	174.9931	17.86	8.93
R_z	ELLOR graphite; honing	FV	3	43.8339	39.4747	22.7907
R_z	ELLOR graphite; honing	conf	3	102.4425	32.9474	19.0222
R_z	ELLOR graphite; honing	fusion	3	187.4351	39.8218	22.9912
R_z	ELLOR graphite; honing	int	4	22.8602	16.301	8.1505
R_z	ELLOR graphite; finish milling	FV	3	21.9829	6.8573	3.9591
R_z	ELLOR graphite; finish milling	conf	3	15.5453	2.0836	1.203
R_z	ELLOR graphite; finish milling	fusion	3	44.7717	35.6366	20.5748
R_z	ELLOR graphite; finish milling	int	4	22.839	31.718	15.859
R_z	ELLOR graphite; rough milling	FV	3	3.371	3.2899	1.8994
R_z	ELLOR graphite; rough milling	conf	3	32.6535	4.7492	2.7419

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_z	ELLOR graphite; rough milling	fusion	3	45.7788	7.5731	4.3723
R_z	ELLOR graphite; rough milling	int	4	32.2681	21.0006	10.5003
R_z	ELLOR graphite; finish face turning	FV	3	18.4183	2.73	1.5762
R_z	ELLOR graphite; finish face turning	conf	3	11.1306	3.5679	2.06
R_z	ELLOR graphite; finish face turning	fusion	3	27.391	8.2748	4.7775
R_z	ELLOR graphite; finish face turning	int	4	15.1867	23.5962	11.7981
R_z	ELLOR graphite; rough face turning	FV	3	7.3489	1.014	0.5854
R_z	ELLOR graphite; rough face turning	conf	3	1.4049	1.2516	0.7226
R_z	ELLOR graphite; rough face turning	fusion	3	8.3011	2.6326	1.52
R_z	ELLOR graphite; rough face turning	int	4	13.8595	23.7535	11.8767
R_z	ELLOR graphite; finish wire EDM	FV	3	20.9224	4.4032	2.5422
R_z	ELLOR graphite; finish wire EDM	conf	3	43.3724	2.7536	1.5898
R_z	ELLOR graphite; finish wire EDM	fusion	3	60.9124	6.0426	3.4887
R_z	ELLOR graphite; finish wire EDM	int	3	36.5172	5.1526	2.9749
R_z	ELLOR graphite; rough wire EDM	FV	3	2.98	2.8945	1.6711
R_z	ELLOR graphite; rough wire EDM	conf	3	24.2658	3.8745	2.2369
R_z	ELLOR graphite; rough wire EDM	fusion	3	34.1806	5.1113	2.951
R_z	ELLOR graphite; rough wire EDM	int	4	40.593	43.665	21.8325
R_z	MO58A brass; burnishing after MF	FV	4	445.8653	251.5522	125.7761
R_z	MO58A brass; burnishing after MF	conf	3	440.0569	42.7006	24.6532
R_z	MO58A brass; burnishing after MF	fusion	3	589.3593	61.5984	35.5638
R_z	MO58A brass; burnishing after MF	int	3	423.3188	512.7949	296.0623
R_z	MO58A brass; glass bead blasting	FV	3	24.344	12.3163	7.1108
R_z	MO58A brass; glass bead blasting	conf	3	97.4676	40.2543	23.2408
R_z	MO58A brass; glass bead blasting	fusion	3	141.5	69.5178	40.1361
R_z	MO58A brass; glass bead blasting	int	4	14.9918	6.6603	3.3302
R_z	MO58A brass; grinding	FV	3	51.5176	19.5051	11.2612
R_z	MO58A brass; grinding	conf	3	39.8341	11.2415	6.4903
R_z	MO58A brass; grinding	fusion	3	78.3011	5.9908	3.4588
R_z	MO58A brass; grinding	int	4	8.1659	4.3822	2.1911
R_z	MO58A brass; honing	FV	3	24.744	21.9918	12.697
R_z	MO58A brass; honing	conf	3	17.3319	14.8544	8.5762
R_z	MO58A brass; honing	fusion	3	51.3419	13.2439	7.6464
R_z	MO58A brass; honing	int	4	8.5704	7.0928	3.5464
R_z	MO58A brass; finish milling	FV	3	248.6251	123.9972	71.5898
R_z	MO58A brass; finish milling	conf	3	295.7917	52.0189	30.0331
R_z	MO58A brass; finish milling	fusion	3	411.3647	69.1366	39.916
R_z	MO58A brass; finish milling	int	4	123.5936	152.6206	76.3103
R_z	MO58A brass; rough milling	FV	3	39.1471	27.2891	15.7554
R_z	MO58A brass; rough milling	conf	3	43.6895	2.5243	1.4574
R_z	MO58A brass; rough milling	fusion	3	26.5235	2.442	1.4099
R_z	MO58A brass; rough milling	int	4	63.4079	10.1476	5.0738
R_z	MO58A brass; finish face turning	FV	3	58.8117	5.2466	3.0291
R_z	MO58A brass; finish face turning	conf	3	53.1362	2.9733	1.7167
R_z	MO58A brass; finish face turning	fusion	3	43.1634	3.208	1.8521
R_z	MO58A brass; finish face turning	int	4	61.4341	3.6446	1.8223
R_z	MO58A brass; rough face turning	FV	3	24.5314	6.5028	3.7544
R_z	MO58A brass; rough face turning	conf	3	21.811	4.6118	2.6626
R_z	MO58A brass; rough face turning	fusion	3	7.0767	3.4093	1.9683
R_z	MO58A brass; rough face turning	int	4	31.5256	4.2861	2.143
R_z	MO58A brass; finish wire EDM	FV	3	32.1191	12.9	7.4478
R_z	MO58A brass; finish wire EDM	conf	3	77.486	18.5186	10.6917

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_z	MO58A brass; finish wire EDM	fusion	3	146.7046	27.8633	16.0869
R_z	MO58A brass; finish wire EDM	int	4	3.3146	2.6803	1.3401
R_z	MO58A brass; rough wire EDM	FV	3	28.143	3.5591	2.0548
R_z	MO58A brass; rough wire EDM	conf	3	12.2904	12.256	7.076
R_z	MO58A brass; rough wire EDM	fusion	3	16.2946	11.9573	6.9035
R_z	MO58A brass; rough wire EDM	int	4	21.7831	8.1235	4.0617
R_z	Ti6Al4V; burnishing after MF	FV	3	131.1393	62.8832	36.3056
R_z	Ti6Al4V; burnishing after MF	conf	3	186.4274	48.188	27.8213
R_z	Ti6Al4V; burnishing after MF	fusion	3	227.9338	44.3178	25.5869
R_z	Ti6Al4V; burnishing after MF	int	4	101.0094	41.4979	20.7489
R_z	Ti6Al4V; glass bead blasting	FV	3	12.4315	10.7233	6.1911
R_z	Ti6Al4V; glass bead blasting	conf	3	85.3118	18.1184	10.4606
R_z	Ti6Al4V; glass bead blasting	fusion	3	160.6849	33.8849	19.5635
R_z	Ti6Al4V; glass bead blasting	int	4	14.1632	2.6217	1.3109
R_z	Ti6Al4V; grinding	FV	3	122.404	23.9898	13.8505
R_z	Ti6Al4V; grinding	conf	3	148.0479	25.1892	14.543
R_z	Ti6Al4V; grinding	fusion	3	192.7492	23.7196	13.6945
R_z	Ti6Al4V; grinding	int	4	89.6835	12.3719	6.186
R_z	Ti6Al4V; honing	FV	3	99.4177	31.7403	18.3252
R_z	Ti6Al4V; honing	conf	3	82.1672	24.392	14.0827
R_z	Ti6Al4V; honing	fusion	3	144.3489	18.7806	10.843
R_z	Ti6Al4V; honing	int	4	10.3941	3.3367	1.6683
R_z	Ti6Al4V; finish milling	FV	3	52.8511	31.559	18.2206
R_z	Ti6Al4V; finish milling	conf	3	87.4199	20.8479	12.0365
R_z	Ti6Al4V; finish milling	fusion	3	126.4347	21.6315	12.4889
R_z	Ti6Al4V; finish milling	int	4	15.9796	9.5988	4.7994
R_z	Ti6Al4V; rough milling	FV	3	28.9579	1.6774	0.9684
R_z	Ti6Al4V; rough milling	conf	3	10.7568	7.1731	4.1414
R_z	Ti6Al4V; rough milling	fusion	3	16.9048	12.7849	7.3813
R_z	Ti6Al4V; rough milling	int	4	42.2734	25.7852	12.8926
R_z	Ti6Al4V; finish face turning	FV	3	13.3834	7.1167	4.1089
R_z	Ti6Al4V; finish face turning	conf	3	10.1294	5.3776	3.1047
R_z	Ti6Al4V; finish face turning	fusion	3	12.0113	11.2178	6.4766
R_z	Ti6Al4V; finish face turning	int	4	20.5054	13.2661	6.633
R_z	Ti6Al4V; rough face turning	FV	3	61.1839	2.7064	1.5625
R_z	Ti6Al4V; rough face turning	conf	3	52.042	7.012	4.0484
R_z	Ti6Al4V; rough face turning	fusion	3	42.3092	6.7194	3.8794
R_z	Ti6Al4V; rough face turning	int	4	61.754	8.0389	4.0194
R_z	Ti6Al4V; finish wire EDM	FV	3	63.1809	21.5938	12.4672
R_z	Ti6Al4V; finish wire EDM	conf	3	132.9912	29.391	16.9689
R_z	Ti6Al4V; finish wire EDM	fusion	3	226.3878	33.1389	19.1327
R_z	Ti6Al4V; finish wire EDM	int	4	18.4478	11.3173	5.6586
R_z	Ti6Al4V; rough wire EDM	FV	3	3.3084	1.7325	1.0002
R_z	Ti6Al4V; rough wire EDM	conf	3	47.7056	24.0447	13.8822
R_z	Ti6Al4V; rough wire EDM	fusion	3	141.2923	54.4987	31.4648
R_z	Ti6Al4V; rough wire EDM	int	4	10.1169	9.691	4.8455
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	FV	3	45.8608	50.3966	29.0965
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	conf	3	75.8648	24.4858	14.1369
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	fusion	3	131.927	25.4755	14.7083
R_{z1max}	AISI 304 / EN 1.4301; burnishing after MF	int	4	45.3898	6.7272	3.3636
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	FV	3	13.5657	11.9205	6.8823
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	conf	3	29.0926	11.1124	6.4158
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	fusion	3	93.7232	19.1661	11.0655
R_{z1max}	AISI 304 / EN 1.4301; glass bead blasting	int	4	39.1489	3.0044	1.5022
R_{z1max}	AISI 304 / EN 1.4301; grinding	FV	3	24.6388	14.5355	8.3921
R_{z1max}	AISI 304 / EN 1.4301; grinding	conf	3	7.0768	5.1102	2.9504

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{z1max}	AISI 304 / EN 1.4301; grinding	fusion	3	37.4174	9.7352	5.6206
R_{z1max}	AISI 304 / EN 1.4301; grinding	int	4	8.188	2.8876	1.4438
R_{z1max}	AISI 304 / EN 1.4301; honing	FV	3	21.5418	22.6609	13.0833
R_{z1max}	AISI 304 / EN 1.4301; honing	conf	3	10.008	5.1929	2.9981
R_{z1max}	AISI 304 / EN 1.4301; honing	fusion	3	53.0344	7.6499	4.4167
R_{z1max}	AISI 304 / EN 1.4301; honing	int	4	20.2059	8.0151	4.0075
R_{z1max}	AISI 304 / EN 1.4301; finish milling	FV	3	22.734	32.2384	18.6128
R_{z1max}	AISI 304 / EN 1.4301; finish milling	conf	3	40.1979	23.5807	13.6143
R_{z1max}	AISI 304 / EN 1.4301; finish milling	fusion	3	71.8063	34.2245	19.7595
R_{z1max}	AISI 304 / EN 1.4301; finish milling	int	4	34.6937	27.5987	13.7993
R_{z1max}	AISI 304 / EN 1.4301; rough milling	FV	3	65.9812	8.7943	5.0774
R_{z1max}	AISI 304 / EN 1.4301; rough milling	conf	3	66.8063	5.9198	3.4178
R_{z1max}	AISI 304 / EN 1.4301; rough milling	fusion	3	59.5569	5.1629	2.9808
R_{z1max}	AISI 304 / EN 1.4301; rough milling	int	4	63.0174	25.2491	12.6245
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	FV	3	45.3176	27.1471	15.6734
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	conf	3	65.06	1.468	0.8476
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	fusion	3	60.7557	2.2764	1.3143
R_{z1max}	AISI 304 / EN 1.4301; finish face turning	int	4	66.9227	6.6013	3.3007
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	FV	3	27.2225	8.5082	4.9122
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	conf	3	22.3269	2.443	1.4105
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	fusion	3	13.2502	4.9062	2.8326
R_{z1max}	AISI 304 / EN 1.4301; rough face turning	int	4	19.3753	2.6541	1.327
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	FV	3	12.4448	5.9708	3.4472
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	conf	3	67.4263	24.1037	13.9163
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	fusion	3	150.5277	26.6069	15.3615
R_{z1max}	AISI 304 / EN 1.4301; finish wire EDM	int	4	23.6299	8.2916	4.1458
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	FV	3	8.2695	0.4113	0.2374
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	conf	3	2.9258	2.3305	1.3455
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	fusion	3	26.5678	21.9519	12.6739
R_{z1max}	AISI 304 / EN 1.4301; rough wire EDM	int	3	4.9631	0.9632	0.5561
R_{z1max}	Al7075; burnishing after MF	FV	3	226.8398	144.3102	83.3175
R_{z1max}	Al7075; burnishing after MF	conf	3	224.8896	53.0599	30.6342
R_{z1max}	Al7075; burnishing after MF	fusion	3	304.5597	66.015	38.1138
R_{z1max}	Al7075; burnishing after MF	int	4	236.4997	312.4754	156.2377
R_{z1max}	Al7075; glass bead blasting	FV	3	12.4437	11.2187	6.4771
R_{z1max}	Al7075; glass bead blasting	conf	3	37.2004	23.8746	13.784
R_{z1max}	Al7075; glass bead blasting	fusion	3	120.3013	73.6369	42.5143
R_{z1max}	Al7075; glass bead blasting	int	4	17.7892	4.5668	2.2834
R_{z1max}	Al7075; grinding	FV	3	20.4378	11.5879	6.6903
R_{z1max}	Al7075; grinding	conf	3	38.1776	6.9309	4.0016

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{z1max}	Al7075; grinding	fusion	3	23.8921	5.7553	3.3228
R_{z1max}	Al7075; grinding	int	4	55.7983	2.6182	1.3091
R_{z1max}	Al7075; honing	FV	3	18.6122	14.9707	8.6434
R_{z1max}	Al7075; honing	conf	3	43.754	8.0574	4.6519
R_{z1max}	Al7075; honing	fusion	3	27.2622	6.7134	3.876
R_{z1max}	Al7075; honing	int	4	58.8556	1.5749	0.7874
R_{z1max}	Al7075; finish milling	FV	3	29.9367	31.3897	18.1229
R_{z1max}	Al7075; finish milling	conf	3	14.7489	14.1033	8.1426
R_{z1max}	Al7075; finish milling	fusion	3	38.8628	20.4873	11.8283
R_{z1max}	Al7075; finish milling	int	4	49.3092	24.1068	12.0534
R_{z1max}	Al7075; rough milling	FV	3	101.9539	79.9796	46.1762
R_{z1max}	Al7075; rough milling	conf	3	52.0281	16.7961	9.6972
R_{z1max}	Al7075; rough milling	fusion	3	99.3735	21.3388	12.32
R_{z1max}	Al7075; rough milling	int	4	66.88	22.8331	11.4166
R_{z1max}	Al7075; finish face turning	FV	3	50.5319	12.6153	7.2835
R_{z1max}	Al7075; finish face turning	conf	3	53.107	6.6483	3.8384
R_{z1max}	Al7075; finish face turning	fusion	3	41.807	7.7386	4.4679
R_{z1max}	Al7075; finish face turning	int	4	60.1521	13.5637	6.7818
R_{z1max}	Al7075; rough face turning	FV	3	32.6729	6.4419	3.7192
R_{z1max}	Al7075; rough face turning	conf	3	26.3534	5.9739	3.449
R_{z1max}	Al7075; rough face turning	fusion	3	21.95	5.7017	3.2919
R_{z1max}	Al7075; rough face turning	int	4	36.0568	4.7084	2.3542
R_{z1max}	Al7075; finish wire EDM	FV	3	29.1717	14.433	8.3329
R_{z1max}	Al7075; finish wire EDM	conf	3	95.8779	13.4541	7.7677
R_{z1max}	Al7075; finish wire EDM	fusion	3	184.8764	41.9	24.191
R_{z1max}	Al7075; finish wire EDM	int	4	13.8394	8.7936	4.3968
R_{z1max}	Al7075; rough wire EDM	FV	3	15.1578	3.2013	1.8483
R_{z1max}	Al7075; rough wire EDM	conf	3	76.0078	26.5251	15.3143
R_{z1max}	Al7075; rough wire EDM	fusion	3	195.3574	37.6943	21.7628
R_{z1max}	Al7075; rough wire EDM	int	4	19.9688	13.9	6.95
R_{z1max}	C45 steel; burnishing after MF	FV	3	71.0881	56.6451	32.7041
R_{z1max}	C45 steel; burnishing after MF	conf	2	114.5407	34.5209	24.41
R_{z1max}	C45 steel; burnishing after MF	fusion	3	153.2613	44.3324	25.5953
R_{z1max}	C45 steel; burnishing after MF	int	5	130.7283	135.1961	60.4615
R_{z1max}	C45 steel; glass bead blasting	FV	3	6.8603	7.967	4.5997
R_{z1max}	C45 steel; glass bead blasting	conf	3	43.004	19.6207	11.328
R_{z1max}	C45 steel; glass bead blasting	fusion	3	91.4057	33.5844	19.3899
R_{z1max}	C45 steel; glass bead blasting	int	4	20.3273	6.1363	3.0682
R_{z1max}	C45 steel; grinding	FV	3	88.2985	28.7946	16.6246
R_{z1max}	C45 steel; grinding	conf	3	34.487	16.7599	9.6763
R_{z1max}	C45 steel; grinding	fusion	3	60.6201	12.2339	7.0632
R_{z1max}	C45 steel; grinding	int	4	11.088	3.8777	1.9389
R_{z1max}	C45 steel; honing	FV	3	15.1993	16.6736	9.6265
R_{z1max}	C45 steel; honing	conf	3	7.9535	7.0236	4.0551
R_{z1max}	C45 steel; honing	fusion	3	22.8615	9.2949	5.3664
R_{z1max}	C45 steel; honing	int	4	18.9083	9.2633	4.6317
R_{z1max}	C45 steel; finish milling	FV	3	11.258	4.0918	2.3624
R_{z1max}	C45 steel; finish milling	conf	2	6.164	8.6637	6.1262
R_{z1max}	C45 steel; finish milling	fusion	3	33.6763	9.7389	5.6228
R_{z1max}	C45 steel; finish milling	int	4	28.853	19.2427	9.6213
R_{z1max}	C45 steel; rough milling	FV	3	34.4637	2.2428	1.2949
R_{z1max}	C45 steel; rough milling	conf	2	19.6151	4.5555	3.2212
R_{z1max}	C45 steel; rough milling	fusion	3	12.1267	5.9432	3.4313
R_{z1max}	C45 steel; rough milling	int	4	33.0503	4.4081	2.2041
R_{z1max}	C45 steel; finish face turning	FV	3	68.6502	1.314	0.7587
R_{z1max}	C45 steel; finish face turning	conf	2	61.7175	1.9673	1.3911
R_{z1max}	C45 steel; finish face turning	fusion	3	57.7858	2.9731	1.7165
R_{z1max}	C45 steel; finish face turning	int	4	66.7736	1.7289	0.8645
R_{z1max}	C45 steel; rough face turning	FV	3	91.5329	1.7144	0.9898
R_{z1max}	C45 steel; rough face turning	conf	2	90.1413	0.7219	0.5105
R_{z1max}	C45 steel; rough face turning	fusion	3	88.3118	1.1331	0.6542
R_{z1max}	C45 steel; rough face turning	int	4	92.7096	1.6659	0.8329
R_{z1max}	C45 steel; finish wire EDM	FV	3	17.0885	12.6457	7.301
R_{z1max}	C45 steel; finish wire EDM	conf	3	131.4382	29.2918	16.9116

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{z1max}	C45 steel; finish wire EDM	fusion	3	223.2935	55.8677	32.2553
R_{z1max}	C45 steel; finish wire EDM	int	4	25.787	6.159	3.0795
R_{z1max}	C45 steel; rough wire EDM	FV	3	6.0941	1.0535	0.6082
R_{z1max}	C45 steel; rough wire EDM	conf	3	7.423	4.867	2.81
R_{z1max}	C45 steel; rough wire EDM	fusion	3	107.3269	36.9915	21.3571
R_{z1max}	C45 steel; rough wire EDM	int	4	7.1887	11.5891	5.7945
R_{z1max}	ELLOR graphite; glass bead blasting	FV	3	9.3137	0.7064	0.4078
R_{z1max}	ELLOR graphite; glass bead blasting	conf	3	4.2568	1.9894	1.1486
R_{z1max}	ELLOR graphite; glass bead blasting	fusion	3	1.3225	0.6752	0.3898
R_{z1max}	ELLOR graphite; glass bead blasting	int	4	5.9158	1.8346	0.9173
R_{z1max}	ELLOR graphite; grinding	FV	3	140.8726	1.229	0.7096
R_{z1max}	ELLOR graphite; grinding	conf	3	155.7808	2.7912	1.6115
R_{z1max}	ELLOR graphite; grinding	fusion	3	168.5271	5.9402	3.4296
R_{z1max}	ELLOR graphite; grinding	int	4	154.9205	25.7193	12.8596
R_{z1max}	ELLOR graphite; honing	FV	3	22.9796	16.3753	9.4543
R_{z1max}	ELLOR graphite; honing	conf	3	13.6189	15.6787	9.0521
R_{z1max}	ELLOR graphite; honing	fusion	3	60.7945	20.5047	11.8384
R_{z1max}	ELLOR graphite; honing	int	4	37.3142	12.1015	6.0508
R_{z1max}	ELLOR graphite; finish milling	FV	3	24.4645	4.5428	2.6228
R_{z1max}	ELLOR graphite; finish milling	conf	3	9.4474	0.7325	0.4229
R_{z1max}	ELLOR graphite; finish milling	fusion	3	28.6043	47.7127	27.5469
R_{z1max}	ELLOR graphite; finish milling	int	4	27.3455	35.0852	17.5426
R_{z1max}	ELLOR graphite; rough milling	FV	3	5.0867	2.503	1.4451
R_{z1max}	ELLOR graphite; rough milling	conf	3	8.1609	1.9491	1.1253
R_{z1max}	ELLOR graphite; rough milling	fusion	3	17.8703	6.1366	3.543
R_{z1max}	ELLOR graphite; rough milling	int	4	18.5524	35.5649	17.7824
R_{z1max}	ELLOR graphite; finish face turning	FV	3	23.1496	1.9199	1.1085
R_{z1max}	ELLOR graphite; finish face turning	conf	3	7.2718	1.0698	0.6177
R_{z1max}	ELLOR graphite; finish face turning	fusion	3	4.2795	5.6583	3.2668
R_{z1max}	ELLOR graphite; finish face turning	int	4	21.5755	27.4302	13.7151
R_{z1max}	ELLOR graphite; rough face turning	FV	3	15.7092	0.5888	0.34
R_{z1max}	ELLOR graphite; rough face turning	conf	3	11.5679	0.4962	0.2865
R_{z1max}	ELLOR graphite; rough face turning	fusion	3	6.73	1.9356	1.1175
R_{z1max}	ELLOR graphite; rough face turning	int	4	19.3078	17.9202	8.9601
R_{z1max}	ELLOR graphite; finish wire EDM	FV	3	14.4252	3.3085	1.9102
R_{z1max}	ELLOR graphite; finish wire EDM	conf	3	15.8257	3.2931	1.9013
R_{z1max}	ELLOR graphite; finish wire EDM	fusion	3	33.0853	3.3725	1.9471
R_{z1max}	ELLOR graphite; finish wire EDM	int	3	11.8726	3.3787	1.9507
R_{z1max}	ELLOR graphite; rough wire EDM	FV	3	13.827	1.2171	0.7027
R_{z1max}	ELLOR graphite; rough wire EDM	conf	3	7.2353	1.9754	1.1405
R_{z1max}	ELLOR graphite; rough wire EDM	fusion	3	1.9671	1.0089	0.5825
R_{z1max}	ELLOR graphite; rough wire EDM	int	4	30.2392	39.2801	19.6401
R_{z1max}	MO58A brass; burnishing after MF	FV	4	334.0121	187.9916	93.9958
R_{z1max}	MO58A brass; burnishing after MF	conf	3	320.4901	37.1009	21.4202
R_{z1max}	MO58A brass; burnishing after MF	fusion	3	444.2748	51.3583	29.6518
R_{z1max}	MO58A brass; burnishing after MF	int	3	350.0031	434.3713	250.7844
R_{z1max}	MO58A brass; glass bead blasting	FV	3	21.7657	13.5338	7.8137
R_{z1max}	MO58A brass; glass bead blasting	conf	3	82.4035	38.2546	22.0863

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{z1max}	MO58A brass; glass bead blasting	fusion	3	136.1441	82.7612	47.7822
R_{z1max}	MO58A brass; glass bead blasting	int	4	10.3133	6.6958	3.3479
R_{z1max}	MO58A brass; grinding	FV	3	38.1975	21.1402	12.2053
R_{z1max}	MO58A brass; grinding	conf	3	16.0377	9.7935	5.6543
R_{z1max}	MO58A brass; grinding	fusion	3	47.3435	5.1765	2.9886
R_{z1max}	MO58A brass; grinding	int	4	7.9573	2.3687	1.1844
R_{z1max}	MO58A brass; honing	FV	3	14.9184	16.1212	9.3076
R_{z1max}	MO58A brass; honing	conf	3	8.549	7.7366	4.4668
R_{z1max}	MO58A brass; honing	fusion	3	21.9007	11.4778	6.6267
R_{z1max}	MO58A brass; honing	int	4	23.2753	6.415	3.2075
R_{z1max}	MO58A brass; finish milling	FV	3	144.2662	80.3403	46.3845
R_{z1max}	MO58A brass; finish milling	conf	3	162.9144	31.1716	17.9969
R_{z1max}	MO58A brass; finish milling	fusion	3	243.7229	52.7823	30.4739
R_{z1max}	MO58A brass; finish milling	int	4	59.8498	73.2319	36.616
R_{z1max}	MO58A brass; rough milling	FV	3	37.2132	25.4454	14.6909
R_{z1max}	MO58A brass; rough milling	conf	3	33.6127	3.3561	1.9376
R_{z1max}	MO58A brass; rough milling	fusion	3	17.7868	5.1669	2.9831
R_{z1max}	MO58A brass; rough milling	int	4	55.9937	8.7937	4.3968
R_{z1max}	MO58A brass; finish face turning	FV	3	65.1266	2.8239	1.6304
R_{z1max}	MO58A brass; finish face turning	conf	3	60.3452	2.7155	1.5678
R_{z1max}	MO58A brass; finish face turning	fusion	3	54.2519	3.5956	2.0759
R_{z1max}	MO58A brass; finish face turning	int	4	65.8451	1.6447	0.8224
R_{z1max}	MO58A brass; rough face turning	FV	3	27.5048	5.5949	3.2302
R_{z1max}	MO58A brass; rough face turning	conf	3	24.4644	4.3892	2.5341
R_{z1max}	MO58A brass; rough face turning	fusion	3	12.1981	4.3717	2.524
R_{z1max}	MO58A brass; rough face turning	int	4	34.4251	3.4254	1.7127
R_{z1max}	MO58A brass; finish wire EDM	FV	3	28.3736	12.0799	6.9743
R_{z1max}	MO58A brass; finish wire EDM	conf	3	64.669	15.0318	8.6786
R_{z1max}	MO58A brass; finish wire EDM	fusion	3	128.8566	24.7936	14.3146
R_{z1max}	MO58A brass; finish wire EDM	int	4	10.8225	3.4858	1.7429
R_{z1max}	MO58A brass; rough wire EDM	FV	3	31.4442	3.0073	1.7363
R_{z1max}	MO58A brass; rough wire EDM	conf	3	14.2635	11.8835	6.8609
R_{z1max}	MO58A brass; rough wire EDM	fusion	3	18.0412	13.5572	7.8272
R_{z1max}	MO58A brass; rough wire EDM	int	4	26.5315	6.3546	3.1773
R_{z1max}	Ti6Al4V; burnishing after MF	FV	3	95.4989	54.9689	31.7363
R_{z1max}	Ti6Al4V; burnishing after MF	conf	3	139.1585	42.7221	24.6656
R_{z1max}	Ti6Al4V; burnishing after MF	fusion	3	175.1791	39.4425	22.7722
R_{z1max}	Ti6Al4V; burnishing after MF	int	4	68.4004	48.6568	24.3284
R_{z1max}	Ti6Al4V; glass bead blasting	FV	3	11.9658	4.9201	2.8406
R_{z1max}	Ti6Al4V; glass bead blasting	conf	3	49.6178	14.7243	8.5011
R_{z1max}	Ti6Al4V; glass bead blasting	fusion	3	116.98	35.1256	20.2798
R_{z1max}	Ti6Al4V; glass bead blasting	int	4	25.0203	2.7659	1.3829
R_{z1max}	Ti6Al4V; grinding	FV	3	45.6334	13.3873	7.7292
R_{z1max}	Ti6Al4V; grinding	conf	3	60.0395	16.0498	9.2663
R_{z1max}	Ti6Al4V; grinding	fusion	3	85.5112	12.7295	7.3494
R_{z1max}	Ti6Al4V; grinding	int	4	27.2632	7.0015	3.5007
R_{z1max}	Ti6Al4V; honing	FV	3	61.2279	26.721	15.4274
R_{z1max}	Ti6Al4V; honing	conf	3	36.6854	17.7181	10.2296
R_{z1max}	Ti6Al4V; honing	fusion	3	83.6203	10.3142	5.9549
R_{z1max}	Ti6Al4V; honing	int	4	13.9073	3.4823	1.7412
R_{z1max}	Ti6Al4V; finish milling	FV	3	24.0739	25.8965	14.9514
R_{z1max}	Ti6Al4V; finish milling	conf	3	54.2432	21.4123	12.3624
R_{z1max}	Ti6Al4V; finish milling	fusion	3	85.141	23.5261	13.5828
R_{z1max}	Ti6Al4V; finish milling	int	4	8.7805	6.1122	3.0561
R_{z1max}	Ti6Al4V; rough milling	FV	3	55.5398	15.3529	8.864
R_{z1max}	Ti6Al4V; rough milling	conf	3	51.2429	7.0033	4.0433
R_{z1max}	Ti6Al4V; rough milling	fusion	3	37.6514	7.7706	4.4864
R_{z1max}	Ti6Al4V; rough milling	int	4	58.8513	23.5213	11.7606
R_{z1max}	Ti6Al4V; finish face turning	FV	3	29.2126	6.18	3.568
R_{z1max}	Ti6Al4V; finish face turning	conf	3	19.3122	11.3772	6.5686
R_{z1max}	Ti6Al4V; finish face turning	fusion	3	11.2862	7.3676	4.2537
R_{z1max}	Ti6Al4V; finish face turning	int	4	33.0201	13.2459	6.623
R_{z1max}	Ti6Al4V; rough face turning	FV	3	39.9207	6.5319	3.7712
R_{z1max}	Ti6Al4V; rough face turning	conf	3	27.9585	11.8071	6.8168

Continued on next page

Parameter	Material/process	System	n	Mean	SD	SE
R_{z1max}	Ti6Al4V; rough face turning	fusion	3	14.0159	11.1925	6.462
R_{z1max}	Ti6Al4V; rough face turning	int	4	43.9619	6.6609	3.3304
R_{z1max}	Ti6Al4V; finish wire EDM	FV	3	47.9277	19.9302	11.5067
R_{z1max}	Ti6Al4V; finish wire EDM	conf	3	101.3034	26.3617	15.22
R_{z1max}	Ti6Al4V; finish wire EDM	fusion	3	182.659	27.2742	15.7468
R_{z1max}	Ti6Al4V; rough wire EDM	int	4	27.0085	9.719	4.8595
R_{z1max}	Ti6Al4V; rough wire EDM	FV	3	12.6316	1.6151	0.9325
R_{z1max}	Ti6Al4V; rough wire EDM	conf	3	51.0428	30.8612	17.8177
R_{z1max}	Ti6Al4V; rough wire EDM	fusion	3	136.3549	44.8491	25.8936
R_{z1max}	Ti6Al4V; rough wire EDM	int	4	12.6058	9.9386	4.9693

2.4 Table S4: Internal tactile repeatability summary

Table S4: Internal repeatability summary of the tactile reference across the eight-parameter manuscript subset. Each row aggregates one archived tactile descriptor per parameter-surface group from the corresponding optics-vs-tactile export. For strictly positive parameters, the reported summary is the relative standard error of the tactile mean, $100 u_S / |S|$, in percent; for R_{sk} , the reported summary is u_S in native parameter units because relative normalisation becomes unstable near zero.

Parameter	Groups	n_S	Median [Q1, Q3]
R_a	59	20	0.89 [0.46, 1.34]%
R_q	59	20	0.93 [0.51, 1.76]%
R_{sk}	59	20	0.0403 [0.0182, 0.0871] (u_S)
R_{sm}	59	20	1.37 [0.9, 2.05]%
R_t	59	20	2.73 [1.89, 4.98]%
R_v	59	20	1.24 [0.86, 1.99]%
R_z	59	20	1.1 [0.74, 1.73]%
R_{z1max}	59	20	3.04 [1.75, 5.01]%

3 Representative supplementary figures

3.1 Case A: Ti6Al4V after finish milling (R_q)




Figure S1: R_q : main effects of system on $|diff|(\%)$ for Ti6Al4V after finish milling




Figure S2: R_q : |diff| (%) versus illumination wavelength for Ti6Al4V after finish milling with fitted screening lines




Figure S3: R_q : technical-distance heatmap between systems for Ti6Al4V after finish milling, based on mean |diff| (%)

3.2 Case B: C45 after wire EDM rough cutting (single-pass) (R_a)




Figure S4: R_a : optical-tactile comparison for C45 after wire EDM rough cutting (single-pass), summarising relative disagreement across systems




Figure S5: R_a : $|diff|(\%)$ versus illumination wavelength for C45 after wire EDM rough cutting (single-pass) with fitted screening lines