

Coroutines

All you need to know about the coroutines

Dawid Pilarski

dawid.pilarski@tomtom.com

blog.panicsoftware.com

Agenda

Coroutine theory - what are the coroutines?

Practical part I - using cppcoro

Theory - implementing own coroutines types

Practical part II - implementing own coroutines types

Coroutine theory - what are the coroutines?

What are the coroutines?

Coroutines are **generalization** of the function, that can be:

- created

What are the coroutines?

Coroutines are **generalization** of the function, that can be:

- created
- **called**

What are the coroutines?

Coroutines are **generalization** of the function, that can be:

- created
- called
- **returned from**

What are the coroutines?

Coroutines are **generalization** of the function, that can be:

- created
- called
- returned from
- **suspended**

What are the coroutines?

Coroutines are **generalization** of the function, that can be:

- created
- called
- returned from
- suspended
- **resumed**


What are the coroutines?

Coroutines are **generalization** of the function, that can be:


- created
- called
- returned from
- suspended
- resumed
- **destroyed**

Coroutine flowchart

Function's flow:




Coroutine flow:




Possible coroutines implementations

Language based



Library based



Closer look into Boost.Fiber

- Need to allocate the stack for the Fiber/Coroutine

Closer look into Boost.Fiber

- Need to allocate the stack for the Fiber/Coroutine
- Can be suspended from the top level functions and below

Closer look into Boost.Fiber

- Need to allocate the stack for the Fiber/Coroutine
- Can be suspended from the top level functions and below
- Allocation of the memory in advance

Closer look into Boost.Fiber

- Need to allocate the stack for the Fiber/Coroutine
- Can be suspended from the top level functions and below
- Allocation of the memory in advance
- Hard to optimize by compilers

Closer look into built-in coroutines

include in the view also `boost.fiber` for comparison

- Need to allocate the frame for the Coroutine

Closer look into built-in coroutines

include in the view also `boost.fiber` for comparison

- Need to allocate the frame for the Coroutine
- Can be suspended only from the top level functions

Closer look into built-in coroutines

include in the view also `boost.fiber` for comparison

- Need to allocate the frame for the Coroutine
- Can be suspended only from the top level functions
- Minimal memory allocation

Closer look into built-in coroutines

include in the view also `boost.fiber` for comparison

- Need to allocate the frame for the Coroutine
- Can be suspended only from the top level functions
- Minimal memory allocation
- Easy to optimize by compilers

Coroutine declarations

Same as functions

```
// returned-type    name      arguments  
//|-----| |-----| |-----|  
generator<int> fibonacci (int from_value);
```

Whether the function is a coroutine depends on it's definition.

3 new keywords

`co_return`

Returning (or not) value and finishing the coroutine

`co_yield`

Returning intermediate value from the coroutine

`co_await`

Awaiting completion of the "task"

Practical part I - using cppcoro

generators - Fibonacci sequence

```
cppcoro::generator<unsigned long long> fibonacci_gen() {  
    std::array arr{0ull, 0ull};  
    unsigned long long result=0;  
  
    do {  
        co_yield result;  
        if(result == 0 and arr == std::array{0ull, 0ull})  
            result = 1;  
        else if (result == 1 and arr == std::array{0ull, 0ull})  
            arr = {0, 1};  
        else{  
            arr[0] = arr[1];  
            arr[1] = result;  
            result = arr[0] + arr[1];  
        }  
    } while (result >= arr[1]);  
}
```

generators - exercise

Implement any generator:

- square number series



- triangular number series



tasks and events

```
void test(){
    single_consumer_event event;
    cppcoro::sync_wait(cppcoro::when_all_ready(
        [&]() -> cppcoro::task<> {
            while(true){
                co_await event;
                event.reset();
                std::this_thread_sleep(500ms)
            }
        }(),
        [&]() -> cppcoro::task<>{
            while(true){
                event.set();
            }
        }()
    ));
}
```

Write an application, that will at the same time (almost)

CHECK IF IT WORKS

implement framework for that.

- Read large content from a file
- Display dots every second

other (for now only msvc)

- mutexes
- file I/O operations
- networking operations

other (for now only msvc)

```
cppcoro::task<int> count_lines(std::string path)
{
    auto file = co_await cppcoro::read_only_file::open(path);

    int lineCount = 0;
    char buffer[1024];
    size_t bytesRead;
    std::uint64_t offset = 0;
    do
    {
        bytesRead = co_await file.read(offset, buffer, sizeof(buffer));
        lineCount += std::count(buffer, buffer + bytesRead, '\n');
        offset += bytesRead;
    } while (bytesRead > 0);

    co_return lineCount;
}
```

Theory - implementing own coroutines types

promise_type

- `promise_type` is responsible for coroutine's behavior:

promise_type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start

promise_type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception

promise_type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end

promise_type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value

promise_type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value
 - on yielding the value

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value
 - on yielding the value
 - partially on waiting for the task's completion

- `promise_type` is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value
 - on yielding the value
 - partially on waiting for the task's completion
- `promise_type` is strongly connected with coroutine's returned type

- promise_type is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value
 - on yielding the value
 - partially on waiting for the task's completion
 - promise_type is strongly connected with coroutine's returned type
 - it can be a member of the returned type
- `returned_type::promise_type`

promise_type

- `promise_type` is responsible for coroutine's behavior:
 - on coroutine's start
 - on throwing unhandled exception
 - on coroutine's end
 - on returning the value
 - on yielding the value
 - partially on waiting for the task's completion
- `promise_type` is strongly connected with coroutine's returned type
 - it can be a member of the returned type
`returned_type::promise_type`
 - it can be defined as (CHECK IT)
`std::coroutine_traits<returned_type>::promise_type`

coroutine body

ADD highlighting to the presentation

Each time we write coroutine, compiler modifies it's body into following form:

```
{
    promise_type promise;
    auto return_object = promise.get_return_object();
    co_await promise.initial_suspend();

    try{
        //our coroutine_body
    }catch(...) {
        promise.unhandled_exception();
    }

    final_suspend:
    co_await promise.final_suspend();

    return return_object;
}
```


We can extend the coroutine body with:

- (mandatory) support for returning void or returning value
- custom memory allocation algorithm (custom operator `new`)
- (optional) support for yielding intermediate values

co_return - support for returning from coroutine

`co_return` is a new keyword

Usage:

without expression:

`co_return`

with void expression:

`co_return <void expression>`

Translated to:

```
<expression>;  
promise.return_void();  
goto final_suspend;
```

co_return - support for returning from coroutine

`co_return` is a new keyword

Usage:

with non-void expression:

```
co_return <expression>
```

Translated to:

```
promise.return_value(<expression>);  
goto final_suspend;
```

co_yield - support for returning intermediate values

co_yield is a new keyword

Usage:

```
co_yield <non-void expression>
```

Translated to:

```
co_await promise.  
    yield_value(<expression>)
```

co_await shortly

```
co_await std::experimental::suspend_always{} -  
    suspends the coroutine  
co_await std::experimental::suspend_never{} -  
    does nothing
```

exercise here!

`co_await` is a new keyword

- represents awaiting for operations' completion
- it's argument is (usually) called awaitable
- it's result is usually called awaiter

co_await translation

If compiler meets the co_await it gets translated into following code:

```
{
    std::exception_ptr exception = nullptr;
    if (not a.await_ready()) {
        suspend_coroutine();

        <await_suspend>
    }

    resume_point:
    if(exception)
        std::rethrow_exception(exception);
    "return" a.await_resume();
}
```


Await suspend

await suspend is of the following form:

```
promise.await_suspend(this_coroutine_handle);
```

await_suspend might return following types:

- void

```
//if await_suspend returns void  
try {  
    a.await_suspend(coroutine_handle);  
    return_to_the_caller();  
} catch (...) {  
    exception = std::current_exception();  
    goto resume_point;  
}  
//endif
```

Await suspend

await suspend is of the following form:

```
promise.await_suspend(this_coroutine_handle);
```

await_suspend might return following types:

- void
- bool

```
//if await_suspend returns bool  
bool await_suspend_result;  
try {  
    await_suspend_result = a.await_suspend(  
                                coroutine_handle);  
} catch (...) {  
    exception = std::current_exception();  
    goto resume_point;  
}  
if (not await_suspend_result)  
    goto resume_point;  
return_to_the_caller();  
//endif
```

Await suspend

await suspend is of the following form:

```
promise.await_suspend(this_coroutine_handle);
```

await_suspend might return following types:

- void
- bool
- coroutine_handle

```
//if await_suspend returns coroutine_handle  
decltype(a.await_suspend(  
    std::declval<coro_handle_t>()))  
another_coro_handle;  
try {  
    another_coro_handle = a.await_suspend(  
        coroutine_handle);  
} catch (...) {  
    exception = std::current_exception();  
    goto resume_point;  
}  
another_coro_handle.resume();  
return_to_the_caller();  
//endif
```

Awaitable and Awaiter

`Awaitable` is an object, which is an operand of the `co_await` operator

`co_await <expression>` expression will be processed in following manner

- `await_transform`

is performed only if promise has
`await_transform` function declared

```
co_await promise.await_transform(<expr>);
```

Awaitable and Awaiter

`Awaitable` is an object, which is an operand of the `co_await` operator

`co_await <expression>` expression will be processed in following manner

- `await_transform`
- `acquiring awaiter`

Awaitable and Awaiter

Awaitable is an object, which is an operand of the co_await operator

co_await <expression> expression will be processed in following manner

- await_transform
- acquiring awaiter
 - co_await operator

is performed only if awaitable has co_await operator

```
auto&& awaiter =  
    <awaitable>.operator co_await();
```

Awaitable and Awaiter

Awaitable is an object, which is an operand of the co_await operator

co_await <expression> expression will be processed in following manner

- await_transform
- acquiring awaiter
 - co_await operator
 - global co_await operator

is performed only if awaitable there is matching global co_await operator

```
auto&& awaiter =  
    operator co_await(<awaitable>);
```

Awaitable and Awaiter

Awaitable is an object, which is an operand of the `co_await` operator

`co_await <expression>` expression will be processed in following manner

- `await_transform`
- acquiring awaiter
 - `co_await` operator
 - global `co_await` operator
 - **awaitable to awaiter**

```
auto&& awaiter = <awaitable>;
```


Practical part II - implementing own coroutines types

type for lazy initialization

requirements:

- synchronous (no support for multithreading + no support for `co_await`).
- no sharing of the value (no copy, only move constructor).
- interface similar to the `std::optional`.

type for generating sequences

requirements:

- synchronous (no support for multithreading + no support for `co_await`).
- next method should return the value and resume the coroutine.
- interface similar to the `std::optional`

type for asynchronous operations

requirements:

- single-threaded
- asynchronous (support for the `co_await`)
- coroutine after finishing must resume the `co_awaiting` coroutine
- some kind of the executor needed to start the coroutines (GitHub)

type for communication of the tasks

requirements:

- stores information whether the event is set.
- stores the continuation object.
- launches the continuation on setting up the event.