

2-Mark Questions & Answers — DBMS Module 3: SQL Standards & Advanced Queries

Q1. Differentiate between DDL and DML commands in SQL.

- **DDL (Data Definition Language):** Defines and modifies database schema structure (`CREATE` , `ALTER` , `DROP` , `TRUNCATE`). Auto-committed.
 - **DML (Data Manipulation Language):** Manages and queries data within tables (`SELECT` , `INSERT` , `UPDATE` , `DELETE`). Requires explicit commit.
-

Q2. What is the difference between WHERE and HAVING clauses?

- **WHERE:** Filters individual rows *before* grouping occurs (cannot use aggregate functions).
 - **HAVING:** Filters aggregated groups *after* `GROUP BY` execution (can use `COUNT` , `SUM` , `AVG`).
-

Q3. What is a Correlated Subquery?

A **Correlated Subquery** is a nested subquery that references columns from the outer query for each row processed, executing once per candidate row of the outer table.

Q4. Define Database Trigger and list its types.

A **Trigger** is a stored PL/SQL program unit that automatically executes in response to specified database events (`INSERT` , `UPDATE` , `DELETE`).

- **Types:** `BEFORE` trigger, `AFTER` trigger, `INSTEAD OF` trigger, Row-level (`FOR EACH ROW`), Statement-level.

Q5. What is the difference between DELETE and TRUNCATE?

- **DELETE:** DML command, deletes specified rows using `WHERE` , can be rolled back, fires delete triggers.
 - **TRUNCATE:** DDL command, removes all rows by deallocating pages, much faster, cannot be rolled back, does not fire triggers.
-