

2-Mark Questions & Answers

Q1. Define Data with an example.

Data refers to raw, unprocessed facts and figures that have no meaning on their own.

Examp

Q2. Define Database with an example.

A Database is an organized, structured collection of related data stored so it can be easily accessed, managed, and updated.

Examp

Q3. Define DBMS.

A Database Management System (DBMS) is system software that enables users to define, create, maintain, and control access to a database. It acts as an interface between the user and the stored data.

Examp

Q4. What is the aim of a DBMS

The primary aim of a DBMS is to provide a convenient and efficient environment to store, retrieve, and manage data while ensuring data integrity, security, consistency, and reduced redundancy.

Q5. Give any four examples of DBMS software.

1. MySQL -- Open-source relational DBMS.

2. Or

Q6. What is a Query Processor

The Query Processor is a DBMS component that interprets and translates high-level user queries (written in SQL) into low-level instructions that the storage manager can execute. It includes the DDL interpreter, DML compiler, and query evaluation engine.

Q7. What is a Storage Manager

The Storage Manager is a DBMS component responsible for interfacing with the OS file manager to store, retrieve, and update data on physical disk storage. It manages the authorization manager, integrity manager, transaction manager, file manager, and buffer manager.

Q8. Define Data Independence.

Data Independence is the ability to modify the schema at one level of the database system without affecting the schema at the next higher level. It ensures that changes in storage or logical structure do not impact the application programs.

Q9. What is Logical Data Independence

Logical Data Independence is the ability to change the conceptual/logical schema (e.g., adding a new attribute or table) without requiring changes to the external/view-level schema or the application programs that use it.

Q10. What is Physical Data Independence

Physical Data Independence is the ability to change the internal/physical schema (e.g., changing the storage structure, file organization, or indexing method) without requiring changes to the conceptual/logical schema.

Q11. What are Naive Users

Naive users are unsophisticated end-users who interact with the database through pre-built application interfaces (forms/GUIs) without knowing the underlying DBMS. They do not write SQL queries.

Examp

Q12. Who are Sophisticated Users

Sophisticated users are engineers, scientists, or business analysts who interact directly with the DBMS by writing SQL queries or using tools like report generators. They understand the database structure well.

Examp

Q13. Define Database Administrator (DBA).

A Database Administrator (DBA) is a person who has central control over the database system. The DBA is responsible for defining the schema, granting access, monitoring performance, handling backups, and ensuring the database runs efficiently and securely.

Q14. What is the View Level in data abstraction

The View Level (External Level) is the highest level of data abstraction. It describes only a part of the entire database that is relevant to a particular user or group of users. Different users see different views of the same data.

Q15. What is the Physical Level in data abstraction

The Physical Level (Internal Level) is the lowest level of data abstraction. It describes how data is actually stored on the physical storage medium -- including file organization, indexing structures, and access paths.

Q16. What is 1-tier architecture

In 1-tier architecture, the database, the application logic, and the user interface all reside on the same single machine. There is no network involved. It is used for local/personal applications.

Examp

Q17. Name the two types of Data Independence.

1. Logical Data Independence -- Changing the logical schema without affecting the view level.

2. Ph

Q18. What is a Data Dictionary

A Data Dictionary (also called a System Catalog) is a repository that stores metadata -- information about the structure of the database such as table names, column names, data types, constraints, and relationships. It is maintained by the DBMS automatically.

Q19. What is an Index in a database

An Index is a data structure (similar to a book's index) maintained by the Storage Manager to enable fast retrieval of records from a database table based on specific column values, avoiding a full table scan.

Q20. Define Concurrency Control (in one line).

Concurrency Control is the mechanism used by a DBMS to manage simultaneous access to the database by multiple users to ensure data consistency and isolation without conflicts.

Q21. Define Entity and Entity Set with an example.

* Entity: A real-world object or concept that is distinguishable from other objects based on its attributes. Example: A specific student "Suraj" with Roll No 101.

* En
a unive

Q22. Define Relationship and Relationship Set with an example.

- * Relationship: An association among two or more entities. Example: Student "Suraj" *enrolls in* Course "DBMS".

* Re
entity s

Q23. What are the three basic concepts of the ER model

1. Entity Sets: Real-world objects/concepts (e.g., STUDENT, COURSE).

2. At

Q24. Define Attribute in the ER model. What is a Domain of an attribute

- * Attribute: A property or characteristic that describes an entity or relationship set (e.g., Age, Salary).

* Do

Q25. Define Degree of a relationship (with binary/ternary examples).

The Degree of a relationship refers to the number of entity sets participating in a single relationship set.

* Bir

Q26. What is meant by "Role" in a relationship

A Role is the explicit function or role that an entity set plays in a relationship. Roles are typically implicit, but they are explicitly labeled on ER diagram lines when the same entity set participates more than once in a recursive relationship.

Examp

Q27. Define Simple and Composite attributes.

- * Simple Attribute: An attribute that cannot be divided into smaller sub-parts. Example: Age, Salary, Roll_No.

* C

First_N

Q28. Define Single-valued and Multivalued attributes.

- * Single-valued Attribute: An attribute that holds a single value for a given entity. Example: Date_of_Birth, SSN.

* M

Examp

Q29. What is a Derived attribute Give an example.

A Derived Attribute is an attribute whose value is not physically stored in the database but is computed dynamically from another attribute or data source. Represented by a dashed ellipse.

Examp

Q30. What is a null value in the context of attributes

A NULL value represents a special value used when an attribute value is unknown, missing, or not applicable for a particular entity.

Examp

Q31. Define Primary Key.

A Primary Key is a candidate key chosen by the database designer to uniquely identify each tuple (row) in a relation or entity in an entity set. It must contain unique values and cannot contain NULL values.

Q32. What is a strong entity set What is a weak entity set

- * Strong Entity Set: An entity set that has a primary key sufficient to uniquely identify all its entities. Example: EMPLOYEE with primary key Emp_ID.

* W

Examp

Q33. Define identifying entity/owner entity and identifying relationship.

- * Identifying/Owner Entity Set: The strong entity set on which a weak entity set depends for existence and identification. Example: EMPLOYEE is the owner of DEPENDENT.

* Id

diamon

Q34. What is a discriminator (partial key)

A Discriminator (or Partial Key) is the set of attributes of a weak entity set that distinguishes among entities belonging to the same owner entity. Represented by a dashed underline.

Examp

Q35. Define Mapping Cardinality. What are its four types

Mapping Cardinality (or Cardinality Ratio) expresses the number of entities in one entity set that can be associated with entities in another entity set via a relationship set.

Four T

Q36. What is Total Participation What is Partial Participation

* Total Participation: Every entity in the entity set MUST participate in at least one relationship in the relationship set (existence dependency). Represented by a double line in ER diagrams. Example: Every LOAN must belong to a CUSTOMER.

* Pa
Not ev

Q37. What symbols represent entity sets, attributes, and relationship sets in ER diagrams

* Entity Set: Rectangle

* We

Q38. Define Specialization and Generalization.

* Specialization: A top-down design process of designating sub-groupings (subclasses) within an entity set (superclass) based on specific distinguishing characteristics. Example: EMPLOYEE specialized into SALARIED_EMP and HOURLY_EMP.

* Ge
(super

Q39. What is Aggregation in the EER model

Aggregation is an abstraction concept in the Enhanced ER (EER) model that allows a relationship set to be treated as a higher-level entity set so that it can participate in another relationship set. It solves the problem of expressing a relationship among relationships.

Q40. Define ISA relationship.

An ISA ("Is A") relationship represents superclass-subclass relationships in Specialization/Generalization hierarchies (e.g., SECRETARY *ISA* EMPLOYEE). It represents inheritance, where the subclass entity inherits all attributes and relationships of its superclass.

Q41. What is a redundant attribute Give an example.

A Redundant Attribute is an attribute present in an entity set or relation that can be derived or obtained from other existing attributes or relationships, creating unnecessary duplication.

Examp

Q42. Define Key Constraint.

A Key Constraint specifies that an entity set or relationship set must have unique identifying values. In a relationship set, a key constraint on an entity set indicates that an entity can participate in at most one relationship instance (specifying 1:1 or 1:N cardinality).

Q43. What is an ER diagram List its two main components.

An Entity-Relationship (ER) Diagram is a graphical representation of the logical structure of a database model.

Two M

Q44. List the three components specified while mapping an ER model to a relational model.

1. Relation Names (tables derived from entity sets or relationship sets)

2. At

Q45. What is the primary key of a relation formed from a weak entity set

The primary key of a relation formed from a weak entity set is the combination of the primary key of its identifying owner entity set (as a foreign key) AND the discriminator (partial key) of the weak entity set.

Examp

Q46. Name the four options available for mapping specialization/generalization to relations.

1. Multiple relations -- Superclass and Subclasses (separate table for superclass, separate table for each subclass containing primary key + specific attributes).

2. M