

Self-Learning: Distributed Transactions, TCL & Performance Tuning -- DBMS

Definition: Distributed Transactions execute across multiple independent database nodes connected over a network, managed using the Two-Phase Commit (2PC) protocol.

1. Detailed Technical Explanation

1. Two-Phase Commit (2PC) Protocol

Coordinates atomic commit/abort decisions across multiple distributed node participants.

COORDINATOR	PARTICIPANTS (Nodes 1, 2, 3)
----- Phase 1: PREPARE Message ----->	
	(Check local log & resources)
<----- VOTE_COMMIT / VOTE_ABORT -----	
(If all VOTE_COMMIT):	
----- Phase 2: GLOBAL_COMMIT Message ----->	
	(Write commit to local disk)
<----- ACKNOWLEDGEMENT -----	

2. Transaction Control Language (TCL) Commands

```
-- 1. Start a explicitly scoped transaction
START TRANSACTION;

-- 2. Modify data
UPDATE Accounts SET Balance = Balance - 5000 WHERE Acc_No = 101;

-- 3. Set a rollback checkpoint
SAVEPOINT sp1;

UPDATE Accounts SET Balance = Balance + 5000 WHERE Acc_No = 102;

-- 4. Rollback to Savepoint if error occurs
ROLLBACK TO SAVEPOINT sp1;

-- 5. Commit remaining updates permanently
COMMIT;
```

3. Database Performance Tuning Strategies

1. Indexing Optimization:

* Cre

4. Quick Recall Flow

2PC -> Prepare Phase (Vote) -> Commit Phase (Global ACK) | TCL -> COMMIT, ROLLBACK, SAVEPOINT | Tuning -> B+ Tree
Indexes