

Basic SQL Operations in IBM Db2 -- DBMS Module 6

Definition: SQL Operations in IBM Db2 adhere to ANSI/ISO SQL standards with specialized extensions for table creation, data manipulation, constraints enforcement, NULL handling, and complex JOIN queries.

1. Detailed Technical Explanation & Executable Statements

1. Database Creation & Connection

```
-- Create a new database named STUDENTDB
CREATE DATABASE STUDENTDB;

-- Connect to the database
CONNECT TO STUDENTDB;
```

2. Data Definition Language (DDL) & Constraints

```
-- Create DEPARTMENT Table
CREATE TABLE DEPARTMENT (
    DEPT_ID INT NOT NULL PRIMARY KEY,
    DEPT_NAME VARCHAR(50) NOT NULL UNIQUE,
    LOCATION VARCHAR(50) DEFAULT 'Main Campus'
);

-- Create STUDENT Table with Foreign Key & Check Constraints
CREATE TABLE STUDENT (
    STUDENT_ID INT NOT NULL PRIMARY KEY,
    FIRST_NAME VARCHAR(30) NOT NULL,
    LAST_NAME VARCHAR(30),
    EMAIL VARCHAR(100) UNIQUE,
    AGE INT CHECK (AGE >= 17),
    DEPT_ID INT,
    FOREIGN KEY (DEPT_ID) REFERENCES DEPARTMENT(DEPT_ID) ON DELETE SET NULL
);
```

3. Data Manipulation Language (DML)

```
-- Insert Records
INSERT INTO DEPARTMENT (DEPT_ID, DEPT_NAME, LOCATION)
VALUES (1, 'Data Science', 'Building A'),
       (2, 'Computer Science', 'Building B');

INSERT INTO STUDENT (STUDENT_ID, FIRST_NAME, LAST_NAME, EMAIL, AGE, DEPT_ID)
VALUES (101, 'Rahul', 'Sharma', 'rahul@example.com', 20, 1),
       (102, 'Anita', 'Verma', 'anita@example.com', 21, 2),
       (103, 'Suresh', NULL, 'suresh@example.com', 19, 1);

-- Update Record
UPDATE STUDENT
SET AGE = 21
WHERE STUDENT_ID = 101;

-- Delete Record
DELETE FROM STUDENT
WHERE STUDENT_ID = 103;
```

4. NULL Value Handling in Db2

In Db2, NULL represents missing or unknown values. Standard comparison operators (=, <>) return UNKNOWN when evaluated against NULL.

```
-- Select students where LAST_NAME is missing
SELECT STUDENT_ID, FIRST_NAME
FROM STUDENT
WHERE LAST_NAME IS NULL;

-- Use VALUE() or COALESCE() to replace NULL with a default display value
SELECT FIRST_NAME, VALUE(LAST_NAME, 'Not Provided') AS LAST_NAME_DISPLAY
FROM STUDENT;
```

5. Join Operations in Db2

```
-- Inner Join
SELECT S.STUDENT_ID, S.FIRST_NAME, D.DEPT_NAME
FROM STUDENT S
INNER JOIN DEPARTMENT D ON S.DEPT_ID = D.DEPT_ID;

-- Left Outer Join
SELECT S.STUDENT_ID, S.FIRST_NAME, D.DEPT_NAME
FROM STUDENT S
LEFT OUTER JOIN DEPARTMENT D ON S.DEPT_ID = D.DEPT_ID;
```

2. Core Concepts & Memory Keywords

- * PRIMARY KEY / FOREIGN KEY: Relational integrity constraints.

* CO

3. Must-Write Points for Exams

- * Db2 supports standard PRIMARY KEY, FOREIGN KEY, UNIQUE, NOT NULL, and CHECK constraints.

* Th

4. Quick Recall Flow

```
CREATE TABLE -> Add Constraints (PK, FK, CHECK) -> INSERT/UPDATE/DELETE -> SELECT with Joins & VALUE(col, 'Default')
```