


**Partner: Panasonic**  
**Model: PT-FW300NT**  
**Device Type: DLP Projector**



## GENERAL INFORMATION

<b>SIMPLWINDOWS NAME:</b>	Panasonic PT-FW300NT v1.0
<b>CATEGORY:</b>	TV/Video Projector
<b>VERSION:</b>	1.0
<b>SUMMARY:</b>	This module will control and/or report Power, Source Select, Picture Mode, Aspect, AV Mute, Freeze, Index Windows, No Signal Timeout, Picture Control and elapsed Lamp Hour usage via RS-232.
<b>GENERAL NOTES:</b>	<p>This module will control the Panasonic PT-FW300NT. Although this module has been tested with the PT-FW300NT, it should also control the following projectors:  PT-FW300  PT-F300NT  PT-F300</p> <p><b>NOTE:</b> This module depends on feedback from the device. You cannot comment out the From_Device. This module is System Builder compatible.</p>
<b>CRESTRON HARDWARE REQUIRED:</b>	X-Series Processor, CNX-COM2, ST-COM, 2-Series Processor, C2COM3
<b>SETUP OF CRESTRON HARDWARE:</b>	RS232 Baud: 9600 Parity: N Data Bits: 8 Stop Bits: 1
<b>VENDOR FIRMWARE:</b>	Unknown
<b>VENDOR SETUP:</b>	None
<b>CABLE DIAGRAM:</b>	CNSP-121



**Partner: Panasonic**  
**Model: PT-FW300NT**  
**Device Type: DLP Projector**


**CONTROL:**

<b>Power_&lt;On/Off/Toggle&gt;</b>	D	Pulse to turn power on or off.
<b>Input_*</b>	D	Pulse to select input.
<b>Picture_Mode_*</b>	D	Pulse to select picture mode.
<b>Aspect_*</b>	D	Pulse to select aspect. Some aspects may not be available depending on the input being displayed.
<b>AV_Mute_&lt;On/Off/Toggle&gt;</b>	D	Pulse to enable or disable the AV mute.
<b>Freeze_&lt;On/Off/Toggle&gt;</b>	D	Pulse to turn freeze mode on or off.
<b>No_Signal_Shut_Off_*_Min</b>	D	Pulse to set or disable the no signal shut off timeout value.
<b>Auto_Setup</b>	D	Pulse to trigger the auto setup function.
<b>&lt;Menu/Enter/Up/Down/Left/Right&gt;</b>	D	Pulse to navigate/select on screen menu items.
<b>Default</b>	D	Pulse to select default settings.
<b>Index_Window</b>	D	Pulse to enable or disable index window function.
<b>Side_By_Side</b>	D	Pulse to enable or disable side by side mode.
<b>Brightness_&lt;Up/Down&gt;</b>	D	Press to adjust brightness.
<b>Contrast_&lt;Up/Down&gt;</b>	D	Press to adjust contrast.
<b>Volume_&lt;Up/Down&gt;</b>	D	Press to adjust volume.
<b>Poll_En</b>	D	Latch high to enable constant polling.
<b>From_Device</b>	S	Serial information returned via an RS-232 port.

**Partner: Panasonic**  
**Model: PT-FW300NT**  
**Device Type: DLP Projector**

**FEEDBACK:**

Power_Is_<On/Off>	D	Indicates the current power state.
Lamp_*	D	Indicates the current lamp status.
Input_Is_*	D	Indicates the currently selected input.
Picture_Mode_Is_*	D	Indicates the current picture mode.
Aspect_Is_*	D	Indicates the current aspect ratio.
AV_Mute_Is_<On/Off>	D	Indicates the current AV mute status.
Freeze_Is_<On/Off>	D	Indicates the freeze mode status.
No_Signal_Shut_Off_Is_*_Min	D	Indicates the no signal shut off setting.
Lamp_Hours	A	Displays the lamp hours.
Brightness_Gauge	A	Indicates the current brightness setting.
Contrast_Gauge	A	Indicates the current contrast setting.
Volume_Gauge	A	Indicates the current volume setting.
To_Device	S	Serial information sent via an RS-232 port.

**TESTING:**

OPS USED FOR TESTING:	v4.001.1012
SIMPL WINDOWS USED FOR TESTING:	2.12.31
DEVICE DB USED FOR TESTING:	27.00.001.00
CRES DB USED FOR TESTING:	21.03.028.00
SYMBOL LIBRARY USED FOR TESTING:	660
SAMPLE PROGRAM:	Panasonic PT-FW300NT v1.0 Demo PRO2
REVISION HISTORY:	v1.0