


HMC CS 158

Quiz 5: SVMs, Kernels

1. We can think of the SVM as solving

$$\min_{\boldsymbol{\theta}} C \sum_{i=1}^n \left(y^{(i)} \text{cost}_1 \left(\boldsymbol{\theta}^T \mathbf{x}^{(i)} \right) + \left(1 - y^{(i)} \right) \text{cost}_0 \left(\boldsymbol{\theta}^T \mathbf{x}^{(i)} \right) \right) + \sum_{j=1}^d \theta_j^2,$$


where the cost functions $\text{cost}_0(z)$ and $\text{cost}_1(z)$ look like this:



The first term in the objective is $C \sum_{i=1}^n \left(y^{(i)} \text{cost}_1 \left(\boldsymbol{\theta}^T \mathbf{x}^{(i)} \right) + \left(1 - y^{(i)} \right) \text{cost}_0 \left(\boldsymbol{\theta}^T \mathbf{x}^{(i)} \right) \right)$. This first term will be zero if two of the following four conditions hold true. Which are the two conditions that would guarantee that this term equals zero?


- (a) For every example with $y^{(i)} = 0$, we have that $\boldsymbol{\theta}^T \mathbf{x}^{(i)} \leq 0$.
- (b) For every example with $y^{(i)} = 1$, we have that $\boldsymbol{\theta}^T \mathbf{x}^{(i)} \geq 1$.
- (c) For every example with $y^{(i)} = 1$, we have that $\boldsymbol{\theta}^T \mathbf{x}^{(i)} \geq 0$.
- (d) For every example with $y^{(i)} = 0$, we have that $\boldsymbol{\theta}^T \mathbf{x}^{(i)} \leq -1$.

2. The formula for the Gaussian kernel is given by the similarity(\mathbf{x}, \mathbf{z}) = $\exp\left(-\frac{\|\mathbf{x}-\mathbf{z}\|^2}{2\sigma^2}\right)$. The figure below shows a plot of $f = \text{similarity}(\mathbf{x}, \mathbf{z})$ when $\sigma^2 = 1$.




Which of the following is a plot of f when $\sigma^2 = 0.25$?


(a)




(c)




(b)



(d)



3. Suppose you have trained an SVM classifier with a Gaussian kernel, and it learned the following decision boundary on the training set:



You suspect that the SVM is underfitting your dataset. Should you try increasing or decreasing C ? Increasing or decreasing σ^2 ?

4. Suppose you have a dataset with $d = 10$ features and $n = 5000$ examples. After training your logistic regression classifier with gradient descent, you find that it has underfit the training set and does not achieve the desired performance on the training or cross-validation sets. Which of the following might be promising steps to take? Check all that apply.
- (a) Create / add new polynomial features.
 - (b) Use an SVM with a Gaussian kernel.
 - (c) Use a different optimization method since using gradient descent to train logistic regression might result in a local minimum.
 - (d) Increase the regularization parameter λ .