

## CTA Block

**Note the red ‘play button’ (right arrow) is from classic. The blue play button to the left of the text is what we should use moving forward.** **1. Overview**

The **CTA (Call-To-Action) / Button block** is designed as a reusable and flexible component to support various button styles and use cases across the site.

It is intended to:

- Support multiple visual styles (e.g., primary, secondary, outline, CTA arrow, video, download, etc.)
- Allow icon-based buttons with explicit authoring control

Given its wide usage (across a large number of pages), the CTA is implemented as a **dedicated block with shared configuration and styling**.

---

## 2. Authoring Model

### CTA Fields

Authors can configure the following fields:

| Field Name      | Description                                                                  |
|-----------------|------------------------------------------------------------------------------|
| Button Text     | Label displayed on the CTA                                                   |
| URL             | Target link for the CTA                                                      |
| Open in New Tab | Boolean flag to open link in a new tab                                       |
| Icon            | Optional icon to display with the CTA (Arrow, Document, Download, Print etc) |
| Type (Style)    | Visual style of the CTA                                                      |

---

### CTA Style Variants

The **Type field** allows authors to select from predefined styles such as:

- Primary

- ~~Secondary~~
- Outline
- Link
- ~~Video~~

This ensures **consistent styling and behavior across the site**.

Additional variants will be added during implementation.

Note: The red 'play button' (right arrow) is from classic. The blue play button to the left of the text is what we should use moving forward


[Request quote/demo](#)

[Watch the features of the CX7 Pro imaging platforms](#) 

[T HCS and HCA Platform Features | Thermo Fisher Scientific - US](#)

-  [Infographic: Five things to consider when improving ergonomics with biological safety cabinets](#)
-  [Video: Setting your stand height](#)

[T Biological Safety Cabinets Resources | Thermo Fisher Scientific - US](#)



[T Flow Measurement | Flow Meters | Flow Computers | Thermo Fisher Scientific - US](#)

### 3. Usage Patterns

#### 3.1 Standalone CTA (Button Block)

- Authors can directly add a **CTA block** to the page
- Configure all CTA properties via block authoring
- Suitable for:
  - Inline CTAs
  - Section-level actions
  - Independent call-to-actions

### 3.2 CTA within Other Blocks

CTA is also reused inside other components such as:

- Cards Block

In such cases:

- CTA fields are exposed as part of the parent block authoring
  - Authors configure CTA within the context of the parent component
  - The rendering follows the same styling and behavior as the standalone button
- 

## 4. Reusability via Partial

To enable reuse and maintain consistency, CTA fields are defined as **shared partials**.

### What are Partial?

- Partial are reusable field definitions
- They allow the same set of fields (CTA configuration) to be reused across multiple blocks

### How CTA Uses Partial

- A shared CTA partial defines:
  - Button text
  - URL
  - Open in new tab
  - Icon
  - Type
- This partial is:
  - Used in the **Button block (standalone usage)**
  - Referenced inside other blocks (e.g., Hero, Teaser)

This ensures:

- No duplication of field definitions
  - Consistent authoring experience
  - Easy updates (change once, reflect everywhere)
- 

### Reference Structure

- **CTA Fields Partial**

```
models/partials/_cta-fields.json
```

→ Defines reusable CTA fields

## 5. Reusability & Consistency

- CTA configuration is **standardized and centrally managed**
- Style and icon options are shared across all implementations
- Same CTA structure is used:
  - In standalone button blocks
  - Inside other blocks

This ensures:

- Uniform authoring experience
- Consistent UI/UX across the site
- Better maintainability and scalability

## Technical Details

### 1. UE Authoring Contract

#### 1.1 AEM Resource (Standalone Block)

| Property      | Value                                        |
|---------------|----------------------------------------------|
| Resource Type | core/franklin/components/block/v1/block      |
| Block Name    | CTA                                          |
| Model ID      | cta                                          |
| Block Type    | Simple (flattened — leaf block, no children) |

#### 2.2 Editable Properties in Universal Editor

**When author clicks the standalone CTA block:**

| JCR Property | UE Properties Panel | Field Type | Editable?      | Notes                      |
|--------------|---------------------|------------|----------------|----------------------------|
| label1       | Button Text         | text       | Yes — Required | Label displayed on the CTA |

|          |                 |                  |                |                                                              |
|----------|-----------------|------------------|----------------|--------------------------------------------------------------|
| href     | URL             | text             | Yes — Required | Target link URL or content path                              |
| external | Open in New Tab | boolean (toggle) | Yes — Optional | Default: false                                               |
| icon     | Icon            | select           | Yes — Optional | Options from _button-icons.json partial. Default: none.      |
| type     | Style           | select           | Yes — Optional | Options from _button-types.json partial. Default: "primary". |

### 2.3 Container vs Leaf Fields

The CTA block is a **leaf block (flattened)**. All fields are on the block itself. No child items, no container behavior, no repeatable groups.

### 2.4 Block Registration — Component Definition

```
1 {
2   "title": "CTA",
3   "id": "cta",
4   "plugins": {
5     "xwalk": {
6       "page": {
7         "resourceType": "core/franklin/components/block/v1/block",
8         "template": {
9           "name": "CTA",
10          "model": "cta"
11        }
12      }
13    }
14  }
15 }
```

## 3. Component Model Definition (Field-Level)

### 3.1 CTA Block Model (Standalone Usage)

| Field | Component | Label | Required | Default | Authored / Derived |
|-------|-----------|-------|----------|---------|--------------------|
|-------|-----------|-------|----------|---------|--------------------|

|                       |         |                 |     |           |          |
|-----------------------|---------|-----------------|-----|-----------|----------|
| <code>label</code>    | text    | Button Text     | Yes | --        | Authored |
| <code>href</code>     | text    | URL             | Yes | --        | Authored |
| <code>external</code> | boolean | Open in New Tab | No  | false     | Authored |
| <code>icon</code>     | select  | Icon            | No  | "" (none) | Authored |
| <code>type</code>     | select  | Style           | No  | "primary" | Authored |

### 3.2 Style Options ( `_button-types.json` )

| Option  | Value                | Visual                                                                 |
|---------|----------------------|------------------------------------------------------------------------|
| Primary | <code>primary</code> | Solid filled button (brand color background, white text)               |
| Outline | <code>outline</code> | Border-only button (transparent background, brand color border + text) |
| Link    | <code>link</code>    | Text link style with optional icon (no background, no border)          |

### 3.3 Icon Options ( `_button-icons.json` )

| Option   | Value                 | Visual                                                                                               |
|----------|-----------------------|------------------------------------------------------------------------------------------------------|
| None     | <code>""</code>       | No icon                                                                                              |
| Arrow    | <code>arrow</code>    | Right-pointing arrow (blue — per PDF: use the blue play button to the left, not the red classic one) |
| Document | <code>document</code> | Document icon                                                                                        |
| Download | <code>download</code> | Download icon                                                                                        |
| Print    | <code>print</code>    | Print icon                                                                                           |

Additional icons will be added during implementation as encountered across the site.

## 4. Partial Architecture — Reuse Across Blocks

### 4.1 Partial File Structure

```
1 | models/partials/  
2 | └─ _cta-fields.json           ← complete CTA field group (5 fields)  
3 | └─ _dual-cta-fields.json     ← two CTA groups for blocks needing  
   | primary + secondary  
4 | └─ _button-types.json       ← type options (Primary, Outline, Link)  
5 | └─ _button-icons.json       ← icon options (Arrow, Document,  
   | Download, Print)  
6 |
```

### 4.2 \_cta-fields.json — Single CTA Field Group

This partial defines the **complete set of CTA fields** that any block can embed. When spread into a block model, authors see these fields as a group in the properties panel.

**Fields included:**

| Field       | Component | Label                                            |
|-------------|-----------|--------------------------------------------------|
| ctaLabel    | text      | CTA Text                                         |
| ctaHref     | text      | CTA URL                                          |
| ctaExternal | boolean   | CTA Open in New Tab                              |
| ctaIcon     | select    | CTA Icon (spreads _button-icons.json#/options )  |
| ctaType     | select    | CTA Style (spreads _button-types.json#/options ) |

**How a block consumes it:**

```
1 | // Inside blocks/testimonial/_testimonial.json → model fields:  
2 | {  
3 |   "id": "testimonial",  
4 |   "fields": [  
5 |     { "component": "richtext", "name": "quote", "label": "Quote" },  
6 |     { "component": "richtext", "name": "attribution", "label":  
7 | "Attribution" },  
8 |     { "component": "reference", "name": "authorImage", "label":  
9 | "Author Image" },  
10 |     { "...": "../models/partials/_cta-fields.json#/fields" }  
11 |   ]  
12 | }
```

One line spreads all 5 CTA fields into the Testimonial block model.

4.3 `_dual-cta-fields.json` — Dual CTA Field Groups

For blocks needing two CTAs (e.g., Hero), this partial wraps two instances of the CTA fields with different prefixes:

Groups included:

| Group         | Prefix                     | Default Type |
|---------------|----------------------------|--------------|
| Primary CTA   | <code>primaryCta*</code>   | "primary"    |
| Secondary CTA | <code>secondaryCta*</code> | "outline"    |

```
1 // Inside blocks/hero/_hero.json → model fields:
2 {
3   "id": "hero",
4   "fields": [
5     { "component": "reference", "name": "image", "label": "Background
6 Image" },
7     { "component": "text", "name": "subtitle", "label": "Subtitle" },
8     { "component": "richtext", "name": "description", "label":
9 "Description" },
10    { "...": "../models/partials/_dual-cta-fields.json#/fields" }
11  ]
12 }
```

One line spreads both primary and secondary CTA field groups into the Hero block model.

4.4 Partial vs Standalone — Field Name Mapping

The standalone CTA block uses **unprefixed** field names. Partials inside other blocks use **prefixed** names to avoid conflicts:

| Standalone CTA Block  | Single CTA Partial<br>(Cards, Testimonial) | Dual CTA Partial —<br>Primary (Hero) | Dual CTA Partial —<br>Secondary (Hero) |
|-----------------------|--------------------------------------------|--------------------------------------|----------------------------------------|
| <code>label</code>    | <code>ctaLabel</code>                      | <code>primaryCtaLabel</code>         | <code>secondaryCtaLabel</code>         |
| <code>href</code>     | <code>ctaHref</code>                       | <code>primaryCtaHref</code>          | <code>secondaryCtaHref</code>          |
| <code>external</code> | <code>ctaExternal</code>                   | <code>primaryCtaExternal</code>      | <code>secondaryCtaExternal</code>      |
| <code>icon</code>     | <code>ctaIcon</code>                       | <code>primaryCtaIcon</code>          | <code>secondaryCtaIcon</code>          |



|      |         |                |                  |
|------|---------|----------------|------------------|
| type | ctaType | primaryCtaType | secondaryCtaType |
|------|---------|----------------|------------------|

Despite different names, they **render identically** — the block JS reads whatever field name is defined and applies the same CTA rendering logic.

4.5 Change Once, Update Everywhere

The core benefit of this architecture:

```
1 CHANGE: Add a new icon option "External Link"
2
3 UPDATE: models/partials/_button-icons.json
4   → Add { "name": "External Link", "value": "external-link" }
5
6 RESULT:
7   ✓ CTA block (standalone) – new icon available
8   ✓ Hero block – new icon available in both primary and secondary CTA
9   ✓ Cards block – new icon available per card
10  ✓ Testimonial block – new icon available
11  ✓ Any future block using _cta-fields.json – new icon available
12
13 ONE file changed. ALL blocks updated.
14
```

Same applies for adding a new type option, changing a label, or modifying validation.

5. Authoring Strategy

Classification: Flattened Block

| Pattern                | Reason                                                                             |
|------------------------|------------------------------------------------------------------------------------|
| <b>Flattened block</b> | All fields on one block. No repeating items.<br>Author fills one properties panel. |