

Regional Fragment Block

This page added by Deepti with details on 04-13-2026

1. Overview

The **Regional Fragment Block** enables authors to display **country-specific content** for markets that do not have dedicated sites in the MSM hierarchy.

In the EDS (xWalk) architecture, this is implemented as a **client-side block** that conditionally renders content based on configured country codes, allowing targeted experiences without introducing additional site structures.

2. Problem Statement

In the current setup:

- Certain countries (e.g., **ni/en**, **pa/en**) do not have dedicated sites in AEM MSM
- These countries consume content from a **shared regional site**, such as:

`/latin-america-other/en`

However, there is a requirement to:

- Display **country-specific content** such as:
 - Legal disclaimers
 - Support information

Without creating separate MSM structures for each country

3. Solution Approach

The solution is to introduce a **Regional Fragment Block** in EDS that:

- Allows authors to configure **country-specific targeting**
 - Dynamically renders content based on the **user's country context (derived from URL)**
 - Uses reusable fragment content authored once and referenced across pages
-

4. Authoring Configuration

The **Regional Fragment Block** provides the following authoring fields:

Field Name	Description
Fragment Path	Path to the fragment page containing the content to be rendered (e.g., <code>/fragments/promos/ni-special-offer</code>)
Country Codes	Country codes for which the content should be displayed (e.g., <code>ni</code> , <code>pa</code>)

Authoring Behavior

- Authors create reusable content as **fragment pages** using standard blocks
- Authors place the Regional Fragment Block on any page
- Authors configure:
 - Fragment reference
 - Target country codes

5. How It Works

Authoring Flow

1. Create Fragment Content

- Example: `/fragments/promos/ni-special-offer`
- Built using standard EDS blocks
- Published for reuse

2. Configure Block

- Add block to page (e.g., `/latin-america-other/en/products/...`)
- Set:
 - Fragment Path
 - Country Codes (`ni`)

Runtime Behavior

- Block reads country from URL:
 - `/ni/en/... → ni`
 - `/pa/en/... → pa`
- Compares with configured country codes

If match:

- Fragment content is fetched and rendered

If no match:

- Block is removed entirely
 - No content is rendered
-

6. Example

Scenario

- Base page: `/latin-america-other/en/products/antibodies`
- Fragment: `/fragments/promos/ni-special-offer`
- Configured country: `ni`

Result

URL	Behavior
<code>/ni/en/products/antibodies</code>	NI-specific content is displayed
<code>/pa/en/products/antibodies</code>	Content not displayed
<code>/latin-america-other/en/products/antibodies</code>	No country-specific content

7. Key Benefits

Benefit	Description
Reusable content	Fragment can be used across multiple pages
Centralized updates	Update once, reflected everywhere
Country-specific targeting	Content shown only for selected countries
No MSM dependency	No need to create new country sites
Consistent authoring	Uses standard EDS blocks

