

Week 6 - Module 4a - Interoperability Standards. WMS, KML and XML

Karl Benedict

GEOG 485L/585L - Spring 2017

Overview

- Extensible Markup Language - XML
 - Definition of a markup language
 - Requirements
 - Extensible ???
- KML - AKA Keyhole Markup Language
 - An XML Document Format
 - Combined representation of spatial data and time
- OGC Web Map Services (WMS)
 - Requests and Results
 - GetCapabilities, GetMap, GetFeatureInfo
- Integration of WMS into KML

Extensible Markup Language - XML

XML Background

- Defined as a markup language profile of Standard Generalized Markup Language (SGML - ISO 8879:1986)
- XML 1.0 released as a W3C Recommendation in 1998
 - currently in [5th edition](#), released in 2008
 - version 1.1 released in 2004, but is [not recommended](#) for use unless the “[new characters in XML names, new line-end conventions, and references to control characters enabled with XML version 1.1 are needed](#)”.

XML Design Goals

- XML shall be straightforwardly usable over the Internet.
- XML shall support a wide variety of applications.
- XML shall be compatible with SGML.
- It shall be easy to write programs which process XML documents.
- The number of optional features in XML is to be kept to the absolute minimum, ideally zero.
- XML documents should be human-legible and reasonably clear.
- The XML design should be prepared quickly.




Figure 1: SGML Relationship with XML and HTML

- The design of XML shall be formal and concise.
- XML documents shall be easy to create.
- Terseness in XML markup is of minimal importance.

From XML 1.0 (5th ed.) [Recommendation](#)

XML Structure - Well Formed / Valid

- [Well Formed XML](#) - a document that conforms to the structural definition of XML. Either well-formed, or not XML
- [Valid XML](#) - a document that is both well-formed and conforms to a specific content structure defined by
 - A [Document Type Definition \(DTD\)](#) - the original XML specification for the definition of the content of a specific XML document
 - A [Schema document](#) - defined in a variety of languages (e.g. W3C Schema, RELAX NG, Schematron, ISO DSDL, etc.)

[XML Wikipedia Article](#)

Simple XML Document

```

1  <?xml version="1.0" encoding="ISO-8859-1"?>
2  <!-- Some comment would go here to describe this document ... -->
3  <note>
4      <to>Tove</to>
5      <from>Jani</from>
6      <heading>Reminder</heading>
7      <body type="instruction" >Don't forget me this weekend!</body>
8  </note>

```

XML Source (modified from original): [w3schools](#)

XML Prolog

Includes XML Declaration and Comment

```

1  <?xml version="1.0" encoding="ISO-8859-1"?>
2  <!-- Some comment would go here to describe this document ... -->

```

XML Elements

Define blocks of content

```

3  <note>
4      <to>Tove</to>
5      <from>Jani</from>
6      <heading>Reminder</heading>
7      <body type="instruction" >Don't forget me this weekend!</body>
8  </note>

```

XML Root Element

- Required
- There is only one
- It must be a pair of opening and closing tags

```
3 <note>
4     ...
5     ...
6     ...
7     ...
8 </note>
```

XML Content Elements

- Contain all other document content
- May be paired opening and closing tags, *or*
- May be self-closing with a terminal “/” in the element, e.g. `
`

```
4 <to>Tove</to>
5 <from>Jani</from>
6 <heading>Reminder</heading>
7 <body type="instruction" >Don't forget me this weekend!</body>
```

XML Attributes

Define additional information about elements as *name=value* pairs.

```
7 <body type="instruction" >Don't forget me this weekend!</body>
```

XML Element Content

The material contained between the opening and closing tags of an *Element*.

```
7 <body type="instruction" >Don't forget me this weekend!</body>
```

Valid XML?

Why is this XML *well-formed* but not *valid*?

There is no DTD or Schema defined for the document against which it can be validated

```
1 <?xml version="1.0" encoding="ISO-8859-1"?>
2 <!-- Edited by XMLSpy® -->
3 <note>
4     <to>Tove</to>
5     <from>Jani</from>
6     <heading>Reminder</heading>
7     <body type="instruction" >Don't forget me this weekend!</body>
8 </note>
```

Common XML Constructs

Document Type Declaration (DTD) references (PROLOG) definition, either by reference or by direct inclusion, the allowed structure of an XML document, for example:

```
<!DOCTYPE greeting SYSTEM "hello.dtd">
```

CDATA Sections blocks of XML that contain characters that would otherwise be recognized as XML markup, for example:

```
<![CDATA[<greeting>Hello, world!</greeting>]]>
```

XML Namespace Declarations additional information included in elements to distinguish between duplicate element names, for example (declared in lines 1-3, used in lines 5-17):

```
1 <root
2   xmlns:h="http://www.w3.org/TR/html4/"
3   xmlns:f="http://www.w3schools.com/furniture">
4
5 <h:table>
6   <h:tr>
7     <h:td>Apples</h:td>
8     <h:td>Bananas</h:td>
9   </h:tr>
10 </h:table>
11 <f:table>
12   <f:legs>4</f:legs>
13   <f:cost>300</f:cost>
14   <f:width>3</f:width>
15   <f:length>5</f:length>
16   <f:height>4</f:height>
17 </f:table>
18 </root>
```

KML

KML Background

- An XML grammar originally developed as Keyhole Markup Language by Keyhole, Inc. for use in their Keyhole Earth Viewer.
- Google acquired Keyhole, Inc. in 2004
- KML version 2.2 became an OGC standard in 2008
- Two delivered KML file formats

KML an XML document, with a “.kml” extension that is directly readable and editable

KMZ a compressed (zipped) file with a “.kmz” extension¹, that contains at least a KML document, but may contain other files as well.

¹A KMZ file may be extracted and its contents examined by many zipfile utilities if you replace the .kmz extension with .zip prior to trying to extract

KML Capabilities

- Annotate the Earth
- Specify icons and labels to identify locations on the surface of the planet
- Create different camera positions to define unique views for KML features
- Define image overlays to attach to the ground or screen
- Define styles to specify KML feature appearance
- Write HTML descriptions of KML features, including hyperlinks and embedded images
- Organize KML features into hierarchies using **folder** elements
- Locate and update retrieved KML documents from local or remote network locations
- Define the location and orientation of textured 3D objects

KML Content

- Model for encoding 2- and 3-dimensional geometries for use in 2-D mappers and 3-D virtual globe applications
- Uses latitude-longitude (based upon WGS84 datum) for encoding horizontal position
- Represents altitude in Meters (based upon the WGS84 ellipsoid and EGM96 geoid)

2D and 3D KML Sample

```
1 <kml xmlns="http://www.opengis.net/kml/2.2">
2 <Document>
3   <Placemark>
4     <Polygon>
5       <altitudeMode>
6         clampToGround
7       </altitudeMode>
8       <outerBoundaryIs>
9         <LinearRing>
10          <coordinates>
11            -135,78.5,300000
12            -135,12.5,300000
13            -45,12.5,300000
14            -45,78.5,300000
15            -135,78.5,300000
16          </coordinates>
17        </LinearRing>
18      </outerBoundaryIs>
19    </Polygon>
20  </Placemark>
21 </Document>
22 </kml>
```

KML Example

Example from: [KML 2.2 Specification \(fig. 6, pg. 21\)](#)

High-Level KML Content Types

Features including documents, folders, placemarks, network links

Geometries including points, linestrings, polygons, models, locations

Polygon in plate carrée (long,lat) plane



Polygon mapped to terrain surface



Figure 2: Illustration of polygon in both planar and terrain surface

Overlays including ground overlays, lat-lon boxes, photo overlays, screen overlays

Styles styles, substyles, icons, label styles

Links read, update, create, delete, change

Views camera, look at

Time time span, timestamp

KML Demonstration and References

New Mexico State Boundary [KML File](#) | [KMZ File](#) (from [NM RGIS](#))

[Google Code KML Documentation](#)

[OGC KML Implementation specification](#)

OGC Web map Services - WMS

WMS - Overview

- Open Geospatial Consortium standard for requesting
 - Service Metadata (**GetCapabilities**) - an XML file representing information about a specific WMS service and its component layers
 - Map Images (**GetMap**) - graphic files representing one or more layers from a single WMS service for a specified area of interest, and, optionally, for a specified point in time
 - Feature Information (**GetFeatureInfo**) - a basic representation (in a variety of formats) of the attributes associated with a specific pixel location in a map image
- A WMS will return to the requesting system one of the above products OR an error message (in XML by default)
- Related [Style Layer Descriptor](#) standard supports dynamic updating of visualization options
- [OGC WMS Documentation Access Page](#)

WMS *GetCapabilities* Request

Request Parameter	1.0	1.1	1.1.1	1.3.0	Description
WMTVER = 1.0.0	R				Request version
VERSION = version		O	O	O	Request version
SERVICE = WMS	R	R	R	R	Service type
REQUEST = capabilities	R				Request name
REQUEST = GetCapabilities		R	R	R	Request name
UPDATESEQUENCE = string		O	O	O	Sequence number or string for cache control
Vendor-specific parameters	O				Vendor-specific parameters

R=Required / O=Optional

WMS *GetMap* Request (Core)

Request Parameter	1.0	1.1	1.1.1	1.3.0	Description
WMTVER = 1.0.0	R				Request version
VERSION = version		R	R	R	Request version.
REQUEST = map	R				Request name.
REQUEST = GetMap		R	R	R	Request name.
LAYERS = layer_list	R	R	R	R	Comma-separated list of one or more map layers. Optional (ver. 1.1, 1.1.1) if SLD parameter is present.
STYLES = style_list	R	R	R	R	Comma-separated list of one rendering style per requested layer. Optional if SLD parameter is present.
SRS = namespace:identifier	R	R	R		Spatial Reference System.
CRS = namespace:identifier				R	Spatial Reference System.

Request Parameter	1.0	1.1	1.1.1	1.3.0	Description
BBOX = minx,miny,maxx,maxy	R	R	R	R	Bounding box corners (lower left, upper right) in SRS units.
WIDTH = output_width	R	R	R	R	Width in pixels of map picture.
HEIGHT = output_height	R	R	R	R	Height in pixels of map picture.
FORMAT = output_format	R	R	R	R	Output format of map.
TRANSPARENT = TRUE or FALSE	O	O	O	O	Background transparency of map (default = FALSE).
BGCOLOR = color_value	O	O	O	O	Hexadecimal red-green-blue color value for the background color (default = 0xFFFFFF).
EXCEPTIONS = exception_format	O	O	O	O	The format in which exceptions are to be reported by the WMS (default = XML).
TIME = time		O	O	O	Time value of layer desired.
ELEVATION = elevation		O	O	O	Elevation of layer desired.
Other sample dimensions		O	O	O	Values of other dimensions as appropriate.
Vendor specific parameters	O	O	O	O	Vendor specific parameters

WMS GetFeatureInfo Request

Request Parameter	1.0	1.1	1.1.1	1.3.0	Description
WMTVER = 1.0.0	R				Request version.
VERSION = version		R	R	R	Request version.
REQUEST = feature_info	R				Request name.
REQUEST = GetFeatureInfo		R	R	R	Request name.
<map_request_copy>	R	R	R	R	Partial copy of the Map request parameters that generated the map for which information is desired
QUERY_LAYERS = layer_list	R	R	R	R	Comma-separated list of one or more layers to be queried.
INFO_FORMAT = output_format	O	O	O	R	Return format of feature information (MIME type).
FEATURE_COUNT = number	O	O	O	O	Number of features about which to return information (default = 1).
X = pixel_column	R	R	R		X coordinate in pixels of feature (measured from upper left corner = 0)
I = pixel_column				R	i coordinate in pixels of feature in Map CS
Y = pixel_row	R	R	R		Y coordinate in pixels of feature (measured from upper left corner = 0)
J = pixel_row				R	j coordinate in pixels of feature in Map CS
EXCEPTIONS = exception_format		O	O	O	The format in which exceptions are to be reported by the WMS (default = XML).
Vendor-specific parameters	O	O	O		Optional experimental parameters.

WMS GetCapabilities

```

1 http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
2 da70dc92f2cc/services/ogc/wms?
3     SERVICE=wms&
4     REQUEST=GetCapabilities&
5     VERSION=1.1.1

```

[Live Link](#)

```

1 <?xml version='1.0' encoding="ISO-8859-1" standalone="no" ?>
2 <!DOCTYPE WMT_MS_Capabilities SYSTEM "http://schemas.opengis.net/wms/1.1.1/
3 WMT_MS_Capabilities.dtd"
4 [
5 <!-- VendorSpecificCapabilities EMPTY -->
6 ]> <!-- end of DOCTYPE declaration -->
7
8 <WMT_MS_Capabilities version="1.1.1">
9
10 <!-- MapServer version 6.0.3 OUTPUT=GIF OUTPUT=PNG OUTPUT=JPEG OUTPUT=KML SUPPORTS=PROJ
11 SUPPORTS=AGG SUPPORTS=FREETYPE SUPPORTS=ICONV SUPPORTS=WMS_SERVER SUPPORTS=WMS_CLIENT
12 SUPPORTS=WFS_SERVER SUPPORTS=WFS_CLIENT SUPPORTS=WCS_SERVER SUPPORTS=SOS_SERVER
13 INPUT=POSTGIS INPUT=OGR INPUT=GDAL INPUT=SHAPEFILE -->

```

```

14
15 <Service>
16   <Name>OGC:WMS</Name>
17   <Title>tl_2010_35_state10</Title>
18   <Abstract>WMS Service for RGIS dataset State Boundary - 2010
19   (6ca5428a-a78c-4c82-8120-da70dc92f2cc)</Abstract>
20   <KeywordList>
21     <Keyword>RGIS</Keyword>
22     <Keyword> New Mexico</Keyword>
23   </KeywordList>
24   <OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
25   xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
26   da70dc92f2cc/services/ogc/wms"/>
27   <ContactInformation>
28     <ContactPersonPrimary>
29       <ContactPerson>GStore Support</ContactPerson>
30       <ContactOrganization>Earth Data Analysis Center</ContactOrganization>
31     </ContactPersonPrimary>
32     <ContactPosition>technical support</ContactPosition>
33     <ContactAddress>
34       <AddressType>Mailing address</AddressType>
35       <Address>Earth Data Analysis Center, MSC01 1110,
36       1 University of New Mexico</Address>
37       <City>Albuquerque</City>
38       <StateOrProvince>NM</StateOrProvince>
39       <PostCode>87131</PostCode>
40       <Country>US</Country>
41     </ContactAddress>
42     <ContactVoiceTelephone>(505) 277-3622</ContactVoiceTelephone>
43     <ContactFacsimileTelephone>(505) 277-3614</ContactFacsimileTelephone>
44     <ContactElectronicMailAddress>gstore@edac.unm.edu</ContactElectronicMailAddress>
45   </ContactInformation>
46   <Fees>None</Fees>
47   <AccessConstraints>none</AccessConstraints>
48 </Service>
49
50 <Capability>
51   <Request>
52     <GetCapabilities>
53       <Format>application/vnd.ogc.wms_xml</Format>
54       <DCPType>
55         <HTTP>
56           <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
57           xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
58           8120-da70dc92f2cc/services/ogc/wms?"/></Get>
59           <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
60           xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
61           8120-da70dc92f2cc/services/ogc/wms?"/></Post>
62         </HTTP>
63       </DCPType>
64     </GetCapabilities>
65     <GetMap>
66       <Format>image/png</Format>
67       <Format>image/gif</Format>

```

```

68     <Format>image/jpeg</Format>
69     <Format>image/png; mode=8bit</Format>
70     <Format>image/tiff</Format>
71     <Format>application/vnd.google-earth.kml+xml</Format>
72     <Format>application/vnd.google-earth.kmz</Format>
73     <DCPType>
74         <HTTP>
75             <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
76                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
77                 8120-da70dc92f2cc/services/ogc/wms?"/></Get>
78             <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
79                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
80                 8120-da70dc92f2cc/services/ogc/wms?"/></Post>
81         </HTTP>
82     </DCPType>
83 </GetMap>
84 <GetFeatureInfo>
85     <Format>text/plain</Format>
86     <Format>application/vnd.ogc.gml</Format>
87     <DCPType>
88         <HTTP>
89             <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
90                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
91                 8120-da70dc92f2cc/services/ogc/wms?"/></Get>
92             <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
93                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-
94                 8120-da70dc92f2cc/services/ogc/wms?"/></Post>
95         </HTTP>
96     </DCPType>
97 </GetFeatureInfo>
98 <DescribeLayer>
99     <Format>text/xml</Format>
100     <DCPType>
101         <HTTP>
102             <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
103                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
104                 da70dc92f2cc/services/ogc/wms?"/></Get>
105             <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
106                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
107                 da70dc92f2cc/services/ogc/wms?"/></Post>
108         </HTTP>
109     </DCPType>
110 </DescribeLayer>
111 <GetLegendGraphic>
112     <Format>image/png</Format>
113     <Format>image/gif</Format>
114     <Format>image/jpeg</Format>
115     <Format>image/png; mode=8bit</Format>
116     <DCPType>
117         <HTTP>
118             <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
119                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
120                 da70dc92f2cc/services/ogc/wms?"/></Get>
121             <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"

```

```

122         xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
123         da70dc92f2cc/services/ogc/wms?"/></Post>
124     </HTTP>
125 </DCPType>
126 </GetLegendGraphic>
127 <GetStyles>
128     <Format>text/xml</Format>
129     <DCPType>
130         <HTTP>
131             <Get><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
132             xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
133             da70dc92f2cc/services/ogc/wms?"/></Get>
134             <Post><OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink"
135             xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-
136             da70dc92f2cc/services/ogc/wms?"/></Post>
137         </HTTP>
138     </DCPType>
139 </GetStyles>
140 </Request>
141 <Exception>
142     <Format>application/vnd.ogc.se_xml</Format>
143     <Format>application/vnd.ogc.se_inimage</Format>
144     <Format>application/vnd.ogc.se_blank</Format>
145 </Exception>
146 <VendorSpecificCapabilities />
147 <UserDefinedSymbolization SupportSLD="1" UserLayer="0" UserStyle="1" RemoteWFS="0"/>
148 <Layer>
149     <Name>t1_2010_35_state10</Name>
150     <Title>t1_2010_35_state10</Title>
151     <Abstract>WMS Service for RGIS dataset State Boundary - 2010
152     (6ca5428a-a78c-4c82-8120-da70dc92f2cc)</Abstract>
153     <KeywordList>
154         <Keyword>RGIS</Keyword>
155         <Keyword> New Mexico</Keyword>
156     </KeywordList>
157     <SRS>EPSG:4269</SRS>
158     <SRS>EPSG:4326</SRS>
159     <SRS>EPSG:4267</SRS>
160     <SRS>EPSG:26913</SRS>
161     <SRS>EPSG:26912</SRS>
162     <SRS>EPSG:26914</SRS>
163     <SRS>EPSG:26713</SRS>
164     <SRS>EPSG:26712</SRS>
165     <SRS>EPSG:26714</SRS>
166     <SRS>EPSG:3857</SRS>
167     <LatLonBoundingBox minx="-109.05" miny="31.3322" maxx="-103.002" maxy="37.0003" />
168     <BoundingBox SRS="EPSG:4326"
169         minx="-109.05" miny="31.3322" maxx="-103.002" maxy="37.0003" />
170     <Layer queryable="1" opaque="0" cascaded="0">
171         <Name>t1_2010_35_state10</Name>
172         <Title>t1_2010_35_state10</Title>
173         <Abstract>State Boundary - 2010</Abstract>
174         <KeywordList>
175             <Keyword></Keyword>

```

```

176     </KeywordList>
177     <SRS>epsg:4326</SRS>
178     <LatLonBoundingBox minx="-109.05" miny="31.3322" maxx="-103.002" maxy="37.0003" />
179     <BoundingBox SRS="epsg:4326"
180         minx="-109.05" miny="31.3322" maxx="-103.002" maxy="37.0003" />
181     <MetadataURL type="FGDC-STD-001-1998">
182         <Format>text/xml</Format>
183         <OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink" xlink:type="simple"
184             xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-da70dc92f2cc/met
185     </MetadataURL>
186     <Style>
187         <Name>default</Name>
188         <Title>default</Title>
189         <LegendURL width="72" height="22">
190             <Format>image/png</Format>
191             <OnlineResource xmlns:xlink="http://www.w3.org/1999/xlink" xlink:type="simple"
192                 xlink:href="http://gstore.unm.edu/apps/rgis/datasets/6ca5428a-a78c-4c82-8120-da70dc92f2cc/
193             </LegendURL>
194         </Style>
195     </Layer>
196 </Layer>
197 </Capability>
198 </WMT_MS_Capabilities>

```

WMS GetMap




Figure 3: Sample WMS response #1

```

1  http://gstore.unm.edu/apps/rgis/datasets/
2  6ca5428a-a78c-4c82-8120-da70dc92f2cc/
3  services/ogc/wms?
4      VERSION=1.1.1&
5      SERVICE=WMS&
6      REQUEST=GetMap&
7      BBOX=-109,31,-102.9,37.1&
8      LAYERS=tl_2010_35_state10&
9      WIDTH=200&
10     HEIGHT=200&
11     SRS=EPSG:4326&

```

```
12  FORMAT=image/jpeg&
13  STYLES=
```

[link](#)



Figure 4: Sample WMS response #2

```
1  http://gstore.unm.edu/apps/rgis/datasets/
2  6ca5428a-a78c-4c82-8120-da70dc92f2cc/
3  services/ogc/wms?
4  VERSION=1.1.1&
5  SERVICE=WMS&
6  REQUEST=GetMap&
7  BBOX=-109,31,-102.9,37.1&
8  LAYERS=t1_2010_35_state10&
9  WIDTH=300&
10 HEIGHT=300&
11 SRS=EPSG:4326&
12 TRANSPARENT=TRUE&
13 FORMAT=image/png&
14 STYLES=
```

[link](#)

Integraton of WMS and KML

- The KML GroundOverlay element may be used to integrate a network accessible map image into a client
- A WMS service may be used to as the source of a KML GroundOverlay element
- KML includes parameterizations that allow for dynamic generation of WMS requests using client bounding box information
- Time-enabled WMS may be accessed through use of manually configured time parameters in WMS URLs and TimeStamp or TimeSpan KML elements

Sample WMS-KML Integration

```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <kml xmlns="http://www.opengis.net/kml/2.2" xmlns:gx="http://www.google.com/kml/ext/2.2"
3   xmlns:kml="http://www.opengis.net/kml/2.2" xmlns:atom="http://www.w3.org/2005/Atom">
4   <GroundOverlay>
5     <name>RGIS Counties WMS</name>
6     <Icon>
7       <href>http://gstore.unm.edu/apps/rgis/datasets/107046/services/ogc/wms?
8         VERSION=1.1.1&SERVICE=WMS&REQUEST=GetMap&BBOX=-109,31,-102.9,37.1
9         &LAYERS=tl_2010_35_state10&WIDTH=800&HEIGHT=800&SRS=EPSG:4326
10        &FORMAT=image/png&STYLES=</href>
11      <viewRefreshMode>onStop</viewRefreshMode>
12    </Icon>
13    <LatLonBox>
14      <north>37.32753828398865</north>
15      <south>30.86418272137246</south>
16      <east>-101.3630220689848</east>
17      <west>-110.6891149310152</west>
18    </LatLonBox>
19  </GroundOverlay>
20 </kml>
```

Sample KML File

This work by Karl Benedict is licensed under a Creative Commons Attribution-ShareAlike 4.0 International License.