

# Data Modelling Methods-III

CS771: Introduction to Machine Learning  
Purushottam Kar



# Mid Semester Examination


- September 21<sup>st</sup>, 2017 (Thursday) 1300–1500 hrs
- Venue L18, 19, L20 (all OROS)
- Syllabus: till whatever we cover today
- Open notes (handwritten only)
- No printed/photocopied material
- No laptops, i-pads, mobile phones (switched off)
- Please bring a notepad with you for rough work
- Please bring a pencil/eraser with you – we will not provide these
- Answers will have to be written on the question paper itself

# Recap

Sept 13, 2017



# The generative story for labelled data



$$\mathbb{P}[\mathbf{x}^i, z^i | \Theta] = \mathbb{P}[z^i | \Theta] \cdot \mathbb{P}[\mathbf{x}^i | z^i, \Theta] = \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i | \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P}[X, \{z^i\} | \Theta] = \prod_{i=1}^n \mathbb{P}[\mathbf{x}^i, z^i | \Theta]$$

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X, \{z^i\} | \Theta]$$

Take log and apply 1<sup>st</sup> order optimality

Read [DAU] Sections 9.1-9.5

$$\pi_1^{\text{MLE}} = \frac{\# \text{ red emails}}{\# \text{ total emails}} = \frac{n_r}{n}$$

$$\mu_{\text{MLE}}^1 = \frac{1}{n_r} \sum_{i: z^i = \bullet} \mathbf{x}^i$$


$$\Sigma_{\text{MLE}}^1 = \frac{1}{n_r} \sum_{i: z^i = \bullet} (\mathbf{x}^i - \mu_{\text{MLE}}^1)(\mathbf{x}^i - \mu_{\text{MLE}}^1)^{\top}$$

# Recap

Sept 13, 2017



# The generative story for unlabelled data



$z^i$  denotes the (unknown) component from which  $x^i$  came

$z^i$  not known from data. It is a *latent variable* (can take  $K$  values).

Gaussian Mixture Model (GMM) with  $K$  components

$\pi_k = \mathbb{P}[z^i = k]$  prior prob. of  $x^i$  coming from  $k$ -th component

Goal: incomplete data, learn  $\mu^k, \Sigma^k, \mathbb{P}[z = k]$

$$\begin{aligned} \mathbb{P}[\mathbf{x}^i | \Theta] &= \sum_{k=1}^K \mathbb{P}[\mathbf{x}^i, z^i = k | \Theta] = \sum_{k=1}^K \pi_k \cdot \mathbb{P}[\mathbf{x}^i | z^i = k, \Theta] \\ &= \sum_{k=1}^K \pi_k \cdot \mathcal{N}(\mathbf{x}^i | \mu^k, \Sigma^k) \end{aligned}$$

# Recap

Sept 13, 2017



# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X \mid \Theta]$$

Looks like block coordinate descent with  $\Theta, \{z^i\}$  being two blocks of "coordinates"

## ALTERNATING OPTIMIZATION


1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} \mid \Theta]$
4. Repeat until convergence

Various ways of updating  $z^i$




# Recap

## The generative story for labelled data



## The generative story for unlabelled data



## A Ray of Hope

$$\hat{\Theta}_{MLE} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

### ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Various ways of updating  $z^i$

Looks like block coordinate descent with  $\Theta, \{z^i\}$  being two blocks of "coordinates"

# Hard Assignment

The K-means algorithm

Sept 8, 2017



# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

Looks like block coordinate descent with  $\Theta, \{z^i\}$  being two blocks of "coordinates"

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Various ways of updating  $z^i$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \mathbb{P}[k | \Theta^t] \cdot \mathbb{P}[\mathbf{x}^i | k, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathbb{P}[\mathbf{x}^i | k, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$



# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# Towards the K-Means Algorithm

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \max_k \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i \mid \boldsymbol{\mu}^{k,t}, \Sigma^{k,t})$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} \mid \Theta]$ 
  1. Let  $\pi_k^{t+1} = \frac{n_k^t}{n}$ , where  $n_k^t = |\{i: z^{i,t} = k\}|$
  2. Let  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
  3. Let  $\Sigma_k^{t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} (\mathbf{x}^i - \boldsymbol{\mu}^{k,t}) (\mathbf{x}^i - \boldsymbol{\mu}^{k,t})^\top$
4. Repeat until convergence



# A few simplifications

- Fix  $\boldsymbol{\pi}_k^t = \frac{1}{K}$  for all iterations. Don't update it.
- Fix  $\boldsymbol{\Sigma}^{k,t} = I$  for all iterations. Don't update it.

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$ 
  1. Let  $z^{i,t} = \arg \max_k \mathcal{N}(\mathbf{x}^i \mid \boldsymbol{\mu}^{k,t}, I)$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# A few simplifications

- Fix  $\boldsymbol{\pi}_k^t = \frac{1}{K}$  for all iterations. Don't update it.
- Fix  $\boldsymbol{\Sigma}^{k,t} = I$  for all iterations. Don't update it.

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# A few simplifications

- Fix  $\boldsymbol{\pi}_k^t = \frac{1}{K}$  for all iterations. Don't update it.
- Fix  $\boldsymbol{\Sigma}^{k,t} = I$  for all iterations. Don't update it.

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# The K-Means Objective

# The K-Means Objective

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\boldsymbol{\mu}^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i = k} \|\mathbf{x}^i - \boldsymbol{\mu}^k\|_2^2$$

# The K-Means Objective

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\boldsymbol{\mu}^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i = k} \|\mathbf{x}^i - \boldsymbol{\mu}^k\|_2^2$$

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# The K-Means Objective

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\boldsymbol{\mu}^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i=k} \|\mathbf{x}^i - \boldsymbol{\mu}^k\|_2^2$$

Alternates between updating  $\{z^i\}$  and  $\{\boldsymbol{\mu}^k\}$

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# The K-Means Objective

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\mu^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i=k} \|\mathbf{x}^i - \mu^k\|_2^2$$

An FA approach to solving a data modelling task!

Alternates between updating  $\{z^i\}$  and  $\{\mu^k\}$

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# The K-Means Objective

NP-hard problem!

An FA approach to solving a data modelling task!

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\mu^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i=k} \|\mathbf{x}^i - \mu^k\|_2^2$$

Alternates between updating  $\{z^i\}$  and  $\{\mu^k\}$

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# The K-Means Objective

NP-hard problem!

An FA approach to solving a data modelling task!

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\mu^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i = k} \|\mathbf{x}^i - \mu^k\|_2^2$$

Alternates between updating  $\{z^i\}$  and  $\{\mu^k\}$

Very scalable but sensitive to initialization!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# The K-Means Objective

NP-hard problem!

An FA approach to solving a data modelling task!

$$\hat{\Theta}_{\text{km}} = \arg \min_{\substack{\{\mu^k\}_{k=1,\dots,K} \\ \{z^i\}_{i=1,\dots,n}}} \sum_{k=1}^K \sum_{i: z^i=k} \|\mathbf{x}^i - \mu^k\|_2^2$$

Alternates between updating  $\{z^i\}$  and  $\{\mu^k\}$

Very scalable but sensitive to initialization!

k-means++ initialization

1. Sample  $i_1 \sim [n]$ , let  $\mu^{1,0} = \mathbf{x}^{i_1}$
2. For  $k = 2, \dots, K$ 
  - Sample  $i_k \propto \text{min distance from } \{\mu^{1,0}, \dots, \mu^{k-1,0}\}$
  - Let  $\mu^{k,0} = \mathbf{x}^{i_k}$

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$ 
  1. Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# K-Means Algorithm in action!




## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence








# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM





1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence






# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

Stuck!!!

# K-Means Algorithm in action!




## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence

# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence






# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence








# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM




1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k^t} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence



# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM


1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k} \sum_{i:z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence





# K-Means Algorithm in action!

## K-MEANS/LLOYD'S ALGORITHM

1. Initialize means  $\{\mu^{k,0}\}_{k=1\dots K}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\mu^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \mu^{k,t}\|_2^2$
3. Update  $\mu^{k,t+1} = \frac{1}{n_k} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
4. Repeat until convergence




Stuck!!! ... but  
at the global  
optimum 😊




# The Magic is not Always very Useful!


# The Magic is not Always very Useful!



# The Magic is not Always very Useful!




# The Magic is not Always very Useful!






# The Magic is not Always very Useful!




# The Magic is not Always very Useful!




# The Magic is not Always very Useful!

Apply the k-means algorithm





# The Magic is not Always very Useful!

Apply the k-means algorithm





# The Magic is not Always very Useful!

Apply the k-means algorithm





# The Magic is not Always very Useful!

Apply the k-means algorithm





# The Magic is not Always very Useful!

Apply the k-means algorithm



# The Magic is not Always very Useful!



Apply the k-means algorithm







# The Magic is not Always very Useful!

Apply the k-means algorithm






# The Magic is not Always very Useful!

Apply the k-means algorithm



# The Magic is not Always very Useful!


Apply the k-means algorithm





The problem is NP hard for a reason!

# The Magic is not Always very Useful!

Apply the k-means algorithm



Most utility of k-means comes in problems that have some apparent structure



The problem is NP hard for a reason!

# Soft Assignment

The EM algorithm

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$



# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \mathbb{P}[k | \Theta^t] \cdot \mathbb{P}[\mathbf{x}^i | k, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathbb{P}[\mathbf{x}^i | k, \Theta^t]$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$
4. Repeat until convergence

Bayes  
Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$

2. For  $i \in [n]$  update  $z^{i,t}$  using  $\Theta^t$

May be throwing away a lot of information!

$$z^{i,t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$$

Repeat until convergence

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

E.g.  $\mathbb{P}[\text{red} | \mathbf{x}^i, \Theta^t] = 0.5,$   
 $\mathbb{P}[\text{blue} | \mathbf{x}^i, \Theta^t] = 0.4,$   
 $\mathbb{P}[\text{green} | \mathbf{x}^i, \Theta^t] = 0.1,$

## EM ALGORITHM: EM ALTERNATING OPTIMIZATION

Initialize  $\Theta^0$

1. For  $i \in [n]$  update  $z^{i,t}$  using  $\Theta^t$

May be throwing away a lot of information!

$$z^{i,t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$$

Bayes Rule!

2. Repeat until convergence

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

E.g.  $\mathbb{P}[\text{red} | \mathbf{x}^i, \Theta^t] = 0.5,$   
 $\mathbb{P}[\text{blue} | \mathbf{x}^i, \Theta^t] = 0.4,$   
 $\mathbb{P}[\text{green} | \mathbf{x}^i, \Theta^t] = 0.1,$

Can we use  $\mathbb{P}[k | \mathbf{x}^i, \Theta^t]$  as weights instead?

For  $i \in [n]$  update  $z^{i,t}$  using  $\Theta^t$

May be throwing away a lot of information!

$$z^{i,t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$$

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \{ \pi^t, \{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \}, \{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \} \}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

Assign point  $\mathbf{x}^i$  to cluster  $k$  with weight  $\propto \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$

E.g.  $\mathbb{P}[\text{red} | \mathbf{x}^i, \Theta^t] = 0.5$ ,  
 $\mathbb{P}[\text{blue} | \mathbf{x}^i, \Theta^t] = 0.4$ ,  
 $\mathbb{P}[\text{green} | \mathbf{x}^i, \Theta^t] = 0.1$ ,

Can we use  $\mathbb{P}[k | \mathbf{x}^i, \Theta^t]$  as weights instead?

EMERNA

For  $i \in [n]$  update  $z^{i,t}$  using  $\Theta^t$

May be throwing away a lot of information!

$$z^{i,t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$$

Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$

$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$

# A Ray of Hope

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X | \Theta]$$

E.g.  $\mathbb{P}[\text{red} | \mathbf{x}^i, \Theta^t] = 0.5,$   
 $\mathbb{P}[\text{blue} | \mathbf{x}^i, \Theta^t] = 0.4,$   
 $\mathbb{P}[\text{green} | \mathbf{x}^i, \Theta^t] = 0.1,$

Assign point  $\mathbf{x}^i$  to cluster  $k$  with weight  $\propto \mathbb{P}[k | \mathbf{x}^i, \Theta^t]$

Can we use  $\mathbb{P}[k | \mathbf{x}^i, \Theta^t]$  as weights instead?

Has a "Bayesian" feel to it – use all available posterior information

For  $i \in [n]$  update  $z^{i,t}$  using  $\Theta^t$

Maybe throwing away a lot of information!

$$z^{i,t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} | \Theta]$$


Bayes Rule!

$$z^{i,t} = \arg \max_{k \in [K]} \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \arg \max_{k \in [K]} \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})$$


$$\Theta^t = \left\{ \pi^t, \left\{ \mu^{1,t}, \mu^{2,t}, \mu^{3,t} \right\}, \left\{ \Sigma^{1,t}, \Sigma^{2,t}, \Sigma^{3,t} \right\} \right\}$$




# Weighted MLE



# Weighted MLE




# Weighted MLE



$$\mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta] = \gamma^i \cdot \mathbb{P} [z^i \mid \Theta] \cdot \mathbb{P} [\mathbf{x}^i \mid z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{z^i}, \Sigma^{z^i})$$


# Weighted MLE



$$\mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta] = \gamma^i \cdot \mathbb{P} [z^i \mid \Theta] \cdot \mathbb{P} [\mathbf{x}^i \mid z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P} [X, \{z^i\}, \{\gamma^i\} \mid \Theta] = \prod_{i=1}^n \mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta]$$

# Weighted MLE




$$\mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta] = \gamma^i \cdot \mathbb{P} [z^i \mid \Theta] \cdot \mathbb{P} [\mathbf{x}^i \mid z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P} [X, \{z^i\}, \{\gamma^i\} \mid \Theta] = \prod_{i=1}^n \mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta]$$

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P} [X, \{z^i\}, \{\gamma^i\} \mid \Theta]$$

# Weighted MLE




$$\mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta] = \gamma^i \cdot \mathbb{P} [z^i \mid \Theta] \cdot \mathbb{P} [\mathbf{x}^i \mid z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P} [X, \{z^i\}, \{\gamma^i\} \mid \Theta] = \prod_{i=1}^n \mathbb{P} [\mathbf{x}^i, z^i, \gamma^i \mid \Theta]$$

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P} [X, \{z^i\}, \{\gamma^i\} \mid \Theta]$$

Take log and apply 1<sup>st</sup> order optimality

# Weighted MLE



$$\mathbb{P}[\mathbf{x}^i, z^i, \gamma^i | \Theta] = \gamma^i \cdot \mathbb{P}[z^i | \Theta] \cdot \mathbb{P}[\mathbf{x}^i | z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i | \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P}[X, \{z^i\}, \{\gamma^i\} | \Theta] = \prod_{i=1}^n \mathbb{P}[\mathbf{x}^i, z^i, \gamma^i | \Theta]$$


$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X, \{z^i\}, \{\gamma^i\} | \Theta]$$

Take log and apply 1<sup>st</sup> order optimality


$$\pi_1^{\text{MLE}} = \frac{\# \text{ eff. red emails}}{\# \text{ eff. total emails}} = \frac{\tilde{n}_r}{n} = \frac{\sum_{i: z^i = \bullet} \gamma^i}{\sum_{j=1}^n \gamma^j}$$

$$\mu_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot \mathbf{x}^i$$

$$\Sigma_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot (\mathbf{x}^i - \mu_{\text{MLE}}^1)(\mathbf{x}^i - \mu_{\text{MLE}}^1)^\top$$



# Weighted MLE



$$\mathbb{P}[\mathbf{x}^i, z^i, \gamma^i \mid \Theta] = \gamma^i \cdot \mathbb{P}[z^i \mid \Theta] \cdot \mathbb{P}[\mathbf{x}^i \mid z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P}[X, \{z^i\}, \{\gamma^i\} \mid \Theta] = \prod_{i=1}^n \mathbb{P}[\mathbf{x}^i, z^i, \gamma^i \mid \Theta]$$

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X, \{z^i\}, \{\gamma^i\} \mid \Theta]$$


Take log and apply 1<sup>st</sup> order optimality

Exercise!

$$\pi_1^{\text{MLE}} = \frac{\# \text{ eff. red emails}}{\# \text{ eff. total emails}} = \frac{\tilde{n}_r}{n} = \frac{\sum_{i: z^i = \bullet} \gamma^i}{\sum_{j=1}^n \gamma^j}$$


$$\mu_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot \mathbf{x}^i$$

$$\Sigma_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot (\mathbf{x}^i - \mu_{\text{MLE}}^1)(\mathbf{x}^i - \mu_{\text{MLE}}^1)^\top$$





# Weighted MLE



Reduces to normal MLE if  $\gamma^i = 1$  for all  $i$



$$\mathbb{P}[\mathbf{x}^i, z^i, \gamma^i | \Theta] = \gamma^i \cdot \mathbb{P}[z^i | \Theta] \cdot \mathbb{P}[\mathbf{x}^i | z^i, \Theta] = \gamma^i \cdot \pi_{z^i} \cdot \mathcal{N}(\mathbf{x}^i | \mu^{z^i}, \Sigma^{z^i})$$

$$\mathbb{P}[X, \{z^i\}, \{\gamma^i\} | \Theta] = \prod_{i=1}^n \mathbb{P}[\mathbf{x}^i, z^i, \gamma^i | \Theta]$$

$$\hat{\Theta}_{\text{MLE}} = \arg \max_{\Theta} \mathbb{P}[X, \{z^i\}, \{\gamma^i\} | \Theta]$$


Take log and apply 1<sup>st</sup> order optimality

Exercise!

$$\pi_1^{\text{MLE}} = \frac{\# \text{ eff. red emails}}{\# \text{ eff. total emails}} = \frac{\tilde{n}_r}{n} = \frac{\sum_{i: z^i = \bullet} \gamma^i}{\sum_{j=1}^n \gamma^j}$$

$$\mu_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot \mathbf{x}^i$$

$$\Sigma_{\text{MLE}}^1 = \frac{1}{\tilde{n}_r} \sum_{i: z^i = \bullet} \gamma^i \cdot (\mathbf{x}^i - \mu_{\text{MLE}}^1)(\mathbf{x}^i - \mu_{\text{MLE}}^1)^\top$$



# Hard Alternating Minimization

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \max_k \pi_k^t \cdot \mathcal{N}(\mathbf{x}^i \mid \boldsymbol{\mu}^{k,t}, \Sigma^{k,t})$
3. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[X, \{z^{i,t}\} \mid \Theta]$
4. Repeat until convergence

# Soft Alternating Minimization

## ALTERNATING OPTIMIZATION

1. For  $i \in [n]$ , create  $k$  copies of the data point
  1. Let  $\mathbf{x}^i \rightarrow \{\mathbf{x}^{\{i,1\}}, \mathbf{x}^{\{i,2\}}, \dots, \mathbf{x}^{\{i,k\}}\}$
  2. Assign the  $k$ -th copy label  $k$  i.e.  $z^{\{i,k\}} = k$
2. Initialize  $\Theta^0$
3. Update weights  $\gamma^{i,k,t}$  using  $\Theta^t$ 
  1. Let  $\gamma^{i,k,t} = \mathbb{P}[k \mid \mathbf{x}^i, \Theta^t] = \frac{\pi_k^t \cdot \mathcal{N}(\mathbf{X}^i \mid \mu^{k,t}, \Sigma^{k,t})}{\sum_j \pi_j^t \cdot \mathcal{N}(\mathbf{X}^i \mid \mu^{j,t}, \Sigma^{j,t})}$
4. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P} [\{x^{\{i,k\}}\}, \{z^{\{i,k\}}\}, \{\gamma^{\{i,k,t\}}\} \mid \Theta]$
5. Repeat until convergence



# Soft Alternating Minimization

## ALTERNATING OPTIMIZATION

1. For  $i \in [n]$ , create  $k$  copies of the data point

1. Let  $\mathbf{x}^i \rightarrow \{\mathbf{x}^{\{i,1\}}, \mathbf{x}^{\{i,2\}}, \dots, \mathbf{x}^{\{i,k\}}\}$

2. Assign the  $k$ -th copy label  $k$  i.e.  $z^{\{i,k\}} = k$

2. Initialize  $\Theta^0$

3. Update weights  $\gamma^{i,k,t}$  using  $\Theta^t$

1. Let  $\gamma^{i,k,t} = \mathbb{P}[k \mid \mathbf{x}^i, \Theta^t] = \frac{\pi_k^t \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{k,t}, \Sigma^{k,t})}{\sum_j \pi_j^t \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{j,t}, \Sigma^{j,t})}$

4. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[\{\mathbf{x}^{\{i,k\}}\}, \{z^{\{i,k\}}\}, \{\gamma^{\{i,k,t\}}\} \mid \Theta]$

5. Repeat until convergence

$$\sum_j \gamma^{\{i,j,t\}} = 1$$

for all  $i$  and  
all  $t$



# Soft Alternating Minimization

## ALTERNATING OPTIMIZATION

1. For  $i \in [n]$ , create  $k$  copies of the data point

1. Let  $\mathbf{x}^i \rightarrow \{\mathbf{x}^{\{i,1\}}, \mathbf{x}^{\{i,2\}}, \dots, \mathbf{x}^{\{i,k\}}\}$

2. Assign the  $k$ -th copy label  $k$  i.e.  $z^{\{i,k\}} = k$

2. Initialize  $\Theta^0$

3. Update weights  $\gamma^{i,k,t}$  using  $\Theta^t$

1. Let  $\gamma^{i,k,t} = \mathbb{P}[k \mid \mathbf{x}^i, \Theta^t] = \frac{\pi_k^t \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{k,t}, \Sigma^{k,t})}{\sum_j \pi_j^t \cdot \mathcal{N}(\mathbf{x}^i \mid \mu^{j,t}, \Sigma^{j,t})}$

4. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[\{\mathbf{x}^{\{i,k\}}\}, \{z^{\{i,k\}}\}, \{\gamma^{\{i,k,t\}}\} \mid \Theta]$

5. Repeat until convergence

Distribute a unit weight across clusters

$$\sum_j \gamma^{\{i,j,t\}} = 1$$

for all  $i$  and all  $t$



# Soft Alternating Minimization

Hard-AM: all weight was on a single cluster

## ALTERNATING OPTIMIZATION

1. For  $i \in [n]$ , create  $k$  copies of the data point

1. Let  $\mathbf{x}^i \rightarrow \{\mathbf{x}^{\{i,1\}}, \mathbf{x}^{\{i,2\}}, \dots, \mathbf{x}^{\{i,k\}}\}$

2. Assign the  $k$ -th copy label  $k$  i.e.  $z^{\{i,k\}} = k$

2. Initialize  $\Theta^0$

3. Update weights  $\gamma^{i,k,t}$  using  $\Theta^t$

1. Let  $\gamma^{i,k,t} = \mathbb{P}[k | \mathbf{x}^i, \Theta^t] = \frac{\pi_k^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{k,t}, \Sigma^{k,t})}{\sum_j \pi_j^t \cdot \mathcal{N}(\mathbf{x}^i | \mu^{j,t}, \Sigma^{j,t})}$

4. Update  $\Theta^{t+1} = \arg \max_{\Theta} \mathbb{P}[\{\mathbf{x}^{\{i,k\}}\}, \{z^{\{i,k\}}\}, \{\gamma^{\{i,k,t\}}\} | \Theta]$

5. Repeat until convergence

Distribute a unit weight across clusters

$$\sum_j \gamma^{\{i,j,t\}} = 1 \text{ for all } i \text{ and all } t$$



# Soft k-means Algorithm

- Fix  $\boldsymbol{\pi}_k^t = \frac{1}{K}$  for all iterations. Don't update it.
- Fix  $\boldsymbol{\Sigma}^{k,t} = I$  for all iterations. Don't update it.

## K-MEANS ALGO

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For all  $i$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Let  $n_k^t = |i: z^{i,t} = k|$
4. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
5. Repeat until convergence

## SOFT K-MEANS ALGO

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For all  $i$ , update  $\gamma^{i,k,t}$  using  $\boldsymbol{\mu}^{k,t}$

$$\text{Let } \gamma^{i,k,t} = \frac{\exp\left(-\frac{\|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2}{2}\right)}{\sum_j \exp\left(-\frac{\|\mathbf{x}^i - \boldsymbol{\mu}^{j,t}\|_2^2}{2}\right)}$$

3. Let  $\tilde{n}_k^t = \sum_i \gamma^{i,k,t}$
4. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{\tilde{n}_k^t} \sum_i \gamma^{i,k,t} \cdot \mathbf{x}^i$
5. Repeat until convergence

# Soft k-means Algorithm

- Fix  $\boldsymbol{\pi}_k^t = \frac{1}{K}$  for all iterations. Don't update it.
- Fix  $\boldsymbol{\Sigma}^{k,t} = I$  for all iterations. Don't update it.

## K-MEANS ALGO

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For all  $i$ , update  $z^{i,t}$  using  $\boldsymbol{\mu}^{k,t}$   
Let  $z^{i,t} = \arg \min_k \|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2$
3. Let  $n_k^t = |i: z^{i,t} = k|$
4. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{n_k^t} \sum_{i: z^{i,t}=k} \mathbf{x}^i$
5. Repeat until convergence

## SOFT K-MEANS ALGO

1. Initialize means  $\{\boldsymbol{\mu}^{k,0}\}_{k=1,\dots,K}$
2. For all  $i$ , update  $\gamma^{i,k,t}$  using  $\boldsymbol{\mu}^{k,t}$

$$\text{Let } \gamma^{i,k,t} = \frac{\exp\left(-\frac{\|\mathbf{x}^i - \boldsymbol{\mu}^{k,t}\|_2^2}{2}\right)}{\sum_j \exp\left(-\frac{\|\mathbf{x}^i - \boldsymbol{\mu}^{j,t}\|_2^2}{2}\right)}$$

3. Let  $\tilde{n}_k^t = \sum_i \gamma^{i,k,t}$
4. Update  $\boldsymbol{\mu}^{k,t+1} = \frac{1}{\tilde{n}_k^t} \sum_i \gamma^{i,k,t} \cdot \mathbf{x}^i$
5. Repeat until convergence



# Mixed Regression

# Mixed Regression

Sept 13, 2017




# Mixed Regression



Sept 13, 2017




# Mixed Regression




Sept 13, 2017



# Mixed Regression




# Mixed Regression




$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}\end{aligned}$$

# Mixed Regression



$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}\end{aligned}$$


# Mixed Regression



$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}\end{aligned}$$



# Mixed Regression




$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}\end{aligned}$$

Regression with a  
classification touch 😊

E.g. recommendation systems, a  
different system might work for  
young and old but we don't know  
age of users

# Mixed Regression



$$\hat{\mathbf{w}}_{\text{MAP}} = \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2$$
$$= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}$$

Regression with a  
classification touch 😊

E.g. recommendation systems, a  
different system might work for  
young and old but we don't know  
age of users

Mixed models, Mixture of Experts

# Mixed Regression

$$\mathbb{P}[y \mid \mathbf{x}^i, z^i, \mathbf{w}] = \mathcal{N}(\langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(y - \langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle)^2}{2\sigma^2}\right)$$

- Assume for sake of simplicity that both models are equally sampled  $\mathbb{P}[z = 0] = \mathbb{P}[z = 1] = 0.5$
- Assume for sake of simplicity that Gaussian noise  $\sigma_1 = \sigma_2 = 1$
- Only unknowns are the two linear models  $\mathbf{w}^1, \mathbf{w}^2$

# Mixed Regression

$$\mathbb{P}[y \mid \mathbf{x}^i, z^i, \mathbf{w}] = \mathcal{N}(\langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(y - \langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle)^2}{2\sigma^2}\right)$$

$z^i \in \{0,1\}$  indicates  
which line  
generated the data

- Assume for sake of simplicity that both models are equally sampled  $\mathbb{P}[z = 0] = \mathbb{P}[z = 1] = 0.5$
- Assume for sake of simplicity that Gaussian noise  $\sigma_1 = \sigma_2 = 1$
- Only unknowns are the two linear models  $\mathbf{w}^1, \mathbf{w}^2$

# Mixed Regression

$$\mathbb{P}[y \mid \mathbf{x}^i, z^i, \mathbf{w}] = \mathcal{N}(\langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(y - \langle \mathbf{w}^{z^i}, \mathbf{x}^i \rangle)^2}{2\sigma^2}\right)$$

$z^i \in \{0,1\}$  indicates  
which line  
generated the data

$z^i$  is a latent  
variable!

- Assume for sake of simplicity that both models are equally sampled  $\mathbb{P}[z = 0] = \mathbb{P}[z = 1] = 0.5$
- Assume for sake of simplicity that Gaussian noise  $\sigma_1 = \sigma_2 = 1$
- Only unknowns are the two linear models  $\mathbf{w}^1, \mathbf{w}^2$

# Hard Mixed Regression

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \max_{k \in \{0,1\}} \mathcal{N}(y^i \mid \mathbf{x}^i, \mathbf{w}^{k,t})$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_{i: z^{i,t}=k} (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

# Hard Mixed Regression

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \max_{k \in \{0,1\}} \mathcal{N}(y^i \mid \mathbf{x}^i, \mathbf{w}^{k,t})$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_{i: z^{i,t}=k} (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

# Hard Mixed Regression

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \min_{k \in \{0,1\}} |y^i - \langle \mathbf{w}^{t,k}, \mathbf{x}^i \rangle|$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_{i: z^{i,t}=k} (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence



# Hard Mixed Regression

## ALTERNATING OPTIMIZATION

Assign to  
the “closest”  
line!

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \min_{k \in \{0,1\}} |y^i - \langle \mathbf{w}^{t,k}, \mathbf{x}^i \rangle|$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_{i: z^{i,t}=k} (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

# Hard Mixed Regression

## ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $z^{i,t}$  using  $\Theta^t$ 
  1. Let  $z^{i,t} = \arg \min_{k \in \{0,1\}} |y^i - \langle \mathbf{w}^{t,k}, \mathbf{x}^i \rangle|$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_{i: z^{i,t}=k} (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

Assign to the "closest" line!

In k-means, we assigned to the closest mean

Exercise: verify these updates

# Weighted Regression

Sept 13, 2017



# Weighted Regression

$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}\end{aligned}$$

# Weighted Regression

$$\begin{aligned}\hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y} \\ \hat{\mathbf{w}}_{\text{MAP}} &= \arg \min \sum_{i=1}^n \gamma_i \cdot \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2 \\ &= (M + \lambda \cdot I)^{-1} \mathbf{b} \\ M &= \sum_{i=1}^n \gamma_i \mathbf{x}^i (\mathbf{x}^i)^\top \\ \mathbf{b} &= \sum_{i=1}^n \gamma_i y_i \cdot \mathbf{x}^i\end{aligned}$$

# Weighted Regression

$$\hat{\mathbf{w}}_{\text{MAP}} = \arg \min \sum_{i=1}^n \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2$$

$$= (\mathbf{X}\mathbf{X}^\top + \lambda \cdot I)^{-1} \mathbf{X}\mathbf{y}$$

$$\hat{\mathbf{w}}_{\text{MAP}} = \arg \min \sum_{i=1}^n \gamma_i \cdot \left( y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle \right)^2 + \lambda \cdot \|\mathbf{w}\|_2^2$$

$$= (M + \lambda \cdot I)^{-1} \mathbf{b}$$

$$M = \sum_{i=1}^n \gamma_i \mathbf{x}^i (\mathbf{x}^i)^\top$$

$$\mathbf{b} = \sum_{i=1}^n \gamma_i y_i \cdot \mathbf{x}^i$$

# Soft Mixed Regression

## SOFT ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $\gamma^{\{i,k,t\}}$  using  $\Theta^t$ 
  1. Let  $c^{\{i,k,t\}} = \exp\left(-\frac{(y^i - \langle \mathbf{w}^{\{t,k\}}, \mathbf{x}^i \rangle)^2}{2}\right)$
  2. Let  $\gamma^{\{i,k,t\}} = \frac{c^{\{i,k,t\}}}{c^{\{i,0,t\}} + c^{\{i,1,t\}}}$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_i \gamma^{\{i,k,t\}} \cdot (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

# Soft Mixed Regression

## SOFT ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $\gamma^{\{i,k,t\}}$  using  $\Theta^t$ 
  1. Let  $c^{\{i,k,t\}} = \exp\left(-\frac{(y^i - \langle \mathbf{w}^{\{t,k\}}, \mathbf{x}^i \rangle)^2}{2}\right)$
  2. Let  $\gamma^{\{i,k,t\}} = \frac{c^{\{i,k,t\}}}{c^{\{i,0,t\}} + c^{\{i,1,t\}}}$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_i \gamma^{\{i,k,t\}} \cdot (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

Exercise: derive these updates



# Soft Mixed Regression

## SOFT ALTERNATING OPTIMIZATION

1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $\gamma^{\{i,k,t\}}$  using  $\Theta^t$ 
  1. Let  $c^{\{i,k,t\}} = \exp\left(-\frac{(y^i - \langle \mathbf{w}^{\{t,k\}}, \mathbf{x}^i \rangle)^2}{2}\right)$
  2. Let  $\gamma^{\{i,k,t\}} = \frac{c^{\{i,k,t\}}}{c^{\{i,0,t\}} + c^{\{i,1,t\}}}$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_i \gamma^{\{i,k,t\}} \cdot (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

$$\propto \mathbb{P}[k | y^i, \mathbf{x}^i, \Theta^t]$$

Exercise: derive these updates

# Soft Mixed Regression

## SOFT ALTERNATING OPTIMIZATION





1. Initialize  $\Theta^0 = \{\mathbf{w}^{\{0,0\}}, \mathbf{w}^{\{0,1\}}\}$
2. For  $i \in [n]$ , update  $\gamma^{\{i,k,t\}}$  using  $\Theta^t$ 
  1. Let  $c^{\{i,k,t\}} = \exp\left(-\frac{(y^i - \langle \mathbf{w}^{\{t,k\}}, \mathbf{x}^i \rangle)^2}{2}\right)$ 

$\propto \mathbb{P}[k | y^i, \mathbf{x}^i, \Theta^t]$
  2. Let  $\gamma^{\{i,k,t\}} = \frac{c^{\{i,k,t\}}}{c^{\{i,0,t\}} + c^{\{i,1,t\}}}$ 

$= \mathbb{P}[k | y^i, \mathbf{x}^i, \Theta^t]$
3. Update  $\mathbf{w}^{\{t+1,k\}} = \arg \min_{\mathbf{w}} \sum_i \gamma^{\{i,k,t\}} \cdot (y^i - \langle \mathbf{w}, \mathbf{x}^i \rangle)^2 + \frac{1}{2} \|\mathbf{w}\|_2^2$
4. Set  $\Theta^{t+1} = \{\mathbf{w}^{\{t+1,0\}}, \mathbf{w}^{\{t+1,1\}}\}$
5. Repeat until convergence

Exercise: derive these updates

# Soft MR in action



# The EM Algorithm

- Generalizes the notion of “soft” updates
- Very powerful algorithm
- Related to alternating minimization
- Will study this next time!

# Please give your Feedback

<http://tinyurl.com/ml17-18afb>