

[NAME](#) | [SYNOPSIS](#) | [DESCRIPTION](#) | [RETURN VALUE](#) | [ERRORS](#) | [CONFORMING TO](#)
| [NOTES](#) | [SEE ALSO](#) | [COLOPHON](#)

Search online pages

NICE(2)

Linux Programmer's Manual

NICE(2)

NAME [top](#)

`nice` - change process priority

SYNOPSIS [top](#)

```
#include <unistd.h>
```

```
int nice(int inc);
```

Feature Test Macro Requirements for glibc (see [feature_test_macros\(7\)](#)):

```
nice() : _XOPEN_SOURCE
|| /* Since glibc 2.19: */ _DEFAULT_SOURCE
|| /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE
```

DESCRIPTION [top](#)

nice() adds *inc* to the nice value for the calling thread. (A higher nice value means a low priority.)

The range of the nice value is +19 (low priority) to -20 (high priority). Attempts to set a nice value outside the range are clamped to the range.

Traditionally, only a privileged process could lower the nice value (i.e., set a higher priority). However, since Linux 2.6.12, an unprivileged process can decrease the nice value of a target process that has a suitable **RLIMIT_NICE** soft limit; see [getrlimit\(2\)](#) for details.

RETURN VALUE [top](#)

On success, the new nice value is returned (but see NOTES below). On error, -1 is returned, and *errno* is set appropriately.

A successful call can legitimately return -1. To detect an error, set *errno* to 0 before the call, and check whether it is nonzero after **nice**() returns -1.

ERRORS [top](#)

EPERM The calling process attempted to increase its priority by supplying a negative *inc* but has insufficient privileges. Under Linux, the **CAP_SYS_NICE** capability is required. (But see the discussion of the **RLIMIT_NICE** resource limit in [setrlimit\(2\)](#).)

CONFORMING TO [top](#)

POSIX.1-2001, POSIX.1-2008, SVr4, 4.3BSD. However, the raw system call and (g)libc (earlier than glibc 2.2.4) return value is nonstandard, see below.

NOTES [top](#)

For further details on the nice value, see [sched\(7\)](#).

Note: the addition of the "autogroup" feature in Linux 2.6.38 means that the nice value no longer has its traditional effect in many circumstances. For details, see [sched\(7\)](#).

C library/kernel differences

POSIX.1 specifies that **nice()** should return the new nice value. However, the raw Linux system call returns 0 on success. Likewise, the **nice()** wrapper function provided in glibc 2.2.3 and earlier returns 0 on success.

Since glibc 2.2.4, the **nice()** wrapper function provided by glibc provides conformance to POSIX.1 by calling [getpriority\(2\)](#) to obtain the new nice value, which is then returned to the caller.

SEE ALSO [top](#)

[nice\(1\)](#), [renice\(1\)](#), [fork\(2\)](#), [getpriority\(2\)](#), [getrlimit\(2\)](#), [setpriority\(2\)](#), [capabilities\(7\)](#), [sched\(7\)](#)

COLOPHON [top](#)

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2016-12-12

NICE(2)

[Copyright and license for this manual page](#)

HTML rendering created 2017-03-13 by [Michael Kerrisk](#), author of *The Linux Programming Interface*, maintainer of the [Linux man-pages project](#).

For details of in-depth Linux/UNIX system programming training courses that I teach, look [here](#).

Hosting by [jambit GmbH](#).

