

[NAME](#) | [SYNOPSIS](#) | [DESCRIPTION](#) | [RETURN VALUE](#) | [ERRORS](#) | [CONFORMING TO](#)
| [NOTES](#) | [SEE ALSO](#) | [COLOPHON](#)

Search online pages

SCHED_RR_GET_INTERVAL(2) Linux Programmer's Manual SCHED_RR_GET_INTERVAL(2)

NAME [top](#)

`sched_rr_get_interval` - get the SCHED_RR interval for the named process

SYNOPSIS [top](#)

```
#include <sched.h>
```

```
int sched_rr_get_interval(pid_t pid, struct timespec *tp);
```

DESCRIPTION [top](#)

`sched_rr_get_interval()` writes into the *timespec* structure pointed to by *tp* the round-robin time quantum for the process identified by *pid*. The specified process should be running under the **SCHED_RR** scheduling policy.

The *timespec* structure has the following form:

```
struct timespec {
    time_t tv_sec;    /* seconds */
    long   tv_nsec;   /* nanoseconds */
};
```

If *pid* is zero, the time quantum for the calling process is written into **tp*.

RETURN VALUE [top](#)

On success, `sched_rr_get_interval()` returns 0. On error, -1 is returned, and *errno* is set appropriately.

ERRORS [top](#)

EFAULT Problem with copying information to user space.

EINVAL Invalid *pid*.

ENOSYS The system call is not yet implemented (only on rather old kernels).

ESRCH Could not find a process with the ID *pid*.

CONFORMING TO [top](#)

POSIX.1-2001, POSIX.1-2008.

NOTES [top](#)

POSIX systems on which `sched_rr_get_interval()` is available define **_POSIX_PRIORITY_SCHEDULING** in *<unistd.h>*.

Linux notes

POSIX does not specify any mechanism for controlling the size of the round-robin time quantum. Older Linux kernels provide a (nonportable) method of doing this. The quantum can be controlled by adjusting the process's nice value (see [setpriority\(2\)](#)). Assigning a negative (i.e., high) nice value results in a longer quantum; assigning a positive (i.e., low) nice value results in a shorter quantum. The default quantum is 0.1 seconds; the degree to which changing the nice value affects the quantum has varied somewhat across kernel versions. This method of adjusting the quantum was removed starting with Linux 2.6.24.

Linux 3.9 added a new mechanism for adjusting (and viewing) the **SCHED_RR** quantum: the `/proc/sys/kernel/sched_rr_timeslice_ms` file exposes the quantum as a millisecond value, whose default is 100. Writing 0 to this file resets the quantum to the default value.

SEE ALSO [top](#)

[sched\(7\)](#)

COLOPHON [top](#)

This page is part of release 4.10 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2015-08-08

SCHED_RR_GET_INTERVAL(2)

[Copyright and license for this manual page](#)

HTML rendering created 2017-03-13 by [Michael Kerrisk](#), author of *The Linux Programming Interface*, maintainer of the [Linux man-pages project](#).

For details of in-depth Linux/UNIX system programming training courses that I teach, look [here](#).

Hosting by [jambit GmbH](#).

