

A COMPARATIVE STUDY OF TECHNIQUES FOR ESTIMATION AND INFERENCE OF NONLINEAR STOCHASTIC TIME SERIES

Dexter Barrows, B.Sc.

Masters Thesis Defence
McMaster University
April 2016

1. Framing
2. Stochastic SIR Model
3. Hamiltonian HMC
4. Iterated Filtering 2
5. Fitting Results
6. Forecasting Frameworks
7. S-maps & Seasonal Outbreaks
8. Spatiotemporal Epidemics
9. Parallelism & Future Directions

Framing



System M
S-I-S
GAL
Particle-Filter
EnKF
Hamiltonian-MCMC
Ensemble-KF
SMC Bootstrap
Complex-Projection
Pop-Regression
MP
ABC
ARIMA
MARSS
MCMC
Kalman-Filter
Particle-Filter
Sampling
MCMC
Parametric
Particle
HMM
SMC
Complex-Projection
Pop-Regression
MP

Stochastic SIR model

$$\frac{dS}{dt} = -\beta SI$$


$$\frac{dI}{dt} = \beta SI - \gamma I$$

$$\frac{dR}{dt} = \gamma I$$

+

$$\beta_{t+1} = \exp [\beta_t + \eta (\bar{\beta} - \beta_t) + \mathcal{N}(0, \sigma_{\text{proc}})]$$

Model simulations



Solid – sample trajectory · dots – sample data · dotted – average · ribbon – overall

Hamiltonian MCMC

3

MCMC

Iteratively construct
Markov chain to
approximate posterior

1. Choose starting parameter set
2. Generate N samples by
 - 2.1 Propose new sample
 - 2.2 Compute acceptance ratio
 - 2.3 Accept/reject sample

HMC

Proposal via Hamiltonian
dynamics

1. Choose starting parameter set
2. Generate N samples by
 - 2.1 Resample moments
 - 2.2 Simulate Hamiltonian dynamics using Leapfrog integration
 - 2.3 Compute acceptance ratio
 - 2.4 Accept/reject sample

Hamiltonian Dynamics

Energy

Kinetic

$$K(r) = \frac{1}{2} r^T M^{-1} r$$

Potential

$$U(\theta) = -\log(\mathcal{L}(\theta)p(\theta))$$

Hamiltonian

$$H(\theta, r) = U(\theta) + K(r)$$

Dynamics simulation

$$\begin{aligned} \frac{d\theta}{dt} &= M^{-1} r \\ \frac{dr}{dt} &= -\nabla U(\theta) \end{aligned}$$


Iterated Filtering 2



Basic particle filter

Iterative prediction-update cycle prunes particle cohort of poor parameter estimates

1. Initialize particles with parameter sets
2. For each data point
 - 2.1 Evolve particle states
 - 2.2 Weight via likelihood
 - 2.3 Resample proportional to weights




Iterated Filtering 2 (IF2)

Evolution of MIF (IFI)

Multiple passes through data

Treat parameter estimates as stochastic processes

- Alleviates risk of particle collapse
- Process noise decreases with passes




Fitting Results

5


IF2

state estimates



HMC


state estimates



Dashed – estimates · solid – true · dots – data · ribbon – trajectories


IF2

final particle
swarm samples









HMC

posterior
distribution
estimates




Dashed – medians · solid – true

Mean parameter estimate distributions



IF2 · HMC

Running times



IF2: 5.7x faster than HMC

Forecasting Frameworks



IF2

Parametric bootstrapping
+ forward simulation

- Provides additional samples from posterior distribution
- Forward simulation using states point estimate, posterior samples


HMC

State reconstructions
+ forward simulation

- Reconstruct states using latent process noise samples
- Simulate forward


IF2

forecast




HMC

forecast



Dotted/dashed - mean · Dark ribbon - state · Light ribbon - observation

Forecast accuracy comparison



S-maps & Seasonal Outbreaks



Stochastic SIRS model

$$\frac{dS}{dt} = -\Gamma(t)\beta SI + \alpha R$$

$$\frac{dI}{dt} = \Gamma(t)\beta SI - \gamma I$$


$$\frac{dR}{dt} = \gamma I - \alpha R$$

+

$$\Gamma(t) = \exp \left[2 \left(\cos \left(\frac{2\pi}{365} t \right) \right) \right]$$

$$\beta_{t+1} = \exp \left[\beta_t + \eta (\bar{\beta} - \beta_t) + \mathcal{N}(0, \sigma_{\text{proc}}) \right]$$

SIRS model simulation




S-map


A little bit of history repeating

- Construct global weighted mapping of time-lagged vectors (the library) to future states
- Weightings are used to penalize poorly matching library vectors


S-map forecast



SIRS model forecasting error



SIRS model forecasting runtimes



S-map: 316,000x faster than IF2, 61,800x faster than HMC

Spatiotemporal Epidemics




Stochastic Spatial SIR model

$$\begin{aligned}\frac{dS_i}{dt} &= - \left(1 - \phi \frac{M}{M+1} \right) \beta_i S_i I_i - \frac{\phi}{M+1} S_i \sum_{j=1}^M \beta_{ij} I_j \\ \frac{dI_i}{dt} &= \left(1 - \phi \frac{M}{M+1} \right) \beta_i S_i I_i + \frac{\phi}{M+1} S_i \sum_{j=1}^M \beta_{ij} I_j - \gamma I_i \\ \frac{dR_i}{dt} &= \gamma I_i\end{aligned}$$

+

$$\beta_{i,t+1} = \exp \left[\beta_{i,t} + \eta \left(\bar{\beta} - \beta_{i,t} \right) + \mathcal{N}(0, \sigma_{\text{proc}}) \right]$$


Stochastic spatial SIR model simulation (ring topology)




Dewdrop Regression

- “Stitching” together multiple short time series into single library
- Requires scaling

Spatial SIR model forecasting error



Spatial SIR model forecasting runtimes



S-map: 116x faster than IF2, 156x faster than HMC

Parallelism & Future Directions




Conclusions

- IF2 produces superior forecasts in all scenarios
- S-mapping runs orders of magnitude faster than other methods

More than Moore

- Moore's Law is ceasing to hold
- Focus now on distributed computing
- MCMC-based methods are resistant to parallelization
 - Chain construction requires iterative dependence
- IF2 exhibits high parallel potential
 - Preliminary CUDA (GPU-accelerated) implementation - **cuIF2**

Spatial SIR model fitting times



cuIF2: 9.33x faster than IF2, 617x faster than HMC

Questions


[1] D. Barrows.

A Comparative Study of Techniques for Estimation and Inference of Nonlinear Stochastic Time Series. Master's thesis, McMaster University, Hamilton, Canada, 2016.

[2] A. Doucet, N. de Freitas, and N. Gordon.

An Introduction to Sequential Monte Carlo Methods.

Sequential Monte Carlo Methods in Practice, pages 3–14, 2001.



THE BEST THESIS DEFENSE IS A GOOD THESIS OFFENSE.