

PRODUCT CATALOG / GEC SERIES

Commercial ceiling

商用天花式抽濕機

MODELS

GEC68LD-HP · GEC145LD-HP · GEC280LD
GEC400LD · GEC550LD

CAPACITY

68–550 L/day

High static pressure ducted ceiling dehumidifiers built for large floors and multi-room distribution. RS485 BMS standard, 68 to 550 L/day capacity. Engineered for offices, retail, hotel ballrooms, indoor pools, and large clubhouses.

為大空間設計的高靜壓商用天花機 — 商廈辦公室、零售商舖、酒店宴會廳、室內泳池、大型會所。RS485 BMS 標配，68 至 550 公升 / 日抽濕量任選，多區管道分送。

01 ABOUT THE GEC SERIES

System overview

The GEC commercial ceiling series handles large floor plates and ducted multi-zone distribution that smaller residential units cannot serve. High static pressure (up to 80 Pa) drives air through long duct runs, while the stainless evaporator and pump drainage suit demanding industrial and commercial environments. Five capacity points cover everything from a 1,000 sq ft retail unit to a 5,000 sq ft hotel ballroom.

GEC 商用天花系列專為大面積、多區管道分送設計 — 高靜壓 (最高 80 Pa) 推動長距離管道送風，不銹鋼蒸發器與排水泵應對嚴苛的商業與工業環境。五款抽濕量由 68 至 550 公升 / 日，涵蓋 1,000 至 5,000 平方呎空間。

KEY FEATURES

What's standard

- High static pressure for ducting
- Stainless steel evaporator & tank
- Pump drainage with 10 m head
- RS485 Modbus BMS interface
- Three-phase models (GEC400LD+)
- DC inverter compressor (HP series)
- Centralised setpoint and alarms
- Concealed false-ceiling mount
- Low-noise EC fan motor

APPLICATIONS

Where it works

- Open-plan offices & coworking
- Retail outlets & showrooms
- Hotel ballrooms & lobbies
- Indoor swimming pools
- Clubhouses & banquet halls
- Logistics & cold storage rooms

02 GEC SERIES MODEL SPECIFICATIONS

Specifications

All measurements at 27 °C / 60% RH unless otherwise stated.

PARAMETER	GEC68LD-HP	GEC145LD-HP	GEC280LD	GEC400LD	GEC550LD
Dehumidification 抽濕量	68 L/day	145 L/day	280 L/day	400 L/day	550 L/day
Coverage 適用面積	800–1,000 sq ft	1,500–1,700 sq ft	2,500–3,000 sq ft	3,000–4,000 sq ft	4,000–5,000 sq ft
Airflow 風量	500 CMH	1,200 CMH	1,700 CMH	3,250 CMH	3,250 CMH
External static 外靜壓	30 Pa	50 Pa	60 Pa	80 Pa	80 Pa
Dimensions (mm) 尺寸	970 × 525 × 345	1,005 × 695 × 440	1,137 × 900 × 512	1,270 × 1,200 × 605	1,270 × 1,200 × 605
Power supply 電源	1ph 230V	1ph 230V	3ph 380V	3ph 380V	3ph 380V

03 HOW TO PICK A GEC MODEL

Sizing guide

Match the right unit to the room load. / 按面積選型

ROOM TYPE	FLOOR AREA	RECOMMENDED	NOTES
Small office / retail	800–1,000 sq ft	GEC68LD-HP	Single zone
Open-plan office	1,500–1,700 sq ft	GEC145LD-HP	BMS-ready
Showroom / hall	2,500–3,000 sq ft	GEC280LD	3-phase
Banquet / clubhouse	3,000–4,000 sq ft	GEC400LD	High static
Indoor pool / hangar	4,000–5,000 sq ft	GEC550LD	Maximum
Multi-zone hotel floor	Custom	GEC400LD x N	Per-zone duct

Free site assessment, 24-hour response

免費場地評估 · 一個工作天回覆

Tell us your floor area, ceiling height, target RH and timeline. A Hong Kong engineer will reply with model recommendation, pricing, lead-time, and a site survey appointment.

→ www.erv.hk/#quote · [WhatsApp +852 8404 3880](https://www.whatsapp.com/channel/0029va833333333333333333) · erv@erv.hk