

PRODUCT CATALOG / UTC SERIES

Ultra-thin ceiling

超薄天花式抽濕機

MODELS

CAPACITY

UTC20 · UTC68 · UTC120

20–120 L/day

A 200 mm slim profile that disappears into any false ceiling. Pure precision dehumidification from 39 dB(A) — quieter than a hushed conversation. UV-C lamp, WiFi App, RS485 BMS, and Hong Kong Grade 1 Energy Label on the entry model.

200 mm 超薄機身，無聲融入假天花。專注於高效抽濕，39 dB(A) 起，比安靜對話更輕。配備 UV-C 殺菌、WiFi App、RS485 BMS，UTC20 取得香港一級能源標籤。

01 ABOUT THE UTC SERIES

System overview

The UTC Series prioritises absolute precision dehumidification with a near-silent profile. At only 200 mm thick (UTC20), it disappears into any false ceiling and is ideal as a humidity supplement when fresh-air ventilation is already handled separately. UV-C sterilisation, scheduled timers, WiFi App, and RS485 Modbus BMS are standard.

UTC 系列專注於精準、靜音抽濕。最薄機型 200 mm (UTC20)，無聲融入假天花，適合已有獨立新風系統的住宅或會所作為濕度補強。標配 UV-C 殺菌燈、定時開關、WiFi App 與 RS485 Modbus 樓宇管理系統接口。

KEY FEATURES

What's standard

- Slim 200–310 mm profile
- 39 dB(A) low-noise operation
- UV-C sterilisation lamp
- Stainless steel mesh filter
- 1.8 m head drain pump
- 5 m humidity sensor cable
- WiFi App + IR remote
- RS485 Modbus BMS
- HK Grade 1 Energy Label (UTC20)

APPLICATIONS

Where it works

- Existing AC + ventilation projects
- Apartments needing pure RH control
- Bedrooms (low-noise priority)
- Wine storage rooms
- Storage & wardrobes
- Server / equipment closets

02 UTC SERIES MODEL SPECIFICATIONS

Specifications

All measurements at 27 °C / 60% RH unless otherwise stated.

PARAMETER	UTC20 ENERGY GRADE 1	UTC68	UTC120
Dehumidification 抽濕量	20 L/day	68 L/day	120 L/day
Coverage 適用面積	200–400 sq ft	800–1000 sq ft	1300–1500 sq ft
Airflow 風量	220 CMH	500 CMH	890 CMH
Noise 噪音	39 dB(A)	48 dB(A)	50 dB(A)
Profile thickness 厚度	200 mm	240 mm	310 mm
Dimensions (mm) 尺寸	865 × 376 × 200	1010 × 500 × 240	1075 × 746 × 310
Weight 重量	28 kg	42 kg	64 kg
Power supply 電源	230V / 50Hz	230V / 50Hz	230V / 50Hz

03 HOW TO PICK A UTC MODEL

Sizing guide

Match the right unit to the room load. / 按面積選型

ROOM TYPE	FLOOR AREA	RECOMMENDED	NOTES
Bedroom	200–300 sq ft	UTC20	Quiet, slim
Studio / 1-bed	200–400 sq ft	UTC20	HK Grade 1
2–3 bed flat	600–1,000 sq ft	UTC68	Pump drainage
Duplex / large	1,000+ sq ft	UTC120	Multi-zone
Wine storage room	any	UTC20	Stable RH
Office / clubhouse	1,000+ sq ft	UTC120	BMS-ready

Free site assessment, 24-hour response

免費場地評估 · 一個工作天回覆

Tell us your floor area, ceiling height, target RH and timeline. A Hong Kong engineer will reply with model recommendation, pricing, lead-time, and a site survey appointment.

→ www.erv.hk/#quote · [WhatsApp +852 8404 3880](https://www.whatsapp.com/channel/0029va333333333333333333) · erv@erv.hk