MOBSF

ANDROID STATIC ANALYSIS REPORT

Shipyee (1.0.7)

File Name: Shipyee.apk

Package Name:	com.egp_food_app
Scan Date:	Jan. 23, 2026, 3:41 a.m.
App Security Score:	55/100 (MEDIUM RISK)
Grade:	B
Trackers Detection:	1/432

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	13	2	2	1

FILE INFORMATION

File Name: Shipyee.apk
Size: 73.05MB
MD5: 1e5e9584c57fe83f4631437bb84a2510
SHA1: cce0830238e93563cef61322c724664d7f29595d
SHA256: 8cd6416237f9037fbc21ea4952e8eda5a0cc97d3f69d90d58625c0077d5408dd

APP INFORMATION

App Name: Shipyee
Package Name: com.egp_food_app
Main Activity: com.egp_food_app.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.0.7
Android Version Code: 1

APP COMPONENTS

Activities: 8
Services: 11
Receivers: 5
Providers: 6
Exported Activities: 2
Exported Services: 1
Exported Receivers: 3

Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=ID, ST=Jakarta, L=Indonesia, O=EGP Food, OU=Development, CN=EGP Food App
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-01-01 12:14:15+00:00
Valid To: 2053-05-19 12:14:15+00:00
Issuer: C=ID, ST=Jakarta, L=Indonesia, O=EGP Food, OU=Development, CN=EGP Food App
Serial Number: 0x3a5764002332e12c
Hash Algorithm: sha384
md5: a35b19a909d74df7364493a23c8ffb5f
sha1: cf41898de33538a77ba86a9cd19df179ab702585
sha256: e5d899ddebb42a30c3f6c09b2e1ad500a6ab8529bbd4ddadf5fa3b6fdf6335b5
sha512: 7ccb7fb407d66e9fbbf7efb5921ce3e6fe851e0843b31925e16c6fcd3b6f08db38dd8c4c2ccc1a608e7b22c82f27a4f05d57dca32a1d1ed7ce468b03a289e0ba
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 1976cb4268b8d41c00a7cc51db6b649f0212c90de7c9fb49d362f5a4307332c5
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.MANAGE_EXTERNAL_STORAGE	dangerous	Allows an application a broad access to external storage in scoped storage	Allows an application a broad access to external storage in scoped storage. Intended to be used by few apps that need to manage files on behalf of the users.
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.
android.permission.READ_MEDIA_VIDEO	dangerous	allows reading video files from external storage.	Allows an application to read video files from external storage.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE	normal	permission defined by google	A custom permission defined by Google.
com.google.android.gms.permission.AD_ID	normal	application shows advertisements	This app uses a Google advertising ID and can possibly serve advertisements.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_ADSERVICES_ATTRIBUTION	normal	allow applications to access advertising service attribution	This enables the app to retrieve information related to advertising attribution, which can be used for targeted advertising purposes. App can gather data about how users interact with ads, such as clicks or impressions, to measure the effectiveness of advertising campaigns.
android.permission.ACCESS_ADSERVICES_AD_ID	normal	allow app to access the device's advertising ID.	This ID is a unique, user-resettable identifier provided by Google's advertising services, allowing apps to track user behavior for advertising purposes while maintaining user privacy.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.google.android.providers.gsf.permission.READ_GSERVICES	unknown	Unknown permission	Unknown permission from android reference
com.egp_food_app.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes2.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Compiler</td><td>r8</td></tr>
</table>
</td></tr>
<tr><td>classes3.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.BRAND check
Build.DEVICE check
Build.PRODUCT check
Build.HARDWARE check
Build.BOARD check
possible Build.SERIAL check
Build.TAGS check
possible VM check</td></tr>
<tr><td>Compiler</td><td>r8</td></tr>
</table>
</td></tr>
</table>

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.google.firebase.auth.internal.GenericIdpActivity	Schemes: genericidp://, Hosts: firebase.auth, Paths: /,

ACTIVITY	INTENT
com.google.firebase.auth.internal.RecaptchaActivity	Schemes: recaptcha://, Hosts: firebase.auth, Paths: /,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: **0** | WARNING: **0** | INFO: **1**

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **1** | WARNING: **6** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version Android 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Broadcast Receiver (io.flutter.plugins.firebase.messaging.FlutterFirebaseMessagingReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Activity (com.google.firebase.auth.internal.GenericIdpActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Activity (com.google.firebase.auth.internal.RecaptchaActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
6	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
7	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 0 | WARNING: 5 | INFO: 2 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java com/mr/flutter/plugin/filepicker/FilePickerDelegate.java defpackage/ea0.java defpackage/f21.java defpackage/ks1.java defpackage/tm1.java defpackage/u81.java defpackage/wr2.java dev/fluttercommunity/plus/androidintent/MethodCallHandlerImpl.java io/flutter/Log.java io/flutter/embedding/android/FlutterActivity.java io/flutter/embedding/android/FlutterActivityAndFragmentDelegate.java io/flutter/embedding/android/FlutterFragment.java io/flutter/embedding/android/FlutterFragmentActivity.java io/flutter/embedding/android/FlutterImageView.java io/flutter/embedding/android/FlutterSurfaceView.java io/flutter/embedding/android/FlutterTextureView.java io/flutter/embedding/android/FlutterView.java io/flutter/embedding/android/KeyEmbedderRespondER.java io/flutter/embedding/android/KeyboardManager.java io/flutter/embedding/android/SurfaceHolderCallbackCompat.java io/flutter/embedding/engine/FlutterEngine.java io/flutter/embedding/engine/FlutterEngineConnectionRegistry.java io/flutter/embedding/engine/FlutterJNI.java io/flutter/embedding/engine/dart/DartExecutor.java io/flutter/embedding/engine/dart/DartMessenger.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	io/flutter/embedding/engine/deferredcomponents/PlayStoreDeferredComponentManager.java io/flutter/embedding/engine/loader/FlutterLoader.java io/flutter/embedding/engine/loader/ResourceExtractor.java io/flutter/embedding/engine/plugins/util/GeneratedPluginRegister.java io/flutter/embedding/engine/renderer/FlutterRenderer.java io/flutter/embedding/engine/systemchannels/AccessibilityChannel.java io/flutter/embedding/engine/systemchannels/BackGestureChannel.java io/flutter/embedding/engine/systemchannels/DeferredComponentChannel.java io/flutter/embedding/engine/systemchannels/KeyEventChannel.java io/flutter/embedding/engine/systemchannels/LifecycleChannel.java io/flutter/embedding/engine/systemchannels/LocalizationChannel.java io/flutter/embedding/engine/systemchannels/MouseCursorChannel.java io/flutter/embedding/engine/systemchannels/NavigationChannel.java io/flutter/embedding/engine/systemchannels/PlatformChannel.java io/flutter/embedding/engine/systemchannels/PlatformViewsChannel.java io/flutter/embedding/engine/systemchannels/PlatformViewsChannel2.java io/flutter/embedding/engine/systemchannels/RestorationChannel.java io/flutter/embedding/engine/systemchannels/ScribeChannel.java io/flutter/embedding/engine/systemchannels/SensitiveContentChannel.java io/flutter/embedding/engine/systemchannels/SettingsChannel.java io/flutter/embedding/engine/systemchannels/SpellCheckChannel.java io/flutter/embedding/engine/systemchannels/SystemChannel.java io/flutter/embedding/engine/systemchannels/TextInputChannel.java io/flutter/plugin/common/BasicMessageChannel.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				io/flutter/plugin/common/BasicMessageChannel.java io/flutter/plugin/common/EventChannel.java io/flutter/plugin/common/MethodChannel.java io/flutter/plugin/editing/InputConnectionAdaptor.java io/flutter/plugin/editing/ListenableEditingState.java io/flutter/plugin/editing/TextEditingDelta.java io/flutter/plugin/editing/TextInputPlugin.java io/flutter/plugin/platform/ImageReaderPlatformViewRenderTarget.java io/flutter/plugin/platform/PlatformPlugin.java io/flutter/plugin/platform/PlatformViewWrapper.java io/flutter/plugin/platform/PlatformViewsController.java io/flutter/plugin/platform/PlatformViewsController2.java io/flutter/plugin/platform/SingleViewPresentation.java io/flutter/plugin/platform/SingleViewWindowManager.java io/flutter/plugins/GeneratedPluginRegistrant.java io/flutter/plugins/firebase/firestore/FlutterFirebaseFirestoreMessageCodec.java io/flutter/plugins/firebase/firestore/utils/ExceptionConverter.java io/flutter/plugins/firebase/firestore/utils/PigeonParser.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingBackgroundExecutor.java io/flutter/plugins/firebase/messaging/JobIntentService.java io/flutter/plugins/imagepicker/FileUtils.java io/flutter/plugins/imagepicker/ImageResizer.java io/flutter/plugins/pathprovider/PathProviderPlugin.java io/flutter/plugins/sharedpreferences/LegacySharedPreferencesPlugin.java io/flutter/plugins/sharedpreferences/SharedPreferencesBackend.java io/flutter/plugins/sharedpreferences/SharedPreferencesPlugin.java io/flutter/plugins/urllauncher/UrlLauncherPlugin.java io/flutter/plugins/videoplayer/VideoPlayerPlugin.java io/flutter/view/AccessibilityBridge.java io/flutter/view/AccessibilityViewEmbedder.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/models/NotificationDetails.java defpackage/cg2.java io/flutter/embedding/android/FlutterActivityAndFragmentDelegate.java io/flutter/embedding/android/FlutterActivityLaunchConfigs.java io/flutter/embedding/engine/loader/ApplicationInfoLoader.java io/flutter/embedding/engine/loader/FlutterLoader.java io/flutter/embedding/engine/systemchannels/SettingsChannel.java io/flutter/plugin/editing/SpellCheckPlugin.java io/flutter/plugins/firebase/auth/Constants.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingBackgroundExecutor.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingUtils.java io/flutter/plugins/imagepicker/ImagePickerCache.java
3	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/InputConnectionAdaptor.java io/flutter/plugin/platform/PlatformPlugin.java
4	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	defpackage/cz1.java defpackage/k02.java
5	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/da0.java defpackage/ea0.java io/flutter/plugins/pathprovider/Messages.java io/flutter/plugins/pathprovider/PathProviderPlugin.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
6	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/bx1.java defpackage/d90.java defpackage/ep1.java defpackage/g0.java defpackage/mx1.java defpackage/o20.java defpackage/o80.java defpackage/oo1.java defpackage/pl1.java defpackage/qo1.java defpackage/rk1.java
7	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/ea0.java defpackage/ks1.java defpackage/tm1.java io/flutter/plugins/imagepicker/ImagePickerDelegate.java
8	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	defpackage/zq2.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00209	Get pixels from the latest rendered image	collection	io/flutter/embedding/android/FlutterImageView.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	io/flutter/embedding/android/FlutterImageView.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/baseflow/permissionhandler/PermissionManager.java com/baseflow/permissionhandler/a.java com/baseflow/permissionhandler/f.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/mr/flutter/plugin/filepicker/FilePickerDelegate.java dev/fluttercommunity/plus/androidintent/MethodCallHandlerImpl.java io/flutter/plugins/imagepicker/ImagePickerDelegate.java io/flutter/plugins/urllauncher/UrlLauncher.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/baseflow/permissionhandler/PermissionManager.java com/baseflow/permissionhandler/a.java com/baseflow/permissionhandler/f.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java io/flutter/plugins/urllauncher/UrlLauncher.java
00036	Get resource file from res/raw directory	reflection	com/baseflow/permissionhandler/PermissionManager.java com/baseflow/permissionhandler/a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java defpackage/da0.java io/flutter/plugins/imagepicker/ImagePickerDelegate.java io/flutter/plugins/urllauncher/UrlLauncher.java
00013	Read file and put it into a stream	file	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java defpackage/bl1.java defpackage/ea0.java defpackage/ga0.java defpackage/ks1.java defpackage/tm1.java defpackage/y40.java xyz/justsoft/video_thumbnail/VideoThumbnailPlugin.java
00175	Get notification manager and cancel notifications	notification	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	defpackage/da0.java defpackage/ea0.java defpackage/fv1.java io/flutter/embedding/engine/deferredcomponents/PlayStoreDeferredComponentManager.java io/flutter/embedding/engine/loader/FlutterLoader.java io/flutter/plugins/pathprovider/PathProviderPlugin.java xyz/justsoft/video_thumbnail/VideoThumbnailPlugin.java
00104	Check if the given path is directory	file	io/flutter/embedding/engine/deferredcomponents/PlayStoreDeferredComponentManager.java
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityBridge.java io/flutter/view/AccessibilityViewEmbedder.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java
00202	Make a phone call	control	com/baseflow/permissionhandler/f.java
00203	Put a phone number into an intent	control	com/baseflow/permissionhandler/f.java
00028	Read file from assets directory	file	io/flutter/embedding/engine/loader/ResourceExtractor.java
00096	Connect to a URL and set request method	command network	defpackage/ih.java
00089	Connect to a URL and receive input stream from the server	command network	defpackage/ih.java
00109	Connect to a URL and get the response code	network command	defpackage/ih.java
00012	Read data and put it into a buffer stream	file	defpackage/ea0.java
00125	Check if the given file path exist	file	io/flutter/embedding/engine/loader/FlutterLoader.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/182597064477/namespaces/firebase:fetch?key=AIzaSyATkBwq-faXq3XIf4jVyECl8njUCnYZ3OE. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	7/25	android.permission.WRITE_EXTERNAL_STORAGE, android.permission.READ_EXTERNAL_STORAGE, android.permission.INTERNET, android.permission.REQUEST_INSTALL_PACKAGES, android.permission.ACCESS_NETWORK_STATE, android.permission.WAKE_LOCK, android.permission.VIBRATE
Other Common Permissions	3/44	com.google.android.finsky.permission.BIND_GET_INSTALL_REFERRER_SERVICE, com.google.android.gms.permission.AD_ID, com.google.android.c2dm.permission.RECEIVE

Malware Permissions:
Top permissions that are widely abused by known malware.
Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
github.com	ok	**IP:** 20.205.243.166 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map
flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
fonts.gstatic.com	ok	**IP:** 64.233.170.94 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
api.cloudinary.com	ok	**IP:** 52.207.33.100 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
docs.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	**IP:** 172.217.194.113 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.35.30.167 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
api.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
dartbug.com	ok	**IP:** 216.239.32.21 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
developer.mozilla.org	ok	**IP:** 146.75.45.91 **Country:** Sweden **Region:** Vastra Gotalands lan **City:** Goeteborg **Latitude:** 57.707161 **Longitude:** 11.966790 **View:** Google Map
www.unicode.org	ok	**IP:** 104.26.10.47 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
bzakrvaisswddprwnktz.supabase.co	ok	**IP:** 172.64.149.246 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map

EMAILS

EMAIL	FILE
_httpparser@16463476.responsepa _imagefilter@17065589.fromcolorf _nativesocket@15069316.pipe _list@0150898.empty _colorfilter@17065589.srgbtoline _growablelist@0150898._ofefficie _growablelist@0150898._ofarray _assertionerror@0150898._create _growablelist@0150898._literal4	

EMAIL	FILE
_pointerpanzoomdata@324213599.fromupdate _file@15069316.fromrawpat _colorfilter@17065589.lineartosr _list@0150898._ofefficie _list@0150898.generate _imagefilter@17065589.composed _hashcollisionnode@42137193.fromcollis _bytebuffer@8027147._new _receiveportimpl@1026248.fromrawrec _uri@0150898.directory _growablelist@0150898.of _growablelist@0150898._literal2 unknown@example.com _directory@15069316.fromrawpat _assetmanifestbin@50287047.fromstanda _uri@0150898.notsimple _typeerror@0150898._create _future@5048458.zonevalue _growablelist@0150898._ofgrowabl _semanticsgeometry@270266271.root _growablelist@0150898.withcapaci _imagefilter@17065589.blur _growablelist@0150898._literal6 storationinformation@180124995.fromserial ngstreamsubscription@5048458.zoned _growablelist@0150898._literal7 _socket@15069316._readpipe authenticationscheme@16463476.fromstring _list@0150898._ofgrowabl _future@5048458.immediatee _growablelist@0150898._ofother _growablelist@0150898._literal3 _colorfilter@17065589.mode _growablelist@0150898._literal5 _list@0150898._ofother _growablelist@0150898._literal _timer@1026248.periodic _list@0150898.of _nativesocket@15069316.normal _growablelist@0150898.generate _future@5048458.immediate _growablelist@0150898._literal1 _uri@0150898.file _rawsocket@15069316._readpipe _timer@1026248._internal _growablelist@0150898._literal8	lib/armeabi-v7a/libapp.so

EMAIL	FILE
_double@0150898.fromintege _link@15069316.fromrawpat shipyeedeveloper@gmail.com	
_list@0150898._ofarray _filestream@15069316.forstdin _invocationmirror@0150898._withtype _compressednode@42137193.single	
appro@openssl.org	lib/x86_64/libflutter.so
appro@openssl.org	lib/arm64-v8a/libflutter.so
_httpparser@16463476.responsepa _imagefilter@17065589.fromcolorf _nativesocket@15069316.pipe _list@0150898.empty _colorfilter@17065589.srgbtoline _growablelist@0150898._ofefficie _growablelist@0150898._ofarray _assertionerror@0150898._create _growablelist@0150898._literal4 _pointerpanzoomdata@324213599.fromupdate _file@15069316.fromrawpat _colorfilter@17065589.lineartosr _list@0150898._ofefficie _list@0150898.generate _imagefilter@17065589.composed _hashcollisionnode@42137193.fromcollis _bytebuffer@8027147._new _receiveportimpl@1026248.fromrawrec _uri@0150898.directory _growablelist@0150898.of _growablelist@0150898._literal2 unknown@example.com _directory@15069316.fromrawpat _assetmanifestbin@50287047.fromstanda _uri@0150898.notsimple _typeerror@0150898._create _future@5048458.zonevalue _growablelist@0150898._ofgrowabl _semanticsgeometry@270266271.root _growablelist@0150898.withcapaci _imagefilter@17065589.blur _growablelist@0150898._literal6 storationinformation@180124995.fromserial ngstreamsubscription@5048458.zoned	apktool_out/lib/armeabi-v7a/libapp.so

EMAIL	FILE
_growablelist@0150898._literal7 _socket@15069316._readpipe authenticationscheme@16463476.fromstring _list@0150898._ofgrowabl _future@5048458.immediatee _growablelist@0150898._ofother _growablelist@0150898._literal3 _colorfilter@17065589.mode _growablelist@0150898._literal5 _list@0150898._ofother _growablelist@0150898._literal _timer@1026248.periodic _list@0150898.of _nativesocket@15069316.normal _growablelist@0150898.generate _future@5048458.immediate _growablelist@0150898._literal1 _uri@0150898.file _rawsocket@15069316._readpipe _timer@1026248._internal _growablelist@0150898._literal8 _double@0150898.fromintege _link@15069316.fromrawpat shipyeedeveloper@gmail.com _list@0150898._ofarray _filestream@15069316.forstdin _invocationmirror@0150898._withtype _compressednode@42137193.single	
appro@openssl.org	apktool_out/lib/x86_64/libflutter.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so

TRACKERS

TRACKER	CATEGORIES	URL
Google Firebase Analytics	Analytics	https://reports.exodus-privacy.eu.org/trackers/49

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"google_api_key" : "AIzaSyATkBwq-faXq3XIf4jVyECl8njUCnYZ3OE"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"google_crash_reporting_api_key" : "AIzaSyATkBwq-faXq3XIf4jVyECl8njUCnYZ3OE"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
a0784d7a4716f3feb4f64e7f4b39bf04
808182838485868788898a8b8c8d8e8f909192939495969798999a9b9c9d9e9f
686479766013060971498190079908139321726943530014330540939446345918554318339765539424505774633321719753296399637136332111386476861244038034037280889270700 5449
bae8e37fc83441b16034566b
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650
16a09e667f3bcc908b2fb1366ea957d3e3adec17512775099da2f590b0667322a
ChNjb20uYW5kcm9pZC52ZW5kaW5nCiBjb20uZ29vZ2xlLmFuZHJvaWQuYXBwcy5tZWV0aW5ncwohY29tLmdvb2dsZS5hbmRyb2lkLmFwcHMubWVzc2FnaW5n
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b
9a04f079-9840-4286-ab92-e65be0885f95

POSSIBLE SECRETS
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057151
e2719d58-a985-b3c9-781a-b030af78d30e
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBCaWdJbnRlZ2Vy
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5
115792089210356248762697446949407573530086143415290314195533631308867097853951
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
3617de4a96262c6f5d9e98bf9292dc29f8f41dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
36864200e0eaf5284d884a0e77d31646
23456789abcdefghjkmnpqrstvwxyz
115792089210356248762697446949407573529996955224135760342422259061068512044369
af60eb711bd85bc1e4d3e0a462e074eea428a8
051953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00
edef8ba9-79d6-4ace-a3c8-27dcd51d21ed

SCAN LOGS

Timestamp	Event	Error
2026-01-23 03:41:36	Generating Hashes	OK
2026-01-23 03:41:36	Extracting APK	OK
2026-01-23 03:41:36	Unzipping	OK
2026-01-23 03:41:36	Parsing APK with androguard	OK
2026-01-23 03:41:37	Extracting APK features using aapt/aapt2	OK
2026-01-23 03:41:37	Getting Hardcoded Certificates/Keystores	OK
2026-01-23 03:41:40	Parsing AndroidManifest.xml	OK
2026-01-23 03:41:40	Extracting Manifest Data	OK
2026-01-23 03:41:40	Manifest Analysis Started	OK
2026-01-23 03:41:40	Performing Static Analysis on: Shipyee (com.egp_food_app)	OK
2026-01-23 03:41:44	Fetching Details from Play Store: com.egp_food_app	OK

2026-01-23 03:41:44	Checking for Malware Permissions	OK
2026-01-23 03:41:44	Fetching icon path	OK
2026-01-23 03:41:44	Library Binary Analysis Started	OK
2026-01-23 03:41:44	Analyzing lib/armeabi-v7a/libflutter.so	OK
2026-01-23 03:41:44	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-01-23 03:41:44	Analyzing lib/armeabi-v7a/libapp.so	OK
2026-01-23 03:41:45	Analyzing lib/x86_64/libflutter.so	OK
2026-01-23 03:41:45	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-01-23 03:41:45	Analyzing lib/x86_64/libapp.so	OK
2026-01-23 03:41:45	Analyzing lib/arm64-v8a/libflutter.so	OK
2026-01-23 03:41:45	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-01-23 03:41:45	Analyzing lib/arm64-v8a/libapp.so	OK

2026-01-23 03:41:46	Analyzing apktool_out/lib/armeabi-v7a/libflutter.so	OK
2026-01-23 03:41:46	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-01-23 03:41:46	Analyzing apktool_out/lib/armeabi-v7a/libapp.so	OK
2026-01-23 03:41:46	Analyzing apktool_out/lib/x86_64/libflutter.so	OK
2026-01-23 03:41:46	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-01-23 03:41:46	Analyzing apktool_out/lib/x86_64/libapp.so	OK
2026-01-23 03:41:47	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2026-01-23 03:41:47	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-01-23 03:41:47	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2026-01-23 03:41:47	Reading Code Signing Certificate	OK
2026-01-23 03:41:48	Running APKiD 3.0.0	OK
2026-01-23 03:42:02	Detecting Trackers	OK

2026-01-23 03:42:07	Decompiling APK to Java with JADX	OK
2026-01-23 03:42:36	Converting DEX to Smali	OK
2026-01-23 03:42:36	Code Analysis Started on - java_source	OK
2026-01-23 03:42:38	Android SBOM Analysis Completed	OK
2026-01-23 03:42:44	Android SAST Completed	OK
2026-01-23 03:42:44	Android API Analysis Started	OK
2026-01-23 03:42:47	Android API Analysis Completed	OK
2026-01-23 03:42:47	Android Permission Mapping Started	OK
2026-01-23 03:42:49	Android Permission Mapping Completed	OK
2026-01-23 03:42:49	Android Behaviour Analysis Started	OK
2026-01-23 03:42:52	Android Behaviour Analysis Completed	OK
2026-01-23 03:42:52	Extracting Emails and URLs from Source Code	OK

2026-01-23 03:42:53	Email and URL Extraction Completed	OK
2026-01-23 03:42:53	Extracting String data from APK	OK
2026-01-23 03:42:53	Extracting String data from SO	OK
2026-01-23 03:42:54	Extracting String data from Code	OK
2026-01-23 03:42:54	Extracting String values and entropies from Code	OK
2026-01-23 03:42:58	Performing Malware check on extracted domains	OK
2026-01-23 03:43:59	Saving to Database	OK

Report Generated by - MobSF v4.4.4

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.