Literature Review: Offline Reinforcement Learning
Version 2: Parts A and B

David Bayha
ITSC 8110

November 2026

Part A: Research Papers

Papers 1–8 carry over from Version 1; Papers 9–18 are new in Version 2. Every work is described with the same four themes, of which each entry names its three most central: distribution shift, the conservatism–improvement trade-off, uncertainty quantification and calibration, and theory vs. practice.

Paper 1: Conservative Q-Learning for Offline Reinforcement Learning (CQL)

CQL trains the critic to be deliberately pessimistic about any action the dataset does not contain, so the policy stops chasing accidentally inflated scores.

1. **What is the citation?** Kumar, A., Zhou, A., Tucker, G., & Levine, S. (2020). Conservative Q-learning for offline reinforcement learning. *Advances in Neural Information Processing Systems, 33*, 1179–1191. Version reviewed: arXiv:2006.04779v3. `https://doi.org/10.48550/arXiv.2006.04779`

2. **What is the research area?** Machine learning, specifically offline reinforcement learning (RL): learning a policy from a fixed log of past decisions with no further trial and error. Within offline RL, CQL belongs to the "pessimistic critic" family: instead of restricting the policy, it lowers the scores assigned to actions outside the data. This distinguishes it from policy-constraint methods (BEAR, BRAC) and ensemble/uncertainty methods.

3. **What is the research question?** Can a critic trained to be systematically pessimistic about unseen actions produce a policy whose predicted value is a guaranteed floor on its true performance, and does that beat methods that instead constrain the policy to stay near the recorded behavior?

4. **What is the significance of the question?** Offline RL is most valuable exactly where live experimentation is expensive or dangerous (robotics, medicine, recommendation) yet where large logs already exist. Standard algorithms fail in this setting because the critic's guesses about unseen actions are never corrected and the policy is drawn to precisely those inflated scores; earlier fixes (modeling the behavior policy, uncertainty penalties) proved fragile. A cheap, principled fix would let RL reuse logged data the way supervised learning reuses datasets.

5. **What are the contributions reported in this paper?** The novel idea is a simple addition to the critic's training objective: push down the scores of whatever actions the critic currently likes too much, while propping up the scores of actions that actually appear in the data, so the net penalty lands mainly on unseen actions. Around this the paper provides two ready-to-use variants (CQL($\mathcal{H}$) and CQL(ρ)), mathematical guarantees that the learned value undercuts the true value and that the policy safely improves on the one that collected the data, and a roughly twenty-line modification of two standard algorithms, with an automatic scheme for setting the caution strength α.

6. **What is the research method?** A mix of algorithm design, mathematical analysis (mostly for simplified tabular cases, with extensions), and large-scale benchmarking on the D4RL suite (simulated locomotion, mazes, dexterous-hand and kitchen tasks) and offline Atari against established prior methods. Diagnostics check directly whether predicted values stay below true returns, and ablations isolate key design choices.

7. **What are the results?** On datasets recorded by a single behavior, CQL is close to the best prior method; on the more realistic mixed-source datasets it usually wins by large margins (e.g., 91.1–110.5 on the three random-expert locomotion tasks where the best competitors score 53.0, 2.7, and 11.1), and only the CQL variants score above zero on the hardest mazes. As designed, its predicted values are confirmed to sit below true returns, while competing methods overestimate.

8. **What are the impacts and limitations of the contributions?** CQL became the field's standard pessimistic baseline and showed pessimism can be added cheaply, without modeling the behavior that produced the data. Its limits: the guarantees cover simplified settings rather than the deep networks actually used; the caution knob α (or its auto-tuning threshold) must be retuned per domain; there is no way to decide when to stop training without trying the policy live; and one global α treats well-covered and poorly covered situations identically.

9. **How were the results evaluated or validated?** By mathematical proofs in appendices, D4RL scores averaged over four runs, direct measurements comparing predicted values against actual returns, and ablations. The evidence is broad but statistically thin: means without spreads, some baselines copied rather than rerun, and a few inconsistent tables.

10. **What are the ethical implications? How are they addressed?** The reviewed version contains no broader-impact discussion. The "safe improvement" guarantee is only relative to the logging policy, probabilistic, and assumption-bound, so the word *safe* invites misplaced trust; a policy kept near the data also keeps the data's biases; all validation is simulated; compute cost is unreported. Conservatism is an indirect step toward safer learning, but bias, deployment safeguards, and societal consequences go undiscussed.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: scores for unseen actions cannot be corrected offline. *The conservatism–improvement trade-off*: pessimism must be dosed, here via α. *Theory vs. practice*: the guarantees assume what deep networks violate.

Connection to the offline RL problem space and BCA: CQL defines the "one global pessimism knob" paradigm of the problem space; applied to CQL, BCA (Bayesian Conformal Aggregation) keeps the critic-side idea but adds calibrated per-sample caution on top of the single α, a move CQL's own appendix hints at with a count-dependent penalty.

Paper 2: A Minimalist Approach to Offline Reinforcement Learning (TD3+BC)

TD3+BC shows that adding one "stay near the recorded actions" penalty to a standard online algorithm matches far more complicated offline methods at a fraction of the compute.

1. **What is the citation?** Fujimoto, S., & Gu, S. S. (2021). A minimalist approach to offline reinforcement learning. *Advances in Neural Information Processing Systems, 34*, 20132–20145. Version reviewed: arXiv:2106.06860v2. `https://doi.org/10.48550/arXiv.2106.06860`

2. **What is the research area?** Offline RL for continuous control (robot-like tasks with smooth action spaces). TD3+BC belongs to the behavior-regularization family: methods that fight inflated scores for unseen actions by keeping the policy close to the recorded behavior.

3. **What is the research question?** Can a standard online algorithm, changed as little as possible, reach state-of-the-art offline performance, and how much of the extra machinery in recent offline methods is actually necessary?

4. **What is the significance of the question?** Every extra component (a learned model of the recorded behavior, pre-training phases, architecture changes) is a choice that normally must be validated by trying policies, which requires the very interaction offline RL is supposed to avoid. A minimal method isolates what actually works, raises the bar that elaborate methods must clear, and stays cheap as datasets grow.

5. **What are the contributions reported in this paper?** Three. First, a detective-style audit showing that two leading methods (CQL and Fisher-BRC) owed much of their scores to poorly justified engineering tweaks, not just their stated ideas. Second, the TD3+BC algorithm itself: one penalty term in the actor's objective ("score high, but stay close to the recorded action") plus standardized inputs, with a single balance setting reused across all tasks. Third, a model of careful practice: unified reruns of competitors, wall-clock timings, a demonstration that offline policies are unstable across episodes, and public code.

6. **What is the research method?** The study combines critical analysis with careful experimentation rather than new mathematics. The actor maximizes $\lambda Q(s, \pi(s)) - (\pi(s) - a)^2$ averaged over recorded state-action pairs, with the balance weight λ automatically rescaled by the typical size of the scores so one value ($\alpha = 2.5$) works everywhere. Experiments cover fifteen standard locomotion datasets with five random seeds, plus ablations removing each ingredient.

7. **What are the results?** Summed over the fifteen tasks, TD3+BC essentially ties the best competitor (979.3 vs. 974.6) and beats CQL by a wide margin (764.3), while training in 39 minutes versus over four hours for CQL. Ablations confirm both the RL term and the penalty are needed; normalization gives a smaller boost. It fails where imitation fails: datasets heavy in poor behavior (28.8 vs. CQL's 100.3 on a half-random, half-expert Walker2d mix) and the hardest mazes.

8. **What are the impacts and limitations of the contributions?** TD3+BC became the field's default baseline and the yardstick new methods must beat. It also urged the community to report stability, not just averages. Limitations: no theory; a uniform pull toward recorded actions cannot tell good recordings from bad ones and can average over genuinely different behaviors; the diagnosed instability is left unsolved; and every sample receives the same constraint strength regardless of how well the data cover it.

9. **How were the results evaluated or validated?** Five seeds, ten test episodes per checkpoint,

scores averaged over the final checkpoints rather than the luckiest one, and the two strongest competitors (CQL and Fisher-BRC) rerun from their own authors' code under one protocol. Weaknesses: no statistical tests or confidence intervals, only five seeds despite high documented variance, and a tie with Fisher-BRC that supports parity rather than superiority.

10. **What are the ethical implications? How are they addressed?** A short statement notes that learning from logged data inherits its biases, warns of misuse (e.g., more habit-forming recommendation), and argues the main effect is wider access. The paper's most useful safety contribution is candid documentation that offline policies can fail badly on individual episodes. No mitigations are proposed; all evidence is simulated.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: inflated scores for unseen actions are fought by keeping the policy close to the recorded behavior. *The conservatism–improvement trade-off*: one uniform pull toward the data, with a single balance setting; it fails where imitation fails. *Theory vs. practice*: a one-line change suffices, and engineering, not just ideas, drove prior scores.

Connection to the offline RL problem space and BCA: TD3+BC is the minimalist pole of the problem space, with one uniform constraint for every sample. Its successor (ReBRAC, Paper 4) showed this constraint is what carries the method; BCA strengthens exactly this term per sample by a calibrated factor, keeping the global weight.

Paper 3: Offline Reinforcement Learning with Implicit Q-Learning (IQL)

IQL learns values using only the actions already in the dataset, never asking "what if" about unseen actions, yet can still stitch together good behavior from suboptimal pieces.

1. **What is the citation?** Kostrikov, I., Nair, A., & Levine, S. (2022). Offline reinforcement learning with implicit Q-learning. In *International Conference on Learning Representations (ICLR 2022)*. Version reviewed: arXiv:2110.06169v1. `https://doi.org/10.48550/arXiv.2110.06169`

2. **What is the research area?** Offline RL. IQL takes a third path beside constraining the policy (TD3+BC) and penalizing the critic (CQL): *in-sample* learning, in which value networks are only ever evaluated on recorded actions, and the policy is extracted afterward by imitation weighted toward better-than-expected actions (AWR).

3. **What is the research question?** Can an offline algorithm still plan ahead by chaining many steps of value backups toward optimal behavior while its value functions are trained only on logged actions, so that unseen actions are never scored at all?

4. **What is the significance of the question?** Asking the critic about unseen actions is the root cause of offline failure, and every existing fix compromises between safety and improvement. One-step in-sample alternatives avoid the problem but cannot stitch fragments of good behavior together; for example, they cannot assemble a full maze solution from partial trajectories. Removing the problem while keeping multi-step planning would resolve the field's central tension, cheaply.

5. **What are the contributions reported in this paper?** The novel core is "implicit" value learning: a state-value network trained with an asymmetric loss (an expectile loss, whose level

acts as an optimism dial) estimates the best value achievable within the data, and a second network then learns action values one step further, so the pair plans ahead without ever scoring an unseen action. Supporting contributions: a proof that turning the dial fully optimistic recovers the best in-data value; policy extraction by weighted imitation; a correction of earlier unfair benchmark comparisons; an offline-to-online fine-tuning study; and fast public code.

6. **What is the research method?** Algorithm design plus a short limiting argument, then benchmarking: a toy maze built to require stitching; standard locomotion, maze, hand-manipulation, and kitchen suites against up to seven baselines; an ablation of the optimism dial; and a fine-tuning study in which offline training is followed by live interaction.

7. **What are the results?** On locomotion, IQL roughly ties the best prior method (692.4 vs. 698.5); on the maze tasks that demand stitching it dominates (378.0 vs. 303.6 total; 39.6 and 47.5 on the largest mazes, where the strongest competitor manages about 15). Training takes about 20 minutes. After live fine-tuning it improves further (370 to 474 on mazes) where CQL collapses on some tasks. It still loses individual tasks, notably to filtered imitation on one locomotion dataset.

8. **What are the impacts and limitations of the contributions?** IQL showed in-sample learning need not give up long-horizon planning, and because its value learning never depends on the policy, the extraction step can be swapped or continued online. Limitations: its two knobs are set per domain; the tables report means without spreads; continuous states usually carry only one recorded action, so the "best in-data value" relies on the network generalizing across similar states; and its fixed weighting amplifies trustworthy and noisy advantages identically.

9. **How were the results evaluated or validated?** Standard benchmark averages (ten seeds on locomotion, 100 episodes on mazes), a corrected all-one-version comparison, and one ablation. Weaknesses: baseline numbers from mixed sources (one competitor's maze scores could not be reproduced and were copied), no reported spreads, no stated procedure for choosing per-domain settings, and only the optimism dial ablated.

10. **What are the ethical implications? How are they addressed?** No ethics discussion. Because the policy is built by reweighting recorded behavior, biases in the log are inherited and can be amplified whenever they scored well; the deliberate optimism of the upper expectile is risky in safety-critical use; and the fine-tuning recipe involves live exploration that would carry physical risk on hardware. Low compute cost is a modest positive.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: avoided by design, since training never queries unseen actions. *The conservatism–improvement trade-off*: a single dial, the expectile level, with the imitation weights, not the critic, holding the caution. *Theory vs. practice*: the proof concerns the fully optimistic limit of the dial, while in practice its two knobs are set per domain and the "best in-data value" relies on the network generalizing across similar states.

Connection to the offline RL problem space and BCA: IQL is one of BCA's four host algorithms: its imitation weight is exactly where calibrated per-sample widths plug in, tempering inflated advantages while keeping IQL's one global strength.

Paper 4: Revisiting the Minimalist Approach to Offline Reinforcement Learning (ReBRAC)

ReBRAC shows that giving the simple TD3+BC baseline the same quiet engineering upgrades newer methods enjoyed, including deeper networks, normalization, and separate penalties, is enough to match or beat far more complex algorithms.

1. **What is the citation?** Tarasov, D., Kurenkov, V., Nikulin, A., & Kolesnikov, S. (2023). Revisiting the minimalist approach to offline reinforcement learning. *Advances in Neural Information Processing Systems, 36*, 11592–11620. Version reviewed: arXiv:2305.09836v2. `https://doi.org/10.48550/arXiv.2305.09836`

2. **What is the research area?** Offline RL, in the behavior-regularization lineage (BRAC, TD3+BC). Deliberately not a new principle: it is a systematic study of which "incidental" design choices bundled with new algorithms actually improve an established baseline.

3. **What is the research question?** How far can a minimalist baseline be improved purely by adopting the small design choices that recent methods shipped quietly alongside their headline ideas (deeper networks, layer normalization, bigger batches, separate penalty weights for actor and critic, and a longer planning horizon), and which of those choices account for the gain?

4. **What is the significance of the question?** If gains credited to new algorithms actually come from quiet engineering, the field mis-attributes progress and practitioners cannot tell what is worth adopting. Establishing how strong a cheap baseline can become resets the bar for everyone and gives practitioners a fast default. The elaborate alternatives were expensive (one needed as many as 500 critic networks).

5. **What are the contributions reported in this paper?** An audit cataloging the hidden engineering inside seven recent methods; ReBRAC itself (TD3+BC plus five upgrades, including separate "stay near the data" penalties on the actor and on the critic); a broad 51-dataset evaluation spanning state-based and image-based benchmarks plus an offline-to-online study; careful ablations identifying what carries the gains; and a full reproducibility package (code, per-dataset settings, compute tables).

6. **What is the research method?** Design by composition, then large-scale benchmarking and ablation; no new theory. Settings are tuned on four random seeds, and the chosen configuration is then re-evaluated on ten fresh seeds using final-checkpoint reporting, a fairer protocol than reporting lucky peaks. Diagnostic runs remove or add one upgrade at a time.

7. **What are the results?** ReBRAC is the best ensemble-free method on average on mazes (76.8) and hand-manipulation tasks (58.6), a close second on locomotion (81.2 vs. SAC-RND's 82.6), and fine-tunes online from 55.0 to 91.1 with the lowest regret of the methods tested. The ablations are the real finding: remove the actor's stay-near-the-data penalty and the method collapses (72.2 to 11.4); remove critic layer normalization and the score halves; the critic-side penalty adds almost nothing. No single upgrade alone rescues plain TD3+BC.

8. **What are the impacts and limitations of the contributions?** ReBRAC reset the field's baseline and gave practical guidance: the actor penalty and critic normalization are essential, and the planning horizon matters when rewards are sparse. Limitations: its two penalty weights are still re-tuned per dataset by trying policies live (best values span two orders of magnitude); most tasks recorded by humans remain unsolved; there is no theory; everything is simulated; and constraint strength never varies *within* a dataset.

9. **How were the results evaluated or validated?** More rigorously than usual: tuning seeds separated from reporting seeds, final-checkpoint reporting, modern aggregate statistics, and a control showing the gains come from the design choices rather than implementation differences. Still, model selection uses real environment returns, which a true offline user lacks, and copied baselines come from weaker protocols.

10. **What are the ethical implications? How are they addressed?** Not discussed beyond scientific scope. Implicitly: staying near logged behavior inherits its biases and unsafe habits; tuning by live trial runs contradicts the offline premise in risky domains; and performance dipped on one task during live fine-tuning, which outside simulation would mean worse behavior in operation. Compute (roughly 18,500 GPU-hours) is disclosed but not discussed.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: the safeguard against unsupported actions is the actor's stay-near-the-data penalty: remove it and the method collapses (72.2 to 11.4). *The conservatism–improvement trade-off*: the penalty weights are still re-tuned per dataset by live evaluation, and constraint strength never varies within a dataset. *Theory vs. practice*: incidental choices explain much "algorithmic" advance, and baselines are re-tuned under the same protocol.

Connection to the offline RL problem space and BCA: ReBRAC's ablations identify the actor's stay-near-the-data term as the lever that matters, but its strength remains a single scalar re-tuned per dataset by live evaluation. BCA's calibrated per-sample weighting is the natural next step: same lever, dosed per sample on top of the host's tuned scalar.

Paper 5: Importance Weighted Actor-Critic for Optimal Conservative Offline Reinforcement Learning (A-Crab)

A-Crab proves that a small change in how the critic's errors are penalized, by weighting each sample's error instead of squaring it, turns a slow-but-practical method into one with the best possible statistical guarantee.

1. **What is the citation?** Zhu, H., Rashidinejad, P., & Jiao, J. (2023). Importance weighted actor-critic for optimal conservative offline reinforcement learning. *Advances in Neural Information Processing Systems, 36*, 49579–49602. Version reviewed: arXiv:2301.12714v2. `https://doi.org/10.48550/arXiv.2301.12714`

2. **What is the research area?** Theoretical offline RL with general function approximation, meaning its guarantees are not tied to tiny toy problems. The work connects two lines: adversarial actor-critic methods (ATAC), in which the critic plays devil's advocate against the policy, and importance weighting, which corrects for how rarely parts of behavior appear in the data.

3. **What is the research question?** Can one practical algorithm achieve the statistically optimal learning speed (error shrinking like $1/\sqrt{N}$ as the data grow) under a weak, averaged assumption about how well the data cover alternative behaviors, where prior practical methods were provably slower or needed unrealistically strong coverage?

4. **What is the significance of the question?** A guarantee is only as useful as its assumptions. Real logs (medical records, robot traces) never cover every possible policy, and worst-case coverage assumptions collapse when a single rarely logged action makes a likelihood ratio

enormous. A practical method with the optimal rate under weak, averaged coverage would narrow the gap between offline RL theory and practice.

5. **What are the contributions reported in this paper?** The novel step is replacing the squared Bellman-error penalty (a Bellman error is how much the critic's predictions disagree with their own one-step lookahead) with the largest *importance-weighted average* error, where the weights emphasize the samples that matter for the policies being compared. Around this: an optimal-rate proof that drops the strong "completeness" closure assumption predecessors needed; a weaker coverage measure; a guarantee of improvement over the logging policy across a wide range of penalty weights; a proof that the old squared penalty fails to reach the optimal rate on some problems; and a practical variant with public code.

6. **What is the research method?** Mathematics first: a game in which the actor tries to beat the logged behavior while the critic minimizes that improvement plus the weighted error penalty, analyzed with finite-sample concentration tools. A tractable approximation then restricts the weights to a boxed range, yielding a closed-form penalty, and is benchmarked against ATAC on twelve simulated locomotion datasets.

7. **What are the results?** In theory, A-Crab attains the optimal $1/\sqrt{N}$ rate against any comparator policy the data cover, improving on its predecessors' slower rates ($1/N^{1/3}$ and $1/N^{1/6}$), and improvement over the logging policy is guaranteed across a wide range of penalty settings. In practice it usually trains more stably than ATAC and scores better on several datasets (e.g., about 110 vs. a noisy 90–100 on one locomotion task), though results appear only as training curves.

8. **What are the impacts and limitations of the contributions?** The conceptual impact matters most: the *form* of the error penalty (linear and sample-weighted rather than squared) is what separates a tractable-but-slow method from an optimal one. Limitations: the assumptions (finite action sets, idealized actor updates, well-behaved weights) are far from deep-learning practice; the benchmarked algorithm departs from the analyzed one; and the elegant per-sample weighting collapses in practice to a single hand-searched constant per dataset.

9. **How were the results evaluated or validated?** The theorems receive full appendix proofs built from standard statistical tools. The empirical side is thin: training curves only, a single baseline, no final-score table, no statistical tests, no ablation isolating the new penalty, and no numerical check of the theoretical rate improvement.

10. **What are the ethical implications? How are they addressed?** No ethics discussion. Optimal-rate language could create false confidence for clinical or robotic use: the guarantees rest on assumptions that cannot be verified from logged data, concern average return rather than per-state safety, and do not cover the version actually benchmarked. Because the method competes only with behaviors the data cover, logging bias passes straight through. Public code is the one clear positive.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: real logs never cover every policy, so guarantees are sought under partial coverage, with optimal rates against covered behaviors only. *The conservatism–improvement trade-off*: weighting each sample's error, instead of squaring it, gives the optimal rate, with improvement over the logging policy guaranteed across a wide range of penalty weights. *Theory vs. practice*: the tested algorithm is not the analyzed one, and the per-sample weighting collapses in practice to one hand-searched constant per dataset.

Connection to the offline RL problem space and BCA: A-Crab's per-sample reweighting of prediction errors is the theoretical cousin of BCA's calibrated widths: the paper proves such weighting attains the optimal statistical rate, and its practical collapse to one global constant marks exactly the gap BCA aims to fill.

Paper 6: A Clean Slate for Offline RL (Unifloral)

Rather than leading with yet another algorithm, this paper rebuilds twelve existing ones in one shared, fast codebase and grades them by a new yardstick: how well each scores for a given amount of live testing spent on tuning, a cost earlier papers rarely stated.

1. **What is the citation?** Jackson, M. T., Berdica, U., Liesen, J., Whiteson, S., & Foerster, J. N. (2025). A clean slate for offline reinforcement learning. *Advances in Neural Information Processing Systems, 38*. Version reviewed: arXiv:2504.11453v1. `https://doi.org/10.48550/arXiv.2504.11453`

2. **What is the research area?** Offline RL methodology, evaluation, and software rather than a new learning rule. Its problem family is hyperparameter and policy selection under limited online access, together with fair benchmarking. This places it beside earlier unification and reimplementation efforts (Rainbow, CORL) rather than beside algorithm papers.

3. **What is the research question?** How should offline RL methods be defined, implemented, and compared so that reported scores honestly reflect the live interaction spent tuning them, and can one cleanly implemented design space, containing prior algorithms as settings, be used to discover better ones?

4. **What is the significance of the question?** Offline RL's selling point, learning without touching the real world, is undermined if published scores quietly depend on hundreds of live test episodes used to pick settings. Numbers from different papers then mix algorithmic quality with tuning effort, and nobody can tell which is which; by 2025 the field had many competing methods, copied baselines, and incomparable codebases.

5. **What are the contributions reported in this paper?** Four. A taxonomy of four offline RL settings, distinguished by when live testing is allowed, plus a definition of "a method" as an algorithm together with one fixed range of settings used on every dataset. An evaluation protocol in which a bandit (a strategy for choosing which trained policy to test next) simulates tuning, so performance is plotted against the live-testing budget. A family tree of prior methods with compact, fast reimplementations of twelve of them, and Unifloral, one configurable implementation covering most of the tree (it omits CQL). Finally, two genuinely new algorithms (TD3-AWR and MoBRAC) created purely by mixing settings, with no new code. All code is public.

6. **What is the research method?** Conceptual analysis, protocol and framework construction, then benchmarking; no new theory. For each algorithm–dataset pair, 20 policies are trained with settings sampled from the original papers' ranges and their episode returns stored; 500 simulated tuning sessions then select among them under a stated budget, making the cost of selection visible. The study uses nine datasets, with timing runs on one GPU.

7. **What are the results?** No prior method dominates: ReBRAC leads on five of nine datasets at some budget, IQL on four, and model-based methods never rise above sixth outside locomotion.

The reimplementations are tiny (59 changed lines turn TD3+BC into ReBRAC) and dramatically faster (CQL trains in about 10 minutes vs. over three hours in a popular library). TD3-AWR beats each of its parent methods on most datasets (ReBRAC on six of nine, IQL on seven). And with only a few noisy test episodes, selection can be fooled by erratic "distractor" policies.

8. **What are the impacts and limitations of the contributions?** The field gains a shared yardstick and toolkit: hidden tuning becomes an explicit, plotted cost, and component-level ideas can be tested by changing settings rather than writing new code. Limitations: only the pre-deployment setting is implemented; rankings depend on the original papers' tuning ranges; everything uses one benchmark suite; some fixed configuration choices degrade certain algorithms relative to their originals; and the two headline average speedups are not recoverable from the reported data.

9. **How were the results evaluated or validated?** By stored-episode tuning simulations with confidence intervals, a reproduction table checking the reimplementations against published scores, timing runs, and a distractor-policy analysis over 100,000 orderings. Gaps: no formal statistical tests; the intervals reflect selection randomness over one pool of trained policies rather than retraining; some protocol details go unreported; and no check confirms the unified implementation matches each standalone file.

10. **What are the ethical implications? How are they addressed?** There is no dedicated ethics section, but the paper is itself a research-integrity intervention: undisclosed live tuning inflates deployability claims, and pricing that budget makes the inflation visible. Unaddressed: selecting policies by average return ignores worst-case outcomes in the safety-critical domains the paper cites; distractor policies are exactly what a careless real selection process would deploy; and every benchmark is simulated. The efficiency gains widen access for smaller labs.

11. **What themes are suggested by this research? (minimum 3)** *The conservatism–improvement trade-off*: much of what separates published methods is settings, not principles, and the strongest methods still tie the policy to the data. *Uncertainty quantification and calibration*: policy selection is itself uncertain: with only a few noisy test episodes it can be fooled by erratic "distractor" policies, and results are reported with confidence intervals over simulated tuning sessions. *Theory vs. practice*: offline RL's promise of learning without live interaction is undermined by scores that depend on live tuning; here tuning is priced in episodes, in one codebase, with budget curves instead of headline numbers.

Connection to the offline RL problem space and BCA: Unifloral is the baseline reference bundled with BCA's code, and its budget-aware protocol is the right measuring stick: if calibrated per-sample caution reduces the search over global knobs, the payoff appears as better scores at small live-testing budgets.

Paper 7: Quantile Q-Learning: Revisiting Offline Extreme Q-Learning with Quantile Regression (QQL)

QQL replaces the most painful hand-tuned knob in a recent offline algorithm, a single "optimism temperature" per dataset, with a per-state scale learned from the data itself.

1. **What is the citation?** Gao, X., Li, S., Cai, Y., & Yu, W. (2026). Quantile Q-learning: Revisiting offline extreme Q-learning with quantile regression. *Transactions on Machine Learning*

Research. Version reviewed: arXiv:2511.11973v2. `https://doi.org/10.48550/arXiv.2511.11973`

2. **What is the research area?** Offline RL, downstream of the in-sample family (IQL, XQL) in which values are learned only on recorded actions and the policy is extracted by weighted imitation. Its specific problem is temperature selection, or how optimistic the value estimates should be. It addresses this by borrowing quantile regression (learning specific percentiles rather than averages) from distributional RL.

3. **What is the research question?** Can an XQL-style algorithm stay stable and competitive across many domains with one fixed configuration, if its temperature is estimated from the data as a per-state quantity instead of being tuned per dataset?

4. **What is the significance of the question?** Per-dataset tuning normally means trying candidate policies live, requiring the interaction offline RL exists to avoid. XQL's temperature is the worst offender, with reproduced values spanning 0.5 to 10 across datasets. Because the temperature feeds both value learning and the policy's imitation weights, a bad choice destabilizes both at once. Making it a learnable per-state scale would remove the most sensitive knob.

5. **What are the contributions reported in this paper?** A neat theoretical move: under a plausible noise model, the temperature equals a constant times the gap between two specific percentiles of the action-value distribution, so it can be learned by ordinary quantile regression instead of hand-tuning. Then QQL itself: two percentile value networks, a bias-corrected value target, and a policy update whose optimism automatically varies by state; a cautious generalization term for unseen actions; and a broad study (19 datasets from D4RL and NeoRL2, ablations, and checks of the noise model).

6. **What is the research method?** Derivation under stated assumptions, then algorithm design and benchmarking. All settings are fixed everywhere (no per-dataset tuning) while baselines are allowed their tuned values; further studies sweep the two remaining knobs, test the noise model on synthetic data, and fit distributions to real prediction errors.

7. **What are the results?** With one fixed configuration, QQL posts the best average on 10 of 17 standard datasets, and when XQL is forced to share one temperature too, QQL wins clearly (locomotion 85.6 vs. 73.6; mazes 84.9 vs. 67.3), with smoother training curves than its nearest relative. It is weak on both Hammer manipulation datasets and, notably, on the one safety-constrained task, where it scores below the dataset's own average. Compute is modest (about four hours per run, 1.6× its parent).

8. **What are the impacts and limitations of the contributions?** QQL is evidence that XQL's most sensitive hyperparameter can be estimated from data, per state; the percentile-gap scale is a reusable idea. Limitations: the assumed noise model fits real errors only loosely (real errors are heavier-tailed); the two learned percentiles can cross, patched by hand; the learned scale carries no coverage guarantee; some ablation claims overstate the figures; one relevant baseline is missing; and no code link is given.

9. **How were the results evaluated or validated?** By five-run averages (three-run on NeoRL2), ablations of both new components, knob sweeps, a synthetic test, and an error-distribution analysis. Weaknesses: no confidence intervals or statistical tests; baselines from mixed sources; an unjustified choice of shared temperature for the head-to-head comparison; a synthetic test that injects exactly the noise it then detects; and a few internally conflicting numbers.

10. **What are the ethical implications? How are they addressed?** None discussed. The claim that fixed settings make the method practical for consequential use rests entirely on simulation, and the only safety-focused task is where it fails, with no reporting of constraint violations. A misestimated scale in sparsely covered states can mean *less* caution exactly where mistakes cost most; logging bias is inherited. The fixed-configuration design does reduce risky live trial runs, which is the paper's implicit safety virtue.

11. **What themes are suggested by this research? (minimum 3)** *The conservatism–improvement trade-off*: optimism is set per state instead of by one temperature, with wider value spread across recorded actions triggering stronger caution. *Uncertainty quantification and calibration*: the learned scale is a modeled quantity with no coverage guarantee. *Theory vs. practice*: hyperparameter sensitivity is relocated, not removed: tuning moves from a global knob into a learned quantity with insensitive controls, under a noise model that fits real errors only loosely.

Connection to the offline RL problem space and BCA: QQL is BCA's closest non-conformal precedent, using a per-state scale that acts on the same imitation weight that BCA modifies. However, its scale is learned under a parametric noise model with no guarantee; BCA's conformally calibrated width is the direct answer (though its coverage concerns held-out residuals, not the policy), and QQL's own heavy-tailed errors argue for it.

Paper 8: UNIQ: Conformal Calibration for Adaptive Conservatism in Offline Reinforcement Learning (UNIQ)

UNIQ gives a standard offline learner (IQL) a per-state caution dial driven by calibrated ensemble disagreement, with more caution where data are sparse and less where they are dense. It does so at a fraction of the memory cost of large-ensemble methods.

1. **What is the citation?** Upadhyay, A. (2026, July 11). *UNIQ: Conformal calibration for adaptive conservatism in offline reinforcement learning* [Poster presentation]. ICML 2026 Workshop on Decision-Making from Offline Datasets to Online Adaptation: Black-Box Optimization to Reinforcement Learning, Seoul, South Korea. Version reviewed: arXiv:2606.07592v1. `https://doi.org/10.48550/arXiv.2606.07592`

2. **What is the research area?** Offline RL, built on IQL. The problem family is pessimism under distribution shift: deciding how much to distrust value estimates in poorly covered situations. Unlike global-knob methods (CQL, IQL, TD3+BC), huge-ensemble methods (SAC-N, EDAC; Paper 17), or learned-model penalties (MOPO), UNIQ pairs a small ensemble of value heads with conformal calibration, a statistics recipe that turns held-out prediction errors into a unit-free uncertainty scale.

3. **What is the research question?** Can IQL's single global optimism setting be replaced by a per-state setting driven by conformally normalized ensemble disagreement, with tighter caution where data are sparse and looser caution where data are dense, without the memory cost of large ensembles?

4. **What is the significance of the question?** The best setting of every mainstream caution knob changes per dataset and is normally found by trying policies live, an option unavailable offline. Raw ensemble disagreement, the usual uncertainty signal, has no common scale across

tasks, so fixed penalties transfer poorly. A calibrated, lightweight, per-state rule would cut both live tuning and hardware demands at once.

5. **What are the contributions reported in this paper?** A three-part mechanism: a small ensemble of value heads trained at three optimism levels, whose spread estimates uncertainty; a conformal step that measures prediction errors on held-out data and converts raw spread into a unit-free ratio; and a controller mapping that ratio to a state-specific optimism setting, with a matching penalty in the value targets. Supporting contributions: a formal appendix (the coverage property, controller behavior, IQL as a special case), a candid benchmark comparison that keeps the losing rows, a memory analysis, and ablations.

6. **What is the research method?** Algorithm design with light formal analysis and benchmarking. UNIQ uses three heads per optimism level; every 5,000 training steps, held-out transitions recalibrate the error scale; the normalized uncertainty drives the per-state setting between 0.5 and 0.90/0.95. Two hand-set configurations cover nine simulated locomotion datasets over three seeds, with baselines copied from a 2023 benchmark report rather than rerun.

7. **What are the results?** UNIQ averages 85.2 across the nine tasks versus IQL's 81.6, beating IQL on every task (by up to 8.1 points) and ranking third overall behind two much heavier or more heavily tuned methods. Its measured memory use is 250 MB against an estimated 2.5 GB for the ensemble leader. The ablations temper the story: a hand-set penalty coefficient matters more than either calibration or adaptivity, and a single head per level (so no uncertainty signal) nearly matches the full method (59.1 vs. 59.4).

8. **What are the impacts and limitations of the contributions?** UNIQ is a proof of concept that conformal calibration can be added cheaply to a standard learner, with unusually honest reporting of losses. Limits: the conformal guarantee covers a task-wide error scale, not individual states; it holds only at each recalibration of a moving ensemble; the gains are partly confounded with per-task penalty settings; the evidence is locomotion-only; and several numbers conflict across tables, text, and appendix.

9. **How were the results evaluated or validated?** By benchmark scores over three seeds against eight baselines copied (not rerun) from a prior report, single-seed ablations with inconsistent labeling, and analytic rather than measured speed and baseline memory estimates. Realized coverage and the distribution of the uncertainty signal are never reported, so the headline 3.6-point gain over IQL is plausible but weakly established, and the IQL comparison is not matched.

10. **What are the ethical implications? How are they addressed?** No dedicated treatment; a frank scope section substitutes. The language of distribution-free finite-sample guarantees could imply a safety assurance the method does not provide: the coverage concerns prediction errors on logged data, not the states the learned policy will visit, and the controller grows *more* optimistic wherever ensemble heads agree, which is dangerous if they share the same error. Data bias is inherited; validation is simulated; no code release is mentioned; the small memory footprint widens access.

11. **What themes are suggested by this research? (minimum 3)** *The conservatism–improvement trade-off*: one global setting is too careful in dense regions, too lax in sparse ones. *Uncertainty quantification and calibration*: raw disagreement needs a common scale. *Theory vs. practice*: conformal coverage on residuals does not transfer to the derived signal or to visited states.

Connection to the offline RL problem space and BCA: UNIQ is BCA's closest prior work: both bring conformal ideas to prediction-error-driven caution. UNIQ calibrates the errors but then normalizes ensemble *spread* with that quantile, so the guarantee never reaches its uncertainty signal; BCA calibrates the errors against a fitted scale model with a WBCP threshold, so width and signal describe the same quantity, with the calibration frozen between periodic refreshes and portable across four host algorithms.

Paper 9: Bayesian Flow Networks for Offline Trajectory Planning (BFN-RL)

BFN-RL swaps the diffusion model inside a trajectory planner for a Bayesian Flow Network, so that one kind of generator can plan over both grid-world (discrete) and robot-control (continuous) states.

1. **What is the citation?** Killingberg, L., & Langseth, H. (2026). *Bayesian flow networks for offline trajectory planning* (arXiv:2608.25163v1) [Preprint]. arXiv. `https://doi.org/10.48550/arXiv.2608.25163`

2. **What is the research area?** Offline RL treated as sequence generation rather than value learning. In the line of Diffuser and the Decision Diffuser, the planner generates a whole future state trajectory conditioned on a desired return or goal, then recovers actions with a learned inverse-dynamics model (a network that infers which action leads from one state to the next). It has no critic, so the inflated-value problem that drives the earlier papers does not arise in the same form.

3. **What is the research question?** Can a Bayesian Flow Network (BFN) serve as a single generator for offline trajectory planning that handles discrete and continuous states natively while staying competitive with diffusion-based planners in each setting?

4. **What is the significance of the question?** Many planning problems are discrete (grid navigation, key-and-door puzzles, box pushing) or mix discrete and continuous variables, yet diffusion planners are built for continuous vectors and need a separate categorical formulation for discrete states. One generator that covers both would simplify planner design, and a matched comparison shows whether the choice of generator deserves attention at all.

5. **What are the contributions reported in this paper?** Three. First, BFN-RL itself: a planner whose generator refines the parameters of a distribution over a state trajectory instead of denoising a noisy trajectory, so the same machinery applies to discrete and continuous spaces. Second, a discrete planner that pairs a categorical BFN with a learned inverse-dynamics model, made workable by an inpainting rule that pins known states during sampling. Third, a cross-domain study: five discrete tasks against a categorical-diffusion baseline matched in everything except the generator, plus D4RL locomotion. The paper claims no theory and mentions no code release.

6. **What is the research method?** An engineering study: design a planner and benchmark it, with no theoretical analysis. The discrete testbed is three MiniGrid tasks, slippery FrozenLake, and two-box Sokoban, where the BFN and diffusion generators share data, network, conditioning, and seeds. For continuous control, a Gaussian BFN is scored on nine D4RL locomotion datasets against eight published baselines. Every experiment uses three seeds.

7. **What are the results?** In the matched discrete comparison neither generator dominates: four of the five tasks are close (e.g., 86.7% vs. 85.5% success on FrozenLake), and BFN-RL wins

clearly only on Sokoban (68.7% vs. 59.0%). On D4RL it averages 77.0, behind the Decision Diffuser (81.8), level with IQL (77), and just below CQL (77.6). It posts the best score in the table on halfcheetah-medium-expert (97.2) but falls below plain behavior cloning (pure imitation of the data) on walker2d-medium (66.9 vs. 75.3).

8. **What are the impacts and limitations of the contributions?** The paper is a proof of concept that BFNs can drive offline planners, with a reusable inpainting rule and a matched-baseline protocol that isolates the generator's effect. Limitations: by the authors' own account BFN-RL does not beat diffusion across the board; no component is ablated; per-task settings such as temperature and step counts are set by hand without explanation; the discrete datasets contain only successful trajectories; and in continuous control it trails the Decision Diffuser by 4.8 points on average.

9. **How were the results evaluated or validated?** On the discrete tasks, by a matched protocol with three training seeds and 100 evaluation episodes per seed (200 on FrozenLake), reporting means and standard deviations. On continuous control, by D4RL normalized scores over three seeds, with every baseline number copied from the Decision Diffuser paper. The matched design is the strongest part; confidence is limited by the three seeds, the lack of significance tests and ablations, and an undescribed hyperparameter selection.

10. **What are the ethical implications? How are they addressed?** The paper has no ethics statement or limitations section. Its introduction motivates offline learning with self-driving cars and clinical treatment, where exploration is dangerous. Yet a generative planner can propose state sequences the system cannot actually reach, and conditioning on returns outside the data may push generation into unfamiliar regions with no uncertainty signal. Everything is simulated. Frequent replanning could act as a safeguard, but the paper presents it only as a planning detail.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: with no critic, the inflated-value problem does not arise in the same form; the planner samples whole trajectories instead of learning values. *The conservatism–improvement trade-off*: the planner seeks improvement by conditioning its generator on a desired return or goal, yet on walker2d-medium it falls below plain behavior cloning (66.9 vs. 75.3). *Theory vs. practice*: a matched baseline isolates the generator, while copied baselines and three seeds weaken the continuous comparison, and per-task settings are hand-set and never ablated.

Connection to the offline RL problem space and BCA: BFN-RL represents the critic-free branch of the problem space. With no critic there are no Bellman residuals (the Bellman errors of Paper 5), so BCA's calibration cannot attach directly; the nearest analogue is its hand-set sampling temperature, which arguably plays the role of a global caution knob.

Paper 10: Conformal Prediction Beyond the Horizon: Distribution-Free Inference for Policy Evaluation (Conformal Policy Evaluation)

This paper adds a conformal calibration layer to a distributional RL model, so that a policy's long-run return comes with a prediction interval checked against held-out data instead of being trusted to the model alone.

1. **What is the citation?** Gan, F., Lu, Y., Zhang, Y., & Liu, Y. (2025). Conformal prediction beyond the horizon: Distribution-free inference for policy evaluation. *Advances in Neural*

Information Processing Systems, 38. Version reviewed: arXiv:2510.26026v1. https://doi.org/10.48550/arXiv.2510.26026

2. **What is the research area?** Statistics applied to RL: conformal prediction (prediction intervals that need no assumption about the data's distribution) for policy evaluation in infinite-horizon discounted problems, both on-policy and off-policy (data collected by the evaluated policy or by a different one). It builds on distributional RL, which learns the whole distribution of returns rather than their average, and connects to offline RL through off-policy evaluation from logged data.

3. **What is the research question?** How can prediction intervals for a target policy's infinite-horizon discounted return be built from finite logged trajectories so that they reach a chosen coverage level without depending on a correctly specified return model, in both on-policy and off-policy settings?

4. **What is the significance of the question?** An expected return hides the spread of outcomes: a policy can look good on average and still do badly from some states, which matters in treatment planning or robotics. Distributional RL estimates the full return distribution, but its quantiles inherit function-approximation bias and can undercover (miss the true return more often than claimed) without warning. Conformal prediction offers model-agnostic validity, but its exchangeability assumption (that the order of the data does not matter) fails for sequential data, and the infinite-horizon returns it needs as labels are never fully observed.

5. **What are the contributions reported in this paper?** Five. A pseudo-return label built from k observed discounted rewards plus a tail sampled from the learned return distribution. Replay-style subsampling of calibration transitions to weaken time dependence. Weighted resampling that corrects for shifts in the state distribution and, off-policy, in action choice. Asymptotic coverage bounds that separate weight-estimation error from model error. And a simulation study with public code.

6. **What is the research method?** Algorithm design, asymptotic analysis, and Monte Carlo simulation. Transitions are split into training and calibration sets; quantile temporal-difference learning (a kernel density estimate on Mountain Car) fits the return distribution; each calibration transition is scored by the gap between its pseudo-return and the predicted value; and intervals from repeated weighted resamples are merged by a voting rule. The testbeds are a two-state problem, a two-dimensional continuous problem, Mountain Car, and a 50-dimensional extension, at a 90% coverage target, against the uncorrected quantile intervals.

7. **What are the results?** In theory, coverage in the large-sample limit is at least the target minus a penalty: weight-estimation error plus a model-error term that shrinks geometrically in the rollout length k. In the two main simulations conformal coverage stays near the 90% target (medians of roughly 0.89–0.92) while the raw quantile intervals undercover (roughly 0.84–0.87), at the price of wider intervals in the continuous example. On Mountain Car, on-policy coverage is near 0.90 but off-policy coverage stays near 0.85. In the two-state problem coverage also swings with k, from 0.87 at $k = 1$ to 0.94 at $k = 8$.

8. **What are the impacts and limitations of the contributions?** The paper shows that a conformal layer can sit on top of an ordinary distributional RL estimator using standard transition data, and it traces leftover miscoverage to two identifiable sources. Limitations: the authors admit that choosing k is unresolved; the guarantees are asymptotic and hold on average over test states; the score used in the main experiments gives every state the same interval width;

a second tuning parameter was set using long simulated rollouts that are unavailable offline; and the experiments are small and synthetic, with the one standard task falling short off-policy.

9. **How were the results evaluated or validated?** By appendix proofs under Markov, stationarity, bounded-density, and overlap assumptions, and by simulation in environments where long rollouts reveal the true return, so coverage is measured directly (boxplots over 50–100 repetitions; baselines are raw quantile intervals and one earlier conformal method). The design isolates coverage cleanly but is narrow, and some claims outrun the figures: the text calls Mountain Car coverage close to the target while its off-policy medians sit near 0.85.

10. **What are the ethical implications? How are they addressed?** There is no ethics section, and in the NeurIPS checklist the authors answer no to the broader-impact and safeguards questions, although the motivation is clinical treatment and autonomous systems. An interval labeled 90% can create unwarranted confidence when its assumptions fail, and because coverage is only an average over states, a patient subgroup can be undercovered while the overall number looks fine. Public code and the goal of exposing uncertainty are positives, but these risks go undiscussed.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: weighted resampling corrects for shifts in the state distribution and, off-policy, in action choice, yet off-policy coverage on Mountain Car stays near 0.85 against a 0.90 target. *Uncertainty quantification and calibration*: raw distributional quantiles undercover until calibrated on held-out data. *Theory vs. practice*: coverage survives an imperfect model only approximately and asymptotically, and the two settings that control validity were assessed against ground-truth returns that logged data cannot provide.

Connection to the offline RL problem space and BCA: This is the evaluation-side counterpart of BCA: both calibrate bootstrapped quantities (targets that lean on the model's own predictions) on held-out transitions. Its theory is a warning for BCA, since with one-step targets coverage is certified only up to the model's own error. The constant-width intervals of its main experiments also contrast with BCA's fitted scale model, which lets the width vary per sample.

Paper 11: Bellman Calibration for V-Learning in Offline Reinforcement Learning (Bellman Calibration)

Bellman calibration checks whether a trained value function's numbers can be taken at face value and, if not, repairs them with a simple one-dimensional correction learned from logged transitions.

1. **What is the citation?** van der Laan, L., & Kallus, N. (2026). *Bellman calibration for V-learning in offline reinforcement learning* (arXiv:2512.23694v2) [Preprint]. arXiv. `https://doi.org/10.48550/arXiv.2512.23694`

2. **What is the research area?** Between statistics and RL: post-hoc calibration of a trained value function for a fixed target policy, which is the policy-evaluation side of offline RL rather than policy optimization. It carries classical calibration tools (histogram binning, isotonic regression) into the Bellman setting.

3. **What is the research question?** Can an already-trained value predictor be checked for systematic errors in its numerical scale, and repaired by learning a single scalar transformation

of its outputs from logged transitions, with finite-sample guarantees that need neither Bellman completeness nor a correctly specified value class?

4. **What is the significance of the question?** Value estimates feed real decisions, such as projected treatment outcomes or customer lifetime value, so a scale that runs too high or too low can distort comparisons between policies even when the ranking of states is sensible. The standard guarantees for fitted value learning rest on structural conditions that are hard to verify for neural critics, and there was little model-agnostic theory for diagnosing and repairing a value function's scale after training.

5. **What are the contributions reported in this paper?** Four. A definition of Bellman calibration: states that share a predicted value should, on average, have a one-step backup (reward plus discounted next prediction) equal to that prediction. A calibration-error measure, with a bound tying value error to calibration error plus what no rescaling can fix, and a doubly robust way to estimate it off-policy (valid if either of two helper models is right). Iterated Bellman Calibration, a post-hoc procedure in histogram, isotonic, and hybrid forms that works with any model. And finite-sample bounds that assume neither completeness nor a correctly specified value class.

6. **What is the research method?** Mainly theory and method, supported by simulations and a benchmark audit. The calibrator repeatedly regresses one-step backup targets on the original predictions, so every iterate stays a transformation of the initial value function. Simulated problems are built around specific failure modes (a mis-scaled reward, early stopping, a reward shift, a saturating reward) with 100 replications. A frozen neural critic on the Deep OPE benchmark's Hopper data is then calibrated across eleven target policies and 20 random splits.

7. **What are the results?** In theory, calibration error shrinks at one-dimensional statistical rates whose leading term does not grow with the horizon. In simulation the corrections cut value error where the scale was wrong (by about a fifth under early stopping, and by more in the mis-scaled-reward case). On Hopper, the recommended hybrid calibrator cuts calibration error to about 0.78 of its raw level for the better-trained of two critics, but the linear and isotonic versions make that critic worse, and the error of the final policy-value estimate barely moves (0.978 of its raw level).

8. **What are the impacts and limitations of the contributions?** The paper offers a cheap, model-agnostic audit-and-repair step for any critic, needing only scalar predictions and held-out transitions, and it explains when rescaling can help (good ranking, wrong scale) and when it cannot. Limitations: the authors stress that calibration is not accuracy; the fully iterated isotonic version lacks a value-error guarantee; the simulations use clipped importance weights rather than the doubly robust targets the theory centers on; and on the one standard benchmark the policy-value error barely improves.

9. **How were the results evaluated or validated?** By proofs in the appendix, by simulations scored against Monte Carlo ground truth over 100 replications, and by a Hopper audit with shared splits, held-out scoring, and bootstrap intervals. The protocol guards against leakage and reports cases where calibrators hurt. Weaknesses: the simulated failure modes are the ones the method is designed to fix; several settings go unreported; the mis-scaled-reward results differ without explanation between a figure and a table (0.42 vs. 0.73–0.75); and no external recalibration or evaluation method is compared.

10. **What are the ethical implications? How are they addressed?** None are discussed.

Because calibration conditions only on the predicted value, errors for one group can cancel against opposite errors elsewhere at the same prediction level, so a low calibration error could hide systematic harm to a subpopulation. A small calibration error might also be over-read as validation. The paper is frank about technical risks but silent on subgroup effects and deployment safeguards, and all evidence is simulated.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: calibration error for a target policy must be estimated from another policy's data, by a doubly robust estimator in theory and by clipped importance weights in the simulations. *Uncertainty quantification and calibration*: calibration carried over to long-horizon value predictions through a post-hoc, one-dimensional fix that leaves the critic untouched; it concerns the reliability of the mean rather than interval coverage. *Theory vs. practice*: the calibrators with value-error guarantees helped, while those without made the better-trained critic worse.

Connection to the offline RL problem space and BCA: Bellman calibration is a complement to BCA, not a competitor: BCA reads uncertainty from the size of Bellman residuals, while this paper corrects their systematic bias at each prediction level. Its calibration error is a natural companion diagnostic for BCA's host critics, though its guarantees cover a frozen critic and a fixed policy, not actor-critic training.

Paper 12: Weighted Bayesian Conformal Prediction (WBCP)

WBCP gives a conformal threshold its own error bar: alongside each prediction interval it reports how firmly the calibration data support that interval's width.

1. **What is the citation?** Lou, X., & Luo, P. (2026). *Weighted Bayesian conformal prediction* (arXiv:2604.06464v2) [Preprint]. arXiv. `https://doi.org/10.48550/arXiv.2604.06464`

2. **What is the research area?** Statistical machine learning rather than RL: conformal prediction, at the meeting point of weighted conformal methods, which reweight calibration scores under covariate shift (test inputs distributed differently from the calibration inputs), and Bayesian quadrature conformal prediction (BQ-CP, Paper 18), which places a posterior over the threshold. Its applications are spatial. The link to offline RL runs through BCA, which borrows its calibration step from this paper.

3. **What is the research question?** Can the posterior over the conformal threshold that BQ-CP provides for i.i.d. data be extended to weighted conformal prediction, so that one procedure stays valid under covariate shift or local weighting and also reports how reliable its own threshold is?

4. **What is the significance of the question?** A conformal threshold is a single number that says nothing about how firmly the calibration data pin it down: the same threshold could rest on two hundred relevant points or on five distant ones. That matters wherever interval width drives decisions and calibration data are unevenly spread. The two existing remedies did not combine, since BQ-CP gave a threshold posterior but needed exchangeable data, while weighted conformal prediction handled shift but returned only a point estimate.

5. **What are the contributions reported in this paper?** Four. WBCP itself, which replaces BQ-CP's flat Dirichlet model over the gaps between sorted calibration scores with a weighted one scaled by Kish's effective sample size (the number of equally weighted points the weighted sample is worth), and returns a conservative threshold together with a posterior spread. A set

of four theoretical results, given as proof sketches, on why the effective sample size is the right scaling and when BQ-CP's guarantees carry over. A spatial version with an adaptive bandwidth (AdaGeoBCP). And an empirical study on a synthetic field and 13 geospatial datasets.

6. **What is the research method?** Algorithm design and asymptotic proof sketches, then benchmarking with ablations. Each of many Monte Carlo draws samples from the weighted Dirichlet and reads off a threshold; a high quantile of those thresholds sets the interval, and their spread gives the reliability measure. Tests target 90% coverage on a synthetic random field and 13 real datasets (house prices, hydrology, county health indicators, and others) against standard, weighted, and Bayesian conformal baselines, with an ablation that removes each ingredient in turn.

7. **What are the results?** Across the 13 real datasets, the spatial version of WBCP reaches a mean coverage of 0.925, essentially tied with BQ-CP (0.928) and above standard conformal prediction (0.903), while the frequentist spatial baseline undercovers (0.824). Its distinguishing output is a reliability measure that varies by location, which BQ-CP cannot give. The costs are visible: the widest intervals on the Seattle house-price data (24.9 vs. 20.4 for BQ-CP), and coverage there that hinges on the chosen posterior level (0.873 at $\beta = 0.5$, 0.95 at $\beta = 0.9$).

8. **What are the impacts and limitations of the contributions?** WBCP turns a conformal threshold into a distribution under any weighting scheme, so each interval comes with a cheap measure of how well the data support it. Limitations, several stated by the authors: correlated residuals inflate the effective sample size; misspecified weights may void the coverage result; the theorems are sketches under an assumed model and need a large effective sample size, while the method ran with roughly 10–13 effective points on some data; and the random splits test no genuine covariate shift.

9. **How were the results evaluated or validated?** By a synthetic field with known noise, a sweep over spatial correlation lengths, 13 real datasets with 10 random splits each, a 50-split study on one dataset, an ablation, and a sweep of the posterior level. Metrics are coverage, interval width, and two reliability diagnostics (effective sample size and posterior spread). The breadth and the clean ablation are strengths. Weaknesses: no significance tests, a lenient rule for counting a dataset as meeting the target, no check of local coverage, and one figure whose values conflict with the matching table.

10. **What are the ethical implications? How are they addressed?** There is no ethics statement. The applications tested (house prices, disease prevalence, vote shares) can shape lending, health-resource allocation, or political targeting. Because sparsely sampled areas receive wider intervals, the reliability map could guide new data collection, or it could be used to justify withholding services from places that are already poorly measured. The outputs also look like rigorous certificates although they rest on an assumed model and correct weights. The authors soften their claims but do not discuss misuse or equity, and no code is linked.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: calibration scores are reweighted for test inputs that differ from the calibration inputs, though the random splits test no genuine covariate shift. *Uncertainty quantification and calibration*: each threshold reports how well the calibration data support it, and thresholds widen most where calibration support is thin. *Theory vs. practice*: relaxing exchangeability makes the conformal guarantees partly model-based.

Connection to the offline RL problem space and BCA: WBCP is the calibration procedure BCA runs,

although BCA's code follows the paper's later v3 revision rather than the v2 reviewed here. BCA uses it with uniform weights, which makes it essentially BQ-CP, so the calibrated width inherits an exchangeability assumption that policy-induced shift and correlated transitions can break. With uniform weights WBCP also yields one global threshold, so BCA's per-sample adaptivity comes from its fitted scale model, not from WBCP.

Paper 13: Off-Policy Deep Reinforcement Learning without Exploration (BCQ)

BCQ shows that standard deep RL algorithms can fail badly when they must learn from a fixed dataset, and repairs them by letting the policy choose only among actions that resemble the recorded ones.

1. **What is the citation?** Fujimoto, S., Meger, D., & Precup, D. (2019). Off-policy deep reinforcement learning without exploration. In *Proceedings of the 36th International Conference on Machine Learning* (Proceedings of Machine Learning Research, Vol. 97, pp. 2052–2062). PMLR. Version reviewed: arXiv:1812.02900v3. `https://doi.org/10.48550/arXiv.1812.02900`

2. **What is the research area?** Offline RL, which this paper calls batch RL (learning from a fixed dataset with no further interaction), for continuous control. BCQ is an early policy-constraint method: where CQL makes the critic pessimistic, BCQ restricts the policy to actions close to those in the data. It sits between imitation learning (copying the data) and off-policy value learning.

3. **What is the research question?** Why do off-policy deep RL algorithms such as DDPG and DQN, which in principle can learn from data gathered by any policy, fail when trained on a fixed dataset they did not collect themselves, and can restricting the policy to actions similar to the recorded ones make learning from such data work in continuous control?

4. **What is the significance of the question?** Learning from a fixed dataset is what RL needs wherever collecting data is costly, risky, or slow, or is best left to a human operator or a monitored program. Imitation learning works when the demonstrations are good but tends to fail on suboptimal ones. Off-policy algorithms seemed to fill that gap, but in practice they train on replay data closely tied to their own current policy, which hides how they behave on data they did not collect.

5. **What are the contributions reported in this paper?** Four. A diagnosis, *extrapolation error*: the critic assigns unrealistic values to state-action pairs the dataset lacks, and without new data these are never corrected. A theory for finite (tabular) problems: in a deterministic environment a policy confined to recorded state-action pairs can be evaluated without this error, and a constrained Q-learning (BCQL) converges to the best such policy. The BCQ algorithm, presented as the first deep continuous-control method that learns from arbitrary fixed data. And four fixed-data test settings (final buffer, concurrent, imitation, imperfect demonstrations) with public code.

6. **What is the research method?** Diagnostic experiments, tabular proofs, and benchmarking. BCQ fits a generative model (a conditional variational auto-encoder) to the recorded actions, samples 10 candidates per state, lets a perturbation network shift each by at most Φ, and picks the one the critic scores highest; training targets weight the lower of two critics' estimates by 0.75. Tests use three simulated locomotion tasks (HalfCheetah, Hopper, Walker2d) and four datasets from DDPG agents: a full replay buffer, a buffer shared with the collecting agent, expert

data, and noisy expert data. Baselines are DDPG, a discretized DQN, and two behavior-cloning (pure imitation) variants.

7. **What are the results?** DDPG trained on fixed data does markedly worse than the agent that collected it, even when both learn from the same replay buffer, and its value estimates are unstable or diverge; BCQ's stay stable. Read off the learning curves (no result tables are given), BCQ far exceeds the data's average return on noisy demonstrations (about 2,300 vs. 450 on Hopper, 6,100 vs. 2,550 on HalfCheetah) and on final-buffer data (8,300 vs. 6,000 on HalfCheetah). On clean expert data behavior cloning is best on two of three tasks, where BCQ ends slightly below the expert; on two toy tasks with random data, plain DDPG also learns.

8. **What are the impacts and limitations of the contributions?** The paper names the core failure of offline value learning and shows one algorithm, with one set of hyperparameters, both imitating expert data and improving on noisy data; the survey in Literature Review 1 cites it for the extrapolation-error observation and as a policy-constraint method. Limitations: the guarantees cover tabular, deterministic problems, not the deep algorithm; the authors report instability on one task under slightly different hyperparameters; on expert data, returns fall sharply as Φ grows, yet Φ is hand-set; Φ and n are the same in every state, whatever the data coverage; and the benchmark data all come from DDPG agents in simulation.

9. **How were the results evaluated or validated?** Five seeds; evaluations every 5,000 steps averaging 10 noise-free episodes; learning curves with half-standard-deviation bands, set against the dataset's average episode return. Value estimates are compared with Monte Carlo returns, and appendix studies vary Φ, try critic-ensemble uncertainty in place of the generative model, and use random-policy data on two toy tasks. Weaknesses: no result tables or significance tests; no earlier batch RL method among the baselines; the Φ used in the main runs is not stated in the text; and the appendix compares Φ settings by simulator returns, which a purely offline user would lack.

10. **What are the ethical implications? How are they addressed?** The paper contains no ethics or broader-impact discussion; the nearest remarks are that fixed-data learning suits settings where data collection is costly or risky, and a closing reference to systematic risks in Q-learning. Implications: a policy held close to logged behavior reproduces the biases and unsafe habits in the log; the guarantee of at least matching the behavior policy is proved only for tabular, deterministic problems, so the deep algorithm carries no safety assurance; and all evidence is simulated. Public code and candor about instability help, but deployment risks go undiscussed.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: values for actions the data do not contain can be badly wrong and cannot be corrected offline (the paper's extrapolation error). *The conservatism–improvement trade-off*: the policy is kept close to recorded actions by a generative model and a bounded perturbation, and Φ and n slide the method between pure imitation and unconstrained Q-learning. *Theory vs. practice*: the guarantees are proved for tabular, deterministic problems, not for the deep algorithm that is tested.

Connection to the offline RL problem space and BCA: BCQ introduces the "stay near the data" policy-constraint idea (batch-constrained RL, in its terms) that two of BCA's hosts, TD3+BC (same first author) and ReBRAC, carry on as a plain penalty. Its constraint (Φ, n) has one strength for every state; BCA keeps a host's global coefficient but modulates the regularization per sample with

a calibrated width. BCQ's appendix also finds that uncertainty from ensembles of 4 or 10 critics did not by itself keep the policy on expert data (one Hopper test), a caution for any method that leans on an uncertainty signal, BCA included.

Paper 14: Stabilizing Off-Policy Q-Learning via Bootstrapping Error Reduction (BEAR)

BEAR traces the failure of Q-learning on fixed datasets to value targets computed at actions the data do not contain, and counters it by keeping the policy within the actions the data support without forcing it to copy how often each was taken.

1. **What is the citation?** Kumar, A., Fu, J., Soh, M., Tucker, G., & Levine, S. (2019). Stabilizing off-policy Q-learning via bootstrapping error reduction. *Advances in Neural Information Processing Systems, 32*. Version reviewed: arXiv:1906.00949v2. `https://doi.org/10.48550/arXiv.1906.00949`

2. **What is the research area?** Offline RL for continuous control, which the paper calls off-policy RL from a static dataset. BEAR belongs to the policy-constraint family alongside BCQ (Paper 13): it restricts which actions the policy and the value targets may use, where CQL (Paper 1) instead lowers the critic's scores. Its distinguishing position is support matching (stay within the set of recorded actions), not distribution matching (also copy how often each was taken). The analysis draws on error-propagation theory from approximate dynamic programming.

3. **What is the research question?** Why do standard Q-learning and actor-critic methods become unstable on a fixed dataset, even a large or expert one, and can restricting the actions used in value updates to the data's support, instead of to the behavior policy's exact distribution, remove that instability while still letting the policy improve on the data?

4. **What is the significance of the question?** Logged data are plentiful in areas such as driving and recommendation, where fresh trial and error is costly, yet off-policy methods of the time could fail on a fixed dataset even when an expert collected it. The failure does not behave like ordinary overfitting: growing the dataset from a thousand to a million samples does not cure it. A closely related earlier fix, BCQ, stays so near the recorded behavior that it gains little over imitation on the mediocre data the authors consider the common practical case.

5. **What are the contributions reported in this paper?** Four. A diagnosis: "bootstrapping error," which enters when a value target is computed at an out-of-distribution (OOD) action, one the data do not cover, and then accumulates through repeated backups. An analysis of a backup restricted to a chosen set of policies, with a bound that splits the final error into a distribution-shift term and a suboptimality term. The BEAR algorithm, whose actor is kept approximately within the data's support by a limit on the maximum mean discrepancy (MMD, a distance between distributions computed from samples alone). And a comparison across random, medium-quality, and expert data, with ablations.

6. **What is the research method?** Theory, algorithm design, and benchmarking. The theory adapts known error-propagation bounds and is illustrated on a small gridworld. The actor maximizes the lowest of several critics' scores subject to an MMD limit ($\varepsilon = 0.05$), enforced by a self-adjusting penalty weight (a Lagrange multiplier). Experiments cover five MuJoCo tasks with one-million-transition datasets from a uniformly random policy, a partially trained SAC

policy, or a converged one (Humanoid: random and medium only). Baselines are naive off-policy RL (TD3), BCQ, KL-control, a static variant of DQfD, and behavior cloning.

7. **What are the results?** All numbers are approximate readings of learning curves. On medium-quality data BEAR ends ahead on Walker2d (about 1,800 vs. 800 for BCQ), Hopper, and Humanoid, narrowly ahead on HalfCheetah, and near 700 on Ant, just under the dataset's average return. There, a KL constraint in place of MMD collapses on Hopper and Walker2d and trails MMD even when heavily tuned. On random data BEAR beats the dataset average on all five tasks, yet naive RL scores higher on HalfCheetah (about 3,300 vs. 2,900) and Hopper. On expert data BEAR, BCQ, and behavior cloning are roughly level.

8. **What are the impacts and limitations of the contributions?** The paper names the instability, explains its mechanism, and separates matching the data's support from matching its distribution; CQL (Paper 1) later uses BEAR as a baseline. The authors admit that performance can still decay over long runs with no stopping rule, that action constraints can be too conservative, especially on mixed-policy data, and that support matching in high-dimensional action spaces still lacks a theoretically robust method. Beyond these, the bound assumes policies that truly stay in the support, which a sampled, state-averaged MMD only approximates, and one threshold serves all states however well each is covered.

9. **How were the results evaluated or validated?** By appendix proofs, a gridworld illustration, and learning curves averaged over five seeds, with 10 evaluation episodes every 1,000 gradient steps and shaded bands for spread. All methods share the same datasets, and BCQ and TD3 run from their authors' code. Weaknesses: no tables or significance tests; the claim to match or exceed the state of the art in all cases outruns the random-data figures, where naive RL averages higher on two tasks; ensemble size and other settings go unreported; and the first term of Theorem 4.1's bound is half what its proof derives.

10. **What are the ethical implications? How are they addressed?** The paper has no ethics or broader-impact discussion; the nearest content is its motivation (driving, recommendation, robotics) and a hope of training on static data before real-world deployment. A policy confined to the data's support inherits the biases of the logged behavior; the bound concerns value error, not safe behavior; and since performance can decay late in training with no offline stopping rule, a policy's quality cannot be confirmed without live trials. All evidence is simulated. The authors are candid about the decay, but bias, safeguards, and misuse go unaddressed.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: value targets at unseen actions cannot be corrected offline, and backups spread the error. *The conservatism–improvement trade-off*: a wider allowed policy set means more shift error but less suboptimality; BEAR holds the policy to the actions the data contain, not to how often each was taken. *Theory vs. practice*: the bound assumes policies that truly stay in the support, which a sampled, state-averaged MMD only approximates.

Connection to the offline RL problem space and BCA: BEAR formalizes the trade-off any caution mechanism, BCA's included, must strike: admit too many actions and errors from unsupported ones spread through backups; admit too few and the policy cannot improve. It settles this with one threshold ($\varepsilon = 0.05$) and one learned penalty weight, enforced on average over states, whereas BCA varies each host's regularization per sample by a calibrated width while keeping the host's global coefficient. BEAR is not one of BCA's four hosts.

Paper 15: Addressing Extrapolation Error in Deep Offline Reinforcement Learning (BRr)

BRr learns the value of the policy that recorded the data rather than of the best possible policy, so its training targets use only recorded actions; it makes its one improvement step at deployment, with a ranking penalty meant to keep unseen actions from looking attractive.

1. **What is the citation?** Gulcehre, C., Gómez Colmenarejo, S., Wang, Z., Sygnowski, J., Paine, T., Żołna, K., Chen, Y., Hoffman, M., Pascanu, R., & de Freitas, N. (2020). Addressing extrapolation error in deep offline reinforcement learning. In *Offline Reinforcement Learning Workshop at NeurIPS 2020*. Version reviewed: the workshop paper. `https://offline-rl-neurips.github.io/pdf/41.pdf` Also available at `https://openreview.net/forum?id=0CRKCul3eKN`; a later version appears as *Regularized behavior value estimation* (arXiv:2103.09575).

2. **What is the research area?** Offline RL for problems with a finite set of actions (Atari games, partially observable DeepMind Lab levels, small bsuite control tasks). Its target is extrapolation error (the term used in BCQ, Paper 13): the mistakes a neural critic makes when scoring state-action pairs the data barely cover. The remedy combines evaluating only the behavior policy (the policy that recorded the data), which resembles the in-sample idea of Paper 3, with pushing down the scores of unseen actions, which the paper groups with BCQ and CQL as behavior constraining.

3. **What is the research question?** Can offline value learning avoid runaway overestimation on poorly covered state-action pairs by estimating the value of the behavior policy instead of the optimal one and taking a single greedy improvement step only at deployment, and, with suitable regularization, does this match or beat existing offline methods as data coverage varies?

4. **What is the significance of the question?** Offline RL is aimed at settings such as healthcare and self-driving cars, where repeated interaction is costly or unsafe while logs are plentiful. But the max over actions in Q-learning includes actions the data lack; the critic's guesses for them are sometimes too high, bootstrapping (building targets from the critic's own predictions) spreads the error, and with no new data nothing corrects it. The paper adds that Double DQN, a standard fix for overestimation, targets a different cause and does not help here.

5. **What are the contributions reported in this paper?** Three techniques, plus datasets and analysis. Behavior value estimation (B): a SARSA-style update whose target uses the next action actually recorded, followed by a greedy policy at test time. A ranking regularizer (R): a hinge penalty asking the recorded action to outscore every other action, weighted toward high-return trajectories. A reparametrized critic (r): a bounded output times one learned scale, penalized when values exceed observed returns. The paper also provides new low-coverage bsuite and DeepMind Lab datasets (release promised) and a constructed divergence example; the later arXiv version names the approach R-BVE.

6. **What is the research method?** Algorithm design plus benchmarking, all simulated and discrete-action; the main formal result is a hand-built four-state example in which offline Q-learning diverges. Three testbeds: bsuite tasks with random actions injected at five noise levels and only 10% of the data kept; RL Unplugged Atari, tuned on one set of games and reported on another; and four partially observable DeepMind Lab levels, plus one level recorded at four noise levels. Baselines include DDQN, BCQ, REM, CQL, IQN, offline R2D2, and behavior cloning (BC, pure imitation). Ablations vary the backup (Q-learning or B), toggle each regularizer, and shrink the Atari data to 10% and 1%.

7. **What are the results?** On the held-out Atari games the top score belongs to QRr, Q-learning with both regularizers (median normalized score 108.2; IQN 104.8, CQL 98.9), which also edges BRr on the tuning games (113.4 vs. 110.7). Behavior value estimation pays off when coverage is thin: on 10% of the Atari tuning-game data B scores 58.6 against DDQN's 14.0, though DDQN leads on the full data (94.1 vs. 88.2). BRr leads at all five cartpole noise levels (933.8 vs. 383.7 for the best baseline at zero noise), and BR beats CQL and offline R2D2 on all four DeepMind Lab levels. BR loses to BC on data recorded with little or no noise (17.1 vs. 28.0 with none).

8. **What are the impacts and limitations of the contributions?** Impact: evidence that one greedy step on a behavior-policy critic can compete with dedicated offline methods when coverage is thin. Limitations: the authors concede that one step can be too conservative in data-rich settings; the headline Atari number comes from QRr, which reinstates the max operator, and no BRr score is given for the held-out games; and the featured variant changes by domain (QRr on Atari, BR on DeepMind Lab after preliminary live results). All tests use discrete actions. The greedy step still relies on scores of untested actions, guarded by a heuristic penalty with no guarantee. On the single-level noise datasets BR's return at each noise level (17.1–31.8) is below that dataset's average recorded return (29.7–40.4), so improvement over the behavior policy is not shown there.

9. **How were the results evaluated or validated?** Stated protocol: sweep 5–10 hyperparameter settings per method, train on five datasets from five behavior seeds, evaluate in the real environment, and report each method's best setting. Atari scores are medians with bootstrapped 25–75 percentile bars on games held out from tuning; DeepMind Lab results carry standard deviations. Weaknesses: best settings are picked by live evaluation (per level on DeepMind Lab); most Atari baselines are taken from the benchmark paper; there are no significance tests, and spreads sometimes overlap (BR 13.4 $\pm$ 11.8 vs. CQL 9.3 $\pm$ 2.5); and Figure 7 and Table 8 disagree (swapped level labels, and an untabulated BRr bar above the BR bar the caption calls best).

10. **What are the ethical implications? How are they addressed?** The paper has no ethics or broader-impact section; it only motivates offline RL with healthcare and self-driving cars, where live trial and error is costly, unsafe, or unethical. Implications: the deployed policy is greedy over scores that include actions the data never tested, with a heuristic penalty as the safeguard; the ranking term favors whatever was done in high-return episodes, so biases in those logs are reinforced; and settings were chosen by live evaluation, which the motivating domains do not allow. The paper treats test-time extrapolation as a technical problem but does not discuss bias or deployment safeguards; all evidence is simulated.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: avoided in training by design: the target bootstraps only from recorded actions, with improvement left to one greedy step at deployment. *The conservatism–improvement trade-off*: one step is the safer choice when coverage is thin but too cautious when data are rich, where regularized Q-learning wins. *Theory vs. practice*: the motivating domains rule out live trials, yet the best settings were picked by live evaluation, and the ranking of methods flips with coverage, noise, and data size.

Connection to the offline RL problem space and BCA: This workshop paper predates IQL (Paper 3, one of BCA's hosts) and shares its in-sample principle: the bootstrap target is built only from recorded actions, though the ranking penalty does score unseen actions in order to push them down. It differs by improving in a single step at deployment, the kind of one-step method Paper 3 contrasts IQL with. Its penalty has one global coefficient, weighted per sample only by trajectory return

(data quality, not critic uncertainty); BCA instead draws its per-sample signal from the size of Bellman residuals and keeps each host's global coefficient.

Paper 16: Uncertainty Weighted Actor-Critic for Offline Reinforcement Learning (UWAC)

UWAC estimates how uncertain the critic is about each training sample and gives uncertain samples less weight in the critic and actor losses, so that value guesses about situations the data do not cover stop destabilizing training.

1. **What is the citation?** Wu, Y., Zhai, S., Srivastava, N., Susskind, J., Zhang, J., Salakhutdinov, R., & Goh, H. (2021). Uncertainty weighted actor-critic for offline reinforcement learning. In *Proceedings of the 38th International Conference on Machine Learning* (Proceedings of Machine Learning Research, Vol. 139, pp. 11319–11328). PMLR. Version reviewed: arXiv:2105.08140v1. `https://doi.org/10.48550/arXiv.2105.08140`

2. **What is the research area?** Offline RL with actor-critic methods, in the uncertainty-based branch: methods that estimate how unreliable the critic is and act on that estimate. UWAC is model-free (it learns no model of the environment) and is built on BEAR (Paper 14), a policy-constraint method that keeps the policy's actions within the support of the data. Its uncertainty tool comes from Bayesian deep learning: Monte Carlo dropout, which leaves dropout's random masking switched on at prediction time and measures how much repeated predictions disagree.

3. **What is the research question?** Can a critic's own dropout-based uncertainty identify out-of-distribution (OOD) state-action pairs, meaning ones the dataset does not cover, and does down-weighting those pairs in the critic and actor losses stabilize offline training and raise returns without adding new loss terms or a learned environment model?

4. **What is the significance of the question?** When training bootstraps (builds value targets from the critic's own predictions) from an action or state the data do not cover, the value there can be arbitrary, and the error spreads to other states through the Bellman backup. The authors argue that the usual remedy, strong constraints or penalties that hold the policy to the data, avoids unseen actions even when the critic could score them accurately, so policies turn out pessimistic and suboptimal. They cite human-demonstration benchmarks where the best offline methods did no better than a random agent.

5. **What are the contributions reported in this paper?** The core idea is a reweighting of the two training losses: each critic update is scaled by the inverse of the estimated variance of its target value, and the actor's objective by the inverse variance of the critic's value for the proposed action, so uncertain samples count for less. Around this the paper provides a low-overhead variance estimate from Monte Carlo dropout, an appendix convergence argument, evidence that dropout variance flags OOD samples, and a diagnosis of why the BEAR baseline's values diverge. The reviewed version links the baseline's code but not UWAC's.

6. **What is the research method?** Algorithm design with a short convergence argument, then experiments. UWAC is BEAR with dropout in its critics: the variance across 100 stochastic forward passes of the target critics is the uncertainty, and each sample's weight is β times the inverse variance (clipped at 1.5). BEAR's settings are otherwise kept, with spectral normalization (a weight constraint the authors use to keep the critic's values bounded) added on Adroit. Tests

cover LunarLander data with a region of states deleted, fifteen D4RL locomotion datasets, twelve Adroit hand-manipulation datasets, and ablations, with five seeds on the benchmarks.

7. **What are the results?** Dropout uncertainty is higher in LunarLander's deleted regions and separates recorded from random actions on walker2d-expert with an AUC of 0.845 (0.5 is chance). On Adroit, UWAC has the best mean on 8 of 12 datasets and lifts BEAR on human demonstrations (pen-human 65.0 vs. -1.0), while BEAR's value targets climb to the order of 10^{12}. On locomotion it leads on 6 of 15 datasets, mostly medium-expert and expert (halfcheetah-medium-expert 127.4 vs. 64.7 for the runner-up). It trails model-based methods on medium-replay data (hopper 39.4 vs. MOReL's 93.6) and falls below BEAR on halfcheetah-random (14.5 vs. 25.1).

8. **What are the impacts and limitations of the contributions?** UWAC shows that per-sample uncertainty weighting can be added to an existing actor-critic cheaply (under 1.5 times BEAR's training time) and can stop value estimates from diverging on narrow data. Limitations: the dropout variance is never calibrated and is scaled by a swept β and a clip; the convergence argument, as the authors note, covers inverse standard deviation, not the clipped inverse variance actually used; only one host algorithm is benchmarked; several human and cloned scores stay near zero (relocate-human 0.5 ± 0.6); and UWAC's pen-human return itself decays from about 1,700 to about 700 during training.

9. **How were the results evaluated or validated?** By five-seed D4RL means and standard deviations beside ten baseline columns per table, training curves against BEAR, and Adroit ablations (spectral normalization alone, ensembles for dropout, standard deviation for variance, and dropout without weighting, which does sharply worse on most tasks). Weaknesses: baseline scores appear quoted from published tables, mostly without spreads; evaluation episodes, dropout rate, and the scored checkpoint are unstated; BEAR is listed at a normalized 98.6 on relocate-expert although Figure 1 shows its average return collapsing to near zero; and the text claims state-of-the-art results on every non-human Adroit dataset, yet other methods lead on three cloned ones.

10. **What are the ethical implications? How are they addressed?** The paper has no ethics or broader-impact statement and no limitations section; it motivates offline RL by the cost of real-world data collection, yet all evidence is simulated. Down-weighting poorly covered samples lets well-covered behavior shape the policy, so biases in the log carry over. An uncertainty score could also be read as a safety signal although it is uncalibrated and imperfect by the paper's own test (AUC 0.845), so some unsupported samples may keep high weight. None of this is discussed; more stable training is at most an indirect benefit.

11. **What themes are suggested by this research? (minimum 3)** *Distribution shift*: value targets built on unsupported actions are blamed for BEAR's diverging critic on narrow data. *The conservatism–improvement trade-off*: each sample's weight shrinks with its own estimated uncertainty, in place of one uniform penalty. *Uncertainty quantification and calibration*: dropout variance is checked as an OOD detector (heat maps, one AUC) but never calibrated or compared with actual value error.

Connection to the offline RL problem space and BCA: UWAC is an earlier instance of BCA's central move: modulating an existing algorithm's training objective per sample by an uncertainty signal. It scales the critic and actor losses of one host (BEAR) by an inverse Monte Carlo dropout variance that is never calibrated; BCA instead derives a conformally calibrated width from Bellman residuals

and uses it to modulate one loss term in each of four hosts. Unlike BCA's current design, UWAC has completed D4RL results.

Paper 17: Uncertainty-Based Offline Reinforcement Learning with Diversified Q-Ensemble (EDAC)

This paper shows that a standard online learner (SAC) becomes a strong offline method when it trusts only the lowest score among many critics, and then adds a diversity term (EDAC) so that tens of critics can do the work of hundreds.

1. **What is the citation?** An, G., Moon, S., Kim, J.-H., & Song, H. O. (2021). Uncertainty-based offline reinforcement learning with diversified Q-ensemble. *Advances in Neural Information Processing Systems, 34*, 7436–7447. Version reviewed: arXiv:2110.01548v2. `https://doi.org/10.48550/arXiv.2110.01548`

2. **What is the research area?** Offline RL for continuous control, in the model-free, uncertainty-based family: caution comes from disagreement among an ensemble of critics (several value networks trained side by side), not from tying the policy to the recorded behavior (BCQ, BEAR, BRAC) or marking down unseen actions directly (CQL). It builds on soft actor-critic (SAC), a standard online algorithm, and on clipped Q-learning, the online habit of trusting the lower of two critics.

3. **What is the research question?** Can the disagreement within an ensemble of critics, applied through clipped Q-learning's take-the-minimum rule, supply on its own the pessimism offline RL needs, with no model of the behavior policy and no sampling of unseen actions? And can the number of critics this requires be cut to a practical size?

4. **What is the significance of the question?** Earlier methods need either an accurate estimate of the behavior policy (the one that collected the data) or samples of out-of-distribution (OOD) actions, meaning actions the data do not contain; each is a hard problem in itself. They also discourage unseen actions wholesale, whether or not the critic can score them reliably, which can hold the policy too close to mediocre data. A penalty tied to the critics' own confidence could be selective, but the plain ensemble version can demand hundreds of networks.

5. **What are the contributions reported in this paper?** Three. First, SAC-N: SAC with N critics instead of two, all trained toward a target built from the lowest of their predictions, plus evidence that this minimum acts like a lower confidence bound (the ensemble average minus a multiple of its spread). Second, a diagnosis of why some datasets need hundreds of critics: when the critics' slopes with respect to the action line up, nearby unseen actions can escape the penalty. Third, EDAC (Ensemble-Diversified Actor Critic), which adds a term, weighted by η, that pushes those slopes apart at dataset actions. The reviewed version links no code of its own.

6. **What is the research method?** Algorithm design with a short supporting analysis under simplifying assumptions, then benchmarking. Tests cover 18 D4RL Gym locomotion datasets (halfcheetah, hopper, and walker2d, six data types each, 3 million training steps) and eight Adroit robotic-hand datasets (200,000 steps), all with four seeds. Baselines are behavior cloning (BC, pure imitation), plain SAC, REM (an earlier critic-ensemble method), and CQL, with five more in an appendix. Diagnostics compare the penalty on dataset vs. random actions, find the smallest workable ensemble per dataset, and measure runtime and memory.

7. **What are the results?** On the 18 Gym datasets EDAC averages 85.2 and SAC-N 84.5, against 73.7 for the rerun CQL, with the largest gains on the medium datasets (hopper-medium: 101.6 vs. 61.9). On Gym the two score alike and EDAC's gain is cost: 50 critics instead of 500 on hopper-medium (where 50 undiversified critics score 7.3) and 1.8 GB of GPU memory instead of 5.1 GB. Losses: CQL wins halfcheetah-random (31.3 vs. 28.4), and EDAC trails SAC-N on hopper-random and walker2d-random. On Adroit, EDAC does well on the pen tasks (pen-cloned: 68.2 vs. CQL's published 40.3) but stays near 10 on door and below 1 on hammer and relocate.

8. **What are the impacts and limitations of the contributions?** The paper shows that critic disagreement alone can supply pessimism, and that diversity can stand in for sheer ensemble size. Limitations: the authors concede that SAC-N can need 500 critics and that a large η can hurt on suboptimal data. Beyond that, N and η are still chosen per environment or dataset (the chosen η runs from 0, i.e., off, to 1,000); the tenfold saving holds on only a few datasets, with none on halfcheetah; the spread is not checked against actual value errors; the analysis gives no performance guarantee; and no maze or kitchen tasks are tested.

9. **How were the results evaluated or validated?** By D4RL normalized scores averaged over four seeds, with a $\pm$ spread the paper does not define and no stated number of test episodes. CQL is rerun from official code beside its published scores, and appendix ablations test rival fixes. EDAC's Gym settings come from small grids (N of 10, 20, or 50 per environment; η of 0, 1, or 5 per dataset) by an unstated criterion, presumably test returns, which a true offline user lacks. Other weaknesses: no significance tests, an Adroit stopping point read off evaluation curves, and a rerun CQL far below its published score on some tasks (hopper-medium: 61.9 vs. 86.6).

10. **What are the ethical implications? How are they addressed?** The reviewed version has no ethics, broader-impact, or limitations section; its introduction merely cites autonomous driving and healthcare as settings where exploration can do damage. The method's selling point is also its risk: it lets the policy leave the data wherever the critics agree, yet agreement is not correctness, since critics trained on the same data can share an error. Settings also appear to be tuned on test rollouts, and all evidence is simulated. Pessimism is an indirect step toward safer learning, but none of these risks is discussed.

11. **What themes are suggested by this research? (minimum 3)** *The conservatism–improvement trade-off*: the penalty grows with disagreement at each state-action pair instead of treating every unseen action alike. *Uncertainty quantification and calibration*: critic disagreement is the uncertainty signal, and its scale is not checked against real errors. *Theory vs. practice*: pessimism is bought with tens to hundreds of critics, and N and η are still chosen per environment or dataset by an unstated criterion.

Connection to the offline RL problem space and BCA: EDAC is not a BCA host, though it is among the baselines in the Unifloral codebase bundled with BCA's repository. It stands for the ensemble route to per-sample caution, the "huge-ensemble" family named in Paper 8: uncalibrated critic spread, tens to hundreds of networks, and settings tuned per dataset. BCA seeks the same selectivity from a conformally calibrated width on Bellman-residual size, with no extra critics, though unlike EDAC its current design has no completed D4RL results yet.

Paper 18: Conformal Prediction as Bayesian Quadrature (BQ-CP)

BQ-CP rereads conformal prediction as Bayesian numerical integration, so that a calibration set yields a whole distribution bounding a black-box model's expected loss instead of a single point estimate.

1. **What is the citation?** Snell, J. C., & Griffiths, T. L. (2025). Conformal prediction as Bayesian quadrature. In *Proceedings of the 42nd International Conference on Machine Learning* (Proceedings of Machine Learning Research, Vol. 267, pp. 56068–56084). PMLR. Version reviewed: arXiv:2502.13228v2. `https://doi.org/10.48550/arXiv.2502.13228`

2. **What is the research area?** Statistical machine learning, not RL: distribution-free uncertainty quantification (guarantees on a black-box model's errors that assume no particular data distribution). The paper re-derives two popular tools, split conformal prediction (a threshold set from held-out scores) and conformal risk control (its extension to other bounded, monotone losses), from Bayesian decision theory and Bayesian quadrature (numerical integration treated as inference, so the integral gets a posterior). Its link to offline RL in this review is BCA, which runs its successor WBCP (Paper 12).

3. **What is the research question?** Can split conformal prediction and conformal risk control be recovered as special cases of a Bayesian procedure that needs no hand-picked prior, and can that procedure give guarantees conditioned on the calibration data actually observed, instead of averaged over calibration sets that were never drawn?

4. **What is the significance of the question?** Black-box predictors are used in high-stakes settings such as medical diagnosis and finance, and a deployment decision rests on the one calibration set in hand. Standard conformal guarantees are marginal: they hold on average over hypothetical calibration sets, so a particular set can still produce a threshold whose real risk is too high. Being frequentist, they also make it hard to use prior knowledge about deployment conditions.

5. **What are the contributions reported in this paper?** Four. A decision-theoretic framing in which split conformal prediction and conformal risk control both keep worst-case risk below a target α. A view of the expected loss as the area under the loss's quantile function (its value at each percentile), handled like Bayesian quadrature but without a prior: take the worst-case function through the observed losses, and use a classical result that gaps between the quantile levels of i.i.d. samples follow a flat Dirichlet distribution. A random variable L^+ whose distribution upper-bounds the posterior of the expected loss, with both conformal methods recovered by using only its mean. And experiments with public code.

6. **What is the research method?** Theory, then simulation. The appendix proofs yield a decision rule: sample the Dirichlet gaps 1,000 times and choose the smallest threshold λ for which L^+ stays below the target risk α with probability $\beta = 0.95$. It is tested over 10,000 random splits in each of three settings: a synthetic binomial loss (10 calibration points), a synthetic regression whose noise grows with the input (200), and false-negative-rate control for multilabel classification on MS-COCO (1,000). Baselines are conformal risk control (CRC) and risk-controlling prediction sets (RCPS) built on a Hoeffding confidence bound.

7. **What are the results?** In theory, given the calibration losses, the expected loss is at most b with posterior probability at least $\Pr(L^+ \leq b)$ under any prior compatible with them. Empirically, CRC's threshold exceeds the target risk in 21.20%, 46.19%, and 45.05% of trials across the three

settings; BQ-CP cuts this to 0.03%, 3.42%, and 5.43%, the last just above its 5% allowance. RCPS records no failures but is widest (mean interval length 14.29 vs. 9.50 for BQ-CP and 7.99 for CRC; set size 3.57 vs. 3.04 and 2.92). At $n = 10$ BQ-CP is very cautious (mean risk 0.1758 against a 0.4 target).

8. **What are the impacts and limitations of the contributions?** BQ-CP shows that a conformal threshold can carry a full posterior without a hand-chosen prior; it received an outstanding paper award at ICML 2025 and is the base WBCP (Paper 12) extends. The authors' stated limits: deployment data must be i.i.d. with the calibration data, losses need a known upper bound, and bounds valid for any prior can be loose. Further limits: the advertised use of prior knowledge is left to future work; the rule returns one global threshold with no per-input guarantee; and no theorem bounds how often it fails over repeated calibration sets.

9. **How were the results evaluated or validated?** By proofs and repeated sampling. The proofs assume i.i.d. continuous losses bounded by B; discrete losses, such as the binomial and 0–1 miscoverage losses of the two synthetic experiments, get only an unproved footnote. One step takes the Dirichlet law of the gaps, a sampling result, as their posterior once the losses are seen, without arguing this for every prior. Strengths: 10,000 splits, a synthetic loss with known true risk, and 95% Clopper–Pearson intervals in two of three tables. Weaknesses: one real dataset, a single β, and an MS-COCO table with no intervals or stated α, whose 5.43% the text calls within the 5% limit.

10. **What are the ethical implications? How are they addressed?** A short impact statement says the method is meant to inform deployment of black-box models in safety-critical applications, that its guarantees may fail if its assumptions are violated, and that deployments should be monitored for distribution shift. Further implications: a posterior bound can be mistaken for a safety certificate when the i.i.d. assumption goes unchecked, and a bound on average loss can hide high loss for a subgroup, though the introduction names fairness as a goal. The statement is candid about the main risk but offers no monitoring method or subgroup analysis; public code is a positive.

11. **What themes are suggested by this research? (minimum 3)** *The conservatism–improvement trade-off*: here caution vs. tightness, since RCPS records no failures but is widest, CRC is tightest but often exceeds the target, and BQ-CP sits between. *Uncertainty quantification and calibration*: a calibration set yields a distribution over the expected loss, not one point estimate. *Theory vs. practice*: a marginal conformal guarantee can hold while 21–46% of individual calibration sets exceed the target risk.

Connection to the offline RL problem space and BCA: BQ-CP is, in effect, the threshold rule BCA runs: WBCP (Paper 12) with uniform weights is the exchangeable case that recovers it, and BCA sets the credibility level to $\beta = 0.95$, the value this paper uses. BCA thus inherits its guarantee, a posterior bound, given the calibration scores, on how often new scores from the same distribution exceed the threshold; this is neither a per-sample nor, as BCA's own documentation says, a policy-performance guarantee. It also inherits the i.i.d. assumption, which same-episode, policy-dependent Bellman residuals strain even after BCA thins its calibration set.

Part A: Literature Reviews

The three literature reviews are new in Version 2. Each is reviewed against the eleven literature-review questions, and their meta-themes are drawn from the same four themes.

Literature Review 1: Offline Reinforcement Learning: Tutorial, Review, and Perspectives on Open Problems (Levine et al., 2020)

This early tutorial helped frame the field: it explains why learning from a fixed dataset is hard, organizes the early methods by how they cope, and lists open problems that later papers took up.

1. **What is the citation?** Levine, S., Kumar, A., Tucker, G., & Fu, J. (2020). *Offline reinforcement learning: Tutorial, review, and perspectives on open problems* (arXiv:2005.01643v3) [Preprint]. arXiv. `https://doi.org/10.48550/arXiv.2005.01643`

2. **What is the survey scope?** Offline RL as a whole: learning a policy from a fixed dataset collected by a possibly unknown behavior policy, with no interaction during training. After RL basics it covers three families of methods (importance-sampling estimators, which reweight logged data to mimic another policy; approximate dynamic programming, meaning critic-based value learning, with policy constraints, uncertainty penalties, or conservative critics; and model-based methods), then evaluation practice and applications such as robotics, healthcare, and driving. It has roughly 190 references up to mid-2020. Exploration and a complete account of model-based RL are set aside. It is a tutorial and conceptual review for researchers entering the area.

3. **What is the survey question?** What prevents current RL algorithms from turning a fixed, previously collected dataset into the best policy the data can support, and which ideas have been proposed to overcome those obstacles?

4. **What is the significance of the survey?** It appeared in May 2020, when offline RL had just become an active topic (BCQ and BEAR, Papers 13 and 14, and BRAC) but still went by competing names and lacked settled evaluation practice. It gave newcomers one entry point, placing older statistical work on importance sampling beside recent deep methods under one notation and one diagnosis: distribution shift created by counterfactual (what-if) queries. The later survey by Figueiredo Prudencio et al. treats it as the main predecessor and presents its own open-problems section as an update of this one.

5. **What are the themes?** *Distribution shift as the core obstacle*: learning offline means answering what-if questions about actions the data never contained. *Policy constraints and penalties*: keep the learned policy near the data, preferably within its support rather than matching it exactly. *Uncertainty estimation and conservative critics*: make the critic itself cautious, with or without an explicit uncertainty model.

6. **What is the survey method?** An expert narrative written as a tutorial, not a systematic review: no search databases, keywords, or inclusion criteria are reported. The material is organized by algorithmic principle rather than chronology, in one shared notation. The authors restate and explain results from the literature but prove no new theorems, run no experiments, and give no benchmark tables; their own critical view appears mainly in the challenges subsections that close each method section.

7. **What are the survey findings?** Importance-sampling variance grows exponentially with the horizon, so those tools are dependable only when the learned policy stays close to the

data. Naive dynamic programming often fails because its targets query unseen actions and the resulting errors compound uncorrected. Policy constraints help but must be tight, which caps improvement. Uncertainty-based methods are principled, but calibrated uncertainty for deep value functions is hard to obtain, so constraint and conservative methods performed better at the time; conservative critics in turn can be too pessimistic, and how to adjust that pessimism on the fly is left open. Benchmarking is judged immature.

8. **What are the limitations of the survey?** Currency is the main one: it stops at mid-2020, before TD3+BC, IQL, ReBRAC, and the sequence-model methods. Coverage is uneven, with uncertainty-based methods given about half a page. No search protocol is reported, and more than 30 of the roughly 190 references include one of the four authors, whose own methods (BEAR, BRAC, CQL) match the remedies the survey favors. It offers no quantitative comparison, and offline hyperparameter selection is never treated directly.

9. **How was the survey assessed relative to other surveys?** It has no related-surveys section; it positions itself against the older batch RL literature and explains why it prefers the term *offline*. Against the other two surveys reviewed here, it is the most formal and conceptual account of *why* offline RL is hard. The survey by Figueiredo Prudencio et al. (2024) is broader and more systematic, with a taxonomy, post-2020 methods, and a benchmark review; He's survey (2023) is a short, more recent list of model-based methods with little analysis.

10. **What are the ethical implications? How are they addressed?** There is no ethics section, and safety appears only in scattered technical remarks: a half-trained treatment policy cannot be tried on real patients, and clinical records over-represent severe cases, which can mislead a naive learner. Left unaddressed are privacy and consent for clinical data, unequal treatment of groups under-represented in logs, persuasive dialogue agents (one motivating example is a sales chatbot), and the danger of treating off-policy estimates as the final check before deployment. Safety serves as a motivation rather than as an ethical question.

11. **What meta-themes are suggested by this survey? (minimum 3)** *Distribution shift*: every family's failure traces to the same mismatch, so later methods can be compared by where they intercept it. *The conservatism–improvement trade-off*: tight constraints are needed to keep errors small, yet they tie the policy to possibly poor behavior. *Uncertainty quantification and calibration*: a principled remedy that is hard to deliver, with self-adjusting caution left as an open problem.

Connection to the offline RL problem space and BCA: The survey lays out the method families that BCA's four host algorithms belong to, and its open problem of caution that adjusts itself to the data is the question BCA takes up, using calibrated residual uncertainty where the survey judged uncertainty estimates hard to calibrate (BCA's calibration covers recorded transitions, not unseen actions).

Literature Review 2: A Survey on Offline Model-Based Reinforcement Learning (He, 2023)

This short primer on offline model-based RL profiles seven methods by how each builds caution into a learned model of the environment.

1. **What is the citation?** He, H. (2023). *A survey on offline model-based reinforcement learning* (arXiv:2305.03360v1) [Preprint]. arXiv. `https://doi.org/10.48550/arXiv.2305.03360`

2. **What is the survey scope?** Offline model-based RL: fit a dynamics and reward model to a fixed log of experience, then plan or optimize a policy inside that model. After brief primers it profiles seven methods from 2020 to early 2023 (MOReL, MOPO, BREMEN, VI-LCB, COMBO, RAMBO, ARMOR) in about five pages, with nineteen references. Model-free methods appear only as a contrast, and benchmarks, quantitative results, off-policy evaluation, and application domains are absent.

3. **What is the survey question?** How have recent offline model-based methods coped with the distribution shift that arises when a model learned from logged data is used to optimize a new policy, and what problems remain unsolved?

4. **What is the significance of the survey?** By May 2023, uncertainty-penalized models had been a main route to offline RL for about three years, yet the general surveys gave model-based methods only a few pages and went no further than COMBO. He's paper is a dedicated, recent, and very short treatment that adds adversarial-model methods and sample-complexity theory. It is a single-author preprint with no peer-reviewed version, so its value is as a quick map rather than an authoritative reference.

5. **What are the themes?** *Model exploitation as the core obstacle*: a policy optimized inside a learned model drifts to regions where the model is wrong but looks rewarding. *Uncertainty-penalized models*: MOReL and MOPO turn ensemble uncertainty into a reward penalty. *Alternatives to uncertainty penalties*: COMBO's conservative critic and the adversarially trained models of RAMBO and ARMOR.

6. **What is the survey method?** A personal, narrative selection: no databases, search terms, or inclusion criteria are named, and the choice of these seven methods is not explained. Each profile gives the core idea, the key equations in the notation of whichever source it follows, and the original authors' claims. There are no figures, tables, experiments, or new results, and no unifying notation; some passages follow Figueiredo Prudencio et al. closely.

7. **What are the survey findings?** Distribution shift, made worse by model exploitation, remains the defining open problem: by the survey's account, none of the reviewed methods provides a performance guarantee that holds regardless of the data. Reward-penalty methods are attractive because they reuse existing planners, but they depend on uncertainty estimates the survey regards as error-prone, which COMBO avoids. The one optimality result it reports, for a penalized form of value iteration, is confined to tabular problems. It also argues that theoretically grounded methods often go unused because they cannot reliably beat the policy already in service.

8. **What are the limitations of the survey?** Coverage is thin (seven methods, nineteen references), with no benchmark results, no comparison table, and no stated selection procedure. Most profiles restate equations and pass on the authors' claims with little independent critique, and some descriptions are loose: COMBO is said to penalize rewards, while the objective the survey prints acts on Q-values (the critic's action values). It has not been revised since its first version.

9. **How was the survey assessed relative to other surveys?** It cites the other two surveys only as background authorities and never says what it adds to them. Of the three reviewed here it is the narrowest, shortest, and most recently written. Levine et al. give model-based methods a more analytical section, and Figueiredo Prudencio et al. place them in a full taxonomy with

benchmark context. He's distinct additions are RAMBO, ARMOR, VI-LCB, and the tabular sample-complexity result, none of which appears in either broader survey.

10. **What are the ethical implications? How are they addressed?** The survey discusses none. Offline learning is framed as improving on a deployed system from that system's own data, so model exploitation means a policy can look excellent inside the learned simulator and fail once it replaces that system, while biases in past decisions pass into both the model and the new policy. With off-policy evaluation omitted, the survey never explains how such policies could be checked before release. Only the technical safe-improvement guarantees of COMBO and ARMOR come near the topic.

11. **What meta-themes are suggested by this survey? (minimum 3)** *The conservatism–improvement trade-off*: most of the methods vary their caution across state-action pairs, but its overall strength is still one hand-set number. *Uncertainty quantification and calibration*: MOReL's and MOPO's penalties rest on ensemble heuristics whose link to actual model error is never examined. *Theory vs. practice*: the only optimality result is tabular, and provable methods often go undeployed.

Connection to the offline RL problem space and BCA: He's survey shows the model-based branch sharing the one-global-weight problem of BCA's model-free hosts, and sizing its penalties by unchecked uncertainty heuristics. Because a method like COMBO mirrors CQL's penalty, calibrated per-sample widths could plausibly carry over to this branch.

Literature Review 3: A Survey on Offline Reinforcement Learning: Taxonomy, Review, and Open Problems (Figueiredo Prudencio et al., 2024)

This survey is the broad, structured update to Levine et al.: it offers a taxonomy that describes each offline algorithm as a class plus optional loss terms, a review of benchmarks, and a refreshed list of open problems.

1. **What is the citation?** Figueiredo Prudencio, R., Maximo, M. R. O. A., & Colombini, E. L. (2024). A survey on offline reinforcement learning: Taxonomy, review, and open problems. *IEEE Transactions on Neural Networks and Learning Systems, 35*(8), 10237–10257. `https://doi.org/10.1109/TNNLS.2023.3250269`

2. **What is the survey scope?** Deep offline RL in the single-agent setting: direct and implicit policy constraints, importance sampling, regularization, uncertainty estimation, model-based methods, one-step methods, imitation learning, and trajectory optimization. Its timeline runs from late 2018 to early 2022; its method table classifies 26 entries, and it cites 91 references. It also reviews off-policy evaluation and the D4RL and RL Unplugged benchmarks. Theoretical analyses, multi-agent methods, and most marginalized importance sampling are left out.

3. **What is the survey question?** How can the fast-growing body of offline RL algorithms be placed in one framework that shows which design choices each method makes, how those choices fare on different kinds of data, and where research effort should go next?

4. **What is the significance of the survey?** When it appeared on arXiv in March 2022, the main broad review was the 2020 tutorial, and many newer methods (TD3+BC, IQL, COMBO, the Decision Transformer) had since been published, several relying on strategies the tutorial never discussed. The survey supplies an updated review in a single notation, a taxonomy that

lets methods be read as combinations of reusable parts, and a mapping from dataset properties to the algorithm classes that handle them, which helps practitioners match methods to their data.

5. **What are the themes?** *Distribution shift as the central difficulty*: most classes are introduced as ways to prevent, penalize, or sidestep it. *Policy constraints and behavior regularization*: direct constraints that estimate the behavior policy versus implicit ones that use only dataset samples. *Evaluating policies without deployment*: off-policy evaluation tied to hyperparameter selection and early stopping.

6. **What is the survey method?** An expert survey whose selection process goes unreported: it names no databases, search strings, or inclusion criteria, and the authors concede that their method table is far from complete. The organizing device is the taxonomy, with every method restated in a shared notation and a timeline ordered by preprint date. The only quantitative analysis is secondary: a heatmap built from D4RL scores collected from the literature, rescaled per dataset and averaged by dataset property. No new experiments are run.

7. **What are the survey findings?** Most new algorithms are different responses to distribution shift, each with a trade-off: direct constraints depend on a good estimate of the behavior policy and can be overly pessimistic, while implicit ones avoid that estimate and suit online fine-tuning better. Two lessons stand out: hyperparameter search mattered more than the choice of divergence (from BRAC), and performance does not track algorithmic complexity (from TD3+BC). Uncertainty estimation in model-based methods is described as difficult and often unreliable. The open problems are led by reliable off-policy evaluation and hyperparameter tuning, followed by incremental RL for changing data and fine-tuning, safety-critical RL, and the use of unlabeled data.

8. **What are the limitations of the survey?** No selection rules are stated, and depth is uneven: the uncertainty section reviews only one line of ensemble work. The introduction promises a discussion of dynamically adjusted conservatism that the open-problems section never delivers. The heatmap pools scores from many papers, so it likely mixes tuning budgets and codebases, shows no variance, and credits each class with its best member. The algorithmic review stops at early 2022, so later methods such as ReBRAC are absent. At least 21 of the 91 references also share a single coauthor from another research group, which tilts the review toward that group.

9. **How was the survey assessed relative to other surveys?** It positions itself against one predecessor, Levine et al. (2020), and claims to add a taxonomy, a single notation, the methods published since, a benchmark review, and a performance figure. Of the three surveys reviewed here it gives the broadest map of model-free methods and is the only one to systematically map benchmark environments to dataset properties. The tutorial by Levine et al. remains longer and more conceptual; He's preprint is far narrower but reaches theory-driven and adversarial model-based work that this survey omits.

10. **What are the ethical implications? How are they addressed?** No section is devoted to ethics. Safety appears as a motivation (testing a policy outside the data's support could be hazardous in driving or medical diagnosis) and as an open problem (safety-critical RL). The survey asks for datasets with risky gaps, such as driving logs without a single crash, to test whether methods learn to avoid hazards missing from the data. It does not discuss prejudice carried in logged human decisions, privacy, consent, or accountability. As scholarship it discloses funding and avoids self-citation.

11. **What meta-themes are suggested by this survey? (minimum 3)** *The conservatism–improvement trade-off*: most of the mechanisms it describes are scaled by one global number, and dynamic modulation of conservatism is named as an open problem but not developed. *Uncertainty quantification and calibration*: uncertainty estimates are called unreliable, yet whether a stated width matches observed error is never asked. *Theory vs. practice*: off-policy evaluation and hyperparameter selection lead the list of open problems.

Connection to the offline RL problem space and BCA: This survey explains three of BCA's four host algorithms side by side (CQL, TD3+BC, IQL) and names the gap BCA targets: conservatism that is modulated dynamically instead of fixed by one number. Its reliance on D4RL is also a caveat for BCA, since any gains measured on that benchmark alone carry its limits.

Part B: Themes and Observations

The twenty-one works (eighteen research papers and three literature reviews) are described with four themes, three per work.

Theory vs. practice is the most prevalent (19 works). It matters because what is proved or reported often differs from what an offline user gets: guarantees assume conditions the tested algorithm breaks, and scores depend on implementation details and live tuning.

The conservatism–improvement trade-off follows (18 works). Every method must decide how far to distrust values its data cannot verify: too little caution lets errors spread, and too much ties the policy to mediocre data. Many methods set that caution with one global number, which is too careful where data are dense and too lax where they are sparse.

Distribution shift (14 works) is the root problem the other themes answer: values for actions the data do not contain cannot be corrected offline.

Uncertainty quantification and calibration is the least prevalent theme (12 works) yet, for this project, the most significant. It is the route from one global dose of caution to caution that varies per sample. The surveys find uncertainty estimates unreliable or hard to calibrate, and QQL, UWAC, and EDAC act on uncertainty signals that carry no calibration guarantee. Only five of the twelve calibrate their uncertainty (Papers 8, 10, 11, 12, and 18), and each documents limits on what its guarantee covers.

Together the four themes motivate, and bound, BCA's calibrated per-sample conservatism: it addresses the trade-off through calibrated uncertainty, and theory vs. practice is the reminder that a calibration guarantee is not a policy-performance guarantee.