

LEGEND

- WORK AREA
- SAFETY BUFFER
- CONES

STOP HERE ON RED SIGNAL
BURNING OFF

CONES MAY BE PLACED ALONG EDGE TO REDUCE LANE WIDTH TO MAX 3.5m

6m
4m SPACINGS
6 CONES

THRESHOLD

BURNING OFF **60**
SMOKE HAZARD

REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVS AND CRESTS

OR

60



REPEATER SIGNAGE MAY BE A STAND ALONE 600x600

GENERAL NOTES:

- THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN
- ALL SIGN LOCATIONS ARE TO BE CHECKED PRIOR TO SETOUT AND POSITIONS ADJUSTED TO ALLOW FOR SPECIFIC SITE CONSTRAINTS SUCH AS VEGETATION, OTHER SIGNS, ROADSIDE FURNITURE AND SUFFICIENT SPACE ON SHOULDERS/EMERGENCY LANES.
- THE POSITIONS OF SIGNS, LENGTH OF TAPERS OR MARKING SHALL BE:
 - MINIMUM 10% LESS THAN THE DISTANCES OR LENGTHS GIVEN,
 - MAXIMUM 25% MORE THAN THE DISTANCES OR LENGTHS GIVEN.
- WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT
- DRIVE SLOWLY CAN BE SWAPPED WITH SMOKE HAZARD, OR BURNING OFF.
- USE OF FOLD UP SIGNS AND SWING SIGNS AND SIGNS ON ONE SIDE OF THE ROAD MAY BE ACCEPTABLE IN NARROW, VERY LOW VOLUME TRACKS <50 VPD
- SUPERVISOR SHALL UNDERTAKE RISK ASSESSMENT TO DETERMINE APPROPRIATE TEMPORARY SPEED RESTRICTION
- THE WORKER SYMBOLIC SIGNS SHALL BE INSTALLED ONLY WHEN ON-FOOT PERSONNEL WILL BE VISIBLE TO PASSING TRAFFIC, OTHERWISE REPLACE WITH BURNING OFF OR SMOKE HAZARD SIGN
- ALL EXISTING SPEED ZONE SIGNAGE WITHIN THE TEMPORARY SPEED ZONE SHALL BE COVERED WITH SUITABLE OPAQUE MATERIAL FOR THE DURATION OF THE WORKS AND COVERS TO BE REMOVED ON COMPLETION OF WORKS EACH DAY UNLESS OTHERWISE NOTED.
- 20km MAX WORK AREA

DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTMM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: CAMERON OLSON
AWTM CERT. No: KTS-AWTM-24-49061-03
SIGNED: 
REVIEWED: MATTHEW BYRNE
AWTM CERT. No: AUS-AWTM-24-1367-05
SIGNED: 

**ROAD AUTHORITY SHALL APPROVE
USAGE OF THIS TGS**

REINSTATE
POSTED SPEED

END OF BURN
DRIVE SAFELY

FOLLOW ME
DO NOT OVERTAKE

ESCORT AND TAIL VEHICLE
SHALL BE DRIVEN BY
DEPARTMENT PERSONNEL
WITH RADIO COMMUNICATION

OPTIONAL
TAIL
VEHICLE

STOP HERE ON RED SIGNAL
BURNING OFF

PREPARE TO STOP
DO NOT OVERTAKE

QUEUED TRAFFIC AHEAD
PREPARE TO STOP

REDUCE SPEED **60**

BURNING OFF **80**
DRIVE SLOWLY

**GOVERNMENT OF
WESTERN AUSTRALIA**

DRIVE SLOWLY
BURNING OFF **80**

REDUCE SPEED **60**

PREPARE TO STOP
QUEUED TRAFFIC AHEAD

DO NOT OVERTAKE
PREPARE TO STOP

BURNING OFF
STOP HERE ON RED SIGNAL

SECONDARY PREPARE TO STOP
SPACING BASED ON ANTICIPATED END
OF QUEUE PLUS 2x OF TABLE A SPACING,
TRAFFIC CONTROLLERS SHALL MONITOR
END OF QUEUE

ESCORT
VEHICLE

Work Area Length

DRIVE SAFELY
END OF BURN
REINSTATE
POSTED SPEED

SECONDARY PREPARE TO STOP
SPACING BASED ON ANTICIPATED END
OF QUEUE PLUS 2x OF TABLE A SPACING,
TRAFFIC CONTROLLERS SHALL MONITOR
END OF QUEUE

TABLE A

POSTED SPEED km/h	SIGN SPACING m
90	80
100	80
110	80

BURNING OFF
90km/h - 110km/h POSTED SPEED
WITH TRAFFIC CONTROL AND ESCORT VEHICLE

DATE: 02/04/2025 REV No: 0 BURN-25-17