

LEGEND

WORK AREA

SAFETY BUFFER

TMP MUST BE AUTHORISED
FOR IMPLEMENTATION BY
THE RELEVANT ROAD AUTHORITY



Table 5.3: Works on shoulders, medians, verges and footpaths – large plant criteria

Criteria	Yes/No
1 The work area is outside of traffic lanes	
2 No workers on foot are required	
3 Clearance from the work area to the edge of the traffic lane is: - greater than 1.2 m where the speed limit is more than 80 km/h - may be less than 1.2 m where speed limit is 80 km/h or less (plant items must not encroach onto the traffic lane)	
4 A vehicle mounted warning device is displayed on each large plant item, is not obscured and meets recommended sight distance requirements for approaching vehicles as shown in Table 5.4.	

*NOTE: If any criteria cannot be met a static worksite TGS should be selected instead.

Table 5.4: Recommended sight distance to the vehicle mounted warning device

Speed (km/h)	Distance (m)
≤ 45	80
46 - 55	100
56 - 65	120
66 – 75	140
76 – 85	160
86 – 95	180
96 – 105	200
> 105	220

These TGS must be applied in bounds of 2km only

DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTMM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: MATTHEW BYRNE
AWTM CERT. No: AUS-AWTM-24-1367-05
SIGNED:

REVIEWED: DALLAS MILLWARD
AWTM CERT. No: AUS-AWTM-23-2352-04
SIGNED:

TABLE A	
POSTED SPEED km/h	SIGN SPACING m
50 OR LESS	30
60	45
70	140
80	160
90	180
100	200
110	220

