

LEGEND

WORK AREA

VMS MESSAGES

BURNING OFF AHEAD

MOBILE PLANT AHEAD

VMS ARE OPTIONAL AND MESSAGES MAY CHANGE TO SUIT WORKS (Refer to section 7.6.4 of the TMP for guidance on suitable messages). REFER TO TABLE A FOR MINIMUM DISTANCE TO BE INSTALLED FROM FIRST TEMPORARY WORK SIGN

TMP MUST BE AUTHORISED FOR IMPLEMENTATION BY THE RELEVANT ROAD AUTHORITY

STANDARD SIGNAGE MAY BE CHANGED WHEN NO BURNING IS OCCURRING

ROAD PLANT AHEAD

SMOKE HAZARD

ROAD PLANT AHEAD

GENERAL NOTES:

1. THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN

2. WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT

3. THE WORKER SYMBOLIC SIGNS SHALL BE INSTALLED ONLY WHEN ON-FOOT PERSONNEL WILL BE VISIBLE TO PASSING TRAFFIC, OTHERWISE REPLACE WITH BURNING OFF OR SMOKE HAZARD SIGN

4. ADVANCED WARNING VEHICLE SHALL BE STOPPED ALONG CURVED OR CRESTED SECTIONS OF ROAD WHERE VISIBILITY IS RESTRICTED TO MAINTAIN MINIMUM SIGHT DISTANCE GIVEN IN TABLE 3.2

5. WHERE SIGHT DISTANCE IS POOR FOR OPPOSING TRAFFIC, MOVE THE LEAD VEHICLE BEYOND DISTANCES GIVEN IN TABLE 3.1 TO MAINTAIN MINIMUM SIGHT DISTANCES GIVEN IN TABLE 3.2

6. WORKERS ON FOOT SHALL MAINTAIN A MINIMUM OF 1.2m CLEARANCE FROM THE TRAFFICABLE LANE AT ALL TIMES

7. WORK PLANT SHALL ONLY TEMPORARILY ENCROACH ONTO THE TRAFFICABLE LANE WHEN SAFE WITH NO APPROACHING TRAFFIC

DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTMM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: MATTHEW BYRNE

AWTM CERT. No: AUS-AWTM-24-1367-05

SIGNED:

REVIEWED: DALLAS MILLWARD

AWTM CERT. No: AUS-AWTM-23-2352-04

SIGNED:

END ROADWORK

DRIVE SAFELY

ROAD PLANT AHEAD

SMOKE HAZARD

ROAD PLANT AHEAD

SMOKE HAZARD

ROAD PLANT AHEAD

SMOKE HAZARD

LEAD VEHICLE

WORK VEHICLE

SHADOW VEHICLE

ADVANCED WARNING VEHICLE

VMS

REFER TABLE 3.1

SEE NOTE 5

20-40m

REFER TABLE 3.1

SEE NOTE 4

REFER TABLE 3.1

SWA

REFER TABLE 3.1

1.2m - 3.0m

GOVERNMENT OF WESTERN AUSTRALIA

TABLE 3.2 - SIGHT DISTANCE TO TRAFFIC MANAGENT VEHICLES

POSTED SPEED (km/h)	MINIMUM SIGHT DISTANCE
≤ 60	150m
≥ 70	250m

Minimum sight distance to be maintained from approaching traffic to convoy vehicles - excluding the work vehicle

TABLE 3.1 - EXCLUDING SHADOW VEHICLE

POSTED SPEED (km/h)	DISTANCE BETWEEN CONVOY VEHICLES
≤40	50m
50	70m
60	90m
70	110m
80	140m
90	160m
100	200m
110	230m

TABLE A

POSTED SPEED km/h	SIGN SPACING m
70	140
80	160

BUSHFIRE RISK MITIGATION MOBILE WORKS OPERATIONS

ALL POSTED SPEEDS

WORKERS ON FOOT GREATER THAN 1.2m FROM TRAFFIC

DATE: 25/03/2026

REV No: 1

BURN-26-19