

LEGEND

- WORK AREA
- SAFETY BUFFER
- CONES

**TMP MUST BE AUTHORISED
FOR IMPLEMENTATION BY
THE RELEVANT ROAD AUTHORITY**



A diagram showing two rectangular signs side-by-side. Above them is a label 'VMS MESSAGES'. The left sign is black with yellow text that reads 'BURNING OFF AHEAD'. The right sign is black with yellow text that reads 'DRIVE CAREFULLY'.

**VMS ARE OPTIONAL AND MESSAGES
MAY CHANGE TO SUIT WORKS
(Refer to section 7.6.4 of
the TMP for guidance on
suitable messages).
REFER TO TABLE A FOR MINIMUM
DISTANCE TO BE INSTALLED
FROM FIRST TEMPORARY WORK SIGN**

The diagram illustrates the layout of two sets of traffic signs. On the left, text indicates that 'BURNING OFF' and 'SMOKE HAZARD' panels are to be changed when no burning is occurring. On the right, two sign configurations are shown. The top configuration consists of a rectangular sign with two sections: the left section contains the text 'BURNING OFF' and the right section is empty. Below this is a single rectangular sign containing the text 'SMOKE HAZARD'. The bottom configuration consists of a rectangular sign with two sections: the left section contains the text 'ROAD CLOSED AHEAD' and the right section is empty. Below this is a single rectangular sign containing the text 'ROADWORKS'.

'BURNING OFF' AND
'SMOKE HAZARD'
PANELS TO BE
CHANGED WHEN
NO BURNING
IS OCCURRING

**BURNING
OFF**

SMOKE HAZARD

**ROAD
CLOSED
AHEAD**

ROADWORKS

GENERAL NOTES:

1. THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN
2. ALL SIGN LOCATIONS ARE TO BE CHECKED PRIOR TO SETOUT AND POSITIONS ADJUSTED TO ALLOW FOR SPECIFIC SITE CONSTRAINTS SUCH AS VEGETATION, OTHER SIGNS, ROADSIDE FURNITURE AND SUFFICIENT SPACE ON SHOULDERS/EMERGENCY LANES.
3. THE POSITIONS OF SIGNS, LENGTH OF TAPERS OR MARKING SHALL BE:
 - a) MINIMUM 10% LESS THAN THE DISTANCES OR LENGTHS GIVEN,
 - b) MAXIMUM 25% MORE THAN THE DISTANCES OR LENGTHS GIVEN.
4. WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT
5. SUPERVISOR SHALL UNDERTAKE RISK ASSESSMENT TO DETERMINE APPROPRIATE TEMPORARY SPEED RESTRICTION
6. ALL EXISTING SPEED ZONE SIGNAGE WITHIN THE TEMPORARY SPEED ZONE SHALL BE COVERED WITH SUITABLE OPAQUE MATERIAL FOR THE DURATION OF THE WORKS AND COVERS TO BE REMOVED ON COMPLETION OF WORKS EACH DAY UNLESS OTHERWISE NOTED.

DISCLAIMER:
IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTMM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: MATTHEW BYRNE
AWTM CERT. No: AUS-AWTM-24-1367-05

SIGNED:

REVIEWED: DALLAS MILLWARD AWTM CERT. No: AUS-AWTM-23-2352-04

SIGNED: 

TABLE A	
POSTED SPEED km/h	SIGN SPACING m
90	180
100	200
110	220

90km/h - 110km/h POSTED SPEED

FULL ROAD CLOSURE

2026	REV No: 1	BI
------	-----------	----

DATE: 25/03/2026	REV No: 1	RIIRN-26-20
------------------	-----------	-------------

REV No: 1 RIIRN-26-20

BIIRN-26-20