

LEGEND

WORK AREA

SAFETY BUFFER

SMOKE HAZARD

BURNING OFF

REPEATER SIGNAGE TO BE PLACED EVERY 500m, AT INTERSECTIONS, CURVS AND CRESTS

STANDARD SIGNAGE MAY BE CHANGED TO 'VERGE WORKS' WHEN NO BURNING IS OCCURING

SMOKE HAZARD

BURNING OFF

VERGE WORKS

GENERAL NOTES:

1. THIS TGS IS ONLY TO BE USED AS PART OF THIS GENERIC TRAFFIC MANAGEMENT PLAN

2. ALL SIGN LOCATIONS ARE TO BE CHECKED PRIOR TO SETOUT AND POSITIONS ADJUSTED TO ALLOW FOR SPECIFIC SITE CONSTRAINTS SUCH AS VEGETATION, OTHER SIGNS, ROADSIDE FURNITURE AND SUFFICIENT SPACE ON SHOULDERS/EMERGENCY LANES.

3. THE POSITIONS OF SIGNS, LENGTH OF TAPERS OR MARKING SHALL BE:

a) MINIMUM 10% LESS THAN THE DISTANCES OR LENGTHS GIVEN,

b) MAXIMUM 25% MORE THAN THE DISTANCES OR LENGTHS GIVEN.

4. WHEN USING MMS ENSURE TWO 5mm THICK CORE FLUTE SIGNS ARE USED BACK TO BACK IN THE FRAME TO HELP PREVENT THE SIGN FROM BLOWING OUT

5. DRIVE SLOWLY CAN BE SWAPPED WITH SMOKE HAZARD, OR BURNING OFF.

6. USE OF FOLD UP SIGNS AND SWING SIGNS AND SIGNS ON ONE SIDE OF THE ROAD MAY BE ACCEPTABLE IN NARROW, VERY LOW VOLUME TRACKS <50 VPD

DISCLAIMER:

IT IS THE RESPONSIBILITY OF THE USER OF THIS TRAFFIC GUIDANCE SCHEME TO CONFIRM THE APPROPRIATENESS OR OTHERWISE FOR THE INTENDED WORK SITE BASED ON RIGOROUS RISK ASSESSMENT AND REVIEW OF THE REQUIREMENTS OF THE AS1742.3 AND MAIN ROADS WA TRAFFIC MANAGEMENT FOR WORKS ON ROADS CoP AND THE AGTTM. ALL RESPONSIBILITY WILL REMAIN WITH THE USER TO ENSURE COMPLIANCE WITH RELEVANT STANDARDS AND THE PROVISION OF THE NECESSARY LEVEL OF PROTECTION FOR WORK PERSONNEL AND WORK SITE.

DRAWN: MATTHEW BYRNE

AWTM CERT. No: AUS-AWTM-24-1367-05

SIGNED:

REVIEWED: DALLAS MILLWARD

AWTM CERT. No: AUS-AWTM-23-2352-04

SIGNED:

TMP MUST BE AUTHORISED FOR IMPLEMENTATION BY THE RELEVANT ROAD AUTHORITY

END OF BURN

DRIVE SAFELY

OR

SMOKE HAZARD

BURNING OFF

SMOKE HAZARD

BURNING OFF

NEXT

km

REFER TABLE A

GREATER THAN 6.0m @ DERESTRICTED
GREATER THAN 6.0m @ 90-110 km/h
BETWEEN 3-6m @ 70-80 km/h
BETWEEN 1.2-3m @ 50-60 km/h

20m BUFFER

WORK AREA

20m BUFFER

REFER TABLE A

SMOKE HAZARD

BURNING OFF

NEXT

km

OR

SMOKE HAZARD

BURNING OFF

DRIVE SAFELY

BURN

END

TABLE A

POSTED SPEED km/h

SIGN SPACING m

50 OR LESS

30

60

45

70

140

80

160

90

180

100

200

110

220

BUSHFIRE RISK MITIGATION

ALL POSTED SPEED ROADS

BETWEEN 1.2m TO 6m BASED ON POSTED SPEED

DATE: 25/03/2026

REV No: 1

BURN-26-01