Apartment 50: Paper 008

AuthorityEffect: None. This is fictional examination staging, not a historical quotation or a source of mathematical authority.

Landau points at the declared carrier. Woland asks which claim its checker can establish. Behemoth asks for the smallest valid near miss. Their task in this companion is **round trips and semantic conservativity**.

Begin with the study guide and instructor key, then attempt the quiz without the key. A lower-case wire token names a role only after its interpretation is declared. Arrows sketch graph edges; they do not automatically attach higher-dimensional cells. A receipt verifies its stated finite check and grants no authority to extend Genesis or make a physical claim.

The examiner's standard is a concrete calculation, an explicit counterexample, or a source-bound missing obligation. The manuscript source reading governs the answer.

Study guide and instructor key: Paper 008

AuthorityEffect: None. Attempt the quiz first. The manuscript distinguishes packet syntax, semantics, formal evidence and recorded observations. The source archive provides selected historical bytes without a working-tree fallback.

L0 to L7 organize this lesson. They do not grade an MSS stage, prove a general theorem or authorize use. Give each answer one point for the concrete result and one for its stated limit; use the total only to identify material to revisit.

Worked answers

L0: Packets and admission

Q01.

Wire	Parses	MSS-0 active	MSS-1 active
`<>`	Yes	Yes	Yes
`<0>`	Yes	No	Yes
`<2>`	Yes	No	No
`op<<1><0>>`	Yes	No	Yes

The raw atom alphabet is ASCII `a-z` and `0-9`. MSS-1 activates only `0` and `1` as **data** glyphs. The application prefix is literally `op<`; its `o` and `p` are syntax, not extra active data atoms. Parsing and admission answer different questions.

Q02. The old-image round trip returns Diff. The upward call on `<0>` raises ValueError. The downward call on `<1>` returns NonDescentReceipt with that original parsed packet. It preserves the rejected object rather than converting it to Diff. The historical record-and-prefix toy returns `None`; it is a separate example. Also, `d_1(parse("<2>"))` returns a refusal even though `<2>` is not MSS-1-active: the caller still needs the upper-level admission check.

Replay: `test_008_source_bound_examples.py::test_actual_parser_and_level_admission_are_separat` and `test_actual_old_image_round_trip_and_typed_foreign_refusal`.

L1: What the round trip proves

Q03. If $u(a) = u(b)$, applying d gives $a = b$. This proves injectivity on the illustrative old carrier. It proves no reverse round trip on foreign x: $d(x)$ is a refusal, outside the domain of u. The actual implemented old carrier is the singleton {Diff}, not this two-element illustration.

Q04. The term inclusion and its syntactic round trip still hold. Conservativity fails because the extension proves old-language P while the old theory does not. A proof that old-language derivability is reflected back to the old theory, with declared interpretations and rules, is required. Identity on strings is insufficient.

L2: Namespaces and grades

Q05.

Stage	Base	Complete block
22	128	128–135
23	136	136–143
100	752	752–759

Since $b(N+1) = b(N)+8$, $b(N)+7 < b(N+1)$. For an eight-bit unsigned wire, $b(N)+7 \leq 255$, so $N \leq 37$: stage 37 ends at 255 and stage 38 begins at 256. Python integer disjointness and wire capacity are separate statements. Neither establishes stage semantics.

Q06. The selected syntax boundary checks passed. The proposed COMPUTED binding fails because its checker accepts the required counterexample. Preserve the syntax evidence and record the unmet checker obligation. The status interface supplies no LEAN or GATED upgrade, and a stage number is not evidence. This question does not prescribe a universal soundness result from successful fixtures.

L3: Every certificate clause

Q07. The primal cost is $|1|+|0|+|0| = 1$. For $y = (1, 0, 0)$, the dual dot product is 1, the gap is 0, and capacity holds. Divergence is $(-1, 1, 0)$, so balance fails and the complete certificate is invalid. For $y = (1, 1, 1)$, divergence is $(0, 0, 0)$, capacity holds and the objective remains 1. A theorem about zero gap proves that clause; it does not erase failed feasibility.

Q08. The compatible dictionaries glue to $a = 0, b = 1, c = 0$. The changed pair conflicts at b, so no dictionary can restrict to both. This is a finite consistency calculation, not a construction of a general sheaf with an existence-and-uniqueness gluing theorem.

Replay: `test_008_source_bound_examples.py::test_zero_gap_fixture_still_needs_flow_balance`. The deposited Lean FlowCertificate statements express the corresponding finite fixture; Python arithmetic is a separate replay.

L4: Bind the instance

Q09. Tree propagation gives $\pi(A) = 0, \pi(B) = 2, \pi(C) = 5$, which fails the declared third claim 6. The closed walk $A \to B \to C \to A$ has signed sum $2 + 3 - 6 = -1$. Its indexed steps are `[(0,1),(1,1),(2,-1)]`. Every potential telescopes to zero on a closed walk, so this nonzero sum rules out a potential.

Q10. With the third claim 5, the potential $(0, 2, 5)$ satisfies every edge. The all-zero proposal changes the claim data; it preserves none of the three original

nonzero values. A repair policy must bind the original instance, identify which claims may change, check the permitted move, and check the required preserved constraints. Consistency of a replacement instance alone does not supply those checks.

Replay: the runner's `test_json_loaded_walks_remain_checkable` and `test_008_source_bound_examples.py::test_graph_certificates_agree_with_an_independent_bounded` The latter checks all 125 integer triangle assignments with edge values from -2 to 2 against an independent bounded potential search.

L5: Read the corpus and the statistics

Q11. $40 + 2 + 8 = 50$, with each audited challenge in one category. Category A records package contents, not a correctness theorem; Category B names a measurement deliverable, not a completed measurement. A missing receipt leaves execution unestablished. C001 has no retained measurement result. C047 has a test-named print-only script, without assertions or a failing exit status, that does not check mutation files. C048 to C050 have no pytest test file. C051 is outside the audited fifty.

Q12. Arm 2's count is $25 - 6 + 17 = 36$. With $n = b + c = 23$, the exact two-sided value is

$$p = \min\left(1, \frac{2\sum_{k=0}^{\min(b,c)} \binom{n}{k}}{2^n}\right) = \frac{145499}{4194304} \approx 0.03469.$$

For $b = c = 0$, the convention is $p = 1$. The hybrid run's 38/50 is separate. The midpoint 37/50 was not observed in either run. The 405B model exceeds the stated 70B limit; the larger run ceiling differs from the protocol's per-arm ceiling. Per-case rows are absent, and these descriptive values are not a general model effect or a multiplicity-adjusted analysis.

Replay: `test_008_source_bound_examples.py::test_exact_mcnemar_arithmetic_keeps_the_two_runs_s` It recomputes the four exact values from the transcribed discordant counts; it does not reconstruct the missing paired cases.

L6: Scoring and custody

Q13. An assisted success shows reproduction of supplied values at this fixture's scope. It does not show unaided discovery or estimate population performance from one trace per cell. A new comparison needs answer-free matched prompts, repeated runs under declared sampling conditions, a pre-registered analysis, and retained per-case outputs scored against the same instance. The historical host could accept a zero claim replacement, so preservation must be checked separately.

Q14. Both malformed or conflicting responses receive UNKNOWN and count as mismatches; substring occurrence is not a valid verdict. The new version-2

receipt binds the case, exact prompt, raw reply, provider label, measurements, host certificate and declared runner source SHA-256. Different raw replies therefore have different digests. A public hash detects changes relative to a trusted expected digest. Someone can edit a record and recompute its hash; it does not authenticate the provider or prove the certificate true.

Replay: `test_malformed_or_conflicting_verdicts_are_not_scored_as_answers` and `test_receipt_digest_binds_the_raw_reply_prompt_case_and_certificate` in the runner test file.

L7: Resolve and replay honestly

Q15. v1 returns HISTORICAL_BYTES_UNAVAILABLE. A v2 resource with the same filename cannot substitute for that pinned historical blob. Without the optional SHA-256, the extra comparison with the caller's expected digest was not performed. Retrieved bytes still need a valid relationship to the claim, and the checker and assumptions still need review.

Q16. Exit 0 with no census is insufficient. The repaired named gate compares the complete expected names and axiom sets and refuses empty, missing, duplicate or extra declarations and changed dependencies. The 39 names are selected theorems from five formal files. The retained 576-declaration report covers the ten local module environments, including ExactRat and generated/private declarations; it does not mean 576 manuscript theorems. The 52 external Level Engine payloads remain a separate surface. A host that cannot start Lean reports a blocked fresh replay and may separately compare source hashes with retained receipts. Mocked gate tests are control-logic evidence, never a compiler pass.

Replay: `code/tests/test_008_deposit_gates.py`.

Offline practice

Install the development tools declared in pyproject.toml, then run from the paper root, one file per command:

```
py -3.12 -m pytest code/tests/test_008_mssn_tower_retraction.py -q
py -3.12 -m pytest code/tests/test_008_deposit_gates.py -q
py -3.12 -m pytest code/tests/test_008_source_bound_examples.py -q
py -3.12 code/retraction_benchmark_runner.py --mock --condition baseline --output-dir <new-b
py -3.12 code/retraction_benchmark_runner.py --mock --condition hinted --output-dir <new-hin
```

Predict 3/6 matches for baseline and 6/6 for hinted. Baseline exits 1 because three verdicts miss; that is the expected negative control. These stub results are plumbing checks. No model is queried and no spending or learning benefit is measured. The package runner's scratchpad condition supplies generic instructions; the historical K4 scratchpad prompt supplied answer values. Do not combine their labels into one experiment.

Common mistakes and the next reading

Mistake	Revisit
Parsing means admission	L0; manuscript Section 2
Injective syntax means conservative theory	L1; Section 3
A stage label or fixture family proves universal soundness	L2; Section 4
Zero objective gap makes an infeasible certificate valid	L3; Section 5
A solved replacement instance repairs the requested instance	L4; Sections 10.1 and 10.3
A folder, aggregate label or midpoint is a retained observation	L5; Sections 8 and 9
An answer-bearing prompt measures unassisted ability	L6; Section 10.1
A digest or mocked successful process proves a theorem	L7; Sections 6 and 7

For each missed question, write the exact counterexample and the missing obligation. Re-run a changed-input control, then restate only the conclusion supported by that check.

Theoretical minimum: Paper 008

AuthorityEffect: None. Read the fictional Apartment 50 preface, then attempt these questions before opening the worked study guide.

These eight learning rungs, L0 to L7, are a teaching sequence. They are separate from MSS stage numbers and the evidence grades NONE, SYNTAX and COMPUTED. Use exact integers or rational fractions. A graph edge is a declared constraint; no filled face is implicit.

Each question earns two points: one for the calculation or concrete disposition, and one for its evidence boundary. The total of 32 is a self-study score. Record the failed obligation even when the arithmetic is correct.

L0: Packets and admission

Q01. Using the archived actual parser, complete a table with three columns: parses, active at MSS-0, active at MSS-1. Test `<>`, `<0>`, `<2>` and `op<<1><0>>`. Explain why `op` does not enlarge the active data alphabet.

Q02. In the actual maps, calculate `d_1(u_0(parse("<>")))`, then predict `u_0(parse("<0>"))` and `d_1(parse("<1>"))`. What information does the refusal preserve? Why is the historical toy's `None` a different interface?

L1: What the round trip proves

Q03. An illustrative old carrier is `{a,b}`; its lift has image `{ua,ub}` inside `{ua,ub,x}`. Let `d(ua)=a`, `d(ub)=b`, and `d(x)=NON_DESCENT`. Prove injectivity of the lift from the round-trip equation. Does $u(d(x)) = x$ follow?

Q04. A new proof system keeps every old term unchanged and adds an axiom asserting an old-language sentence P that the old system cannot prove. Does the syntactic round trip survive? Does conservativity of old-language provability survive? Name the missing kind of theorem.

L2: Namespaces and grades

Q05. For stages $N \geq 22$, $b(N) = 128 + 8(N - 22)$. Calculate the eight-wide blocks at stages 22, 23 and 100. Prove adjacent blocks are disjoint. If all opcodes must fit an unsigned eight-bit wire, what is the last permitted stage? Does any calculation here implement that stage's semantics?

Q06. A packet passes its own-stage admission and fails one-stage-earlier admission. A proposed checker accepts its positive fixture **and also accepts its required negative fixture**. Which syntax evidence is available, and why is the COMPUTED obligation unmet? Can an unrelated Lean file or a level number fill that gap?

L3: Every certificate clause

Q07. On the directed cycle $0 \to 1 \to 2 \to 0$, use loads $c = (1, 0, 0)$, unit capacities and zero vertex potentials. For flows $y = (1, 0, 0)$, compute primal cost, $c^{\mathsf{T}} y$, gap, and divergence (inflow minus outflow). Is the complete certificate valid? Repeat the balance check for $y = (1, 1, 1)$.

Q08. Glue dictionaries on $\{a, b\}$ and $\{b, c\}$: the first assigns $a = 0, b = 1$, and the second assigns $b = 1, c = 0$. Then change the second value at b to zero. Which case glues? What does this finite check leave unproved about the file title "Sheaf Descent"?

L4: Bind the instance

Q09. Edge indices 0, 1, 2 are $A \to B = 2$, $B \to C = 3$, $A \to C = 6$. Set $\pi(A) = 0$. Produce either a valid potential or a closed signed walk that proves contradiction. Check its edge continuity, closure and signed claim sum.

Q10. Change only the third claim to 5 and give the new certificate. A different proposal instead replaces all claims by zero and gets a zero defect. Which original constraints did it preserve? State what an acceptance rule must bind before "accepted" can mean repair of the requested instance.

L5: Read the corpus and the statistics

Q11. At the census commit, 40 challenges are delivered solver packages with two checker modules, 2 are model-measurement specifications, and 8 are specification-only. Check the total and the disjoint partition. Does folder membership certify execution, correctness or a completed model measurement? What does a missing scoring receipt imply?

Q12. In the three-arm C005 run, Arm 1 has 25 correct cases; discordant counts against Arm 2 are $b = 6, c = 17$. Calculate Arm 2's count and the exact two-sided binomial McNemar value. The separate hybrid run has Arm 2 at 38/50. Is 37/50 an observed result? Which protocol and data limitations qualify these tables?

L6: Scoring and custody

Q13. The eight K4 records have one trace per model/condition cell. The scratchpad and hinted prompts contain the three repair values; the other two conditions do not. What does an assisted success establish? Give two changes required for a defensible unassisted comparison.

Q14. A response says `VERDICT: NOT CONSISTENT`. Another contains conflicting explicit verdict lines. State their score disposition. Two well-formed responses have the same verdict but different raw text: should their new receipt digests match? Can a public unkeyed hash authenticate the provider?

L7: Resolve and replay honestly

Q15. Historical mode v1 requests an exact revision and path that are unavailable, while active mode v2 has a file of the same name. Give the v1 disposition. If no optional SHA-256 was supplied, which extra comparison was not performed? Does byte recovery settle the cited mathematical claim?

Q16. A Lean process exits 0 but emits no declaration census. May the named verification gate pass? Distinguish the 39 selected theorem names, the retained 576 package-local environment declarations, and the separate 52 Level Engine payloads. If this host cannot start Lean, what may its review record honestly report?

Evidence worksheet

For each answer retain: the declared input, your prediction, the calculation or named check, the result, and the remaining obligation. A malformed contract calls for refusal; missing execution is not a PASS. The study guide supplies worked answers, common mistakes and offline commands.