DRAFT

AN IDE FOR BUILDING SLIDES

sl-ide starter deck

Prepared by Your name · October 2026

sl-ide

IN BRIEF

- Pages are React components at a fixed 16:9 size, printed to a vector PDF
- Your agent writes the copy and the layout; you steer by commenting on the page
- Impeccable sets the visual system once, so every page shares it
- An audit catches clipped, crowded and overlapping pages before you ship

DRAFT

Three steps take this starter to your first real deck

Open Claude Code or Codex in this folder, keep pnpm dev running, and work through these in order.

1

Install the skills

`pnpm skills`

Restores **impeccable**, **copy-editing** and **copywriting** from skills-lock.json into gitignored project folders. If you have them installed globally, there is nothing to do here.

2

Learn the style

`/new-deck`

Impeccable interviews you for **PRODUCT.md** (audience, purpose, constraints), then reads your brand from a site, PDF or guide and writes **DESIGN.md** and the tokens.

3

Build the slides

`ask in plain words`

Ask for pages and they land in the preview. Press **c** to comment on any element, **/slide-lab** to compare takes and **/ship-it** to audit, print and commit the deck.

Codex users: invoke skills as $new-deck, $slide-lab and so on. The terminal under pnpm dev and the setup chip in the dev bar show which steps are left.

Each page is copy in content.js, placed in inch boxes

PRELIMINARY
First pass

How a page is made

- **content.js** holds every word and box; components only place them.
- **One component per page** in src/slides/; index.jsx sets the order and the appendix.
- **Tokens only**: colour and type live on :root in styles.css, never in a slide.
- **Action titles** state the page's point, so the titles alone tell the story.
- Open facts stay visible: *[TBD: a figure you still need]* prints as written.

Building blocks

Region
A box placed by box([x, y, w, h]); the audit flags copy that overflows it.

Card
A filled panel for one idea. Give it the card class so the audit measures it.

Sticker
A titleTag such as PRELIMINARY marks a page as a first pass.

Source: sl-ide starter. The outlined card shows the one-per-page emphasis pattern: an outline, not a fill.

The preview flags crowded or clipped pages as you edit

CHECK	WHAT IT CATCHES	WHERE YOU SEE IT
CLIPPED	Content runs past the footer. Pages are a fixed box, so the PDF would hide it.	Rail badge, pnpm run audit
SPILL	A card or region is too small for its own copy.	Rail badge, pnpm run audit
OVERLAP	Two stacked bands print on top of each other.	Rail badge, pnpm run audit
WORDY	The page is over the word budget (META.wordBudget).	Rail word count, audit
RAGGED	A wrapped line ends in a stub under a third of the width. Advisory.	pnpm run audit
Fonts	A glyph fell back to a system font in the PDF.	pre-commit, CI

The pre-commit hook runs the audit and prints the PDF; a failing page blocks the commit. CI does the same on every push.

Appendix

A1 Where things live

Where things live

`src/deck/content.js`	Every word and region box. Edit copy here.
`src/slides/`	One component per page; index.jsx sets the order.
`src/styles.css`	Tokens on :root, then page styles, then the dev chrome.
`PRODUCT.md · DESIGN.md`	Audience and visual system, written by impeccable.
`AGENTS.md`	The rules every agent follows here (CLAUDE.md imports it).
`.agents/skills/`	new-deck, slide-lab, copy-pass, ship-it, clean-up.
`skills-lock.json`	The third-party skills this repo expects.
`scripts/`	audit, pdf, shots, lab, fonts, doctor.