

Charles Proxy

Charles 4.5.1 - Session 1 *

Structure

Sequence

https://bonates.com

nsbrazil19

validation.json

Overview

Contents

Summary

Chart

Notes

GET /nsbrazil19/validation.json HTTP/1.1

Cookie __cfduid=dcda7d08eaec9984bba7c4a5b3ced86301573275935

Host bonates.com

Connection close

User-Agent Paw/3.1.9 (Macintosh; OS X/10.15.1) GCDHTTPRequest

Headers

Cookies

Raw

```
{
  "code": 4001,
  "message": "Campos inválidos",
  "invalid_fields": [{
    "field_name": "address_name",
    "message": "O nome do endereço é obrigatório"
  }, {
    "field_name": "phone_number",
    "message": "O campo Telefone deve possuir no máximo 15 caracteres"
  }],
  "response": []
}
```

Filter: bonates

Headers

Text

Hex

JavaScript

JSON


JSON Text


Raw

CONNECT https://p24-caldav.icloud.com

Map Local

Recording

▼  https://bonates.com

▼  nsbrazil19

 validation.json

Copy URL
Copy cURL Request
Copy Response
Save Response...
Find In...
Export Session...

Compose
Repeat
Repeat Advanced...
Validate
Publish Gist

View Request As ▶
View Response As ▶
Viewer Mappings...

Show in Sequence

Sort By ▶

Focus
Ignore

Clear
Clear Others

SSL Proxying: Enabled
Disable SSL Proxying

Breakpoints
No Caching
Block Cookies
Block List
Allow List
Client Process

Map Remote...
Map Local...

Edit Mapping

Map From

Protocol:

Host:

Port:

Path:


Query:


Map To

Local path:

☒ Case-sensitive

To map from a path and its subdirectories you must end the path with a *. To map an entire host leave the path blank.







Mappearend print para un arquiv local