

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

Open Information Extraction

Dominik Both, Tonio Weidler

Proseminar *Text Mining*
Andrea Zielinski

Institut für Computerlinguistik, Universität Heidelberg, 15.07.2016

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oooooo
oooo

Papers

Identifying Relations for Open Information Extraction (Fader et al., 2011)

LODifier: Generating Linked Data from Unstructured Text
(Augenstein et al., 2012)

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oooooo
oooo

Strukturierung

- 1 Introduction to Information Extraction
- 2 OIE - Principles
- 3 Example: LODifier
- 4 Conclusion

ooo
ooooooooooooo
ooooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo
oooo

Introduction to Information Extraction

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

What is Information Extraction?

Information Extraction

Goal of Information Extraction is automatically extracting information from unseen text

Information: entities, relations, events...

To make the dough for a good pizza, we start with putting 1kg of flour into the mixing bowl.
(1kg of flour, put into, mixing bowl)

ooo
oooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo
oooo

Problems of Information Extraction

- Named Entity Recognition
- Relationship Extraction
- Coreference Resolution
- Comment Extraction
- many more..

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo
oooo


OIE - Principles

●○○
○○○○○○○○○○○○
○○○○○○○○○

○○○○
○○○○○○○○
○○○○○
○○○○○
○○○○○
○○○○

OIE - Principles

Open Information Extraction




Open Information Extraction

IE: Extractor for each target relation

Open: No pre-specified extractors

Unsupervised learning of relation phrases

Extraction of information on every given domain



Problems of Open Information Extraction

■ Incoherent extractions:

This guide contains dead links and omits sites
contains omits

■ Uninformative extractions:

Faust made a deal with the devil
(Faust, made, a deal)

○○○
●○○○○○○○○○○○
○○○○○○○○○

○○○○
○○○○○○○○○
○○○○○
○○○○○
○○○○○
○○○○

OIE - Principles

Methods



Text Runner and WOE

- 1 *Label*: Automatic sentence labeling by heuristics
- 2 *Learn*: A relation phrase extractor is learned
- 3 *Extract*: Identifying NP pairs and searching relations words between

ooo
oo●ooooooooo
ooooooooo

oooo
ooooooooo
ooooo
ooooo
ooooo
oooo

Problems

- Large number of labeled training examples required
- Alternative heuristic labeling leads to huge noise and stacked uncertainty
- Ignores both holistic and lexical aspects



Syntactic constraint

- Limits relations to those matching a certain POS Tag pattern:
- Always chooses longest possible match
- Merge adjacent matches together

$V \mid VP \mid VW^*P$

V = verb particle? adv?

W = (noun | adj | adv | pron | det)

P = (prep | particle | inf. marker)

Faust made a deal with the devil

ooo
oooo●oooooooo
ooooooooo

oooo
ooooooooo
ooooo
ooooo
ooooo
oooo

Lexical constraint

- Only assume relations that appear in the corpus for a certain amount
- The Obama administration is **offering only modest greenhouse gas reduction targets** at the conference

○○○
 ○○○○○●○○○○○
 ○○○○○○○○

○○○○
 ○○○○○○○○
 ○○○○
 ○○○○
 ○○○○

Limitations of those constraints

- In a set of 300 hand-annotated sentences 85% relations fell into those constraints
- Model is not complete and has its flaws
- Of all relation phrases in the gold standard:
 - 85% satisfied constraints and were found
 - 8% Non-contiguous phrase structure
 - Coordination*: X is produced and maintained by Y
 - Multiple Args*: X was founded in 1995 by Y
 - Phrasal Verbs*: X turned Y off
 - 4% Relation phrase not between arguments
 - Introductions*: Discovered by Y, X ...
 - Relative Cl.*: ... the Y that X discovered
 - 3% Not matching POS pattern
 - Interrupting Modifiers*: X has a lot of faith in Y
 - Infinitives*: X to attack Y



ReVerb Extraction Algorithm

- *Relation Extraction*: Find the longest possible string of words that match the relation constraints, merge adjacents
- *Argument Extraction*: Find the nearest NP left and right to the relation that is not a relativ pronoun, WHO-adverb or existential-there.
- How is the lexical constraint being checked? By creating a list of relational phrases by applying this algorithm on a 500 million Web sentences.

```

ooo
oooooooo●oooo
ooooooooo

```

```

oooo
ooooooooo
ooooo
ooooo
ooooo
oooo

```

Methods

ReVerb Confidence Function

- The Algorithm has a high recall, but low precision
- Now the extracted relation is weighted by a confidence function:


Examples:

- 1.16 (x, r, y) covers all words in s
- 0.50 The last preposition in r is for
- 0.43 $\text{len}(s)$ under 10
- -0.65 There is a preposition to the left of x in s
- ...

○○○
 ○○○○○○○○●○○○
 ○○○○○○○○

○○○
 ○○○○○○○○
 ○○○○
 ○○○○
 ○○○○



Evaluation



Better results than TextRunner through lexical features, but still low recall.



Why?



Argument extraction is open to improvements

Source: Fader et al., 2011



Why?

Evaluating the evaluation:

REVERB - Incorrect Extractions	
65%	Correct relation phrase, incorrect arguments
16%	N-ary relation
8%	Non-contiguous relation phrase
2%	Imperative verb
2%	Overspecified relation phrase
7%	Other, including POS/chunking errors

REVERB - Missed Extractions	
52%	Could not identify correct arguments
23%	Relation filtered out by lexical constraint
17%	Identified a more specific relation
8%	POS/chunking error

Source: Fader et al., 2011

○○○
○○○○○○○○○○●
○○○○○○○○○

○○○○
○○○○○○○○
○○○○○
○○○○○
○○○○○
○○○○○

Conclusion

Acceptable results on easy sentences. Fails on more complex sentences. *Possible points of improvement:*

- Does not support n-ary relations
- Relations seem overly specific in many results
- Coordination is not in all cases correctly recognized
- Coreference is not predicted by the system
- Syntactic fixation on S-V-O word order

○○○
○○○○○○○○○○○○○
●○○○○○○○○○

○○○○
○○○○○○○○○
○○○○○
○○○○○
○○○○


OIE - Principles

Data Representation

ooo
oooooooooooooooo
o●oooooooo

oooo
oooooooooo
oooooo
ooooo
oooo

Standard Patterns



Argument A is in a directed relation to **Argument B**.

ooo
ooooooooooooo
oo●oooooo

oooo
ooooooooooooo
oooooo
oooooo
oooooo
oooo

Unnormalized Annotation

(argument_a, predicate_x, argument_b)
(argument_a, predicate_y, argument_c)
(argument_a, predicate_y, argument_d)

Problems

- redundant
- unnormalized
- can only produce binary predicates

ooo
oooooooooooo
ooo●ooooo


oooo
oooooooo
ooooo
ooooo
ooooo
oooo

RDF and Linked Data

Resource Description Framework

Models propositions by constructing *triples* including **Subjects**, **Objects** and **Predicates**

Generates a directed graph





RDF Concepts and Notation

- **URIs**
identifies resources (S, R, O) distinctively and references further informations (triples)
- **Conclusions**
allows to draw conclusions using rules
- **Turtle**
allows syntax abbreviations
- **Blanknodes**
placeholder for something without a URI
- **Queries**
can be searched by querying (eg SPARQL)

ooo
oooooooooooooooo
oooo●ooo

oooo
oooooooooooo
ooooo
ooooo
ooooo
oooo

RDF Reification

Motivation: How can I realize embedded propositions?

Example: Peter said, he watched the movie.

ooo
oooooooooooooooo
oooo●ooo

oooo
oooooooooo
ooooo
ooooo
ooooo
oooo

RDF Reification

Motivation: How can I realize embedded propositions?

Example: Peter said, he watched the movie.

Wrong proposition

:Peter :watched :movie



RDF Reification

Motivation: How can I realize embedded propositions?

Example: Peter said, he watched the movie.

Reification

```
:Peter :said __:prop.  
__:prop rdf:subject :Peter.  
__:prop rdf:predicate :watched.  
__:prop rdf:object :movie.
```

ooo
ooooooooooooo
oooooooo●oo

oooo
ooooooooo
ooooo
ooooo
ooooo
oooo

Vocabularies & Ontologies

Several vocabularies provide useful relations and functionality, eg.:

- RDF (rdf:type, ...)
- RDFS (rdfs:subClassOf, rdfs:domain, rdfs:range, ...)
- OWL (owl:sameAs, owl:SymmetricProperty, ...)
- FOAF

Ontologies are huge RDF Graphs containing many triples, eg.:

- DBpedia
- Wikidata
- WordNet

ooo
ooooooooooooo
oooooooo●o

oooo
ooooooooo
ooooo
ooooo
ooooo
oooo

RDF Syntax


```
dbr:Barack_Obama a foaf:person, :President;  
    dbo:spouse dbr:Michelle_Obama.  
dbr:Bernie_Sanders dbo:birthPlace dbr:New_York,  
    dbr:Brooklyn;  
dbr:Brooklyn dbo:isPartOf dbr:New_York
```


ooo
oooooooooooooooo
ooooooooo●

oooo
oooooooooo
oooooo
ooooo
ooooo
oooo

Data Representation

... as Graph



ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo
oooo

Example: LODifier

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oooooo
oooo

LODifier: Generating Linked Data from Unstructured Text (Augenstein et al., 2012)

Generate an RDF Graph from unstructured Text

Past Approaches: Use Patterns to trade recall for precision

LODifier: Process the entire text

○○○
○○○○○○○○○○○○○
○○○○○○○○○

●○○○
○○○○○○○○○
○○○○○
○○○○○
○○○○


Example: LODifier Architecture

○○○
 ○○○○○○○○○○○○
 ○○○○○○○○

●○○○
 ○○○○○○○○
 ○○○○
 ○○○○
 ○○○○

Architecture

Architecture



(Augenstein et al., 2012)

○○○
○○○○○○○○○○○○○
○○○○○○○○○

○○●○
○○○○○○○○○
○○○○○
○○○○○
○○○○

Approach

- 1 **Parse** the input text (POS, Treetagging, NER)
- 2 Apply **Deep Semantic Analysis** to get relations
- 3 Enrich NEs and words with **URIs** (DBpedia and WordNet)
- 4 Forge an **RDF Graph** of this information

○○○
○○○○○○○○○○○○○
○○○○○○○○○

○○○●
○○○○○○○○○
○○○○○
○○○○○
○○○○

Architecture

How does it happen?

Lets go through the process step-by-step!

Example Text:

The New York Times reported that John McCarthy died. He invented the programming language LISP.

example taken from Augenstein et al., 2012

ooo
oooooooooooooooo
oooooooooooo

oooo
●ooooooooo
ooooo
ooooo
ooooo
oooo

Example: LODifier

Preprocessing

ooo
ooooooooooooo
oooooooooooo

oooo
o●oooooo
ooooo
ooooo
ooooo
oooo

Named Entity Recognition - Wikifier

Wikifier

Recognizes NE and replaces them with the Wikipedia Page Link
Disambiguates by comparing links between pages.

Example Text Output:

[The New York Times] reported that [John McCarthy (computer scientist)|John McCarthy] died. He invented the [Programming language|programming language] [Lisp (programming language)|LISP].

ooo
oooooooooooooooo
oooooooooooo

oooo
oo●ooooo
ooooo
ooooo
ooooo
ooooo

Parsing Syntax - C&C

C&C Parser

Syntactical Parser that tags POS and builds Parse Trees in CCG.

Combinatory Categorical Grammar (CCG)

Grammatical formalism allows parallel analysis of syntax and semantics

Associates words with categories that can be combined (rule-based) to form a sentence

Syntax via Category Combination, Semantics via lambda calculus

```

ooo
ooooo
oooooooooooo
ooooooooo

```

```

oooo
ooo●oooo
ooooo
ooooo
ooooo
oooo

```

Preprocessing

Parsing - Output

```

ccg(1, rp(s:dcl,
  ba(s:dcl,
    lx(np, n,
      t(n, 'The_New_York_Times', 'The_New_York_Times', 'NNS', 'I-NP', 'O')),
    fa(s:dcl\np,
      t((s:dcl\np)/s:em, 'reported', 'report', 'VBD', 'I-VP', 'O')),
    fa(s:em,
      t(s:em/s:dcl, 'that', 'that', 'IN', 'I-SBAR', 'O')),
    ba(s:dcl,
      lx(np, n,
        t(n, 'John_McCarthy', 'John_McCarthy', 'NNP', 'I-NP', 'I-PER')),
        t(s:dcl\np, 'died', 'die', 'VBD', 'I-VP', 'O'))))))),
  t(period, '.', '.', '.', 'O', 'O'))).
ccg(2, rp(s:dcl,
  ba(s:dcl,
    t(np, 'He', 'he', 'PRP', 'I-NP', 'O'),
    fa(s:dcl\np,
      t((s:dcl\np)/np, 'invented', 'invent', 'VBD', 'I-VP', 'O'),
      fa(np:nb,
        t(np:nb/n, 'the', 'the', 'DT', 'I-NP', 'O'),
        fa(n,
          t(n/n, 'programming_language', 'programming_language', 'NN', 'I-NP', 'O'),
          t(n, 'LISP', 'LISP', 'NNP', 'I-NP', 'O'))))))),
  t(period, '.', '.', '.', 'O', 'O'))).

```

ooo
oooooooooooooooo
oooooooooooo

oooo
oooo●ooo
ooooo
ooooo
ooooo
oooo

Preprocessing

Find Relations - Boxer

Boxer

Creates DRSs from C&C Output



Find Relations - Boxer

Boxer

Creates DRSs from C&C Output

Discours Representation Structure (DRS)

Represents the discourse via *relations* between *entities*
Allows referencing over the entire discourse

ooo
ooooooooooooo
oooooooooooo

oooo
oooo●ooo
ooooo
ooooo
ooooo
oooo

Find Relations - Boxer

Boxer

Creates DRSs from C&C Output

Discours Representation Structure (DRS)

Represents the discourse via *relations* between *entities*
Allows referencing over the entire discourse

Boxers DRS Relations (Conditions):


- **Unary Relations (Classes):** eg. *topic, person, event, male, ...*
+ all verbs
- **Binary Relations:** agent, patient, ... (semantic roles)

○○○
 ○○○○○○○○○○○○
 ○○○○○○○○○

○○○○
 ○○○○○●○○
 ○○○○
 ○○○○
 ○○○○
 ○○○○

Preprocessing

Boxer Output



ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooo●o
ooooo
ooooo
ooooo
oooo

Assign WordNet URIs

RDF WordNet

WN: Lexicography containing senses linked by semantic relations

RDF WN: LD Representation of WN providing URIs for words

Steps:

- 1 Lemmatization
- 2 WSD (UKB)
- 3 Assign RDF WN URIs to word senses

ooo
oooooooooooooooo
oooooooooooo

oooo
ooooooooo●
ooooo
ooooo
ooooo
oooo

Preprocessing

Preprocessing Result

We now have ...

- URIs for all NEs
- URIs for all (disambiguated) words
- Relations between entities (those URIs)

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
●oooo
ooooo
oooo

Example: LODifier

RDF Construction

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
o●oooo
ooooo
oooo

What now?

Let's now construct the RDF Graph from this information!

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oo●ooo
ooooo
oooo

Namespaces/Vocabularies

LODifier introduces several namespaces:

- **drsclass**: contains Boxer classes (event, person, ...) and :named relation
- **drsrel**: contains Boxer relations (agent, patient, ...)
- **ne**: contains the named entity URIs
- **reify**: reification (embedding propositions into propositions)

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
ooo●ooo
ooooo
oooo

Namespaces/Vocabularies

And uses standard namespaces:

- **rdf:** mainly for `rdf:type` and reification
- **owl:** for `owl:sameAs`

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
ooo●ooo
ooooo
oooo

Namespaces/Vocabularies

Finally the two ontologies:


- **wn30**: contains all WordNet URIs
- **dbpedia**: contains the dbpedia URIs
- **class**: contains classes not in wn30 nor in dbpedia



RDF Construction Strategy I

Create a blanknode `_:x` for each discourse referent (x_0, x_1, \dots)

RDF Construction Strategy II






RDF Construction Strategy III

if NE, then create
_:x *drsclass:named ne:URI*



RDF Construction

RDF Construction Strategy IV




RDF Construction Strategy V

if NE and DBpedia URI exists create
__ :x owl:sameAs dbpedia:URI

RDF Construction

RDF Construction Strategy VI




RDF Construction Strategy VII

via `rdf:type` assign closed classes (event, person, ...)

`_:x rdf:type drsclass:CLOSEDCLASS`

RDF Construction

RDF Construction Strategy VIII






RDF Construction Strategy IX

via `rdf:type` assign open classes (die, programming_language, ...)
`_:x rdf:type wn30:OPENCLASS, class:OPENCLASS`



RDF Construction

RDF Construction Strategy X






RDF Construction Strategy XI

create triples from binary relations (agent, theme, ...)

`_:x drsrel:RELATION _:y`

RDF Construction

RDF Construction Strategy XII



RDF Construction Strategy XIII

recursive reification of embedded propositions (eg. by *report* or *says*)

RDF Construction Strategy XIV



```

ooo
oooooooooooooooo
oooooooooooo

```

```

oooo
oooooooooooo
oooo●●
ooooo
oooo

```

RDF Construction

RDF Construction: Output

```

_:var0x0 drsclass:named ne:john_mccarthy ;
        rdf:type drsclass:male , foaf:Person ;
        owl:sameAs dbpedia:John_McCarthy_(computer_scientist) .
_:var0x1 rdf:type class:programming_language ;
        owl:sameAs dbpedia:Programming_language .
_:var0x2 drsrel:nn _:var0x1 .
_:var0x2 drsclass:named ne:lisp ;
        owl:sameAs dbpedia:Lisp_(programming_language) .
_:var0x3 drsclass:named ne:the_new_york_times ;
        owl:sameAs dbpedia:The_New_York_Times .
_:var0x4 rdf:type drsclass:event , wn30:wordsense-invent-verb-2 .
        drsrel:agent _:var0x0 ; drsrel:patient _:var0x2 .
_:var0x5 rdf:type drsclass:event , wn30:wordsense-report-verb-3 ;
        drsrel:agent _:var0x3 ; drsrel:theme _:var0x6 .
_:var0x6 rdf:type drsclass:proposition , reify:proposition , reify:conjunction ;
        reify:conjunct [ rdf:subject _:var0x7 ;
                        rdf:predicate rdf:type ;
                        rdf:object drsclass:event . ]
        reify:conjunct [ rdf:subject _:var0x7 ;
                        rdf:predicate rdf:type ;
                        rdf:object wn30:wordsense-die-verb-1 . ]
        reify:conjunct [ rdf:subject _:var0x7 ;
                        rdf:predicate drsrel:agent ;
                        rdf:object _:var0x0 . ]

```

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
●oooo
oooo

Example: LODifier Experiments

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
o●oooo
oooo

Method

- Evaluate by testing similarity of two given documents:
- *the problem of deciding whether two randomly selected stories discuss the same news topic* (Augenstein et al., 2012)
- TDT-2 benchmark dataset: 84.000 news documents
- Extract 183 positive and 183 negative pairs (avg. 11.2 per topic)
- Calculate similarity and evaluate the system on the result

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oo●ooo
oooo

Similarity measurements

- 1 NEs identified by Wikifier and successfully disambiguated words in UKB
- 2 add NEs recognized by Boxer
- 3 add URIs of unrecognized words

Further add structural features: Measurement of the similarity of the RDF graphs of the two documents

Accuracy

Model	normal	extended
Similarity measures without structural knowledge		
Random Baseline	50.0	–
Bag of Words	63.0	–
Bag of URIs (Variant 1)	61.6	75.1
Bag of URIs (Variant 2)	70.6	76.0
Bag of URIs (Variant 3)	73.4	76.4
Similarity measures with structural knowledge		
proSim _{cnt} (k=8, Variant 1)	77.7	77.6
proSim _{cnt} (k=8, Variant 2)	79.2	79.0
proSim _{cnt} (k=8, Variant 3)	82.1	81.9

Source: Augenstein et al., 2012

Precision - Recall




Fig. 5. Precision-Recall-plot for best Story Link Detection models

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
ooooo
ooooo
●ooo

Example: LODifier

Conclusions

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oooooo
oooooo
o●ooo

Conclusions

What to draw from this?

- deep semantic analysis can work for OIE
- combining several existing NLP Systems provides a well functioning extraction system
- information gained by unsupervised OIE can already improve real world tasks

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

What we liked

- full-text OIE

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

Conclusions

What we liked

- full-text OIE
- uses many strengths of RDF

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

Conclusions

What we liked

- full-text OIE
- uses many strengths of RDF
- relations aren't overspecified

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

Conclusions

What we liked

- full-text OIE
- uses many strengths of RDF
- relations are not overspecified
- extendable/improvable by improving/swapping Systems in the architecture

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

What we liked

- full-text OIE
- uses many strengths of RDF
- relations are not overspecified
- extendable/improvable by improving/swapping Systems in the architecture
- part of the LOD-Cloud

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
oo●oo

What we liked

- full-text OIE
- uses many strengths of RDF
- relations are not overspecified
- extendable/improvable by improving/swapping Systems in the architecture
- part of the LOD-Cloud
- results in standardized notation

ooo
ooooooooooooo
ooooooooooooo

oooo
ooooooooooooo
oooooo
oooooo
oooooo
oo●oo

Conclusions

What we liked

- full-text OIE
- uses many strengths of RDF
- relations are not overspecified
- extendable/improvable by improving/swapping Systems in the architecture
- part of the LOD-Cloud
- results in standardized notation
- domain-independent

What we didnt like

- Redundant processes like NER

What we didnt like

- Redundant processes like NER
- BlankNode Massacre

Conclusions

What we didnt like

- Redundant processes like NER
- BlankNode Massacre
- confusing boxer relations not simplified for RDF (will be hard to search through)

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
ooo●

Conclusions

What we didnt like

- Redundant processes like NER
- BlankNode Massacre
- confusing boxer relations not simplified for RDF (will be hard to search through)
- Paper scratches only the surface of the system

ooo
oooooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooooo
ooo●

Conclusions

What we didnt like

- Redundant processes like NER
- BlankNode Massacre
- confusing boxer relations not simplified for RDF (will be hard to search through)
- Paper scratches only the surface of the system
- Some points are unclear / not even described

Conclusion

Weaknesses and Strengths of OIE

- trades precision for recall

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
ooooo
oooo
oooo

Weaknesses and Strengths of OIE

- trades precision for recall
- $OIE > IE$ if no special task/domain is defined

Weaknesses and Strengths of OIE

- trades precision for recall
- $OIE > IE$ if no sepcial task/domain is defined
- theory independent

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

Weaknesses and Strengths of OIE

- trades precision for recall
- $OIE > IE$ if no special task/domain is defined
- theory independent
- relations may be redundant/overspecified/unintended

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

Weaknesses and Strengths of OIE

- trades precision for recall
- $OIE > IE$ if no special task/domain is defined
- theory independent
- relations may be redundant/overspecified/unintended
- restricted usability of results due to low precision

Future Opportunities

- better subsystems

Future Opportunities

- better subsystems
 - Coreference Resolution

Future Opportunities

- better subsystems
 - Coreference Resolution
 - NER

Future Opportunities

- better subsystems
 - Coreference Resolution
 - NER
 - Disambiguation

Future Opportunities

- better subsystems
 - Coreference Resolution
 - NER
 - Disambiguation
- improve semantic analysis

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

References I

A. Fader, S. Soderland, O. Etzioni. Identifying relations for open information extraction. Proc. of the Conf. on Empirical Methods in Natural Language, 2011

Augenstein, Isabelle, Sebastian Padó, and Sebastian Rudolph. Lodifier: Generating linked data from unstructured text. The Semantic Web: Research and Applications. Springer Berlin Heidelberg, 2012. 210-224.

ooo
ooooooooooooo
oooooooooooo

oooo
oooooooooooo
oooooo
oooooo
oooo

References II

James R. Curran, Stephen Clark, and Johan Bos. 2007.
Linguistically motivated large-scale NLP with C&C and boxer. In
Proceedings of the 45th Annual Meeting of the ACL on Interactive
Poster and Demonstration Sessions (ACL '07). Association for
Computational Linguistics, Stroudsburg, PA, USA, 33-36.

Unpublished draft of Andreas Harths "Linked Data" Book (Version
February 2016) as provided in his Linked Data lecture at Heidelberg
University.